

MPE REPORT

FCC ID: 2AFOS-WT52810-S1

Date of issue: Nov. 16, 2020

Report number:	MTi20101309-1E2
Sample description:	Bluetooth Module
Model(s):	WT52810-S1
Applicant:	Wireless-Tag Technology Co., Ltd.
Address:	Room 115-118, Building A, Chengshishanhai Center, No. 11, Zhongxing Road, Bantian Sub-District, Longgang district, Shenzhen, 518000 China
Date of test:	Oct. 28, 2020 to Nov. 16, 2020

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

This test report is valid for the tested samples only. It cannot be reproduced except in full without prior written consent of Shenzhen Microtest Co., Ltd.

Tel: (86-755) 88850135

Fax: (86-755) 88850136

Web: <http://www.mtitest.com>

E-mail: mti@51mti.com

Address: 101, No. 7, Zone 2, Xinxing Industrial Park, Fuhai Avenue, Xinhe Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China.



TEST RESULT CERTIFICATION	
Applicant's name:	Wireless-Tag Technology Co., Ltd.
Address:	Room 115-118, Building A, Chengshishanhai Center, No. 11, Zhongxing Road, Bantian Sub-District, Longgang district, Shenzhen, 518000 China
Manufacture's name:	Wireless-Tag Technology Co., Ltd.
Address:	Room 115-118, Building A, Chengshishanhai Center, No. 11, Zhongxing Road, Bantian Sub-District, Longgang district, Shenzhen, 518000 China
Product name:	Bluetooth Module
Trademark:	WT52810-S1
Model and/or type reference:	N/A
Serial model:	KDB 447498 D01 v06
RF exposure procedures:	Wireless-Tag Technology Co., Ltd.

This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Tested by:

Demi Mu

Nov. 16, 2020

Reviewed by:

Leo Su

Nov. 16, 2020

Approved by:

Tom Xue

Nov. 16, 2020



RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm(20cm)

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.



Measurement Result

BLE:

Operation Frequency: BLE: 2402-2480MHz,

Power density limited: 1mW/ cm²

Antenna Type: PCB Antenna;

antenna gain: 1dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(1/10)}=1.26$

Channel Freq. (MHz)	modulation	conducted power	Tune- up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric	(mW/cm2)	(mW/cm2)
2402	GFSK	-1.834	-1±1	0	1.000	1	1.26	0.0003	1
2440		-1.814	-1±1	0	1.000	1	1.26	0.0003	1
2480		-2.366	-2±1	-1	0.794	1	1.26	0.0002	1

Conclusion:

For the max result: $0.0003 \leq 1.0$ for 1g SAR, No SAR is required.

----END OF REPORT----