

TEST REPORT


Applicant	SZ Telstar CO.,LTD
Address	Telstar Technology Park No.12~14,Gangbei Industrial Zone, Ailian, Longgang District, ShenZhen

Manufacturer or Supplier	SZ Telstar CO.,LTD
Address	Telstar Technology Park No.12~14,Gangbei Industrial Zone, Ailian, Longgang District, ShenZhen
Product	Projector
Brand Name	miroir
Model	MP125
Additional Model & Model Difference	M200A, see item 3.1
Date of tests	Aug. 26, 2016 ~ Sep. 02, 2016

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Tom Chen Project Engineer / EMC Department	Approved by Glyn He Supervisor/ EMC Department
	 Date: Sep. 21, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
2 MEASUREMENT UNCERTAINTY	5
3 GENERAL INFORMATION	6
3.1 GENERAL DESCRIPTION OF EUT.....	6
3.2 DESCRIPTION OF TEST MODES.....	7
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST	8
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	8
3.3 DUTY CYCLE OF TEST SIGNAL	10
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS.....	11
3.5 DESCRIPTION OF SUPPORT UNITS.....	11
4 TEST TYPES AND RESULTS.....	12
4.1 CONDUCTED EMISSION MEASUREMENT	12
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	12
4.1.2 TEST INSTRUMENTS.....	12
4.1.3 TEST PROCEDURES	13
4.1.4 DEVIATION FROM TEST STANDARD	13
4.1.5 TEST SETUP.....	14
4.1.6 EUT OPERATING CONDITIONS	14
4.1.7 TEST RESULTS	15
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	17
4.2.2 TEST INSTRUMENTS.....	18
4.2.3 TEST PROCEDURES	19
4.2.4 DEVIATION FROM TEST STANDARD	19
4.2.5 TEST SETUP.....	20
4.2.6 EUT OPERATING CONDITIONS	20
4.2.7 TEST RESULTS	21
4.3 6dB BANDWIDTH MEASUREMENT	37
4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT	37
4.3.2 TEST INSTRUMENTS.....	37
4.3.3 TEST PROCEDURE.....	37
4.3.4 DEVIATION FROM TEST STANDARD	37
4.3.5 TEST SETUP.....	38
4.3.6 EUT OPERATING CONDITIONS	38

4.3.7	TEST RESULTS	39
4.4	CONDUCTED OUTPUT POWER	41
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	41
4.4.2	TEST SETUP	41
4.4.3	TEST INSTRUMENTS.....	41
4.4.4	TEST PROCEDURES	42
4.4.5	DEVIATION FROM TEST STANDARD	42
4.4.6	EUT OPERATING CONDITIONS	42
4.4.7	TEST RESULTS	43
4.4.7.1	MAXIMUM PEAK OUTPUT POWER	43
4.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE)	44
4.5	POWER SPECTRAL DENSITY MEASUREMENT	45
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	45
4.5.2	TEST SETUP	45
4.5.3	TEST INSTRUMENTS.....	45
4.5.4	TEST PROCEDURE.....	45
4.5.5	DEVIATION FROM TEST STANDARD	45
4.5.6	EUT OPERATING CONDITION	46
4.5.7	TEST RESULTS	46
4.6	OUT OF BAND EMISSION MEASUREMENT	48
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	48
4.6.2	TEST SETUP	48
4.6.3	TEST INSTRUMENTS.....	48
4.6.4	TEST PROCEDURE.....	48
4.6.5	DEVIATION FROM TEST STANDARD	49
4.6.6	EUT OPERATING CONDITION	49
4.6.7	TEST RESULTS	50
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	56
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	57



BUREAU
VERITAS

Test Report No.: RF160810N018-2

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF160810N018-2	Original release	Sep. 21, 2016

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.90dB
	30MHz ~ 1GMHz	3.83dB
	1GHz ~ 18GHz	4.93dB
	18GHz ~ 40GHz	4.80dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Projector
MODEL NO.	MP125
ADDITIONAL NO.	M200A
FCC ID	2AFOW-125MIROIR
NOMINAL VOLTAGE	DC 5V From Adapter or DC 3.7V From Li-ion Battery
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM BT-LE(GFSK) for DTS
MODULATION TECHNOLOGY	DSSS, OFDM, DTS
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20) 2402-2480MHz for BT-LE(GFSK)
PEAK POWER	WLAN: 23.19dBm(Maximum) BT-LE: 8.38dBm(Maximum)
ANTENNA TYPE	Integral FPCB Antenna, 2.89dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	HDMI cable: Shielded, Detachable, 0.7m USB cable: Shielded, Detachable, 1.0m

NOTE:

1. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	FUNCTION
802.11b	1TX/1RX
802.11g	1TX/1RX
802.11n (HT20)	1TX/1RX
BT-LE	1TX/1RX

2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Please refer to the EUT photo document (Reference No.: 160810N018) for detailed product photo.
5. Additional mode M200A is identical with the test model MP125, except the model number for marketing purpose.

6. The EUT can be powered by adapter as list as following:

ADAPTER	
BRAND:	N/A
MODEL:	FJ-SW268D0503000U
INPUT:	AC 100-240V 50/60Hz 0.6A Max
OUTPUT:	DC 5V/3A Max
DC CABLE:	N/A

3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n(HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

40 channels are provided for BT-LE(GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.

The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	√	Powered by Adapter with (WIFI + BT) function

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

POWER LINE CONDUCTED EMISSION TEST:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CONDITION
-	BT Link+ WIFI (2.4G) Link

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1	OFDM	DBPSK	6.0
A	BT-LE	0 to 39	39	DTS	GFSK	1.0

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	CCK	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
A	BT-LE	0 to 39	0,19, 39	DTS	GFSK	1.0

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
A	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
A	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
A	BT-LE	0 to 39	0,19, 39	DTS	GFSK	1.0

ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 11	CCK	DBPSK	1.0
A	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
A	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
A	BT-LE	0 to 39	0,19, 39	DTS	GFSK	1.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	25deg. C, 53%RH	DC 5V From Adapter	Eric Fang
RE≥1G	25deg. C, 53%RH	DC 5V From Adapter	Eric Fang
PLC	20deg. C, 56%RH	DC 5V From Adapter	Sen He
APCM	20deg. C, 55%RH	DC 5V From Adapter	Sen He

3.3 DUTY CYCLE OF TEST SIGNAL

Duty cycle of test signal is 100 %

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v03r05

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

NOTE: It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B(DoC). The test report has been issued separately.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together without other necessary accessories or support units.

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101588	Jan. 22,16	Jan. 21,17
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 04,16	Mar. 03,17
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,16	Apr. 04,17
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 08,16	Jan. 07,17
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The test was performed in shielded room 553.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.


4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: BT+WIFI

PHASE	Line	6dB BANDWIDTH	9kHz
-------	------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.11	37.11	18.85	47.22	28.96	66.00	56.00	-18.78	-27.04
2	0.22200	10.13	31.17	14.29	41.30	24.42	62.74	52.74	-21.44	-28.32
3	0.25575	10.15	30.21	16.28	40.36	26.43	61.57	51.57	-21.21	-25.14
4	0.56703	10.29	23.11	13.81	33.40	24.10	56.00	46.00	-22.60	-21.90
5	12.34275	10.52	31.37	22.27	41.89	32.79	60.00	50.00	-18.11	-17.21
6	21.40125	10.72	21.38	4.13	32.10	14.85	60.00	50.00	-27.90	-35.15

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






PHASE	Neutral	6dB BANDWIDTH	9kHz
-------	---------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.86	32.31	14.38	42.17	24.24	66.00	56.00	-23.83	-31.76
2	0.23290	9.88	28.03	12.34	37.91	22.22	62.35	52.35	-24.44	-30.13
3	0.33264	9.89	29.91	13.95	39.80	23.84	59.39	49.39	-19.58	-25.54
4	0.55959	9.93	27.21	14.77	37.14	24.70	56.00	46.00	-18.86	-21.30
5	12.14925	10.44	43.39	34.54	53.83	44.98	60.00	50.00	-6.17	-5.02
6	18.16575	10.56	23.27	14.93	33.83	25.49	60.00	50.00	-26.17	-24.51

- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,16	Apr. 04,17
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 14, 16	Jul. 13, 17
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 18,16	May 17,17
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 16	Aug. 07, 17
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Mar. 12,16	Mar. 11,18
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 12,16	Mar. 11,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,16	Mar. 03, 17
Pre-Amplifier(1-18G)	HP	8449B	3008A00409	Apr. 25,16	Apr. 24,17
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,15	Nov. 19,16
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 08,16	Aug. 07,17

NOTE:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 494399.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.



4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	120.00	17.36	43.50	-26.14	100	0	34.43	-17.07
2	178.41	17.56	43.50	-25.94	100	0	37.10	-19.54
3	212.63	20.22	43.50	-23.28	100	0	39.70	-19.48
4	262.95	26.83	46.00	-19.17	100	0	40.61	-13.78
5	301.96	28.82	46.00	-17.18	100	0	42.72	-13.90
6	399.99	25.66	46.00	-20.34	100	0	35.21	-9.55

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.12	34.05	40.00	-5.95	100	0	45.52	-11.47
2	64.59	28.70	40.00	-11.30	100	0	53.58	-24.88
3	72.35	27.03	40.00	-12.97	100	0	51.33	-24.30
4	214.78	25.07	43.50	-18.43	100	0	44.19	-19.12
5	274.02	26.69	46.00	-19.31	100	0	41.38	-14.69
6	331.00	29.98	46.00	-16.02	100	0	43.64	-13.66

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	30.20 PK	74.0	-43.80	1.16 H	258	26.33	3.87
2	2390.00	19.12 AV	54.0	-34.88	1.16 H	258	15.25	3.87
3	*2412.00	87.95 PK			1.16 H	258	84.01	3.94
4	*2412.00	83.46 AV			1.16 H	258	79.52	3.94
5	4824.00	40.20 PK	74.0	-33.80	1.59 H	246	32.19	8.01
6	4824.00	26.49 AV	54.0	-27.51	1.59 H	246	18.48	8.01
7	#7236.00	45.93 PK	67.95	-22.02	1.98 H	247	31.93	14.00
8	#7236.00	33.13 AV	63.46	-30.33	1.98 H	247	19.13	14.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	31.29 PK	74.0	-42.71	1.58 V	203	27.42	3.87
2	2390.00	19.35 AV	54.0	-34.65	1.58 V	203	15.48	3.87
3	*2412.00	84.54 PK			1.58 V	203	80.60	3.94
4	*2412.00	79.85 AV			1.58 V	203	75.91	3.94
5	4824.00	40.25 PK	74.0	-33.75	1.94 V	265	32.24	8.01
6	4824.00	27.54 AV	54.0	-26.46	1.94 V	265	19.53	8.01
7	#7236.00	48.60 PK	64.54	-15.94	1.05 V	265	34.60	14.00
8	#7236.00	34.52 AV	59.85	-25.33	1.05 V	265	20.52	14.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	92.60 PK			1.16 H	130	88.59	4.01
2	*2437.00	88.81 AV			1.16 H	130	84.80	4.01
3	4874.00	41.62 PK	74.0	-32.38	1.67 H	201	33.54	8.08
4	4874.00	28.66 AV	54.0	-25.34	1.67 H	201	20.58	8.08
5	7311.00	48.32 PK	74.0	-25.68	1.85 H	228	34.19	14.13
6	7311.00	36.58 AV	54.0	-17.42	1.85 H	228	22.45	14.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	88.73 PK			1.74 V	223	84.72	4.01
2	*2437.00	83.95 AV			1.74 V	223	79.94	4.01
3	4874.00	42.54 PK	74.0	-31.46	1.69 V	230	34.46	8.08
4	4874.00	27.71 AV	54.0	-26.29	1.69 V	230	19.63	8.08
5	7311.00	48.05 PK	74.0	-25.95	1.69 V	284	33.92	14.13
6	7311.00	35.69 AV	54.0	-18.31	1.69 V	284	21.56	14.13

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	91.33 PK			1.15 H	283	87.24	4.09
2	*2462.00	87.97 AV			1.15 H	283	83.88	4.09
3	2483.50	33.58 PK	74.0	-40.42	2.06 H	156	29.42	4.16
4	2483.50	22.62 AV	54.0	-31.38	2.06 H	156	18.46	4.16
5	4924.00	42.65 PK	74.0	-31.35	1.85 H	220	34.51	8.14
6	4924.00	28.64 AV	54.0	-25.36	1.85 H	220	20.50	8.14
7	7386.00	49.36 PK	74.0	-24.64	1.95 H	203	35.11	14.25
8	7386.00	36.80 AV	54.0	-17.20	1.95 H	203	22.55	14.25
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	86.23 PK			1.52 V	268	82.14	4.09
2	*2462.00	83.08 AV			1.52 V	268	78.99	4.09
3	2483.50	32.16 PK	74.0	-41.84	1.52 V	268	28.00	4.16
4	2483.50	20.74 AV	54.0	-33.26	1.52 V	268	16.58	4.16
5	4924.00	41.95 PK	74.0	-32.05	1.69 V	185	33.81	8.14
6	4924.00	28.96 AV	54.0	-25.04	1.69 V	185	20.82	8.14
7	7386.00	47.79 PK	74.0	-26.21	1.50 V	296	33.54	14.25
8	7386.00	35.31 AV	54.0	-18.69	1.50 V	296	21.06	14.25

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	51.54 PK	74.0	-22.46	1.18 H	259	47.67	3.87
2	2390.00	32.47 AV	54.0	-21.53	1.18 H	259	28.60	3.87
3	*2412.00	93.95 PK			1.18 H	259	90.01	3.94
4	*2412.00	82.36 AV			1.18 H	259	78.42	3.94
5	4824.00	43.95 PK	74.0	-30.05	1.94 H	233	35.94	8.01
6	4824.00	27.62 AV	54.0	-26.38	1.94 H	233	19.61	8.01
7	#7236.00	48.33 PK	73.95	-25.62	1.85 H	256	34.33	14.00
8	#7236.00	36.57 AV	62.36	-25.79	1.85 H	256	22.57	14.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	37.88 PK	74.0	-36.12	1.68 V	246	34.01	3.87
2	2390.00	23.52 AV	54.0	-30.48	1.68 V	246	19.65	3.87
3	*2412.00	89.32 PK			1.68 V	246	85.38	3.94
4	*2412.00	76.37 AV			1.68 V	246	72.43	3.94
5	4824.00	43.52 PK	74.0	-30.48	1.61 V	238	35.51	8.01
6	4824.00	28.56 AV	54.0	-25.44	1.61 V	238	20.55	8.01
7	#7236.00	48.61 PK	69.32	-20.71	1.95 V	211	34.61	14.00
8	#7236.00	36.50 AV	56.37	-19.87	1.95 V	211	22.50	14.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	93.56 PK			1.96 H	223	89.55	4.01
2	*2437.00	81.85 AV			1.96 H	223	77.84	4.01
3	4874.00	42.55 PK	74.0	-31.45	1.96 H	248	34.47	8.08
4	4874.00	27.56 AV	54.0	-26.44	1.96 H	248	19.48	8.08
5	7311.00	48.90 PK	74.0	-25.10	1.69 H	251	34.77	14.13
6	7311.00	36.50 AV	54.0	-17.50	1.69 H	251	22.37	14.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	90.11 PK			1.98 V	201	86.10	4.01
2	*2437.00	76.97 AV			1.98 V	201	72.96	4.01
3	4874.00	43.90 PK	74.0	-30.10	1.69 V	224	35.82	8.08
4	4874.00	26.40 AV	54.0	-27.60	1.69 V	224	18.32	8.08
5	7311.00	49.32 PK	74.0	-24.68	1.85 V	249	35.19	14.13
6	7311.00	36.54 AV	54.0	-17.46	1.85 V	249	22.41	14.13

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	92.07 PK			1.92 H	251	87.98	4.09
2	*2462.00	80.27 AV			1.92 H	251	76.18	4.09
3	2483.50	51.66 PK	74.0	-22.34	1.92 H	251	47.50	4.16
4	2483.50	34.58 AV	54.0	-19.42	1.92 H	251	30.42	4.16
5	4924.00	43.60 PK	74.0	-30.40	1.15 H	326	35.46	8.14
6	4924.00	28.49 AV	54.0	-25.51	1.15 H	326	20.35	8.14
7	7386.00	47.22 PK	74.0	-26.78	1.95 H	201	32.97	14.25
8	7386.00	34.90 AV	54.0	-19.10	1.95 H	201	20.65	14.25
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	89.62 PK			1.49 V	238	85.53	4.09
2	*2462.00	77.61 AV			1.49 V	238	73.52	4.09
3	2483.50	53.58 PK	74.0	-20.42	1.49 V	238	49.42	4.16
4	2483.50	30.48 AV	54.0	-23.52	1.49 V	238	26.32	4.16
5	4924.00	42.65 PK	74.0	-31.35	1.47 V	163	34.51	8.14
6	4924.00	28.42 AV	54.0	-25.58	1.47 V	163	20.28	8.14
7	7386.00	49.32 PK	74.0	-24.68	1.54 V	205	35.07	14.25
8	7386.00	36.80 AV	54.0	-17.20	1.54 V	205	22.55	14.25

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



802.11n 20MHz

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	41.22 PK	74.0	-32.78	1.95 H	234	37.35	3.87
2	2390.00	26.97 AV	54.0	-27.03	1.95 H	234	23.10	3.87
3	*2412.00	88.41 PK			1.95 H	234	84.47	3.94
4	*2412.00	76.05 AV			1.95 H	234	72.11	3.94
5	4824.00	41.63 PK	74.0	-32.37	1.69 H	263	33.62	8.01
6	4824.00	28.64 AV	54.0	-25.36	1.69 H	263	20.63	8.01
7	#7236.00	48.95 PK	68.41	-19.46	1.59 H	209	34.95	14.00
8	#7236.00	34.28 AV	56.05	-21.77	1.59 H	209	20.28	14.00
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	36.90 PK	74.0	-37.10	1.56 V	243	33.03	3.87
2	2390.00	23.38 AV	54.0	-30.62	1.56 V	243	19.51	3.87
3	*2412.00	86.76 PK			1.56 V	243	82.82	3.94
4	*2412.00	74.36 AV			1.56 V	243	70.42	3.94
5	4824.00	43.60 PK	74.0	-30.40	1.66 V	303	35.59	8.01
6	4824.00	26.59 AV	54.0	-27.41	1.66 V	303	18.58	8.01
7	#7236.00	49.25 PK	66.76	-17.51	1.49 V	225	35.25	14.00
8	#7236.00	36.58 AV	54.36	-17.78	1.49 V	225	22.58	14.00

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



**BUREAU
VERITAS**

Test Report No.: RF160810N018-2

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	94.04 PK			1.43 H	246	90.03	4.01
2	*2437.00	80.90 AV			1.43 H	246	76.89	4.01
3	4874.00	43.68 PK	74.0	-30.32	1.49 H	263	35.60	8.08
4	4874.00	28.54 AV	54.0	-25.46	1.49 H	263	20.46	8.08
5	7311.00	48.95 PK	74.0	-25.05	1.49 H	258	34.82	14.13
6	7311.00	36.54 AV	54.0	-17.46	1.49 H	258	22.41	14.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	90.74 PK			2.16 V	221	86.73	4.01
2	*2437.00	77.98 AV			2.16 V	221	73.97	4.01
3	4874.00	43.58 PK	74.0	-30.42	1.59 V	263	35.50	8.08
4	4874.00	28.47 AV	54.0	-25.53	1.59 V	263	20.39	8.08
5	7311.00	48.95 PK	74.0	-25.05	1.49 V	203	34.82	14.13
6	7311.00	36.64 AV	54.0	-17.36	1.49 V	203	22.51	14.13

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	88.11 PK			1.49 H	213	84.02	4.09
2	*2462.00	75.75 AV			1.49 H	213	71.66	4.09
3	2483.50	48.01 PK	74.0	-25.99	1.49 H	213	43.85	4.16
4	2483.50	28.85 AV	54.0	-25.15	1.49 H	213	24.69	4.16
5	4924.00	43.56 PK	74.0	-30.44	1.48 H	232	35.42	8.14
6	4924.00	28.54 AV	54.0	-25.46	1.48 H	232	20.40	8.14
7	7386.00	49.02 PK	74.0	-24.98	2.16 H	201	34.77	14.25
8	7386.00	35.48 AV	54.0	-18.52	2.16 H	201	21.23	14.25
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	87.85 PK			1.25 V	327	83.76	4.09
2	*2462.00	76.13 AV			1.25 V	327	72.04	4.09
3	2483.50	51.06 PK	74.0	-22.94	1.25 V	327	46.90	4.16
4	2483.50	30.08 AV	54.0	-23.92	1.25 V	327	25.92	4.16
5	4924.00	43.69 PK	74.0	-30.31	1.54 V	255	35.55	8.14
6	4924.00	27.40 AV	54.0	-26.60	1.54 V	255	19.26	8.14
7	7386.00	49.67 PK	74.0	-24.33	1.44 V	203	35.42	14.25
8	7386.00	36.60 AV	54.0	-17.40	1.44 V	203	22.35	14.25

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



BELOW 1GHz WORST-CASE DATA:


BT-LE (GFSK)

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.61	23.55	40.00	-16.45	100	0	35.27	-11.72
2	122.73	22.02	43.50	-21.48	100	0	39.25	-17.23
3	265.07	28.22	46.00	-17.78	100	0	42.22	-14.00
4	296.93	30.85	46.00	-15.15	100	0	45.11	-14.26
5	317.94	35.43	46.00	-10.57	100	0	49.19	-13.76
6	331.97	32.42	46.00	-13.58	100	0	46.06	-13.64

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.64	33.43	40.00	-6.57	100	0	45.16	-11.73
2	64.10	29.26	40.00	-10.74	100	0	54.13	-24.87
3	75.89	25.40	40.00	-14.60	100	0	48.77	-23.37
4	211.24	23.30	43.50	-20.20	100	0	43.03	-19.73
5	274.02	26.69	46.00	-19.31	100	0	41.38	-14.69
6	329.61	26.78	46.00	-19.22	100	0	40.46	-13.68

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





ABOVE 1GHz TEST DATA:

BT-LE (GFSK)

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	36.54 PK	74.0	-37.46	1.19 H	249	32.67	3.87
2	2390.00	24.57 AV	54.0	-29.43	1.19 H	249	20.70	3.87
3	*2402.00	87.29 PK			1.19 H	249	83.39	3.90
4	*2402.00	64.44 AV			1.19 H	249	60.54	3.90
5	4804.00	47.99 PK	74.0	-26.01	1.77 H	328	40.01	7.98
6	4804.00	36.73 AV	54.0	-17.27	1.77 H	328	28.75	7.98
7	#7206.00	48.52 PK	67.29	-18.77	1.85 H	332	34.57	13.95
8	#7206.00	34.31 AV	44.44	-10.13	1.85 H	332	20.36	13.95
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	30.10 PK	74.0	-43.90	1.52 V	230	26.23	3.87
2	2390.00	18.94 AV	54.0	-35.06	1.52 V	230	15.07	3.87
3	*2402.00	82.43 PK			1.52 V	230	78.53	3.90
4	*2402.00	58.96 AV			1.52 V	230	55.06	3.90
5	4804.00	41.70 PK	74.0	-32.30	1.13 V	259	33.72	7.98
6	4804.00	27.58 AV	54.0	-26.42	1.13 V	259	19.60	7.98
7	#7206.00	48.09 PK	62.43	-14.34	1.54 V	100	34.14	13.95
8	#7206.00	34.20 AV	38.96	-4.76	1.54 V	100	20.25	13.95

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	89.75 PK			1.85 H	302	85.73	4.02
2	*2440.00	66.21 AV			1.85 H	302	62.19	4.02
3	4880.00	40.25 PK	74.0	-33.75	1.54 H	110	32.16	8.09
4	4880.00	27.65 AV	54.0	-26.35	1.54 H	110	19.56	8.09
5	7320.00	47.67 PK	74.0	-26.33	1.50 H	98	33.53	14.14
6	7320.00	35.11 AV	54.0	-18.89	1.50 H	98	20.97	14.14
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	84.13 PK			1.52 V	265	80.11	4.02
2	*2440.00	59.61 AV			1.52 V	265	55.59	4.02
3	4880.00	40.30 PK	74.0	-33.70	1.95 V	206	32.21	8.09
4	4880.00	27.68 AV	54.0	-26.32	1.95 V	206	19.59	8.09
5	7320.00	47.71 PK	74.0	-26.29	1.25 V	263	33.57	14.14
6	7320.00	35.06 AV	54.0	-18.94	1.25 V	263	20.92	14.14

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	88.55 PK			1.98 H	247	84.40	4.15
2	*2480.00	63.64 AV			1.98 H	247	59.49	4.15
3	2483.50	35.48 PK	74.0	-38.52	1.98 H	247	31.32	4.16
4	2483.50	20.30 AV	54.0	-33.70	1.98 H	247	16.14	4.16
5	4960.00	43.36 PK	74.0	-30.64	1.85 H	263	35.17	8.19
6	4960.00	31.25 AV	54.0	-22.75	1.85 H	263	23.06	8.19
7	7440.00	49.59 PK	74.0	-24.41	1.64 H	237	35.25	14.34
8	7440.00	35.20 AV	54.0	-18.80	1.64 H	237	20.86	14.34
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	84.20 PK			1.64 V	224	80.05	4.15
2	*2480.00	60.72 AV			1.64 V	224	56.57	4.15
3	2483.50	32.06 PK	74.0	-41.94	1.64 V	224	27.90	4.16
4	2483.50	19.65 AV	54.0	-34.35	1.64 V	224	15.49	4.16
5	4960.00	41.29 PK	74.0	-32.71	1.52 V	203	33.10	8.19
6	4960.00	27.82 AV	54.0	-26.18	1.52 V	203	19.63	8.19
7	7440.00	47.86 PK	74.0	-26.14	1.89 V	203	33.52	14.34
8	7440.00	35.22 AV	54.0	-18.78	1.89 V	203	20.88	14.34

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 04,16	May 03,17
Power Sensor	Keysight	U2021XA	MY55060018	May 04,16	May 03,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct.11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.07,15	Sep. 06,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 28,15	Nov. 27,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Nov. 09,15	Nov. 08,16
Agile Signal Generator	Agilent	8645A	Agilent	Aug.08, 16	Aug.07, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Apr. 22, 16	Apr. 21, 17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.08, 16	Aug.07, 17

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.3.3 TEST PROCEDURE


1. Set resolution bandwidth (RBW) = 100KHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.



4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	8.09	0.5	PASS
6	2437	9.00	0.5	PASS
11	2462	8.10	0.5	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.04	0.5	PASS
6	2437	15.81	0.5	PASS
11	2462	15.81	0.5	PASS

802.11n 20MHz

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	17.20	0.5	PASS
6	2437	16.59	0.5	PASS
11	2462	16.68	0.5	PASS


BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	0.71	0.5	PASS
19	2440	0.70	0.5	PASS
39	2480	0.69	0.5	PASS



BUREAU
VERITAS

Test Report No.: RF160810N018-2






4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm).

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 04,16	May 03,17
Power Sensor	Keysight	U2021XA	MY55060018	May 04,16	May 03,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct.11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.07,15	Sep. 06,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 28,15	Nov. 27,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 09,15	Nov. 08,16
Signal Generator	Agilent	N5183A	MY50140980	Nov. 09,15	Nov. 08,16
Agile Signal Generator	Agilent	8645A	Agilent	Aug.08, 16	Aug.07, 17
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Apr. 22, 16	Apr. 21, 17
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.08, 16	Aug.07, 17

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.4.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	18.44	69.823	1	PASS
6	2437	18.41	69.343	1	PASS
11	2462	18.35	68.391	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	23.19	208.449	1	PASS
6	2437	23.02	200.447	1	PASS
11	2462	22.89	194.536	1	PASS

802.11n 20MHz

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
1	2412	21.77	150.314	1	PASS
6	2437	21.59	144.212	1	PASS
11	2462	21.36	136.773	1	PASS

BT-LE (GFSK)

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	PEAK POWER LIMIT (W)	PASS/FAIL
0	2402	8.38	6.887	1	PASS
19	2440	8.09	6.442	1	PASS
39	2480	7.16	5.200	1	PASS

4.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)	PEAK POWER LIMIT (W)	PASS / FAIL
1	2412	15.68	36.983	1	PASS
6	2437	15.65	36.728	1	PASS
11	2462	15.28	33.729	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)	PEAK POWER LIMIT (W)	PASS / FAIL
1	2412	15.07	32.137	1	PASS
6	2437	14.98	31.477	1	PASS
11	2462	14.56	28.576	1	PASS

802.11n 20MHz

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)	PEAK POWER LIMIT (W)	PASS / FAIL
1	2412	13.84	24.21	1	PASS
6	2437	13.76	23.768	1	PASS
11	2462	13.35	21.627	1	PASS

BT-LE (GFSK)


CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)
0	2402	5.07	3.214
19	2440	4.93	3.112
39	2480	3.94	2.477

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: 3KHz
- Set VBW $\geq 3 \times$ RBW.
- Detector = peak
- Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- Sweep time = auto couple.
- Use the peak marker function to determine the maximum amplitude level.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as item 4.3.6.

4.5.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-6.28	8.00	PASS
6	2437	-5.66	8.00	PASS
11	2462	-6.94	8.00	PASS

802.11g

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-9.94	8.00	PASS
6	2437	-10.24	8.00	PASS
11	2462	-10.37	8.00	PASS

802.11n 20MHz

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-9.95	8.00	PASS
6	2437	-9.79	8.00	PASS
11	2462	-10.88	8.00	PASS


BT-LE (GFSK)

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
0	2402	-6.76	8.00	PASS
19	2440	-6.87	8.00	PASS
39	2480	-7.79	8.00	PASS



BUREAU
VERITAS

Test Report No.: RF160810N018-2



4.6 OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD


No deviation.

4.6.6 EUT OPERATING CONDITION

Same as item 4.3.6

4.6.7 TEST RESULTS

802.11b






BUREAU
VERITAS

Test Report No.: RF160810N018-2

802.11g




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China


Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

802.11n 20MHz




BT-LE (GFSK)


CH 0




CH 19




CH 39




802.11b




802.11g



802.11n 20MHz



BT-LE (GFSK)





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---