

TEST REPORT

Reference No..... : WTN16S0448493E
FCC ID..... : 2AFOYL434FCNN
Applicant..... : Le Shi Zhi Xin Electronic Technology (Tian jin) Limited
Address..... : 201-427 2F B1 District, Anime building, No.126 Anime Middle Road,
Eco-city Tianjin, China
Manufacturer : Goertek.Inc
Address..... : West of Weian Road, North of Yingqian Street, High-tech Industrial
Development Zone, Weifang, Shandong Province, China., ShenZhen,
China
Product Name..... : LED TV
Model No..... : L434FCNN
Brand..... : LeEco
Standards..... : FCC CFR47 Part 15 Section 15.249: 2015
Date of Receipt sample..... : Apr. 15, 2016
Date of Test..... : Apr. 16 – May. 31, 2016
Date of Issue..... : Jun. 01, 2016
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China

Tel :+86-755-83551033


Fax:+86-755-83552400

Tested by:



Zero Zhou / Test Engineer

Approved by:



Philo Zhong / Manager

2 Test Summary

Test Items	Test Requirement	Result
Conducted Emissions	15.207	PASS
Radiated Emission	15.249(a) 15.209 15.205(a)	PASS
Periodic Operation	15.35(c)	PASS
Outside of Band Emission	15.249 15.205 15.209	PASS
20dB Bandwidth	15:215(c)	PASS
Antenna Requirement	15.203	PASS

3 Contents

	Page
1 COVER PAGE.....	1
2 TEST SUMMARY.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 GENERAL DESCRIPTION OF E.U.T.....	4
4.2 DETAILS OF E.U.T.....	5
4.3 CHANNEL LIST.....	5
4.4 TEST MODE.....	5
4.5 TEST FACILITY.....	5
5 EQUIPMENT USED DURING TEST.....	7
5.1 EQUIPMENTS LIST.....	7
5.2 DESCRIPTION OF SUPPORT UNITS.....	8
5.3 MEASUREMENT UNCERTAINTY.....	8
5.4 TEST EQUIPMENT CALIBRATION.....	8
6 CONDUCTED EMISSION.....	9
6.1 E.U.T. OPERATION.....	9
6.2 EUT SETUP.....	9
6.3 MEASUREMENT DESCRIPTION.....	9
6.4 CONDUCTED EMISSION TEST RESULT.....	10
7 RADIATION EMISSION TEST.....	12
7.1 EUT OPERATION.....	12
7.2 TEST SETUP.....	13
7.3 SPECTRUM ANALYZER SETUP.....	14
7.4 TEST PROCEDURE.....	15
7.5 TEST RESULT.....	16
8 PERIODIC OPERATION.....	23
9 20 DB BANDWIDTH MEASUREMENT.....	24
9.1 TEST PROCEDURE.....	24
9.2 TEST RESULT.....	24
10 ANTENNA REQUIREMENT.....	26

4 General Information

4.1 General Description of E.U.T.

Product Name:	LED TV
Model No.:	L434FCNN
Model Description:	N/A
Operation Frequency:	IEEE 802.11b/g/n(HT20):2412MHz ~ 2462MHz IEEE 802.11n(HT40):2422MHz~2452MHz IEEE 802.11a/ n(HT20/40)/ac(HT20/40/80): 5150MHz to 5250MHz IEEE 802.11a/ n(HT20/40)/ac(HT20/40/80): 5725MHz to 5850MHz BT: 2402-2480MHz SRD: 2403-2480MHz
The Lowest Oscillator:	32.768KHz
Antenna Gain:	ANT 0 2.4GHz WIFI:3.2 dBi 5.2GHz WIFI:4.1 dBi 5.8GHz WIFI:4.0 dBi ANT 1 2.4GHz WIFI:3.2 dBi 5.2GHz WIFI:3.3 dBi 5.8GHz WIFI:3.4 dBi ANT 2 2.4GHz BT:3.2 dBi ANT 3 2.4GHz SRD:3.1 dBi
Type of modulation:	IEEE 802.11b DSSS(CCK/QPSK/BPSK) IEEE 802.11g OFDM(BPSK/QPSK/16QAM/64QAM) IEEE 802.11n OFDM(BPSK/QPSK/16QAM/64QAM) IEEE for 802.11a: OFDM(BPSK/QPSK/16QAM/64QAM) IEEE for 802.11n : OFDM(BPSK/QPSK/16QAM/64QAM) IEEE for 802.11ac : OFDM (BPSK/QPSK/16QAM/64QAM/256QAM) BT: GFSK,PI/4-DQPSK,8DPSK SRD: GFSK
Number of transmitter chains:	WIFI:2*2 (MIMO) BT: 1 SRD: 1

The device supports MIMO 2*2, and the MIMO works with STBC(Space-Time Block Coding).The antenna is omnidirectional, does not support any directional gain in any modes.

TX power for MIMO rate, the wifi chip has a power/rate table that controls TX power from chipout, it's preset in nvram, FW don't need to calculate it again when MIMO rate is fixed. Of course the real radiation power is also related to antenna efficient.

Two transmitter signals are not correlated with each other.

4.2 Details of E.U.T.

Technical Data : AC 120V~60Hz, 73W

4.3 Channel List

Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)	Channel No.	Frequency (MHz)
1	2403	2	2408	3	2413	4	2418
5	2423	6	2428	7	2433	8	2440
9	2445	10	2450	11	2455	12	2460
13	2465	14	2470	15	2475	16	2480

4.4 Test Mode

Test Mode Description:

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Transmitting duty cycle is no less 98%.

The software is installed in operation system, named "RFTestTool.apk", Version 1, date 20160518.

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test mode	channel
Transmitting	2403MHz
Transmitting	2440MHz
Transmitting	2480MHz

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **IC – Registration No.: 7760A-1**

Waltek Services (Shenzhen) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration 7760A-1, Oct. 15, 2015.

- **FCC Test Site 1#– Registration No.: 880581**

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, April 29, 2014.

- **FCC Test Site 2#– Registration No.: 328995**

Waltek Services (Shenzhen) Co.,Ltd.
<http://www.waltek.com.cn>

Waltek Services(Shenzhen) Co., Ltd. EMC Laboratory `has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 328995, December 3, 2014

5 Equipment Used during Test

5.1 Equipments List

Conducted Emissions at Mains Terminals Disturbance Voltage(1#)						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMI Test Receiver	R&S	ESCI	100947	2015.09.14	2016.09.13
2	LISN	R&S	ENV216	100115	2015.09.14	2016.09.13
3	Cable	Top	TYPE16(3.5M)	-	2015.09.14	2016.09.13
Conducted Emissions at Mains Terminals Disturbance Voltage(2#)						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	EMI Test Receiver	R&S	ESCI	101155	2015.09.14	2016.09.13
2	LISN	SCHWARZBECK	NSLK 8128	8128-289	2015.09.14	2016.09.13
3	Limiter	York	MTS-IMP-136	261115-001-0024	2015.09.14	2016.09.13
4	Cable	Laplace	RF300	-	2015.09.14	2016.09.13
3m Semi-anechoic Chamber for Radiation(1#)						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Spectrum Analyzer	R&S	FSP	100091	2015.09.14	2016.09.13
2	Amplifier	Agilent	8447D	2944A10178	2015.09.14	2016.09.13
3	Active Loop Antenna	Beijing Dazhi	ZN30900A	0703	2015.09.14	2016.09.13
4	Trilog Broadband Antenna	SCHWARZBECK	VULB9163	336	2015.09.14	2016.09.13
5	Coaxial Cable (below 1GHz)	Top	TYPE16(13M)	-	2015.09.14	2016.09.13
6	Broad-band Horn Antenna	SCHWARZBECK	BBHA 9120 D	667	2015.09.14	2016.09.13
7	Broadband Preamplifier	COMPLIANCE DIRECTION	PAP-1G18	2004	2015.09.14	2016.09.13
8	Coaxial Cable (above 1GHz)	Top	1GHz-25GHz	EW02014-7	2015.09.14	2016.09.13
3m Semi-anechoic Chamber for Radiation(2#)						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Calibration Due Date
1	Test Receiver	R&S	ESCI	101296	2016.03.23	2017.03.22
2	Trilog Broadband Antenna	SCHWARZBECK	VULB9160	9160-3325	2016.03.23	2017.03.22
3	Amplifier	ANRITSU	MH648A	M43381	2016.03.23	2017.03.22
4	Cable	HUBER+SUHNER	CBL2	525178	2016.03.23	2017.03.22

5.2 Description of Support Units

Equipment	Manufacturer	Model No.	Series No.
/	/	/	/

5.3 Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-6}$
RF Power	± 1.0 dB
RF Power Density	± 2.2 dB
Radiated Spurious Emissions test	± 5.03 dB (Bilog antenna 30M~1000MHz)
	± 5.47 dB (Horn antenna 1000M~25000MHz)

5.4 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Conducted Emission

Test Requirement:	FCC CFR 47 Part 15 Section 15.207
Test Method:	ANSI C63.10:2009
Test Result:	PASS
Frequency Range:	150kHz to 30MHz
Class/Severity:	Class B
Limit:	66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth)

6.1 E.U.T. Operation

Operating Environment :


Temperature:	25.5 °C
Humidity:	51 % RH
Atmospheric Pressure:	101.2kPa

EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.

6.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2013.




6.3 Measurement Description

The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.


6.4 Conducted Emission Test Result

Live line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector	Remark
1	0.1980	34.10	10.26	44.36	63.69	-19.33	QP	
2	0.1980	24.96	10.26	35.22	53.69	-18.47	AVG	
3	0.2660	33.65	10.27	43.92	61.24	-17.32	QP	
4	0.2660	24.60	10.27	34.87	51.24	-16.37	AVG	
5	0.3899	31.42	10.27	41.69	58.06	-16.37	QP	
6	0.3899	20.37	10.27	30.64	48.06	-17.42	AVG	
7	0.6419	31.03	10.33	41.36	56.00	-14.64	QP	
8	0.6419	17.90	10.33	28.23	46.00	-17.77	AVG	
9	0.7060	27.48	10.36	37.84	56.00	-18.16	QP	
10	0.7060	16.40	10.36	26.76	46.00	-19.24	AVG	
11	5.3179	37.43	10.55	47.98	60.00	-12.02	QP	
12	5.3179	33.14	10.55	43.69	50.00	-6.31	AVG	

Neutral line:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Margin (dB)	Detector	Remark
1	0.1980	40.27	10.26	50.53	63.69	-13.16	QP	
2	0.1980	32.44	10.26	42.70	53.69	-10.99	AVG	
3	0.2620	34.48	10.26	44.74	61.36	-16.62	QP	
4	0.2620	25.50	10.26	35.76	51.36	-15.60	AVG	
5	0.3300	33.06	10.29	43.35	59.45	-16.10	QP	
6	0.3300	22.72	10.29	33.01	49.45	-16.44	AVG	
7	0.3980	32.13	10.27	42.40	57.89	-15.49	QP	
8	0.3980	20.56	10.27	30.83	47.89	-17.06	AVG	
9	0.4580	31.67	10.26	41.93	56.73	-14.80	QP	
10	0.4580	19.65	10.26	29.91	46.73	-16.82	AVG	
11	5.4500	38.26	10.56	48.82	60.00	-11.18	QP	
12	5.4500	33.21	10.56	43.77	50.00	-6.23	AVG	

7 Radiation Emission Test

Test Requirement: FCC Part15 Paragraph 15.249

Test Method: ANSI 63.10: 2009

Measurement Distance: 3m

Test Result: PASS

15.249(a)Limit:

Fundamental frequency	Field strength of fundamental		Field strength of harmonics	
	mV/m	dBuV/m	uV/m	dBuV/m
902-928 MHz	50	94	500	54
2400-2483.5 MHz	50	94	500	54
5725-5875 MHz	50	94	500	54
24.0-24.25 GHz	250	108	2500	68

15.209 Limit:

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Distance	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	$20\log^{(2400/F(kHz))} + 80$
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	$20\log^{(24000/F(kHz))} + 40$
1.705 ~ 30	30	30	100 * 30	$20\log^{(30)} + 40$
30 ~ 88	100	3	100	$20\log^{(100)}$
88 ~ 216	150	3	150	$20\log^{(150)}$
216 ~ 960	200	3	200	$20\log^{(200)}$
Above 960	500	3	500	$20\log^{(500)}$

Note: RF Voltage(dBuV)=20 log₁₀ RF Voltage(uV)

7.1 EUT Operation

Operating Environment :

Temperature: 23.5 °C

Humidity: 51.1 % RH

Atmospheric Pressure: 101.2kPa


EUT Operation :

The test was performed in transmitting mode, the test data were shown in the report.


7.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI 63.10: 2009.


The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

Below 30MHz

Sweep Speed..... Auto
 IF Bandwidth..... 10kHz
 Video Bandwidth..... 10kHz
 Resolution Bandwidth..... 10kHz

30MHz ~ 1GHz

Sweep Speed..... Auto
 Detector..... PK
 Resolution Bandwidth..... 100kHz
 Video Bandwidth..... 300kHz

Above 1GHz

Sweep Speed..... Auto
 DetectorPK
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 3MHz
 DetectorAve.
 Resolution Bandwidth..... 1MHz
 Video Bandwidth..... 10Hz

7.4 Test Procedure

1. The EUT is placed on a turntable, which is above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions. The spectrum was investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

7.5 Test Result

Test Frequency: 32.768kHz~30MHz

Frequency (MHz)	Measurement results	Detector	Correct factor	Extrapolation factor	Measurement results (calculated)	Limits	Margin
	dB μ V @3m	PK/QP	dB/m	dB	dB μ V/m @30m	dB μ V/m @30m	dB
26.980	26.24	QP	19.90	40.00	6.14	29.54	-23.40

Test Frequency: 30MHz ~ 18GHz

Test Mode: Low Channel

Frequency	Receive r Reading	Detector	Turn table Angle	RX Antenna		Correcte d Factor	Corrected Amplitude	FCC Part 15.231/209/205	
				Heigh t	Polar			Limit	Margin
(MHz)	(dB μ V)	(PK/QP /Ave)	Degree	(m)	(H/V)	(dB/m)	(dB μ V/m)	(dB μ V/m)	(dB)
302.56	39.21	QP	140	1.9	V	-11.40	27.81	40.00	-12.19
*2403.00	69.54	PK	174	1.1	H	-13.08	56.46	114.00	-57.54
*2403.00	64.31	PK	69	1.7	V	-13.08	51.23	114.00	-62.77
4806.00	45.65	PK	352	1.4	H	0.09	45.74	94.00	-48.26
4806.00	48.12	PK	57	1.3	V	0.09	48.21	94.00	-45.79
7209.00	46.55	PK	97	1.0	H	3.01	49.56	94.00	-44.44
7209.00	45.37	PK	258	1.8	V	3.01	48.38	94.00	-45.62

* Fundamental Frequency

Frequency	PK	Turn table Angle	RX Antenna		Duty cycle Factor	AV	FCC Part 15.231/209/205	
			Height	Polar			Limit	Margin
(MHz)	(dB μ V/m)	Degree	(m)	(H/V)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
*2403.00	56.46	174	1.1	H	-38.50	17.96	94.00	-76.04
*2403.00	51.23	69	1.7	V	-38.50	12.73	94.00	-81.27
4806.00	45.74	352	1.4	H	-38.50	7.24	74.00	-66.76
4806.00	48.21	57	1.3	V	-38.50	9.71	74.00	-64.29
7209.00	49.56	97	1.0	H	-38.50	11.06	74.00	-62.94
7209.00	48.38	258	1.8	V	-38.50	9.88	74.00	-64.12

* Fundamental Frequency

Test Mode: Middle Channel

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.231/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP /Ave)	Degree	(m)	(H/V)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)
302.56	38.27	QP	103	1.1	V	-11.40	26.87	40.00	-13.13
*2440.00	70.12	PK	331	1.0	H	-13.08	57.04	114.00	-56.96
*2440.00	66.89	PK	229	1.0	V	-13.08	53.81	114.00	-60.19
4880.00	44.29	PK	343	2.0	H	0.09	44.38	94.00	-49.62
4880.00	49.31	PK	300	1.4	V	0.09	49.40	94.00	-44.60
7320.00	47.58	PK	318	1.8	H	3.01	50.59	94.00	-43.41
7320.00	45.12	PK	84	1.0	V	3.01	48.13	94.00	-45.87

* Fundamental Frequency

Frequency	PK	Turn table Angle	RX Antenna		Duty cycle Factor	AV	FCC Part 15.231/209/205	
			Height	Polar			Limit	Margin
(MHz)	(dBμV/m)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
*2440.00	57.04	331	1.0	H	-38.50	18.54	94.00	-75.46
*2440.00	53.81	229	1.0	V	-38.50	15.31	94.00	-78.69
4880.00	44.38	343	2.0	H	-38.50	5.88	74.00	-68.12
4880.00	49.40	300	1.4	V	-38.50	10.90	74.00	-63.10
7320.00	50.59	318	1.8	H	-38.50	12.09	74.00	-61.91
7320.00	48.13	84	1.0	V	-38.50	9.63	74.00	-64.37

* Fundamental Frequency

Test Mode: High Channel

Frequency	Receiver Reading	Detector	Turn table Angle	RX Antenna		Corrected Factor	Corrected Amplitude	FCC Part 15.231/209/205	
				Height	Polar			Limit	Margin
(MHz)	(dBμV)	(PK/QP /Ave)	Degree	(m)	(H/V)	(dB/m)	(dBμV/m)	(dBμV/m)	(dB)
302.56	39.51	QP	244	1.9	V	-11.40	28.11	40.00	-11.89
*2480.00	71.23	PK	349	1.4	H	-13.08	58.15	114.00	-55.85
*2480.00	67.38	PK	170	1.5	V	-13.08	54.30	114.00	-59.70
4960.00	45.69	PK	149	1.0	H	0.09	45.78	94.00	-48.22
4960.00	50.21	PK	328	1.2	V	0.09	50.30	94.00	-43.70
7440.00	48.33	PK	95	1.7	H	3.01	51.34	94.00	-42.66
7440.00	46.29	PK	113	1.8	V	3.01	49.30	94.00	-44.70

* Fundamental Frequency

Frequency	PK	Turn table Angle	RX Antenna		Duty cycle Factor	AV	FCC Part 15.231/209/205	
			Height	Polar			Limit	Margin
(MHz)	(dBμV/m)	Degree	(m)	(H/V)	(dB)	(dBμV/m)	(dBμV/m)	(dB)
*2480.00	58.15	349	1.4	H	-38.50	19.65	94.00	-74.35
*2480.00	54.30	170	1.5	V	-38.50	15.80	94.00	-78.20
4960.00	45.78	149	1.0	H	-38.50	7.28	74.00	-66.72
4960.00	50.30	328	1.2	V	-38.50	11.80	74.00	-62.20
7440.00	51.34	95	1.7	H	-38.50	12.84	74.00	-61.16
7440.00	49.30	113	1.8	V	-38.50	10.80	74.00	-63.20

* Fundamental Frequency


Test Frequency :From 18GHz to 25GHz

The measurements were more than 20 dB below the limit and not reported.


Outside of Band Emissions

Left band- 2403MHz transmitting

Horizontal




Vertical




Right band-2480MHz transmitting

Horizontal



Vertical



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	2483.500	67.27	-15.39	51.88	74.00	-22.12	peak	
2	2483.500	57.58	-15.39	42.19	54.00	-11.81	AVG	
3	2484.880	64.18	-15.39	48.79	74.00	-25.21	peak	
4	2484.880	54.54	-15.39	39.15	54.00	-14.85	AVG	

8 Periodic Operation

The duty cycle was determined by the following equation:

To calculate the actual field intensity, the duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

Duty Cycle(%)=Total On interval in a complete pulse train/ Length of a complete pulse train * %


Duty Cycle Correction Factor(dB)=20 * Log₁₀(Duty Cycle(%))

Total transmission time(ms)	0.238
Length of a complete transmission period(ms)	20.02
Duty Cycle(%)	1.19
Duty Cycle Correction Factor(dB)	-38.50

Refer to the duty cycle plot (as below), This device meets the FCC requirement.

Length of a complete pulse train:

Remark: FCC part15.35(c) required that a complete pulse train is more than 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.



9 20 dB Bandwidth Measurement

Test Requirement:

FCC CFR47 Part 15 Section 15.215(c)

Test Method:

ANSI C63.10:2013

Test Mode:

Transmitting

9.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 30kHz, VBW = 100kHz



9.2 Test Result

Test Channel	Bandwidth
2403MHz	2401.7MHz
2440MHz	2438.7MHz
2480MHz	2478.4MHz

Test plots

Low





10 Antenna Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. This device uses of an antenna that uses a unique coupling to the intentional radiator. Antenna connector complied with the requirement.

=====End of Report=====