

**TEST REPORT
RADIO FREQUENCY
FOR WIRELESS POWER TRANSFER**

Report Number.....:	ITA26B07001347W 002
Test date	2026-07-20 to 2026-08-24
Issue date	2026-08-24
Total number of pages	8
Standard/According to	KDB 680106 D01 Wireless Power Transfer v04
Template version	V2.0
Testing Laboratory	Itestek Testing Co., Ltd. (Dongguan)
Address	Room 116, Building 8 and Room 606, Building 3, Innovation Port of Hanyuan, Liyuan Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518000, People's Republic of China
Tested by	Tom Zhang 
Checked by	Oliver Qiao 
Approved by	Rock Huang 
	
Applicant's name	Shenzhen Powerqi Technology Co., Ltd
Address	Room 201, 302, 401 of A4 Building, Block A, Fangxing Science and Technology Park, No. 13 of Baonan Road, Longgang District, Shenzhen, China
Manufacturer's name	Same as applicant
Address	Same as applicant
Factory's name	Same as applicant
Address	Same as applicant
Trade Mark.....	N/A
Product description	Wireless Car Charger
Model/Type reference	MQ08
Ratings.....	For Wireless Car Charger Input: 5Vdc, 3A; 9Vdc, 3A; 12Vdc, 2.5A; 15Vdc, 2A Output: 25W Max For car charger (model XY-DD035001) Input: 12-24Vdc Output: 5Vdc, 3A; 9Vdc, 3A; 12Vdc, 3A
FCC ID	2AFP2MQ08
Test result.....	Pass

Declare:

1. This report shall not be partially reproduced without the consent of the laboratory.
2. If the report without tester's signature, auditor's signature, approver's signature and inspection seal, the report is invalid.
3. The test results are valid only for the tested samples.
4. After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.
5. If the report is not stamped with the accreditation recognized seal, it will only be used for scientific research, education, and internal quality control activities, and is not used for the purpose of issuing supporting data to the society.

Testing laboratory:

Itestek Testing Co., Ltd. (Dongguan)

Room 116, Building 8 and Room 606, Building 3, Innovation Port of Hanyuwan, Liyuan Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, 518000, People's Republic of China

FCC designation number CN1436

A2LA has accredited, certificate Number 7609.01


1. General test information

1.1. Description of EUT

Details of technical specification refer to the description in follows:

Test model number	MQ08
Model different	/
Frequency range (Hz)	111K-205K,360K
Modulation technique	FSK
Antenna type	Coil Antenna
Antenna gain	1 dBi
Temperature range (°C)	-20 ~ 80
Hardware version	V1.0
Software version	V1.0

Block diagram EUT configuration for test



1.2. Test modes

Mode	Test Status
1	AC Mains + Mobile phone charging mode for output 5W (111K-205K Hz)
2	AC Mains + Mobile phone charging mode for output 7.5W (111K-205KHz)
3	AC Mains + Mobile phone charging mode for output 10W (111K-205KHz)
4	AC Mains + Mobile phone charging mode for output 15W (360KHz)
5	AC Mains + Mobile phone charging mode for output 25W (360KHz)
6	AC Mains + standby

Worst case statement:

The aforementioned testing modes were all conducted under Battery Status: ≤1% (full load), Battery Status: ≈50% (half load), and Battery Status: ≥99% (no load) conditions.

After testing, it was found that the test data under full load condition is the worst-case.

The report reflecting only the worst-case test data.

1.3. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range (°C)	15-35
Humidity range (%)	30-75
Pressure range (kPa)	85-105

1.4. Test environment conditions

Item	Equipment	Mfr/Brand	Model / Type	Series No.	Note
1	Load	Apple	Iphone 17	--	Wireless charging of phone: 5W, 7.5W, 15W, 25W
2	Load	YBT	P V3.1-Qi2.2/MPP	--	Wireless charging of phone: 5W, 7.5W, 10W, 15W, 25W
3	HUAWEI Super Charge	Huawei	HW-2005C02	--	Input: 100-240Vac, 50/60Hz, 2.4A Output: USB-C 5Vdc, 3A; 9Vdc, 3A; 10Vdc, 4A; 11Vdc, 6A; 12Vdc, 3A; 15Vdc, 3A; 20Vdc, 5A; USB-A 5Vdc, 2A; 10Vdc, 4A; 11Vdc, 6A; 20Vdc, 5A
Remark: The test utilized HUAWEI Super Charge, and the input voltage of HUAWEI Super Charge was 120Vac, 60Hz.					

2. RF exposure test

2.1 Measuring standard

KDB 680106 D01 Wireless Power Transfer v04
47 CFR Part 2.1091

2.2 Measurement uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	E-field	$\pm 0.97\%$
2	H-field	$\pm 0.74\%$
3	Temperature	$\pm 0.5^{\circ}\text{C}$
4	Humidity	$\pm 2\%$
Decision Rule		
☒ Uncertainty is not included		
☐ Uncertainty is includedS		

2.3 Test procedure

The RF exposure test was performed in anechoic chamber.

The measurement probe was placed at test distance (20 cm from all sides and 20 cm from the top) which is between the edge of the charger and the geometric center of probe.

The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E) were completed.

The EUT was measured according to the dictates of KDB 680106 D01 v04.

Remark: The EUT's test position A, B, C, D and E is valid for the E and H field measurements.

2.4 Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)


Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz
 *=Plane-wave equivalent power density
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

2.5 Test setup

For mobile exposure conditions:



2.6 Test equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Near-field Electric and Electric Field Sensor System	Schmid & Partner Engineering AG	MAGPy-8H3D + E3D V2	3127	2026-09-08
2	Near-field Electric and Electric Field Sensor System	Schmid & Partner Engineering AG	MAGPy-DASV 2	3121	2026-09-08
3	Near-field Electric and	Narda	EHP-400	4772	2026-09-08

	Electric Field Sensor System				
--	---------------------------------	--	--	--	--

2.7 Test result

Test Mode	3	Remark	/			Result	PASS
H-Filed Strength at 20 cm from the edges surrounding the EUT							
Top (A/m)	Bottom (A/m)	Left (A/m)	Right (A/m)	Front (A/m)	Rear (A/m)	50% Limits (A/m)	Limits (A/m)
0.02	0.03	0.01	0.02	0.02	0.04	0.815	1.63

Test Mode	5	Remark	/			Result	PASS
H-Filed Strength at 20 cm from the edges surrounding the EUT							
Top (A/m)	Bottom (A/m)	Left (A/m)	Right (A/m)	Front (A/m)	Rear (A/m)	50% Limits (A/m)	Limits (A/m)
0.03	0.02	0.03	0.03	0.03	0.04	0.815	1.63