

FCC Radio Test Report

Product Name:	LI-ION Battery Charger/W Bluetooth Speaker
Trademark:	MobilePower, LLC
FCC ID:	2AFPJLI7000
Model Name :	LI7000
Prepared For :	MobilePower LLC
Address :	18 Maywood Way, Bluffton, South Carolina 29910
Prepared By :	DongGuan Precise Testing Service Co., Ltd.
Address :	Building D, Baoding Technology Park, Guangming Road 2, Guangming Community, Dongcheng District, Dongguan, Guangdong, China
Test Date:	Aug. 03 - Aug. 17, 2015
Date of Report :	Aug. 17, 2015
Report No.:	PT1507298256F

TEST RESULT CERTIFICATION

Applicant's name : MobilePower LLC

Address : 18 Maywood Way, Bluffton, South Carolina 29910

Manufacture's Name : Shenzhen YKSH Sci&Tech Development Co.,ltd

Address : Room 1403-1404, Block B Shandong Building, Nanhai Avenue
Nanshan District Shenzhen Guangdong China

Product description

Product name : LI-ION Battery Charger/W Bluetooth Speaker

Model and/or type reference : LI7000

Serial Model : N/A

Standards : FCC Part15.247

Test procedure ANSI C63.4-2003

This device described above has been tested by PTS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of PTS, this document may be altered or revised by PTS, personal only, and shall be noted in the revision of the document.

Testing Engineer : _____




(Juan Zeng)

Technical Manager : _____



(Tom Zhang)

Authorized Signatory : _____



(Chris Du)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	14
3.1.2 TEST PROCEDURE	15
3.1.3 DEVIATION FROM TEST STANDARD	15
3.1.4 TEST SETUP	15
3.1.5 EUT OPERATING CONDITIONS	15
3.1.6 TEST RESULTS	16
3.2 RADIATED EMISSION MEASUREMENT	18
3.2.1 RADIATED EMISSION LIMITS	18
3.2.2 TEST PROCEDURE	19
3.2.3 DEVIATION FROM TEST STANDARD	19
3.2.4 TEST SETUP	20
3.2.5 EUT OPERATING CONDITIONS	21
3.2.6 TEST RESULTS (BELOW 30 MHZ)	22
3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)	23
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	25
3.2.9 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)	43
4 . NUMBER OF HOPPING CHANNEL	55
4.1 APPLIED PROCEDURES / LIMIT	55
4.1.1 TEST PROCEDURE	55
4.1.2 DEVIATION FROM STANDARD	55
4.1.3 TEST SETUP	55
4.1.4 EUT OPERATION CONDITIONS	55
4.1.5 TEST RESULTS	56
5 . AVERAGE TIME OF OCCUPANCY	57

Table of Contents	Page
5.1 APPLIED PROCEDURES / LIMIT	57
5.1.1 TEST PROCEDURE	57
5.1.2 DEVIATION FROM STANDARD	57
5.1.3 TEST SETUP	58
5.1.4 EUT OPERATION CONDITIONS	58
5.1.5 TEST RESULTS	59
6 . HOPPING CHANNEL SEPARATION MEASUREMENT	65
6.1 APPLIED PROCEDURES / LIMIT	65
6.1.1 TEST PROCEDURE	65
6.1.2 DEVIATION FROM STANDARD	65
6.1.3 TEST SETUP	65
6.1.4 EUT OPERATION CONDITIONS	65
6.1.5 TEST RESULTS	66
7 . BANDWIDTH TEST	72
7.1 APPLIED PROCEDURES / LIMIT	72
7.1.1 TEST PROCEDURE	72
7.1.2 DEVIATION FROM STANDARD	72
7.1.3 TEST SETUP	72
7.1.4 EUT OPERATION CONDITIONS	72
7.1.5 TEST RESULTS	73
8 . PEAK OUTPUT POWER TEST	79
8.1 APPLIED PROCEDURES / LIMIT	79
8.1.1 TEST PROCEDURE	79
8.1.2 DEVIATION FROM STANDARD	79
8.1.3 TEST SETUP	79
8.1.4 EUT OPERATION CONDITIONS	79
8.1.5 TEST RESULTS	80
9 . ANTENNA REQUIREMENT	86
9.1 STANDARD REQUIREMENT	86
9.2 EUT ANTENNA	86
10 . EUT TEST PHOTO	87
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

1.1 TEST FACILITY

FCC Registration No.: 371540, IC Registration No.: 12191A-1

Dongguan Precise Testing Service Co., Ltd.

Add.: Building D,Baoding Technology Park,Guangming Road2,Dongcheng District, Dongguan, Guangdong, China

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power,conducted	$\pm 0.16\text{dB}$
3	Spurious emissions,conducted	$\pm 0.21\text{dB}$
4	All emissions,radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions,radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	LI-ION Battery Charger/W Bluetooth Speaker	
Trade Name	MobilePower, LLC	
Model Name	LI7000	
Serial Model	N/A	
Model Difference	N/A	
Product Description	The EUT is a LI-ION Battery Charger/W Bluetooth Speaker	
	Operation Frequency:	2402~2480 MHz
	Modulation Type:	BT(1Mbps): GFSK BT EDR(2Mbps): $\pi/4$ -DQPSK BT EDR(3Mbps): 8-DPSK
	Bit Rate of Transmitter	1Mbps/2Mbps/3Mbps
	Number Of Channel	79 CH
	Antenna Designation:	Please see Note 3.
	Output Power(Conducted):	BT(1Mbps): 3.628dBm BT EDR(2Mbps): 3.090dBm BT EDR(3Mbps): 3.191dBm
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Adapter	N/A	
Battery	N/A	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	NA	1.0	BT Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Link

For Conducted Emission	
Final Test Mode	Description
Mode 4	Link

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:


- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The EUT use new battery.
- (3) The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: Broadcom		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1/2/3Mbps)	DEF	DEF	DEF

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	LI-ION Battery Charger/W Bluetooth Speaker	MobilePower, LLC	LI7000	N/A	EUT
E-2	Netbook	DELL	PP10L	N/A	
E-3	Netbook Adapter	DELL	HA65NS1-00	N/A	

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	80cm	
C2	NO	YES	150cm	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA
2. N/A = No Calibration Request.

FOR CONDUCTED EMISSION TEST:

Name of Equipment	Manufacturer	Model	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2015	July 7, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2015	July 7, 2016
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2015	July 3, 2016
Shielded Room	CHENGYU	843	PTS-002	June 6, 2015	June 5, 2016

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA and NIM/CHINA

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.


3.1.6 TEST RESULTS

EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC120V	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1740	41.42	11.10	52.52	64.76	-12.24	QP
0.1740	28.34	11.10	39.44	54.76	-15.32	AVG
0.2340	33.60	10.77	44.37	62.30	-17.93	QP
0.2340	21.25	10.77	32.02	52.30	-20.28	AVG
3.9580	31.96	10.60	42.56	56.00	-13.44	QP
3.9580	25.60	10.60	36.20	46.00	-9.80	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	26 °C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	AC120V	Test Mode :	Mode 4

Frequency	Reading Level	Correct Factor	Measure-ment	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV)	(dBμV)	(dB)	
0.1740	41.39	11.37	52.76	64.76	-12.00	QP
0.1740	25.00	11.37	36.37	54.76	-18.39	AVG
0.2340	33.28	11.01	44.29	62.30	-18.01	QP
0.2340	22.44	11.01	33.45	52.30	-18.85	AVG
4.5979	30.50	10.62	41.12	56.00	-14.88	QP
4.5979	25.15	10.62	35.77	46.00	-10.23	AVG

Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5 th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

- The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BELOW 30 MHZ)

EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX	Polarization :	---

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance/test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.


3.2.7 TEST RESULTS (BETWEEN 30M – 1000 MHZ)

EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	Model 4	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
197.8926	17.80	8.99	26.79	43.50	-16.71	QP
234.1682	18.76	11.03	29.79	46.00	-16.21	QP
774.1584	10.69	26.16	36.85	46.00	-9.15	QP

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	Mode 4	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
31.5093	13.67	17.66	31.33	40.00	-8.67	QP
541.3723	14.46	22.44	36.90	46.00	-9.10	QP
758.0407	10.38	26.40	36.78	46.00	-9.22	QP

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



3.2.8 TEST RESULTS (ABOVE 1000 MHZ)


EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz – CH 00(1Mbps)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4804.121	64.95	-3.64	61.31	74.00	-12.69	peak
4804.121	48.32	-3.64	44.68	54.00	-9.32	AVG
7206.132	56.42	-0.95	55.47	74.00	-18.53	peak
7206.132	42.78	-0.95	41.83	54.00	-12.17	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz – CH 00(1Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.115	6.06	-3.64	2.42	74.00	-71.58	peak
4804.115	49.56	-3.64	45.92	54.00	-8.08	AVG
7206.122	57.33	-0.95	56.38	74.00	-17.62	peak
7206.122	44.32	-0.95	43.37	54.00	-10.63	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2441MHz – CH 39(1Mbps)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4882.163	64.64	-3.68	60.96	74.00	-13.04	peak
4882.163	46.26	-3.68	42.58	54.00	-11.42	AVG
7323.136	55.25	-0.82	54.43	74.00	-19.57	peak
7323.136	42.25	-0.82	41.43	54.00	-12.57	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2441MHz – CH 39(1Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4882.123	64.24	-3.68	60.56	74.00	-13.44	peak
4882.123	46.23	-3.68	42.55	54.00	-11.45	AVG
7323.146	55.48	-0.82	54.66	74.00	-19.34	peak
7323.146	41.45	-0.82	40.63	54.00	-13.37	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2480MHz – CH 78(1Mbps)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4960.156	65.86	-3.59	62.27	74.00	-11.73	peak
4960.156	46.58	-3.59	42.99	54.00	-11.01	AVG
7440.155	54.76	-0.68	54.08	74.00	-19.92	peak
7440.155	45.03	-0.68	44.35	54.00	-9.65	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2480MHz – CH 78(1Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4960.131	63.56	-3.59	59.97	74.00	-14.03	peak
4960.131	48.45	-3.59	44.86	54.00	-9.14	AVG
7440.150	56.26	-0.68	55.58	74.00	-18.42	peak
7440.150	44.56	-0.68	43.88	54.00	-10.12	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz – CH 00(2Mbps)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.126	63.03	-3.64	59.39	74.00	-14.61	peak
4804.126	47.56	-3.64	43.92	54.00	-10.08	AVG
7206.112	53.56	-0.95	52.61	74.00	-21.39	peak
7206.112	42.80	-0.95	41.85	54.00	-12.15	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz – CH 00(2Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.119	64.56	-3.64	60.92	74.00	-13.08	peak
4804.119	49.56	-3.64	45.92	54.00	-8.08	AVG
7206.128	56.78	-0.95	55.83	74.00	-18.17	peak
7206.128	41.23	-0.95	40.28	54.00	-13.72	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2441MHz – CH 39(2Mbps)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4882.158	64.56	-3.68	60.88	74.00	-13.12	peak
4882.158	45.89	-3.68	42.21	54.00	-11.79	AVG
7323.174	56.59	-0.82	55.77	74.00	-18.23	peak
7323.174	42.19	-0.82	41.37	54.00	-12.63	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2441MHz – CH 39(2Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4882.191	64.95	-3.68	61.27	74.00	-12.73	peak
4882.191	46.45	-3.68	42.77	54.00	-11.23	AVG
7323.165	57.65	-0.82	56.83	74.00	-17.17	peak
7323.165	41.32	-0.82	40.50	54.00	-13.50	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2480MHz – CH 78(2Mbps)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4960.126	65.99	-3.59	62.40	74.00	-11.60	peak
4960.126	42.11	-3.59	38.52	54.00	-15.48	AVG
7440.153	53.56	-0.68	52.88	74.00	-21.12	peak
7440.153	42.89	-0.68	42.21	54.00	-11.79	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2480MHz – CH 78(2Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4960.112	65.56	-3.59	61.97	74.00	-12.03	peak
4960.112	47.55	-3.59	43.96	54.00	-10.04	AVG
7440.126	58.57	-0.68	57.89	74.00	-16.11	peak
7440.126	45.56	-0.68	44.88	54.00	-9.12	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz – CH00 (3Mbps)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.130	63.25	-3.64	59.61	74.00	-14.39	peak
4804.130	46.31	-3.64	42.67	54.00	-11.33	AVG
7206.145	53.56	-0.95	52.61	74.00	-21.39	peak
7206.145	42.32	-0.95	41.37	54.00	-12.63	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2402MHz – CH00 (3Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4804.105	63.56	-3.64	59.92	74.00	-14.08	peak
4804.105	45.26	-3.64	41.62	54.00	-12.38	AVG
7206.127	56.67	-0.95	55.72	74.00	-18.28	peak
7206.127	42.25	-0.95	41.30	54.00	-12.70	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2441MHz – CH39(3Mbps)	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4882.172	64.16	-3.68	60.48	74.00	-13.52	peak
4882.172	46.56	-3.68	42.88	54.00	-11.12	AVG
7323.188	55.86	-0.82	55.04	74.00	-18.96	peak
7323.188	42.75	-0.82	41.93	54.00	-12.07	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2441MHz – CH39 (3Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4882.112	62.25	-3.68	58.57	74.00	-15.43	peak
4882.112	46.63	-3.68	42.95	54.00	-11.05	AVG
7323.141	54.53	-0.82	53.71	74.00	-20.29	peak
7323.141	42.25	-0.82	41.43	54.00	-12.57	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2480MHz – CH78 (3Mbps)	Polarization :	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
4960.176	61.87	-3.59	58.28	74.00	-15.72	peak
4960.176	46.87	-3.59	43.28	54.00	-10.72	AVG
7440.155	55.32	-0.68	54.64	74.00	-19.36	peak
7440.155	42.32	-0.68	41.64	54.00	-12.36	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX 2480MHz – CH78 (3Mbps)	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
4960.175	61.26	-3.59	57.67	74.00	-16.33	peak
4960.175	46.23	-3.59	42.64	54.00	-11.36	AVG
7440.114	53.12	-0.68	52.44	74.00	-21.56	peak
7440.114	41.23	-0.68	40.55	54.00	-13.45	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No emission detected above 18GHz




3.2.9 TEST RESULTS (RESTRICTED BANDS REQUIREMENTS)

EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2402MHz-1Mbps	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2310.000	51.00	-12.89	38.11	74.00	-35.89	peak
2390.000	52.44	-13.06	39.38	74.00	-34.62	peak
2400.000	81.24	-12.99	68.25	74.00	-5.75	peak
2400.000	57.43	-12.99	44.44	54.00	-9.56	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2402MHz-1Mbps	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2310.000	50.76	-12.89	37.87	74.00	-36.13	peak
2390.000	50.75	-13.06	37.69	74.00	-36.31	peak
2400.000	74.95	-12.99	61.96	74.00	-12.04	peak
2400.000	59.01	-12.99	46.02	54.00	-7.98	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2480MHz-1Mbps	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	56.68	-12.78	43.90	74.00	-30.10	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2480MHz-1Mbps	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	53.68	-12.78	40.90	74.00	-33.10	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2402MHz-2Mbps	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2310.000	50.56	-12.89	37.67	74.00	-36.33	peak
2390.000	51.08	-13.06	38.02	74.00	-35.98	peak
2400.000	78.86	-12.99	65.87	74.00	-8.13	peak
2400.000	60.42	-12.99	47.43	54.00	-6.57	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2402MHz-2Mbps	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2310.000	50.56	-12.89	37.67	74.00	-36.33	peak
2390.000	50.75	-13.06	37.69	74.00	-36.31	peak
2400.000	72.89	-12.99	59.90	74.00	-14.10	peak
2400.000	56.86	-12.99	43.87	54.00	-10.13	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2480MHz-2Mbps	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	55.65	-12.78	42.87	74.00	-31.13	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2480MHz-2Mbps	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	51.56	-12.78	38.78	74.00	-35.22	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2402MHz-3Mbps	Polarization :	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
2310.000	50.12	-12.89	37.23	74.00	-36.77	peak
2390.000	52.86	-13.06	39.80	74.00	-34.20	peak
2400.000	79.24	-12.99	66.25	74.00	-7.75	peak
2400.000	59.89	-12.99	46.90	54.00	-7.10	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2402MHz-3Mbps	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2310.000	50.49	-12.89	37.60	74.00	-36.40	peak
2390.000	51.56	-13.06	38.50	74.00	-35.50	peak
2400.000	74.46	-12.99	61.47	74.00	-12.53	peak
2400.000	58.07	-12.99	45.08	54.00	-8.92	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2480MHz-3Mbps	Polarization :	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	56.75	-12.78	43.97	74.00	-30.03	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	DC 3.7V
Test Mode :	TX /2480MHz-3Mbps	Polarization :	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	
2483.500	51.79	-12.78	39.01	74.00	-34.99	peak

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.



4. NUMBER OF HOPPING CHANNEL

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥ 15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	$RBW \geq 1\%$ of the span
VB	$VBW \geq RBW$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


4.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : $RBW = 1\text{MHz}$, $VBW = 3\text{MHz}$, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP




4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	DC 3.7V
Test Mode :	Hopping Mode		

Number of Hopping Channel	79
---------------------------	----



5. AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyzer
- Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- Use a video trigger with the trigger level set to enable triggering only on full pulses.
- Sweep Time is more than once pulse time.
- Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- Measure the maximum time duration of one single pulse.
- Set the EUT for DH5, DH3 and DH1 packet transmitting.
- Measure the maximum time duration of one single pulse.
- A Period Time = (channel number)*0.4
 DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)
 DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)
 DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS


EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH5 ,2DH5,3DH5		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441	2.95	0.315	0.4
2DH1	2441	2.95	0.315	0.4
3DH1	2441	2.97	0.317	0.4


CH39-DH5



CH39-2DH5




CH39-3DH5




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH3,2DH3,3DH3		


Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441	1.725	0.276	0.4
2DH1	2441	1.7	0.272	0.4
3DH1	2441	1.712	0.274	0.4



CH39-2DH3




CH39-3DH3




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH39-DH1,2DH1,3DH1		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441	0.4875	0.156	0.4
2DH1	2441	0.45	0.144	0.4
3DH1	2441	0.4625	0.148	


CH39-DH1



CH39-2DH1



CH39-3DH1



6. HOPPING CHANNEL SEPARATION MEASUREMENT

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	wide enough to capture the peaks of two adjacent channels
RB	$\geq 1\%$ of the span
VB	$\geq$ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


6.1.1 TEST PROCEDURE

- The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- The resolution bandwidth of 30 kHz and the video bandwidth of 30 kHz were utilised for channel separation measurement.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT was programmed to be in continuously transmitting mode.

6.1.5 TEST RESULTS


EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation(MHz)	Limit (MHz)	Result
2402 MHz	1.005	796.195	PASS
2441 MHz	1.005	734.692	PASS
2480 MHz	1.005	801.635	PASS


Ch. Separation Limits: >20dB bandwidth



CH39 -1Mbps




CH78 -1Mbps




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (2Mbps Mode)		

Frequency	Ch. Separation (MHz)	Limit (MHz)	Result
2402 MHz	1.005	1.152*2/3	PASS
2441 MHz	1.005	1.157*2/3	PASS
2480 MHz	1.005	1.149*2/3	PASS


Ch. Separation Limits: >2/3 of 20dB bandwidth



CH39 -2Mbps




CH78 -2Mbps




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	LIMIT (MHz)	Result
2402 MHz	1.005	1.164*2/3	PASS
2441 MHz	0.998	1.167*2/3	PASS
2480 MHz	1.005	1.161*2/3	PASS


Ch. Separation Limits: >2/3 of 20dB bandwidth



CH39 -3Mbps



CH78 -3Mbps



7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	30 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


7.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting : RBW= 30KHz, VBW=100KHz, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP




7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


7.1.5 TEST RESULTS

EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(1Mbps)		


Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	796.195	PASS
2441 MHz	734.692	PASS
2480 MHz	801.635	PASS



CH39 -1Mbps




CH78 -1Mbps




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(2Mbps)		


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.152	PASS
2441 MHz	1.157	PASS
2480 MHz	1.149	PASS



CH39 -2Mbps




CH78 -2Mbps




EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00 / CH39 /C78(3Mbps)		


Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.164	PASS
2441 MHz	1.167	PASS
2480 MHz	1.161	PASS



CH39 -3Mbps



CH78 -3Mbps



8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	30dbm or 20.96dBm	2400-2483.5	PASS

8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured
 - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
 - VBW $\geq$ RBW
 - Sweep = auto
 - Detector function = peak
 - Trace = max hold

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP




8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


8.1.5 TEST RESULTS

EUT :	LI-ION Battery Charger/W Bluetooth Speaker	Model Name :	LI7000
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 3.7V
Test Mode :	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		


1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	3.129	30
CH39	2441	3.597	30
CH78	2480	3.628	30
2Mbps			
CH00	2402	2.653	20.96
CH39	2441	3.090	20.96
CH78	2480	2.787	20.96
3Mbps			
CH00	2402	2.661	20.96
CH39	2441	3.191	20.96
CH78	2480	2.997	20.96




CH39 -1Mbps




CH78 -1Mbps







CH39 -2Mbps




CH78 -2Mbps






CH39 -3Mbps



CH78 -3Mbps



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is Integrated (PCB) antenna. It comply with the standard requirement.

10. EUT TEST PHOTO

Radiated Measurement Photos



CONDUCTED EMISSION Photos

