



FCC RF Test Report

APPLICANT : LugTrack, LLC.
EQUIPMENT : GLOBAL LOCATOR
BRAND NAME : TUMI
MODEL NAME : 014341D
MARKETING NAME : TUMI Global Locator
FCC ID : 2AFPZ-TGL001
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)
CLASSIFICATION : PCS Licensed Transmitter (PCB)

The product was received on Aug. 24, 2015 and testing was completed on Dec. 21, 2015. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Andy Yeh / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (SHENZHEN) INC.

**1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,
Nanshan District, Shenzhen, Guangdong, P. R. China**



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	6
1.1 Applicant.....	6
1.2 Manufacturer	6
1.3 Product Feature of Equipment Under Test	6
1.4 Product Specification of Equipment Under Test	7
1.5 Modification of EUT	7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	8
1.7 Testing Location	8
1.8 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode.....	10
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration	11
2.4 Measurement Results Explanation Example	12
3 CONDUCTED TEST RESULT.....	13
3.1 Measuring Instruments.....	13
3.2 Test Setup	13
3.3 Test Result of Conducted Test.....	13
3.4 Conducted Output Power	14
3.5 Peak-to-Average Ratio	14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	15
3.7 Conducted Band Edge	16
3.8 Conducted Spurious Emission	17
3.9 Frequency Stability	18
4 RADIATED TEST ITEMS	19
4.1 Measuring Instruments.....	19
4.2 Test Setup	19
4.3 Test Result of Radiated Test.....	19
4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement	20
4.5 Field Strength of Spurious Radiation Measurement	22
5 LIST OF MEASURING EQUIPMENT	23
6 UNCERTAINTY OF EVALUATION	24
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG582403	Rev. 01	Initial issue of report	Mar. 15, 2016



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.4	§2.1046	RSS-132 (5.4) RSS-133 (6.4)	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	RSS-132 (5.4) RSS-133 (6.4)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	RSS-GEN(6.6) RSS-132(3.1) RSS-133(3.1)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	RSS-GEN(6.11) RSS-132 (5.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235	RSS-GEN(6.11) RSS-133 (6.3)		Within Authorized Band		



Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
4.4	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
4.5	§2.1053 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 3.94 dB at 2546.400 MHz



1 General Description

1.1 Applicant

LugTrack, LLC.

225 US Highway 35, Suite #201, Red Bank, New Jersey, 07701 USA

1.2 Manufacturer

LugTrack, LLC.

225 US Highway 35, Suite #201, Red Bank, New Jersey, 07701 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GLOBAL LOCATOR
Brand Name	TUMI
Model Name	014341D
Marketing Name	TUMI Global Locator
FCC ID	2AFPZ-TGL001
EUT supports Radios application	GPRS/EGPRS/WCDMA/HSPA/ HSPA+(16QAM uplink is not supported)/ WLAN2.4GHz 802.11b/g/n HT20/HT40/ Bluetooth v2.1+EDR/Bluetooth v4.0 LE
IMEI Code	Conducted:35258207050922 Radiation: 352582070509246
HW Version	LGT-001-V1
SW Version	MOLY.WR8.W1315.MD.WG.MP.V35.P4
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz
Rx Frequency	GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz
Maximum Output Power to Antenna	GPRS/EDGE: 850: 33.10 dBm 1900: 30.31 dBm WCDMA: Band V: 22.78 dBm Band II: 23.12 dBm
Antenna Type	PIFA Antenna
Type of Modulation	GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : QPSK (Uplink) HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (16QAM uplink is not supported)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22H	GSM850 GPRS class 8	GMSK	0.6761	0.0108 ppm	248KGXW
Part 22H	GSM850 EDGE class 8	8PSK	0.1462	0.0395 ppm	248KG7W
Part 22H	WCDMA Band V RMC 12.2Kbps	QPSK	0.0541	0.0110 ppm	4M16F9W
Part 24E	GSM1900 GPRS class 8	GMSK	0.9162	0.0167 ppm	248KGXW
Part 24E	GSM1900 EDGE class 8	8PSK	0.3443	0.0239 ppm	255KG7W
Part 24E	WCDMA Band II RMC 12.2Kbps	QPSK	0.1466	0.0160 ppm	4M17F9W

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755-8637-9589 FAX: +86-755-8637-9595	
Test Site No.	Sporton Site No.	
	TH01-SZ	

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.	
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China TEL: +86-755- 3320-2398	
Test Site No.	Sporton Site No.	FCC/IC Registration No.
	03CH01-SZ	831040/4086F

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- ♦ IC RSS-132 Issue 3
- ♦ IC RSS-133 Issue 6
- ♦ IC RSS-Gen Issue 4
- ♦

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	■ GPRS class 8 Link ■ EDGE class 8 Link	■ GPRS class 8 Link ■ EDGE class 8 Link
GSM 1900	■ GPRS class 8 Link ■ EDGE class 8 Link	■ GPRS class 8 Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.5 + 10 = 14.5 \text{ (dB)}\end{aligned}$$


3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-D-2010 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

4.5 Field Strength of Spurious Radiation Measurement

4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)] \text{ (dB)}$
 $= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$
 $= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Jan. 28, 2015	Dec. 09, 2015~ Dec. 21, 2015	Jan. 27, 2016	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Aug. 07, 2015	Dec. 09, 2015~ Dec. 21, 2015	Aug. 06, 2016	Conducted (TH01-SZ)
Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz;Max 30dBm	Jun. 07, 2015	Dec. 17, 2015	Jun. 06, 2016	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Oct. 17, 2015	Dec. 17, 2015	Oct. 16, 2016	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1285	1GHz~18GHz	Jan. 20, 2015	Dec. 17, 2015	Jan. 19, 2016	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Aug.19, 2015	Dec. 17, 2015	Aug. 18, 2016	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz ~3000MHz / 30 dB	Jan. 28, 2015	Dec. 17, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 28, 2015	Dec. 17, 2015	Jan. 27, 2016	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	May 05, 2015	Dec. 17, 2015	May 04, 2016	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	NCR	Dec. 17, 2015	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Dec. 17, 2015	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Dec. 17, 2015	NCR	Radiation (03CH01-SZ)



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	--------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

SIM 1:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	33.04	32.96	33.10	30.28	30.13	30.31
GPRS class 10	31.72	31.70	31.89	29.02	28.98	29.20
GPRS class 11	29.10	29.20	29.37	26.46	26.53	26.88
GPRS class 12	27.83	27.94	28.06	25.22	25.30	25.67
EGPRS class 8	25.93	25.89	26.10	24.73	24.76	25.10
EGPRS class 10	24.91	24.98	25.10	23.66	23.88	24.15
EGPRS class 11	22.77	22.90	23.03	21.56	21.85	22.95
EGPRS class 12	21.50	21.65	21.74	20.32	20.50	20.65

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2K	22.71	22.73	22.78	23.12	22.98	22.90
HSDPA Subtest-1	21.39	21.62	21.59	21.82	21.80	21.63
HSDPA Subtest-2	21.42	21.65	21.60	21.83	21.80	21.62
HSDPA Subtest-3	20.97	21.19	21.11	21.34	21.34	21.17
HSDPA Subtest-4	20.94	21.15	20.40	21.33	21.33	21.13
HSUPA Subtest-1	19.51	19.64	19.64	19.88	19.86	19.76
HSUPA Subtest-2	19.49	19.67	19.62	19.85	19.85	19.69
HSUPA Subtest-3	20.49	20.60	20.62	20.84	20.82	20.67
HSUPA Subtest-4	18.93	19.13	19.10	19.32	19.34	19.16
HSUPA Subtest-5	21.50	21.60	21.60	21.90	21.80	21.70



SIM 2:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GPRS class 8	33.03	32.95	33.07	30.20	30.10	30.30
GPRS class 10	31.70	31.69	31.88	28.93	28.88	29.18
GPRS class 11	29.08	29.18	29.35	26.41	26.42	26.86
GPRS class 12	27.81	27.85	27.99	25.15	25.25	25.55
EGPRS class 8	25.85	25.90	25.99	24.72	24.75	25.03
EGPRS class 10	24.78	24.96	25.06	23.64	23.84	24.10
EGPRS class 11	22.68	22.80	22.92	21.54	21.80	22.93
EGPRS class 12	21.35	21.58	21.65	20.30	20.48	20.60

Conducted Power (*Unit: dBm)						
Band	WCDMA Band V			WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
RMC 12.2K	22.61	22.63	22.67	23.03	22.82	22.60
HSDPA Subtest-1	21.41	21.66	21.55	21.84	21.75	21.57
HSDPA Subtest-2	21.46	21.67	21.56	21.82	21.75	21.61
HSDPA Subtest-3	20.99	21.22	21.12	21.38	21.27	21.11
HSDPA Subtest-4	20.97	21.17	21.10	21.36	21.28	21.08
HSUPA Subtest-1	19.52	19.65	19.59	19.84	19.83	19.75
HSUPA Subtest-2	19.50	19.65	19.60	19.86	19.80	19.65
HSUPA Subtest-3	20.47	20.63	20.61	20.83	20.72	20.62
HSUPA Subtest-4	18.94	19.11	19.09	19.30	19.24	19.14
HSUPA Subtest-5	21.50	21.60	21.60	21.80	21.70	21.50



A1. GSM

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.20	2.84	PASS
Middle CH	0.20	2.76	
Highest CH	0.24	2.88	

Mode	GSM1900		Limit: 13dB
Mod.	GPRS class 8	EDGE class 8	Result
Lowest CH	0.24	2.80	PASS
Middle CH	0.24	2.80	
Highest CH	0.24	2.72	



GSM850 (GPRS class 8)		GSM850 (EDGE class 8)	
Lowest Channel		Lowest Channel	
Ref: 34.5 dBm Att: 30 dB AQT: 3.125 ms Center: 824.2 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 33.14 dBm Peak: 33.34 dBm Crest: 0.20 dB 10 %: 0.16 dB 1 %: 0.20 dB .1 %: 0.20 dB .01 %: 0.20 dB Date: 9.DEC.2015 10:08:34		Ref: 34.5 dBm Att: 30 dB AQT: 3.125 ms Center: 824.2 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 24.41 dBm Peak: 27.34 dBm Crest: 2.93 dB 10 %: 2.28 dB 1 %: 2.76 dB .1 %: 2.84 dB .01 %: 2.88 dB Date: 21.DEC.2015 21:01:04	
Middle Channel		Middle Channel	
Ref: 34.5 dBm Att: 30 dB AQT: 3.125 ms Center: 835.4 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 33.11 dBm Peak: 33.27 dBm Crest: 0.16 dB 10 %: 0.16 dB 1 %: 0.20 dB .1 %: 0.20 dB .01 %: 0.20 dB Date: 9.DEC.2015 10:08:54		Ref: 34.5 dBm Att: 30 dB AQT: 3.125 ms Center: 835.4 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 24.54 dBm Peak: 27.34 dBm Crest: 2.80 dB 10 %: 2.28 dB 1 %: 2.68 dB .1 %: 2.76 dB .01 %: 2.80 dB Date: 21.DEC.2015 21:01:30	
Highest Channel		Highest Channel	
Ref: 34.5 dBm Att: 30 dB AQT: 3.125 ms Center: 848.8 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 33.14 dBm Peak: 33.34 dBm Crest: 0.20 dB 10 %: 0.16 dB 1 %: 0.20 dB .1 %: 0.24 dB .01 %: 0.24 dB Date: 9.DEC.2015 10:09:13		Ref: 34.5 dBm Att: 30 dB AQT: 3.125 ms Center: 848.8 MHz Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean: 24.49 dBm Peak: 27.41 dBm Crest: 2.92 dB 10 %: 2.32 dB 1 %: 2.80 dB .1 %: 2.88 dB .01 %: 2.92 dB Date: 21.DEC.2015 21:02:03	





GSM1900 (GPRS class 8)		GSM1900 (EDGE class 8)	
Lowest Channel		Lowest Channel	

**26dB Bandwidth**

Mode	GSM850	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.315	0.273
Middle CH	0.316	0.292
Highest CH	0.286	0.268

Mode	GSM1900	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.309	0.290
Middle CH	0.301	0.291
Highest CH	0.313	0.290







**Occupied Bandwidth**

Mode	GSM850	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.245	0.243
Middle CH	0.248	0.248
Highest CH	0.239	0.247

Mode	GSM1900	
Mod.	GPRS class 8	EDGE class 8
Lowest CH	0.248	0.252
Middle CH	0.243	0.255
Highest CH	0.245	0.250








Conducted Band Edge


GSM850 (GPRS class 8)

Lowest Band Edge



Date: 9.DEC.2015 09:52:29


Highest Band Edge



Date: 9.DEC.2015 09:54:13


GSM850 (EDGE class 8)

Lowest Band Edge



Date: 21.DEC.2015 21:07:51

Highest Band Edge




Date: 21.DEC.2015 21:09:37




GSM1900 (GPRS class 8)

Lowest Band Edge



Date: 9.DEC.2015 10:24:35


Highest Band Edge



Date: 9.DEC.2015 10:26:09


GSM1900 (EDGE class 8)

Lowest Band Edge



Date: 21.DEC.2015 20:49:49







Highest Band Edge




Date: 21.DEC.2015 20:51:31



Conducted Spurious Emission

GSM850 (GPRS class 8)		GSM850 (EDGE class 8)																																																																																					
Lowest Channel		Lowest Channel																																																																																					
 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>801.435000 M</td><td>-44.86</td><td>-31.86</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>866.678751 M</td><td>-44.14</td><td>-31.14</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>2.9805000 G</td><td>-42.79</td><td>-29.79</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.0130000 G</td><td>-37.93</td><td>-24.93</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.4785000 G</td><td>-36.39</td><td>-23.39</td></tr></table> Date: 9.DEC.2015 09:57:07		Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	801.435000 M	-44.86	-31.86	850.000 M	1.000 G	1.00 M	866.678751 M	-44.14	-31.14	1.000 G	3.000 G	1.00 M	2.9805000 G	-42.79	-29.79	3.000 G	7.000 G	1.00 M	3.0130000 G	-37.93	-24.93	7.000 G	9.000 G	1.00 M	8.4785000 G	-36.39	-23.39	 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>394.385000 M</td><td>-44.70</td><td>-31.70</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>866.926251 M</td><td>-44.06</td><td>-31.06</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>2.9965000 G</td><td>-42.54</td><td>-29.54</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.0330000 G</td><td>-37.70</td><td>-24.70</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.4700000 G</td><td>-37.01</td><td>-24.01</td></tr></table> Date: 21.DEC.2015 21:11:19		Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	394.385000 M	-44.70	-31.70	850.000 M	1.000 G	1.00 M	866.926251 M	-44.06	-31.06	1.000 G	3.000 G	1.00 M	2.9965000 G	-42.54	-29.54	3.000 G	7.000 G	1.00 M	3.0330000 G	-37.70	-24.70	7.000 G	9.000 G	1.00 M	8.4700000 G	-37.01	-24.01
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	801.435000 M	-44.86	-31.86																																																																																		
850.000 M	1.000 G	1.00 M	866.678751 M	-44.14	-31.14																																																																																		
1.000 G	3.000 G	1.00 M	2.9805000 G	-42.79	-29.79																																																																																		
3.000 G	7.000 G	1.00 M	3.0130000 G	-37.93	-24.93																																																																																		
7.000 G	9.000 G	1.00 M	8.4785000 G	-36.39	-23.39																																																																																		
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	394.385000 M	-44.70	-31.70																																																																																		
850.000 M	1.000 G	1.00 M	866.926251 M	-44.06	-31.06																																																																																		
1.000 G	3.000 G	1.00 M	2.9965000 G	-42.54	-29.54																																																																																		
3.000 G	7.000 G	1.00 M	3.0330000 G	-37.70	-24.70																																																																																		
7.000 G	9.000 G	1.00 M	8.4700000 G	-37.01	-24.01																																																																																		
Middle Channel		Middle Channel																																																																																					
 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>554.757500 M</td><td>-44.14</td><td>-31.14</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>974.616250 M</td><td>-44.39</td><td>-31.39</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>2.9920000 G</td><td>-42.45</td><td>-29.45</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.0100000 G</td><td>-37.60</td><td>-24.60</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>7.9030000 G</td><td>-36.17</td><td>-23.17</td></tr></table> Date: 9.DEC.2015 09:58:47		Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	554.757500 M	-44.14	-31.14	850.000 M	1.000 G	1.00 M	974.616250 M	-44.39	-31.39	1.000 G	3.000 G	1.00 M	2.9920000 G	-42.45	-29.45	3.000 G	7.000 G	1.00 M	3.0100000 G	-37.60	-24.60	7.000 G	9.000 G	1.00 M	7.9030000 G	-36.17	-23.17	 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>522.170000 M</td><td>-44.75</td><td>-31.75</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>868.521251 M</td><td>-44.02</td><td>-31.02</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>2.9925000 G</td><td>-42.45</td><td>-29.45</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.0030000 G</td><td>-37.39</td><td>-24.39</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>7.4890000 G</td><td>-36.42</td><td>-23.42</td></tr></table> Date: 21.DEC.2015 21:12:17		Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	522.170000 M	-44.75	-31.75	850.000 M	1.000 G	1.00 M	868.521251 M	-44.02	-31.02	1.000 G	3.000 G	1.00 M	2.9925000 G	-42.45	-29.45	3.000 G	7.000 G	1.00 M	3.0030000 G	-37.39	-24.39	7.000 G	9.000 G	1.00 M	7.4890000 G	-36.42	-23.42
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	554.757500 M	-44.14	-31.14																																																																																		
850.000 M	1.000 G	1.00 M	974.616250 M	-44.39	-31.39																																																																																		
1.000 G	3.000 G	1.00 M	2.9920000 G	-42.45	-29.45																																																																																		
3.000 G	7.000 G	1.00 M	3.0100000 G	-37.60	-24.60																																																																																		
7.000 G	9.000 G	1.00 M	7.9030000 G	-36.17	-23.17																																																																																		
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	522.170000 M	-44.75	-31.75																																																																																		
850.000 M	1.000 G	1.00 M	868.521251 M	-44.02	-31.02																																																																																		
1.000 G	3.000 G	1.00 M	2.9925000 G	-42.45	-29.45																																																																																		
3.000 G	7.000 G	1.00 M	3.0030000 G	-37.39	-24.39																																																																																		
7.000 G	9.000 G	1.00 M	7.4890000 G	-36.42	-23.42																																																																																		
Highest Channel		Highest Channel																																																																																					
 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>406.412500 M</td><td>-44.45</td><td>-31.45</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>997.245010 M</td><td>-44.04</td><td>-31.04</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>1.6975000 G</td><td>-43.79</td><td>-28.79</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.0330000 G</td><td>-37.07</td><td>-24.07</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>7.2705000 G</td><td>-36.80</td><td>-23.80</td></tr></table> Date: 9.DEC.2015 10:00:11		Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	406.412500 M	-44.45	-31.45	850.000 M	1.000 G	1.00 M	997.245010 M	-44.04	-31.04	1.000 G	3.000 G	1.00 M	1.6975000 G	-43.79	-28.79	3.000 G	7.000 G	1.00 M	3.0330000 G	-37.07	-24.07	7.000 G	9.000 G	1.00 M	7.2705000 G	-36.80	-23.80	 <table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbs</th><th>Δ Limit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30.000 M</td><td>820.000 M</td><td>1.00 M</td><td>769.045000 M</td><td>-45.05</td><td>-32.05</td></tr><tr><td>850.000 M</td><td>1.000 G</td><td>1.00 M</td><td>857.682500 M</td><td>-44.32</td><td>-31.32</td></tr><tr><td>1.000 G</td><td>3.000 G</td><td>1.00 M</td><td>2.9950000 G</td><td>-43.70</td><td>-28.70</td></tr><tr><td>3.000 G</td><td>7.000 G</td><td>1.00 M</td><td>3.5190000 G</td><td>-37.03</td><td>-24.03</td></tr><tr><td>7.000 G</td><td>9.000 G</td><td>1.00 M</td><td>8.4410000 G</td><td>-37.00</td><td>-24.00</td></tr></table> Date: 21.DEC.2015 21:13:22		Start	Stop	RBW	Freq	PerAbs	Δ Limit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30.000 M	820.000 M	1.00 M	769.045000 M	-45.05	-32.05	850.000 M	1.000 G	1.00 M	857.682500 M	-44.32	-31.32	1.000 G	3.000 G	1.00 M	2.9950000 G	-43.70	-28.70	3.000 G	7.000 G	1.00 M	3.5190000 G	-37.03	-24.03	7.000 G	9.000 G	1.00 M	8.4410000 G	-37.00	-24.00
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	406.412500 M	-44.45	-31.45																																																																																		
850.000 M	1.000 G	1.00 M	997.245010 M	-44.04	-31.04																																																																																		
1.000 G	3.000 G	1.00 M	1.6975000 G	-43.79	-28.79																																																																																		
3.000 G	7.000 G	1.00 M	3.0330000 G	-37.07	-24.07																																																																																		
7.000 G	9.000 G	1.00 M	7.2705000 G	-36.80	-23.80																																																																																		
Start	Stop	RBW	Freq	PerAbs	Δ Limit																																																																																		
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																		
30.000 M	820.000 M	1.00 M	769.045000 M	-45.05	-32.05																																																																																		
850.000 M	1.000 G	1.00 M	857.682500 M	-44.32	-31.32																																																																																		
1.000 G	3.000 G	1.00 M	2.9950000 G	-43.70	-28.70																																																																																		
3.000 G	7.000 G	1.00 M	3.5190000 G	-37.03	-24.03																																																																																		
7.000 G	9.000 G	1.00 M	8.4410000 G	-37.00	-24.00																																																																																		



**Frequency Stability**

Test Conditions	Middle Channel	GSM850 (GPRS class 8)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0036	0.0084	PASS
40	Normal Voltage	0.0012	0.0395	
30	Normal Voltage	0.0024	0.0024	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0012	0.0012	
0	Normal Voltage	0.0036	0.0395	
-10	Normal Voltage	0.0060	0.0024	
-20	Normal Voltage	0.0084	0.0060	
-30	Normal Voltage	0.0108	0.0072	
20	Maximum Voltage	0.0012	0.0012	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0012	0.0024	

Note: Normal Voltage = 3.7 V. ; Battery End Point (BEP) = 3.4 V. ; Maximum Voltage = 4.2 V



Test Conditions	Middle Channel	GSM1900 (GPRS class 8)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0084	0.0032	PASS
40	Normal Voltage	0.0060	0.0234	
30	Normal Voltage	0.0036	0.0005	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0036	0.0011	
0	Normal Voltage	0.0072	0.0021	
-10	Normal Voltage	0.0108	0.0239	
-20	Normal Voltage	0.0132	0.0011	
-30	Normal Voltage	0.0167	0.0037	
20	Maximum Voltage	0.0012	0.0011	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0012	0.0021	

Note:

1. Normal Voltage = 3.7 V. ; Battery End Point (BEP) = 3.4 V. ; Maximum Voltage =4.2 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.









A2. WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.44	2.80	PASS
Middle CH	3.24	2.76	
Highest CH	3.04	2.68	



WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	Lowest Channel
 Center 826.4 MHz Ref 30 dBm Att 30 dB AQT 3.125 ms Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.60 dBm Peak 26.37 dBm Crest 3.77 dB 10 % 1.88 dB 1 % 2.88 dB .1 % 3.44 dB .01 % 3.64 dB Date: 9.DEC.2015 11:34:43	 Center 1.8524 GHz Ref 30 dBm Att 30 dB AQT 3.125 ms Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.87 dBm Peak 26.09 dBm Crest 3.22 dB 10 % 1.64 dB 1 % 2.40 dB .1 % 2.80 dB .01 % 3.00 dB Date: 9.DEC.2015 11:10:04
Middle Channel	Middle Channel
 Center 830.4 MHz Ref 30 dBm Att 30 dB AQT 3.125 ms Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.46 dBm Peak 26.02 dBm Crest 3.56 dB 10 % 1.84 dB 1 % 2.76 dB .1 % 3.24 dB .01 % 3.44 dB Date: 9.DEC.2015 11:34:59	 Center 1.88 GHz Ref 30 dBm Att 30 dB AQT 3.125 ms Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.61 dBm Peak 25.67 dBm Crest 3.06 dB 10 % 1.68 dB 1 % 2.36 dB .1 % 2.76 dB .01 % 2.92 dB Date: 9.DEC.2015 11:10:24
Highest Channel	Highest Channel
 Center 846.6 MHz Ref 30 dBm Att 30 dB AQT 3.125 ms Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.54 dBm Peak 25.95 dBm Crest 3.41 dB 10 % 1.76 dB 1 % 2.64 dB .1 % 3.04 dB .01 % 3.20 dB Date: 9.DEC.2015 11:35:47	 Center 1.9076 GHz Ref 30 dBm Att 30 dB AQT 3.125 ms Complementary Cumulative Distribution Function (100000 samples) Trace 1 Mean 22.25 dBm Peak 25.24 dBm Crest 3.00 dB 10 % 1.64 dB 1 % 2.36 dB .1 % 2.68 dB .01 % 2.84 dB Date: 9.DEC.2015 11:10:41


**26dB Bandwidth**

Mode	WCDMA Band V	WCDMA Band II
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.66	4.68
Middle CH	4.68	4.71
Highest CH	4.67	4.71



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 9.DEC.2015 11:12:31


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 9.DEC.2015 10:50:43

Middle Channel




Date: 9.DEC.2015 11:13:10

Middle Channel




Date: 9.DEC.2015 10:52:12

Highest Channel



Date: 9.DEC.2015 11:13:46


Highest Channel




Date: 9.DEC.2015 10:52:51


**Occupied Bandwidth**

Mode	WCDMA Band V	WCDMA Band II
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.15	4.16
Middle CH	4.16	4.16
Highest CH	4.15	4.17



**Conducted Band Edge****WCDMA Band V (RMC 12.2Kbps)****Lowest Band Edge**

Date: 9.DEC.2015 11:21:09


Highest Band Edge

Date: 9.DEC.2015 11:25:14




WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge



Date: 9.DEC.2015 10:58:50







Highest Band Edge



Date: 9.DEC.2015 11:01:46



Conducted Spurious Emission

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)																																																																																										
Lowest Channel	Lowest Channel																																																																																										
<table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbn</th><th>ΔLimit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30,000 M</td><td>820,000 M</td><td>1,000 M</td><td>605,910000 M</td><td>-45.49</td><td>-32.49</td></tr><tr><td>855,000 M</td><td>1,000 G</td><td>1,000 M</td><td>881,136250 M</td><td>-44.91</td><td>-31.91</td></tr><tr><td>1,000 G</td><td>3,000 G</td><td>1,000 M</td><td>2,924500 G</td><td>-42.48</td><td>-29.48</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,046000 G</td><td>-37.90</td><td>-24.90</td></tr><tr><td>7,000 G</td><td>9,000 G</td><td>1,000 M</td><td>8,717000 G</td><td>-36.77</td><td>-23.77</td></tr></table> Date: 9.DEC.2015 11:29:24	Start	Stop	RBW	Freq	PerAbn	ΔLimit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	820,000 M	1,000 M	605,910000 M	-45.49	-32.49	855,000 M	1,000 G	1,000 M	881,136250 M	-44.91	-31.91	1,000 G	3,000 G	1,000 M	2,924500 G	-42.48	-29.48	3,000 G	7,000 G	1,000 M	3,046000 G	-37.90	-24.90	7,000 G	9,000 G	1,000 M	8,717000 G	-36.77	-23.77	<table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbn</th><th>ΔLimit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30,000 M</td><td>1,000 G</td><td>1,000 M</td><td>639,160000 M</td><td>-44.78</td><td>-31.78</td></tr><tr><td>1,000 G</td><td>1,845 G</td><td>1,000 M</td><td>1,664170 G</td><td>-43.98</td><td>-30.98</td></tr><tr><td>1,915 G</td><td>3,000 G</td><td>1,000 M</td><td>2,992296 G</td><td>-41.81</td><td>-28.81</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,032000 G</td><td>-37.30</td><td>-24.30</td></tr><tr><td>7,000 G</td><td>13,600 G</td><td>1,000 M</td><td>12,354250 G</td><td>-35.04</td><td>-22.04</td></tr><tr><td>13,600 G</td><td>19,100 G</td><td>1,000 M</td><td>13,660500 G</td><td>-23.69</td><td>-10.69</td></tr></table> Date: 9.DEC.2015 11:04:16	Start	Stop	RBW	Freq	PerAbn	ΔLimit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	1,000 G	1,000 M	639,160000 M	-44.78	-31.78	1,000 G	1,845 G	1,000 M	1,664170 G	-43.98	-30.98	1,915 G	3,000 G	1,000 M	2,992296 G	-41.81	-28.81	3,000 G	7,000 G	1,000 M	3,032000 G	-37.30	-24.30	7,000 G	13,600 G	1,000 M	12,354250 G	-35.04	-22.04	13,600 G	19,100 G	1,000 M	13,660500 G	-23.69	-10.69
Start	Stop	RBW	Freq	PerAbn	ΔLimit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	820,000 M	1,000 M	605,910000 M	-45.49	-32.49																																																																																						
855,000 M	1,000 G	1,000 M	881,136250 M	-44.91	-31.91																																																																																						
1,000 G	3,000 G	1,000 M	2,924500 G	-42.48	-29.48																																																																																						
3,000 G	7,000 G	1,000 M	3,046000 G	-37.90	-24.90																																																																																						
7,000 G	9,000 G	1,000 M	8,717000 G	-36.77	-23.77																																																																																						
Start	Stop	RBW	Freq	PerAbn	ΔLimit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	1,000 G	1,000 M	639,160000 M	-44.78	-31.78																																																																																						
1,000 G	1,845 G	1,000 M	1,664170 G	-43.98	-30.98																																																																																						
1,915 G	3,000 G	1,000 M	2,992296 G	-41.81	-28.81																																																																																						
3,000 G	7,000 G	1,000 M	3,032000 G	-37.30	-24.30																																																																																						
7,000 G	13,600 G	1,000 M	12,354250 G	-35.04	-22.04																																																																																						
13,600 G	19,100 G	1,000 M	13,660500 G	-23.69	-10.69																																																																																						
Middle Channel	Middle Channel																																																																																										
<table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbn</th><th>ΔLimit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30,000 M</td><td>820,000 M</td><td>1,000 M</td><td>447,317500 M</td><td>-45.28</td><td>-32.28</td></tr><tr><td>855,000 M</td><td>1,000 G</td><td>1,000 M</td><td>864,932500 M</td><td>-44.45</td><td>-31.45</td></tr><tr><td>1,000 G</td><td>3,000 G</td><td>1,000 M</td><td>2,948500 G</td><td>-43.55</td><td>-30.55</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,063000 G</td><td>-37.65</td><td>-24.65</td></tr><tr><td>7,000 G</td><td>9,000 G</td><td>1,000 M</td><td>7,978500 G</td><td>-36.79</td><td>-23.79</td></tr></table> Date: 9.DEC.2015 11:30:46	Start	Stop	RBW	Freq	PerAbn	ΔLimit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	820,000 M	1,000 M	447,317500 M	-45.28	-32.28	855,000 M	1,000 G	1,000 M	864,932500 M	-44.45	-31.45	1,000 G	3,000 G	1,000 M	2,948500 G	-43.55	-30.55	3,000 G	7,000 G	1,000 M	3,063000 G	-37.65	-24.65	7,000 G	9,000 G	1,000 M	7,978500 G	-36.79	-23.79	<table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbn</th><th>ΔLimit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30,000 M</td><td>1,000 G</td><td>1,000 M</td><td>119,845000 M</td><td>-44.78</td><td>-31.78</td></tr><tr><td>1,000 G</td><td>1,845 G</td><td>1,000 M</td><td>1,132310 G</td><td>-43.15</td><td>-30.15</td></tr><tr><td>1,915 G</td><td>3,000 G</td><td>1,000 M</td><td>2,924321 G</td><td>-42.14</td><td>-29.14</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,003000 G</td><td>-36.39</td><td>-23.39</td></tr><tr><td>7,000 G</td><td>13,600 G</td><td>1,000 M</td><td>12,869500 G</td><td>-35.45</td><td>-22.45</td></tr><tr><td>13,600 G</td><td>19,100 G</td><td>1,000 M</td><td>13,633688 G</td><td>-23.54</td><td>-10.54</td></tr></table> Date: 9.DEC.2015 11:05:33	Start	Stop	RBW	Freq	PerAbn	ΔLimit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	1,000 G	1,000 M	119,845000 M	-44.78	-31.78	1,000 G	1,845 G	1,000 M	1,132310 G	-43.15	-30.15	1,915 G	3,000 G	1,000 M	2,924321 G	-42.14	-29.14	3,000 G	7,000 G	1,000 M	3,003000 G	-36.39	-23.39	7,000 G	13,600 G	1,000 M	12,869500 G	-35.45	-22.45	13,600 G	19,100 G	1,000 M	13,633688 G	-23.54	-10.54
Start	Stop	RBW	Freq	PerAbn	ΔLimit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	820,000 M	1,000 M	447,317500 M	-45.28	-32.28																																																																																						
855,000 M	1,000 G	1,000 M	864,932500 M	-44.45	-31.45																																																																																						
1,000 G	3,000 G	1,000 M	2,948500 G	-43.55	-30.55																																																																																						
3,000 G	7,000 G	1,000 M	3,063000 G	-37.65	-24.65																																																																																						
7,000 G	9,000 G	1,000 M	7,978500 G	-36.79	-23.79																																																																																						
Start	Stop	RBW	Freq	PerAbn	ΔLimit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	1,000 G	1,000 M	119,845000 M	-44.78	-31.78																																																																																						
1,000 G	1,845 G	1,000 M	1,132310 G	-43.15	-30.15																																																																																						
1,915 G	3,000 G	1,000 M	2,924321 G	-42.14	-29.14																																																																																						
3,000 G	7,000 G	1,000 M	3,003000 G	-36.39	-23.39																																																																																						
7,000 G	13,600 G	1,000 M	12,869500 G	-35.45	-22.45																																																																																						
13,600 G	19,100 G	1,000 M	13,633688 G	-23.54	-10.54																																																																																						
Highest Channel	Highest Channel																																																																																										
<table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbn</th><th>ΔLimit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30,000 M</td><td>820,000 M</td><td>1,000 M</td><td>784,035000 M</td><td>-45.49</td><td>-32.49</td></tr><tr><td>855,000 M</td><td>1,000 G</td><td>1,000 M</td><td>856,922350 M</td><td>-44.24</td><td>-31.24</td></tr><tr><td>1,000 G</td><td>3,000 G</td><td>1,000 M</td><td>2,994500 G</td><td>-43.36</td><td>-30.36</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,032000 G</td><td>-37.90</td><td>-24.90</td></tr><tr><td>7,000 G</td><td>9,000 G</td><td>1,000 M</td><td>8,736000 G</td><td>-36.57</td><td>-23.57</td></tr></table> Date: 9.DEC.2015 11:32:21	Start	Stop	RBW	Freq	PerAbn	ΔLimit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	820,000 M	1,000 M	784,035000 M	-45.49	-32.49	855,000 M	1,000 G	1,000 M	856,922350 M	-44.24	-31.24	1,000 G	3,000 G	1,000 M	2,994500 G	-43.36	-30.36	3,000 G	7,000 G	1,000 M	3,032000 G	-37.90	-24.90	7,000 G	9,000 G	1,000 M	8,736000 G	-36.57	-23.57	<table><tr><th>Start</th><th>Stop</th><th>RBW</th><th>Freq</th><th>PerAbn</th><th>ΔLimit</th></tr><tr><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[Hz]</th><th>[dBm]</th><th>[dB]</th></tr><tr><td>30,000 M</td><td>1,000 G</td><td>1,000 M</td><td>855,955000 M</td><td>-44.25</td><td>-31.25</td></tr><tr><td>1,000 G</td><td>1,845 G</td><td>1,000 M</td><td>1,210405 G</td><td>-43.96</td><td>-30.96</td></tr><tr><td>1,915 G</td><td>3,000 G</td><td>1,000 M</td><td>2,993334 G</td><td>-42.20</td><td>-29.20</td></tr><tr><td>3,000 G</td><td>7,000 G</td><td>1,000 M</td><td>3,044000 G</td><td>-37.24</td><td>-24.24</td></tr><tr><td>7,000 G</td><td>13,600 G</td><td>1,000 M</td><td>10,482325 G</td><td>-35.56</td><td>-22.56</td></tr><tr><td>13,600 G</td><td>19,100 G</td><td>1,000 M</td><td>13,622000 G</td><td>-23.89</td><td>-10.89</td></tr></table> Date: 9.DEC.2015 11:07:10	Start	Stop	RBW	Freq	PerAbn	ΔLimit	[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]	30,000 M	1,000 G	1,000 M	855,955000 M	-44.25	-31.25	1,000 G	1,845 G	1,000 M	1,210405 G	-43.96	-30.96	1,915 G	3,000 G	1,000 M	2,993334 G	-42.20	-29.20	3,000 G	7,000 G	1,000 M	3,044000 G	-37.24	-24.24	7,000 G	13,600 G	1,000 M	10,482325 G	-35.56	-22.56	13,600 G	19,100 G	1,000 M	13,622000 G	-23.89	-10.89
Start	Stop	RBW	Freq	PerAbn	ΔLimit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	820,000 M	1,000 M	784,035000 M	-45.49	-32.49																																																																																						
855,000 M	1,000 G	1,000 M	856,922350 M	-44.24	-31.24																																																																																						
1,000 G	3,000 G	1,000 M	2,994500 G	-43.36	-30.36																																																																																						
3,000 G	7,000 G	1,000 M	3,032000 G	-37.90	-24.90																																																																																						
7,000 G	9,000 G	1,000 M	8,736000 G	-36.57	-23.57																																																																																						
Start	Stop	RBW	Freq	PerAbn	ΔLimit																																																																																						
[Hz]	[Hz]	[Hz]	[Hz]	[dBm]	[dB]																																																																																						
30,000 M	1,000 G	1,000 M	855,955000 M	-44.25	-31.25																																																																																						
1,000 G	1,845 G	1,000 M	1,210405 G	-43.96	-30.96																																																																																						
1,915 G	3,000 G	1,000 M	2,993334 G	-42.20	-29.20																																																																																						
3,000 G	7,000 G	1,000 M	3,044000 G	-37.24	-24.24																																																																																						
7,000 G	13,600 G	1,000 M	10,482325 G	-35.56	-22.56																																																																																						
13,600 G	19,100 G	1,000 M	13,622000 G	-23.89	-10.89																																																																																						

**Frequency Stability**

Test Conditions Temperature (°C)	Middle Channel Voltage (Volt)	WCDMA Band V (RMC 12.2KbpsRMC 12.2Kbps)	Limit 2.5ppm
		Deviation (ppm)	Result
50	Normal Voltage	0.0110	PASS
40	Normal Voltage	0.0063	
30	Normal Voltage	0.0023	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0035	
0	Normal Voltage	0.0017	
-10	Normal Voltage	0.0017	
-20	Normal Voltage	0.0040	
-30	Normal Voltage	0.0104	
20	Maximum Voltage	0.0087	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0035	

Note: Normal Voltage = 3.7V. : Battery End Point (BEP) = 3.4 V. : Maximum Voltage =4.2V



Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0122	PASS
40	Normal Voltage	0.0074	
30	Normal Voltage	0.0016	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0043	
0	Normal Voltage	0.0074	
-10	Normal Voltage	0.0090	
-20	Normal Voltage	0.0117	
-30	Normal Voltage	0.0160	
20	Maximum Voltage	0.0021	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0064	

Note:

1. Normal Voltage = 3.7V. ; Battery End Point (BEP) = 3.4 V. ; Maximum Voltage =4.2V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Appendix B. Test Results of Radiated Test

ERP/EIRP

Channel	Mode	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	GSM850 GPRS class 8	27.88	0.6138	21.15	0.1303
Middle		28.25	0.6683	22.16	0.1644
Highest		28.30	0.6761	22.78	0.1897
Lowest	GSM850 EDGE class 8	20.69	0.1172	14.13	0.0259
Middle		21.01	0.1262	14.74	0.0298
Highest		21.65	0.1462	14.46	0.0279
Lowest	WCDMA Band V RMC 12.2Kbps	17.33	0.0541	11.63	0.0146
Middle		17.05	0.0507	10.04	0.0101
Highest		17.25	0.0531	10.93	0.0124
Limit	ERP < 7W	Result		PASS	



Channel	Mode	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900 GPRS class 8	28.47	0.7031	29.62	0.9162
Middle		27.59	0.5741	28.70	0.7413
Highest		26.79	0.4775	28.18	0.6577
Lowest	GSM1900 EDGE class 8	21.90	0.1549	25.16	0.3281
Middle		22.48	0.1770	24.83	0.3041
Highest		22.52	0.1786	25.37	0.3443
Lowest	WCDMA Band II RMC 12.2Kbps	19.44	0.0879	20.44	0.1107
Middle		20.05	0.1012	21.66	0.1466
Highest		17.84	0.0608	21.30	0.1349
Limit	EIRP < 2W	Result		PASS	

**Radiated Spurious Emission**

GSM850 (GPRS class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648.4	-23.23	-13	-10.23	-35.42	-29.91	0.57	9.40	H
	2472.6	-27.71	-13	-14.71	-45.11	-35.42	0.74	10.60	H
	3296.8	-44.61	-13	-31.61	-61.47	-54.21	0.85	12.60	H
	4120	-47.90	-13	-34.90	-65.79	-57.46	0.89	12.60	H
	4945	-44.61	-13	-31.61	-64.68	-54.22	0.94	12.70	H
	5770	-43.00	-13	-30.00	-64.85	-52.74	1.11	13.00	H
	6595	-48.15	-13	-35.15	-71.34	-56.48	1.22	11.70	H
	7420	-49.95	-13	-36.95	-74.41	-57.41	1.69	11.30	H
	1648.4	-26.52	-13	-13.52	-37.82	-33.20	0.57	9.40	V
	2472.6	-23.95	-13	-10.95	-41.52	-31.66	0.74	10.60	V
	3296.8	-44.26	-13	-31.26	-61.57	-53.86	0.85	12.60	V
	4120	-49.87	-13	-36.87	-67.35	-59.43	0.89	12.60	V
	4945	-42.70	-13	-29.70	-62.97	-52.31	0.94	12.70	V
	5770	-45.74	-13	-32.74	-65.97	-55.48	1.11	13.00	V
	6595	-49.07	-13	-36.07	-72.46	-57.40	1.22	11.70	V
	7420	-45.99	-13	-32.99	-70.17	-53.45	1.69	11.30	V
Middle	1672	-22.23	-13	-9.23	-34.37	-28.91	0.57	9.40	H
	2510	-25.85	-13	-12.85	-43.29	-33.56	0.74	10.60	H
	3346	-39.34	-13	-26.34	-57.99	-48.94	0.85	12.60	H
	4180	-46.72	-13	-33.72	-64.61	-56.28	0.89	12.60	H
	5020	-45.51	-13	-32.51	-65.58	-55.12	0.94	12.70	H
	5855	-43.75	-13	-30.75	-65.60	-53.49	1.11	13.00	H
	6690	-49.51	-13	-36.51	-72.70	-57.84	1.22	11.70	H
	7530	-48.17	-13	-35.17	-72.63	-55.63	1.69	11.30	H
	1672	-26.16	-13	-13.16	-37.52	-32.84	0.57	9.40	V
	2510	-19.08	-13	-6.08	-36.72	-26.79	0.74	10.60	V
	3346	-41.20	-13	-28.20	-59.28	-50.80	0.85	12.60	V
	4180	-47.73	-13	-34.73	-65.21	-57.29	0.89	12.60	V
	5020	-43.99	-13	-30.99	-64.09	-53.60	0.94	12.70	V
	5855	-46.09	-13	-33.09	-66.32	-55.83	1.11	13.00	V
	6690	-45.16	-13	-32.16	-68.55	-53.49	1.22	11.70	V
	7530	-47.26	-13	-34.26	-71.44	-54.72	1.69	11.30	V
Highest	1697.6	-22.34	-13	-9.34	-34.49	-29.02	0.57	9.40	H
	2546.4	-23.57	-13	-10.57	-41.06	-31.28	0.74	10.60	H
	3395.2	-41.29	-13	-28.29	-59.26	-50.89	0.85	12.60	H
	4245	-49.11	-13	-36.11	-67.00	-58.67	0.89	12.60	H
	5095	-44.58	-13	-31.58	-64.65	-54.19	0.94	12.70	H
	5940	-46.65	-13	-33.65	-68.50	-56.39	1.11	13.00	H
	6790	-48.66	-13	-35.66	-71.85	-56.99	1.22	11.70	H



	7640	-49.28	-13	-36.28	-73.74	-56.74	1.69	11.30	H
	1697.6	-25.31	-13	-12.31	-36.63	-31.99	0.57	9.40	V
	2546.4	-16.94	-13	-3.94	-34.61	-24.65	0.74	10.60	V
	3395.2	-41.76	-13	-28.76	-59.65	-51.36	0.85	12.60	V
	4245	-47.42	-13	-34.42	-64.90	-56.98	0.89	12.60	V
	5095	-47.07	-13	-34.07	-66.69	-56.68	0.94	12.70	V
	5940	-43.29	-13	-30.29	-63.52	-53.03	1.11	13.00	V
	6790	-50.06	-13	-37.06	-73.45	-58.39	1.22	11.70	V
	7640	-48.43	-13	-35.43	-72.61	-55.89	1.69	11.30	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648.4	-57.37	-13	-44.37	-64.94	-64.05	0.57	9.40	H
	2472.6	-31.22	-13	-18.22	-48.43	-38.93	0.74	10.60	H
	3296.8	-54.96	-13	-41.96	-70.56	-64.56	0.85	12.60	H
	1648.4	-58.02	-13	-45.02	-64.85	-64.70	0.57	9.40	V
	2472.6	-38.27	-13	-25.27	-54.77	-45.98	0.74	10.60	V
	3296.8	-56.14	-13	-43.14	-70.75	-65.74	0.85	12.60	V
Middle	1672	-61.22	-13	-48.22	-68.79	-67.90	0.57	9.40	H
	2510	-33.81	-13	-20.81	-50.78	-41.52	0.74	10.60	H
	3346	-55.67	-13	-42.67	-71.27	-65.27	0.85	12.60	H
	1672	-59.63	-13	-46.63	-66.46	-66.31	0.57	9.40	V
	2510	-37.17	-13	-24.17	-53.87	-44.88	0.74	10.60	V
	3346	-56.92	-13	-43.92	-71.53	-66.52	0.85	12.60	V
Highest	1697.6	-57.89	-13	-44.89	-65.46	-64.57	0.57	9.40	H
	2546.4	-31.93	-13	-18.93	-49.19	-39.64	0.74	10.60	H
	3395.2	-55.87	-13	-42.87	-71.47	-65.47	0.85	12.60	H
	1697.6	-57.83	-13	-44.83	-64.66	-64.51	0.57	9.40	V
	2546.4	-37.93	-13	-24.93	-54.50	-45.64	0.74	10.60	V
	3395.2	-56.53	-13	-43.53	-71.14	-66.13	0.85	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GPRS class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700.4	-36.47	-13	-23.47	-58.69	-48.20	0.87	12.60	H
	5550.6	-36.83	-13	-23.83	-60.43	-48.86	1.07	13.10	H
	7400.8	-35.14	-13	-22.14	-61.98	-44.75	1.69	11.30	H
	9251	-33.20	-13	-20.20	-63.86	-43.27	1.83	11.90	H
	3700.4	-38.17	-13	-25.17	-60.6	-49.90	0.87	12.6	V
	5550.6	-31.44	-13	-18.44	-57.05	-43.47	1.07	13.1	V
	7400.8	-35.04	-13	-22.04	-61.62	-44.47	1.87	11.3	V
	9251	-39.80	-13	-26.80	-69.08	-49.87	1.83	11.9	V
Middle	3760	-40.13	-13	-27.13	-61.42	-51.86	0.87	12.60	H
	5640	-35.80	-13	-22.80	-59.67	-47.83	1.07	13.10	H
	7520	-30.46	-13	-17.46	-58.78	-40.07	1.69	11.30	H
	9400	-38.94	-13	-25.94	-69.16	-49.01	1.83	11.90	H
	3760	-40.98	-13	-27.98	-62.79	-52.71	0.87	12.6	V
	5640	-30.37	-13	-17.37	-56.17	-42.40	1.07	13.1	V
	7520	-31.84	-13	-18.84	-59.76	-41.27	1.87	11.3	V
	9400	-40.58	-13	-27.58	-69.86	-50.65	1.83	11.9	V
Highest	3819.6	-46.52	-13	-33.52	-66.85	-58.25	0.87	12.60	H
	5729.4	-35.54	-13	-22.54	-59.48	-47.57	1.07	13.10	H
	7639.2	-27.03	-13	-14.03	-56.10	-36.64	1.69	11.30	H
	9549	-37.42	-13	-24.42	-67.64	-47.49	1.83	11.90	H
	3819.6	-46.29	-13	-33.29	-67.85	-58.02	0.87	12.6	V
	5729.4	-30.64	-13	-17.64	-56.4	-42.67	1.07	13.1	V
	7639.2	-29.69	-13	-16.69	-57.93	-39.12	1.87	11.3	V
	9549	-40.26	-13	-27.26	-69.54	-50.33	1.83	11.9	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (EDGE class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700.4	-46.62	-13	-33.62	-66.95	-58.35	0.87	12.60	H
	5550.6	-37.89	-13	-24.89	-61.34	-49.92	1.07	13.10	H
	7400.8	-47.90	-13	-34.90	-73.03	-57.51	1.69	11.30	H
	3700.4	-47.68	-13	-34.68	-69.24	-59.41	0.87	12.6	V
	5550.6	-42.64	-13	-29.64	-65.39	-54.67	1.07	13.1	V
	7400.8	-49.06	-13	-36.06	-73.97	-58.49	1.87	11.3	V
Middle	3760	-48.18	-13	-35.18	-68.51	-59.91	0.87	12.60	H
	5640	-38.91	-13	-25.91	-61.91	-50.94	1.07	13.10	H
	7520	-45.78	-13	-32.78	-70.91	-55.39	1.69	11.30	H
	3760	-47.38	-13	-34.38	-68.94	-59.11	0.87	12.6	V
	5640	-34.60	-13	-21.60	-59.4	-46.63	1.07	13.1	V
	7520	-47.23	-13	-34.23	-72.14	-56.66	1.87	11.3	V
Highest	3819.6	-52.76	-13	-39.76	-73.09	-64.49	0.87	12.60	H
	5729.4	-36.52	-13	-23.52	-60.20	-48.55	1.07	13.10	H
	7639.2	-42.18	-13	-29.18	-67.31	-51.79	1.69	11.30	H
	3819.6	-51.20	-13	-38.20	-72.76	-62.93	0.87	12.6	V
	5729.4	-33.46	-13	-20.46	-58.47	-45.49	1.07	13.1	V
	7639.2	-45.76	-13	-32.76	-70.67	-55.19	1.87	11.3	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1652.8	-45.90	-13	-32.90	-56.08	-52.58	0.57	9.40	H
	2479.2	-38.54	-13	-25.54	-54.72	-46.25	0.74	10.60	H
	3305.6	-54.38	-13	-41.38	-69.98	-63.98	0.85	12.60	H
	1652.8	-45.95	-13	-32.95	-55.86	-52.63	0.57	9.40	V
	2479.2	-53.32	-13	-40.32	-64.82	-61.03	0.74	10.60	V
	3305.6	-55.49	-13	-42.49	-70.10	-65.09	0.85	12.60	V
Middle	1672	-40.85	-13	-27.85	-52.09	-47.53	0.57	9.40	H
	2510	-41.85	-13	-28.85	-57.28	-49.56	0.74	10.60	H
	3346	-53.49	-13	-40.49	-69.09	-63.09	0.85	12.60	H
	1672	-43.64	-13	-30.64	-53.79	-50.32	0.57	9.40	V
	2510	-41.31	-13	-28.31	-57.23	-49.02	0.74	10.60	V
	3346	-55.67	-13	-42.67	-70.28	-65.27	0.85	12.60	V
Highest	1693.2	-43.43	-13	-30.43	-54.16	-50.11	0.57	9.40	H
	2539.8	-44.97	-13	-31.97	-59.88	-52.68	0.74	10.60	H
	3386.4	-53.33	-13	-40.33	-68.93	-62.93	0.85	12.60	H
	1693.2	-46.09	-13	-33.09	-55.97	-52.77	0.57	9.40	V
	2539.8	-53.52	-13	-40.52	-65.02	-61.23	0.74	10.60	V
	3386.4	-55.43	-13	-42.43	-70.04	-65.03	0.85	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3704.8	-52.72	-13	-39.72	-73.05	-64.45	0.87	12.60	H
	5557.2	-42.74	-13	-29.74	-65.61	-54.77	1.07	13.10	H
	7409.6	-49.55	-13	-36.55	-74.68	-59.16	1.69	11.30	H
	3704.8	-51.69	-13	-38.69	-73.25	-63.42	0.87	12.6	V
	5557.2	-43.52	-13	-30.52	-66.27	-55.55	1.07	13.1	V
	7409.6	-50.76	-13	-37.76	-75.67	-60.19	1.87	11.3	V
Middle	3760	-52.29	-13	-39.29	-72.62	-64.02	0.87	12.60	H
	5640	-45.89	-13	-32.89	-68.76	-57.92	1.07	13.10	H
	7520	-49.76	-13	-36.76	-74.89	-59.37	1.69	11.30	H
	3760	-50.69	-13	-37.69	-72.25	-62.42	0.87	12.6	V
	5640	-45.76	-13	-32.76	-68.51	-57.79	1.07	13.1	V
	7520	-49.04	-13	-36.04	-73.95	-58.47	1.87	11.3	V
Highest	3815.2	-50.74	-13	-37.74	-71.07	-62.47	0.87	12.60	H
	5722.8	-43.86	-13	-30.86	-66.73	-55.89	1.07	13.10	H
	7630.4	-50.06	-13	-37.06	-75.19	-59.67	1.69	11.30	H
	3815.2	-49.27	-13	-36.27	-70.83	-61.00	0.87	12.6	V
	5722.8	-46.22	-13	-33.22	-68.97	-58.25	1.07	13.1	V
	7630.4	-49.98	-13	-36.98	-74.89	-59.41	1.87	11.3	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.