




Plot 4.11
Tx @ 2437MHz 802.11n, 40MHz



Plot 4.12
Tx @ 2452MHz 802.11n, 40MHz




Plot 4.13
Conducted Band Edge, Tx @ 2412MHz 802.11b




Date: 20.OCT.2015 08:32:11

Plot 4.14
Conducted Band Edge, Tx @ 2462MHz 802.11b



Date: 20.OCT.2015 08:45:56


Plot 4.15
Conducted Band Edge, Tx @ 2412MHz 802.11g (Power 10.45dBm)



Date: 20.OCT.2015 08:22:51


Plot 4.16

Conducted Band Edge, Tx @ 2417MHz 802.11g (Power 13.45dBm)




Date: 20.OCT.2015 08:17:14

Plot 4.17
Conducted Band Edge, Tx @ 2422MHz 802.11g




Date: 20.OCT.2015 08:24:51

Plot 4.18
Conducted Band Edge, Tx @ 2462MHz 802.11g




Date: 20.OCT.2015 08:47:52

Plot 4.19
Conducted Band Edge, Tx @ 2412MHz 802.11n 20MHz (Power 10.46dBm)




Date: 20.OCT.2015 08:27:02

Plot 4.20
Conducted Band Edge, Tx @ 2417MHz 802.11n 20MHz (Power 13.48dBm)




Date: 20.OCT.2015 08:28:28

Plot 4.21
Conducted Band Edge, Tx @ 2422MHz 802.11n 20MHz




Date: 20.OCT.2015 08:30:23

Plot 4.22
Conducted Band Edge, Tx @ 2462MHz 802.11n 20MHz



Date: 20.OCT.2015 08:49:37

Plot 4.23
Conducted Band Edge, Tx @ 2422MHz 802.11n 40MHz




Date: 20.OCT.2015 08:39:46

```

* RBW 100 kHz      Marker 1 [T1 ]
* VBW 300 kHz      -1.01 dBm
  SWT 35 ms        2.463250000 GHz

```



Date: 20.OCT.2015 08:42:13



4.5 Transmitter Radiated Emissions & Antenna Port Emissions FCC Rule 15.247(d), 15.209, 15.205; RSS-247

4.5.1 Requirement

Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

For out of band radiated emissions (except for frequencies in restricted bands), in any 100 kHz bandwidths outside the EUT pass-band, the RF power shall be at least 20dB (peak) or 30 dB (average) below that of the maximum in-band 100 kHz emissions.

4.5.2 Procedure – Radiated Emissions

Radiated emission measurements were performed from 30 MHz to 25 GHz according to the procedure described in ANSI C64.10. Spectrum Analyzer Resolution Bandwidth is 100 kHz or greater for frequencies 30 MHz to 1000 MHz, 1 MHz for frequencies above 1000 MHz. Above 1000 MHz Peak and Average measurements were performed.

The EUT is placed on a plastic turntable that is 80 cm in height for below 1000MHz and 1.5m in height for above 1GHz. If the EUT attaches to peripherals, they are connected and operational (as typical as possible). During testing, all cables were manipulated to produce worst-case emissions. The signal is maximized through rotation. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters.

Radiated emissions are taken at 3 meters for frequencies above 1 GHz and at 10 meters for frequencies below 1 GHz.

Measurements made from 1 GHz to 18GHz had a 2.4-2.5GHz notch filter in place. A preamp was used from 30MHz to 26GHz.

All measurements were made with a Peak Detector and compared to QP limits for 30MHz – 1GHz and Average limits for 1GHz – 26GHz.

Data is included of the worst-case configuration (the configuration which resulted in the highest emission levels).



4.5.3 Field Strength Calculation

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$FS = RA + AF + CF - AG$; if measurement is performed at a distance other than specified in the rule, a Distance Correction Factor (DCF) shall be added.

Where FS = Field Strength in $dB(\mu V/m)$

RA = Receiver Amplitude (including preamplifier) in $dB(\mu V)$; AF = Antenna Factor in $dB(1/m)$

CF = Cable Attenuation Factor in dB ; AG = Amplifier Gain in dB

Assume a receiver reading of $52.0\text{ dB}(\mu V)$ is obtained. The antennas factor of $7.4\text{ dB}(1/m)$ and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted, giving field strength of $32\text{ dB}(\mu V/m)$. This value in $dB(\mu V/m)$ was converted to its corresponding level in $\mu V/m$.

$RA = 52.0\text{ dB}(\mu V)$

$AF = 7.4\text{ dB}(1/m)$

$CF = 1.6\text{ dB}$

$AG = 29.0\text{ dB}$

$FS = 52.0 + 7.4 + 1.6 - 29.0 = 32\text{ dB}(\mu V/m)$.

Level in $\mu V/m$ = Common Antilogarithm $[(32\text{ dB}\mu V/m)/20] = 39.8\text{ }\mu V/m$.



4.5.4 Antenna-port conducted measurements

Antenna-port conducted measurements may also be used as an alternative to radiated measurements for demonstrating compliance in the restricted frequency bands. If conducted measurements are performed, then proper impedance matching must be ensured and an additional radiated test for cabinet/case spurious emissions is required.

4.5.6 General Procedure for conducted measurements in restricted bands

- a) Measure the conducted output power (in dBm) using the detector specified for determining quasi-peak, peak, and average conducted output power, respectively.
- b) Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
- c) Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies ≤ 30 MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies > 1000 MHz).
- d) For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (*e.g.*, Watts, mW).
- e) Convert the resultant EIRP level to an equivalent electric field strength using the following relationship:
$$E = \text{EIRP} - 20\log D + 104.8$$
where:
E = electric field strength in dB μ V/m,
EIRP = equivalent isotropic radiated power in dBm
D = specified measurement distance in meters.
- f) Compare the resultant electric field strength level to the applicable limit.
- g) Perform radiated spurious emission test

4.5.7 Test Results



The data on the following pages list the significant emission frequencies, the limit and the margin of compliance where emissions are within 3dB of the limit.

All conducted antenna port plots are corrected with the consideration of a 3.6dBi Antenna Gain.

Radiated emission measurements were performed up to 26GHz. No Emissions were identified when scanned from 18-25 GHz.



Test Results: 15.209/15.205 Restricted Band Emissions at Antenna Port

Out-of-Band Spurious Emissions at the Band Edge - 802.11b, 2412 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBμV/m	dBμV/m	dB		
2.390	52.8	54	-1.2	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11b, 2462 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	53.8	54	-0.2	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2412 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	52.8	54	-1.2	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2417 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBµV/m	dBµV/m	dB		
2.390	72.7	74	-1.3	Peak	Pass
2.390	52.6	54	-1.4	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2422 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	72.5	54	-1.5	Peak	Pass
2.390	52.9	54	-1.1	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2427 MHz




Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	52.6	54	-1.4	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2432 MHz




Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	53.3	54	-0.7	Avg	Pass



Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2437 MHz



Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2442 MHz





Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2447 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	73.2	74	-0.8	Peak	Pass
2.4835	53.7	54	-0.3	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2452 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	72.8	74	-1.2	Peak	Pass
2.4835	52.6	54	-1.4	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2457 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	72.5	74	-1.5	Peak	Pass
2.4835	52.4	54	-1.6	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11g, 2462 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	72.7	74	-1.3	0.2	Pass
2.4835	53.8	54	-0.2	1.3	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2412 MHz




Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBμV/m	dBμV/m	dB		
2.390	73.1	74	-0.9	Peak	Pass
2.390	53.0	54	-1.0	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2417 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	71.8	54	-2.2	Peak	Pass
2.390	52.3	54	-1.7	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2422 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.388	52.8	74	-0.9	Peak	Pass
2.390	52.8	54	-1.2	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2427 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	73.1	74	-0.9	Peak	Pass
2.390	52.6	54	-1.4	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2432 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBμV/m	dBμV/m	dB		
2.4835	52.8	54	-1.2	Peak	Pass
2.4835	53.3	54	-0.7	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2437 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBμV/m	dBμV/m	dB		
2.4885	53.3	54	-0.7	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2442 MHz



Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4938	52.8	54	-1.2	Avg	Pass



Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2447 MHz



2499.35



Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	73.1	74	-0.9	Peak	Pass
2.4835	52.8	54	-1.2	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2452 MHz




Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBμV/m	dBμV/m	dB		
2.4835	73.2	74	-0.8	Peak	Pass
2.4835	53.3	54	-0.7	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2457 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	53.7	54	-0.3	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 20MHz, 2462 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	53.9	54	-0.1	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 40MHz, 2422 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	52.9	54	-1.1	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 40MHz, 2427 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	53.6	54	-0.4	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 40MHz, 2432 MHz




Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	53.0	54	-1.0	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 40MHz, 2437 MHz




Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.390	73.0	74	-1.0	Peak	Pass
2.390	52.4	54	-1.6	Avg	Pass
2.4835	73.4	74	-0.6	Peak	Pass
2.4835	53.8	54	-0.2	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 40MHz, 2442 MHz





Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	73.5	74	-0.5	Peak	Pass
2.4835	53.9	54	-0.1	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 40MHz, 2447 MHz



Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	52.7	54	-1.3	Avg	Pass

Out-of-Band Spurious Emissions at the Band Edge - 802.11n 40MHz, 2452 MHz




Frequency	Corrected Amplitude	Limit	Margin	Detector	Results
GHz	dBuV/m	dBuV/m	dB		
2.4835	53.8	54	-0.2	Avg	Pass


Out-of-Band Conducted Spurious Emissions (at Antenna Port)

Tx @ 2412MHz 802.11b

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dB μ V/m	dB μ V/m	dB	
4.828	47.9	54	-6.1	Pass
12.060	51.0	54	-3.0	Pass

Tx @ 2437MHz 802.11b

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.874	50.3	54	-3.7	Pass
12.185	53.7	54	-0.3	Pass

Tx @ 2462MHz 802.11b

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.924	49.0	54	-5.0	Pass
12.309	52.3	54	-1.7	Pass

Tx @ 2412MHz 802.11g

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.825	41.9	54	-12.1	Pass
12.060	41.8	54	-12.2	Pass

Tx @ 2437MHz 802.11g

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.874	41.8	54	-12.2	Pass
12.185	42.0	54	-12.0	Pass

Tx @ 2462MHz 802.11g

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBμV/m	dBμV/m	dB	
4.921	41.7	54	-12.3	Pass
12.307	41.6	54	-12.4	Pass

Tx @ 2412MHz 802.11n 20MHz

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.824	41.7	54	-12.3	Pass
12.060	41.5	54	-12.5	Pass

Tx @ 2437MHz 802.11n 20MHz

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.874	41.6	54	-12.4	Pass
12.185	42.1	54	-11.9	Pass

Tx @ 2462MHz 802.11n 20MHz

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.921	41.4	54	-12.6	Pass
12.306	41.8	54	-12.2	Pass

Tx @ 2422MHz 802.11n 40MHz

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.844	42.7	54	-11.3	Pass
12.110	43.5	54	-10.5	Pass

Tx @ 2437MHz 802.11n 40MHz

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz




Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz




Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.874	43.0	54	-11.0	Pass
12.206	43.9	54	-10.1	Pass

Tx @ 2452MHz 802.11n 40MHz

Out-of-Band Spurious Emissions at Antenna Port - 30 MHz to 1 GHz



Out-of-Band Spurious Emissions at Antenna Port - 1 GHz to 26 GHz



Frequency	Corrected Amplitude	Limit	Margin	Results
GHz	dBuV/m	dBuV/m	dB	
4.913	42.6	54	-11.4	Pass
12.237	43.6	54	-10.4	Pass