

TEST REPORT

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (1) / (31) pages

1. Applicant


- Name : SOLUM CO.,LTD.
- Address : 7F, 2354, Yonggu-daero, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
- Date of Receipt : 2026-04-03

2. Manufacturer

- Name : SOLUM CO.,LTD.

3. Use of Report : For FCC Certification & ISED Certification**4. Test sample / Model** : Newton E-Paper 32" / EL315TVW6S**5. Date(s) of test** : 2026-04-09 to 2026-05-13**6. Test Standard (Method) used** : FCC 47 CFR part 15 subpart C 15.247,
ANSI C63.10, RSS-247, RSS-Gen**7. Testing Environment** : refer to 7 page**8. Test Results** : Compliance**9. Location of Test** : ☒ Permanent Testing Lab ☐ On Site Testing
(Address : 5, Dongbu-ro 221beon-gil, Cheoin-gu, Yongin-si, Gyeonggi-do, 17141 Korea)

The results shown in this test report refer only to the sample(s) tested unless otherwise stated.
This report cannot be reproduced or copied without the written consent of CTK.

Approval	Tested by:	Technical Manager:
	 Seong-uk Park (Signature)	 Young-taek Lee (Signature)

2026-09-02

CTK Co., Ltd.



**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (2) / (31) pages

REPORT REVISION HISTORY

Date	Revision	Page No
2026-09-02	Issued (CTK-2026-02451)	all

This report shall not be reproduced except in full, without the written approval of CTK Co., Ltd. This document may be altered or revised by CTK Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CTK Co., Ltd. will constitute fraud and shall nullify the document.

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (3) / (31) pages

CONTENTS

1. General Product Description	4
1.1 Applicant Information	4
1.2 Manufacturer Information	4
1.3 Product Information	4
1.4 Peripheral Devices	5
2. Accreditations	6
2.1 Laboratory Accreditations and Listings	6
2.2 Calibration Details of Equipment Used for Measurement	6
3. Test Specifications	7
3.1 Standards	7
3.2 Mode of operation during the test.....	8
3.3 Measurement Uncertainty	8
3.4 Test Software	8
3.5 Testing Environment	8
4. Technical Characteristic Test	9
4.1 6dB Bandwidth & 99% Bandwidth.....	9
4.2 Maximum peak Conducted Output Power	11
4.3 Power Spectral Density	13
4.4 Band Edge & Conducted Spurious emission	15
4.5 Radiated Emission	18
4.6 AC Conducted Emissions.....	29
APPENDIX A – Test Equipment Used For Tests	31

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (4) / (31) pages

1. General Product Description

1.1 Applicant Information

Company	SOLUM CO.,LTD.
Contact Point	7F, 2354, Yonggu-daero, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
Contact Person	Name : Ki Dong Lee E-mail : kdlee007@solu-m.com Tel : +82-31-8006-7677

1.2 Manufacturer Information

Manufacturer	SOLUM CO.,LTD.
Address	7F, 2354, Yonggu-daero, Giheung-gu, Yongin-si, Gyeonggi-do, Republic of Korea
Factory #1	SOLUM VINA CO., LTD
Factory #1 Address	Plot B3, Ba Thien II Industrial Park, Thien Ke Ward, Binh Xuyen District, Vinh Phuc Province, VIETNAM

1.3 Product Information

FCC ID	2AFWN-EL315TVW6S
IC	22800-EL315TVW6S
Product Description	Newton E-Paper 32"
Model name	EL315TVW6S
Variant Model name	EL315TVW6S/WWW (For the EL315TVW6S/WWW variants, the RF specification has been changed from the base model's 2.4GHz SRD to Bluetooth LE due to software modifications. There are no changes to the WLAN, nor are there any other hardware changes.) EL315HVVW6S/WWW (For the variant models EL315HVVW6S/WWW, has no technical differences with each model except for the model name for marketing purposes.)
Operating Frequency	2 401 MHz - 2 480 MHz
RF Output Power	-1.648 dBm(0.684 mW)
Antenna Specification	Antenna type : PCB Patch Antenna Peak Gain : 4.72 dBi
Number of channels	80
Channel Spacing	1 MHz
Type of Modulation	GFSK
Power Source	DC 3.7 V(Battery)
FVIN	V049(EL315TVW6S, EL315HVVW6S/WWW), V008(EL315TVW6S/WWW)
Test Software(Version)	Tera term (Version 4.8.5)
RF Power setting in Test SW	Power setting input "4"

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (5) / (31) pages

1.4 Peripheral Devices

-For Conducted Measurement and Radiated Measurement

Device	Manufacturer	Model No.	Serial No.
Notebook	Samsung Electronics Co., Ltd	550XDA	KQFJ99YRA002J0
AC Adapter	Samsung Electronics Co., Ltd	PA-1400-96	CN60BA4400295AD2VHNCHF042

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (6) / (31) pages

2. Accreditations

2.1 Laboratory Accreditations and Listings

Country	Agency	Registration Number
USA	FCC	805871
CANADA	ISED	CN : 8737A CAB ID : KR0025
KOREA	NRRA	KR0025

2.2 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (7) / (31) pages

3. Test Specifications

3.1 Standards

Section in FCC	Section in RSS	Requirement(s)	Status (Note 1)	Test Condition
15.247(a)	RSS-247 6.3.1(a)	6 dB Bandwidth & 99% Bandwidth	C	Conducted
15.247(e)	RSS-247 6.3.1(b)	Transmitter power spectral density	C	
15.247(b)	RSS-247 5.3.2	Maximum peak conducted output power	C	
15.247(d)	RSS-247 6.6	Unwanted emission	C	
15.209	RSS-Gen 6.13	Transmitter emission	C	Radiated
15.207	RSS-Gen 8.8	AC Conducted Emission	C	Line Conducted
Note 1: C=Complies NC=Not Complies NT=Not Tested NA=Not Applicable				
Note 2: The data in this test report are traceable to the national or international standards.				
Note 3: The sample was tested according to the following specification: FCC Part 15.247, RSS-247 Issue 4				
Note 4: The tests were performed according to the method of measurements prescribed in KDB No.558074. ANSI C63.10-2020+Cor 1-2023+C63.10a-2024+Errata to C63.10a-2024, RSS-Gen Issue 5.				
Note 5: This equipment has been tested in a 100% duty cycle transmission situation using applicant supplied software.				

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (8) / (31) pages

3.2 Mode of operation during the test

The EUT is operated in a manner representative of the typical of the equipments.
During at testing, system components were manipulated within the confines of typical usage to maximize each emission. All modulation modes were tests.
The results are only attached worst cases.

Test Frequency

Lowest channel	Middle channel	Highest channel
2 401 MHz	2 440 MHz	2 480 MHz

3.3 Measurement Uncertainty

The value of the measurement uncertainty for the measurement of each parameter.
Coverage factor $k = 2$, Confidence levels of 95 %

Description	Uncertainty
Conducted RF Output Power	0.46 dB (C.L.: Approx. 95 %, $k = 2$)
Power Spectral Density	1.5 dB (C.L.: Approx. 95 %, $k = 2$)
Occupied Bandwidth	1.00 kHz (C.L.: Approx. 95 %, $k = 2$)
Unwanted Emission(conducted)	0.54 dB (C.L.: Approx. 95 %, $k = 2$)
Radiated Emissions ($f \leq 1$ GHz)	4.11 dB (C.L.: Approx. 95 %, $k = 2$)
Radiated Emissions ($f > 1$ GHz)	4.34 dB (C.L.: Approx. 95 %, $k = 2$)
Line Conducted Emission	2.06 dB (C.L.: Approx. 95 %, $k = 2$)

3.4 Test Software

Conducted Test	Ics Pro Ver. 6.0.3
Radiated Test	EP5RE Ver. 6.0.10, ES10 Ver. 2022.04.000
Line Conducted Test	EMC32 Ver. 10.50.00

3.5 Testing Environment

Test Item	Test Date	Temperature (°C)	Relative Humidity (%)
6 dB Bandwidth	2026-04-09	22 ±1	31 ±3
Transmitter power spectral density			
Maximum peak conducted output power			
Unwanted emission			
Radiated Emissions ($f \leq 1$ GHz)	2026-04-20, 2026-04-24	20 ±1, 20 ±1	34 ±3, 24 ±3
Radiated Emissions ($f > 1$ GHz)	2026-05-13	25 ±1	32 ±3
AC Conducted Emissions	2026-04-29	19 ±1	42 ±3

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (9) / (31) pages

4. Technical Characteristic Test

4.1 6dB Bandwidth & 99% Bandwidth

ANSI C63.10-2020 - Section 11.8.2

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

ANSI C63.10-2020 - Section 6.9.3

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Use the 99 % power bandwidth function of the instrument and report the measured bandwidth.

Test Settings :

Center frequency = the highest, middle and the lowest channels

- a) RBW = 100 kHz(6dB Bandwidth),
30 kHz(99% Bandwidth)
- b) VBW $\geq 3 \times$ RBW
- c) Detector = peak
- d) Trace mode = Max hold
- e) Sweep = auto couple
- f) Allow trace to fully stabilize
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Limit :

6 dB Bandwidth > 500 kHz

Test Data :

Channel	Frequency [MHz]	6 dB Bandwidth [MHz]	99 % Bandwidth [MHz]	Result
Low	2 401	0.719	1.046	Complies
Middle	2 440	0.727	1.059	Complies
High	2 480	0.712	1.063	Complies

See next pages for actual measured spectrum plots.




CTK Co., Ltd.


(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (10) / (31) pages


6 dB Bandwidth[MHz] Low channel




99% Bandwidth[MHz] Low channel




Middle channel




Middle channel



High channel



High channel



**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (11) / (31) pages

4.2 Maximum peak Conducted Output Power

Test Procedures(ANSI C63.10-2020 11.9.1)

The following procedure can be used when the maximum available RBW of the instrument is less than the DTS bandwidth:

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) $RBW \geq DTS \text{ Bandwidth}$
- b) $VBW \geq 3 \times RBW$
- c) $span \geq 3 \times RBW$
- d) Sweep time = auto couple
- e) Detector = peak
- f) Trace mode= max hold
- g) Allow trace to fully stabilize
- h) Use peak marker function to determine the peak amplitude level.

Limit :

Maximum Output Power < 1 W (30 dBm)

Test Data :

Channel	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
Low	2 401	-1.648	30	Complies
Middle	2 440	-2.160	30	Complies
High	2 480	-2.559	30	Complies

See next pages for actual measured spectrum plots.




CTK Co., Ltd.


(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (12) / (31) pages


Output Power Low channel



Middle channel



High channel



**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (13) / (31) pages

4.3 Power Spectral Density

Test Procedures(ANSI C63.10-2020 11.10.2)

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) RBW : $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- b) VBW $\geq 3 \times \text{RBW}$
- c) span $\geq 1.5 \times \text{DTS bandwidth}$
- d) Sweep time = auto couple
- e) Detector = peak
- f) Trace mode = max hold
- g) Allow trace to fully stabilize
- h) Use the peak marker function to determine the maximum amplitude level within the RBW.

Limit :

Power Spectral Density < 8 dBm @ 3 kHz BW

Test Data :

Channel	Frequency [MHz]	Measurement data [dBm]	Limit [dBm]	Result
Low	2 401	-14.129	8	Complies
Middle	2 440	-15.050	8	Complies
High	2 480	-14.514	8	Complies

See next pages for actual measured spectrum plots.




CTK Co., Ltd.


(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (14) / (31) pages


Power Spectral Density Low channel



Middle channel



High channel



**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (15) / (31) pages

4.4 Band Edge & Conducted Spurious emission

Test Procedures(ANSI C63.10-2020 11.11.3)

The Unwanted emission from the EUT were measured according to the dictates PKPSD measurement procedure in section 11.11 of ANSI C63.10-2020.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(4), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Test Settings:

Center frequency = the highest, middle and the lowest channels

- a) RBW = 100 kHz
- b) VBW $\geq 3 \times$ RBW
- c) Detector = peak
- d) Sweep time = auto couple
- e) Trace mode= max hold
- f) Allow trace to fully stabilize
- g) Use the peak marker function to determine the maximum amplitude level.

Limit :

Emission level < 30 dBc

Test results: Complies

- All conducted emission in any 100kHz bandwidth outside of the spread spectrum band was at least 30dB lower than the highest in-band spectral density. Therefore the applying equipment meets the requirement.



See next pages for actual measured spectrum plots.



CTK Co., Ltd.
(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (16) / (31) pages

Conducted Band-Edge







CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (17) / (31) pages

Conducted Spurious Emission



**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (18) / (31) pages

4.5 Radiated Emission

Test Location

- ☒ 10 m SAC (test distance : ☐ 10 m, ☒ 3 m)
☒ 3 m SAC (test distance : 3 m)

Test Procedures

KDB 789033 - Section G
ANSI C63.10-2020 – Section 12.7

- 1) In the frequency range of 9 kHz to 30 MHz, magnetic field is measured with Loop Antenna. The Test Antenna is positioned with its plane vertical at 3 m distance from the EUT. The center of the Loop Test Antenna is 1 m above the ground. During the measurement the Loop Test Antenna rotates about its vertical axis for maximum response at each azimuth about the EUT.
- 2) In the frequency range above 30 MHz, Bi-Log Test Antenna(30 MHz to 1 GHz) and Horn Test Antenna(above 1 GHz) are used. Test Antenna is 3 m away from the EUT. Test Antenna height is carried from 1 m to 4 m above the ground to determine the maximum value of the field strength. The emissions levels at both horizontal and vertical polarizations should be tested.

Test Settings:

Frequency Range = 9 kHz to 1 GHz

- a) RBW = 100 kHz for $f < 1$ GHz, 9 kHz for $f < 30$ MHz
b) VBW $\geq$ RBW
c) Detector = CISPR Quasi-peak
d) Sweep time = auto couple

- Peak

Frequency Range = 1 GHz to 40 GHz

- a) RBW = 1 MHz
b) VBW $\geq 3 \times$ RBW
c) Detector = peak
d) Sweep time = auto
e) Trace mode = max hold

- Average (duty cycle ≥ 98 %)

Frequency Range = 1 GHz to 40 GHz

- a) RBW = 1 MHz
b) VBW $\geq 3 \times$ RBW
c) Detector = RMS
d) Sweep time = auto
e) Averaging type = power (i.e., RMS)
f) Trace mode = average (at least 100 traces)

- Average (duty cycle < 98 %, duty cycle variations are less than ± 2 %)

Frequency Range = 1 GHz to 40 GHz

- a) RBW = 1 MHz
b) VBW $\geq 3 \times$ RBW
c) Detector = RMS
d) Sweep time = auto
e) Averaging type = power (i.e., RMS)
f) Trace mode = average (at least 100 traces)

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (19) / (31) pages

If power averaging (RMS) mode, then the applicable correction factor is $10 \log(1/x)$, where x is the duty cycle.

Limit :

- 15.209(a) and RSS-GEN § 8.9

Frequency [MHz]	Magnetic Field Strength [uA/m]	Field Strength [uV/m]	Field Strength [dBuV/m]	Deasurement Distance [meters]
0.009-0.490	6.37/F (F in kHz)	2400/F(kHz)	48.5-13.8	300
0.490-1.705	63.7/F (F in kHz)	24000/F(kHz)	33.8-23	30
1.705-30	0.08	30	29.5	30
30-88	-	100**	40	3
88-216	-	150**	43.5	3
216-960	-	200**	46	3
Above 960	-	500	54	3

** Except as provided in 15.209(g). Fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz, 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g. 15.231 and 15.241.

** Except as provided in RSS-GEN § 8.9. The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

FCC Part 15 § 15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

Table 1. Restricted Frequency Bands (FCC)

MHz	MHz	MHz	MHz	MHz	GHz
0.09-0.11	8.37626-8.38675	73-74.6	399.9-410	2690-2900	10.6-12.7
¹ 0.495-0.505	8.41425-8.41475	74.8-75.2	608-614	3260-3267	13.25-13.4
2.1735-2.1905	12.29-12.293	108-121.94	960-1240	3332-3339	14.47-14.5
4.125-4.128	12.51975-12.52025	123-138	1300-1427	3345.8-3358	15.35-16.2
4.17725-4.17775	12.57675-12.57725	149.9-150.05	1435-1626.5	3600-4400	17.7-21.4
4.20725-4.20775	13.36-13.41	156.52475-156.52525	1645.5-1646.5	4500-5150	22.01-23.12
6.215-6.218	16.42-16.423	156.7-156.9	1660-1710	5350-5460	23.6-24
6.26775-6.26825	16.69475-16.69525	162.0125-167.17	1718.8-1722.2	7250-7750	31.2-31.8
6.31175-6.31225	16.80425-16.80475	167.72-173.2	2200-2300	8025-8500	36.43-36.5
8.291-8.294	25.5-25.67	240-285	2310-2390	9000-9200	² Above 38.6
8.362-8.366	37.5-38.25	322-335.4	2483.5-2500	9300-9500	

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

§ 15.205 (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions.

The provisions in Section 15.35 apply to these measurements.

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (20) / (31) pages

According to RSS-GEN §8.10 Unwanted emissions that fall into restricted frequency bands listed in table 2 shall comply with the limits specified in table 2.

Table 2. Restricted Frequency Bands (ISED)

MHz	MHz	MHz	MHz	MHz	GHz
0.090-0.110	8.291-8.294	25.5-25.67	322-335.4	2655-2900	10.6-12.7
0.495-0.505	8.362-8.366	37.5-38.25	399.9-410	3260 – 3267	13.25-13.4
2.1735-2.1905	8.37625-8.38675	73-74.6	608-614	3332-3339	14.47-14.5
3.020-3.026	8.41425-8.41475	74.8-75.2	960-1427	3345.8-3358	15.35-16.2
4.125-4.128	12.29-12.293	108 – 138	1435-1626.5	3500-4400	10.6-12.7
4.17725-4.17775	12.51975-12.52025	149.9-150.05	1645.5-1646.5	4500-5150	22.01-23.12
4.20725-4.20775	12.57675-12.57725	156.52475-156.52525	1660-1710	5350-5460	23.6-24.0
5.677-5.683	13.36-13.41	156.7-156.9	1718.8-1722.2	7250-7750	31.2-31.8
6.215-6.218	16.42-16.423	162.0125-167.17	2200-2300	8025–8500	36.43-36.5
6.26775-6.26825	16.69475-16.69525	167.72-173.2	2310-2390	9000-9200	Above 38.6
6.31175-6.31225	16.80425-16.80475	240 – 285	2483.5-2500	9300-9500	


Note 1: Certain frequency bands listed in table 2 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

Note :


- 1) For above 1 GHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
- 2) For above 1 GHz, limit field strength of harmonics : 54 dBuV/m@3 m (AV) and 74 dBuV/m@3 m (PK)

Test Setup:


- 1) For field strength of emissions from 9 kHz to 30 MHz



- 2) For field strength of emissions from 30 MHz to 1 GHz



3) For field strength of emissions above 1 GHz





CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (23) / (31) pages


Test results

1. 9 kHz to 30 MHz

Test mode : Transmit, Low Channel(Worst case)

The requirements are:

☒ Complies



Note :

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator
4. The emissions were 20 dB lower than the limit.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (24) / (31) pages


2. 30 MHz to 1 GHz

The requirements are:

☒ Complies

Test mode : Transmit, Low Channel(Worst case)

Test Data



Spectrum Selection

No.	Frequency [MHz]	Pol	Reading PK [dB (μV)]	c.f [dB (1/m)]	Result PK [dB (μV/m)]	Limit QP [dB (μV/m)]	Margin QP-PK [dB]	Height [cm]	Angle [deg]
1	225.455	H	49.9	-13.8	36.1	46.0	9.9	100.0	191.3
2	230.693	H	50.9	-13.3	37.6	46.0	8.4	100.0	0.0
3	232.342	H	51.0	-13.1	37.9	46.0	8.1	100.0	45.4
4	235.834	H	50.3	-12.8	37.5	46.0	8.5	100.0	130.1
5	236.707	H	49.2	-12.6	36.6	46.0	9.4	100.0	112.9
6	239.714	H	46.6	-12.2	34.4	46.0	11.6	100.0	133.0

Remark :

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(Z axis) and the worst case was recorded.
 2. Result = Reading + c.f(Correction factor)
 3. Correction factor = Antenna factor + Cable loss + 6 dB attenuator - Amp Gain
- * Reading data is the peak value.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501


REPORT No.:
CTK-2026-02451
Page (25) / (31) pages

3. 2 310 MHz to 2 390 MHz

The requirements are:

☒ Complies

Test mode : Transmit, Low Channel(Worst case)



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Note
2 325.8	V	42.5	-4.8	-----	37.7	-----	54.0	-----	16.3	Average
2 338.8	H	53.8	-4.8	49.0	-----	74.0	-----	25.0	-----	Peak
2 371.9	H	42.4	-4.7	-----	37.7	-----	54.0	-----	16.3	Average
2 373.3	V	53.5	-4.6	48.9	-----	74.0	-----	25.1	-----	Peak

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain
4. Radiated Emission measured at 100 % duty cycle.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501


REPORT No.:
CTK-2026-02451
Page (26) / (31) pages

4. 2 483.5 MHz – 2 500 MHz

The requirements are:

☒ Complies

Test mode : Transmit, High Channel(Worst case)



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Note
2 484.8	H	42.5	-4.2	----	38.3	----	54.0	----	15.7	Average
2 489.8	H	53.2	-4.1	49.1	----	74.0	----	24.9	----	Peak
2 497.3	V	53.3	-4.0	49.3	----	74.0	----	24.7	----	Peak
2 500.0	V	41.8	-4.0	----	37.8	----	54.0	----	16.2	Average

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain
4. Radiated Emission measured at 100 % duty cycle.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501


REPORT No.:
CTK-2026-02451
Page (27) / (31) pages

5. 1 GHz to 18 GHz

The requirements are:

☒ Complies

Test mode : Transmit, Low Channel(Worst case)



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Note
4 801.4	H	49.2	3.3	52.5	-----	74.0	-----	21.5	-----	Peak
4 802.0	H	40.3	3.3	-----	43.6	-----	54.0	-----	10.4	Average
4 802.0	V	46.1	3.3	49.4	-----	74.0	-----	24.6	-----	Peak
4 802.0	V	36.8	3.3	-----	40.1	-----	54.0	-----	13.9	Average

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in stand-up position(Z axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain
4. Radiated Emission measured at 100 % duty cycle.



CTK Co., Ltd.

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501


REPORT No.:
CTK-2026-02451
Page (28) / (31) pages

6. 18.0 GHz to 26.5 GHz

Test mode : Transmit, Low Channel(Worst case)

The requirements are:

☒ Complies



Frequency [MHz]	(P)	Reading [dBuV]	c.f [dB(1/m)]	Level PK [dB(uV/m)]	Level AV [dB(uV/m)]	Limit PK [dB(uV/m)]	Limit AV [dB(uV/m)]	Margin PK [dB]	Margin AV [dB]	Note
-----------------	-----	----------------	---------------	---------------------	---------------------	---------------------	---------------------	----------------	----------------	------

No Peak Data

Remarks

1. The Unwanted emission was measured in the following position: EUT stand-up position(Z axis), lie-down position(X,Y axis). The worst emission was found in lie-down position(X axis) and the worst case was recorded.
2. Result = Reading + c.f(correction factor)
3. Correction factor = Antenna factor + Cable loss - Amp Gain
4. Radiated Emission measured at 100 % duty cycle.

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (29) / (31) pages

4.6 AC Conducted Emissions

Frequency Range of Measurement

150 kHz to 30 MHz

Instrument Settings

IF Band Width: 9 kHz

Test Procedures

ANSI C63.10-2020 - Section 6.2

RSS-Gen - Section 8.8

The EUT was placed on a non-metallic table 0.8m above the metallic, grounded floor and 0.4m from the reference ground plane wall. The distance to other metallic surfaces was at least 0.8m.

Amplitude measurements were performed with a quasi-peak detector and an average detector.

Limit

- 15.207(a)

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average**
0.15 ~ 0.5	66 to 56*	56 to 46*
0.5 ~ 5	56	46
5 ~ 30	60	50

* The level decreases linearly with the logarithm of the frequency.

** A linear average detector is required.

Test Results

The requirements are:

☒ Complies



CTK Co., Ltd.


(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (30) / (31) pages

Test Data

Transmitter - Low Channel(Worst case)

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBμV)	CAverage (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.154500	38.83	---	65.75	26.93	15000.0	9.000	N	ON	9.9
0.487500	---	33.77	46.21	12.44	15000.0	9.000	L1	ON	10.2
0.532500	45.29	---	56.00	10.71	15000.0	9.000	L1	ON	10.2
0.537000	---	34.69	46.00	11.31	15000.0	9.000	N	ON	10.2
0.537000	45.29	---	56.00	10.71	15000.0	9.000	N	ON	10.2
0.766500	---	29.03	46.00	16.97	15000.0	9.000	N	ON	10.1
12.673500	45.96	---	60.00	14.04	15000.0	9.000	N	ON	10.7
14.239500	56.24	---	60.00	3.76	15000.0	9.000	N	ON	10.8
14.680500	---	42.35	50.00	7.65	15000.0	9.000	N	ON	10.9
15.922500	50.00	---	60.00	10.00	15000.0	9.000	N	ON	10.9
16.440000	---	40.69	50.00	9.31	15000.0	9.000	N	ON	11.0
19.639500	---	39.50	50.00	10.50	15000.0	9.000	N	ON	11.1

**CTK Co., Ltd.**

(Ho-dong), 113, Yejik-ro, Cheoin-gu, Yongin-si,
Gyeonggi-do, 17142, Korea
Tel: +82-1551-9871
Fax: +82-31-624-9501

REPORT No.:
CTK-2026-02451
Page (31) / (31) pages

APPENDIX A – Test Equipment Used For Tests

No.	Name of Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	Signal Analyzer	Agilent	N9020A	MY50510324	2025-11-25	2026-11-25
2	Signal Generator	Rohde & Schwarz	SMB100A	175528	2026-03-12	2027-03-12
3	EMI TEST RECEIVER	Rohde & Schwarz	ESW44	102039	2025-04-28	2026-04-28
4	Active Loop Antenna	SCHWARZBECK	FMZB 1513	1513-125	2027-03-25	2028-03-25
5	Bilog Antenna	TESEQ	CBL6111D	60654	2025-08-21	2027-08-21
6	AMPLIFIER	SONOMA INSTRUMENT	310N	411011	2026-07-20	2027-07-20
7	ATTENUATOR	PASTERNAK	PE7AP006-06	L20210504000023	2026-07-20	2027-07-20
8	ATTENUATOR	NONE	6dB	190557	2025-09-18	2026-09-18
9	Preamplifier	Agilent	8449B	3008A00620	2026-03-11	2027-03-11
10	Double Ridged Guide Antenna	ETS-Lindgren	3115	00078895	2026-03-13	2027-03-13
11	Horn Antenna	SCHWARZBECK	BBHA9170	01153	2025-09-30	2026-09-30
12	Low Noise Amplifier	TESTEK	TK-PA1840H	210124-L	2025-09-30	2026-09-30
13	Band Reject Filter	Micro Tronics	BRM50702	G233	2025-11-25	2026-11-25
14	Spectrum Analyzer	Rohde & Schwarz	FSV40	101574	2026-01-13	2027-01-13
15	DC Power Supply	Agilent	E3632A	MY50370042	2026-07-03	2027-07-03
16	LISN	Rohde & Schwarz	ENV216	102698	2026-04-27	2027-04-27
17	EMI TEST RECEIVER	Rohde & Schwarz	ESR3	102826	2026-04-27	2027-04-27

No.	Cable	Manufacturer	Model No.	Serial No.	Check Date
1	RF Cable (Conducted)	Junkosha Inc.	MWX221	2008S252	2026-04-09
2	RF Cable (Line Conducted)	Canare Corporation	L-5D2W	N/A	2026-04-16
3	RF Cable (9 kHz - 1 GHz Radiated)	HUBER+SUHNER	SUCOFLEX 104	MY27558/4	2026-04-16
4	RF Cable (9 kHz - 1 GHz Radiated)	HUBER+SUHNER	L-5D2W	N/A	2026-04-16
5	RF Cable (1 GHz - 18 GHz Radiated)	Junkosha Inc.	MWX221	2008S246	2025-02-21-
6	RF Cable (1 GHz - 18 GHz Radiated)	Junkosha Inc.	MWX221	J0970749	2025-02-21-
7	RF Cable (1 GHz - 18 GHz Radiated)	Sensorview Co., LTD	13A26	TPC2204060007	2025-02-21-
8	RF Cable (18GHz-26.5GHz Radiated)	HUBER+SUHNER	SUCOFLEX 102	MY2372/2	2025-02-21-
9	RF Cable (18GHz-26.5GHz Radiated)	Sensorview Co., LTD	9A40	TP210713-001	2025-02-21-

-END-