FCC Part 22H & 24E
Measurement and Test Report

For

FACTORYTECH S.A.

Km 16 Via Daule, Guayaquil- Ecuador

FCC ID: 2AFWX-Z45

FCC Rules:	FCC Part 22H, FCC Part 24E
Product Description:	Mobile phone
Tested Model:	Infineum Z45
Report No.:	STR15118297I-1
Tested Date:	2015-11-22 to 2015-12-19
Issued Date:	2015-12-21
Tested By:	Silin Chen / EMC Manager
Reviewed By:	Suan Su / Engineer
Approved & Authorized By:	Jandy So / PSQ Manager

Prepared By:

Shenzhen SEM.Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C.（518101）
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM. Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION 3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 3
1.2 TEST STANDARDS 5
1.3 TEST METHODOLOGY 5
1.4 TEST FACILITY 5
1.5 EUT SETUP AND TEST MODE 6
1.6 TEST EQUIPMENT LIST AND DETAILS 7
2. SUMMARY OF TEST RESULTS 8
3. RF EXPOSURE 9
3.1 STANDARD APPLICABLE 9
3.2 TEST RESULT 9
4. RF OUTPUT POWER 10
4.1 STANDARD APPLICABLE 10
4.2 TEST PROCEDURE 10
4.3 ENVIRONMENTAL CONDITIONS 10
4.4 SUMMARY OF TEST RESULTS/PLOTS 11
5. PEAK-TO-AVERAGE RADIO (PAR) OF TRANSMITTER 19
5.1 STANDARD APPLICABLE 19
5.2 TEST PROCEDURE 19
5.3 ENVIRONMENTAL CONDITIONS 19
5.4 SUMMARY OF TEST RESULTS 20
6. EMISSION BANDWIDTH 21
6.1 STANDARD APPLICABLE 21
6.2 TEST PROCEDURE 21
6.3 ENVIRONMENTAL CONDITIONS 21
6.4 SUMMARY OF TEST RESULTS/PLOTS 22
7. OUT OF BAND EMISSIONS AT ANTENNA TERMINAL 42
7.1 STANDARD APPLICABLE 42
7.2 TEST PROCEDURE 42
7.3 ENVIRONMENTAL CONDITIONS 42
7.4 SUMMARY OF TEST RESULTS/PLOTS 43
8. SPURIOUS RADIATED EMISSIONS 91
8.1 MEASUREMENT UNCERTAINTY 91
8.2 STANDARD APPLICABLE 91
8.3 TEST PROCEDURE 91
8.4 ENVIRONMENTAL CONDITIONS 91
8.5 SUMMARY OF TEST RESULTS/PLOTS 91
9. FREQUENCY STABILITY 101
9.1 STANDARD APPLICABLE 101
9.2 TEST PROCEDURE 101
9.3 ENVIRONMENTAL CONDITIONS 101
9.4 SUMMARY OF TEST RESULTS/PLOTS 102

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: FACTORYTECH S.A.
Address of applicant: Km 16 Via Daule, Guayaquil- Ecuador

Manufacturer: FACTORYTECH S.A.
Address of manufacturer: Km 16 Via Daule, Guayaquil- Ecuador

General Description of EUT:	
Product Name:	Mobile phone
Brand Name:	PIXELA
Model No.:	Infineum Z45
Rated Voltage:	DC 3.8V Li-ion Battery
Battery Capacity:	1800mAh
Device Category:	Portable Device
The EUT Main board support GSM850/PCS1900, WCDMA Band 2/5, LTE Band 2/4/7 function. It is intended for speech, Multimedia Message Service (MMS) transmission. It is equipped with GPRS/EDGE class 12 for GSM850//PCS1900, GPS, Bluetooth and Wi-Fi functions. For more information see the following datasheet	
Note: The test data is gathered from a production sample provided by the manufacturer.	

Technical Characteristics of EUT:	
2G	
Support Networks:	GSM, GPRS, EDGE
Support Band:	GSM850/PCS1900
Uplink Frequency:	GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz
Downlink Frequency:	GSM/GPRS/EDGE 850: 869~894MHz GSM/GPRS/EDGE 1900: 1930~1990MHz
Max RF Output Power:	GSM850: 32.13dBm, GSM1900: 29.01dBm EDGE850: 25.87dBm, EDGE1900: 24.93dBm
Type of Emission:	GSM850: 259KGXW, GSM1900: 259KGXW EDGE850: 265KG7W, EDGE1900: 257KG7W
Type of Modulation:	GMSK, 8PSK
Type of Antenna:	Integral Antenna
Antenna Gain:	GSM850: 0.63dBi, GSM1900: 1.11dBi
GPRS/EDGE Class:	Class 12
3G	
Support Networks:	WCDMA, HSDPA, HSUPA
Support Band:	WCDMA Band 2, WCDMA Band 5
Uplink Frequency:	WCDMA Band 2: 1850~1910MHz WCDMA Band 5: 824~849MHz
Downlink Frequency:	WCDMA Band 2: 1930~1990MHz WCDMA Band 5: 869~894MHz
RF Output Power:	WCDMA Band 2: 21.78dBm, WCDMA Band 5: 22.02dBm
Type of Emission:	WCDMA Band 2: 4M18F9W WCDMA Band 5: 4M16F9W
Type of Modulation:	BPSK
Antenna Type:	Integral Antenna
Antenna Gain:	WCDMA Band 2: 1.12dBi, WCDMA Band 5: 0.58dBi

1.2 Test Standards

The following report is prepared on behalf of the FACTORYTECH S.A. in accordance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E and FCC Part 27 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 2 subpart J, FCC Part 22 subpart H and FCC Part 24 subpart E and FCC Part 27 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI/TIA-603-D: 2010 and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

- **FCC – Registration No.: 934118**
  Shenzhen SEM.Test Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files and the Registration is 934118.

- **Industry Canada (IC) Registration No.: 11464A**
  The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

- **CNAS Registration No.: L4062**
  Shenzhen SEM.Test Technology Co., Ltd. is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L4062. All measurement facilities used to collect the measurement data are located at 1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road, Bao'an District, Shenzhen, P.R.C (518101)

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	GSM 850	Low, Middle, High Channels
TM2	GPRS 850	Low, Middle, High Channels
TM3	EDGE 850	Low, Middle, High Channels
TM4	GSM 1900	Low, Middle, High Channels
TM5	GPRS 1900	Low, Middle, High Channels
TM6	EDGE 1900	Low, Middle, High Channels
TM7	WCDMA Band 5	Low, Middle, High Channels
TM8	HSDPA Band 5	Low, Middle, High Channels
TM9	HSUPA Band 5	Low, Middle, High Channels
TM10	WCDMA Band 2	Low, Middle, High Channels
TM11	HSDPA Band 2	Low, Middle, High Channels
TM12	HSUPA Band 2	Low, Middle, High Channels

Testing Configure			
Support Band	Support Standard	Channel Frequency	Channel Number
GSM 850	GSM/GPRS/EDGE	824.2 MHz	128
		836.6 MHz	190
		848.8 MHz	251
PCS 1900	GSM/GPRS/EDGE	1850.2 MHz	512
		1880.0 MHz	661
		1909.8 MHz	810
WCDMA Band 5	WCDMA/HSDPA/HSUPA	826.4 MHz	4132
		836.6 MHz	4183
		846.6 MHz	4233
WCDMA Band 2	WCDMA/HSDPA/HSUPA	1852.4 MHz	9262
		1880.0 MHz	9400
		1907.6 MHz	9538
Note: the transmitter has been tested on the communications mode of GSM, GPRS, EDGE, WCDMA, HSDPA, HSUPA compliance test and record the worst case.			

EUT Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
USB Cable	1.0	Shielded	Without Ferrite
Earphone Cable	1.2	Unshielded	Without Ferrite

Auxiliary Equipment List and Details

Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E10	LR-63C8R

Special Cable List and Details

Cable Description	Length (M)	Shielded/Unshielded	With Core/Without Core
/	/	/	/

1.6 Test Equipment List and Details

Kind of Equipment	Manufacturer	Type	S/N	Cal Date	Due Date
Equipment list of < Shenzhen SEM.Test Technology Co., Ltd.>					
Test SIM card	-		-	N/A	
GSM Tester	Rohde & Schwarz	CMU200	104036	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	E4407B	MY41440400	2015-06-17	2016-06-16
Spectrum Analyzer	Agilent	N9020A	US47140102	2015-06-17	2016-06-16
Signal Generator	Agilent	83752A	3610A01453	2015-06-17	2016-06-16
Vector Signal Generator	Agilent	N5182A	MY47070202	2015-06-17	2016-06-16
Power Divider	Weinschel	1506A	PM204	2015-06-17	2016-06-16
Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2015-06-17	2016-06-16
Spectrum Analyzer	Rohde & Schwarz	FSP	836079/035	2015-06-17	2016-06-16
EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2015-06-17	2016-06-16
Amplifier	Agilent	8447F	3113A06717	2015-06-17	2016-06-16
Amplifier	C&D	PAP-1G18	2002	2015-06-17	2016-06-16
Broadband Antenna	Schwarz beck	VULB9163	9163-333	2015-06-17	2016-06-16
Horn Antenna	ETS	3117	00086197	2015-06-17	2016-06-16
Horn Antenna	ETS	3116B	00088203	2015-06-17	2016-06-16

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 1.1307, § 2.1093	RF Exposure	Compliant
§ 22.913 (a), § 24.232 (c)	RF Output Power	Compliant
§ 24.51	Peak-to-average Radio (PAR) of Transmitter	Compliant
§ 22.917 (b), § 24.238 (b)	Emission Bandwidth	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliant
§ 22.917 (a), § 24.238 (a)	Spurious Radiation Emissions	Compliant
§ 22.917 (a), § 24.238 (a)	Out of Band Emissions	Compliant
§ 22.355, § 24.235	Frequency Stability	Compliant

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the SAR report.

4. RF Output Power

4.1 Standard Applicable

According to §22.913(a)(2), The ERP of mobile and portable stations transmitters and auxiliary test transmitters must not exceed 7 Watts.

According to §24.232 (c), Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

4.2 Test Procedure

Conducted output power test method:



Radiated power test method:

1.The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.

4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

4.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

4.4 Summary of Test Results/Plots

Max. Radiated Power

ERP For GSM Mode GSM850

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	30.24	1.5	0	H	1.5	0	28.74	38.45
824.2	30.78	1.5	0	V	1.5	0	29.28	38.45
Middle Channel								
836.4	29.73	1.5	0	H	1.5	0	28.23	38.45
836.4	30.51	1.5	0	V	1.5	0	29.01	38.45
High Channel								
848.8	29.62	1.5	0	H	1.5	0	28.12	38.45
848.8	30.53	1.5	0	V	1.5	0	29.03	38.45

EIRP For GSM Mode PCS1900

Frequency	Substitute SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	20.73	1.5	0	H	1.9	7.7	26.53	33.00
1850.2	22.62	1.5	0	V	1.9	7.7	28.42	33.00
Middle Channel								
1880.0	20.53	1.5	0	H	1.9	7.7	26.33	33.00
1880.0	22.65	1.5	0	V	1.9	7.7	28.45	33.00
High Channel								
1909.8	20.51	1.5	0	H	1.9	7.7	26.31	33.00
1909.8	22.72	1.5	0	V	1.9	7.7	28.52	33.00

ERP For GPRS Mode GSM850

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	29.61	1.5	0	H	1.5	0	28.11	38.45
824.2	31.12	1.5	0	V	1.5	0	29.62	38.45
Middle Channel								
836.6	29.72	1.5	0	H	1.5	0	28.22	38.45
836.6	30.73	1.5	0	V	1.5	0	29.23	38.45
High Channel								
848.8	29.62	1.5	0	H	1.5	0	28.12	38.45
848.8	30.72	1.5	0	V	1.5	0	29.22	38.45

EIRP For GPRS Mode PCS1900

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	18.42	1.5	0	H	1.9	7.7	24.22	33.00
1850.2	19.83	1.5	0	V	1.9	7.7	25.63	33.00
Middle Channel								
1880.0	18.43	1.5	0	H	1.9	7.7	24.23	33.00
1880.0	19.64	1.5	0	V	1.9	7.7	25.44	33.00
High Channel								
1909.8	18.32	1.5	0	H	1.9	7.7	24.12	33.00
1909.8	19.43	1.5	0	V	1.9	7.7	25.23	33.00

ERP For EDGE Mode GSM850

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	dBm	dBm
Low Channel								
824.2	23.84	1.5	0	H	1.5	0	22.34	38.45
824.2	25.82	1.5	0	V	1.5	0	24.32	38.45
Middle Channel								
836.6	23.84	1.5	0	H	1.5	0	22.34	38.45
836.6	26.05	1.5	0	V	1.5	0	24.55	38.45
High Channel								
848.8	23.81	1.5	0	H	1.5	0	22.31	38.45
848.8	26.12	1.5	0	V	1.5	0	24.62	38.45

EIRP For EDGE Mode PCS1900

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1850.2	15.53	1.5	0	H	1.9	7.7	21.33	33.00
1850.2	17.51	1.5	0	V	1.9	7.7	23.31	33.00
Middle Channel								
1880.0	15.31	1.5	0	H	1.9	7.7	21.11	33.00
1880.0	17.52	1.5	0	V	1.9	7.7	23.32	33.00
High Channel								
1909.8	15.43	1.5	0	H	1.9	7.7	21.23	33.00
1909.8	17.53	1.5	0	V	1.9	7.7	23.33	33.00

ERP For WCDMA Mode Band 5

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	19.84	1.5	0	H	1.5	0	18.34	38.45
826.4	21.62	1.5	0	V	1.5	0	20.12	38.45
Middle Channel								
836.6	19.05	1.5	0	H	1.5	0	17.55	38.45
836.6	20.82	1.5	0	V	1.5	0	19.32	38.45
High Channel								
846.6	19.69	1.5	0	H	1.5	0	18.19	38.45
846.6	20.84	1.5	0	V	1.5	0	19.34	38.45

ERP For HSDPA Mode Band 5

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	19.73	1.5	0	H	1.5	0	18.23	38.45
826.4	20.83	1.5	0	V	1.5	0	19.33	38.45
Middle Channel								
836.6	20.02	1.5	0	H	1.5	0	18.52	38.45
836.6	20.84	1.5	0	V	1.5	0	19.34	38.45
High Channel								
846.6	18.84	1.5	0	H	1.5	0	17.34	38.45
846.6	21.13	1.5	0	V	1.5	0	19.63	38.45

ERP For HSUPA Mode Band 5

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 22H Limit
MHz	dBm	Meter	Degree	H / V	dB	dBd	dBm	dBm
Low Channel								
826.4	19.73	1.5	0	H	1.5	0	18.23	38.45
826.4	20.84	1.5	0	V	1.5	0	19.34	38.45
Middle Channel								
836.6	19.83	1.5	0	H	1.5	0	18.33	38.45
836.6	20.59	1.5	0	V	1.5	0	19.09	38.45
High Channel								
846.6	19.82	1.5	0	H	1.5	0	18.32	38.45
846.6	20.84	1.5	0	V	1.5	0	19.34	38.45

EIRP For WCDMA Mode Band 2

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	13.42	1.5	0	H	1.9	7.7	19.22	33
1852.4	14.39	1.5	0	V	1.9	7.7	20.19	33
Middle Channel								
1880.0	12.62	1.5	0	H	1.9	7.7	18.42	33
1880.0	13.54	1.5	0	V	1.9	7.7	19.34	33
High Channel								
1907.6	12.62	1.5	0	H	1.9	7.7	18.42	33
1907.6	13.82	1.5	0	V	1.9	7.7	19.62	33

EIRP For HSDPA Mode Band 2

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	12.42	1.5	0	H	1.9	7.7	18.22	33
1852.4	13.51	1.5	0	V	1.9	7.7	19.31	33
Middle Channel								
1880.0	11.54	1.5	0	H	1.9	7.7	17.34	33
1880.0	12.83	1.5	0	V	1.9	7.7	18.63	33
High Channel								
1907.6	12.64	1.5	0	H	1.9	7.7	18.44	33
1907.6	12.84	1.5	0	V	1.9	7.7	18.64	33

EIRP For HSUPA Mode Band 2

Frequency	Substitude SG	Height	Table	Polar	Cable loss	Antenna Gain	Result	FCC Part 24E Limit
MHz	dBm	Meter	Degree	H / V	dB	dB	DBm	dBm
Low Channel								
1852.4	11.64	1.5	0	H	1.9	7.7	17.44	33
1852.4	13.56	1.5	0	V	1.9	7.7	19.36	33
Middle Channel								
1880.0	11.46	1.5	0	H	1.9	7.7	17.26	33
1880.0	13.72	1.5	0	V	1.9	7.7	19.52	33
High Channel								
1907.6	11.64	1.5	0	H	1.9	7.7	17.44	33
1907.6	13.65	1.5	0	V	1.9	7.7	19.45	33

Note: Result = Substitude - Cable loss + Antenna Gain

Max. Conducted Output Power

For Cellular Band (GSM850)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
GSM	Low Channel	824.2	32.01	38.45
	Middle Channel	836.6	32.13	38.45
	High Channel	848.8	31.59	38.45
GPRS(1 Slot)	Low Channel	824.2	31.31	38.45
	Middle Channel	836.6	31.65	38.45
	High Channel	848.8	31.57	38.45
EDGE(1 Slot)	Low Channel	824.2	25.87	38.45
	Middle Channel	836.6	25.62	38.45
	High Channel	848.8	25.72	38.45

For PCS Band (GSM1900)

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
GSM	Low Channel	1850.2	29.01	33.0
	Middle Channel	1880.0	28.45	33.0
	High Channel	1909.8	28.61	33.0
GPRS(1 Slot)	Low Channel	1850.2	28.88	33.0
	Middle Channel	1880.0	28.62	33.0
	High Channel	1909.8	28.50	33.0
EDGE(1 Slot)	Low Channel	1850.2	24.93	33.0
	Middle Channel	1880.0	24.84	33.0
	High Channel	1909.8	24.55	33.0

For WCDMA Band 5

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 22.913 Limit (dBm)
WCDMA	Low Channel	826.4	22.02	38.45
	Middle Channel	836.6	21.86	38.45
	High Channel	846.6	21.89	38.45
HSDPA	Low Channel	826.4	21.34	38.45
	Middle Channel	836.6	21.63	38.45
	High Channel	846.6	21.42	38.45
HSUPA	Low Channel	826.4	21.57	38.45
	Middle Channel	836.6	21.33	38.45
	High Channel	846.6	21.46	38.45

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	Average Power (dBm)	FCC Part 24.232 Limit (dBm)
WCDMA	Low Channel	1852.4	21.78	33.00
	Middle Channel	1880.0	21.53	33.00
	High Channel	1907.6	21.63	33.00
HSDPA	Low Channel	1852.4	21.66	33.00
	Middle Channel	1880.0	21.24	33.00
	High Channel	1907.6	21.29	33.00
HSUPA	Low Channel	1852.4	21.32	33.00
	Middle Channel	1880.0	21.12	33.00
	High Channel	1907.6	20.94	33.00

5. Peak-to-average Radio (PAR) of Transmitter

5.1 Standard Applicable

According to §24.232(d), Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

5.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the peak-to-average ratio (PAR) of the transmission was recorded.

Test Configuration for the emission bandwidth testing:



5.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

5.4 Summary of Test Results

For PCS Band

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
GSM	512	1850.2	31.79	29.01	2.78	13
	661	1880.0	31.44	28.45	2.99	13
	810	1909.8	31.66	28.61	3.05	13
GPRS (1 Slot)	512	1850.2	31.43	28.88	2.55	13
	661	1880.0	30.45	28.62	1.83	13
	810	1909.8	30.73	28.50	2.23	13
EDGE (1 Slot)	512	1850.2	26.86	24.93	1.93	13
	661	1880.0	26.63	24.84	1.79	13
	810	1909.8	26.64	24.55	2.09	13

For WCDMA Band 2

Test Mode	Channel	Frequency (MHz)	Peak Power (dBm)	Average Power (dBm)	PAR (dB)	Limit (dB)
WCDMA	9262	1852.4	24.53	21.78	2.75	13
	9400	1880.0	24.35	21.53	2.82	13
	9538	1907.6	24.32	21.63	2.69	13
HSDPA	9262	1852.4	24.41	21.66	2.75	13
	9400	1880.0	24.34	21.24	3.1	13
	9538	1907.6	23.31	21.29	2.02	13
HSUPA	9262	1852.4	23.62	21.32	2.3	13
	9400	1880.0	23.74	21.12	2.62	13
	9538	1907.6	23.68	20.94	2.74	13

6. Emission Bandwidth

6.1 Standard Applicable

According to §22.917(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §24.238(b), The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

According to §27.53, The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

6.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 30kHz and the 26dB bandwidth was recorded.

Test Configuration for the emission bandwidth testing:



6.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

6.4 Summary of Test Results/Plots

For Cellular Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	128	824.2	259.2102	334.896
	190	836.6	254.1985	339.343
	251	848.8	251.3081	337.482
GPRS	128	824.2	256.3382	340.158
	190	836.6	255.0411	334.599
	251	848.8	252.5709	336.062
EDGE	128	824.2	258.8848	339.700
	190	836.6	259.8724	343.378
	251	848.8	265.1020	343.838

For PCS Band

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM	512	1850.2	250.5795	334.597
	661	1880.0	259.0225	338.380
	810	1909.8	256.5288	334.597
GPRS	512	1850.2	253.7786	335.265
	661	1880.0	256.5494	330.187
	810	1909.8	250.6550	337.357
EDGE	512	1850.2	257.3682	331.464
	661	1880.0	253.0496	320.620
	810	1909.8	250.8665	319.469

For Band 5

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	4132	826.4	4.1466	4.615
	4183	836.6	4.1531	4.643
	4233	846.6	4.1300	4.607
HSDPA	4132	826.4	4.1473	4.605
	4183	836.6	4.1480	4.617
	4233	846.6	4.1412	4.606
HSUPA	4132	826.4	4.1474	4.628
	4183	836.6	4.1403	4.623
	4233	846.6	4.1605	4.602

For Band 2

Test Mode	Channel	Frequency (MHz)	99% Emission Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
WCDMA	9262	1852.4	4.1717	4.622
	9400	1880.0	4.1551	4.595
	9538	1907.6	4.1839	4.727
HSDPA	9262	1852.4	4.1561	4.606
	9400	1880.0	4.1492	4.588
	9538	1907.6	4.1746	4.611
HSUPA	9262	1852.4	4.1409	4.601
	9400	1880.0	4.1505	4.621
	9538	1907.6	4.1335	4.593

For Cellular Band

GSM Low Channel



GSM Middle Channel



GSM High channel



GPRS Low Channel



GPRS Middle Channel



GPRS High Channel



EDGE Low Channel



EDGE Middle Channel



EDGE High Channel



For PCS Band

GSM Low Channel



GSM Middle Channel



GSM High channel



GPRS Low Channel



GPRS Middle Channel



GPRS High Channel



EDGE Low Channel



EDGE Middle Channel



EDGE High Channel



For Band 5

WCDMA Low Channel



WCDMA Middle Channel



WCDMA High Channel



HSDPA Low Channel



HSDPA Middle Channel



HSDPA High Channel



HSUPA Low Channel



HSUPA Middle Channel



HSUPA High Channel



For Band 2

WCDMA Low Channel



WCDMA Middle Channel



WCDMA High Channel



HSDPA Low Channel



HSDPA Middle Channel



HSDPA High Channel



HSUPA Low Channel



HSUPA Middle Channel



HSUPA High Channel



7. Out of Band Emissions at Antenna Terminal

7.1 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least 43 + 10 log10 (P) dB.

7.2 Test Procedure

The RF output terminal of the transmitter was connected to the input of the spectrum analyzer via a suitable attenuation. The RBW of the spectrum analyzer was set to 100kHz and 1MHz for the scan frequency from 30MHz to 1GHz and the scan frequency from 1GHz to up to 10th harmonic.

Test Configuration for the out of band emissions testing:



7.3 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	53%
ATM Pressure:	1018 mbar

7.4 Summary of Test Results/Plots

Please refer to the following test plots For Cellular Band

Please refer to the following test plots For Cellular Band
GSM Low Channel 30MHz to 1GHz



Above 1GHz



GSM Middle Channel
30MHz to 1GHz



Above 1GHz



GSM High Channel
30MHz to 1GHz



Above 1GHz



GSM Low Band Emission



GSM High Band Emission



GPRS Low Channel
30MHz to 1GHz



Above 1GHz



GPRS Middle Channel
30MHz to 1GHz



Above 1GHz



GPRS High Channel
30MHz to 1GHz



Above 1GHz



GPRS Low Band Emission



GPRS High Band Emission



EDGE Low Channel
30MHz to 1GHz



Above 1GHz



EDGE Middle Channel
30MHz to 1GHz



Above 1GHz



EDGE High Channel
30MHz to 1GHz



Above 1GHz



EDGE Low Band Emission



EDGE High Band Emission



For PCS Band
GSM Low Channel
30MHz to 1GHz



Above 1GHz



GSM Middle Channel
30MHz to 1GHz



Above 1GHz



GSM High Channel
30MHz to 1GHz



Above 1GHz



GSM Low Band Emission



GSM High Band Emission



GPRS Low Channel
30MHz to 1GHz



Above 1GHz



GPRS Middle Channel
30MHz to 1GHz



Above 1GHz



GPRS High Channel
30MHz to 1GHz



Above 1GHz



GPRS Low Band Emission



GPRS High Band Emission



EDGE Low Channel
30MHz to 1GHz



Above 1GHz



EDGE Middle Channel
30MHz to 1GHz



Above 1GHz



EDGE High Channel
30MHz to 1GHz



Above 1GHz



EDGE Low Band Emission



EDGE High Band Emission



For Band 5
WCDMA Low Channel
30MHz to 1GHz



Above 1GHz



WCDMA Middle Channel
30MHz to 1GHz



Above 1GHz



WCDMA High Channel
30MHz to 1GHz



Above 1GHz



WCDMA Low Band Spurious Emission



WCDMA High Band Spurious Emission



HSDPA Low Channel
30MHz to 1GHz



Above 1GHz



HSDPA Middle Channel
30MHz to 1GHz



Above 1GHz



HSDPA High Channel
30MHz to 1GHz



Above 1GHz



HSDPA Low Band Spurious Emission



HSDPA High Band Spurious Emission



HSUPA Low Channel
30MHz to 1GHz



Above 1GHz



HSUPA Middle Channel
30MHz to 1GHz



Above 1GHz



HSUPA High Channel
30MHz to 1GHz



Above 1GHz



HSUPA Low Band Spurious Emission



HSUPA High Band Spurious Emission



For Band 2
WCDMA Low Channel
30MHz to 1GHz



Above 1GHz



WCDMA Middle Channel
30MHz to 1GHz



Above 1GHz



WCDMA High Channel
30MHz to 1GHz



Above 1GHz



WCDMA Low Band Spurious Emission



WCDMA High Band Spurious Emission



HSDPA Low Channel
30MHz to 1GHz



Above 1GHz



HSDPA Middle Channel
30MHz to 1GHz



Above 1GHz



HSDPA High Channel
30MHz to 1GHz



Above 1GHz



HSDPA Low Band Spurious Emission



HSDPA High Band Spurious Emission



HSUPA Low Channel
30MHz to 1GHz



Above 1GHz



HSUPA Middle Channel
30MHz to 1GHz



Above 1GHz



HSUPA High Channel
30MHz to 1GHz



Above 1GHz



HSUPA Low Band Spurious Emission



Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
The measurements greater than 20dB below the limit from 9kHz to 30MHz, so the data is not display.

8. Spurious Radiated Emissions

8.1 Measurement Uncertainty

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement is ±5.20 dB.

8.2 Standard Applicable

According to §22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.

According to §27.53 (h), the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least 43 + 10 log10 (P) dB.

8.3 Test Procedure

1. The setup of EUT is according with per ANSI/TIA-603-D: 2010 and ANSI C63.4-2014 measurement procedure.
2. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
3. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
4. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious attenuation limit in dB =43+10 Log_{10} (power out in Watts)

8.4 Environmental Conditions

Temperature:	25 °C
Relative Humidity:	52%
ATM Pressure:	1012 mbar

8.5 Summary of Test Results/Plots

According to the data below, the FCC Part 22.917 and 24.238 standards, and had the worst margin of:

Note: this EUT was tested in 3 orthogonal positions and the worst case position (Vertical) data was reported.

For Cellular Band_ GSM850 Mode

Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	Factor(dB)	(dBm)	(dBm)	(dB)	
1	57.1914	-68.26	1.95	-66.31	-13.00	-53.31	ERP
2	116.1321	-69.48	1.25	-68.23	-13.00	-55.23	ERP
3	372.0045	-69.75	8.67	-61.08	-13.00	-48.08	ERP
4	779.6068	-69.37	15.92	-53.45	-13.00	-40.45	ERP

Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	Factor(dB)	(dBm)	(dBm)	(dB)	
1	47.1599	-68.78	3.03	-65.75	-13.00	-52.75	ERP
2	83.5222	-69.10	-0.38	-69.48	-13.00	-56.48	ERP
3	364.2595	-69.19	8.64	-60.55	-13.00	-47.55	ERP
4	711.6734	-68.69	14.83	-53.86	-13.00	-40.86	ERP

For Cellular Band_ GSM1900 Mode

Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	Factor(dB)	(dBm)	(dBm)	(dB)	
1	52.9453	-68.21	2.83	-65.38	-13.00	-52.38	ERP
2	213.7634	-69.85	4.16	-65.69	-13.00	-52.69	ERP
3	649.6597	-69.15	14.03	-55.12	-13.00	-42.12	ERP
4	922.5157	-68.71	17.59	-51.12	-13.00	-38.12	ERP

Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	Factor(dB)	(dBm)	(dBm)	(dB)	
1	126.7723	-68.26	1.12	-67.14	-13.00	-54.14	ERP
2	228.4904	-68.71	4.95	-63.76	-13.00	-50.76	ERP
3	344.3855	-68.71	8.42	-60.29	-13.00	-47.29	ERP
4	670.4893	-68.41	14.30	-54.11	-13.00	-41.11	ERP

For band 5 Mode

Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	Factor(dB)	(dBm)	(dBm)	(dB)	
1	49.5328	-69.36	3.38	-65.98	-13.00	-52.98	ERP
2	201.3930	-68.35	3.68	-64.67	-13.00	-51.67	ERP
3	245.0900	-69.10	5.50	-63.60	-13.00	-50.60	ERP
4	975.7529	-67.86	18.00	-49.86	-13.00	-36.86	ERP

Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	56.0007	-68.39	2.19	-66.20	-13.00	-53.20	ERP
2	356.6758	-68.73	8.66	-60.07	-13.00	-47.07	ERP
3	570.6100	-68.44	12.59	-55.85	-13.00	-42.85	ERP
4	752.7432	-69.08	15.68	-53.40	-13.00	-40.40	ERP

For band 2 Mode

Horizontal:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	dB	(dBm)	(dBm)	(dB)	
1	135.5062	-68.93	0.98	-67.95	-13.00	-54.95	ERP
2	413.2706	-68.33	9.83	-58.50	-13.00	-45.50	ERP
3	839.1818	-67.22	16.50	-50.72	-13.00	-37.72	ERP

Vertical:



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBm)	Factor(dB)	(dBm)	(dBm)	(dB)	
1	42.4508	-69.64	2.34	-67.30	-13.00	-54.30	ERP
2	108.2667	-69.17	1.21	-67.96	-13.00	-54.96	ERP
3	455.9058	-68.80	10.32	-58.48	-13.00	-45.48	ERP
4	929.0082	-67.64	17.61	-50.03	-13.00	-37.03	ERP

Note: Margin= (Reading+ Correct)- Limit

Spurious Emissions Above 1GHz

Frequency (MHz)	Reading (dBm)	Correct dB	Result (dBm)	Limit (dBm)	Margin (dB)	Polar H/V
GSM850 Mode-Low Channel (worst case)						
1648.4	-49.46	4.94	-44.52	-13.00	-31.52	H
2472.6	-51.46	8.46	-43.00	-13.00	-30.00	H
1648.4	-50.06	4.94	-45.12	-13.00	-32.12	V
2472.6	-53.71	8.46	-45.25	-13.00	-32.25	V
GSM1900 Mode-Low Channel (worst case)						
3700.4	-54.90	10.54	-44.36	-13.00	-31.36	H
5550.6	-57.62	13.37	-44.25	-13.00	-31.25	H
3700.4	-53.90	10.54	-43.36	-13.00	-30.36	V
5550.6	-57.62	13.37	-44.25	-13.00	-31.25	V
Band 5 Mode-Low Channel (worst case)						
1652.8	-58.19	4.94	-53.25	-13	-40.25	H
2479.2	-58.71	8.46	-50.25	-13	-37.25	H
1652.8	-57.16	4.94	-52.22	-13	-39.22	V
2479.2	-58.39	8.46	-49.93	-13	-36.93	V
Band 2 Mode-Low Channel (worst case)						
3704.8	-57.55	10.17	-47.38	-13	-34.38	H
5557.2	-58.11	14.69	-43.42	-13	-30.42	H
3704.8	-58.61	10.17	-48.44	-13	-35.44	V
5557.2	-58.84	14.69	-44.15	-13	-31.15	V

Note: Result=Reading+ Correct, Margin= Result- Limit

Testing is carried out with frequency rang 9kHz to 20GHz, which above 3th Harmonics are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
The measurements greater than 20dB below the limit from 9kHz to 30MHz.so the data is not display.

9. Frequency Stability

9.1 Standard Applicable

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Cellular Band

Frequency range (MHz)	Base, fixed (ppm)	Mobile ≤3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929	5.0	N/A	N/A
929 to 960	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A

According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

According to §27.54 The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

9.2 Test Procedure

According to §2.1055, the following test procedure was performed.
The Frequency Stability is measured directly with a Frequency Domain Analyzer. Frequency Deviation in ppm is calculated from the measured peak to peak value.
The Carrier Frequency Stability over Power Supply Voltage and over Temperature is measured with a Frequency Domain Analyzer in histogram mode

Temperature:	Supply Voltage
20°C	85-115% of declared nominal voltage
-30°C to +50°C	Normal

9.3 Environmental Conditions

Temperature:	20°C
Relative Humidity:	54%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

For Cellular Band GSM Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	77	0.0920
40	3.8	65	0.0777
30	3.8	52	0.0622
20	3.8	48	0.0574
10	3.8	37	0.0442
0	3.8	26	0.0311
-10	3.8	48	0.0574
-20	3.8	61	0.0729
-30	3.8	71	0.0849

For PCS Band GSM Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.8	73	0.0388
40	3.8	51	0.0271
30	3.8	42	0.0223
20	3.8	32	0.0170
10	3.8	22	0.0117
0	3.8	15	0.0080
-10	3.8	32	0.0170
-20	3.8	42	0.0223
-30	3.8	62	0.0330

For Cellular Band GPRS Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	53	0.0634
40	3.7	45	0.0538
30	3.7	40	0.0478
20	3.7	26	0.0311
10	3.7	17	0.0203
0	3.7	13	0.0155
-10	3.7	30	0.0359
-20	3.7	36	0.0430
-30	3.7	51	0.0610

For PCS Band GPRS Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	62	0.0330
40	3.7	43	0.0229
30	3.7	32	0.0170
20	3.7	21	0.0112
10	3.7	21	0.0112
0	3.7	15	0.0080
-10	3.7	25	0.0133
-20	3.7	35	0.0186
-30	3.7	57	0.0303

For Cellular Band EDGE Mode

Reference Frequency(Middle Channel): 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	52	0.0622
40	3.7	48	0.0574
30	3.7	41	0.0490
20	3.7	32	0.0383
10	3.7	16	0.0191
0	3.7	10	0.0120
-10	3.7	26	0.0311
-20	3.7	35	0.0418
-30	3.7	49	0.0586

For PCS Band EDGE Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	63	0.0753
40	3.7	53	0.0634
30	3.7	42	0.0502
20	3.7	28	0.0335
10	3.7	23	0.0275
0	3.7	15	0.0179
-10	3.7	29	0.0347
-20	3.7	43	0.0514
-30	3.7	62	0.0741

For WCDMA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	58	0.0693
40	3.7	51	0.0610
30	3.7	38	0.0454
20	3.7	32	0.0383
10	3.7	21	0.0251
0	3.7	16	0.0191
-10	3.7	22	0.0263
-20	3.7	32	0.0383
-30	3.7	43	0.0514

For WCDMA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	47	0.0562
40	3.7	34	0.0406
30	3.7	26	0.0311
20	3.7	19	0.0227
10	3.7	13	0.0155
0	3.7	30	0.0359
-10	3.7	41	0.0490
-20	3.7	53	0.0634
-30	3.7	67	0.0801

For HSDPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	64	0.0765
40	3.7	48	0.0574
30	3.7	47	0.0562
20	3.7	36	0.0430
10	3.7	25	0.0299
0	3.7	20	0.0239
-10	3.7	32	0.0383
-20	3.7	44	0.0526
-30	3.7	56	0.0670

For HSDPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	54	0.0645
40	3.7	47	0.0562
30	3.7	35	0.0418
20	3.7	31	0.0371
10	3.7	26	0.0311
0	3.7	21	0.0251
-10	3.7	35	0.0418
-20	3.7	43	0.0514
-30	3.7	56	0.0670

For HSUPA Band 5 Mode

Reference Frequency(Middle Channel): 836.6 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	65	0.0777
40	3.7	51	0.0610
30	3.7	43	0.0514
20	3.7	37	0.0442
10	3.7	27	0.0323
0	3.7	22	0.0263
-10	3.7	24	0.0287
-20	3.7	36	0.0430
-30	3.7	64	0.0765

For HSUPA Band 2 Mode

Reference Frequency(Middle Channel): 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		MCF (Hz)	Error (ppm)
50	3.7	52	0.0277
40	3.7	47	0.0250
30	3.7	32	0.0170
20	3.7	29	0.0154
10	3.7	26	0.0138
0	3.7	25	0.0133
-10	3.7	39	0.0207
-20	3.7	42	0.0223
-30	3.7	54	0.0287

So, Frequency Stability Versus Input Voltage is:

Reference Frequency(Middle Channel): GSM 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	39	0.0466
	3.7	21	0.0251
	4.2	37	0.0442

Reference Frequency(Middle Channel): GSM 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	34	0.0181
	3.7	14	0.0074
	4.2	22	0.0117

Reference Frequency(Middle Channel): GPRS 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	37	0.0442
	3.7	09	0.0108
	4.2	27	0.0323

Reference Frequency(Middle Channel): GPRS 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	43	0.0229
	3.7	34	0.0181
	4.2	47	0.0250

Reference Frequency(Middle Channel): EDGE 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	52	0.0622
	3.7	20	0.0239
	4.2	43	0.0514
Reference Frequency(Middle Channel): EDGE 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	52	0.0277
	3.7	25	0.0133
	4.2	51	0.0271
Reference Frequency(Middle Channel): WCDMA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	51	0.0610
	3.7	19	0.0227
	4.2	49	0.0586
Reference Frequency(Middle Channel): WCDMA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	51	0.0271
	3.7	21	0.0112
	4.2	48	0.0255
Reference Frequency(Middle Channel): HSDPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	49	0.0586
	3.7	25	0.0299
	4.2	51	0.0610

Reference Frequency(Middle Channel): HSDPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	36	0.0191
	3.7	16	0.0085
	4.2	48	0.0255
Reference Frequency(Middle Channel): HSUPA 836.6MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	37	0.0442
	3.7	19	0.0227
	4.2	41	0.0490
Reference Frequency(Middle Channel): HSUPA 1880 MHz, Limit: 2.5ppm			
Environment Temperature (°C)	Power Supplied (VDC)	Frequency Measure with Time Elapsed	
		Frequency (Hz)	Error (ppm)
20	3.3	44	0.0234
	3.7	16	0.0085
	4.2	35	0.0186

******* END OF REPORT *******