



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01



Certificate #6613.01

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	Xiaomi Communications Co.,Ltd.
Address:	#019, 9th Floor, Building 6, 33Xi' erqi Middle Road, Haidian District, Beijing, China

Manufacturer or Supplier:	Xiaomi Communications Co.,Ltd.
Address:	#019, 9th Floor, Building 6, 33Xi' erqi Middle Road, Haidian District, Beijing, China
Product:	2.4GHz WIFI+Bluetooth dual-mode module
Model Name:	MHCWB8G-B
FCC ID:	2AFZZ-MHCWB8G-B
Date of tests:	Sep. 24, 2025 ~ Oct. 27, 2025

The tests have been carried out according to the requirements of the following standard:

☒ FCC Part 15, Subpart C, Section 15.247

☒ ANSI C63.10-2020

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
 Date: Oct. 15, 2025	 Date: Oct. 27, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	5
1 SUMMARY OF TEST RESULTS.....	6
1.1 MEASUREMENT UNCERTAINTY	7
2 GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	11
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	11
2.3 DUTY CYCLE OF TEST SIGNAL	14
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
2.5 DESCRIPTION OF SUPPORT UNITS	15
3 TEST TYPES AND RESULTS.....	16
3.1 CONDUCTED EMISSION MEASUREMENT	16
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	16
3.1.2 TEST INSTRUMENTS.....	16
3.1.3 TEST PROCEDURES	17
3.1.4 DEVIATION FROM TEST STANDARD	17
3.1.5 TEST SETUP	18
3.1.6 EUT OPERATING CONDITIONS	18
3.1.7 TEST RESULTS	18
3.2 RADIATED EMISSION MEASUREMENT	19
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	19
3.2.2 TEST INSTRUMENTS.....	20
3.2.3 TEST PROCEDURES	21
3.2.4 DEVIATION FROM TEST STANDARD	21
3.2.5 TEST SETUP	22
3.2.6 EUT OPERATING CONDITIONS	23
3.2.7 TEST RESULTS	23
3.3 6 DB BANDWIDTH MEASUREMENT	81
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	81
3.3.2 TEST INSTRUMENTS.....	81
3.3.3 TEST PROCEDURE.....	82
3.3.4 DEVIATION FROM TEST STANDARD	82



**BUREAU
VERITAS**

Test Report No.: PSU-NQN2510130209RF01

3.3.5	TEST SETUP	82
3.3.6	EUT OPERATING CONDITIONS	82
3.3.7	TEST RESULTS	82
3.4	CONDUCTED OUTPUT POWER.....	83
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	83
3.4.2	TEST SETUP	83
3.4.3	TEST INSTRUMENTS	83
3.4.4	TEST PROCEDURES	83
3.4.5	DEVIATION FROM TEST STANDARD	83
3.4.6	EUT OPERATING CONDITIONS	83
3.4.7	TEST RESULTS	83
3.4.7.1	MAXIMUM PEAK OUTPUT POWER	83
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	84
3.5	POWER SPECTRAL DENSITY MEASUREMENT	85
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	85
3.5.2	TEST SETUP	85
3.5.3	TEST INSTRUMENTS	85
3.5.4	TEST PROCEDURE	85
3.5.5	DEVIATION FROM TEST STANDARD	85
3.5.6	EUT OPERATING CONDITION	85
3.5.7	TEST RESULTS	85
3.6	OUT OF BAND EMISSION MEASUREMENT	86
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	86
3.6.2	TEST SETUP	86
3.6.3	TEST INSTRUMENTS	86
3.6.4	TEST PROCEDURE	86
3.6.5	DEVIATION FROM TEST STANDARD	87
3.6.6	EUT OPERATING CONDITION	87
3.6.7	TEST RESULTS	87
3.7	ANTENNA REQUIREMENTS	88
3.7.1	STANDARD APPLICABLE	88
3.7.2	ANTENNA CONNECTED CONSTRUCTION	88
3.7.3	ANTENNA GAIN	88
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	88
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	88
6	APPENDIX1	89



7 APPENDIX2	96
WLAN 2.4G	96
DTS BANDWIDTH	96
TEST RESULT	96
TEST GRAPHS	98
OCCUPIED CHANNEL BANDWIDTH	116
TEST RESULT	116
TEST GRAPHS	118
MAXIMUM CONDUCTED OUTPUT POWER	136
TEST RESULT	136
MAXIMUM POWER SPECTRAL DENSITY	139
TEST RESULT	139
TEST GRAPHS	140
BAND EDGE MEASUREMENTS	149
TEST GRAPHS	149
CONDUCTED SPURIOUS EMISSION	152
TEST GRAPHS	152
DUTY CYCLE	160
TEST RESULT	160
TEST GRAPHS	161



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-NQN2510130209RF01	Original release	Oct. 27, 2025



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
15.207	AC Power Conducted Emission	N/A
15.205 15.209	Radiated Emissions	Compliance
15.247(d)	Out of band Emission Measurement	Compliance
15.247(a)(2)	6dB bandwidth	Compliance
15.247(b)	Conducted Output power	Compliance
15.247(e)	Power Spectral Density	Compliance
15.203	Antenna Requirement	Compliance

Note : 1.Except RSE other data please refer to Appendix 1 (for BLE) and Appendix 2 (for WIFI-2.4G).

*Test Lab Information Reference

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	2.4GHz WIFI+Bluetooth dual-mode module
BRAND NAME*	MI
MODEL NAME*	MHCWB8G-B
NOMINAL VOLTAGE*	3.3Vdc (DC supply)
MODULATION *	DSSS, OFDM, OFDMA, GFSK
TRANSMISSION RATE	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n(HT20)/ax(HE20): up to 144.4 Mbps 802.11n(HT40)/ax(HE40): up to 300 Mbps 802.11ax 20 (RU26/52/106/242): up to 286.8Mbps 802.11ax 40 (RU484): up to 573.5Mbps BT_LE: 1 Mbps
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20/40) 2402-2480MHz for BT-LE(GFSK) 2412-2462MHz for ax(20M RU26/52/106/242)/ax (40M RU484)
MAX. OUTPUT POWER	WLAN: 138.99mW (Maximum) BT-LE:4.655mW (Maximum) RU WLAN: 238.23mW (Maximum)
ANTENNA TYPE	PCB Antenna with 2.4dBi gain for WIFI PCB Antenna with 2.4dBi gain for BLE
Directional Gain:	N/A
Beamforming Directional Gain:	N/A
HW VERSION	V1.1
SW VERSION	V1.0.4
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

**NOTE:**

1. *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. The EUT incorporates a SISO function. Physically, the EUT provides one transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	1TX /1RX
802.11g	1TX /1RX
802.11n(HT20)/ax(HE20)	1TX /1RX
802.11n(HT40)/ax(HE40)	1TX /1RX
802.11ax (20MHz RU 26/52/106/242)	1TX /1RX
802.11ax (40MHz RU 26/52/106/242/484)	1TX /1RX
BT_LE(1MHz)	1TX /1RX

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
5. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.



2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20), 802.11ax20 (HE20); 802.11ax20 (RU 26/52/106/242):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40), 802.11ax40 (HE40); 802.11ax 40(RU 26/52/106/242/484):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	N/A	√	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
BT-LE	0 to 39	39	GFSK	1.0

**RADIATED EMISSION TEST (ABOVE 1GHz):**

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11ax HE40	3 to 9	3,6,9	OFDM	MCS0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11ax 40 (RU 26/52/106/242/484)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0

POWER LINE CONDUCTED EMISSION TEST

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
BT-LE	0 to 39	39	GFSK	1.0

**BANDEDGE MEASUREMENT:**

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11ax HE40	3 to 9	3,6,9	OFDM	MCS0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11ax 40 (RU 26/52/106/242/484)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0

**ANTENNA PORT CONDUCTED MEASUREMENT:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax HE20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
802.11ax HE40	3 to 9	3,6,9	OFDM	MCS0
802.11ax 20 (RU 26/52/106/242)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11ax 40 (RU 26/52/106/242/484)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1.0

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC3.3V DC Supply	Hanwen Xu
RE≥1G	23deg. C, 70%RH	DC3.3V DC Supply	Hanwen Xu
PLC	25deg. C, 52%RH	DC3.3V DC Supply	Hanwen Xu
APCM	25deg. C, 60%RH	DC3.6V By DC Supply	Hanwen Xu

2.3 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix1/2 Of this test report.



2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2020

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Mar.28,24	Mar.27,26
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Mar.28,24	Mar.27,26
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.27,25	Apr.26,26
CABLE	Rohde&Schwarz	W601	N/A	Apr.27,25	Apr.26,26

NOTE:

1. The test was performed in CE shielded room.

2. The calibration interval of the above test instruments is 12 /24months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

3.1.7 TEST RESULTS

N/A



3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,25	Aug.28,27
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Signal Generator	R&S	SMB100A	182185	Mar.29,24	Mar.28,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Aug.20,25	Aug.19,28
EMI TEST Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Jul.04,25	Jul.03,27
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.20,25	Aug.19,27
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Jul.15,24	Jul.14,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Mar.22,25	Mar.21,27
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Jul.08,25	Jul.07,27
WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Jul.31,25	Jul.30,27
Hygrothermograph	DELI	20210528	SZ014	Mar.18,25	Mar.17,27
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.26,25	Apr.25,26
CABLE	R&S	W12.14	N/A	Apr.26,25	Apr.25,26

- NOTE:**
1. The calibration interval of the above test instruments is 12/ 24/ 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Chamber.
 3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation




3.2.5 TEST SETUP

<Frequency Range 9KHz~30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

3.2.7 TEST RESULTS


Note 1: Both horizontal and vertical polarizations of the antenna are set to make the measurement.

Note 2: Three-axis equipment has been evaluated in test.

Note 3: The relevant tests have been performed in order to verify in which mode would have the worst features, the result show above is the worst case (Channel, Mode, Rate, Chain...).



Radiated Emission Band Edge for BLE




Carrier frequency (MHz): 2402

Channel No.:0

Test Mode: GFSK (LE 1Mbps)

Polarity: Vertical



Carrier frequency (MHz): 2402

Channel No.:0


Test Mode: GFSK (LE 1Mbps)

Polarity: Horizontal



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Carrier frequency (MHz): 2480

Channel No.:39

Test Mode: GFSK (LE 1Mbps)

Polarity: Vertical



Carrier frequency (MHz): 2480

Channel No.:39

Test Mode: GFSK (LE 1Mbps)

Polarity: Horizontal



Radiated Emission for BLE

After comparison, the worst case attitude is EUT lay down.

Determining Spurious Emissions Levels

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

Result = $P_{mea} + A_{Rpl}$

Sample calculation: $(8.25 \text{ dB}\mu\text{V/m}) = (25.15 \text{ BuV}) + (-16.9 \text{ dB/m})$, the corresponding frequency is 39.6515 MHz.

For GFSK (LE 1Mbps)

Channel No.: 0

Frequency (MHz)	Result (dBuV/m)	A_{Rpl} (dB)	P_{mea} (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
39.6515	8.25	-16.9	25.15	Vertical	40.0	31.75
79.082	10.02	-22.0	32.02	Vertical	40.0	29.98
169.1465	9.49	-19.6	29.09	Vertical	43.5	34.01
264.449	18.23	-15.3	33.53	Vertical	46.0	27.77
550.987	14.70	-7.7	22.40	Vertical	46.0	31.30
799.986	25.08	-4.1	29.18	Vertical	46.0	20.92

Channel No.: 19


Frequency (MHz)	Result (dBuV/m)	A_{Rpl} (dB)	P_{mea} (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
46.005	8.97	-16.1	25.07	Vertical	40.0	31.03
55.511	8.70	-16.3	25.00	Vertical	40.0	31.30
169.001	6.39	-19.6	25.99	Vertical	43.5	37.11
267.3105	18.33	-15.2	33.53	Vertical	46.0	27.67
537.698	14.88	-8.0	22.88	Vertical	46.0	31.12
799.986	25.02	-4.1	29.12	Vertical	46.0	20.98



BUREAU VERITAS Test Report No.: PSU-NQN2510130209RF01

Channel No.:39

Frequency (MHz)	Result (dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
49.6425	8.63	-15.6	24.23	Vertical	40.0	31.37
55.8505	8.82	-16.3	25.12	Vertical	40.0	31.18
111.771	8.60	-18.0	26.60	Vertical	43.5	34.90
268.6685	16.54	-15.1	31.64	Vertical	46.0	29.46
519.8985	14.47	-8.6	23.07	Vertical	46.0	31.53
799.986	24.94	-4.1	29.04	Vertical	46.0	21.06



Frequency Range: 9kHz -30MHz

Detector: QP mode

Note : The relevant tests have been performed in order to verify in which mode would have the worst features, the result show above is the worst case.




BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

LE 1Mbps


Channel No.:0



Frequency Range: 30MHz-1GHz

Detector: QP mode

Modulation type: GFSK (LE 1Mbps)



Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode

Huarui 7layers High Technology
(Suzhou) Co., Ltd.

Tower N, Innovation Center, 88 Zuyi Road, High-tech
District, Suzhou City, Anhui Province, China

Tel: +86 (0557) 368 1008




BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Modulation type: GFSK (LE 1Mbps)

Full Spectrum




Frequency Range: 3GHz-18GHz

Detector: Av mode and PK mode

Modulation type: GFSK (LE 1Mbps)

Full Spectrum



Frequency Range: 18GHz-26GHz

Detector: Av mode and PK mode

Modulation type: GFSK (LE 1Mbps)




BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Channel No.:19

Full Spectrum




Frequency Range: 30MHz-1GHz

Detector: QP mode

Modulation type: GFSK (LE 1Mbps)

Full Spectrum



Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode


Modulation type: GFSK (LE 1Mbps)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz-18GHz

Detector: Av mode and PK mode

Modulation type: GFSK (LE 1Mbps)

Full Spectrum



Frequency Range: 18GHz-26GHz

Detector: Av mode and PK mode


Modulation type: GFSK (LE 1Mbps)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01


Channel No.:39



Frequency Range: 30MHz-1GHz

Detector: QP mode

Modulation type: GFSK (LE 1Mbps)



Frequency Range: 1GHz-3GHz

Detector: Av mode and PK mode


Modulation type: GFSK (LE 1Mbps)



BUREAU
VERITAS


Test Report No.: PSU-NQN2510130209RF01

Full Spectrum



Frequency Range: 3GHz-18GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE 1Mbps)

Full Spectrum




Frequency Range: 18GHz-26GHz
Detector: Av mode and PK mode
Modulation type: GFSK (LE 1Mbps)



BUREAU VERITAS Test Report No.: PSU-NQN2510130209RF01

Radiated Emission Band Edge for WIFI




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11b

Polarization : V



Radiated Emission Band Edge

Channel No.:1


Test Mode: 802.11b

Polarization : H



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11b

Polarization : V



Radiated Emission Band Edge

Channel No.:11


Test Mode: 802.11b

Polarization : H



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11g

Polarization : V



Radiated Emission Band Edge

Channel No.:1


Test Mode: 802.11g

Polarization : H



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11g

Polarization : V



Radiated Emission Band Edge

Channel No.:11


Test Mode: 802.11g

Polarization : H



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11n(HT20)

Polarization : V



Radiated Emission Band Edge

Channel No.:1


Test Mode: 802.11n(HT20)

Polarization : H



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11n(HT20)

Polarization : V



Radiated Emission Band Edge

Channel No.:11


Test Mode: 802.11n(HT20)

Polarization : H



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11ax(HE20)

Polarization : V



Radiated Emission Band Edge

Channel No.:1


Test Mode: 802.11ax(HE20)

Polarization : H



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11ax(HE20)

Polarization : V



Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11ax(HE20)


Polarization : H

Partial RU (Tone26)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:1

Test Mode: 802.11ax(HE20)

Polarization : V



Radiated Emission Band Edge

Channel No.:1


Test Mode: 802.11ax(HE20)

Polarization : H



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01




Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11ax(HE20)

Polarization : V



Radiated Emission Band Edge

Channel No.:11

Test Mode: 802.11ax(HE20)

Polarization : H



Radiated Emission for WIFI

After comparison, the worst case attitude is EUT lay down.

Determining Spurious Emissions Levels

A “reference path loss” is established and the A_{Rpl} is the attenuation of “reference path loss”, and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

The measurement results are obtained as described below:

$$\text{Result} = P_{\text{mea}} + A_{Rpl}$$

Sample calculation: $(9.11 \text{ dB}\mu\text{V/m}) = (25.21 \text{ dB}\mu\text{V}) + (-16.1 \text{ dB/m})$, the corresponding frequency is 46.296 MHz.

For 802.11b Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
46.296	9.11	-16.1	25.21	Vertical	40.0	30.89
53.862	9.11	-16.2	25.31	Vertical	40.0	30.89
101.295	7.21	-17.3	24.51	Vertical	43.5	36.29
303.637	12.89	-14.2	27.09	Vertical	46.0	33.11
311.979	12.42	-13.9	26.32	Vertical	46.0	33.58
800.0345	24.34	-4.1	28.44	Vertical	46.0	21.66

For 802.11g Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
49.4	8.73	-15.6	24.33	Vertical	40.0	31.27
55.026	8.99	-16.2	25.19	Vertical	40.0	31.01
111.8195	8.23	-18.0	26.23	Vertical	43.5	35.27
196.0155	14.31	-17.3	31.61	Vertical	43.5	29.19
556.3705	15.19	-7.6	22.79	Vertical	46.0	30.81
799.986	25.39	-4.1	29.49	Vertical	46.0	20.61

For 802.11n(HT20) Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl	Pmea	Polarity	Limit	Margin
----------------	----------------	------	------	----------	-------	--------



		(dB)	(dBuV/m)		(dBuV/m)	(dB)
47.4115	9.46	-15.9	25.36	Vertical	40.0	30.54
53.959	9.08	-16.2	25.28	Vertical	40.0	30.92
169.292	7.88	-19.6	27.48	Vertical	43.5	35.62
258.9685	17.14	-15.5	32.64	Vertical	46.0	28.86
534.206	14.95	-8.1	23.05	Vertical	46.0	31.05
800.0345	24.11	-4.1	28.21	Vertical	46.0	21.89

For 802.11ax(HE20) Channel No.:1

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
47.3145	9.43	-16.0	25.43	Vertical	40.0	30.57
61.7675	7.53	-17.4	24.93	Vertical	40.0	32.47
169.098	9.41	-19.6	29.01	Vertical	43.5	34.09
303.6855	11.89	-14.2	26.09	Vertical	46.0	34.11
311.979	11.79	-13.9	25.69	Vertical	46.0	34.21
799.986	25.33	-4.1	29.43	Vertical	46.0	20.67

For 802.11b Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
48.721	8.97	-15.8	24.77	Vertical	40.0	31.03
56.2385	8.59	-16.4	24.99	Vertical	40.0	31.41
114.6325	6.32	-18.4	24.72	Vertical	43.5	37.18
303.6855	12.37	-14.2	26.57	Vertical	46.0	33.63
311.979	11.63	-13.9	25.53	Vertical	46.0	34.37
800.0345	24.15	-4.1	28.25	Vertical	46.0	21.85

For 802.11g Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
50.564	8.81	-15.6	24.41	Vertical	40.0	31.19
54.929	8.91	-16.2	25.11	Vertical	40.0	31.09
169.1465	9.85	-19.6	29.45	Vertical	43.5	33.65



BUREAU VERITAS Test Report No.: PSU-NQN2510130209RF01

273.3245	15.67	-15.0	30.67	Vertical	46.0	30.33
541.0445	14.94	-8.0	22.94	Vertical	46.0	31.06
799.986	25.09	-4.1	29.19	Vertical	46.0	20.91

For 802.11n(HT20) Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
52.9405	8.53	-16.0	24.53	Vertical	40.0	31.47
53.862	9.02	-16.2	25.22	Vertical	40.0	30.98
100.5675	7.06	-17.2	24.26	Vertical	43.5	36.44
264.8855	15.42	-15.2	30.62	Vertical	46.0	30.58
538.1345	14.98	-8.0	22.98	Vertical	46.0	31.02
799.986	25.33	-4.1	29.43	Vertical	46.0	20.67

For 802.11ax(HE20) Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
47.072	9.39	-16.0	25.39	Vertical	40.0	30.61
55.026	8.91	-16.2	25.11	Vertical	40.0	31.09
169.0495	6.90	-19.6	26.50	Vertical	43.5	36.60
193.251	14.58	-17.5	32.08	Vertical	43.5	28.92
515	14.57	-8.6	23.17	Vertical	46.0	31.43
800.0345	24.02	-4.1	28.12	Vertical	46.0	21.98

For 802.11b Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
49.9335	8.77	-15.6	24.37	Vertical	40.0	31.23
54.4925	8.97	-16.2	25.17	Vertical	40.0	31.03
107.1635	6.38	-17.6	23.98	Vertical	43.5	37.12
193.2995	14.93	-17.5	32.43	Vertical	43.5	28.57
535.273	14.89	-8.1	22.99	Vertical	46.0	31.11



BUREAU VERITAS Test Report No.: PSU-NQN2510130209RF01

799.986	25.16	-4.1	29.26	Vertical	46.0	20.84
---------	-------	------	-------	----------	------	-------

For 802.11g Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
49.7395	8.73	-15.6	24.33	Vertical	40.0	31.27
55.1715	8.87	-16.3	25.17	Vertical	40.0	31.13
100.713	6.99	-17.3	24.29	Vertical	43.5	36.51
265.516	15.95	-15.2	31.15	Vertical	46.0	30.05
548.077	14.88	-7.8	22.68	Vertical	46.0	31.12
799.986	25.15	-4.1	29.25	Vertical	46.0	20.85

For 802.11n(HT20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
41.6885	8.19	-16.6	24.79	Vertical	40.0	31.81
79.082	9.81	-22.0	31.81	Vertical	40.0	30.19
169.098	9.25	-19.6	28.85	Vertical	43.5	34.25
269.3475	17.75	-15.1	32.85	Vertical	46.0	28.25
505.785	14.39	-8.9	23.29	Vertical	46.0	31.61
800.0345	23.95	-4.1	28.05	Vertical	46.0	22.05

For 802.11ax(HE20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
47.654	9.42	-15.9	25.32	Vertical	40.0	30.58
54.5895	8.94	-16.2	25.14	Vertical	40.0	31.06
169.195	9.63	-19.6	29.23	Vertical	43.5	33.87
263.2365	17.71	-15.3	33.01	Vertical	46.0	28.29
550.2595	14.73	-7.7	22.43	Vertical	46.0	31.27
799.986	24.95	-4.1	29.05	Vertical	46.0	21.05

**Partial RU (Tone26)**

For 802.11ax(HE20) Channel No.:1


Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
41.058	8.34	-16.6	24.94	Vertical	40.0	31.66
55.026	8.80	-16.2	25.00	Vertical	40.0	31.20
102.459	7.14	-17.4	24.54	Vertical	43.5	36.36
266.1465	16.74	-15.2	31.94	Vertical	46.0	29.26
507.3855	14.25	-8.8	23.05	Vertical	46.0	31.75
800.0345	23.80	-4.1	27.90	Vertical	46.0	22.20

For 802.11ax(HE20) Channel No.:6

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
45.132	8.69	-16.2	24.89	Vertical	40.0	31.31
54.1045	8.94	-16.2	25.14	Vertical	40.0	31.06
169.098	9.65	-19.6	29.25	Vertical	43.5	33.85
262.9455	15.22	-15.3	30.52	Vertical	46.0	30.78
528.3375	14.63	-8.3	22.93	Vertical	46.0	31.37
799.986	24.97	-4.1	29.07	Vertical	46.0	21.03

For 802.11ax(HE20) Channel No.:11

Frequency(MHz)	Result(dBuV/m)	ARpl (dB)	Pmea (dBuV/m)	Polarity	Limit (dBuV/m)	Margin (dB)
47.072	9.33	-16.0	25.33	Vertical	40.0	30.67
55.996	8.64	-16.4	25.04	Vertical	40.0	31.36
111.771	8.59	-18.0	26.59	Vertical	43.5	34.91
271.821	15.27	-15.1	30.37	Vertical	46.0	30.73
555.7885	14.76	-7.6	22.36	Vertical	46.0	31.24
799.986	25.13	-4.1	29.23	Vertical	46.0	20.87



Frequency Range: 9kHz -30MHz

Detector: QP mode

Note : The relevant tests have been performed in order to verify in which mode would have the worst features, the result show above is the worst case.




BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Carrier frequency (MHz): 2412

Channel No.:1

Full Spectrum




Frequency Range 30MHz -1GHz

Detector: Av mode and PK mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11b



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode


Modulation type: 802.11b



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11g



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode


Modulation type: 802.11g



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11n(HT20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode


Modulation type: 802.11n(HT20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11 ax(HE20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)




BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Carrier frequency (MHz): 2437

Channel No.:6



Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode


Modulation type: 802.11b



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode


Modulation type: 802.11b



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode


Modulation type: 802.11g



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode


Modulation type: 802.11g



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum



Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode


Modulation type: 802.11n(HT20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum



Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode


Modulation type: 802.11n(HT20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum



Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode


Modulation type: 802.11 ax(HE20)



BUREAU
VERITAS


Test Report No.: PSU-NQN2510130209RF01

Full Spectrum



Frequency Range: 1GHz -3GHz
Detector: Av mode and PK mode
Modulation type: 802.11 ax(HE20)

Full Spectrum




Frequency Range: 3GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11 ax(HE20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)




BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Carrier frequency (MHz): 2462

Channel No.:11

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11b



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11b

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode


Modulation type: 802.11b



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11g



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11g

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode


Modulation type: 802.11g



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11n(HT20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11n(HT20)

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode


Modulation type: 802.11n(HT20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11 ax(HE20)



BUREAU
VERITAS


Test Report No.: PSU-NQN2510130209RF01

Full Spectrum



Frequency Range: 3GHz -18GHz
Detector: Av mode and PK mode
Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 18GHz -26GHz
Detector: Av mode and PK mode
Modulation type: 802.11 ax(HE20)



BUREAU
VERITAS


Test Report No.: PSU-NQN2510130209RF01

Partial RU (Tone26)

Carrier frequency (MHz): 2412

Channel No.:1

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: QP mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11 ax(HE20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)




BUREAU VERITAS Test Report No.: PSU-NQN2510130209RF01

Carrier frequency (MHz): 2437

Channel No.:6

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Detector: QP mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11 ax(HE20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)




BUREAU VERITAS Test Report No.: PSU-NQN2510130209RF01

Carrier frequency (MHz): 2462

Channel No.:11

Full Spectrum




Frequency Range: 30MHz -1GHz

Detector: Detector: QP mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 1GHz -3GHz

Detector: Av mode and PK mode


Modulation type: 802.11 ax(HE20)



BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

Full Spectrum




Frequency Range: 3GHz -18GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)

Full Spectrum



Frequency Range: 18GHz -26GHz

Detector: Av mode and PK mode

Modulation type: 802.11 ax(HE20)



3.3 6 dB BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

3.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	R&S	ESW 44	101973	Mar.28,24	Mar.27,26
Open Switch and Control Unit	R&S	OSP-B157W8	100836	N/A	N/A
Vector Signal Generator	R&S	SMBV100B	102176	Mar.29,24	Mar.28,26
Signal Generator	R&S	SMB100A03	182185	Mar.29,24	Mar.28,26
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Hygrothermograph	DELI	20210528	SZ015	Mar.18,25	Mar.17,27
PC	LENOVO	E14	HRSW0024	N/A	N/A
CABLE	R&S	J12J103539-00-1	SEP-03-20-069	Apr.26,25	Apr.25,26
CABLE	R&S	J12J103539-00-1	SEP-03-20-070	Apr.26,25	Apr.25,26
Test Software	EMC32	EMC32	N/A	N/A	N/A
Temperature Chamber	votsch	VT4002	58566078100050	May.30,24	May.29,26
Power Meter	R&S	NRX	102380	Mar.28,24	Mar.27,26
Power Meter probe	R&S	NRP6A	102942	Mar.28,24	Mar.27,26

NOTE:

1. The calibration interval of the above test instruments is 12/ 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in RF Oven room.



3.3.3 TEST PROCEDURE


In accordance with ANSI C63.10-2020 11.8.1 Option 2:

- a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100kHz.
- b) Set the VBW $\geq [3 \times \text{RBW}]$.
- c) Detector = peak.
- d) Trace mode = max-hold.
- e) Sweep = No faster than coupled (auto) time.
- f) Allow the trace to stabilize.
- g) The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB

3.3.4 DEVIATION FROM TEST STANDARD

No deviation.

3.3.5 TEST SETUP



3.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.3.7 TEST RESULTS

Please Refer to Appendix1/2 Of this test report.




3.4 CONDUCTED OUTPUT POWER

3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm)

3.4.2 TEST SETUP



3.4.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.4.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

3.4.5 DEVIATION FROM TEST STANDARD

No deviation.

3.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.4.7 TEST RESULTS

3.4.7.1 MAXIMUM PEAK OUTPUT POWER

Please Refer to Appendix1 Of this test report.



Test Report No.: PSU-NQN2510130209RF01

3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE)

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

Please Refer to Appendix1/2 Of this test report.




3.5 POWER SPECTRAL DENSITY MEASUREMENT

3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

3.5.2 TEST SETUP



3.5.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.5.4 TEST PROCEDURE

1. Set the span to 1.5 times the DTS bandwidth
2. Set the RBW = 3 kHz, VBW $\geq 3 \times$ RBW, Detector = peak.
3. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
4. Use the peak marker function to determine the maximum amplitude level.

3.5.5 DEVIATION FROM TEST STANDARD

No deviation.

3.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.5.7 TEST RESULTS

Please Refer to Appendix 1/2 Of this test report.




3.6 OUT OF BAND EMISSION MEASUREMENT

3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

3.6.2 TEST SETUP



3.6.3 TEST INSTRUMENTS

Refer to section 3.3.2 to get information of above instrument.

3.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

3.6.5 DEVIATION FROM TEST STANDARD

No deviation.

3.6.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

3.6.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.

Please Refer to Appendix1/2 Of this test report.



3.7 ANTENNA REQUIREMENTS

3.7.1 STANDARD APPLICABLE

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 ANTENNA CONNECTED CONSTRUCTION

An embedded-in antenna design is used.

3.7.3 ANTENNA GAIN

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit and PSD limit.

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.



6 APPENDIX1

BLE

1 Duty Cycle and Antenna Gain

Test Mode	Frequency (MHz)	Plot	Duty Cycle	Correction Factor(dB)	Antenna Gain(dBi)
GFSK (LE 1Mbps)	2402	Fig.1	98.70%	0.06	2.40

Note: Correction Factor= $10 \cdot \log(1/\text{Duty Cycle})$

Test Mode: GFSK (LE 1Mbps)




Fig.1

**2 EIRP****Conducted Power**

Modulation type	Conducted Peak Power(dBm)		
	2402MHz	2440MHz	2480MHz
GFSK (LE 1Mbps)	6.68	6.43	6.65

Modulation type	Conducted Average Power(dBm)		
	2402MHz	2440MHz	2480MHz
GFSK (LE 1Mbps)	4.37	4.13	4.49

EIRP

Modulation type	Peak EIRP(dBm)		
	2402MHz	2440MHz	2480MHz
GFSK (LE 1Mbps)	9.08	8.83	9.05

Modulation type	Average EIRP(dBm)		
	2402MHz	2440MHz	2480MHz
GFSK (LE 1Mbps)	6.77	6.53	6.89

EIRP (dBm)=Conducted Power(dBm)+Antenna Gain(dBi)



3 Occupied Bandwidth and 6dB Bandwidth

6dB Bandwidth

Test Mode	Carrier frequency (MHz)	6dB Bandwidth(KHz)
GFSK (LE 1Mbps)	2402	646.3
GFSK (LE 1Mbps)	2440	647.2
GFSK (LE 1Mbps)	2480	642.7

Test Mode: GFSK (LE 1Mbps)

Test Mode:GFSK (LE 1Mbps) 2402MHz	Test Mode:GFSK (LE 1Mbps) 2440MHz
Test Mode:GFSK (LE 1Mbps) 2480MHz	






BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

99% Bandwidth

Test Mode	Carrier frequency (MHz)	99% Bandwidth(kHz)
GFSK (LE 1Mbps)	2402	1027.1
GFSK (LE 1Mbps)	2440	1025.7
GFSK (LE 1Mbps)	2480	1025.5

Test Mode: GFSK (LE 1Mbps)

	
Test Mode:GFSK (LE 1Mbps) 2402MHz	Test Mode:GFSK (LE 1Mbps) 2440MHz
	
Test Mode:GFSK (LE 1Mbps) 2480MHz	




BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

4 Transmitter Power Spectral Density

Test Mode	Carrier frequency (MHz)	Channel No.	Power Density (dBm/3kHz)
GFSK (LE 1Mbps)	2402	0	-10.5
GFSK (LE 1Mbps)	2440	19	-8.7
GFSK (LE 1Mbps)	2480	39	-8.5

Test Mode: GFSK (LE 1Mbps)






BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

5 Conducted Out of band emission measurement

Test Mode: GFSK (LE 1Mbps)





6 Band Edge measurement

Test Mode: GFSK (LE 1Mbps)





7 APPENDIX2

WLAN 2.4G

DTS BANDWIDTH

TEST RESULT

Mode	TX Type	Frequency (MHz)	RU	RU Pos	ANT	6dB Bandwidth (MHz)		Verdict
						Result	Limit	
802.11b	SISO	2412	/	/	1	9.522	>=0.5	Pass
		2437	/	/	1	9.529	>=0.5	Pass
		2462	/	/	1	9.534	>=0.5	Pass
802.11g	SISO	2412	/	/	1	16.525	>=0.5	Pass
		2437	/	/	1	16.515	>=0.5	Pass
		2462	/	/	1	16.489	>=0.5	Pass
802.11n (HT20)	SISO	2412	/	/	1	17.453	>=0.5	Pass
		2437	/	/	1	17.543	>=0.5	Pass
		2462	/	/	1	17.479	>=0.5	Pass
802.11n (HT40)	SISO	2422	/	/	1	35.793	>=0.5	Pass
		2437	/	/	1	35.825	>=0.5	Pass
		2452	/	/	1	35.787	>=0.5	Pass
802.11ax (HEW20)	SISO	2412	RU26	Left	1	2.252	>=0.5	Pass
				Mid	1	2.907	>=0.5	Pass
				Right	1	2.233	>=0.5	Pass
			RU242	Left	1	18.988	>=0.5	Pass
		2437	RU26	Left	1	2.263	>=0.5	Pass
				Mid	1	2.891	>=0.5	Pass
				Right	1	2.206	>=0.5	Pass
			RU242	Left	1	18.992	>=0.5	Pass
		2462	RU26	Left	1	2.210	>=0.5	Pass
				Mid	1	3.050	>=0.5	Pass
				Right	1	2.284	>=0.5	Pass
			RU242	Left	1	18.991	>=0.5	Pass
802.11ax (HEW40)	SISO	2422	RU26	Left	1	2.474	>=0.5	Pass
				Mid	1	2.448	>=0.5	Pass
				Right	1	2.528	>=0.5	Pass
			RU484	Left	1	37.835	>=0.5	Pass



Test Report No.: PSU-NQN2510130209RF01

		2437	RU26	Left	1	2.329	≥ 0.5	Pass
				Mid	1	2.036	≥ 0.5	Pass
				Right	1	2.220	≥ 0.5	Pass
			RU484	Left	1	37.685	≥ 0.5	Pass
		2452	RU26	Left	1	2.314	≥ 0.5	Pass
				Mid	1	2.653	≥ 0.5	Pass
				Right	1	2.332	≥ 0.5	Pass
			RU484	Left	1	38.098	≥ 0.5	Pass




BUREAU
VERITAS


Test Report No.: PSU-NQN2510130209RF01

TEST GRAPHS

802.11b_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11b_MCH_2437MHz_Ant1 (SISO)_NTNV







BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV



802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV







BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV







BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV



802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV







BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV







BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV






BUREAU
VERITAS

Test Report No.: PSU-NQN2510130209RF01

802.11ax(HEW20)_LCH_2412MHz_RU26_Left_Ant1 (SISO)_NTNV



802.11ax(HEW20)_LCH_2412MHz_RU26_Mid_Ant1 (SISO)_NTNV

