



FCC RF Test Report

APPLICANT : XIAOMI COMMUNICATIONS CO., LTD.
EQUIPMENT : Mobile Phone
BRAND NAME : Redmi
MODEL NAME : M1901F7G
FCC ID : 2AFZZ-RMSF7G
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Oct. 23, 2018 and testing was completed on Dec. 14, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency and Channel	8
2.2 Test Mode	9
2.3 Connection Diagram of Test System.....	11
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	12
2.6 Measurement Results Explanation Example.....	12
3 TEST RESULT.....	13
3.1 26dB & 99% Occupied Bandwidth Measurement	13
3.2 Maximum Conducted Output Power Measurement	15
3.3 Power Spectral Density Measurement	17
3.4 Unwanted Emissions Measurement.....	20
3.5 AC Conducted Emission Measurement.....	25
3.6 Automatically Discontinue Transmission	27
3.7 Antenna Requirements.....	28
4 LIST OF MEASURING EQUIPMENT	29
5 UNCERTAINTY OF EVALUATION	30
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR8O2308D	Rev. 01	Initial issue of report	Jan. 16, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	2.1049 & 15.403(i)	26dB & 99% Bandwidth	-	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 24 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 11 dBm	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) & 15.209(a)	Pass	Under limit 4.38 dB at 5149.96 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.39 dB at 0.158 MHz
3.6	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.7	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	M1901F7G
FCC ID	2AFZZ-RMSF7G
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n (HT20) WLAN 5GHz 802.11a/n (HT20/HT40) WLAN 5GHz 802.11ac (VHT20/VHT40/VHT80) Bluetooth BR/EDR/LE
IMEI Code	Conducted: 867325040003678/867325040006655 Radiation: 864605040003965/864605040008303 Conduction: 864605040003445/864605040007784
HW Version	P2
SW Version	MIUI10
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5700 MHz
Maximum Output Power to Antenna	<5180 MHz ~ 5240 MHz> 802.11a : 15.87 dBm / 0.0386 W 802.11n HT20 : 13.85 dBm / 0.0243 W 802.11n HT40 : 13.88 dBm / 0.0244 W 802.11ac VHT80 : 12.11 dBm / 0.0163 W <5260 MHz ~ 5320 MHz> 802.11a : 15.90 dBm / 0.0389 W 802.11n HT20 : 13.84 dBm / 0.0242 W 802.11n HT40 : 13.86 dBm / 0.0243 W 802.11ac VHT80 : 12.14 dBm / 0.0164 W <5500 MHz ~ 5700 MHz > 802.11a : 15.65 dBm / 0.0367 W 802.11n HT20 : 13.57 dBm / 0.0228 W 802.11n HT40 : 13.91 dBm / 0.0246 W 802.11ac VHT80 : 11.99 dBm / 0.0158 W
99% Occupied Bandwidth	<5180 MHz ~ 5240 MHz> 802.11a : 17.48 MHz 802.11n HT20 : 18.73 MHz 802.11n HT40 : 36.56 MHz 802.11 ac VHT80 : 75.76 MHz <5260 MHz ~ 5320 MHz> 802.11a : 17.43 MHz 802.11n HT20 : 18.68 MHz 802.11n HT40 : 36.56 MHz 802.11 ac VHT80 : 75.64 MHz <5500 MHz ~ 5700 MHz > 802.11a : 17.48 MHz 802.11n HT20 : 18.63 MHz 802.11n HT40 : 36.66 MHz 802.11 ac VHT80 : 75.64 MHz
Antenna Gain / Gain	<5180 MHz ~ 5240 MHz> Fixed internal Antenna with gain -4.47 dBi <5260 MHz ~ 5320 MHz> Fixed internal Antenna with gain -5.4 dBi <5500 MHz ~ 5720 MHz > Fixed internal Antenna with gain -6.1 dBi
Type of Modulation	802.11a/n: OFDM (BPSK/QPSK/16QAM/64QAM) 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	TH01-KS CO01-KS 03CH02-KS	CN5013	630927

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq.(MHz)	Channel	Freq.(MHz)
5150-5250 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	42 [#]	5210		

Frequency Band	Channel	Freq.(MHz)	Channel	Freq.(MHz)
5250-5350 MHz Band 2 (U-NII-2A)	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	58 [#]	5290		

Frequency Band	Channel	Freq.(MHz)	Channel	Freq.(MHz)
5470-5725 MHz Band 3 (U-NII-2C)	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	106 [#]	5530	134*	5670
	108	5540	136	5680
	110*	5550	140	5700

Frequency Band	Channel	Freq.(MHz)	Channel	Freq.(MHz)
TDWR Channel	118*	5590	124	5620
	120	5600	126*	5630
	122 [#]	5610	128	5640

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "[#]" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0
802.11ac VHT40 (Covered by HT40)	MCS0
802.11ac VHT80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable 2 (Charging from adapter 2) + Earphone
Remark: The accessories are from Part 15B worst case.	




Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11a	802.11a	802.11a
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140

Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11n HT20	802.11n HT20	802.11n HT20
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140

Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11n HT40	802.11n HT40	802.11n HT40
L	Low	38	54	102
M	Middle	-	-	110
H	High	46	62	134

Ch. #		Band I : 5150-5250 MHz	Band II : 5250-5350 MHz	Band III : 5470-5725MHz
		802.11ac VHT80	802.11ac VHT80	802.11ac VHT80
L	Low	-	-	106
M	Middle	42	58	-
H	High	-	-	122

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
3.	WLAN AP	DIR-855	KA2DIR855A2	N/A	N/A	Unshielded, 1.8 m
4.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A



2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss

Following shows an offset computation example with cable loss 6.6 dB.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} \\ &= 6.6 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1MHz and set the Video bandwidth (VBW) $\geq 3 * RBW$.
8. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 26dB & 99% Occupied Bandwidth

Please refer to Appendix A.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm $10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For the 5.47–5.6 GHz and 5.65–5.725 GHz band, the maximum conducted output power shall not exceed 250 mW or $11 + 10 \log_{10} B$, dBm, whichever power is less. The maximum e.i.r.p. shall not exceed 1.0 W or $17 + 10 \log_{10} B$, dBm, whichever is less. B is the 99% emission bandwidth in megahertz.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures


The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For Straddle Channel, According to KDB 789033 D02 General UNII Test Procedures New Rules v02r01, If the power and PSD of the devices are uniform and comply with the lower limits specified for the U-NII-2 bands, a single measurement over the entire emission bandwidth can be performed to show compliance.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.


Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 1 MHz.
- Set VBW $\geq$ 3 MHz.
- Number of points in sweep $\geq$ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Note: Average Power Density (dB) = Measured value+ Duty Factor

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5600 MHz and 5650-5725MHz band: all emissions outside of the 5470-5600 MHz and 5650-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$\text{EIRP} = E_{\text{Meas}} + 20\log(d_{\text{Meas}}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

(3) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

3.4.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures


1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 7, 2018	Nov. 15, 2018	Aug. 6, 2019	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 18, 2018	Nov. 15, 2018	Jan. 17, 2019	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 18, 2018	Nov. 15, 2018	Jan. 17, 2019	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1435004	50MHz Bandwidth	Jan. 18, 2018	Nov. 15, 2018	Jan. 17, 2019	Conducted (TH01-KS)
Thermal Chamber	Hongzhan	LP-150U	H20140114 40	-40~+150°C 20%~95%RH	Jun. 27, 2018	Nov. 15, 2018	Jun. 26, 2019	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Aug. 06, 2018	Dec. 14, 2018	Aug.05, 2019	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 08	10Hz~44G,MAX 30dB	Apr. 17, 2018	Dec. 14, 2018	Apr. 16, 2019	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Dec. 14, 2018	Oct. 18, 2019	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz~2GHz	Jan. 29, 2018	Dec. 14, 2018	Jan. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 21, 2018	Dec. 14, 2018	Jan. 20, 2019	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Feb. 07, 2018	Dec. 14, 2018	Feb. 06, 2019	Radiation (03CH02-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2025788	100MHz~18GHz	Apr. 17, 2018	Dec. 14, 2018	Apr. 16, 2019	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz~1GHz	Aug. 06, 2018	Dec. 14, 2018	Aug. 05, 2019	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY532702 03	500MHz~26.5G Hz	Apr. 18, 2018	Dec. 14, 2018	Apr. 17, 2019	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Feb. 08, 2018	Dec. 14, 2018	Feb. 07, 2019	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Dec. 14, 2018	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Dec. 14, 2018	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Dec. 14, 2018	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Nov. 13, 2018	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Nov. 13, 2018	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 18, 2017	Nov. 13, 2018	Nov. 17, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Nov. 13, 2018	Oct. 11, 2019	Conduction (CO01-KS)

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

	5.2 dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------



Appendix A. Conducted Test Results

Test Engineer:	Smile Wang	Temperature:	21~25	°C
Test Date:	2018/11/15	Relative Humidity:	51~54	%

TEST RESULTS DATA
26dB and 99% OBW

Band I										
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)		Note
11a	6Mbps	1	36	5180	17.38	22.73	-	22.40		
11a	6Mbps	1	44	5220	17.48	23.73	-	22.43		
11a	6Mbps	1	48	5240	17.43	23.33	-	22.41		
HT20	MCS0	1	36	5180	18.63	24.68	-	22.70		
HT20	MCS0	1	44	5220	18.73	24.93	-	22.73		
HT20	MCS0	1	48	5240	18.68	24.63	-	22.71		
HT40	MCS0	1	38	5190	36.56	41.63	-	23.01		
HT40	MCS0	1	46	5230	36.56	41.63	-	23.01		
VHT80	MCS0	1	42	5210	75.76	83.44	-	23.01		

TEST RESULTS DATA
Average Power Table

FCC Band I										
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6Mbps	1	36	5180	0.21	15.64	24.00	-4.47		Pass
11a	6Mbps	1	44	5220	0.21	15.60	24.00	-4.47		Pass
11a	6Mbps	1	48	5240	0.21	15.87	24.00	-4.47		Pass
HT20	MCS0	1	36	5180	0.22	13.67	24.00	-4.47		Pass
HT20	MCS0	1	44	5220	0.22	13.63	24.00	-4.47		Pass
HT20	MCS0	1	48	5240	0.22	13.85	24.00	-4.47		Pass
HT40	MCS0	1	38	5190	0.47	13.56	24.00	-4.47		Pass
HT40	MCS0	1	46	5230	0.47	13.88	24.00	-4.47		Pass
VHT20	MCS0	1	36	5180	0.22	11.49	24.00	-4.47		Pass
VHT20	MCS0	1	44	5220	0.22	11.50	24.00	-4.47		Pass
VHT20	MCS0	1	48	5240	0.22	11.93	24.00	-4.47		Pass
VHT40	MCS0	1	38	5190	0.44	11.81	24.00	-4.47		Pass
VHT40	MCS0	1	46	5230	0.44	12.03	24.00	-4.47		Pass
VHT80	MCS0	1	42	5210	0.77	12.11	24.00	-4.47		Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)	-	Pass/Fail
11a	6Mbps	1	36	5180	0.21	4.96	11.00	-4.47		Pass
11a	6Mbps	1	44	5220	0.21	4.77	11.00	-4.47		Pass
11a	6Mbps	1	48	5240	0.21	5.35	11.00	-4.47		Pass
HT20	MCS0	1	36	5180	0.22	2.67	11.00	-4.47		Pass
HT20	MCS0	1	44	5220	0.22	3.15	11.00	-4.47		Pass
HT20	MCS0	1	48	5240	0.22	2.92	11.00	-4.47		Pass
HT40	MCS0	1	38	5190	0.47	-0.76	11.00	-4.47		Pass
HT40	MCS0	1	46	5230	0.47	-0.08	11.00	-4.47		Pass
VHT80	MCS0	1	42	5210	0.77	-4.70	11.00	-4.47		Pass

TEST RESULTS DATA
26dB and 99% OBW

Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6M bps	1	52	5260	17.43	23.33	23.41	29.41	23.98	
11a	6M bps	1	60	5300	17.43	23.38	23.41	29.41	23.98	
11a	6M bps	1	64	5320	17.43	23.43	23.41	29.41	23.98	
HT20	MCS 0	1	52	5260	18.68	24.88	23.71	29.71	23.98	
HT20	MCS 0	1	60	5300	18.68	24.28	23.71	29.71	23.98	
HT20	MCS 0	1	64	5320	18.68	25.18	23.71	29.71	23.98	
HT40	MCS 0	1	54	5270	36.56	41.54	23.98	30.00	23.98	
HT40	MCS 0	1	62	5310	36.46	41.45	23.98	30.00	23.98	
VHT80	MCS 0	1	58	5290	75.64	82.64	23.98	30.00	23.98	

TEST RESULTS DATA
Average Power Table

FCC Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	52	5260	0.21	15.90	23.98	-5.40	26.99	Pass
11a	6M bps	1	60	5300	0.21	15.65	23.98	-5.40	26.99	Pass
11a	6M bps	1	64	5320	0.21	15.23	23.98	-5.40	26.99	Pass
HT20	MCS 0	1	52	5260	0.22	13.84	23.98	-5.40	26.99	Pass
HT20	MCS 0	1	60	5300	0.22	13.78	23.98	-5.40	26.99	Pass
HT20	MCS 0	1	64	5320	0.22	13.37	23.98	-5.40	26.99	Pass
HT40	MCS 0	1	54	5270	0.47	13.86	23.98	-5.40	26.99	Pass
HT40	MCS 0	1	62	5310	0.47	13.76	23.98	-5.40	26.99	Pass
VHT20	MCS 0	1	52	5260	0.22	11.91	23.98	-5.40	26.99	Pass
VHT20	MCS 0	1	60	5300	0.22	11.68	23.98	-5.40	26.99	Pass
VHT20	MCS 0	1	64	5320	0.22	11.50	23.98	-5.40	26.99	Pass
VHT40	MCS 0	1	54	5270	0.44	12.13	23.98	-5.40	26.99	Pass
VHT40	MCS 0	1	62	5310	0.44	12.08	23.98	-5.40	26.99	Pass
VHT80	MCS 0	1	58	5290	0.77	12.14	23.98	-5.40	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

Band II										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6M bps	1	52	5260	0.21	5.18	11.00	-5.40		Pass
11a	6M bps	1	60	5300	0.21	5.00	11.00	-5.40		Pass
11a	6M bps	1	64	5320	0.21	4.41	11.00	-5.40		Pass
HT20	MCS 0	1	52	5260	0.22	2.64	11.00	-5.40		Pass
HT20	MCS 0	1	60	5300	0.22	2.60	11.00	-5.40		Pass
HT20	MCS 0	1	64	5320	0.22	2.17	11.00	-5.40		Pass
HT40	MCS 0	1	54	5270	0.47	-0.39	11.00	-5.40		Pass
HT40	MCS 0	1	62	5310	0.47	-0.33	11.00	-5.40		Pass
VHT80	MCS 0	1	58	5290	0.77	-5.20	11.00	-5.40		Pass

TEST RESULTS DATA
26dB and 99% OBW

Band III										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6M bps	1	100	5500	17.48	23.33	23.43	29.43	23.98	
11a	6M bps	1	116	5580	17.43	23.73	23.41	29.41	23.98	
11a	6M bps	1	140	5700	17.48	23.68	23.43	29.43	23.98	
HT20	MCS 0	1	100	5500	18.63	24.38	23.70	29.70	23.98	
HT20	MCS 0	1	116	5580	18.63	24.48	23.70	29.70	23.98	
HT20	MCS 0	1	140	5700	18.63	24.53	23.70	29.70	23.98	
HT40	MCS 0	1	102	5510	36.66	41.72	23.98	30.00	23.98	
HT40	MCS 0	1	110	5550	36.66	41.90	23.98	30.00	23.98	
HT40	MCS 0	1	134	5670	36.56	41.63	23.98	30.00	23.98	
VHT80	MCS 0	1	106	5530	75.64	83.12	23.98	30.00	23.98	
VHT80	MCS 0	1	122	5610	75.52	83.28	23.98	30.00	23.98	

TEST RESULTS DATA
Average Power Table


FCC Band III										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	100	5500	0.21	15.65	23.98	-6.10	26.99	Pass
11a	6M bps	1	116	5580	0.21	15.62	23.98	-6.10	26.99	Pass
11a	6M bps	1	140	5700	0.21	14.49	23.98	-6.10	26.99	Pass
HT20	MCS 0	1	100	5500	0.22	13.57	23.98	-6.10	26.99	Pass
HT20	MCS 0	1	116	5580	0.22	13.50	23.98	-6.10	26.99	Pass
HT20	MCS 0	1	140	5700	0.22	12.55	23.98	-6.10	26.99	Pass
HT40	MCS 0	1	102	5510	0.47	13.84	23.98	-6.10	26.99	Pass
HT40	MCS 0	1	110	5550	0.47	13.91	23.98	-6.10	26.99	Pass
HT40	MCS 0	1	134	5670	0.47	13.10	23.98	-6.10	26.99	Pass
VHT20	MCS 0	1	100	5500	0.22	11.70	23.98	-6.10	26.99	Pass
VHT20	MCS 0	1	116	5580	0.22	11.67	23.98	-6.10	26.99	Pass
VHT20	MCS 0	1	140	5700	0.22	10.61	23.98	-6.10	26.99	Pass
VHT40	MCS 0	1	102	5510	0.44	11.79	23.98	-6.10	26.99	Pass
VHT40	MCS 0	1	110	5550	0.44	11.87	23.98	-6.10	26.99	Pass
VHT40	MCS 0	1	134	5670	0.44	11.00	23.98	-6.10	26.99	Pass
VHT80	MCS 0	1	106	5530	0.77	11.99	23.98	-6.10	26.99	Pass
VHT80	MCS 0	1	122	5610	0.77	11.39	23.98	-6.10	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6M bps	1	100	5500	0.21	4.62	11.00	-6.10		Pass
11a	6M bps	1	116	5580	0.21	4.73	11.00	-6.10		Pass
11a	6M bps	1	140	5700	0.21	3.71	11.00	-6.10		Pass
HT20	MCS 0	1	100	5500	0.22	2.33	11.00	-6.10		Pass
HT20	MCS 0	1	116	5580	0.22	2.51	11.00	-6.10		Pass
HT20	MCS 0	1	140	5700	0.22	1.48	11.00	-6.10		Pass
HT40	MCS 0	1	102	5510	0.47	-0.19	11.00	-6.10		Pass
HT40	MCS 0	1	110	5550	0.47	-0.07	11.00	-6.10		Pass
HT40	MCS 0	1	134	5670	0.47	-0.88	11.00	-6.10		Pass
VHT80	MCS 0	1	106	5530	0.77	-5.28	11.00	-6.10		Pass
VHT80	MCS 0	1	122	5610	0.77	-4.93	11.00	-6.10		Pass




Appendix B. AC Conducted Emission Test Results





Test Engineer :	Amos Zhao	Temperature :	25.3~26.2℃
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15E LISN-N-181013-060103 NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.151	49.99	-15.97	65.96	39.30	0.21	10.48	QP
2	0.151	34.89	-21.07	55.96	24.20	0.21	10.48	Average
3 *	0.158	54.17	-11.39	65.56	43.50	0.21	10.46	QP
4	0.158	34.97	-20.59	55.56	24.30	0.21	10.46	Average
5	0.167	45.94	-19.18	65.12	35.29	0.21	10.44	QP
6	0.167	29.94	-25.18	55.12	19.29	0.21	10.44	Average
7	0.214	47.15	-15.90	63.05	36.60	0.20	10.35	QP
8	0.214	28.85	-24.20	53.05	18.30	0.20	10.35	Average
9	0.266	42.02	-19.23	61.25	31.50	0.20	10.32	QP
10	0.266	24.72	-26.53	51.25	14.20	0.20	10.32	Average
11	0.637	35.93	-20.07	56.00	25.49	0.20	10.24	QP
12	0.637	27.63	-18.37	46.00	17.19	0.20	10.24	Average



Appendix C. Radiated Spurious Emission

Band 1 - 5150~5250MHz

5150.WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz		5147.04	55.08	-18.92	74	47.12	31.16	8.47	31.67	100	360	P	H
		5149.98	41.55	-12.45	54	33.59	31.16	8.47	31.67	100	360	A	H
	*	5180	98.52	-	-	90.6	31.1	8.48	31.66	100	360	P	H
	*	5180	91.08	-	-	83.16	31.1	8.48	31.66	100	360	A	H
		5148.96	56.66	-17.34	74	48.7	31.16	8.47	31.67	100	243	P	V
		5149.98	41.83	-12.17	54	33.87	31.16	8.47	31.67	100	243	A	V
	*	5182	100.31	-	-	92.39	31.1	8.48	31.66	100	243	P	V
	*	5182	92.32	-	-	84.4	31.1	8.48	31.66	100	243	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 36 5180MHz		10360	41.23	-27.07	68.3	53.96	38.04	12.29	63.06	100	0	P	H
		10360	40.94	-27.36	68.3	53.67	38.04	12.29	63.06	100	0	P	V
802.11a CH 44 5220MHz		10440	41.78	-26.52	68.3	54.33	38.14	12.35	63.04	100	0	P	H
		10440	41.41	-26.89	68.3	53.96	38.14	12.35	63.04	100	0	P	V
802.11a CH 48 5240MHz		10480	43.11	-25.19	68.3	55.52	38.22	12.4	63.03	100	0	P	H
		10480	41.81	-26.49	68.3	54.22	38.22	12.4	63.03	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		5123.84	54.42	-19.58	74	46.45	31.19	8.47	31.69	100	29	P	H
		5149.76	40.33	-13.67	54	32.37	31.16	8.47	31.67	100	29	A	H
	*	5182	96.39	-	-	88.47	31.1	8.48	31.66	100	29	P	H
	*	5182	89.39	-	-	81.47	31.1	8.48	31.66	100	29	A	H
		5143.68	52.76	-21.24	74	44.82	31.16	8.47	31.69	177	208	P	V
		5149.98	40.2	-13.80	54	32.24	31.16	8.47	31.67	177	208	A	V
	*	5180	98.39	-	-	90.47	31.1	8.48	31.66	177	208	P	V
	*	5180	90.63	-	-	82.71	31.1	8.48	31.66	177	208	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		10360	41.14	-27.16	68.3	53.87	38.04	12.29	63.06	100	0	P	H
		10360	40.27	-28.03	68.3	53	38.04	12.29	63.06	100	0	P	V
802.11n HT20 CH 44 5220MHz		10440	40.49	-27.81	68.3	53.04	38.14	12.35	63.04	100	0	P	H
		10440	41.09	-27.21	68.3	53.64	38.14	12.35	63.04	100	0	P	V
802.11n HT20 CH 48 5240MHz		10480	41.34	-26.96	68.3	53.75	38.22	12.4	63.03	100	0	P	H
		10480	42.33	-25.97	68.3	54.74	38.22	12.4	63.03	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		5148.32	56.74	-17.26	74	48.78	31.16	8.47	31.67	300	182	P	H
	!	5149.98	48.83	-5.170	54	40.87	31.16	8.47	31.67	300	182	A	H
	*	5194	96.61	-	-	88.72	31.07	8.48	31.66	300	182	P	H
	*	5194	86.51	-	-	78.62	31.07	8.48	31.66	300	182	A	H
		5396.58	48.27	-25.73	74	40.38	30.72	8.72	31.55	300	182	P	H
		5382.9	37.99	-16.01	54	30.09	30.75	8.7	31.55	300	182	A	H
		5149.76	57.56	-16.44	74	49.6	31.16	8.47	31.67	100	284	P	V
	!	5149.96	49.62	-4.38	54	41.66	31.16	8.47	31.67	100	284	A	V
	*	5194	97.07	-	-	89.18	31.07	8.48	31.66	100	284	P	V
	*	5194	90.12	-	-	82.23	31.07	8.48	31.66	100	284	A	V
		5352.12	47.5	-26.50	74	39.6	30.81	8.66	31.57	100	284	P	V
		5383.08	38.04	-15.96	54	30.14	30.75	8.7	31.55	100	284	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		10380	41.53	-26.77	68.3	54.21	38.07	12.3	63.05	100	0	P	H
		10380	41.56	-26.74	68.3	54.24	38.07	12.3	63.05	100	0	P	V
802.11n HT40 CH 46 5230MHz		10460	41.23	-27.07	68.3	53.73	38.17	12.37	63.04	100	0	P	H
		10460	41.35	-26.95	68.3	53.85	38.17	12.37	63.04	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 42 5210MHz		5148	57.75	-16.25	74	49.79	31.16	8.47	31.67	300	125	P	H
	!	5149.76	48.69	-5.31	54	40.73	31.16	8.47	31.67	300	125	A	H
	*	5204	91.75	-	-	83.85	31.07	8.48	31.65	300	125	P	H
	*	5204	84.67	-	-	76.77	31.07	8.48	31.65	300	125	A	H
		5355.54	47.72	-26.28	74	39.82	30.81	8.66	31.57	300	125	P	H
		5379.48	38.76	-15.24	54	30.86	30.75	8.7	31.55	300	125	A	H
		5135.84	57.03	-16.97	74	49.06	31.19	8.47	31.69	100	208	P	V
	!	5147.68	48.51	-5.49	54	40.55	31.16	8.47	31.67	100	208	A	V
	*	5192	91.78	-	-	83.89	31.07	8.48	31.66	100	208	P	V
	*	5192	84.72	-	-	76.83	31.07	8.48	31.66	100	208	A	V
		5397.3	47.43	-26.57	74	39.54	30.72	8.72	31.55	100	208	P	V
		5382.54	38.62	-15.38	54	30.72	30.75	8.7	31.55	100	208	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac		10420	42.28	-26.02	68.3	54.87	38.12	12.34	63.05	100	360	P	H
VHT80													
CH 42		10420	41.81	-26.49	68.3	54.4	38.12	12.34	63.05	300	0	P	V
5210MHz													
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 - 5250~5350MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 64 5320MHz	*	5316	97.12	-	-	89.23	30.86	8.62	31.59	164	190	P	H
	*	5316	90.88	-	-	82.99	30.86	8.62	31.59	164	190	A	H
		5367.1	50.57	-23.43	74	42.68	30.78	8.68	31.57	164	190	P	H
		5350.2	40.03	-13.97	54	32.13	30.81	8.66	31.57	164	190	A	H
	*	5320	102.48	-	-	94.59	30.86	8.62	31.59	100	330	P	V
	*	5320	94.83	-	-	86.94	30.86	8.62	31.59	100	330	A	V
		5359	55.25	-18.75	74	47.35	30.81	8.66	31.57	100	330	P	V
		5350	42.06	-11.94	54	34.16	30.81	8.66	31.57	100	330	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 52 5260MHz		10520	40.85	-27.45	68.3	53.18	38.27	12.43	63.03	100	0	P	H
		10520	41.22	-27.08	68.3	53.55	38.27	12.43	63.03	100	0	P	V
802.11a CH 60 5300MHz		10600.01	41.14	-32.86	74	53.24	38.39	12.52	63.01	100	0	P	H
		10600.01	41.15	-32.85	74	53.25	38.39	12.52	63.01	100	0	P	V
802.11a CH 64 5320MHz		10640	42.99	-31.01	74	55	38.44	12.55	63	100	0	P	H
		10640	42.27	-31.73	74	54.28	38.44	12.55	63	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 64 5320MHz	*	5322	96.68	-	-	88.79	30.86	8.62	31.59	145	187	P	H
	*	5322	88.76	-	-	80.87	30.86	8.62	31.59	145	187	A	H
		5362.3	51.22	-22.78	74	43.33	30.78	8.68	31.57	145	187	P	H
		5350.7	39.38	-14.62	54	31.48	30.81	8.66	31.57	145	187	A	H
	*	5322	99.74	-	-	91.85	30.86	8.62	31.59	100	331	P	V
	*	5322	93.14	-	-	85.25	30.86	8.62	31.59	100	331	A	V
		5364.3	57.42	-16.58	74	49.53	30.78	8.68	31.57	100	331	P	V
		5351.3	41.04	-12.96	54	33.14	30.81	8.66	31.57	100	331	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 52 5260MHz		10520	40.84	-27.46	68.3	53.17	38.27	12.43	63.03	100	0	P	H
		10520	41.74	-26.56	68.3	54.07	38.27	12.43	63.03	100	0	P	V
802.11n HT20 CH 60 5300MHz		10600.01	40.89	-33.11	74	52.99	38.39	12.52	63.01	100	0	P	H
		10600.01	41.33	-32.67	74	53.43	38.39	12.52	63.01	100	0	P	V
802.11n HT20 CH 64 5320MHz		10640	42.12	-31.88	74	54.13	38.44	12.55	63	100	0	P	H
		10640	43.13	-30.87	74	55.14	38.44	12.55	63	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 62 5310MHz		5126.56	49.6	-24.40	74	41.63	31.19	8.47	31.69	300	156	P	H
		5102.72	40	-14.00	54	31.99	31.25	8.46	31.7	300	156	A	H
	*	5306	94.91	-	-	87.01	30.89	8.6	31.59	300	156	P	H
	*	5306	87.51	-	-	79.61	30.89	8.6	31.59	300	156	A	H
		5350.6	56.9	-17.10	74	49	30.81	8.66	31.57	300	156	P	H
		5350.5	44.17	-9.83	54	36.27	30.81	8.66	31.57	300	156	A	H
		5106.72	49.17	-24.83	74	41.19	31.22	8.46	31.7	100	283	P	V
		5118.4	39.85	-14.15	54	31.86	31.22	8.46	31.69	100	283	A	V
	*	5306	96.89	-	-	88.99	30.89	8.6	31.59	100	283	P	V
	*	5306	89.2	-	-	81.3	30.89	8.6	31.59	100	283	A	V
		5364	58.76	-15.24	74	50.87	30.78	8.68	31.57	100	283	P	V
		5350.01	45.88	-8.12	54	37.98	30.81	8.66	31.57	100	283	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 54 5270MHz		10540	42.24	-26.06	68.3	54.52	38.29	12.45	63.02	100	360	P	H
		10540	42.17	-26.13	68.3	54.45	38.29	12.45	63.02	300	0	P	V
802.11n HT40 CH 62 5310MHz		10620	42.81	-31.19	74	54.88	38.41	12.53	63.01	100	360	P	H
		10620	42.95	-31.05	74	55.02	38.41	12.53	63.01	300	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 58 5290MHz		5106.08	48.81	-25.19	74	40.83	31.22	8.46	31.7	100	325	P	H
		5119.68	40.4	-13.60	54	32.41	31.22	8.46	31.69	100	325	A	H
	*	5280	89.63	-	-	81.74	30.92	8.58	31.61	100	325	P	H
	*	5280	81.75	-	-	73.86	30.92	8.58	31.61	100	325	A	H
		5359.1	52.36	-21.64	74	44.46	30.81	8.66	31.57	100	325	P	H
		5350	45	-9.00	54	37.1	30.81	8.66	31.57	100	325	A	H
		5121.6	49.83	-24.17	74	41.84	31.22	8.46	31.69	104	289	P	V
		5101.92	40.51	-13.49	54	32.5	31.25	8.46	31.7	104	289	A	V
	*	5282	92.49	-	-	84.6	30.92	8.58	31.61	104	289	P	V
	*	5282	84.39	-	-	76.5	30.92	8.58	31.61	104	289	A	V
		5353.5	54.83	-19.17	74	46.93	30.81	8.66	31.57	104	289	P	V
		5350.3	45.7	-8.30	54	37.8	30.81	8.66	31.57	104	289	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac		10580	44.29	-24.01	68.3	56.43	38.37	12.5	63.01	100	360	P	H
VHT80													
CH 58		10580	43.34	-24.96	68.3	55.48	38.37	12.5	63.01	300	0	P	V
5290MHz													
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 100 5500MHz		5439.28	49.79	-24.21	74	41.91	30.66	8.75	31.53	100	192	P	H
		5468.24	53.65	-14.65	68.3	45.78	30.6	8.78	31.51	100	192	P	H
		5451.92	39.74	-14.26	54	31.85	30.63	8.77	31.51	100	192	A	H
	*	5502	98.69	-	-	90.83	30.54	8.81	31.49	100	192	P	H
	*	5502	91.4	-	-	83.54	30.54	8.81	31.49	100	192	A	H
		5458.32	54.87	-19.13	74	46.98	30.63	8.77	31.51	100	223	P	V
		5468.08	55.72	-12.58	68.3	47.85	30.6	8.78	31.51	100	223	P	V
		5459.44	40.4	-13.60	54	32.51	30.63	8.77	31.51	100	223	A	V
	*	5500	101.48	-	-	93.63	30.54	8.81	31.5	100	223	P	V
	*	5500	94	-	-	86.15	30.54	8.81	31.5	100	223	A	V
802.11a CH 140 5700MHz	*	5700	99.53	-	-	91.32	30.72	8.98	31.49	236	229	P	H
	*	5700	92.02	-	-	83.81	30.72	8.98	31.49	236	229	A	H
		5726.12	54.13	-14.17	68.3	45.65	30.99	9.01	31.52	236	229	P	H
	*	5700	91.23	-	-	83.02	30.72	8.98	31.49	100	143	P	V
	*	5700	83.66	-	-	75.45	30.72	8.98	31.49	100	143	A	V
		5759.32	49.09	-19.21	68.3	40.35	31.27	9.05	31.58	100	143	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 100 5500MHz		11000	42.49	-31.51	74	53.57	38.96	12.89	62.93	100	0	P	H
		11000	42.82	-31.18	74	53.9	38.96	12.89	62.93	100	0	P	V
802.11a CH 116 5580MHz		11160	43.35	-30.65	74	53.99	39.21	13.05	62.9	100	0	P	H
		11160	43.33	-30.67	74	53.97	39.21	13.05	62.9	100	0	P	V
802.11a CH 140 5700MHz		11400	43.74	-30.26	74	53.76	39.55	13.28	62.85	100	0	P	H
		11400	44.58	-29.42	74	54.6	39.55	13.28	62.85	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 100 5500MHz		5453.04	56.97	-17.03	74	49.08	30.63	8.77	31.51	100	188	P	H
		5461.52	57.59	-10.71	68.3	49.7	30.63	8.77	31.51	100	188	P	H
		5456.72	39.99	-14.01	54	32.1	30.63	8.77	31.51	100	188	A	H
	*	5500	95.95	-	-	88.1	30.54	8.81	31.5	100	188	P	H
	*	5500	89.38	-	-	81.53	30.54	8.81	31.5	100	188	A	H
		5452.56	58.24	-15.76	74	50.35	30.63	8.77	31.51	100	322	P	V
		5467.92	60.12	-8.18	68.3	52.25	30.6	8.78	31.51	100	322	P	V
		5459.96	41.01	-12.99	54	33.12	30.63	8.77	31.51	100	322	A	V
	*	5496	98.61	-	-	90.74	30.57	8.8	31.5	100	322	P	V
	*	5496	91.71	-	-	83.84	30.57	8.8	31.5	100	322	A	V
802.11n HT20 CH 140 5700MHz	*	5702	96.14	-	-	87.78	30.85	9	31.49	100	199	P	H
	*	5702	89.39	-	-	81.03	30.85	9	31.49	100	199	A	H
		5738.52	54.62	-13.68	68.3	46.01	31.13	9.03	31.55	100	199	P	H
	*	5702	99.04	-	-	90.68	30.85	9	31.49	100	318	P	V
	*	5702	91.37	-	-	83.01	30.85	9	31.49	100	318	A	V
		5732.04	56.89	-11.41	68.3	48.44	30.99	9.01	31.55	100	318	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 100 5500MHz		11000	43.13	-30.87	74	54.21	38.96	12.89	62.93	100	0	P	H
		11000	43.36	-30.64	74	54.44	38.96	12.89	62.93	100	0	P	V
802.11n HT20 CH 116 5580MHz		11160	43.42	-30.58	74	54.06	39.21	13.05	62.9	100	0	P	H
		11160	43.25	-30.75	74	53.89	39.21	13.05	62.9	100	0	P	V
802.11n HT20 CH 140 5700MHz		11400	44.13	-29.87	74	54.15	39.55	13.28	62.85	100	0	P	H
		11400	43.74	-30.26	74	53.76	39.55	13.28	62.85	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 102 5510MHz		5453.2	56.14	-17.86	74	48.25	30.63	8.77	31.51	100	338	P	H
		5468.08	59.22	-9.08	68.3	51.35	30.6	8.78	31.51	100	338	P	H
		5459.96	44.51	-9.49	54	36.62	30.63	8.77	31.51	100	338	A	H
	*	5500	96.03	-	-	88.18	30.54	8.81	31.5	100	338	P	H
	*	5500	88.06	-	-	80.21	30.54	8.81	31.5	100	338	A	H
		5729.24	49.67	-18.63	68.3	41.19	30.99	9.01	31.52	100	338	P	H
		5453.04	62.72	-11.28	74	54.83	30.63	8.77	31.51	100	277	P	V
		5464.4	61.06	-7.24	68.3	53.19	30.6	8.78	31.51	100	277	P	V
		5459.96	46.42	-7.58	54	38.53	30.63	8.77	31.51	100	277	A	V
	*	5512	98.67	-	-	90.81	30.54	8.81	31.49	100	277	P	V
	*	5512	90.58	-	-	82.72	30.54	8.81	31.49	100	277	A	V
		5726.36	50.72	-17.58	68.3	42.24	30.99	9.01	31.52	100	277	P	V
802.11n HT40 CH 134 5670MHz		5454.96	48.5	-25.5	74	40.61	30.63	8.77	31.51	100	314	P	H
		5464.08	47.27	-21.03	68.3	39.4	30.6	8.78	31.51	100	314	P	H
		5457.04	38.67	-15.33	54	30.78	30.63	8.77	31.51	100	314	A	H
	*	5666	95.6	-	-	87.66	30.44	8.95	31.45	100	314	P	H
	*	5666	88.05	-	-	80.11	30.44	8.95	31.45	100	314	A	H
		5726.28	59.56	-8.74	68.3	51.08	30.99	9.01	31.52	100	314	P	H
		5414.16	49	-25.00	74	41.11	30.69	8.74	31.54	100	281	P	V
		5468.88	47.54	-20.76	68.3	39.67	30.6	8.78	31.51	100	281	P	V
		5452.72	38.94	-15.06	54	31.05	30.63	8.77	31.51	100	281	A	V
	*	5674	96.05	-	-	87.95	30.58	8.97	31.45	100	281	P	V
	*	5674	88.33	-	-	80.23	30.58	8.97	31.45	100	281	A	V
		5726.04	57.36	-10.94	68.3	48.88	30.99	9.01	31.52	100	281	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 CH 102 5510MHz		11020	43.2	-30.8	74	54.24	38.98	12.91	62.93	100	360	P	H
		11020	42.94	-31.06	74	53.98	38.98	12.91	62.93	300	0	P	V
802.11n HT40 CH 110 5550MHz		11100	44.11	-29.89	74	54.92	39.11	12.99	62.91	100	360	P	H
		11100	44.5	-29.50	74	55.31	39.11	12.99	62.91	300	0	P	V
802.11n HT40 CH 134 5670MHz		11340	46.32	-27.68	74	56.52	39.45	13.21	62.86	100	360	P	H
		11340	45.04	-28.96	74	55.24	39.45	13.21	62.86	300	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 106 5530MHz		5451.76	54.93	-19.07	74	47.04	30.63	8.77	31.51	100	340	P	H
		5462	55.2	-13.10	68.3	47.31	30.63	8.77	31.51	100	340	P	H
		5459.96	45.9	-8.10	54	38.01	30.63	8.77	31.51	100	340	A	H
	*	5524	90.46	-	-	82.62	30.51	8.82	31.49	100	340	P	H
	*	5524	83.16	-	-	75.32	30.51	8.82	31.49	100	340	A	H
		5743.56	48.99	-19.31	68.3	40.38	31.13	9.03	31.55	100	340	P	H
		5449.84	59.03	-14.97	74	51.14	30.63	8.77	31.51	100	280	P	V
		5460.24	57.61	-10.69	68.3	49.72	30.63	8.77	31.51	100	280	P	V
	!	5459.76	48.88	-5.12	54	40.99	30.63	8.77	31.51	100	280	A	V
	*	5520	92.3	-	-	84.46	30.51	8.82	31.49	100	280	P	V
	*	5520	84.61	-	-	76.77	30.51	8.82	31.49	100	280	A	V
		5742.12	49.47	-18.83	68.3	40.86	31.13	9.03	31.55	100	280	P	V
802.11ac VHT80 CH 122 5610MHz		5387.6	48.07	-25.93	74	40.17	30.75	8.7	31.55	103	341	P	H
		5463.92	47.95	-20.35	68.3	40.08	30.6	8.78	31.51	103	341	P	H
		5458.48	39.08	-14.92	54	31.19	30.63	8.77	31.51	103	341	A	H
	*	5592	90.55	-	-	82.73	30.39	8.88	31.45	103	341	P	H
	*	5592	82.68	-	-	74.86	30.39	8.88	31.45	103	341	A	H
		5745.96	49.65	-18.65	68.3	41.04	31.13	9.03	31.55	103	341	P	H
		5439.6	48.28	-25.72	74	40.4	30.66	8.75	31.53	100	280	P	V
		5463.76	47.15	-21.15	68.3	39.28	30.6	8.78	31.51	100	280	P	V
		5455.6	39.15	-14.85	54	31.26	30.63	8.77	31.51	100	280	A	V
	*	5592	91.34	-	-	83.52	30.39	8.88	31.45	100	280	P	V
	*	5592	83.77	-	-	75.95	30.39	8.88	31.45	100	280	A	V
		5740.52	49.7	-18.6	68.3	41.09	31.13	9.03	31.55	100	280	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz

WIFI 802.11n VHT80 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ac VHT80 CH 106 5530MHz		11060	43.36	-30.64	74	54.27	39.06	12.95	62.92	100	360	P	H
		11060	43.91	-30.09	74	54.82	39.06	12.95	62.92	300	0	P	V
802.11ac VHT80 CH 122 5610MHz		11220	43.72	-30.28	74	54.23	39.28	13.1	62.89	100	360	P	H
		11220	43.95	-30.05	74	54.46	39.28	13.1	62.89	300	0	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

WIFI 802.11n HT40 (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT40 LF		33.88	21.14	-18.86	40	31.65	21.96	0.49	32.96			P	H
		159.98	16.34	-27.16	43.5	32.1	15.9	1.29	32.95			P	H
		397.63	25.03	-20.97	46	34.49	21.55	2.11	33.12			P	H
		453.89	24.72	-21.28	46	33.14	22.57	2.24	33.23			P	H
		697.36	29.13	-16.87	46	34.65	24.89	2.87	33.28	100	0	P	H
		959.26	28.94	-17.06	46	30.07	27.03	3.47	31.63			P	H
		31.94	24.21	-15.79	40	33.62	23.08	0.48	32.97			P	V
		38.73	26.93	-13.07	40	40.22	19.16	0.53	32.98	100	0	P	V
		216.24	20.62	-25.38	46	36.77	15.28	1.51	32.94			P	V
		424.79	24.2	-21.80	46	33.15	22.05	2.17	33.17			P	V
		756.53	29.38	-16.62	46	33.88	25.58	3.02	33.1			P	V
		903.97	28.12	-17.88	46	30.5	26.53	3.36	32.27			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

**Note symbol**

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is not under limit 6dB .
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)


Both peak and average measured complies with the limit line, so test result is “PASS”.




Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	95.20	2.063	0.48	0.51KHz
5GHz 802.11n HT20	94.88	1.928	0.52	0.56KHz
5GHz 802.11n HT40	89.47	0.937	1.07	1.10KHz
5GHz 802.11acVHT80	82.86	0.464	2.16	2.20KHz

802.11a




802.11n HT20





802.11n HT40



802.11ac VHT80

