FCC RF Test Report

APPLICANT	:	**Xiaomi Communications Co., Ltd.**
EQUIPMENT	:	**Mobile Phone**
BRAND NAME	:	**Redmi**
MODEL NAME	:	**M1901F7G**
FCC ID	:	**2AFZZ-RMSF7G**
STANDARD	:	**FCC Part 15 Subpart E §15.407**
CLASSIFICATION	:	**(NII) Unlicensed National Information Infrastructure**

The product was received on Oct. 23, 2018 and testing was completed on Jan. 02, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

James Huang

Approved by: James Huang / Manager

NVLAP®
TESTING
NVLAP LAB CODE 600155-0

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Testing Location 7
1.7 Applicable Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Carrier Frequency and Channel 8
2.2 Test Mode 9
2.3 Connection Diagram of Test System 10
2.4 Support Unit used in test configuration and system 10
2.5 EUT Operation Test Setup 11
2.6 Measurement Results Explanation Example 11
3 TEST RESULT **12**
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 12
3.2 Maximum Conducted Output Power Measurement 15
3.3 Power Spectral Density Measurement 16
3.4 Unwanted Emissions Measurement 18
3.5 AC Conducted Emission Measurement 23
3.6 Automatically Discontinue Transmission 25
3.7 Antenna Requirements 26
4 LIST OF MEASURING EQUIPMENT **27**
5 UNCERTAINTY OF EVALUATION **28**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION
APPENDIX D. DUTY CYCLE PLOTS
APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR8O2308E	Rev. 01	Initial issue of report	Jan. 16, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) &15.209(a)	Pass	Under limit 14.83 dB at 40.67 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 11.39 dB at 0.158 MHz
3.6	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.7	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.
The Rainbow City of China Resources,NO.68,Qinghe Middle Street,Haidian District,Beijing,China

1.2 Manufacturer

Xiaomi Communications Co., Ltd.
The Rainbow City of China Resources,NO.68,Qinghe Middle Street,Haidian District,Beijing,China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	M1901F7G
FCC ID	2AFZZ-RMSF7G
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA//HSPA/DC-HSDPA/HSPA+/LTE WLAN 2.4GHz 802.11b/g/n (HT20) WLAN 5GHz 802.11a/n (HT20/HT40) WLAN 5GHz 802.11ac (VHT20/VHT40/VHT80) Bluetooth BR/EDR/LE
IMEI Code	Conducted: 867325040003678/867325040006655 Radiation: 864605040003965/864605040008303 Conduction: 864605040003445/864605040007784
HW Version	P2
SW Version	MIUI10
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5805 MHz
Maximum Output Power	**<5745 MHz ~ 5805 MHz>** 802.11a : 15.85 dBm / 0.0385 W 802.11n HT20 : 13.83 dBm / 0.0242 W 802.11n HT40 : 13.93 dBm / 0.0247 W 802.11ac VHT80: 12.08 dBm / 0.0161 W
99% Occupied Bandwidth	802.11a : 17.48 MHz 802.11n HT20 : 18.73 MHz 802.11n HT40 : 36.66 MHz 802.11ac VHT80 : 75.52 MHz
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)
Antenna Type / Gain	Fixed internal Antenna with gain -5.1 dBi

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC designation No.**	**FCC Test Firm Registration No.**
	TH01-KS CO01-KS 03CH02-KS	CN5013	630927

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	-	-

Note:

1. The above Frequency and Channel in "*" were 802.11n HT40 and 802.11ac VHT40.
2. The above Frequency and Channel in "#" were 802.11ac VHT80.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT80	MCS0

AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable 2 (Charging from adapter 2) + Earphone
Remark: The accessories are from Part 15B worst case.	

Ch. #		Band IV：5725-5850 MHz			
		802.11a	802.11n HT20	802.11n HT40	802.11ac VHT80
L	149	149	149	151	-
M	157	157	157	-	155
H	165	165	165	159	-

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
3.	WLAN AP	DIR-855	KA2DIR855A2	N/A	N/A	Unshielded, 1.8 m
4.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss

Following shows an offset computation example with cable loss 6.6 dB.

Offset(dB) = RF cable loss(dB)

= 6.6 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW ≥ 3 x RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth



Maximum 26dB Bandwidth



Maximum 99% Occupied Bandwidth



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, 10 log(1/x), where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(500kHz/RBW) to the test result.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.2

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log(d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

(3) ANSI C63.10-2013 clause 12.7.3 note 97

As specified by regulatory requirements, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit. However, an out-of-band emission that complies with both the average and peak general regulatory limits is not required to satisfy the peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 7, 2018	Nov. 15, 2018~ Jan. 02, 2019	Aug. 6, 2019	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 18, 2018	Nov. 15, 2018~ Jan. 02, 2019	Jan. 17, 2019	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 18, 2018	Nov. 15, 2018~ Jan. 02, 2019	Jan. 17, 2019	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1435004	50MHz Bandwidth	Jan. 18, 2018	Nov. 15, 2018~ Jan. 02, 2019	Jan. 17, 2019	Conducted (TH01-KS)
Thermal Chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jun. 27, 2018	Nov. 15, 2018~ Jan. 02, 2019	Jun. 26, 2019	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Aug. 06, 2018	Dec. 14, 2018	Aug.05, 2019	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44G,MAX 30dB	Apr. 17, 2018	Dec. 14, 2018	Apr. 16, 2019	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Dec. 14, 2018	Oct. 18, 2019	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-2GHz	Jan. 29, 2018	Dec. 14, 2018	Jan. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 21, 2018	Dec. 14, 2018	Jan. 20, 2019	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 07, 2018	Dec. 14, 2018	Feb. 06, 2019	Radiation (03CH02-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2025788	100MHz-18GHz	Apr. 17, 2018	Dec. 14, 2018	Apr. 16, 2019	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2018	Dec. 14, 2018	Aug. 05, 2019	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 18, 2018	Dec. 14, 2018	Apr. 17, 2019	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Feb. 08, 2018	Dec. 14, 2018	Feb. 07, 2019	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Dec. 14, 2018	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Dec. 14, 2018	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Dec. 14, 2018	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Nov. 13, 2018	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Nov. 13, 2018	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 18, 2017	Nov. 13, 2018	Nov. 17, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Nov. 13, 2018	Oct. 11, 2019	Conduction (CO01-KS)

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.9 dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.8 dB**

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.2 dB**

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.0 dB**

Appendix A. Conducted Test Results

Report Number : FR8O2308E

Test Engineer:	Smile Wang	Temperature:	21~25	°C
Test Date:	2018/11/15~2019/01/02	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	17.38	23.477	15.125	0.5	Pass
11a	6Mbps	1	157	5785	17.48	24.076	15.325	0.5	Pass
11a	6Mbps	1	161	5805	17.48	23.876	15.495	0.5	Pass
HT20	MCS 0	1	149	5745	18.63	24.326	15.125	0.5	Pass
HT20	MCS 0	1	157	5785	18.73	24.625	15.125	0.5	Pass
HT20	MCS 0	1	161	5805	18.73	24.625	15.974	0.5	Pass
HT40	MCS 0	1	151	5755	36.56	41.628	35.125	0.5	Pass
HT40	MCS 0	1	159	5795	36.66	41.808	35.125	0.5	Pass
VHT80	MCS 0	1	155	5775	75.52	82.96	75.125	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.21	15.85	30.00	-5.10		Pass
11a	6Mbps	1	157	5785	0.21	15.27	30.00	-5.10		Pass
11a	6Mbps	1	161	5805	0.21	15.16	30.00	-5.10		Pass
HT20	MCS 0	1	149	5745	0.22	13.83	30.00	-5.10		Pass
HT20	MCS 0	1	157	5785	0.22	13.20	30.00	-5.10		Pass
HT20	MCS 0	1	161	5805	0.22	12.98	30.00	-5.10		Pass
HT40	MCS 0	1	151	5755	0.47	13.93	30.00	-5.10		Pass
HT40	MCS 0	1	159	5795	0.47	13.59	30.00	-5.10		Pass
VHT20	MCS 0	1	149	5745	0.22	11.87	30.00	-5.10		Pass
VHT20	MCS 0	1	157	5785	0.22	11.36	30.00	-5.10		Pass
VHT20	MCS 0	1	161	5805	0.22	11.13	30.00	-5.10		Pass
VHT40	MCS 0	1	151	5755	0.44	11.92	30.00	-5.10		Pass
VHT40	MCS 0	1	159	5795	0.44	11.46	30.00	-5.10		Pass
VHT80	MCS 0	1	155	5775	0.77	12.08	30.00	-5.10		Pass

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.21	2.22	2.00	30.00	-5.10	Pass
11a	6Mbps	1	157	5785	0.21	2.22	1.25	30.00	-5.10	Pass
11a	6Mbps	1	161	5805	0.21	2.22	3.08	30.00	-5.10	Pass
HT20	MCS 0	1	149	5745	0.22	2.22	0.31	30.00	-5.10	Pass
HT20	MCS 0	1	157	5785	0.22	2.22	-0.82	30.00	-5.10	Pass
HT20	MCS 0	1	161	5805	0.22	2.22	0.82	30.00	-5.10	Pass
HT40	MCS 0	1	151	5755	0.47	2.22	-2.78	30.00	-5.10	Pass
HT40	MCS 0	1	159	5795	0.47	2.22	-3.34	30.00	-5.10	Pass
VHT80	MCS 0	1	155	5775	0.77	2.22	-7.23	30.00	-5.10	Pass

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhao	**Temperature :**	25.3~26.2℃
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15E LISN-L-181013-060103 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.154	54.00	-11.78	65.78	43.30	0.23	10.47	QP
2	0.154	39.00	-16.78	55.78	28.30	0.23	10.47	Average
3	0.168	49.86	-15.22	65.08	39.20	0.23	10.43	QP
4	0.168	33.86	-21.22	55.08	23.20	0.23	10.43	Average
5	0.219	47.77	-15.11	62.88	37.20	0.22	10.35	QP
6	0.219	31.47	-21.41	52.88	20.90	0.22	10.35	Average
7	0.262	42.15	-19.23	61.38	31.60	0.22	10.33	QP
8	0.262	26.15	-25.23	51.38	15.60	0.22	10.33	Average
9	0.315	40.13	-19.71	59.84	29.61	0.22	10.30	QP
10	0.315	27.83	-22.01	49.84	17.31	0.22	10.30	Average
11	0.373	39.80	-18.63	58.43	29.29	0.23	10.28	QP
12	0.373	23.10	-25.33	48.43	12.59	0.23	10.28	Average

Test Engineer :	Amos Zhao	**Temperature :**	25.3~26.2℃
		Relative Humidity :	48~50%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC PART 15E LISN-N-181013-060103 NEUTRAL

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.151	49.99	-15.97	65.96	39.30	0.21	10.48	QP
2		0.151	34.89	-21.07	55.96	24.20	0.21	10.48	Average
3	*	0.158	54.17	-11.39	65.56	43.50	0.21	10.46	QP
4		0.158	34.97	-20.59	55.56	24.30	0.21	10.46	Average
5		0.167	45.94	-19.18	65.12	35.29	0.21	10.44	QP
6		0.167	29.94	-25.18	55.12	19.29	0.21	10.44	Average
7		0.214	47.15	-15.90	63.05	36.60	0.20	10.35	QP
8		0.214	28.85	-24.20	53.05	18.30	0.20	10.35	Average
9		0.266	42.02	-19.23	61.25	31.50	0.20	10.32	QP
10		0.266	24.72	-26.53	51.25	14.20	0.20	10.32	Average
11		0.637	35.93	-20.07	56.00	25.49	0.20	10.24	QP
12		0.637	27.63	-18.37	46.00	17.19	0.20	10.24	Average

Appendix C. Radiated Spurious Emission

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5644	49.16	-19.14	68.3	41.35	30.3	8.93	31.42	107	315	P	H
		5697.6	57.02	-46.51	103.53	48.81	30.72	8.98	31.49	107	315	P	H
		5719.6	57.98	-52.81	110.79	49.5	30.99	9.01	31.52	107	315	P	H
		5724.4	63.08	-57.85	120.93	54.6	30.99	9.01	31.52	107	315	P	H
		5744	102.47	------	------	93.86	31.13	9.03	31.55	107	315	P	H
		5744	95.18	------	------	86.57	31.13	9.03	31.55	107	315	A	H
		5640.4	48.28	-20.02	68.3	40.47	30.3	8.93	31.42	100	275	P	V
		5696.8	50.99	-51.95	102.94	42.78	30.72	8.98	31.49	100	275	P	V
		5714.8	59.28	-50.17	109.45	50.95	30.85	9	31.52	100	275	P	V
		5724.8	62.41	-59.43	121.84	53.93	30.99	9.01	31.52	100	275	P	V
		5748	98.86	------	------	90.25	31.13	9.03	31.55	100	275	P	V
		5748	93.86	------	------	85.25	31.13	9.03	31.55	100	275	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 161 5805MHz		5806	101.4	------	------	92.26	31.68	9.07	31.61	100	313	P	H
		5806	94.19	------	------	85.05	31.68	9.07	31.61	100	313	A	H
		5850.4	50.29	-71.1	121.39	40.95	31.96	9.06	31.68	100	313	P	H
		5857.6	50.25	-59.92	110.17	40.77	32.1	9.06	31.68	100	313	P	H
		5885.2	49.88	-47.85	97.73	40.39	32.15	9.05	31.71	100	313	P	H
		5958.4	49.55	-18.75	68.3	39.85	32.42	9.02	31.74	100	313	P	H
		5804	102.79	------	------	93.65	31.68	9.07	31.61	265	224	P	V
		5804	95.15	------	------	86.01	31.68	9.07	31.61	265	224	A	V
		5850.8	50.33	-70.15	120.48	40.99	31.96	9.06	31.68	265	224	P	V
		5865.6	53.92	-54.01	107.93	44.46	32.1	9.06	31.7	265	224	P	V
		5908.4	49.41	-31.14	80.55	39.82	32.26	9.04	31.71	265	224	P	V
		5930	49.61	-18.69	68.3	40	32.31	9.03	31.73	265	224	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	45	-29	74	54.79	39.68	13.36	62.83	100	360	P	H
		11490	45.02	-28.98	74	54.81	39.68	13.36	62.83	300	0	P	V
802.11a CH 157 5785MHz		11570	44.38	-29.62	74	54.27	39.49	13.44	62.82	100	360	P	H
		11570	44.13	-29.87	74	54.02	39.49	13.44	62.82	300	0	P	V
802.11a CH 161 5805MHz		11610	44.22	-29.78	74	54.17	39.39	13.47	62.81	100	0	P	H
		11610	44.52	-29.48	74	54.47	39.39	13.47	62.81	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5604.4	48.57	-19.73	68.3	40.74	30.36	8.9	31.43	100	338	P	H
		5699.2	56.86	-47.85	104.71	48.65	30.72	8.98	31.49	100	338	P	H
		5719.6	59.76	-51.03	110.79	51.28	30.99	9.01	31.52	100	338	P	H
		5724.8	64.32	-57.52	121.84	55.84	30.99	9.01	31.52	100	338	P	H
		5742	98.7	------	------	90.09	31.13	9.03	31.55	100	338	P	H
		5742	92.54	------	------	83.93	31.13	9.03	31.55	100	338	A	H
		5608.4	49.49	-18.81	68.3	41.66	30.36	8.9	31.43	172	252	P	V
		5695.2	57.34	-44.42	101.76	49.13	30.72	8.98	31.49	172	252	P	V
		5707.2	58.9	-48.42	107.32	50.57	30.85	9	31.52	172	252	P	V
		5723.6	61.57	-57.54	119.11	53.09	30.99	9.01	31.52	172	252	P	V
		5748	98.8	------	------	90.19	31.13	9.03	31.55	172	252	P	V
		5748	92.21	------	------	83.6	31.13	9.03	31.55	172	252	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 161 5805MHz		5804	98.8	------	------	89.66	31.68	9.07	31.61	100	314	P	H
		5804	90.9	------	------	81.76	31.68	9.07	31.61	100	314	A	H
		5851.2	51.21	-68.35	119.56	41.87	31.96	9.06	31.68	100	314	P	H
		5864	50.34	-58.04	108.38	40.88	32.1	9.06	31.7	100	314	P	H
		5906.4	49.39	-32.64	82.03	39.8	32.26	9.04	31.71	100	314	P	H
		5956	49.67	-18.63	68.3	39.97	32.42	9.02	31.74	100	314	P	H
		5806	98.61	------	------	89.47	31.68	9.07	31.61	100	199	P	V
		5806	90.86	------	------	81.72	31.68	9.07	31.61	100	199	A	V
		5852.8	48.82	-67.09	115.91	39.48	31.96	9.06	31.68	100	199	P	V
		5859.6	53.1	-56.51	109.61	43.64	32.1	9.06	31.7	100	199	P	V
		5886.8	50.29	-46.25	96.54	40.8	32.15	9.05	31.71	100	199	P	V
		5959.6	50.3	-18	68.3	40.6	32.42	9.02	31.74	100	199	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	45.96	-28.04	74	55.75	39.68	13.36	62.83	100	360	P	H
		11490	45.6	-28.4	74	55.39	39.68	13.36	62.83	300	0	P	V
802.11n HT20 CH 157 5785MHz		11570	45.23	-28.77	74	55.12	39.49	13.44	62.82	100	360	P	H
		11570	44.08	-29.92	74	53.97	39.49	13.44	62.82	300	0	P	V
802.11n HT20 CH 161 5805MHz		11610	44.57	-29.43	74	54.52	39.39	13.47	62.81	100	360	P	H
		11610	43.39	-30.61	74	53.34	39.39	13.47	62.81	300	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5627.6	48.41	-19.89	68.3	40.59	30.33	8.92	31.43	100	312	P	H
		5698.4	56.23	-47.89	104.12	48.02	30.72	8.98	31.49	100	312	P	H
		5716.4	64.19	-45.7	109.89	55.86	30.85	9	31.52	100	312	P	H
		5724.8	64.06	-57.78	121.84	55.58	30.99	9.01	31.52	100	312	P	H
		5750	97.41	------	------	88.8	31.13	9.03	31.55	100	312	P	H
		5750	89.85	------	------	81.24	31.13	9.03	31.55	100	312	A	H
		5852	48.98	-68.76	117.74	39.64	31.96	9.06	31.68	100	312	P	H
		5858.4	49.52	-60.43	109.95	40.06	32.1	9.06	31.7	100	312	P	H
802.11n		5896.4	49.21	-40.22	89.43	39.66	32.21	9.05	31.71	100	312	P	H
HT40		5972.8	49.02	-19.28	68.3	39.29	32.47	9.02	31.76	100	312	P	H
CH 151		5636	48.91	-19.39	68.3	41.1	30.3	8.93	31.42	100	251	P	V
5755MHz		5692.4	57.36	-42.34	99.7	49.15	30.72	8.98	31.49	100	251	P	V
		5718.4	62.68	-47.77	110.45	54.2	30.99	9.01	31.52	100	251	P	V
		5724.4	63.24	-57.69	120.93	54.76	30.99	9.01	31.52	100	251	P	V
		5752	96.22	------	------	87.45	31.27	9.05	31.55	100	251	P	V
		5752	89.2	------	------	80.43	31.27	9.05	31.55	100	251	A	V
		5850.4	48.7	-72.69	121.39	39.36	31.96	9.06	31.68	100	251	P	V
		5860.4	49.23	-60.16	109.39	39.77	32.1	9.06	31.7	100	251	P	V
		5919.2	49.27	-23.31	72.58	39.7	32.26	9.04	31.73	100	251	P	V
		6000	50.02	-18.28	68.3	40.27	32.52	9.01	31.78	100	251	P	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5607.6	48.16	-20.14	68.3	40.33	30.36	8.9	31.43	100	285	P	H
		5690.4	48.58	-49.64	98.22	40.37	30.72	8.98	31.49	100	285	P	H
		5706	52.37	-54.61	106.98	44.04	30.85	9	31.52	100	285	P	H
		5721.2	48.77	-64.87	113.64	40.29	30.99	9.01	31.52	100	285	P	H
		5792	96.83	------	------	87.81	31.55	9.08	31.61	100	285	P	H
		5792	89.15	------	------	80.13	31.55	9.08	31.61	100	285	A	H
		5850.4	53.98	-67.41	121.39	44.64	31.96	9.06	31.68	100	285	P	H
		5858	51.29	-58.77	110.06	41.83	32.1	9.06	31.7	100	285	P	H
		5887.6	50.07	-45.88	95.95	40.52	32.21	9.05	31.71	100	285	P	V
		5936.4	50.33	-17.97	68.3	40.73	32.31	9.03	31.74	100	285	P	V
		5636.4	48.68	-19.62	68.3	40.87	30.3	8.93	31.42	264	224	P	V
		5699.6	49.98	-55.03	105.01	41.77	30.72	8.98	31.49	264	224	P	V
		5715.6	56.03	-53.64	109.67	47.7	30.85	9	31.52	264	224	P	V
		5724	58.63	-61.39	120.02	50.15	30.99	9.01	31.52	264	224	P	V
		5790	97.8	------	------	88.78	31.55	9.08	31.61	264	224	P	V
		5790	90.63	------	------	81.61	31.55	9.08	31.61	264	224	A	V
		5852.8	50.19	-65.72	115.91	40.85	31.96	9.06	31.68	264	224	P	V
		5865.6	52.35	-55.58	107.93	42.89	32.1	9.06	31.7	264	224	P	V
		5899.2	50.34	-37.01	87.35	40.79	32.21	9.05	31.71	264	224	P	V
		5952	49.24	-19.06	68.3	39.58	32.37	9.03	31.74	264	224	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	46.01	-27.99	74	55.77	39.7	13.37	62.83	100	360	P	H
		11510	44.9	-29.1	74	54.66	39.7	13.37	62.83	300	0	P	V
802.11n HT40 CH 159 5795MHz		11590	43.6	-30.4	74	53.52	39.44	13.45	62.81	100	360	P	H
		11590	44.01	-29.99	74	53.93	39.44	13.45	62.81	300	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 155 5775MHz		5648	48.16	-20.14	68.3	40.35	30.3	8.93	31.42	100	338	P	H
		5695.6	57.71	-44.35	102.06	49.5	30.72	8.98	31.49	100	338	P	H
		5714.8	63.47	-45.98	109.45	55.14	30.85	9	31.52	100	338	P	H
		5724.4	59.02	-61.91	120.93	50.54	30.99	9.01	31.52	100	338	P	H
		5766	91.81	------	------	83.07	31.27	9.05	31.58	100	338	P	H
		5766	83.1	------	------	74.36	31.27	9.05	31.58	100	338	A	H
		5854.8	52.97	-58.39	111.36	43.49	32.1	9.06	31.68	100	338	P	H
		5868	52.16	-55.1	107.26	42.7	32.1	9.06	31.7	100	338	P	H
		5878.4	51.67	-51.1	102.77	42.17	32.15	9.05	31.7	100	338	P	H
		5999.6	49.73	-18.57	68.3	39.98	32.52	9.01	31.78	100	338	P	H
		5602.4	48.85	-19.45	68.3	41.04	30.36	8.9	31.45	253	224	P	V
		5694.4	59.09	-42.08	101.17	50.88	30.72	8.98	31.49	253	224	P	V
		5719.6	61.01	-49.78	110.79	52.53	30.99	9.01	31.52	253	224	P	V
		5722.8	61.79	-55.5	117.29	53.31	30.99	9.01	31.52	253	224	P	V
		5766	93.48	------	------	84.74	31.27	9.05	31.58	253	224	P	V
		5766	85.62	------	------	76.88	31.27	9.05	31.58	253	224	A	V
		5851.2	53.11	-66.45	119.56	43.77	31.96	9.06	31.68	253	224	P	V
		5858	52.37	-57.69	110.06	42.91	32.1	9.06	31.7	253	224	P	V
		5881.6	51.47	-48.93	100.4	41.97	32.15	9.05	31.7	253	224	P	V
		5980	50.3	-18	68.3	40.57	32.47	9.02	31.76	253	224	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11ac VHT80 (Harmonic @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11ac VHT80 CH 155 5775MHz		11550	44.57	-29.43	74	54.43	39.54	13.42	62.82	100	0	P	H
		11550	44.25	-29.75	74	54.11	39.54	13.42	62.82	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

Emission below 1GHz

5GHz WIFI 802.11a (LF @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
5GHz 802.11n HT40 LF		34.85	21.42	-18.58	40	32.47	21.4	0.5	32.95			P	H
		50.37	17.57	-22.43	40	35.81	14.1	0.62	32.96			P	H
		123.12	14.9	-28.6	43.5	28.93	17.81	1.1	32.94			P	H
		398.6	23.63	-22.37	46	33.05	21.58	2.12	33.12			P	H
		746.83	25.67	-20.33	46	30.34	25.46	2.99	33.12			P	H
		957.32	27.94	-18.06	46	29.1	27.02	3.46	31.64	100	0	P	H
		40.67	25.17	-14.83	40	39.41	18.19	0.55	32.98	100	0	P	V
		47.46	24.91	-15.09	40	41.93	15.33	0.61	32.96			P	V
		125.06	15.84	-27.66	43.5	29.91	17.75	1.12	32.94			P	V
		408.3	23.72	-22.28	46	32.96	21.76	2.14	33.14			P	V
		671.17	24.95	-21.05	46	30.65	24.81	2.78	33.29			P	V
		949.56	28	-18	46	29.31	26.95	3.45	31.71			P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	95.20	2.063	0.48	0.51KHz
5GHz 802.11n HT20	94.88	1.928	0.52	0.56KHz
5GHz 802.11n HT40	89.47	0.937	1.07	1.10KHz
5GHz 802.11acVHT80	82.86	0.464	2.16	2.20KHz

802.11a



802.11n HT20



802.11n HT40



802.11ac VHT80