FCC RF Test Report

APPLICANT	:	Xiaomi Communications Co., Ltd.
EQUIPMENT	:	Mobile Phone
BRAND NAME	:	XIAOMI
MODEL NAME	:	2211133G
FCC ID	:	2AFZZ133G
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DSS) Spread Spectrum Transmitter
TEST DATE(S)	:	Oct. 19, 2022 ~ Nov. 05, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Testing Location 7
1.7 Test Software 7
1.8 Applicable Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Carrier Frequency Channel 8
2.2 Test Mode 9
2.3 Connection Diagram of Test System 10
2.4 Support Unit used in test configuration and system 11
2.5 EUT Operation Test Setup 11
2.6 Measurement Results Explanation Example 11
3 TEST RESULT **12**
3.1 Number of Channel Measurement 12
3.2 Hopping Channel Separation Measurement 16
3.3 Dwell Time Measurement 35
3.4 20dB Bandwidth Measurement 37
3.5 Output Power Measurement 56
3.6 Conducted Band Edges Measurement 57
3.7 Conducted Spurious Emission Measurement 82
3.8 Radiated Band Edges and Spurious Emission Measurement 119
3.9 AC Conducted Emission Measurement 123
3.10 Antenna Requirements 125
4 LIST OF MEASURING EQUIPMENT **127**
5 UNCERTAINTY OF EVALUATION **128**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION
APPENDIX D. DUTY CYCLE PLOTS
APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR291702A	Rev. 01	Initial issue of report	Nov. 11, 2022

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	-	Report only	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 11.34 dB at 39.700 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 16.82 dB at 1.310 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.
#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.
#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	XIAOMI
Model Name	2211133G
FCC ID	2AFZZ133G
IMEI Code	Conducted: 866917060028337/866917060028345 Conduction: 866917060031976/866917060031984 Radiation: 866917060031372/866917060031380
HW Version	P2
SW Version	MIUI 14
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	**<SISO Ant. 1>** Bluetooth BR(1Mbps) : 16.48 dBm (0.0445 W) Bluetooth EDR (2Mbps) : 16.15 dBm (0.0412 W) Bluetooth EDR (3Mbps) : 16.86 dBm (0.0485 W) **<SISO Ant. 2>** Bluetooth BR(1Mbps) : 17.32 dBm (0.0540 W) Bluetooth EDR (2Mbps) : 16.63 dBm (0.0460 W) Bluetooth EDR (3Mbps) : 17.29 dBm (0.0536W) **<Beamforming Ant. 1+2>** Bluetooth BR(1Mbps) : 14.63 dBm (0.0290 W) Bluetooth EDR (2Mbps) : 13.29 dBm (0.0213 W) Bluetooth EDR (3Mbps) : 13.63 dBm (0.0231 W)
Antenna Type / Gain	**Ant. 1:** PIFA Antenna type with gain -3.5 dBi **Ant. 2:** PIFA Antenna type with gain -0.1 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) :π/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

Note:

1. Bluetooth Ant. 1 / Ant. 2 corresponding to EUT Photo Ant. 15 / Ant. 18
2. Bluetooth BR/EDR supports Beamforming mode.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	CO01-KS 03CH07-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH07-KS	AUDIX	E3	6.2009-8-24al
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	**Data Rate / Modulation**		
	Bluetooth BR 1Mbps GFSK	**Bluetooth EDR 2Mbps π/4-DQPSK**	**Bluetooth EDR 3Mbps 8-DPSK**
Conducted Test Cases	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated Test Cases	**Bluetooth BR/EDR** 3Mbps **8-DPSK**		
	As Appendix C		
AC Conducted Emission	Mode 1 : GSM 850 Idle + BT Link + WLAN Link(2.4G) + USB Cable (Charging From Adapter)		
Remark: For Radiated Test Cases, The tests were performed with Adapter and USB Cable .			

2.3 Connection Diagram of Test System

For Conducted Emission:



For Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded, 1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
5.	SD Card	Kingston	8GB	N/A	N/A	N/A
6.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8m

2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.8 dB.

Offset(dB) = RF cable loss(dB).

= 5.8 (dB)

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

Number of Hopping Channel Plot on Channel 00 - 78



Date: 19.OCT.2022 14:36:58



Date: 19.OCT.2022 14:37:59

Beamforming

<Ant.1+2(1)>

Number of Hopping Channel Plot on Channel 00 - 78



Date: 3.NOV.2022 22:13:42



Date: 3.NOV.2022 22:14:05

<Ant.1+2(2)>

Number of Hopping Channel Plot on Channel 00 - 78



Date: 3.NOV.2022 23:23:28



Date: 3.NOV.2022 23:23:47

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peaks of two adjacent channels;
   RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

< Ant.1>

<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 19.OCT.2022 09:48:38

Channel Separation Plot on Channel 39 - 40



Date: 19.OCT.2022 09:55:07

Channel Separation Plot on Channel 77 - 78



Date: 19.OCT.2022 10:11:48

<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 19.OCT.2022 10:26:20

Channel Separation Plot on Channel 39 - 40



Date: 19.OCT.2022 10:46:06

Channel Separation Plot on Channel 77 - 78



Date: 19.OCT.2022 10:37:27

<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 19.OCT.2022 10:53:33

Channel Separation Plot on Channel 39 - 40



Date: 19.OCT.2022 11:06:51

Channel Separation Plot on Channel 77 - 78



Date: 19.OCT.2022 11:12:22

< Ant.2>

<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 19.OCT.2022 12:02:50

Channel Separation Plot on Channel 39 - 40



Date: 19.OCT.2022 13:57:14

Channel Separation Plot on Channel 77 - 78



Date: 19.OCT.2022 14:01:58

<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 19.OCT.2022 14:10:42

Channel Separation Plot on Channel 39 - 40



Date: 19.OCT.2022 14:15:00

Channel Separation Plot on Channel 77 - 78



Date: 19.OCT.2022 14:19:32

<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 19.OCT.2022 14:25:10

Channel Separation Plot on Channel 39 - 40



Date: 19.OCT.2022 14:29:26

Channel Separation Plot on Channel 77 - 78



Date: 19.OCT.2022 14:34:47

Beamforming

< Ant.1+2(1)>

<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 3.NOV.2022 22:01:37

Channel Separation Plot on Channel 39 - 40



Date: 3.NOV.2022 22:00:23

Channel Separation Plot on Channel 77 - 78



Date: 3.NOV.2022 22:08:51

<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 3.NOV.2022 22:22:16

Channel Separation Plot on Channel 39 - 40



Date: 3.NOV.2022 22:26:40

Channel Separation Plot on Channel 77 - 78



Date: 3.NOV.2022 22:34:54

<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 3.NOV.2022 22:43:40

Channel Separation Plot on Channel 39 - 40



Date: 3.NOV.2022 22:48:50

Channel Separation Plot on Channel 77 - 78



Date: 3.NOV.2022 22:50:00

< Ant.1+2(2)>

<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 3.NOV.2022 23:21:13

Channel Separation Plot on Channel 39 - 40



Date: 3.NOV.2022 23:38:16

Channel Separation Plot on Channel 77 - 78



Date: 3.NOV.2022 23:22:56

<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 3.NOV.2022 23:51:32

Channel Separation Plot on Channel 39 - 40



Date: 4.NOV.2022 00:27:39

Channel Separation Plot on Channel 77 - 78



Date: 4.NOV.2022 00:25:03

<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 4.NOV.2022 00:53:05

Channel Separation Plot on Channel 39 - 40



Date: 4.NOV.2022 00:54:17

Channel Separation Plot on Channel 77 - 78



Date: 4.NOV.2022 00:56:32

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

Package Transfer Time Plot (Worse case)



Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots (5 Transmit and 1 Receive slot) in 79 hopping channels.

   With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),

   Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.

2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.

   With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),

   Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.

3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB Bandwidth Measurement

3.4.1 Limit of 20dB Bandwidth

Reporting only

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
   Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
   The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
   Sweep = auto; Detector function = peak;
   Trace = max hold.
5. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

< Ant.1>

<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.OCT.2022 09:41:16

20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2022 09:52:00

20 dB Bandwidth Plot on Channel 78



Date: 19.OCT.2022 09:58:32

<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.OCT.2022 10:17:17

20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2022 10:27:42

20 dB Bandwidth Plot on Channel 78



Date: 19.OCT.2022 10:33:09

<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.OCT.2022 10:48:00

20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2022 11:02:33

20 dB Bandwidth Plot on Channel 78



< Ant.2>

<1Mbps>

20 dB Bandwidth Plot on Channel 00



20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2022 13:43:09

20 dB Bandwidth Plot on Channel 78



Date: 19.OCT.2022 13:58:44

<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.OCT.2022 14:06:10

20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2022 14:12:08

20 dB Bandwidth Plot on Channel 78



Date: 19.OCT.2022 14:16:36

<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 19.OCT.2022 14:21:20

20 dB Bandwidth Plot on Channel 39



Date: 19.OCT.2022 14:26:44

20 dB Bandwidth Plot on Channel 78



Date: 19.OCT.2022 11:08:02

Beamforming

< Ant.1+2(1)>

<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 3.NOV.2022 21:48:38

20 dB Bandwidth Plot on Channel 39



Date: 3.NOV.2022 21:55:34