



FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Tablet Computer
BRAND NAME : Xiaomi
MODEL NAME : 24091RPADG
FCC ID : 2AFZZ1RPADG
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Oct. 26, 2024 ~ Nov. 09, 2024

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (KunShan)

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Test Software.....	6
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	9
2.4 EUT Operation Test Setup	10
2.5 Measurement Results Explanation Example.....	10
3 TEST RESULT	11
3.1 6dB Bandwidth Measurement	11
3.2 Output Power Measurement.....	12
3.3 Conducted Band Edges and Spurious Emission Measurement	14
3.4 Radiated Band Edges and Spurious Emission Measurement	15
3.5 Antenna Requirements.....	19
4 LIST OF MEASURING EQUIPMENT.....	20
5 MEASUREMENT UNCERTAINTY	21
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR480902-02B	Rev. 01	Initial issue of report	Dec. 02, 2024



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
-	-	99% Bandwidth	-	Not Required	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
-	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Not Required	-
3.3	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 30\text{dBc}$	Pass	-
3.4	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 8.92 dB at 2486.92 MHz
-	15.207	AC Conducted Emission	15.207(a)	Not Required	-
3.5	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Remark:

1. Not required means after assessing, test items are not necessary to carry out.
2. This is a variant report for 24091RPADG, the difference is to add a 2.4 GHz filter. Based on the similarity between current and previous project, only the related test cases from original test report (Sporton Report Number FR480902B) were verified for the differences.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet Computer
Brand Name	Xiaomi
Model Name	24091RPADG
FCC ID	2AFZZ1RPADG
SN Code	Conducted: 6287b57e Radiation: 9P439K000030
HW Version	135100O81
SW Version	Xiaomi HyperOS 2.0
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna (Average Power)	<SISO_ANT0> BLE 125Kbps: 5.55 dBm (0.0036 W) BLE 2Mbps: 5.52 dBm (0.0036 W) <SISO_ANT2> BLE 125Kbps: 5.62 dBm (0.0036 W) BLE 2Mbps: 5.79 dBm (0.0038 W)
Antenna Type / Gain	<ANT0> : PIFA Antenna with gain -3.8 dBi <ANT2> : Resonant Cavity Antenna with gain -1.57 dBi
Type of Modulation	Bluetooth LE : GFSK

Note:

1. BLE ANT 0 & ANT 2 can't transmit simultaneously.
2. For BLE 125Kbps/500Kbps/1Mbps, they are same modulation and transmit bandwidth, thus only full test BLE 125Kbps to cover BLE 500Kbps/1Mbps by referred to the highest output power.
3. BLE 2Mbps does not support the three primary advertising channels (CH00/12/39).



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH08-KS	CN1257	314309

Note: Test data subcontracted: Radiation test case in section 3.4 of this report

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH08-KS	AUDIX	E3	210616



1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH39_2480 MHz_BLE 125Kbps
	Mode 2: Bluetooth Tx CH38_2478 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH38_2478 MHz_BLE 2Mbps
Remark: For Radiated Test Cases, The tests were performed with Adapter and USB Cable.	

2.3 Connection Diagram of Test System





2.4 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.04 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 2.04 + 10 = 12.04 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



**3.2.5 Test Result of Average Output Power****<SISO_ANT0>**

Mode	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
BLE 125kbps	39	1	5.55	30.00	Pass

Mode	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
BLE 2Mbps	38	1	5.52	30.00	Pass

<SISO_ANT2>

Mode	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
BLE 125kbps	39	1	5.62	30.00	Pass

Mode	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
BLE 2Mbps	38	1	5.79	30.00	Pass

3.3 Conducted Band Edges and Spurious Emission Measurement

3.3.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.3.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.4 Radiated Band Edges and Spurious Emission Measurement

3.4.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.4.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.4.7 Duty Cycle

Please refer to Appendix C.

3.4.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix B.



3.5 Antenna Requirements

3.5.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.5.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.5.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400023	3Hz~8.5GHz;Max 30dBm	Jan. 02, 2024	Nov. 09, 2024	Jan. 01, 2025	Radiation (03CH08-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY57441079	10Hz~44GHz	Oct. 09, 2024	Nov. 09, 2024	Oct. 08, 2025	Radiation (03CH08-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Nov. 09, 2024	Sep. 07, 2025	Radiation (03CH08-KS)
Bilog Antenna	TESEQ	CBL 6111D	59915	30MHz~1GHz	Aug. 18, 2024	Nov. 09, 2024	Aug.17, 2025	Radiation (03CH08-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00240138	1GHz~18GHz	Jul. 06, 2024	Nov. 09, 2024	Jul. 05, 2025	Radiation (03CH08-KS)
high gain Amplifier	EM	EM01G18GA	060845	1Ghz~18Ghz	Jan. 03, 2024	Nov. 09, 2024	Jan. 02, 2025	Radiation (03CH08-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 27, 2024	Nov. 09, 2024	Jan. 26, 2025	Radiation (03CH08-KS)
Amplifier	SONOMA	310N	413741	9KHz~1GHz	Jan. 02, 2024	Nov. 09, 2024	Jan. 01, 2025	Radiation (03CH08-KS)
Amplifier	Keysight	83017A	MY53270417	500MHz~26.5GHz	Oct. 09, 2024	Nov. 09, 2024	Oct. 08, 2025	Radiation (03CH08-KS)
Amplifier	EM	EM18G40GGA	060728	18~40GHz	Jan. 02, 2024	Nov. 09, 2024	Jan. 01, 2025	Radiation (03CH08-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Nov. 09, 2024	NCR	Radiation (03CH08-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Nov. 09, 2024	NCR	Radiation (03CH08-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Nov. 09, 2024	NCR	Radiation (03CH08-KS)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Oct. 26, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 29, 2023	Oct. 26, 2024	Dec. 28, 2024	Conducted (TH01-SZ)
Thermo meter	Anymetre	JR593	#7	- 10℃ ~ 50℃ 10%RH~99%RH	Apr. 09, 2024	Oct. 26, 2024	Apr. 08, 2025	Conducted (TH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Conducted Power Spectral Density	±1.32 dB
Frequency	±1.3 Hz

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.30 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.04 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.26 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.40 dB
---	---------

----- THE END -----



Appendix A. Conducted Test Results



Ambient Condition: 24-26 °C, 45-55 %RH

Test Date: 2024.10.26 Test Engineer: Chen ZhiQiang


DTS Bandwidth



Test Result


TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_2M	Ant0	2478	1.14	2477.44	2478.58	0.5	PASS
	Ant2	2478	1.15	2477.44	2478.58	0.5	PASS
BLE_125K	Ant0	2480	0.61	2479.70	2480.31	0.5	PASS
	Ant2	2480	0.60	2479.70	2480.31	0.5	PASS



Test Graphs










Reference level measurement



Test Result


TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_2M	Ant0	2478	2478.01	4.70
	Ant2	2478	2478.01	5.11
BLE_125K	Ant0	2480	2480.01	4.72
	Ant2	2480	2480.01	4.79



Test Graphs










Band edge measurements



Test Result


TestMode	Antenna	Channel Name	Freq(MHz)	RefLevel[dBm/100KHz]	Result[dBm/100KHz]	Limit[dBm/100KHz]	Verdict
BLE_2M	Ant0	High	2478	4.70	-53.64	≤-25.3	PASS
	Ant2	High	2478	5.11	-53.44	≤-24.89	PASS
BLE_125K	Ant0	High	2480	4.72	-53.86	≤-25.28	PASS
	Ant2	High	2480	4.79	-52.91	≤-25.21	PASS



Test Graphs










Conducted Spurious Emission



Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
BLE_2M	Ant0	2478	30~1000	4.70	-45.99	≤-25.3	PASS
			1000~26500	4.70	-35.76	≤-25.3	PASS
	Ant2	2478	30~1000	5.11	-45.38	≤-24.89	PASS
			1000~26500	5.11	-35.48	≤-24.89	PASS
BLE_125K	Ant0	2480	30~1000	4.72	-45.99	≤-25.28	PASS
			1000~26500	4.72	-36.01	≤-25.28	PASS
	Ant2	2480	30~1000	4.79	-45.74	≤-25.21	PASS
			1000~26500	4.79	-36.33	≤-25.21	PASS






Test Graphs













Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Koi Ji	Relative Humidity :	51-52%
		Temperature :	20.9-21.4℃





Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	0	Bluetooth-LE	38	2478	2Mbps	-	-





Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE	38	2486.92	45.08	54.00	-8.92	V	AVERAGE	Pass	Band Edge
1	Bluetooth-LE	38	7434.00	42.65	74.00	-31.35	H	PEAK	Pass	Harmonic



Mode	1																																																																																																												
	Band Edge																																																																																																												
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																																																												
ANT	0																																																																																																												
Pol.	Horizontal						Fundamental																																																																																																						
Peak																																																																																																													
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.70</td><td>54.97</td><td>74.00</td><td>-19.03</td><td>39.01</td><td>32.37</td><td>8.24</td><td>30.65</td><td>6.00</td><td>311</td><td>69 PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2484.70	54.97	74.00	-19.03	39.01	32.37	8.24	30.65	6.00	311	69 PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>98.51</td><td>-----</td><td>-----</td><td>82.59</td><td>32.36</td><td>8.22</td><td>30.66</td><td>6.00</td><td>311</td><td>69 PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	98.51	-----	-----	82.59	32.36	8.22	30.66	6.00	311
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	2484.70	54.97	74.00	-19.03	39.01	32.37	8.24	30.65	6.00	311	69 PEAK																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	2478.00	98.51	-----	-----	82.59	32.36	8.22	30.66	6.00	311	69 PEAK																																																																																																		
Avg																																																																																																													
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2497.18</td><td>44.70</td><td>54.00</td><td>-9.30</td><td>28.70</td><td>32.39</td><td>8.26</td><td>30.65</td><td>6.00</td><td>311</td><td>69 AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2497.18	44.70	54.00	-9.30	28.70	32.39	8.26	30.65	6.00	311	69 AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>96.65</td><td>-----</td><td>-----</td><td>80.73</td><td>32.36</td><td>8.22</td><td>30.66</td><td>6.00</td><td>311</td><td>69 AVERAGE</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	96.65	-----	-----	80.73	32.36	8.22	30.66	6.00	311
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	2497.18	44.70	54.00	-9.30	28.70	32.39	8.26	30.65	6.00	311	69 AVERAGE																																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																				
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	2478.00	96.65	-----	-----	80.73	32.36	8.22	30.66	6.00	311	69 AVERAGE																																																																																																		



Mode	1																																																																																																			
	Band Edge																																																																																																			
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																																																			
ANT	0																																																																																																			
Pol.	Vertical						Fundamental																																																																																													
Peak																																																																																																				
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2491.06</td><td>55.59</td><td>74.00</td><td>-18.41</td><td>39.61</td><td>32.38</td><td>8.25</td><td>30.65</td><td>6.00</td><td>159</td><td>360</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2491.06	55.59	74.00	-18.41	39.61	32.38	8.25	30.65	6.00	159	360	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>98.38</td><td>-----</td><td>-----</td><td>82.46</td><td>32.36</td><td>8.22</td><td>30.66</td><td>6.00</td><td>159</td><td>360</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	98.38	-----	-----	82.46	32.36	8.22	30.66	6.00	159	360	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2491.06	55.59	74.00	-18.41	39.61	32.38	8.25	30.65	6.00	159	360	PEAK																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2478.00	98.38	-----	-----	82.46	32.36	8.22	30.66	6.00	159	360	PEAK																																																																																								
Avg																																																																																																				
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2486.92</td><td>45.08</td><td>54.00</td><td>-8.92</td><td>29.12</td><td>32.37</td><td>8.24</td><td>30.65</td><td>6.00</td><td>159</td><td>360</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2486.92	45.08	54.00	-8.92	29.12	32.37	8.24	30.65	6.00	159	360	AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>96.57</td><td>-----</td><td>-----</td><td>80.65</td><td>32.36</td><td>8.22</td><td>30.66</td><td>6.00</td><td>159</td><td>360</td><td>AVERAGE</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2478.00	96.57	-----	-----	80.65	32.36	8.22	30.66	6.00	159	360	AVERAGE
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2486.92	45.08	54.00	-8.92	29.12	32.37	8.24	30.65	6.00	159	360	AVERAGE																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																										
1	2478.00	96.57	-----	-----	80.65	32.36	8.22	30.66	6.00	159	360	AVERAGE																																																																																								



Mode	1																																																								
	Harmonic																																																								
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																								
ANT	0																																																								
Pol.	Horizontal						Vertical																																																		
Peak Avg																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr><tr><td>1</td><td>4956.00</td><td>40.28</td><td>74.00</td><td>-33.72</td><td>60.27</td><td>33.92</td><td>11.84</td><td>65.75</td></tr><tr><td>2</td><td>7434.00</td><td>42.65</td><td>74.00</td><td>-31.35</td><td>57.77</td><td>35.00</td><td>14.63</td><td>65.55</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	4956.00	40.28	74.00	-33.72	60.27	33.92	11.84	65.75	2	7434.00	42.65	74.00	-31.35	57.77	35.00	14.63	65.55
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																	
1	4956.00	40.28	74.00	-33.72	60.27	33.92	11.84	65.75																																																	
2	7434.00	42.65	74.00	-31.35	57.77	35.00	14.63	65.55																																																	
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr><tr><td>1</td><td>4956.00</td><td>40.49</td><td>74.00</td><td>-33.51</td><td>60.48</td><td>33.92</td><td>11.84</td><td>65.75</td></tr><tr><td>2</td><td>7434.00</td><td>42.59</td><td>74.00</td><td>-31.41</td><td>57.71</td><td>35.00</td><td>14.63</td><td>65.55</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	1	4956.00	40.49	74.00	-33.51	60.48	33.92	11.84	65.75	2	7434.00	42.59	74.00	-31.41	57.71	35.00	14.63	65.55
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB																																																	
1	4956.00	40.49	74.00	-33.51	60.48	33.92	11.84	65.75																																																	
2	7434.00	42.59	74.00	-31.41	57.71	35.00	14.63	65.55																																																	



Mode	1	
	18-25G	
	2400-2483.5_Bluetooth-LE_CH38_2478MHz	
ANT	0	
Pol.	Horizontal	Vertical
Peak Avg	Level (dBuV/m) Frequency (MHz) FCC PART 15C -50dB FCC PART 15C (AVG) -50dB	Level (dBuV/m) Frequency (MHz) FCC PART 15C -50dB FCC PART 15C (AVG) -50dB



Mode	1																																																																																																																																																																																										
	30-1G																																																																																																																																																																																										
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																																																																																																																																										
ANT	0																																																																																																																																																																																										
Pol.	Horizontal						Vertical																																																																																																																																																																																				
Peak	Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>92.08</td><td>20.65</td><td>43.50</td><td>-22.85</td><td>36.70</td><td>15.14</td><td>1.45</td><td>32.64</td><td>---</td><td>--- Peak</td></tr><tr><td>2</td><td>197.81</td><td>28.89</td><td>43.50</td><td>-14.61</td><td>44.65</td><td>15.19</td><td>2.14</td><td>33.09</td><td>---</td><td>--- Peak</td></tr><tr><td>3</td><td>267.65</td><td>30.98</td><td>46.00</td><td>-15.02</td><td>42.66</td><td>18.85</td><td>2.50</td><td>33.03</td><td>---</td><td>--- Peak</td></tr><tr><td>4</td><td>398.60</td><td>25.98</td><td>46.00</td><td>-20.02</td><td>33.86</td><td>21.87</td><td>3.05</td><td>32.80</td><td>---</td><td>--- Peak</td></tr><tr><td>5</td><td>638.19</td><td>25.88</td><td>46.00</td><td>-20.12</td><td>28.22</td><td>26.46</td><td>3.85</td><td>32.65</td><td>---</td><td>--- Peak</td></tr><tr><td>6</td><td>802.12</td><td>28.07</td><td>46.00</td><td>-17.93</td><td>27.90</td><td>28.34</td><td>4.33</td><td>32.50</td><td>---</td><td>--- Peak</td></tr></tbody></table> Level (dBuV/m) Frequency (MHz) <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>Line</th><th>Limit</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>41.64</td><td>29.34</td><td>40.00</td><td>-10.66</td><td>42.61</td><td>18.60</td><td>0.97</td><td>32.84</td><td>---</td><td>--- Peak</td></tr><tr><td>2</td><td>90.14</td><td>30.41</td><td>43.50</td><td>-13.09</td><td>46.67</td><td>14.90</td><td>1.44</td><td>32.60</td><td>---</td><td>--- Peak</td></tr><tr><td>3</td><td>197.81</td><td>28.53</td><td>43.50</td><td>-14.97</td><td>44.29</td><td>15.19</td><td>2.14</td><td>33.09</td><td>---</td><td>--- Peak</td></tr><tr><td>4</td><td>422.85</td><td>25.19</td><td>46.00</td><td>-20.81</td><td>32.35</td><td>22.45</td><td>3.14</td><td>32.75</td><td>---</td><td>--- Peak</td></tr><tr><td>5</td><td>560.59</td><td>26.71</td><td>46.00</td><td>-19.29</td><td>30.23</td><td>25.45</td><td>3.61</td><td>32.58</td><td>---</td><td>--- Peak</td></tr><tr><td>6</td><td>741.98</td><td>28.11</td><td>46.00</td><td>-17.89</td><td>28.53</td><td>28.13</td><td>4.17</td><td>32.72</td><td>---</td><td>--- Peak</td></tr></tbody></table>												Freq	Level	Limit	Over	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	Line	Limit	Level	Factor	Loss	Factor	cm	deg	1	92.08	20.65	43.50	-22.85	36.70	15.14	1.45	32.64	---	--- Peak	2	197.81	28.89	43.50	-14.61	44.65	15.19	2.14	33.09	---	--- Peak	3	267.65	30.98	46.00	-15.02	42.66	18.85	2.50	33.03	---	--- Peak	4	398.60	25.98	46.00	-20.02	33.86	21.87	3.05	32.80	---	--- Peak	5	638.19	25.88	46.00	-20.12	28.22	26.46	3.85	32.65	---	--- Peak	6	802.12	28.07	46.00	-17.93	27.90	28.34	4.33	32.50	---	--- Peak		Freq	Level	Limit	Over	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	Line	Limit	Level	Factor	Loss	Factor	cm	deg	1	41.64	29.34	40.00	-10.66	42.61	18.60	0.97	32.84	---	--- Peak	2	90.14	30.41	43.50	-13.09	46.67	14.90	1.44	32.60	---	--- Peak	3	197.81	28.53	43.50	-14.97	44.29	15.19	2.14	33.09	---	--- Peak	4	422.85	25.19	46.00	-20.81	32.35	22.45	3.14	32.75	---	--- Peak	5	560.59	26.71	46.00	-19.29	30.23	25.45	3.61	32.58	---	--- Peak	6	741.98	28.11	46.00	-17.89	28.53	28.13	4.17	32.72	---	--- Peak
		Freq	Level	Limit	Over	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																
		MHz	dBuV/m	Line	Limit	Level	Factor	Loss	Factor	cm	deg																																																																																																																																																																																
1	92.08	20.65	43.50	-22.85	36.70	15.14	1.45	32.64	---	--- Peak																																																																																																																																																																																	
2	197.81	28.89	43.50	-14.61	44.65	15.19	2.14	33.09	---	--- Peak																																																																																																																																																																																	
3	267.65	30.98	46.00	-15.02	42.66	18.85	2.50	33.03	---	--- Peak																																																																																																																																																																																	
4	398.60	25.98	46.00	-20.02	33.86	21.87	3.05	32.80	---	--- Peak																																																																																																																																																																																	
5	638.19	25.88	46.00	-20.12	28.22	26.46	3.85	32.65	---	--- Peak																																																																																																																																																																																	
6	802.12	28.07	46.00	-17.93	27.90	28.34	4.33	32.50	---	--- Peak																																																																																																																																																																																	
	Freq	Level	Limit	Over	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																	
	MHz	dBuV/m	Line	Limit	Level	Factor	Loss	Factor	cm	deg																																																																																																																																																																																	
1	41.64	29.34	40.00	-10.66	42.61	18.60	0.97	32.84	---	--- Peak																																																																																																																																																																																	
2	90.14	30.41	43.50	-13.09	46.67	14.90	1.44	32.60	---	--- Peak																																																																																																																																																																																	
3	197.81	28.53	43.50	-14.97	44.29	15.19	2.14	33.09	---	--- Peak																																																																																																																																																																																	
4	422.85	25.19	46.00	-20.81	32.35	22.45	3.14	32.75	---	--- Peak																																																																																																																																																																																	
5	560.59	26.71	46.00	-19.29	30.23	25.45	3.61	32.58	---	--- Peak																																																																																																																																																																																	
6	741.98	28.11	46.00	-17.89	28.53	28.13	4.17	32.72	---	--- Peak																																																																																																																																																																																	

Appendix C. Duty Cycle Plots

Antenna	Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
0	Bluetooth LE 2Mbps	33.17	0.207	4.831	5.1kHz

Bluetooth LE 2Mbps

