ACCREDITED
Certificate # 3939.01

FCC TEST REPORT

(PART 27)

Applicant:	Xiaomi Communications Co., Ltd.
Address:	The Rainbow City of China Resources,NO.68,Qinghe Middle Street, Haidian District, Beijing, China

Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	The Rainbow City of China Resources,NO.68,Qinghe Middle Street, Haidian District, Beijing, China
Product:	Mobile Phone
Brand Name:	Redmi
Model Name:	M1908C3XG
FCC ID:	2AFZZC3XG
Date of tests:	Aug 24, 2019 ~ Sep 17, 2019

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 27, Subpart C, L** ☒ **ANSI/TIA/EIA-603- D**
☒ **FCC Part 2** ☒ **ANSI/TIA/EIA-603-E** ☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Alex Chen Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
Alex	Luke Lu
Date: Sep 24, 2019	Date: Sep 24, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 SUMMARY OF TEST RESULTS 5

1.1 MEASUREMENT UNCERTAINTY 5
1.2 TEST SITE AND INSTRUMENTS 6

2 GENERAL INFORMATION 7

2.1 GENERAL DESCRIPTION OF EUT 7
2.2 CONFIGURATION OF SYSTEM UNDER TEST 10
2.3 DESCRIPTION OF SUPPORT UNITS 11
2.4 DESCRIPTION OF TEST MODES 11
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS 14

3 TEST TYPES AND RESULTS 15

3.1 OUTPUT POWER MEASUREMENT 15
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT 15
3.1.2 TEST PROCEDURES 15
3.1.3 TEST SETUP 16
3.1.4 TEST RESULTS 17
3.2 FREQUENCY STABILITY MEASUREMENT 28
3.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT 28
3.2.2 TEST PROCEDURE 28
3.2.3 TEST SETUP 28
3.2.4 TEST RESULTS 29
3.3 OCCUPIED BANDWIDTH MEASUREMENT 36
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT 36
3.3.2 TEST SETUP 36
3.3.3 TEST PROCEDURES 36
3.3.4 TEST RESULTS 37
3.4 PEAK TO AVERAGE RATIO 44
3.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT 44
3.4.2 TEST SETUP 44
3.4.3 TEST PROCEDURES 44
3.4.4 TEST RESULTS 45
3.5 BAND EDGE MEASUREMENT 54
3.5.1 LIMITS OF BAND EDGE MEASUREMENT 54
3.5.2 TEST SETUP 54
3.5.3 TEST PROCEDURES 55
3.5.4 TEST RESULTS 56
3.6 CONDUCTED SPURIOUS EMISSIONS 75
3.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT 75
3.6.2 TEST PROCEDURE 75
3.6.3 TEST SETUP 75
3.6.4 TEST RESULTS 76
3.7 RADIATED EMISSION MEASUREMENT 83
3.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT 83
3.7.2 TEST PROCEDURES 83
3.7.3 DEVIATION FROM TEST STANDARD 83
3.7.4 TEST SETUP 84
3.7.5 TEST RESULTS 85

4 INFORMATION ON THE TESTING LABORATORIES 109

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 110

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF190823W003-6	Original release	Sep 24, 2019

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 27 & Part 2		
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**
2.1046 27.50(d)(4)	Maximum Peak Output Power	Compliance
2.1055 27.54	Frequency Stability	Compliance
2.1049 27.53(h)	Occupied Bandwidth	Compliance
27.50(d)(5)	Peak to average ratio	Compliance
27.53(h)	Band Edge Measurements	Compliance
2.1051 27.53(h)	Conducted Spurious Emissions	Compliance
2.1053 27.53(h)	Radiated Spurious Emissions	Compliance

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	±76.97Hz
Radiated emissions & Radiated Power (30MHz~1GMHz)	±4.98dB
Radiated emissions & Radiated Power (1GMHz ~6GMHz)	±4.70dB
Radiated emissions (6GMHz ~18GMHz)	±4.60dB
Radiated emissions (18GMHz ~40GMHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Band Edge Measurements	±4.70dB
Peak to average ratio	±0.76dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 26,19	Feb. 25,20
EXA Signal Analyzer	KEYSIGHT	N9010A-526	MY54510322	Feb. 26,19	Feb. 25,20
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 26,19	Feb. 25,20
Horn Antenna (1GHz-18GHz)	ETS-LINDGREN	3117	00168692	Nov. 30, 18	Nov. 29, 19
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-00361	15433	Nov. 21, 18	Nov. 20, 19
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 26,19	Feb. 25,20
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 24,19	Jun. 23,20
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 24,19	Jun. 23,20
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jun. 24,19	Jun. 23,20
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Feb. 26,19	Feb. 25,20
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 24,19	Jun. 23,20
Power Meter	Anritsu	ML2495A	1506002	Feb. 26,19	Feb. 25,20
Power Sensor	Anritsu	MA2411B	1339352	Feb. 26,19	Feb. 25,20
Humid & Temp Programmable Tester	Juyi	ITH-120-45-CP-AR	IAA1504-001	Jun. 24,19	Jun. 23,20
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 26,19	Feb. 25,20
Power Divider	MCLI/USA	PS2-15	24880	Jul. 09,19	Jul. 08,20

NOTE: 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.

3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.

4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile Phone	
BRAND NAME	Redmi	
MODEL NAME	M1908C3XG	
POWER SUPPLY	5V/9V/12Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery) V_{min}=3.65V, V_{nor}=3.85V,V_{max}=4.4V	
MODULATION TECHNOLOGY	**WCDMA**	BPSK, QPSK
	LTE	QPSK, 16QAM, 64QAM
FREQUENCY RANGE	**WCDMA IV**	1712.4MHz ~ 1752.6MHz
	LTE Band 4 Channel Bandwidth: 1.4MHz	1710.7MHz ~ 1754.3MHz
	LTE Band 4 Channel Bandwidth: 3MHz	1711.5MHz ~ 1753.5MHz
	LTE Band 4 Channel Bandwidth: 5MHz	1712.5MHz ~ 1752.5MHz
	LTE Band 4 Channel Bandwidth: 10MHz	1715.0MHz ~ 1750.0MHz
	LTE Band 4 Channel Bandwidth: 15MHz	1717.5MHz ~ 1747.5MHz
	LTE Band 4 Channel Bandwidth: 20MHz	1720.0MHz ~ 1745.0MHz
EMISSION DESIGNATOR	**WCDMA IV**	4M15F9W
	LTE Band 4 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M09W7D
		64QAM: 1M09W7D
	LTE Band 4 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M68W7D
		64QAM: 2M68W7D
	LTE Band 4 Channel Bandwidth: 5MHz	QPSK: 4M48G7D
		16QAM: 4M48W7D
		64QAM: 4M48W7D
	LTE Band 4 Channel Bandwidth: 10MHz	QPSK: 8M95G7D
		16QAM: 8M93W7D
		64QAM: 8M94W7D

EMISSION DESIGNATOR	**LTE Band 4 Channel Bandwidth: 15MHz**	QPSK: 13M4G7D
		16QAM: 13M4W7D
		64QAM: 13M4W7D
	LTE Band 4 Channel Bandwidth: 20MHz	QPSK: 17M9G7D
		16QAM: 17M8W7D
		64QAM: 17M9W7D
MAX. ERP/EIRP POWER	**WCDMA IV**	95mw
	LTE Band 4 Channel Bandwidth: 1.4MHz	324mw
	LTE Band 4 Channel Bandwidth: 3MHz	320mw
	LTE Band 4 Channel Bandwidth: 5MHz	324mw
	LTE Band 4 Channel Bandwidth: 10MHz	332mw
	LTE Band 4 Channel Bandwidth: 15MHz	323mw
	LTE Band 4 Channel Bandwidth: 20MHz	291mw
ANTENNA TYPE	Main Antenna(ANT 0): Fixed Internal Antenna 0 with 0.7dBi gain for WCDMA IV/LTE B4	
HW VERSION	P2	
SW VERSION	MIUI 10	
ACCESSORY DEVICE	Refer to user's manual	
DATA CABLE	USB cable: 1.0 meter, shielded cable, without ferrite core	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

List of Accessories:

ACCESSORIES	BRAND	MODEL	MANUFACTURER	SPECIFICATION
AC Adapter	MI	MDY-10-ED	Chenyang	I/P: 100 - 240Vac,500mA, O/P: 5Vdc, 3000mA/9V,2A/12V,1.5A
Battery	MI	BN46	CosMX	Rating: 3.85Vdc, Min. 3900mAh,Typ.4000 mAh, Li-ion, Y
USB Cable 1	MI	L23312	LUXSHARE Precision Industry Co., Ltd.	1.0 meter, shielded cable, without ferrite core
USB Cable 2	MI	K23312	SU ZHOU KELI SCIENCE&TECHNOLOGY DEVELOPMENT CO.,LTD	1.0 meter, shielded cable, without ferrite core

2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.8m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

2.4 DESCRIPTION OF TEST MODES

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports The worst case in ERP/EIRP and radiated emission was found when positioned on X-plane for WCDMA /LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	**EUT + Adapter + USB Cable with WCDMA or LTE link**
B	EUT + Battery with **WCDMA or LTE link**

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	EIRP	1312 to 1513	1312, 1413, 1513	WCDMA
B	FREQUENCY STABILITY	1312 to 1513	1312, 1513	WCDMA
B	OCCUPIED BANDWIDTH	1312 to 1513	1312, 1413, 1513	WCDMA
B	BAND EDGE	1312 to 1513	1312, 1513	WCDMA
B	PEAK TO AVERAGE RATIO	1312 to 1513	1312, 1413, 1513	WCDMA
B	CONDCUDETED EMISSION	1312 to 1513	1312, 1413, 1513	WCDMA
A	RADIATED EMISSION	1312 to 1513	1312, 1413, 1513	WCDMA

LTE BAND 4

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	19957 to 20393	19957, 20393	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	19965, 20385	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	19975, 20375	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20000, 20350	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20025, 20325	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20050, 20300	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM, 64QAM	6 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM, 64QAM	15 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM, 64QAM	25 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM, 64QAM	50 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM, 64QAM	75 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM, 64QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
B	BAND EDGE	19957 to 20393	19957	1.4MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
						6 RB / 0 RB Offset
			20393	1.4MHz	QPSK, 16QAM, 64QAM	1 RB / 5 RB Offset
						6 RB / 0 RB Offset
		19965 to 20385	19965	3MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
						15 RB / 0 RB Offset
			20385	3MHz	QPSK, 16QAM, 64QAM	1 RB / 14 RB Offset
						15 RB / 0 RB Offset
		19975 to 20375	19975	5MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
						25 RB / 0 RB Offset
			20375	5MHz	QPSK, 16QAM, 64QAM	1 RB / 24 RB Offset
						25 RB / 0 RB Offset
		20000 to 20350	20000	10MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
						50 RB / 0 RB Offset
			20350	10MHz	QPSK, 16QAM, 64QAM	1 RB / 49 RB Offset
						50 RB / 0 RB Offset

B	BAND EDGE	20025 to 20325	20025	15MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
						75 RB / 0 RB Offset
			20325	15MHz	QPSK, 16QAM, 64QAM	1 RB / 74 RB Offset
						75 RB / 0 RB Offset
		20050 to 20300	20050	20MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
						100 RB / 0 RB Offset
			20300	20MHz	QPSK, 16QAM, 64QAM	1 RB / 99 RB Offset
						100 RB / 0 RB Offset
B	CONDCUDETED EMISSION	19957 to 20393	19957, 20175, 20393	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	19965, 20175, 20385	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	19975, 20175, 20375	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20025, 20175, 20325	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20050, 20175, 20300	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	19957 to 20393	20175	1.4MHz	QPSK	1 RB / 0 RB Offset
		19965 to 20385	20175	3MHz	QPSK	1 RB / 0 RB Offset
		19975 to 20375	20175	5MHz	QPSK	1 RB / 0 RB Offset
		20000 to 20350	20000, 20175, 20350	10MHz	QPSK	1 RB / 0 RB Offset
		20025 to 20325	20175	15MHz	QPSK	1 RB / 0 RB Offset
		20050 to 20300	20175	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	24deg. C, 60%RH	3.85Vdc from Battery	Star Le
FREQUENCY STABILITY	24deg. C, 61%RH	DC 3.65V/3.85V/4.4V	Kevin Zhang
OCCUPIED BANDWIDTH	24deg. C, 61%RH	3.85Vdc from Battery	Kevin Zhang
PEAK TO AVERAGE RATIO	24deg. C, 61%RH	3.85Vdc from Battery	Kevin Zhang
BAND EDGE	24deg. C, 61%RH	3.85Vdc from Battery	Kevin Zhang
CONDCUDETED EMISSION	24deg. C, 61%RH	3.85Vdc from Battery	Kevin Zhang
RADIATED EMISSION	23deg. C, 70%RH	DC 5V/9V/12V from adaptor	Star Le

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 27

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Fixed, mobile, and portable (hand-held) stations operating in the 1710–1755 MHz band are limited to 1 watt EIRP.

3.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

a. The EUT was set up for the maximum power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 3 channels (low, middle and high operational frequency range). RBW and VBW is 10MHz for LTE.

b. E.I.R.P power measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G

d. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn

e. E.R.P = E.I.R.P- 2.15 dB

CONDUCTED POWER MEASUREMENT:

a. The EUT was set up for the maximum power with LTE link data modulation and link up with simulator.

b. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

EIRP MEASUREMENT:
<Radiated Emission below or equal 1 GHz>



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:

3.1.4 TEST RESULTS

AVERAGE CONDUCTED OUTPUT POWER (dBm)

Band	WCDMA IV			
TX Channel	1312	1413	1513	Max. Tune-up Power
Rx Channel	1537	1638	1738	
Frequency	1712.4	1732.6	1752.6	
RMC 12.2K	24.37	24.34	24.48	24.5
HSDPA Subtest-1	23.34	23.39	23.42	24.0
HSDPA Subtest-2	23.32	23.38	23.41	24.0
HSDPA Subtest-3	22.85	22.92	23.06	23.5
HSDPA Subtest-4	22.84	22.91	23.05	23.5
DC-HSDPA Subtest-1	23.28	23.37	23.49	24.0
DC-HSDPA Subtest-2	23.25	23.34	23.47	24.0
DC-HSDPA Subtest-3	22.80	22.85	23.01	23.5
DC-HSDPA Subtest-4	22.78	22.86	23.00	23.5
HSUPA Subtest-1	23.32	23.36	23.48	24.0
HSUPA Subtest-2	21.35	21.31	21.50	22.0
HSUPA Subtest-3	22.34	22.35	22.52	23.0
HSUPA Subtest-4	21.31	21.36	21.50	22.0
HSUPA Subtest-5	23.40	23.41	23.51	24.0
HSPA+ Subtest-1	20.88	20.84	20.94	21.5

LTE Band 4								
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)	Max. Tune-up (dBm)
		Channel		20050	20175	20300		
		Frequence (MHz)		1720	1732.5	1745		
20M	QPSK	1	0	24.17	24.29	24.22	0	24.5
		1	50	24.01	24.13	24.06	0	24.5
		1	99	23.99	24.11	24.04	0	24.5
		50	0	22.31	22.43	22.36	1	23.5
		50	25	22.24	22.36	22.29	1	23.5
		50	50	22.21	22.33	22.26	1	23.5
		100	0	22.26	22.38	22.31	1	23.5
	16QAM	1	0	22.17	22.32	22.23	1	23.5
		1	50	22.12	22.19	22.11	1	23.5
		1	99	21.94	22.05	21.93	1	23.5
		50	0	21.11	21.19	21.06	2	22.5
		50	25	21.01	21.11	21.04	2	22.5
		50	50	20.91	21.03	20.87	2	22.5
		100	0	20.93	21.07	20.90	2	22.5
	64QAM	1	0	22.28	22.32	22.25	2	22.5
		1	50	22.24	22.28	22.21	2	22.5
		1	99	22.21	22.25	22.18	2	22.5
		50	0	21.33	21.37	21.30	2	22.5
		50	25	21.31	21.35	21.28	2	22.5
		50	50	21.27	21.31	21.24	2	22.5
		100	0	21.28	21.32	21.25	2	22.5
BW	MCS Index	Channel		20025	20175	20325	3GPP MPR	Max. Tune-up
		Frequence (MHz)		1717.5	1732.5	1747.5		
15M	QPSK	1	0	24.17	24.20	24.12	0	24.5
		1	37	23.96	24.09	24.01	0	24.5
		1	74	23.91	24.09	23.96	0	24.5
		36	0	22.27	22.36	22.28	1	23.5
		36	19	22.17	22.30	22.26	1	23.5
		36	39	22.21	22.27	22.22	1	23.5
		75	0	22.25	22.28	22.23	1	23.5
	16QAM	1	0	22.10	22.26	22.19	1	23.5
		1	37	22.09	22.11	22.11	1	23.5
		1	74	21.88	22.01	21.90	1	23.5
		36	0	21.09	21.14	20.99	2	22.5
		36	19	20.96	21.07	21.01	2	22.5
		36	39	20.83	21.01	20.77	2	22.5
		75	0	20.91	21.02	20.90	2	22.5
	64QAM	1	0	22.25	22.29	22.15	2	22.5
		1	37	22.24	22.27	22.11	2	22.5
		1	74	22.11	22.25	22.08	2	22.5
		36	0	21.30	21.34	21.30	2	22.5
		36	19	21.23	21.34	21.25	2	22.5
		36	39	21.19	21.22	21.19	2	22.5
		75	0	21.25	21.25	21.19	2	22.5

BW	MCS Index	Channel		20000	20175	20350	3GPP MPR	Max. Tune-up
		Frequence (MHz)		1715	1732.5	1750		
10M	QPSK	1	0	24.04	24.11	24.15	0	24.5
		1	24	23.96	24.02	24.04	0	24.5
		1	49	23.87	23.91	23.96	0	24.5
		25	0	22.25	22.35	22.29	1	23.5
		25	12	21.99	22.27	22.13	1	23.5
		25	25	22.03	22.26	22.05	1	23.5
		50	0	22.12	22.23	22.12	1	23.5
	16QAM	1	0	22.01	22.22	22.00	1	23.5
		1	24	21.90	22.07	22.03	1	23.5
		1	49	21.86	21.94	21.73	1	23.5
		25	0	20.92	21.08	20.92	2	22.5
		25	12	20.86	21.02	20.94	2	22.5
		25	25	20.82	20.91	20.71	2	22.5
		50	0	20.71	21.02	20.71	2	22.5
	64QAM	1	0	22.23	22.19	22.10	2	22.5
		1	24	22.11	22.19	22.05	2	22.5
		1	49	22.03	22.23	22.05	2	22.5
		25	0	21.19	21.25	21.21	2	22.5
		25	12	21.13	21.18	21.10	2	22.5
		25	25	21.07	21.18	21.19	2	22.5
		50	0	21.22	21.18	21.09	2	22.5

BW	MCS Index	Channel		19975	20175	20375	3GPP MPR	Max. Tune-up
		Frequence (MHz)		1712.5	1732.5	1752.5		
5M	QPSK	1	0	24.10	24.20	24.04	0	24.5
		1	12	23.92	24.09	23.80	0	24.5
		1	24	23.86	23.94	23.83	0	24.5
		12	0	22.19	22.32	22.13	1	23.5
		12	6	22.10	22.25	22.08	1	23.5
		12	13	22.12	22.20	22.21	1	23.5
		25	0	22.16	22.33	22.15	1	23.5
	16QAM	1	0	22.14	22.20	22.01	1	23.5
		1	12	21.95	22.17	21.99	1	23.5
		1	24	21.79	21.91	21.78	1	23.5
		12	0	20.95	21.04	20.92	2	22.5
		12	6	20.93	21.01	20.94	2	22.5
		12	13	20.73	20.92	20.77	2	22.5
		25	0	20.77	20.94	20.75	2	22.5
	64QAM	1	0	22.15	22.26	22.19	2	22.5
		1	12	22.16	22.10	22.12	2	22.5
		1	24	22.06	22.09	22.05	2	22.5
		12	0	21.18	21.16	21.22	2	22.5
		12	6	21.16	21.27	21.19	2	22.5
		12	13	21.23	21.13	21.07	2	22.5
		25	0	21.16	21.16	21.09	2	22.5

BW	MCS Index	Channel		19965	20175	20385	3GPP MPR	Max. Tune-up
		Frequence (MHz)		1711.5	1732.5	1753.5		
3M	QPSK	1	0	24.08	24.19	24.08	0	24.5
		1	7	23.91	24.01	23.91	0	24.5
		1	14	23.87	23.92	23.92	0	24.5
		8	0	22.27	22.33	22.30	1	23.5
		8	3	22.15	22.26	22.18	1	23.5
		8	7	22.11	22.18	22.09	1	23.5
		15	0	22.14	22.27	22.06	1	23.5
	16QAM	1	0	22.06	22.28	22.07	1	23.5
		1	7	21.94	22.14	22.11	1	23.5
		1	14	21.77	21.94	21.81	1	23.5
		8	0	20.87	20.96	21.02	2	22.5
		8	3	20.98	21.01	20.99	2	22.5
		8	7	20.78	20.92	20.75	2	22.5
		15	0	20.82	20.87	20.75	2	22.5
	64QAM	1	0	22.16	22.14	22.18	2	22.5
		1	7	22.11	22.17	22.13	2	22.5
		1	14	22.20	22.07	22.07	2	22.5
		8	0	21.26	21.19	21.17	2	22.5
		8	3	21.10	21.28	21.16	2	22.5
		8	7	21.22	21.18	21.14	2	22.5
		15	0	21.10	21.25	21.18	2	22.5
BW	MCS Index	Channel		19957	20175	20393	3GPP MPR	Max. Tune-up
		Frequence (MHz)		1710.7	1732.5	1754.3		
1.4M	QPSK	1	0	24.17	24.27	24.09	0	24.5
		1	2	23.94	23.98	23.85	0	24.5
		1	5	23.79	24.01	23.94	0	24.5
		3	0	23.20	23.28	23.35	0	24.5
		3	1	23.18	23.26	23.10	0	24.5
		3	3	23.01	23.29	23.10	0	24.5
		6	0	22.16	22.27	22.21	1	23.5
	16QAM	1	0	21.99	22.11	22.04	1	23.5
		1	2	22.07	22.12	21.90	1	23.5
		1	5	21.80	21.86	21.83	1	23.5
		3	0	21.97	21.97	21.86	1	23.5
		3	1	21.87	21.94	21.92	1	23.5
		3	3	21.86	21.88	21.70	1	23.5
		6	0	20.76	21.04	20.78	2	22.5
	64QAM	1	0	22.12	22.16	22.13	2	22.5
		1	2	22.20	22.16	22.07	2	22.5
		1	5	22.11	22.10	22.05	2	22.5
		3	0	22.25	22.28	22.13	2	22.5
		3	1	22.18	22.23	22.15	2	22.5
		3	3	22.11	22.29	22.06	2	22.5
		6	0	21.17	21.27	21.12	2	22.5

EIRP

WCDMA IV

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
1312	1712.40	-27.89	41.39	13.50	22.38	H
1413	1732.60	-27.21	41.36	14.15	26.00	H
1513	1752.60	-27.65	42.63	14.98	31.47	H
1312	1712.40	-25.42	44.17	18.75	74.92	V
1413	1732.60	-25.23	44.20	18.97	78.89	V
1513	1752.60	-24.58	44.35	19.77	**94.73**	V

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-23.88	41.29	17.41	55.13	H	1
20175	1732.5	-24.22	41.36	17.14	51.76	H	1
20393	1754.3	-23.36	42.74	19.38	86.66	H	1
19957	1710.7	-19.87	44.25	24.38	273.84	V	1
20175	1732.5	-19.09	44.20	25.11	**324.34**	V	1
20393	1754.3	-19.45	44.09	24.64	290.74	V	1

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-24.75	41.29	16.54	45.12	H	1
20175	1732.5	-25.15	41.36	16.21	41.78	H	1
20393	1754.3	-24.32	42.74	18.42	69.47	H	1
19957	1710.7	-20.74	44.25	23.51	224.13	V	1
20175	1732.5	-20.02	44.20	24.18	261.82	V	1
20393	1754.3	-20.41	44.09	23.68	233.08	V	1

CHANNEL BANDWIDTH: 1.4MHz 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19957	1710.7	-26.84	41.29	14.45	27.89	H	1
20175	1732.5	-27.27	41.36	14.09	25.64	H	1
20393	1754.3	-26.48	42.74	16.26	42.25	H	1
19957	1710.7	-22.82	44.25	21.43	138.84	V	1
20175	1732.5	-22.08	44.20	22.12	162.93	V	1
20393	1754.3	-22.47	44.09	21.62	145.04	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-23.86	41.27	17.41	55.04	H	1
20175	1732.5	-24.28	41.36	17.08	51.05	H	1
20385	1753.5	-23.31	42.76	19.45	88.04	H	1
19965	1711.5	-19.85	44.26	24.41	276.18	V	1
20175	1732.5	-19.15	44.20	25.05	**319.89**	V	1
20385	1753.5	-19.40	44.23	24.83	304.23	V	1

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-24.93	41.27	16.34	43.02	H	1
20175	1732.5	-25.17	41.36	16.19	41.59	H	1
20385	1753.5	-24.30	42.76	18.46	70.10	H	1
19965	1711.5	-20.92	44.26	23.34	215.87	V	1
20175	1732.5	-20.04	44.20	24.16	260.62	V	1
20385	1753.5	-20.39	44.23	23.84	242.21	V	1

CHANNEL BANDWIDTH: 3MHz 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19965	1711.5	-27.00	41.27	14.27	26.71	H	1
20175	1732.5	-27.20	41.36	14.16	26.06	H	1
20385	1753.5	-26.17	42.76	16.59	45.57	H	1
19965	1711.5	-23.00	44.26	21.26	133.72	V	1
20175	1732.5	-22.11	44.20	22.09	161.81	V	1
20385	1753.5	-22.54	44.23	21.69	147.64	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-23.92	41.39	17.47	55.83	H	1
20175	1732.5	-24.23	41.36	17.13	51.64	H	1
20375	1752.5	-23.26	42.63	19.37	86.48	H	1
19975	1712.5	-19.91	44.17	24.26	266.44	V	1
20175	1732.5	-19.10	44.20	25.10	**323.59**	V	1
20375	1752.5	-19.35	44.35	25.00	315.86	V	1

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-24.75	41.39	16.64	46.12	H	1
20175	1732.5	-25.25	41.36	16.11	40.83	H	1
20375	1752.5	-24.36	42.63	18.27	67.13	H	1
19975	1712.5	-20.74	44.17	23.43	220.09	V	1
20175	1732.5	-20.12	44.20	24.08	255.86	V	1
20375	1752.5	-20.45	44.35	23.90	245.19	V	1

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
19975	1712.5	-26.81	41.39	14.58	28.70	H	1
20175	1732.5	-27.29	41.36	14.07	25.53	H	1
20375	1752.5	-26.42	42.63	16.21	41.77	H	1
19975	1712.5	-22.79	44.17	21.38	137.28	V	1
20175	1732.5	-22.18	44.20	22.02	159.22	V	1
20375	1752.5	-22.50	44.35	21.85	152.93	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-23.73	41.49	17.76	59.65	H	1
20175	1732.5	-24.17	41.36	17.19	52.36	H	1
20350	1750.0	-23.13	42.28	19.15	82.28	H	1
20000	1715.0	-19.72	44.06	24.34	271.83	V	1
20175	1732.5	-19.04	44.20	25.16	328.10	V	1
20350	1750.0	-19.22	44.43	25.21	**331.89**	V	1

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-24.88	41.49	16.61	45.77	H	1
20175	1732.5	-25.27	41.36	16.09	40.64	H	1
20350	1750.0	-24.29	42.28	17.99	62.99	H	1
20000	1715.0	-20.87	44.06	23.19	208.59	V	1
20175	1732.5	-20.14	44.20	24.06	254.68	V	1
20350	1750.0	-20.38	44.43	24.05	254.10	V	1

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20000	1715.0	-26.98	41.49	14.51	28.22	H	1
20175	1732.5	-27.34	41.36	14.02	25.23	H	1
20350	1750.0	-26.34	42.28	15.94	39.29	H	1
20000	1715.0	-22.96	44.06	21.10	128.91	V	1
20175	1732.5	-22.23	44.20	21.97	157.40	V	1
20350	1750.0	-22.40	44.43	22.03	159.59	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-23.74	41.34	17.60	57.52	H	1
20175	1732.5	-24.24	41.36	17.12	51.52	H	1
20325	1747.5	-23.20	42.09	18.89	77.37	H	1
20025	1717.5	-19.73	44.04	24.31	270.02	V	1
20175	1732.5	-19.11	44.20	25.09	**322.85**	V	1
20325	1747.5	-19.29	44.22	24.93	310.81	V	1

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-24.60	41.34	16.74	47.18	H	1
20175	1732.5	-25.11	41.36	16.25	42.17	H	1
20325	1747.5	-24.05	42.09	18.04	63.62	H	1
20025	1717.5	-20.59	44.04	23.45	221.51	V	1
20175	1732.5	-19.98	44.20	24.22	264.24	V	1
20325	1747.5	-20.14	44.22	24.08	255.56	V	1

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20025	1717.5	-26.65	41.34	14.69	29.43	H	1
20175	1732.5	-25.17	41.36	16.19	41.59	H	1
20325	1747.5	-25.20	42.09	16.89	48.82	H	1
20025	1717.5	-22.63	44.04	21.41	138.48	V	1
20175	1732.5	-22.01	44.20	22.19	165.58	V	1
20325	1747.5	-22.20	44.22	22.02	159.04	V	1

LTE BAND 4

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-24.32	41.28	16.96	49.67	H	1
20175	1732.5	-24.69	41.36	16.67	46.46	H	1
20300	1745.0	-23.78	41.96	18.18	65.72	H	1
20050	1720.0	-20.31	44.14	23.83	241.27	V	1
20175	1732.5	-19.56	44.20	24.64	**290.80**	V	1
20300	1745.0	-19.87	43.88	24.01	251.88	V	1

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-25.25	41.28	16.03	40.10	H	1
20175	1732.5	-25.76	41.36	15.60	36.32	H	1
20300	1745.0	-24.61	41.96	17.35	54.29	H	1
20050	1720.0	-21.24	44.14	22.90	194.76	V	1
20175	1732.5	-20.63	44.20	23.57	227.30	V	1
20300	1745.0	-20.70	43.88	23.18	208.07	V	1

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
20050	1720.0	-27.53	41.28	13.75	23.72	H	1
20175	1732.5	-27.89	41.36	13.47	22.24	H	1
20300	1745.0	-26.76	41.96	15.20	33.09	H	1
20050	1720.0	-23.27	44.14	20.87	122.04	V	1
20175	1732.5	-22.74	44.20	21.46	139.83	V	1
20300	1745.0	-22.79	43.88	21.09	128.59	V	1

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILIITY MEASUREMENT

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.2.2 TEST PROCEDURE

a. Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.

b. EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.

c. The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the ±0.5℃ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP



3.2.4 TEST RESULTS

WCDMA BAND IV

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
V_{nor}	0.0021	0.0021	2.5
V_{min}	-0.0025	-0.0021	2.5
V_{max}	0.0026	0.0021	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0119	-0.0115	2.5
-20	-0.0103	-0.0104	2.5
-10	-0.0085	-0.0083	2.5
0	-0.0077	-0.0076	2.5
10	-0.0056	-0.0054	2.5
20	-0.0043	-0.0038	2.5
30	-0.0040	-0.0037	2.5
40	-0.0023	-0.0019	2.5
50	-0.0004	-0.0003	2.5

LTE BAND 4

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V_{nor}	0.0021	0.0025	2.5
V_{min}	-0.0031	-0.0030	2.5
V_{max}	0.0021	0.0020	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0115	-0.0115	2.5
-20	-0.0106	-0.0104	2.5
-10	-0.0084	-0.0079	2.5
0	-0.0074	-0.0072	2.5
10	-0.0046	-0.0048	2.5
20	-0.0044	-0.0039	2.5
30	-0.0039	-0.0032	2.5
40	-0.0022	-0.0019	2.5
50	-0.0003	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V_{nor}	0.0021	0.0021	2.5
V_{min}	-0.0021	-0.0025	2.5
V_{max}	0.0018	0.0018	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0118	-0.0118	2.5
-20	-0.0100	-0.0098	2.5
-10	-0.0082	-0.0083	2.5
0	-0.0078	-0.0074	2.5
10	-0.0046	-0.0051	2.5
20	-0.0039	-0.0038	2.5
30	-0.0034	-0.0025	2.5
40	-0.0020	-0.0019	2.5
50	-0.0006	-0.0004	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V_{nor}	0.0021	0.0024	2.5
V_{min}	-0.0023	-0.0030	2.5
V_{max}	0.0021	0.0021	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0120	-0.0115	2.5
-20	-0.0105	-0.0102	2.5
-10	-0.0081	-0.0083	2.5
0	-0.0076	-0.0075	2.5
10	-0.0051	-0.0050	2.5
20	-0.0044	-0.0037	2.5
30	-0.0039	-0.0028	2.5
40	-0.0020	-0.0020	2.5
50	-0.0004	-0.0005	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V_{nor}	0.0025	0.0024	2.5
V_{min}	-0.0031	-0.0030	2.5
V_{max}	0.0026	0.0024	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0120	-0.0119	2.5
-20	-0.0104	-0.0102	2.5
-10	-0.0086	-0.0083	2.5
0	-0.0078	-0.0073	2.5
10	-0.0048	-0.0051	2.5
20	-0.0043	-0.0042	2.5
30	-0.0035	-0.0035	2.5
40	-0.0016	-0.0023	2.5
50	-0.0003	-0.0003	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V_{nor}	0.0024	0.0025	2.5
V_{min}	-0.0031	-0.0030	2.5
V_{max}	0.0026	0.0024	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0113	-0.0116	2.5
-20	-0.0108	-0.0101	2.5
-10	-0.0084	-0.0079	2.5
0	-0.0074	-0.0074	2.5
10	-0.0047	-0.0044	2.5
20	-0.0039	-0.0043	2.5
30	-0.0037	-0.0024	2.5
40	-0.0016	-0.0020	2.5
50	-0.0003	-0.0003	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
V_{nor}	0.0024	0.0026	2.5
V_{min}	-0.0030	-0.0030	2.5
V_{max}	0.0024	0.0025	2.5

NOTE: The applicant defined the normal working voltage of the battery is from V_{min} to Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (℃)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0118	-0.0115	2.5
-20	-0.0100	-0.0098	2.5
-10	-0.0083	-0.0081	2.5
0	-0.0075	-0.0073	2.5
10	-0.0046	-0.0049	2.5
20	-0.0042	-0.0040	2.5
30	-0.0040	-0.0033	2.5
40	-0.0021	-0.0018	2.5
50	-0.0004	-0.0005	2.5

3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

a. The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

b. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.4 TEST RESULTS

WCDMA BAND IV

Channel	FREQ. (MHz)	99% Occupied Bandwidth (MHz)	Channel	FREQ. (MHz)	26dB Bandwidth (MHz)
		WCDMA			WCDMA
1312	1712.40	4.13	1312	1712.40	4.73
1413	1732.60	4.12	1413	1732.60	4.72
1513	1752.60	**4.15**	1513	1752.60	4.72

SPECTRUM PLOT OF WORST VALUE	
99% Occupied Bandwidth	26dB Bandwidth
	

LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		
		QPSK	16QAM	64QAM
19957	1710.7	1.09	1.09	1.08
20175	1732.5	1.08	1.09	1.09
20393	1754.3	1.08	1.08	1.08
CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
19957	1710.7	1.22	1.23	1.23
20175	1732.5	1.23	1.23	1.24
20393	1754.3	1.23	1.21	1.21

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



1.4MHz / 64QAM



LTE BAND 4

CHANNEL BANDWIDTH: 3MHz				
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		
		QPSK	16QAM	64QAM
19965	1711.5	2.69	2.68	2.68
20175	1732.5	2.68	2.68	2.68
20385	1753.5	2.68	2.68	2.68
CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
19965	1711.5	2.98	2.93	2.90
20175	1732.5	2.97	2.93	2.91
20385	1753.5	2.91	2.94	2.90

SPECTRUM PLOT OF WORST VALUE

3MHz / QPSK



3MHz / 16QAM



3MHz / 64QAM



LTE BAND 4

CHANNEL BANDWIDTH: 5MHz				
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		
		QPSK	16QAM	64QAM
19975	1712.5	4.47	4.47	4.48
20175	1732.5	4.48	4.47	4.48
20375	1752.5	4.48	4.48	4.48
CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
19975	1712.5	4.87	4.88	4.87
20175	1732.5	4.87	4.84	4.87
20375	1752.5	4.89	4.88	4.87

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



5MHz / 64QAM

LTE BAND 4

CHANNEL BANDWIDTH: 10MHz				
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		
		QPSK	16QAM	64QAM
20000	1715	8.94	8.93	8.94
20175	1732.5	8.92	8.92	8.92
20350	1750	8.95	8.93	8.93
CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
20000	1715	9.54	9.61	9.64
20175	1732.5	9.57	9.55	9.60
20350	1750	9.54	9.55	9.61

SPECTRUM PLOT OF WORST VALUE

10MHz / QPSK

10MHz / 16QAM



10MHz / 64QAM

LTE BAND 4

CHANNEL BANDWIDTH: 15MHz				
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		
		QPSK	16QAM	64QAM
20025	1717.5	13.40	13.40	13.39
20175	1732.5	13.39	13.40	13.39
20325	1747.5	13.39	13.40	13.40
CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
20025	1717.5	14.47	14.51	14.49
20175	1732.5	14.44	14.39	14.52
20325	1747.5	14.44	14.51	14.44

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK

15MHz / 16QAM

15MHz / 64QAM

LTE BAND 4

CHANNEL BANDWIDTH: 20MHz				
CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)		
		QPSK	16QAM	64QAM
20050	1720	17.92	17.84	17.88
20175	1732.5	17.91	17.82	17.86
20300	1745	17.85	17.79	17.88
CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)		
		QPSK	16QAM	64QAM
20050	1720	19.38	19.09	19.22
20175	1732.5	19.45	19.02	19.12
20300	1745	19.01	18.89	19.02

SPECTRUM PLOT OF WORST VALUE

20MHz / QPSK



20MHz / 16QAM



20MHz / 64QAM

3.4 PEAK TO AVERAGE RATIO

3.4.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.

3.4.4 TEST RESULTS

WCDMA Band IV

CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
1312	1712.4	2.68

SPECTRUM PLOT OF WORST VALUE



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
1413	1732.6	2.79

SPECTRUM PLOT OF WORST VALUE



CHANNEL	FREQUENCY (MHz)	PEAK TO AVERAGE RATIO (dB)
1513	1752.6	2.97

SPECTRUM PLOT OF WORST VALUE



LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz				
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)		
		QPSK	16QAM	64QAM
19957	1710.7	4.33	5.40	5.40
20175	1732.5	4.54	5.69	5.66
20393	1754.3	4.92	6.02	6.01

SPECTRUM PLOT OF WORST VALUE

1.4MHz / QPSK



1.4MHz / 16QAM



1.4MHz / 64QAM



LTE BAND 4

CHANNEL BANDWIDTH: 3MHz				
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)		
		QPSK	16QAM	64QAM
19965	1711.5	4.44	5.55	6.26
20175	1732.5	4.53	5.71	6.37
20385	1753.5	4.86	6.05	6.76

SPECTRUM PLOT OF WORST VALUE

3MHz / QPSK



3MHz / 16QAM



3MHz / 64QAM



CHANNEL BANDWIDTH: 5MHz				
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)		
		QPSK	16QAM	64QAM
19975	1712.5	4.74	5.70	6.37
20175	1732.5	4.78	5.79	6.44
20375	1752.5	4.98	6.02	6.70

SPECTRUM PLOT OF WORST VALUE

5MHz / QPSK



5MHz / 16QAM



5MHz / 64QAM

CHANNEL BANDWIDTH: 10MHz				
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)		
		QPSK	16QAM	64QAM
20000	1715	4.64	5.63	6.34
20175	1732.5	4.63	5.69	6.32
20350	1750	4.82	5.85	6.51

SPECTRUM PLOT OF WORST VALUE

10MHz / QPSK



10MHz / 16QAM



10MHz / 64QAM



CHANNEL BANDWIDTH: 15MHz				
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)		
		QPSK	16QAM	64QAM
20025	1717.5	4.74	5.86	6.47
20175	1732.5	4.65	5.69	6.34
20325	1747.5	4.79	5.85	6.50

SPECTRUM PLOT OF WORST VALUE

15MHz / QPSK



15MHz / 16QAM



15MHz / 64QAM



CHANNEL BANDWIDTH: 20MHz				
CHANNEL	Frequency (MHz)	PEAK TO AVERAGE RATIO (dB)		
		QPSK	16QAM	64QAM
20050	1720	4.73	5.88	6.51
20175	1732.5	4.62	5.72	6.34
20300	1745	4.75	5.86	6.49

SPECTRUM PLOT OF WORST VALUE

20MHz / QPSK



20MHz / 16QAM



20MHz / 64QAM



3.5 BAND EDGE MEASUREMENT

3.5.1 LIMITS OF BAND EDGE MEASUREMENT

The power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater.
However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

3.5.2 TEST SETUP



3.5.3 TEST PROCEDURES

a. The EUT was set up for the maximum peak power with LTE link data modulation. The power was measured with R&S Spectrum Analyzer. All measurements were done at 2 channels (low and high operational frequency range.).

b. The band edge measurement used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.

c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz (WCDMA).

d. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 20kHz and VBW of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz)

e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 30kHz and VBW of the spectrum is 100kHz. (LTE bandwidth 3MHz)

f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 50kHz and VBW of the spectrum is 200kHz. (LTE bandwidth 5MHz)

g. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz. (LTE bandwidth 10MHz)

h. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz. (LTE bandwidth 15MHz)

i. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz. (LTE bandwidth 20MHz)

j. Record the max trace plot into the test report.

3.5.4 TEST RESULTS

WCDMA BAND 4

WCDMA			
CHANNEL	1312	CHANNEL	1513
			

LTE BAND 4

Channel Bandwidth: 1.4MHz QPSK					
CHANNEL	19957	1 RB	CHANNEL	20393	1 RB
CHANNEL	19957	Full RB	CHANNEL	20393	Full RB

Channel Bandwidth: 1.4MHz 16QAM

CHANNEL	19957	1 RB	CHANNEL	20393	1 RB

CHANNEL	19957	Full RB	CHANNEL	20393	Full RB

Channel Bandwidth: 1.4MHz 64QAM

CHANNEL	19957	1 RB	CHANNEL	20393	1 RB

CHANNEL	19957	Full RB	CHANNEL	20393	Full RB



LTE BAND 4

Channel Bandwidth: 3MHz QPSK

CHANNEL	19965	1 RB	CHANNEL	20385	1 RB

CHANNEL	19965	Full RB	CHANNEL	20385	Full RB

Channel Bandwidth: 3MHz 16QAM

CHANNEL	19965	1 RB	CHANNEL	20385	1 RB

CHANNEL	19965	Full RB	CHANNEL	20385	Full RB

Channel Bandwidth: 3MHz 64QAM

CHANNEL	19965	1 RB	CHANNEL	20385	1 RB

CHANNEL	19965	Full RB	CHANNEL	20385	Full RB

LTE BAND 4

Channel Bandwidth: 5MHz QPSK

CHANNEL	19975	1 RB	CHANNEL	20375	1 RB

CHANNEL	19975	Full RB	CHANNEL	20375	Full RB

Channel Bandwidth: 5MHz 16QAM

CHANNEL	19975	1 RB	CHANNEL	20375	1 RB

CHANNEL	19975	Full RB	CHANNEL	20375	Full RB



Channel Bandwidth: 5MHz 64QAM

CHANNEL	19975	1 RB	CHANNEL	20375	1 RB

CHANNEL	19975	Full RB	CHANNEL	20375	Full RB



LTE BAND 4

Channel Bandwidth: 10MHz QPSK

CHANNEL	20000	1 RB	CHANNEL	20350	1 RB

CHANNEL	20000	Full RB	CHANNEL	20350	Full RB



Channel Bandwidth: 10MHz 16QAM

CHANNEL	20000	1 RB	CHANNEL	20350	1 RB

CHANNEL	20000	Full RB	CHANNEL	20350	Full RB

Channel Bandwidth: 10MHz 64QAM

CHANNEL	20000	1 RB	CHANNEL	20350	1 RB

CHANNEL	20000	Full RB	CHANNEL	20350	Full RB

LTE BAND 4

Channel Bandwidth: 15MHz QPSK

CHANNEL	20025	1 RB	CHANNEL	20325	1 RB

CHANNEL	20025	Full RB	CHANNEL	20325	Full RB



Channel Bandwidth: 15MHz 16QAM

CHANNEL	20025	1 RB	CHANNEL	20325	1 RB

CHANNEL	20025	Full RB	CHANNEL	20325	Full RB



Channel Bandwidth: 15MHz 64QAM

CHANNEL	20025	1 RB	CHANNEL	20325	1 RB

CHANNEL	20025	Full RB	CHANNEL	20325	Full RB

LTE BAND 4

Channel Bandwidth: 20MHz QPSK

CHANNEL	20050	1 RB	CHANNEL	20300	1 RB

CHANNEL	20050	Full RB	CHANNEL	20300	Full RB



Channel Bandwidth: 20MHz 16QAM

CHANNEL	20050	1 RB	CHANNEL	20300	1 RB

CHANNEL	20050	Full RB	CHANNEL	20300	Full RB



Channel Bandwidth: 20MHz 64QAM

CHANNEL	20050	1 RB	CHANNEL	20300	1 RB

CHANNEL	20050	Full RB	CHANNEL	20300	Full RB



3.6 CONDUCTED SPURIOUS EMISSIONS

3.6.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 +10 log10(P) dB. The limit of emission equal to –13dBm

3.6.2 TEST PROCEDURE

a. The EUT makes a phone call to the communication simulator. All measurements were done at middle operational frequency range.

b. Measuring frequency range is from 30 MHz to 19.1GHz for WCDMA Band 4 & LTE Band 4. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

3.6.3 TEST SETUP



3.6.4 TEST RESULTS

WCDMA	
CHANNEL 1312	CHANNEL 1413
FREQUENCY RANGE : 30MHz~18.0GHz	FREQUENCY RANGE : 30MHz~18.0GHz
	
CHANNEL 1513	
FREQUENCY RANGE : 30MHz~18.0GHz	
	

LTE BAND 4

1.4MHz / QPSK

CHANNEL 19957

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20175

FREQUENCY RANGE : 30MHz~18.0GHz

CHANNEL 20393

FREQUENCY RANGE : 30MHz~18.0GHz



3MHz / QPSK

CHANNEL 19965

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20175

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20385

FREQUENCY RANGE : 30MHz~18.0GHz



5MHz / QPSK

CHANNEL 19975

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20175

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20375

FREQUENCY RANGE : 30MHz~18.0GHz



10MHz / QPSK

CHANNEL 20000

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20175

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20350

FREQUENCY RANGE : 30MHz~18.0GHz



15MHz / QPSK

CHANNEL 20025

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20175

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20325

FREQUENCY RANGE : 30MHz~18.0GHz



20MHz / QPSK

CHANNEL 20050

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20175

FREQUENCY RANGE : 30MHz~18.0GHz



CHANNEL 20300

FREQUENCY RANGE : 30MHz~18.0GHz



3.7 RADIATED EMISSION MEASUREMENT

3.7.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least 43 +10 log10(P) dB. The limit of emission equal to –13dBm

3.7.2 TEST PROCEDURES

a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.

b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G

c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.

d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.P.R power - 2.15dBi.

NOTE: The resolution bandwidth of spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz.

3.7.3 DEVIATION FROM TEST STANDARD

No deviation

3.7.4 TEST SETUP

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.7.5 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

30 MHz – 1GHz data:

LTE BAND 4

CHANNEL BANDWIDTH: 10MHz / QPSK

MODE	TX channel 20175	**FREQUENCY RANGE**	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	**INPUT POWER**	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		46.230	-45.18	-51.75	-13.00	-32.18	6.57	Peak	Horizontal
2		88.410	-54.09	-45.26	-13.00	-41.09	-8.83	Peak	Horizontal
3	PP	135.230	-37.34	-19.51	-13.00	-24.34	-17.83	Peak	Horizontal
4		195.120	-51.59	-34.23	-13.00	-38.59	-17.36	Peak	Horizontal
5		245.410	-59.09	-42.72	-13.00	-46.09	-16.37	Peak	Horizontal
6		304.690	-53.20	-39.55	-13.00	-40.20	-13.65	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1		56.320	-50.23	-40.67	-13.00	-37.23	-9.56	Peak	Vertical
2	PP	126.350	-40.16	-28.23	-13.00	-27.16	-11.93	Peak	Vertical
3		185.630	-61.66	-49.21	-13.00	-48.66	-12.45	Peak	Vertical
4		225.360	-44.34	-33.26	-13.00	-31.34	-11.08	Peak	Vertical
5		321.450	-56.84	-45.62	-13.00	-43.84	-11.22	Peak	Vertical
6		415.210	-51.71	-41.34	-13.00	-38.71	-10.37	Peak	Vertical



ABOVE 1GHz

Note: For higher frequency, the emission is too low to be detected.

WCDMA Band IV:

CH 1312

MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3418.000	-41.53	-50.12	-13.00	-28.53	8.59	Peak	Horizontal
2	5137.200	-45.42	-54.36	-13.00	-32.42	8.94	Peak	Horizontal



MODE	TX channel 1312	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3418.000	-41.74	-50.85	-13.00	-28.74	9.11	Peak	Vertical
2	5137.200	-45.57	-55.42	-13.00	-32.57	9.85	Peak	Vertical



CH 1413

MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3470.000	-41.29	-49.87	-13.00	-28.29	8.58	Peak	Horizontal
2	5197.800	-46.12	-55.24	-13.00	-33.12	9.12	Peak	Horizontal



MODE	TX channel 1413	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-41.15	-50.31	-13.00	-28.15	9.16	Peak	Vertical
2		5197.800	-44.84	-54.66	-13.00	-31.84	9.82	Peak	Vertical



CH 1513

MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3496.000	-41.88	-50.45	-13.00	-28.88	8.57	Peak	Horizontal
2		5257.800	-44.86	-54.16	-13.00	-31.86	9.30	Peak	Horizontal



MODE	TX channel 1513	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3496.000	-42.04	-51.23	-13.00	-29.04	9.19	Peak	Vertical
2		5257.800	-44.87	-54.67	-13.00	-31.87	9.80	Peak	Vertical



LTE BAND 4

CHANNEL BANDWIDTH: 1.4MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3470.000	-43.78	-52.36	-13.00	-30.78	8.58	Peak	Horizontal
2	5197.500	-45.59	-54.71	-13.00	-32.59	9.12	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-42.32	-51.48	-13.00	-29.32	9.16	Peak	Vertical
2		5197.500	-46.41	-56.23	-13.00	-33.41	9.82	Peak	Vertical



CHANNEL BANDWIDTH: 3MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-42.76	-51.34	-13.00	-29.76	8.58	Peak	Horizontal
2		5197.500	-45.57	-54.69	-13.00	-32.57	9.12	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-41.13	-50.29	-13.00	-28.13	9.16	Peak	Vertical
2		5197.500	-44.46	-54.28	-13.00	-31.46	9.82	Peak	Vertical



CHANNEL BANDWIDTH: 5MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3470.000	-42.66	-51.24	-13.00	-29.66	8.58	Peak	Horizontal
2	5197.500	-45.24	-54.36	-13.00	-32.24	9.12	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-41.26	-50.42	-13.00	-28.26	9.16	Peak	Vertical
2		5197.500	-45.41	-55.23	-13.00	-32.41	9.82	Peak	Vertical



CHANNEL BANDWIDTH: 10MHz / QPSK

CH 20000

MODE	TX channel 20000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3418.000	-41.17	-49.76	-13.00	-28.17	8.59	Peak	Horizontal
2	5145.000	-46.29	-55.25	-13.00	-33.29	8.96	Peak	Horizontal



MODE	TX channel 20000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3418.000	-40.52	-49.63	-13.00	-27.52	9.11	Peak	Vertical
2		5145.000	-45.40	-55.24	-13.00	-32.40	9.84	Peak	Vertical



CH 20175

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3470.000	-40.63	-49.21	-13.00	-27.63	8.58	Peak	Horizontal
2	5197.500	-45.24	-54.36	-13.00	-32.24	9.12	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-39.08	-48.24	-13.00	-26.08	9.16	Peak	Vertical
2		5197.500	-43.43	-53.25	-13.00	-30.43	9.82	Peak	Vertical



CH 20350

MODE	TX channel 20350	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3496.000	-40.99	-49.56	-13.00	-27.99	8.57	Peak	Horizontal
2		5250.000	-45.34	-54.61	-13.00	-32.34	9.27	Peak	Horizontal



MODE	TX channel 20350	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3496.000	-40.49	-49.68	-13.00	-27.49	9.19	Peak	Vertical
2		5250.000	-44.51	-54.31	-13.00	-31.51	9.80	Peak	Vertical



CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-41.07	-49.65	-13.00	-28.07	8.58	Peak	Horizontal
2		5197.500	-46.14	-55.26	-13.00	-33.14	9.12	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-42.12	-51.28	-13.00	-29.12	9.16	Peak	Vertical
2		5197.500	-44.85	-54.67	-13.00	-31.85	9.82	Peak	Vertical



CHANNEL BANDWIDTH: 20MHz / QPSK

MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3470.000	-41.65	-50.23	-13.00	-28.65	8.58	Peak	Horizontal
2	5197.500	-46.62	-55.74	-13.00	-33.62	9.12	Peak	Horizontal



MODE	TX channel 20175	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	DC 5V/9V/12V from adapter
TESTED BY	Star Le		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3470.000	-40.96	-50.12	-13.00	-27.96	9.16	Peak	Vertical
2		5197.500	-45.03	-54.85	-13.00	-32.03	9.82	Peak	Vertical



4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:
Tel: +86-755-88696566
Fax: +86-755-88696577

Email: customerservice.dg@cn.bureauveritas.com
Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

---END---