

EMC TEST REPORT

Applicant	Xiaomi Communications Co., Ltd.
FCC ID	Wireless Earphones: 2AFZZM2540E1 Charging Case: 2AFZZEC2501
Product	Wireless Earphones Charging Case
Brand	Wireless Earphones: Xiaomi Charging Case: Xiaomi
Model	Wireless Earphones: M2540E1 Charging Case: EC2501
Report No.	EFTA25090180-IE-01-E1V1
Issue Date	October 24, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2024)/ ANSI C63.4-2014**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Liu Wei

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Table of Contents

1	Test Laboratory	5
1.1	Notes of the Test Report.....	5
1.2	Test Facility	5
1.3	Testing Location.....	5
2	General Description of Equipment Under Test	6
2.1	Applicant and Manufacturer Information	6
2.2	General Information	6
2.3	Applied Standards	7
2.4	Test Mode	8
3	Test Case Results	9
3.1	Radiated Emission	9
3.2	Conducted Emission	14
4	Uncertainty Measurement.....	17
5	Main Test Instruments	18
6	The EUT Appearance.....	19
7	Test Setup Photos	20

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	October 20, 2025
Rev.1	Updated information.	October 24, 2025
Note: This revised report (Report No.: EFTA25090180-IE-01-E1V1) supersedes and replaces the previously issued report (Report No.: EFTA25090180-IE-01-E1). Please discard or destroy the previously issued report and dispose of it accordingly.		

Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Date of Testing: September 26, 2025 ~ September 29, 2025			
Date of Sample Received: September 15, 2025			
Note:			
1. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

2 General Description of Equipment Under Test

2.1 Applicant and Manufacturer Information

Applicant	Xiaomi Communications Co., Ltd.
Applicant address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer	Xiaomi Communications Co., Ltd.
Manufacturer address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

2.2 General Information

EUT Description				
Device Type	Portable Device			
Model	Wireless Earphones: M2540E1 Charging Case: EC2501			
SN	71608CRAG515W300			
HW Version	Wireless Earphones: V4 Charging Case: V3			
SW Version	Wireless Earphones: 1.1.2.5 Charging Case: 1.0.4.1			
Power Rating	Wireless Earphones: 1# DC 3.85V Supplied from battery 2# DC 5V Supplied from EC2501 Charging Case: 1# DC 3.8V Supplied from battery 2# DC 5V Supplied from Adapter or host equipment			
Connecting I/O Port(s)	Please refer to the User's Manual.			
Antenna Type	Wireless Earphones: Laser engraved antenna Charging Case: FPC Antenna			
Frequency	Band		Tx (MHz)	Rx (MHz)
	Wireless Earphones	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
		Bluetooth LE	2400 ~ 2483.5	2400 ~ 2483.5
	Charging Case	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
Auxiliary Test Equipment				
Adapter	Manufacturer: HUAWEI Model: HW-050200E01 Input: 100-240V~50/60Hz 0.5A Output: 5.0V  2.0A			
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.				

2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

FCC Code CFR47 Part15B (2024)

ANSI C63.4-2014

2.4 Test Mode

Test Mode	
Mode 1	Adapter + USB cable + Charging Case + Wireless Earphones + charging
Mode 2	Adapter + USB cable + Charging Case + Wireless Earphones + BT pairing + play music

Test Type	Test Mode	Worst Mode
Radiated Emission	Mode 1, 2	Mode 1
Conducted Emission	Mode 1, 2	Mode 1
After technical evaluation or/and preliminary test, the test data of the worst-case condition was recorded in this report.		

3 Test Case Results

3.1 Radiated Emission

Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:


(a) PEAK Detector: RBW=1MHz / VBW=3MHz/ Sweep=AUTO

(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO


The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

Test Setup

Below 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

Limits

Class B

Frequency (MHz)	Field Strength (dB μ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 th harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak


Frequency range of radiated measurements

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier.

The following graphs display the maximum values of horizontal and vertical by software.



~ QP Level @Spectrum Overview H ~ QP Level @Spectrum Overview V ◆ QP Level @Final Results — QP Limit


Radiated Emission from 30MHz to 1GHz

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
49.92	16.33	40.00	23.67	1000.00	225.0	V	11.00	20
66.42	14.43	40.00	25.57	1000.00	125.0	V	24.00	17
173.09	13.33	43.50	30.17	1000.00	125.0	V	130.00	16
208.75	14.92	43.50	28.58	1000.00	174.0	H	54.00	18
551.11	23.56	46.00	22.44	1000.00	101.0	H	76.00	26
949.76	29.05	46.00	16.95	1000.00	108.0	V	338.00	31

Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss)

2. Margin = Limit – Quasi-Peak



PK Level @Spectrum Overview H PK Level @Spectrum Overview V PK Level @Final Results PK Limit
 AVG Level @Spectrum Overview H AVG Level @Spectrum Overview V AVG Level @Final Results AVG Limit

Radiated Emission from 1GHz to 18GHz

Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
1527.00	---	17.99	54.00	36.01	1000.00	220.0	H	218.00	-14
1544.00	30.78	---	74.00	43.22	1000.00	104.0	V	245.00	-14
2413.13	---	23.14	54.00	30.86	1000.00	225.0	H	209.00	-11
2615.00	33.31	---	74.00	40.69	1000.00	108.0	H	135.00	-10
4193.88	---	23.86	54.00	30.14	1000.00	101.0	V	330.00	-6
4213.00	36.32	---	74.00	37.68	1000.00	214.0	H	320.00	-6
6737.50	---	28.68	54.00	25.32	1000.00	125.0	V	129.00	0
6739.63	41.38	---	74.00	32.62	1000.00	109.0	H	250.00	0
10373.38	---	33.18	54.00	20.82	1000.00	100.0	V	178.00	5
10811.13	46.71	---	74.00	27.29	1000.00	193.0	V	284.00	5
14574.50	51.46	---	74.00	22.54	1000.00	114.0	V	192.00	9
14606.38	---	38.59	54.00	15.41	1000.00	125.0	V	22.00	9

Remark: 1. Correction Factor = Antenna factor + Insertion loss (cable loss + amplifier gain)

2. Margin = Limit – MaxPeak / Average

3.2 Conducted Emission


Ambient Condition

Temperature	Relative humidity
15°C ~ 35°C	30% ~ 60%

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

Test Setup




Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

Limits

Frequency (MHz)	Class A (dBμV)		Class B (dBμV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 to 56 *	56 to 46*
0.5 - 5	73	60	56	46
5 - 30	73	60	60	50
*: Decreases with the logarithm of the frequency.				

Note: The EUT should meet CLASS B limit.

Test Results




Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	AVG Level [dBµV]	AVG: CAV Limit [dBµV]	AVG Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]	Meas. Time [s]
0.235	29.53	62.27	32.74	15.89	52.27	36.38	20.99	L1	9.000	1.000
0.503	34.13	56.00	21.87	30.46	46.00	15.54	20.77	L1	9.000	1.000
1.253	16.73	56.00	39.27	11.74	46.00	34.26	19.98	L1	9.000	1.000
3.664	15.75	56.00	40.25	10.86	46.00	35.14	19.44	L1	9.000	1.000
8.730	14.78	60.00	45.22	9.77	50.00	40.23	19.41	L1	9.000	1.000
23.631	15.01	60.00	44.99	9.93	50.00	40.07	19.77	L1	9.000	1.000

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 kHz to 30 MHz



Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	AVG Level [dBµV]	AVG: CAV Limit [dBµV]	AVG Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]	Meas. Time [s]
0.209	34.92	63.25	28.33	20.46	53.25	32.79	21.02	N	9.000	1.000
0.499	36.29	56.02	19.73	28.69	46.02	17.33	20.79	N	9.000	1.000
1.136	17.22	56.00	38.78	12.19	46.00	33.81	20.07	N	9.000	1.000
2.783	15.86	56.00	40.14	10.78	46.00	35.22	19.52	N	9.000	1.000
8.042	15.62	60.00	44.38	10.52	50.00	39.48	19.42	N	9.000	1.000
21.769	14.79	60.00	45.21	9.57	50.00	40.43	19.75	N	9.000	1.000

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 kHz to 30 MHz

4 Uncertainty Measurement

Case	Uncertainty	Factor k
Radiated Emission 30MHz – 200MHz	4.17 dB	1.96
Radiated Emission 200MHz – 1GHz	4.84 dB	1.96
Radiated Emission 1GHz – 18GHz	4.35 dB	1.96
Conducted Emission	2.57 dB	2

5 Main Test Instruments

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Expiration Time
Radiated Emission					
EMI Test Receiver	R&S	ESCI3	100948	2025-05-07	2026-05-06
Signal Analyzer	R&S	FSV40	101186	2025-05-06	2026-05-05
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2023-07-14	2026-07-13
Horn Antenna	SCHWARZBECK	BBHA 9120D	430	2024-07-18	2027-07-17
Amplifier	R&S	SCU18F	101022	2025-05-06	2026-05-05
Software	R&S	EMC32	9.26.01	/	/
Conducted Emission					
Artificial main network	R&S	ENV216	102191	2024-12-02	2026-12-01
EMI Test Receiver	R&S	ESR	101667	2025-05-06	2026-05-05
Software	R&S	EMC32	10.35.10	/	/

6 The EUT Appearance

Refer to *EUT Appearance*.

7 Test Setup Photos

Refer to *EMC Test Setup*.

***** END OF REPORT *****