FCC RADIO TEST REPORT

FCC ID	:	**2AFZZK2G**
Equipment	:	**Mobile Phone**
Brand Name	:	**Xiaomi**
Model Name	:	**M2011K2G**
Applicant	:	**Xiaomi Communications Co., Ltd. #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085**
Manufacturer	:	**Xiaomi Communications Co., Ltd. #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085**
Standard	:	**FCC Part 15 Subpart C §15.247**

The product was received on Nov. 10, 2020 and testing was started from Nov. 15, 2020 and completed on Dec. 10, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Reviewed by: Louis Wu

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 6
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 Number of Channel Measurement 11
3.2 Hopping Channel Separation Measurement 14
3.3 Dwell Time Measurement 25
3.4 20dB and 99% Bandwidth Measurement 28
3.5 Output Power Measurement 49
3.6 Conducted Band Edges Measurement 50
3.7 Conducted Spurious Emission Measurement 63
3.8 Radiated Band Edges and Spurious Emission Measurement 82
3.9 AC Conducted Emission Measurement 86
3.10 Antenna Requirements 88
4 List of Measuring Equipment **89**
5 Uncertainty of Evaluation **91**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission
Appendix D. Radiated Spurious Emission Plots
Appendix E. Duty Cycle Plots
Appendix F. Setup Photographs

History of this test report

Report No.	Version	Description	Issued Date
FR0N0303A	01	Initial issue of report	Dec. 17, 2020

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 8.71 dB at 815.700 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 15.09 dB at 11.749 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Ruby Zou

1 General Description

1.1 Product Feature of Equipment Under Test

GSM/WCDMA/LTE/5G NR, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax, Wi-Fi 5GHz 802.11a/n/ac/ax, NFC, WPC/WPT and GNSS.

Product Specification subjective to this standard	
Sample 1	Memory (8+256GB)
Sample 2	Memory (8+128GB)
Antenna Type	WWAN: PIFA Antenna WLAN **<2400 MHz ~ 2483.5 MHz>** <Ant. 5>: PIFA Antenna <Ant. 7>: PIFA Antenna **<5150 MHz ~ 5850 MHz>** <Ant. 8>: PIFA Antenna <Ant. 10>: PIFA Antenna Bluetooth <Ant. 5>: PIFA Antenna <Ant. 7>: PIFA Antenna GPS / Glonass / Galileo / BDS: PIFA Antenna NFC: planar Antenna WPC/WPT: Coil antenna

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	Ant. 5: -1.35 dBi Ant. 7: -1.87 dBi

Remark: The above EUT's information was declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.2 Modification of EUT

No modifications are made to the EUT during all test items.

1.3 Testing Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	**Sporton Site No.**
	TH05-HY, CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH13-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z and WPC Charging Mode. The worst cases (X plane for Ant. 5 and Z plane for Ant. 7) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	**Data Rate / Modulation**		
Conducted Test Cases	**Bluetooth BR 1Mbps GFSK**	**Bluetooth EDR 2Mbps π/4-DQPSK**	**Bluetooth EDR 3Mbps 8-DPSK**
	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	**Bluetooth EDR 3Mbps 8-DPSK**		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN (2.4GHz) Link + MPEG4 + USB Cable (Charging from AC Adapter) for Sample 1		

Remark:
1. For radiated test cases, the worst mode data rate 3Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 3Mbps, and no other significantly frequencies found in conducted spurious emission.
2. For Radiated Test Cases, the tests were performed with Sample 1

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	Dell	Latitude 3400	FCC DoC	N/A	AC I/P：Unshielded, 1.2m DC O/P：Shielded, 1.8m
5.	Mobile Phone	xlaomi	K2	M2011K2G	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, make the EUT get into the engineering modes to contact with base station to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:
The spectrum analyzer offset is derived from RF cable loss and attenuator factor.
Offset = RF cable loss + attenuator factor.
Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

<Ant. 5>

Number of Hopping Channel Plot on Channel 00 - 78



Date: 4.DEC.2020 00:04:22



Date: 4.DEC.2020 00:05:06

<Ant. 7>

Number of Hopping Channel Plot on Channel 00 - 78



Date: 4.DEC.2020 01:45:35



Date: 4.DEC.2020 01:46:24

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
   Span = wide enough to capture the peaks of two adjacent channels;
   RBW = 300kHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

<Ant. 5>

<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 3.DEC.2020 23:26:43

Channel Separation Plot on Channel 39 - 40



Date: 3.DEC.2020 23:25:52

Channel Separation Plot on Channel 77 - 78



Date: 3.DEC.2020 23:27:35

<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 3.DEC.2020 23:28:28

Channel Separation Plot on Channel 39 - 40



Date: 3.DEC.2020 23:29:19

Channel Separation Plot on Channel 77 - 78



Date: 3.DEC.2020 23:30:14

<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 4.DEC.2020 00:09:36

Channel Separation Plot on Channel 39 - 40



Date: 4.DEC.2020 02:11:08

Channel Separation Plot on Channel 77 - 78



Date: 4.DEC.2020 02:12:17

<Ant. 7>

<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 4.DEC.2020 00:59:10

Channel Separation Plot on Channel 39 - 40



Date: 4.DEC.2020 00:59:58

Channel Separation Plot on Channel 77 - 78



Date: 4.DEC.2020 01:00:51

<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 4.DEC.2020 01:53:25

Channel Separation Plot on Channel 39 - 40



Date: 4.DEC.2020 01:55:52

Channel Separation Plot on Channel 77 - 78



Date: 4.DEC.2020 01:04:03

<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 4.DEC.2020 01:58:49

Channel Separation Plot on Channel 39 - 40



Date: 4.DEC.2020 02:00:43

Channel Separation Plot on Channel 77 - 78



Date: 4.DEC.2020 01:11:27

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

<Ant. 5>

Package Transfer Time Plot



Date: 18.NOV.2020 05:48:57

<Ant. 7>

Package Transfer Time Plot



Date: 21.NOV.2020 03:55:32

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.

2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.

3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
   Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
   RBW ≥ 1% of the 20 dB bandwidth; VBW ≥ RBW; Sweep = auto; Detector function = peak;
   Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
   Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
   RBW ≥ 1-5% of the 99% bandwidth; VBW ≥ 3 * RBW; Sweep = auto; Detector function = peak;
   Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

<Ant. 5>

<1Mbps>

20 dB Bandwidth Plot on Channel 00

Date: 3.DEC.2020 23:15:17

20 dB Bandwidth Plot on Channel 39



Date: 3.DEC.2020 23:16:37

20 dB Bandwidth Plot on Channel 78



Date: 3.DEC.2020 23:17:36

<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 3.DEC.2020 23:18:44

20 dB Bandwidth Plot on Channel 39



Date: 3.DEC.2020 23:19:41

20 dB Bandwidth Plot on Channel 78



Date: 3.DEC.2020 23:20:36

<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 3.DEC.2020 23:21:42

20 dB Bandwidth Plot on Channel 39



Date: 3.DEC.2020 23:22:43

20 dB Bandwidth Plot on Channel 78



<Ant. 7>

<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 4.DEC.2020 01:12:59

20 dB Bandwidth Plot on Channel 39



Date: 4.DEC.2020 01:14:04

20 dB Bandwidth Plot on Channel 78



Date: 4.DEC.2020 01:14:59

<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 4.DEC.2020 01:16:00

20 dB Bandwidth Plot on Channel 39



Date: 4.DEC.2020 01:17:10

20 dB Bandwidth Plot on Channel 78



Date: 4.DEC.2020 01:18:02

<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 4.DEC.2020 01:19:22

20 dB Bandwidth Plot on Channel 39



Date: 4.DEC.2020 01:21:06

20 dB Bandwidth Plot on Channel 78



Date: 4.DEC.2020 01:21:52

3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<Ant. 5>

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00



99% Occupied Bandwidth Plot on Channel 39

99% Occupied Bandwidth Plot on Channel 78

Date: 3.DEC.2020 23:39:24

<2Mbps>

99% Occupied Bandwidth Plot on Channel 00

Date: 3.DEC.2020 23:40:26

99% Occupied Bandwidth Plot on Channel 39



Date: 3.DEC.2020 23:41:14

99% Occupied Bandwidth Plot on Channel 78



Date: 3.DEC.2020 23:41:56

<3Mbps>

99% Occupied Bandwidth Plot on Channel 00

Date: 3.DEC.2020 23:42:39

99% Occupied Bandwidth Plot on Channel 39



Date: 3.DEC.2020 23:43:20

99% Occupied Bandwidth Plot on Channel 78

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<Ant. 7>

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 4.DEC.2020 01:25:39

99% Occupied Bandwidth Plot on Channel 39



Date: 4.DEC.2020 01:26:21

99% Occupied Bandwidth Plot on Channel 78

Date: 4.DEC.2020 01:27:01

<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 4.DEC.2020 01:27:46

99% Occupied Bandwidth Plot on Channel 39



Date: 4.DEC.2020 01:28:28

99% Occupied Bandwidth Plot on Channel 78



Date: 4.DEC.2020 01:29:21

<3Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 4.DEC.2020 01:30:42

99% Occupied Bandwidth Plot on Channel 39



Date: 4.DEC.2020 01:31:24

99% Occupied Bandwidth Plot on Channel 78



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following: For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

<Ant. 5>

<1Mbps>

Low Band Edge Plot on Channel 00



Date: 3.DEC.2020 23:56:38

High Band Edge Plot on Channel 78



Date: 3.DEC.2020 23:57:08

<2Mbps>

Low Band Edge Plot on Channel 00



Date: 3.DEC.2020 23:57:39

High Band Edge Plot on Channel 78



Date: 3.DEC.2020 23:58:05

<3Mbps>

Low Band Edge Plot on Channel 00



Date: 3.DEC.2020 23:58:36

High Band Edge Plot on Channel 78



Date: 3.DEC.2020 23:59:04

<Ant. 7>

<1Mbps>

Low Band Edge Plot on Channel 00



Date: 4.DEC.2020 01:22:24

High Band Edge Plot on Channel 78



Date: 4.DEC.2020 01:22:50

<2Mbps>

Low Band Edge Plot on Channel 00



Date: 4.DEC.2020 01:23:28

High Band Edge Plot on Channel 78



Date: 4.DEC.2020 01:23:55

<3Mbps>

Low Band Edge Plot on Channel 00



Date: 4.DEC.2020 01:24:23

High Band Edge Plot on Channel 78



Date: 4.DEC.2020 01:24:56

3.6.6 Test Result of Conducted Hopping Mode Band Edges

<Ant. 5>

<1Mbps>

Hopping Mode Low Band Edge Plot



Date: 4.DEC.2020 00:00:31

Hopping Mode High Band Edge Plot



Date: 4.DEC.2020 00:01:07

<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 4.DEC.2020 00:01:35

Hopping Mode High Band Edge Plot



Date: 4.DEC.2020 00:02:08

<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 4.DEC.2020 00:02:46

Hopping Mode High Band Edge Plot



Date: 4.DEC.2020 00:03:12