FCC RF Test Report

APPLICANT	:	Xiaomi Communications Co., Ltd.
EQUIPMENT	:	Mobile Phone
BRAND NAME	:	Redmi
MODEL NAME	:	M2101K6G
FCC ID	:	2AFZZK6G
STANDARD	:	47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Nov. 28, 2020 and completely tested on Dec. 10, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7
1.7 Testing Location 7
1.8 Test Software 8
1.9 Applicable Standards 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**

2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration 10
2.4 Measurement Results Explanation Example 10
2.5 Frequency List of Low/Middle/High Channels 11

3 CONDUCTED TEST RESULT **12**

3.1 Measuring Instruments 12
3.2 Test Setup 12
3.3 Test Result of Conducted Test 12
3.4 Conducted Output Power and ERP/EIRP 13
3.5 Peak-to-Average Ratio 14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 15
3.7 Conducted Band Edge 16
3.8 Conducted Spurious Emission 17
3.9 Frequency Stability 18

4 RADIATED TEST ITEMS **19**

4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 19
4.4 Field Strength of Spurious Radiation Measurement 20

5 LIST OF MEASURING EQUIPMENT **21**

6 UNCERTAINTY OF EVALUATION **22**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG0N2803A	Rev. 01	Initial issue of report	Dec. 30, 2020

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 25.97 dB at 2510.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.
#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.
#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	M2101K6G
FCC ID	2AFZZK6G
EUT supports Radios application	GSM/WCDMA/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE FM Receiver and GNSS
IMEI Code	Conducted: 861489050004665/861489050004673 Radiation: 861489050005944/861489050005951
HW Version	P2
SW Version	MIUI 12
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are three types of EUT, the sample 1 is 6+64GB capacity, the sample 2 is 6+128GB capacity and the sample 3 is 8+128GB capacity. According to the difference, we only choose sample 1 to perform full tests.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	**GSM/GPRS/EDGE:** 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz **WCDMA:** Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	**GSM/GPRS/EDGE:** 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz **WCDMA:** Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	**Ant:2：Top Antenna:** **GSM/GPRS/EDGE:** 850: 32.68 dBm 1900: 30.45 dBm **WCDMA:** Band V: 23.92 dBm Band II: 24.06 dBm Band IV: 23.81 dBm
Antenna Type	PIFA Antenna for Bottom Antenna Loop Antenna for Top Antenna
Antenna Gain	**Ant:2：Top Antenna:** Cellular Band: -4.9 dBi PCS Band: -1.9 dBi AWS Band: -0.6 dBi **Ant 1：Bottom Antenna:** Cellular Band: -5.7 dBi PCS Band: -1.5 dBi AWS Band: -1.2 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK HSPA : QPSK HSUPA : QPSK HSPA+ : 16QAM DC-HSDPA : 64QAM

Note: The Maximum ERP/EIRP is calculated from Max Output power and Max antenna gain, only the maximum ERP/EIRP is shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.3656	0.0328 ppm	244KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.0891	0.0234 ppm	245KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	BPSK	0.0486	0.0278 ppm	4M14F9W
Part 24	GSM1900 GSM	GMSK	0.7161	0.0146 ppm	244KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.2600	0.0182 ppm	250KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	BPSK	0.1644	0.0174 ppm	4M13F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	BPSK	0.2094	0.0150 ppm	4M14F9W

1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV.
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.9 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.9 + 10 = 14.9 (dB)

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	Apr. 14, 2020	Dec. 07, 2020	Apr. 13, 2021	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 03, 2020	Dec. 07, 2020	Jul. 02, 2021	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 15, 2020	Dec. 10, 2020	Apr. 14, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jan. 03, 2020	Dec. 10, 2020	Jan. 02, 2021	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 20, 2020	Dec. 10, 2020	Apr. 19, 2021	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 09, 2020	Dec. 10, 2020	Nov. 08, 2021	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 03, 2020	Dec. 10, 2020	Jan. 02, 2021	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 08, 2020	Dec. 10, 2020	Jan. 07, 2021	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Jan. 03, 2020	Dec. 10, 2020	Jan. 02, 2021	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 14, 2020	Dec. 10, 2020	Oct. 13, 2021	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Dec. 10, 2020	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 10, 2020	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 10, 2020	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Top Antenna:

Conducted Power (*Unit: dBm)						
Band	**GSM850**			**GSM1900**		
Channel	**128**	**189**	**251**	**512**	**661**	**810**
Frequency	**824.2**	**836.4**	**848.8**	**1850.2**	**1880.0**	**1909.8**
GSM	32.68	32.51	32.22	30.26	30.24	30.45
GPRS 1 Tx slots	32.66	32.50	32.20	30.25	30.43	30.42
GPRS 2 Tx slots	29.53	29.54	29.06	26.65	26.62	26.73
GPRS 3 Tx slots	27.55	27.48	27.25	24.80	24.60	25.00
GPRS 4 Tx slots	25.71	26.08	25.62	23.38	23.26	23.56
EGPRS 1 Tx slots	26.55	26.44	26.11	26.05	25.76	25.87
EGPRS 2 Tx slots	23.41	23.21	23.12	22.59	22.68	22.74
EGPRS 3 Tx slots	21.47	21.42	21.23	21.14	20.78	20.94
EGPRS 4 Tx slots	20.05	19.97	19.56	19.40	19.03	19.32

Conducted Power (*Unit: dBm)									
Band	**WCDMA Band V**			**WCDMA Band II**			**WCDMA Band IV**		
Channel	**4132**	**4182**	**4233**	**9262**	**9400**	**9538**	**1312**	**1413**	**1513**
Frequency	**826.4**	**836.4**	**846.6**	**1852.4**	**1880**	**1907.6**	**1712.4**	**1732.6**	**1752.6**
AMR 12.2K	23.84	23.90	23.82	24.00	23.76	23.75	23.66	23.80	23.70
RMC 12.2K	23.86	23.92	23.83	24.05	24.06	23.76	23.68	23.81	23.72
HSDPA Subtest-1	23.04	23.08	22.98	23.02	22.93	22.93	22.98	22.99	23.05
HSDPA Subtest-2	23.06	23.01	23.02	23.05	22.94	22.94	23.02	23.01	23.07
HSDPA Subtest-3	22.57	22.56	22.50	22.56	22.46	22.44	22.53	22.52	22.58
HSDPA Subtest-4	22.55	22.58	22.50	22.56	22.44	22.43	22.48	22.52	22.56
DC-HSDPA Subtest-1	22.57	22.66	22.54	22.61	22.44	22.48	22.30	22.26	22.28
DC-HSDPA Subtest-2	22.61	22.74	22.57	22.65	22.40	22.53	22.33	22.34	22.26
DC-HSDPA Subtest-3	22.12	22.13	22.08	22.17	21.95	21.98	21.81	21.81	21.77
DC-HSDPA Subtest-4	22.12	22.20	22.07	22.11	21.95	22.02	21.82	21.78	21.79
HSUPA Subtest-1	22.96	23.00	22.97	22.99	22.85	22.89	22.94	22.93	23.01
HSUPA Subtest-2	20.98	20.96	20.94	21.01	20.87	20.87	20.93	20.97	21.01
HSUPA Subtest-3	21.99	21.97	21.99	22.01	21.86	21.90	21.95	21.96	22.03
HSUPA Subtest-4	20.97	20.99	21.00	20.99	20.87	20.87	20.96	20.97	20.99
HSUPA Subtest-5	23.00	23.00	23.00	23.00	22.90	22.90	23.00	23.00	23.00

Bottom Antenna:

Conducted Power (*Unit: dBm)						
Band	**GSM850**			**GSM1900**		
Channel	**128**	**189**	**251**	**512**	**661**	**810**
Frequency	**824.2**	**836.4**	**848.8**	**1850.2**	**1880.0**	**1909.8**
GSM	32.14	31.97	31.68	29.70	29.64	29.55
GPRS 1 Tx slots	32.12	31.96	31.66	29.68	29.70	29.58
GPRS 2 Tx slots	28.78	28.80	28.65	26.41	26.38	26.49
GPRS 3 Tx slots	27.01	26.94	26.87	24.56	24.36	24.76
GPRS 4 Tx slots	25.17	25.54	25.08	23.14	23.02	23.32
EGPRS 1 Tx slots	26.01	25.90	25.57	25.81	25.52	25.63
EGPRS 2 Tx slots	22.87	22.67	22.65	22.35	22.44	22.50
EGPRS 3 Tx slots	20.93	20.88	20.86	20.90	20.54	20.70
EGPRS 4 Tx slots	19.51	19.43	19.02	19.16	18.79	19.08

Conducted Power (*Unit: dBm)									
Band	**WCDMA Band V**			**WCDMA Band II**			**WCDMA Band IV**		
Channel	**4132**	**4182**	**4233**	**9262**	**9400**	**9538**	**1312**	**1413**	**1513**
Frequency	**826.4**	**836.4**	**846.6**	**1852.4**	**1880**	**1907.6**	**1712.4**	**1732.6**	**1752.6**
AMR 12.2K	23.54	23.60	23.52	23.50	23.53	23.25	23.36	23.50	23.40
RMC 12.2K	23.56	23.62	23.53	23.55	23.56	23.26	23.48	23.51	23.46
HSDPA Subtest-1	22.99	23.06	23.06	22.89	22.70	22.67	22.78	22.86	22.94
HSDPA Subtest-2	22.95	23.04	23.06	22.82	22.70	22.63	22.75	22.84	22.85
HSDPA Subtest-3	22.67	22.67	22.76	22.33	22.43	22.21	22.34	22.45	22.43
HSDPA Subtest-4	22.78	22.77	22.87	22.45	22.36	22.32	22.20	22.34	22.45
DC-HSDPA Subtest-1	22.98	23.03	23.04	22.86	22.68	22.66	22.76	22.85	22.91
DC-HSDPA Subtest-2	22.94	23.01	23.04	22.79	22.68	22.62	22.73	22.83	22.82
DC-HSDPA Subtest-3	22.66	22.64	22.74	22.30	22.41	22.20	22.32	22.44	22.40
DC-HSDPA Subtest-4	22.77	22.74	22.85	22.42	22.34	22.31	22.18	22.33	22.42
HSUPA Subtest-1	22.76	22.80	22.79	22.71	22.48	22.44	22.52	22.58	22.65
HSUPA Subtest-2	20.70	20.76	20.84	20.64	20.46	20.44	20.54	20.57	20.61
HSUPA Subtest-3	21.75	21.79	21.79	21.69	21.48	21.46	21.55	21.57	21.69
HSUPA Subtest-4	20.78	20.82	20.79	20.67	20.45	20.43	20.50	20.54	20.67
HSUPA Subtest-5	22.80	22.80	22.80	22.70	22.50	22.50	22.50	22.60	22.60

ERP/EIRP

Top antenna

GSM850 (G_T - L_C= -4.9 dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	32.68	32.51	32.22
Conducted Power (Watts)	1.8535	1.7824	1.6672
ERP(dBm)	25.63	25.46	25.17
ERP(Watts)	0.3656	0.3516	0.3289
EDGE850 (G_T - L_C= -4.9 dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	26.55	26.44	26.11
Conducted Power (Watts)	0.4519	0.4406	0.4083
ERP(dBm)	19.50	19.39	19.06
ERP(Watts)	0.0891	0.0869	0.0805
WCDMA Band V (G_T - L_C = -4.9 dB)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency (MHz)	826.4	836.4	846.6
Conducted Power (dBm)	23.86	23.92	23.83
Conducted Power (Watts)	0.2432	0.2466	0.2415
ERP(dBm)	16.81	16.87	16.78
ERP(Watts)	0.0480	0.0486	0.0476

GSM1900 (G_T - L_C= -1.9 dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	30.26	30.24	30.45
Conducted Power (Watts)	1.0617	1.0568	1.1092
EIRP(dBm)	28.36	28.34	28.55
EIRP(Watts)	0.6855	0.6823	0.7161
EDGE1900 (G_T - L_C= -1.9 dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	26.05	25.76	25.87
Conducted Power (Watts)	0.4027	0.3767	0.3864
EIRP(dBm)	24.15	23.86	23.97
EIRP(Watts)	0.2600	0.2432	0.2495
WCDMA Band IV (G_T - L_C = -0.6 dB)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	23.68	23.81	23.72
Conducted Power (Watts)	0.2333	0.2404	0.2355
EIRP(dBm)	23.08	23.21	23.12
EIRP(Watts)	0.2032	0.2094	0.2051

WCDMA Band II (G_T - L_C = -1.9 dB)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency (MHz)	1852.4	1880	1907.6
Conducted Power (dBm)	24.05	24.06	23.76
Conducted Power (Watts)	0.2541	0.2547	0.2377
EIRP(dBm)	22.15	22.16	21.86
EIRP(Watts)	0.1641	0.1644	0.1535

GSM

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.17	3.42	PASS
Middle CH	0.12	3.33	
Highest CH	0.12	3.13	

Mode	GSM1900		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	0.20	PASS
Middle CH	0.12	0.17	
Highest CH	0.12	0.20	

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

26dB Bandwidth

Mode	GSM850	
Mod.	GSM	EDGE class 8
Lowest CH	0.3127	0.3157
Middle CH	0.3177	0.3137
Highest CH	0.3167	0.3147

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.3157	0.3107
Middle CH	0.3167	0.3167
Highest CH	0.3107	0.3057

GSM850 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM850 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**





Middle Channel	Middle Channel





Highest Channel	Highest Channel





Occupied Bandwidth

Mode	GSM850	
Mod.	GSM	EDGE class 8
Lowest CH	0.2418	0.2448
Middle CH	0.2438	0.2438
Highest CH	0.2428	0.2428

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.2438	0.2498
Middle CH	0.2428	0.2468
Highest CH	0.2428	0.2458

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

Conducted Band Edge

GSM850 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.43207 MHz	-47.62 dBm	-34.62 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99701 MHz	-16.69 dBm	-3.69 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.26697 MHz	23.76 dBm	-11.24 dB

Date: 7.DEC.2020 11:53:40

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.78293 MHz	21.78 dBm	-13.22 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.02295 MHz	-16.39 dBm	-3.39 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.51199 MHz	-47.48 dBm	-34.48 dB

Date: 7.DEC.2020 11:55:13

GSM850 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.43207 MHz	-50.61 dBm	-37.61 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99701 MHz	-25.83 dBm	-12.83 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.22006 MHz	16.62 dBm	-18.38 dB

Date: 7.DEC.2020 13:51:02

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.85978 MHz	16.33 dBm	-18.67 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.00898 MHz	-26.91 dBm	-13.91 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.54695 MHz	-50.21 dBm	-37.21 dB

Date: 7.DEC.2020 13:52:35

GSM1900 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84896 GHz	-38.83 dBm	-25.83 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.85000 GHz	-19.26 dBm	-6.26 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85027 GHz	22.59 dBm	-12.41 dB

Date: 7.DEC.2020 14:14:57

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90987 GHz	23.55 dBm	-11.45 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-21.00 dBm	-8.00 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91108 GHz	-38.99 dBm	-25.99 dB

Date: 7.DEC.2020 14:16:34

GSM1900 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84898 GHz	-41.11 dBm	-28.11 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.84999 GHz	-27.66 dBm	-14.66 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85022 GHz	17.46 dBm	-17.54 dB

Date: 7.DEC.2020 15:15:25

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90980 GHz	17.76 dBm	-17.24 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91001 GHz	-26.91 dBm	-13.91 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91101 GHz	-40.76 dBm	-27.76 dB

Date: 7.DEC.2020 15:16:58

Conducted Spurious Emission

GSM850 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	764.92504 MHz	-37.64 dBm	-24.64 dB
855.000 MHz	1.000 GHz	1.000 MHz	899.45652 MHz	-36.65 dBm	-23.65 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.90889 GHz	-36.64 dBm	-23.64 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.74478 GHz	-32.66 dBm	-19.66 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.23147 GHz	-34.27 dBm	-21.27 dB

Date: 7.DEC.2020 12:02:48

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	585.68466 MHz	-36.98 dBm	-23.98 dB
855.000 MHz	1.000 GHz	1.000 MHz	989.38406 MHz	-37.01 dBm	-24.01 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.67279 GHz	-33.51 dBm	-20.51 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.66329 GHz	-32.90 dBm	-19.90 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.87014 GHz	-33.60 dBm	-20.60 dB

Date: 7.DEC.2020 12:04:22

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	164.43028 MHz	-36.92 dBm	-23.92 dB
855.000 MHz	1.000 GHz	1.000 MHz	906.84783 MHz	-36.42 dBm	-23.42 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.69754 GHz	-33.18 dBm	-20.18 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.24484 GHz	-32.35 dBm	-19.35 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.12798 GHz	-35.19 dBm	-22.19 dB

Date: 7.DEC.2020 12:05:43

GSM850 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	43.22589 MHz	-37.73 dBm	-24.73 dB
855.000 MHz	1.000 GHz	1.000 MHz	935.54348 MHz	-36.52 dBm	-23.52 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.70279 GHz	-36.56 dBm	-23.56 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.94576 GHz	-32.26 dBm	-19.26 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.80390 GHz	-34.44 dBm	-21.44 dB

Date: 7.DEC.2020 13:54:02

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	59.41279 MHz	-36.97 dBm	-23.97 dB
855.000 MHz	1.000 GHz	1.000 MHz	960.03623 MHz	-36.57 dBm	-23.57 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.89164 GHz	-37.53 dBm	-24.53 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.52431 GHz	-32.63 dBm	-19.63 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.81565 GHz	-35.66 dBm	-22.66 dB

Date: 7.DEC.2020 13:55:42

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	810.72214 MHz	-36.98 dBm	-23.98 dB
855.000 MHz	1.000 GHz	1.000 MHz	900.47101 MHz	-37.37 dBm	-24.37 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.93663 GHz	-36.07 dBm	-23.07 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.47682 GHz	-32.22 dBm	-19.22 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.00575 GHz	-35.77 dBm	-22.77 dB

Date: 7.DEC.2020 13:57:21

GSM1900 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	552.32634 MHz	-36.91 dBm	-23.91 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.50907 GHz	-37.63 dBm	-24.63 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.78933 GHz	-36.59 dBm	-23.59 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.94476 GHz	-30.91 dBm	-17.91 dB
7.000 GHz	13.600 GHz	1.000 MHz	11.25646 GHz	-33.82 dBm	-20.82 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.33575 GHz	-31.13 dBm	-18.13 dB

Date: 7.DEC.2020 14:18:01

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	913.95552 MHz	-36.63 dBm	-23.63 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.66278 GHz	-38.33 dBm	-25.33 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.16513 GHz	-36.06 dBm	-23.06 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.66829 GHz	-31.54 dBm	-18.54 dB
7.000 GHz	13.600 GHz	1.000 MHz	9.12293 GHz	-34.99 dBm	-21.99 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.31847 GHz	-31.77 dBm	-18.77 dB

Date: 7.DEC.2020 14:19:55

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	667.21389 MHz	-36.80 dBm	-23.80 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.74048 GHz	-37.65 dBm	-24.65 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.93945 GHz	-34.65 dBm	-21.65 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.42732 GHz	-32.31 dBm	-19.31 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.34255 GHz	-35.42 dBm	-22.42 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.31532 GHz	-31.23 dBm	-18.23 dB

Date: 7.DEC.2020 14:21:17

GSM1900 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	523.72564 MHz	-36.37 dBm	-23.37 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.32917 GHz	-36.91 dBm	-23.91 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.13557 GHz	-35.94 dBm	-22.94 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.85939 GHz	-32.63 dBm	-19.63 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.39488 GHz	-35.44 dBm	-22.44 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.28115 GHz	-32.46 dBm	-19.46 dB

Date: 7.DEC.2020 15:18:26

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	893.59570 MHz	-36.48 dBm	-23.48 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.62604 GHz	-37.99 dBm	-24.99 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.81334 GHz	-36.46 dBm	-23.46 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.60580 GHz	-32.00 dBm	-19.00 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.80782 GHz	-35.33 dBm	-22.33 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.26740 GHz	-32.61 dBm	-19.61 dB

Date: 7.DEC.2020 15:19:49

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	931.40680 MHz	-36.05 dBm	-23.05 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.68474 GHz	-37.45 dBm	-24.45 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.87585 GHz	-36.87 dBm	-23.87 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.83777 GHz	-31.45 dBm	-18.45 dB
7.000 GHz	13.600 GHz	1.000 MHz	9.85359 GHz	-34.99 dBm	-21.99 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.34321 GHz	-33.06 dBm	-20.06 dB

Date: 7.DEC.2020 15:21:17

Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0191	0.0233	PASS
40	Normal Voltage	0.0126	0.0172	
30	Normal Voltage	0.0133	0.0032	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0145	0.0153	
0	Normal Voltage	0.0078	0.0166	
-10	Normal Voltage	0.0175	0.0234	
-20	Normal Voltage	0.0152	0.0061	
-30	Normal Voltage	0.0141	0.0109	
20	Maximum Voltage	0.0090	0.0182	
20	Normal Voltage	0.0328	0.0204	
20	Battery End Point	0.0106	0.0025	

Note: Normal Voltage = 3.87V. ; Battery End Point (BEP) =3.6V. ; Maximum Voltage =4.45 V

Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0121	0.0024	PASS
40	Normal Voltage	0.0013	0.0134	
30	Normal Voltage	0.0116	0.0025	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0146	0.0116	
0	Normal Voltage	0.0136	0.0135	
-10	Normal Voltage	0.0089	0.0174	
-20	Normal Voltage	0.0021	0.0127	
-30	Normal Voltage	0.0118	0.0113	
20	Maximum Voltage	0.0052	0.0014	
20	Normal Voltage	0.0011	0.0131	
20	Battery End Point	0.0054	0.0182	

Note:

1. Normal Voltage = 3.87V. ; Battery End Point (BEP) =3.6V. ; Maximum Voltage =4.45 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.01	3.33	3.16	PASS
Middle CH	3.04	3.36	3.33	
Highest CH	3.01	3.13	3.22	

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



26dB Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.705	4.695	4.695
Middle CH	4.735	4.695	4.695
Highest CH	4.725	4.705	4.685

WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band II (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel