



RF TEST REPORT

Applicant Xiaomi Communications Co., Ltd.
FCC ID 2AFZZN91Y
Product Mobile Phone
Brand Redmi
Model 22126RN91Y
Report No. R2209A0810-R1
Issue Date November 21, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2021)/ FCC CFR 47 Part 22H (2021)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Xu Ying

Approved by: Xu Kai

TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the Test Report	4
1.2. Test facility	4
1.3. Testing Location	4
2. General Description of Equipment under Test	5
2.1. Applicant and Manufacturer Information	5
2.2. General Information	5
3. Applied Standards	7
4. Test Configuration	8
5. Test Case	10
5.1. RF Power Output and Effective Radiated Power	10
5.2. Occupied Bandwidth	11
5.3. Band Edge Compliance	12
5.4. Peak-to-Average Power Ratio (PAPR)	13
5.5. Frequency Stability	14
5.6. Spurious Emissions at Antenna Terminals	16
5.7. Radiated Spurious Emission	17
6. Test Result	20
6.1. RF Power Output and Effective Radiated Power	20
6.2. Occupied Bandwidth	27
6.3. Band Edge Compliance	37
6.4. Peak-to-Average Power Ratio (PAPR)	47
6.5. Frequency Stability	49
6.6. Spurious Emissions at Antenna Terminals	52
6.7. Radiated Spurious Emission	56
7. Main Test Instruments	62
ANNEX A: The EUT Appearance	63
ANNEX B: Test Setup Photos	64
ANNEX C: Product Change Description	66

Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Radiated Power	2.1046 22.913(a)(5)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	2.1051 / 22.917(a)	PASS
4	Peak-to-Average Power Ratio	22.913(d) KDB 971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 22.355	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
7	Radiated Spurious Emission	2.1053 / 22.917 (a)	PASS

Date of Testing: October 11, 2022 ~ October 24, 2022

Date of Sample Received: October 8, 2022

Note: PASS: The EUT complies with the essential requirements in the standard.

FAIL: The EUT does not comply with the essential requirements in the standard.

All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.

22126RN91Y (Report No.: R2209A0810-R1) is a variant model of 2212ARNC4L (Report No.: R2209A0813-R1). There is only test Radiated Spurious Emission (GSM850 and WCDMA Band V for Upper antenna; GSM850 and WCDMA Band V for Low Antenna). Radiated Spurious Emission did not worsen, so they were not recorded in the report.

The detailed product change description please refers to the Difference Declaration Letter.



1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	Xiaomi Communications Co., Ltd.
Applicant address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer	Xiaomi Communications Co., Ltd.
Manufacturer address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

2.2. General Information

EUT Description			
Model	22126RN91Y		
IMEI	Original (2212ARNC4L)	IMEI 1: 861591060034168 IMEI 2: 861591060034176	
	Variant (22126RN91Y)	IMEI 1: 867932060030141 IMEI 2: 867932060030158	
Hardware Version	P1.1		
Software Version	MIUI 13		
Antenna Type	PIFA Antenna		
Antenna Gain	Band	Low Antenna	Upper Antenna
	GSM 850	-3.3 dBi	-2.9 dBi
	WCDMA Band V	-3.3 dBi	-2.9 dBi
	LTE Band 5	-3.3 dBi	-2.9 dBi
Test Mode(s)	GSM 850; WCDMA Band V; LTE Band 5;		
Test Modulation	(GSM/GPRS)GMSK, (EGPRS) GMSK/ 8PSK; (WCDMA) BPSK, QPSK; (LTE) QPSK, 16QAM, 64QAM;		
GPRS Multislot Class	12		
EGPRS Multislot Class	12		
HSDPA UE Category	4		
HSUPA UE Category	5		
LTE Category	5		
Maximum E.R.P.	GSM 850:	27.46 dBm	
	WCDMA Band V:	18.13 dBm	
	LTE Band 5:	18.55 dBm	
Rated Power Supply Voltage	3.85V		
Operating Voltage	Minimum: 3.65V Maximum: 4.20V		
Operating Temperature	Lowest: 0°C Highest: +40°C		



Testing Temperature	Lowest: -30°C Highest: +50°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 5	824 ~ 849	869 ~ 894
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant. 2. Low antenna and Upper antenna can't transmit simultaneously.			



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR 47 Part 22H (2021)

FCC CFR47 Part 2 (2021)

Reference standard:

ANSI C63.26-2015

KDB 971168 D01 Power Meas License Digital Systems v03r01

4. Test Configuration

There is more than one SIM card slot, each one should be applied throughout the compliance test respectively, and however, only the worst case (SIM 1) will be recorded in this report.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, vertical polarization for Upper Antenna GSM/WCDMA/LTE Band; X axis, horizontal polarization for Low Antenna GSM/WCDMA Band; X axis, vertical polarization for Low Antenna LTE Band) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated.

Subsequently, only the worst case emissions are reported.

The following testing in GSM/WCDMA/LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

Test items	Modes/Modulation	
	GSM 850	WCDMA Band V
RF Power Output and Effective Radiated power	GSM GPRS EGPRS	RMC/ AMR HSDPA/HSUPA DC-HSDPA
Occupied Bandwidth	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Band Edge Compliance	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Peak-to-Average Power Ratio	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Frequency Stability	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Spurious Emissions at Antenna Terminals	GSM	RMC
Radiated Spurious Emission	GSM	RMC

Test modes are chosen as the worst case configuration below for LTE Band 5

Test items	Modes	Bandwidth (MHz)					Modulation		RB			Test Channel		
		1.4	3	5	10	15	QPSK	16QAM/ 64QAM	1	50%	100%	L	M	H
RF power output and Effective Radiated power	LTE 5	O	O	O	O	-	O	O	O	O	O	O	O	O
Occupied Bandwidth	LTE 5	O	O	O	O	-	O	O	-	-	O	O	O	O
Band Edge Compliance	LTE 5	O	O	O	O	-	O	O	O	-	O	O	-	O
Peak-to-Average Power Ratio	LTE 5	O	O	O	O	-	O	O	-	-	O	O	O	O
Frequency Stability	LTE 5	O	O	O	O	-	O	O	O	-	-	-	O	-
Spurious Emissions at Antenna Terminals	LTE 5	O	O	O	O	-	O	-	O	-	-	O	O	O
Radiated Spurious Emission	LTE 5	O	-	O	O	-	O	-	O	-	-	-	O	-
Note	1. The mark "O" means that this configuration is chosen for testing. 2. The mark "-" means that this configuration is not testing.													

5. Test Case

5.1. RF Power Output and Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.


ERP can then be calculated as follows:

EIRP (dBm) = Output Power (dBm) + Antenna Gain (dBi)

where: dBd refers to gain relative to an ideal dipole.

EIRP (dBm) = ERP (dBm) + 2.15 (dB).

Test Setup



Limits

No specific RF power output requirements in part 2.1046.

Rule Part 22.913(a)(5) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	$\leq 7 \text{ W}$ (38.45 dBm)
-------	--------------------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4 \text{ dB}$ for RF power output, $k = 2$, $U = 1.19 \text{ dB}$ for ERP.

Test Results

Refer to the section 6.1 of this report for test data.

5.2. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to $\geq 1\%EBW$, VBW is set to 3x RBW.

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.

Test Results

Refer to the section 6.2 of this report for test data.

5.3. Band Edge Compliance

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used. RBW is set to $\geq 1\%EBW$, VBW is set to 3x RBW.

Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684\text{dB}$.

Test Results

Refer to the section 6.3 of this report for test data.

5.4. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk} . And measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.

Test Results

Refer to the section 6.4 of this report for test data.

5.5. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.


(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements. Frequency Stability (Voltage Variation)

The frequency stability shall be measured with variation of primary supply voltage as follows:

Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.65 V and 4.20 V, with a nominal voltage of 3.85V.

Test setup



Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm
--------	-----------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.



Test Results

Refer to the section 6.5 of this report for test data.

5.6. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier.

The peak detector is used.

RBW is set to 1 kHz (0.009MHz~ 0.15 MHz),

RBW is set to 10 kHz (0.15 MHz~ 30 MHz)


RBW is set to 100 kHz (30MHz~1000 MHz)

RBW is set to 1000 kHz (above 1000MHz)

Sweep is set to ATUO.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-20GHz	1.407 dB

Test Results

Refer to the section 6.6 of this report for test data.

5.7. Radiated Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26-2015.
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=100kHz, VBW=300kHz, and the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$


The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dB) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP

= EIRP-2.15dB.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz~ 30MHz



30MHz~ 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ Db.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ Db.

Test Results

Refer to the section 6.7 of this report for test data.

6. Test Result

6.1. RF Power Output and Effective Radiated Power

GSM850 Low Antenna		Maximum Output Power (dBm)			ERP (dBm)		
		Channel/Frequency(MHz)			Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8	128/824.2	190/836.6	251/848.8
GSM	CS	31.73	31.78	31.66	26.28	26.33	26.21
GPRS/EGPRS (GMSK)	1 Tx Slot	31.79	31.74	31.72	26.34	26.29	26.27
	2 Tx Slots	29.47	29.39	29.40	24.02	23.94	23.95
	3 Tx Slots	26.42	26.32	26.29	20.97	20.87	20.84
	4 Tx Slots	25.48	25.36	25.36	20.03	19.91	19.91
EGPRS (8PSK)	1 Tx Slot	26.61	26.89	26.37	21.16	21.44	20.92
	2 Tx Slots	22.94	23.06	22.91	17.49	17.61	17.46
	3 Tx Slots	20.07	20.17	19.86	14.62	14.72	14.41
	4 Tx Slots	18.64	18.54	18.47	13.19	13.09	13.02

GSM850 Upper Antenna		Maximum Output Power (dBm)			ERP (dBm)		
		Channel/Frequency(MHz)			Channel/Frequency(MHz)		
		128/824.2	190/836.6	251/848.8	128/824.2	190/836.6	251/848.8
GSM	CS	32.51	32.45	32.31	27.46	27.40	27.26
GPRS/EGPRS (GMSK)	1 Tx Slot	32.50	32.45	32.30	27.45	27.40	27.25
	2 Tx Slots	30.14	30.08	29.96	25.09	25.03	24.91
	3 Tx Slots	27.04	26.97	26.81	21.99	21.92	21.76
	4 Tx Slots	26.08	26.00	25.87	21.03	20.95	20.82
EGPRS (8PSK)	1 Tx Slot	26.34	27.07	26.65	21.29	22.02	21.60
	2 Tx Slots	23.11	23.43	23.38	18.06	18.38	18.33
	3 Tx Slots	20.39	20.09	19.93	15.34	15.04	14.88
	4 Tx Slots	19.32	18.99	18.93	14.27	13.94	13.88



WCDMA Band V Low Antenna		Maximum Output Power (dBm)			ERP (dBm)		
		Channel/Frequency(MHz)			Channel/Frequency(MHz)		
		4132/826.4	4183/836.6	4233/846.6	4132/826.4	4183/836.6	4233/846.6
RMC	12.2k	23.19	23.18	23.13	17.74	17.73	17.68
AMR	12.2k	23.11	23.06	23.13	17.66	17.61	17.68
HSDPA	Subtest 1	22.03	22.16	22.03	16.58	16.71	16.58
	Subtest 2	22.07	22.06	21.99	16.62	16.61	16.54
	Subtest 3	21.83	21.56	21.57	16.38	16.11	16.12
	Subtest 4	21.81	21.72	21.69	16.36	16.27	16.24
HSUPA	Subtest 1	20.35	20.12	20.29	14.90	14.67	14.84
	Subtest 2	20.31	20.34	19.97	14.86	14.89	14.52
	Subtest 3	21.03	21.06	21.03	15.58	15.61	15.58
	Subtest 4	19.67	19.84	19.67	14.22	14.39	14.22
	Subtest 5	21.03	21.16	21.09	15.58	15.71	15.64
DC-HSDPA	Subtest 1	22.11	22.10	22.05	16.66	16.65	16.60
	Subtest 2	22.19	22.12	22.17	16.74	16.67	16.72
	Subtest 3	21.67	21.54	21.59	16.22	16.09	16.14
	Subtest 4	21.69	21.64	21.47	16.24	16.19	16.02

WCDMA Band V Upper Antenna		Maximum Output Power (dBm)			ERP (dBm)		
		Channel/Frequency(MHz)			Channel/Frequency(MHz)		
		4132/826.4	4183/836.6	4233/846.6	4132/826.4	4183/836.6	4233/846.6
RMC	12.2k	23.01	23.06	23.02	17.96	18.01	17.97
AMR	12.2k	23.07	23.18	23.01	18.02	18.13	17.96
HSDPA	Subtest 1	21.85	22.14	21.96	16.80	17.09	16.91
	Subtest 2	21.93	22.22	22.02	16.88	17.17	16.97
	Subtest 3	21.43	21.66	21.40	16.38	16.61	16.35
	Subtest 4	21.59	21.54	21.48	16.54	16.49	16.43
HSUPA	Subtest 1	20.07	20.06	20.03	15.02	15.01	14.98
	Subtest 2	19.91	20.02	19.98	14.86	14.97	14.93
	Subtest 3	21.03	21.18	21.14	15.98	16.13	16.09
	Subtest 4	19.45	19.64	19.46	14.40	14.59	14.41
	Subtest 5	21.15	21.14	20.88	16.10	16.09	15.83
DC-HSDPA	Subtest 1	21.99	21.90	22.06	16.94	16.85	17.01
	Subtest 2	21.93	22.14	22.12	16.88	17.09	17.07
	Subtest 3	21.41	21.56	21.58	16.36	16.51	16.53
	Subtest 4	21.53	21.66	21.64	16.48	16.61	16.59



LTE Band 5 Low Antenna				Maximum Output Power (dBm)			ERP (dBm)		
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				20407/ 824.7	20525/ 836.5	20643/ 848.3	20407/ 824.7	20525/ 836.5	20643/ 848.3
1.4MHz	QPSK	1	0	23.60	23.65	23.60	18.15	18.20	18.15
		1	2	23.74	23.71	23.68	18.29	18.26	18.23
		1	5	23.62	23.58	23.55	18.17	18.13	18.10
		3	0	23.72	23.68	23.73	18.27	18.23	18.28
		3	2	23.66	23.69	23.67	18.21	18.24	18.22
		3	3	23.65	23.59	23.59	18.2	18.14	18.14
		6	0	22.77	22.71	22.73	17.32	17.26	17.28
	16QAM	1	0	22.85	22.95	22.92	17.40	17.50	17.47
		1	2	22.98	23.04	22.97	17.53	17.59	17.52
		1	5	22.95	22.91	22.79	17.5	17.46	17.34
		3	0	22.68	22.61	22.66	17.23	17.16	17.21
		3	2	22.66	22.65	22.65	17.21	17.20	17.20
		3	3	22.63	22.63	22.50	17.18	17.18	17.05
		6	0	21.75	21.73	21.74	16.30	16.28	16.29
	64QAM	1	0	21.78	21.80	21.82	16.33	16.35	16.37
		1	2	21.91	21.94	21.88	16.46	16.49	16.43
		1	5	21.83	21.87	21.74	16.38	16.42	16.29
		3	0	21.66	21.62	21.65	16.21	16.17	16.20
		3	2	21.66	21.62	21.62	16.21	16.17	16.17
		3	3	21.63	21.63	21.55	16.18	16.18	16.10
		6	0	20.76	20.71	20.74	15.31	15.26	15.29
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				20415/ 825.5	20525/ 836.5	20635/ 847.5	20415/ 825.5	20525/ 836.5	20635/ 847.5
3MHz	QPSK	1	0	23.59	23.67	23.59	18.14	18.22	18.14
		1	7	23.70	23.70	23.69	18.25	18.25	18.24
		1	14	23.62	23.58	23.55	18.17	18.13	18.10
		8	0	22.79	22.75	22.82	17.34	17.30	17.37
		8	4	22.76	22.75	22.74	17.31	17.30	17.29
		8	7	22.73	22.68	22.65	17.28	17.23	17.20
		15	0	22.77	22.74	22.74	17.32	17.29	17.29
	16QAM	1	0	22.85	22.93	22.92	17.40	17.48	17.47
		1	7	22.98	23.02	22.98	17.53	17.57	17.53
		1	14	22.94	22.93	22.78	17.49	17.48	17.33
		8	0	21.77	21.70	21.75	16.32	16.25	16.30
		8	4	21.74	21.73	21.73	16.29	16.28	16.28
		8	7	21.70	21.70	21.59	16.25	16.25	16.14
		15	0	21.76	21.73	21.72	16.31	16.28	16.27



	64QAM	1	0	21.78	21.82	21.82	16.33	16.37	16.37
		1	7	21.91	21.96	21.87	16.46	16.51	16.42
		1	14	21.86	21.84	21.73	16.41	16.39	16.28
		8	0	20.75	20.71	20.78	15.3	15.26	15.33
		8	4	20.74	20.70	20.70	15.29	15.25	15.25
		8	7	20.70	20.70	20.64	15.25	15.25	15.19
		15	0	20.77	20.71	20.72	15.32	15.26	15.27
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				20425/ 826.5	20525/ 836.5	20625/ 846.5	20425/ 826.5	20525/ 836.5	20625/ 846.5
5MHz	QPSK	1	0	23.60	23.64	23.60	18.15	18.19	18.15
		1	13	23.71	23.74	23.70	18.26	18.29	18.25
		1	24	23.61	23.57	23.54	18.16	18.12	18.09
		12	0	22.80	22.76	22.83	17.35	17.31	17.38
		12	6	22.76	22.75	22.74	17.31	17.3	17.29
		12	13	22.72	22.69	22.66	17.27	17.24	17.21
		25	0	22.79	22.72	22.73	17.34	17.27	17.28
	16QAM	1	0	22.87	22.94	22.92	17.42	17.49	17.47
		1	13	23.00	23.03	22.99	17.55	17.58	17.54
		1	24	22.95	22.91	22.78	17.50	17.46	17.33
		12	0	21.77	21.73	21.76	16.32	16.28	16.31
		12	6	21.73	21.72	21.72	16.28	16.27	16.27
		12	13	21.71	21.71	21.60	16.26	16.26	16.15
		25	0	21.76	21.73	21.72	16.31	16.28	16.27
	64QAM	1	0	21.75	21.79	21.82	16.3	16.34	16.37
		1	13	21.92	21.93	21.88	16.47	16.48	16.43
		1	24	21.86	21.85	21.77	16.41	16.40	16.32
		12	0	20.77	20.78	20.79	15.32	15.33	15.34
		12	6	20.74	20.71	20.72	15.29	15.26	15.27
		12	13	20.71	20.71	20.65	15.26	15.26	15.20
		25	0	20.77	20.71	20.72	15.32	15.26	15.27
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				20450/ 829	20525/ 836.5	20600/ 844	20450/ 829	20525/ 836.5	20600/ 844
10MHz	QPSK	1	0	23.57	23.60	23.57	18.12	18.15	18.12
		1	25	23.70	23.70	23.68	18.25	18.25	18.23
		1	49	23.59	23.56	23.51	18.14	18.11	18.06
		25	0	22.77	22.71	22.79	17.32	17.26	17.34
		25	13	22.74	22.71	22.71	17.29	17.26	17.26
		25	25	22.69	22.64	22.62	17.24	17.19	17.17
		50	0	22.76	22.67	22.69	17.31	17.22	17.24
	16QAM	1	0	22.84	22.90	22.87	17.39	17.45	17.42
		1	25	22.97	23.01	22.95	17.52	17.56	17.50



		1	49	22.92	22.88	22.76	17.47	17.43	17.31
		25	0	21.74	21.69	21.73	16.29	16.24	16.28
		25	13	21.70	21.70	21.69	16.25	16.25	16.24
		25	25	21.68	21.66	21.56	16.23	16.21	16.11
		50	0	21.74	21.69	21.69	16.29	16.24	16.24
	64QAM	1	0	21.73	21.75	21.77	16.28	16.3	16.32
		1	25	21.88	21.91	21.84	16.43	16.46	16.39
		1	49	21.80	21.79	21.71	16.35	16.34	16.26
		25	0	20.72	20.70	20.72	15.27	15.25	15.27
		25	13	20.70	20.67	20.66	15.25	15.22	15.21
		25	25	20.68	20.66	20.61	15.23	15.21	15.16
		50	0	20.75	20.67	20.69	15.30	15.22	15.24

LTE Band 5 Upper Antenna				Maximum Output Power (dBm)			ERP (dBm)		
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				20407/ 824.7	20525/ 836.5	20643/ 848.3	20407/ 824.7	20525/ 836.5	20643/ 848.3
1.4MHz	QPSK	1	0	23.38	23.44	23.40	18.33	18.39	18.35
		1	2	23.57	23.56	23.48	18.52	18.51	18.43
		1	5	23.47	23.41	23.43	18.42	18.36	18.38
		3	0	23.53	23.53	23.53	18.48	18.48	18.48
		3	2	23.49	23.52	23.49	18.44	18.47	18.44
		3	3	23.46	23.48	23.41	18.41	18.43	18.36
		6	0	22.59	22.59	22.55	17.54	17.54	17.50
	16QAM	1	0	22.69	22.77	22.77	17.64	17.72	17.72
		1	2	22.88	22.87	22.84	17.83	17.82	17.79
		1	5	22.79	22.76	22.71	17.74	17.71	17.66
		3	0	22.53	22.47	22.48	17.48	17.42	17.43
		3	2	22.47	22.49	22.50	17.42	17.44	17.45
		3	3	22.43	22.48	22.34	17.38	17.43	17.29
		6	0	21.58	21.56	21.55	16.53	16.51	16.50
	64QAM	1	0	21.63	21.61	21.57	16.58	16.56	16.52
		1	2	21.78	21.71	21.65	16.73	16.66	16.60
		1	5	21.61	21.67	21.56	16.56	16.62	16.51
		3	0	21.50	21.46	21.47	16.45	16.41	16.42
		3	2	21.46	21.46	21.49	16.41	16.41	16.44
		3	3	21.42	21.47	21.38	16.37	16.42	16.33
		6	0	20.54	20.58	20.54	15.49	15.53	15.49
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				20415/ 825.5	20525/ 836.5	20635/ 847.5	20415/ 825.5	20525/ 836.5	20635/ 847.5
3MHz	QPSK	1	0	23.39	23.47	23.42	18.34	18.42	18.37
		1	7	23.56	23.60	23.53	18.51	18.55	18.48



		1	14	23.49	23.45	23.46	18.44	18.40	18.41
		8	0	22.63	22.65	22.66	17.58	17.60	17.61
		8	4	22.62	22.63	22.60	17.57	17.58	17.55
		8	7	22.56	22.61	22.52	17.51	17.56	17.47
		15	0	22.63	22.64	22.60	17.58	17.59	17.55
	16QAM	1	0	22.73	22.78	22.79	17.68	17.73	17.74
		1	7	22.92	22.89	22.88	17.87	17.84	17.83
		1	14	22.81	22.80	22.73	17.76	17.75	17.68
		8	0	21.65	21.61	21.61	16.60	16.56	16.56
		8	4	21.57	21.61	21.61	16.52	16.56	16.56
		8	7	21.53	21.60	21.47	16.48	16.55	16.42
		15	0	21.62	21.61	21.57	16.57	16.56	16.52
	64QAM	1	0	21.65	21.62	21.59	16.60	16.57	16.54
		1	7	21.81	21.73	21.67	16.76	16.68	16.62
		1	14	21.63	21.66	21.58	16.58	16.61	16.53
		8	0	20.62	20.60	20.60	15.57	15.55	15.55
		8	4	20.56	20.58	20.60	15.51	15.53	15.55
		8	7	20.52	20.59	20.51	15.47	15.54	15.46
		15	0	20.58	20.63	20.56	15.53	15.58	15.51
Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				20425/ 826.5	20525/ 836.5	20625/ 846.5	20425/ 826.5	20525/ 836.5	20625/ 846.5
5MHz	QPSK	1	0	23.38	23.43	23.40	18.33	18.38	18.35
		1	13	23.54	23.59	23.50	18.49	18.54	18.45
		1	24	23.46	23.40	23.42	18.41	18.35	18.37
		12	0	22.61	22.61	22.63	17.56	17.56	17.58
		12	6	22.59	22.58	22.56	17.54	17.53	17.51
		12	13	22.53	22.58	22.48	17.48	17.53	17.43
		25	0	22.61	22.60	22.55	17.56	17.55	17.50
	16QAM	1	0	22.71	22.76	22.77	17.66	17.71	17.72
		1	13	22.90	22.86	22.86	17.85	17.81	17.81
		1	24	22.79	22.76	22.70	17.74	17.71	17.65
		12	0	21.62	21.59	21.58	16.57	16.54	16.53
		12	6	21.54	21.56	21.57	16.49	16.51	16.52
		12	13	21.51	21.56	21.44	16.46	16.51	16.39
		25	0	21.59	21.56	21.53	16.54	16.51	16.48
	64QAM	1	0	21.60	21.60	21.57	16.55	16.55	16.52
		1	13	21.79	21.70	21.65	16.74	16.65	16.60
		1	24	21.64	21.65	21.59	16.59	16.60	16.54
		12	0	20.61	20.62	20.61	15.56	15.57	15.56
		12	6	20.54	20.55	20.59	15.49	15.50	15.54
		12	13	20.50	20.55	20.48	15.45	15.50	15.43
		25	0	20.55	20.58	20.52	15.50	15.53	15.47



Bandwidth	Modulation	RB allocation	offset	Channel/Frequency(MHz)			Channel/Frequency(MHz)		
				20450/ 829	20525/ 836.5	20600/ 844	20450/ 829	20525/ 836.5	20600/ 844
10MHz	QPSK	1	0	23.35	23.39	23.37	18.30	18.34	18.32
		1	25	23.55	23.55	23.48	18.50	18.50	18.43
		1	49	23.44	23.39	23.39	18.39	18.34	18.34
		25	0	22.60	22.56	22.59	17.55	17.51	17.54
		25	13	22.57	22.54	22.53	17.52	17.49	17.48
		25	25	22.50	22.53	22.44	17.45	17.48	17.39
		50	0	22.58	22.55	22.51	17.53	17.50	17.46
	16QAM	1	0	22.68	22.72	22.72	17.63	17.67	17.67
		1	25	22.87	22.84	22.82	17.82	17.79	17.77
		1	49	22.76	22.73	22.68	17.71	17.68	17.63
		25	0	21.59	21.55	21.55	16.54	16.50	16.50
		25	13	21.51	21.54	21.54	16.46	16.49	16.49
		25	25	21.48	21.51	21.40	16.43	16.46	16.35
		50	0	21.57	21.52	21.50	16.52	16.47	16.45
	64QAM	1	0	21.58	21.56	21.52	16.53	16.51	16.47
		1	25	21.75	21.68	21.61	16.70	16.63	16.56
		1	49	21.58	21.59	21.53	16.53	16.54	16.48
		25	0	20.56	20.54	20.54	15.51	15.49	15.49
		25	13	20.50	20.51	20.53	15.45	15.46	15.48
		25	25	20.47	20.50	20.44	15.42	15.45	15.39
		50	0	20.53	20.54	20.49	15.48	15.49	15.44

6.2. Occupied Bandwidth

Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
GSM 850 (GMSK)	128	824.2	0.2463	0.3042
	190	836.6	0.2481	0.3130
	251	848.8	0.2484	0.3068
GPRS 850 (GMSK)	128	824.2	0.2511	0.3174
	190	836.6	0.2444	0.3145
	251	848.8	0.2479	0.3137
EGPRS 850 (8PSK)	128	824.2	0.2461	0.3140
	190	836.6	0.2517	0.3029
	251	848.8	0.2444	0.3105


Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
WCDMA Band V	4132	826.4	4.1685	4.6840
	4183	836.6	4.1674	4.6870
	4233	846.6	4.1637	4.7030

LTE Band 5						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	20407	824.7	1.0951	1.2570
			20525	836.5	1.0917	1.2790
			20643	848.3	1.0874	1.2890
		3	20415	825.5	2.6958	2.9190
			20525	836.5	2.6985	2.9310
			20635	847.5	2.6869	2.8940
		5	20425	826.5	4.4945	4.8850
			20525	836.5	4.5216	4.9120
			20625	846.5	4.5100	4.8550
		10	20450	829	8.9826	9.7420
			20525	836.5	8.9837	9.7120
			20600	844	8.9980	9.6130



	16QAM	1.4	20407	824.7	1.0923	1.2800
			20525	836.5	1.0981	1.3010
			20643	848.3	1.0945	1.2600
		3	20415	825.5	2.6960	2.9130
			20525	836.5	2.6896	2.9220
			20635	847.5	2.6849	2.9290
		5	20425	826.5	4.4935	4.9050
			20525	836.5	4.5212	4.9350
			20625	846.5	4.5222	4.9500
		10	20450	829	8.9716	9.6810
			20525	836.5	8.9665	9.6970
			20600	844	8.9686	9.7230
	64QAM	1.4	20407	824.7	1.0950	1.2880
			20525	836.5	1.0975	1.3090
			20643	848.3	1.0912	1.2710
		3	20415	825.5	2.6893	2.9110
			20525	836.5	2.6827	2.9400
			20635	847.5	2.6797	2.9540
		5	20425	826.5	4.5116	4.9400
			20525	836.5	4.5015	4.9360
			20625	846.5	4.4987	4.9030
		10	20450	829	8.9821	9.6970
			20525	836.5	8.9829	9.6390
			20600	844	8.9845	9.6980

GSM 850 CH-Low



GSM 850 GPRS CH-Low



GSM 850 CH-Middle



GSM 850 GPRS CH-Middle




GSM 850 CH-High




GSM 850 GPRS CH-High



GSM 850 EGPRS CH-Low




WCDMA Band V CH-Low




GSM 850 EGPRS CH-Middle




WCDMA Band V CH-Middle




GSM 850 EGPRS CH-High




WCDMA Band V CH-High




LTE Band 5 QPSK 1.4MHz CH-Low




LTE Band 5 QPSK 3MHz CH-Low




LTE Band 5 QPSK 1.4MHz CH-Middle




LTE Band 5 QPSK 3MHz CH-Middle



LTE Band 5 QPSK 1.4MHz CH-High




LTE Band 5 QPSK 3MHz CH-High







LTE Band 5 QPSK 5MHz CH-Low



LTE Band 5 QPSK 10MHz CH-Low




LTE Band 5 QPSK 5MHz CH-Middle




LTE Band 5 QPSK 10MHz CH-Middle



LTE Band 5 QPSK 5MHz CH-High




LTE Band 5 QPSK 10MHz CH-High







LTE Band 5 16QAM 1.4MHz CH-Low




LTE Band 5 16QAM 3MHz CH-Low



LTE Band 5 16QAM 1.4MHz CH-Middle




LTE Band 5 16QAM 3MHz CH-Middle



LTE Band 5 16QAM 1.4MHz CH-High




LTE Band 5 16QAM 3MHz CH-High







LTE Band 5 16QAM 5MHz CH-Low




LTE Band 5 16QAM 10MHz CH-Low




LTE Band 5 16QAM 5MHz CH-Middle




LTE Band 5 16QAM 10MHz CH-Middle



LTE Band 5 16QAM 5MHz CH-High




LTE Band 5 16QAM 10MHz CH-High







LTE Band 5 64QAM 1.4MHz CH-Low




LTE Band 5 64QAM 3MHz CH-Low




LTE Band 5 64QAM 1.4MHz CH-Middle




LTE Band 5 64QAM 3MHz CH-Middle



LTE Band 5 64QAM 1.4MHz CH-High




LTE Band 5 64QAM 3MHz CH-High







LTE Band 5 64QAM 5MHz CH-Low




LTE Band 5 64QAM 10MHz CH-Low




LTE Band 5 64QAM 5MHz CH-Middle




LTE Band 5 64QAM 10MHz CH-Middle



LTE Band 5 64QAM 5MHz CH-High



LTE Band 5 64QAM 10MHz CH-High



6.3. Band Edge Compliance


GSM 850 CH-Low




GSM 850 CH-High




GSM 850 GPRS CH-Low




GSM 850 GPRS CH-High



GSM 850 EGPRS CH-Low




GSM 850 EGPRS CH-High






WCDMA Band V CH-Low




WCDMA Band V CH-High



LTE Band 5 QPSK 1.4MHz CH-Low 1RB



LTE Band 5 QPSK 1.4MHz CH-High 1RB




LTE Band 5 QPSK 1.4MHz CH-Low 100%RB




LTE Band 5 QPSK 1.4MHz CH-High 100%RB




LTE Band 5 QPSK 3MHz CH-Low 1RB



LTE Band 5 QPSK 3MHz CH-High 1RB




LTE Band 5 QPSK 3MHz CH-Low 100%RB




LTE Band 5 QPSK 3MHz CH-High 100%RB




LTE Band 5 QPSK 5MHz CH-Low 1RB




LTE Band 5 QPSK 5MHz CH-High 1RB




LTE Band 5 QPSK 5MHz CH-Low 100%RB




LTE Band 5 QPSK 5MHz CH-High 100%RB




LTE Band 5 QPSK 10MHz CH-Low 1RB




LTE Band 5 QPSK 10MHz CH-High 1RB




LTE Band 5 QPSK 10MHz CH-Low 100%RB




LTE Band 5 QPSK 10MHz CH-High 100%RB




LTE Band 5 16QAM 1.4MHz CH-Low 1RB



LTE Band 5 16QAM 1.4MHz CH-High 1RB




LTE Band 5 16QAM 1.4MHz CH-Low 100%RB




LTE Band 5 16QAM 1.4MHz CH-High 100%RB




LTE Band 5 16QAM 3MHz CH-Low 1RB




LTE Band 5 16QAM 3MHz CH-High 1RB



LTE Band 5 16QAM 3MHz CH-Low 100%RB




LTE Band 5 16QAM 3MHz CH-High 100%RB




LTE Band 5 16QAM 5MHz CH-Low 1RB




LTE Band 5 16QAM 5MHz CH-High 1RB




LTE Band 5 16QAM 5MHz CH-Low 100%RB




LTE Band 5 16QAM 5MHz CH-High 100%RB




LTE Band 5 16QAM 10MHz CH-Low 1RB



LTE Band 5 16QAM 10MHz CH-High 1RB




LTE Band 5 16QAM 10MHz CH-Low 100%RB




LTE Band 5 16QAM 10MHz CH-High 100%RB




LTE Band 5 64QAM 1.4MHz CH-Low 1RB




LTE Band 5 64QAM 1.4MHz CH-High 1RB




LTE Band 5 64QAM 1.4MHz CH-Low 100%RB




LTE Band 5 64QAM 1.4MHz CH-High 100%RB




LTE Band 5 64QAM 3MHz CH-Low 1RB




LTE Band 5 64QAM 3MHz CH-High 1RB




LTE Band 5 64QAM 3MHz CH-Low 100%RB




LTE Band 5 64QAM 3MHz CH-High 100%RB



LTE Band 5 64QAM 5MHz CH-Low 1RB




LTE Band 5 64QAM 5MHz CH-High 1RB






LTE Band 5 64QAM 5MHz CH-Low 100%RB




LTE Band 5 64QAM 5MHz CH-High 100%RB




LTE Band 5 64QAM 10MHz CH-Low 1RB




LTE Band 5 64QAM 10MHz CH-High 1RB



LTE Band 5 64QAM 10MHz CH-Low 100%RB



LTE Band 5 64QAM 10MHz CH-High 100%RB



6.4. Peak-to-Average Power Ratio (PAPR)

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
GSM 850 (GMSK)	128	824.2	32.39	29.79	2.60	≤13	PASS
	190	836.6	32.32	29.71	2.61	≤13	PASS
	251	848.8	32.20	29.60	2.60	≤13	PASS
GPRS 850 (GMSK)	128	824.2	32.38	29.78	2.60	≤13	PASS
	190	836.6	32.25	29.65	2.60	≤13	PASS
	251	848.8	32.24	29.63	2.61	≤13	PASS
EGPRS 850 (8PSK)	128	824.2	29.86	24.04	5.82	≤13	PASS
	190	836.6	29.72	23.89	5.83	≤13	PASS
	251	848.8	29.67	23.81	5.86	≤13	PASS
WCDMA Band V (RMC)	4132	826.4	25.78	22.82	2.96	≤13	PASS
	4183	836.6	25.78	22.76	3.02	≤13	PASS
	4233	846.6	25.81	22.78	3.03	≤13	PASS

LTE Band 5								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	20407	824.7	27.26	22.12	5.14	≤13	PASS
		20525	836.5	27.29	22.02	5.27	≤13	PASS
		20643	848.3	26.81	22.07	4.74	≤13	PASS
	3	20415	825.5	27.25	22.05	5.20	≤13	PASS
		20525	836.5	27.30	22.01	5.29	≤13	PASS
		20635	847.5	26.98	22.01	4.97	≤13	PASS
	5	20425	826.5	27.34	22.06	5.28	≤13	PASS
		20525	836.5	27.41	22.03	5.38	≤13	PASS
		20625	846.5	27.11	22.00	5.11	≤13	PASS
	10	20450	829	27.39	22.10	5.29	≤13	PASS
		20525	836.5	27.40	22.05	5.35	≤13	PASS
		20600	844	27.33	22.04	5.29	≤13	PASS
16QAM	1.4	20407	824.7	27.03	21.06	5.97	≤13	PASS
		20525	836.5	27.02	21.05	5.97	≤13	PASS
		20643	848.3	26.65	21.07	5.58	≤13	PASS
	3	20415	825.5	27.08	21.02	6.06	≤13	PASS



		20525	836.5	27.17	21.04	6.13	≤13	PASS
		20635	847.5	26.76	21.02	5.74	≤13	PASS
	5	20425	826.5	27.01	21.06	5.95	≤13	PASS
		20525	836.5	27.12	21.03	6.09	≤13	PASS
		20625	846.5	26.89	20.99	5.90	≤13	PASS
	10	20450	829	27.15	21.09	6.06	≤13	PASS
		20525	836.5	27.15	21.04	6.11	≤13	PASS
		20600	844	27.09	21.01	6.08	≤13	PASS
	64QAM	1.4	20407	824.7	26.58	20.64	5.94	≤13
20525			836.5	26.54	20.58	5.96	≤13	PASS
20643			848.3	26.21	20.58	5.63	≤13	PASS
3		20415	825.5	26.62	20.55	6.07	≤13	PASS
		20525	836.5	26.68	20.55	6.13	≤13	PASS
		20635	847.5	26.33	20.55	5.78	≤13	PASS
5		20425	826.5	26.60	20.60	6.00	≤13	PASS
		20525	836.5	26.69	20.58	6.11	≤13	PASS
		20625	846.5	26.45	20.55	5.90	≤13	PASS
10		20450	829	26.75	20.66	6.09	≤13	PASS
		20525	836.5	26.72	20.60	6.12	≤13	PASS
		20600	844	26.63	20.56	6.07	≤13	PASS

6.5. Frequency Stability

GSM850						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	GMSK	8PSK	GMSK	8PSK	
Normal (25℃)	Normal	7.55	13.79	0.00902	0.01648	PASS
Extreme (50℃)		3.04	3.69	0.00364	0.00441	PASS
Extreme (40℃)		3.93	9.51	0.00470	0.01137	PASS
Extreme (30℃)		15.81	6.19	0.01890	0.00739	PASS
Extreme (20℃)		16.86	8.52	0.02016	0.01019	PASS
Extreme (10℃)		7.21	10.18	0.00862	0.01217	PASS
Extreme (0℃)		15.48	2.58	0.01850	0.00309	PASS
Extreme (-10℃)		12.43	2.77	0.01486	0.00331	PASS
Extreme (-20℃)		11.85	1.87	0.01417	0.00223	PASS
Extreme (-30℃)		2.28	16.91	0.00272	0.02022	PASS
25℃	LV	13.91	15.37	0.01663	0.01837	PASS
	HV	15.21	16.21	0.01818	0.01938	PASS

WCDMA Band V						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	BPSK	QPSK	BPSK	QPSK	
Normal (25℃)	Normal	6.00	6.95	0.00717	0.00831	PASS
Extreme (50℃)		16.90	15.31	0.02021	0.01831	PASS
Extreme (40℃)		16.90	15.46	0.02020	0.01847	PASS
Extreme (30℃)		9.78	4.52	0.01169	0.00541	PASS
Extreme (20℃)		15.19	9.42	0.01816	0.01125	PASS
Extreme (10℃)		13.57	17.86	0.01622	0.02135	PASS
Extreme (0℃)		9.33	2.88	0.01115	0.00345	PASS
Extreme (-10℃)		16.60	4.55	0.01984	0.00544	PASS
Extreme (-20℃)		8.72	9.50	0.01042	0.01136	PASS
Extreme (-30℃)		10.20	16.41	0.01220	0.01961	PASS
25℃	LV	8.26	7.66	0.00987	0.00916	PASS
	HV	17.15	2.73	0.02050	0.00326	PASS



LTE Band 5								
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	1.4MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25℃)	Normal	8.11	15.44	7.35	0.00969	0.01846	0.00879	PASS
Extreme (50℃)		9.12	15.35	10.84	0.01090	0.01835	0.01296	PASS
Extreme (40℃)		3.87	16.89	3.68	0.00463	0.02019	0.00440	PASS
Extreme (30℃)		7.95	4.29	16.95	0.00950	0.00513	0.02026	PASS
Extreme (20℃)		9.67	3.59	9.02	0.01156	0.00429	0.01078	PASS
Extreme (10℃)		7.01	16.51	17.75	0.00838	0.01974	0.02122	PASS
Extreme (0℃)		9.19	12.09	12.44	0.01099	0.01446	0.01487	PASS
Extreme (-10℃)		15.88	2.49	6.13	0.01898	0.00297	0.00733	PASS
Extreme (-20℃)		3.79	2.26	12.32	0.00453	0.00270	0.01473	PASS
Extreme (-30℃)		5.13	3.25	12.34	0.00613	0.00388	0.01476	PASS
25℃	LV	16.42	15.42	11.55	0.01963	0.01844	0.01381	PASS
	HV	15.13	16.64	1.96	0.01809	0.01990	0.00235	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	3MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25℃)	Normal	9.17	17.02	4.04	0.01096	0.02034	0.00483	PASS
Extreme (50℃)		4.54	15.64	11.03	0.00543	0.01870	0.01318	PASS
Extreme (40℃)		11.82	5.92	5.69	0.01413	0.00707	0.00681	PASS
Extreme (30℃)		1.75	17.60	11.49	0.00209	0.02103	0.01374	PASS
Extreme (20℃)		13.34	9.82	15.29	0.01594	0.01174	0.01828	PASS
Extreme (10℃)		3.88	17.92	14.22	0.00464	0.02142	0.01700	PASS
Extreme (0℃)		11.44	9.15	14.06	0.01368	0.01094	0.01681	PASS
Extreme (-10℃)		6.56	9.07	5.27	0.00784	0.01085	0.00630	PASS
Extreme (-20℃)		2.26	8.47	5.57	0.00270	0.01013	0.00666	PASS
Extreme (-30℃)		12.19	7.70	4.03	0.01457	0.00921	0.00482	PASS
25℃	LV	1.12	13.18	9.35	0.00134	0.01575	0.01118	PASS
	HV	3.12	10.98	14.61	0.00373	0.01313	0.01747	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25℃)	Normal	17.56	8.30	7.03	0.02099	0.00992	0.00840	PASS
Extreme (50℃)		2.55	3.31	1.34	0.00304	0.00396	0.00160	PASS



Extreme (40℃)		1.69	11.75	4.62	0.00201	0.01405	0.00552	PASS
Extreme (30℃)		3.43	8.00	7.14	0.00410	0.00956	0.00854	PASS
Extreme (20℃)		3.02	9.95	16.27	0.00362	0.01190	0.01945	PASS
Extreme (10℃)		14.74	13.34	13.21	0.01762	0.01595	0.01579	PASS
Extreme (0℃)		15.24	4.79	9.60	0.01821	0.00573	0.01147	PASS
Extreme (-10℃)		11.82	10.64	15.48	0.01413	0.01272	0.01850	PASS
Extreme (-20℃)		1.73	14.04	2.86	0.00207	0.01679	0.00342	PASS
Extreme (-30℃)		12.90	3.48	6.28	0.01543	0.00416	0.00751	PASS
25℃	LV	3.26	9.84	14.96	0.00389	0.01176	0.01789	PASS
	HV	8.96	6.13	2.93	0.01071	0.00733	0.00350	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25℃)	Normal	6.85	15.73	9.37	0.00819	0.01880	0.01121	PASS
Extreme (50℃)		1.43	2.31	16.38	0.00171	0.00276	0.01958	PASS
Extreme (40℃)		10.96	5.70	2.22	0.01310	0.00681	0.00265	PASS
Extreme (30℃)		11.64	11.25	17.97	0.01392	0.01345	0.02148	PASS
Extreme (20℃)		6.65	3.30	15.63	0.00795	0.00394	0.01868	PASS
Extreme (10℃)		17.70	1.67	3.10	0.02116	0.00200	0.00371	PASS
Extreme (0℃)		11.35	11.16	8.34	0.01357	0.01334	0.00998	PASS
Extreme (-10℃)		4.94	5.80	9.50	0.00590	0.00693	0.01135	PASS
Extreme (-20℃)		5.23	14.41	14.87	0.00625	0.01722	0.01778	PASS
Extreme (-30℃)		4.42	10.33	2.65	0.00528	0.01235	0.00317	PASS
25℃	LV	14.20	4.78	5.16	0.01698	0.00572	0.00617	PASS
	HV	16.61	6.16	15.06	0.01986	0.00736	0.01800	PASS




6.6. Spurious Emissions at Antenna Terminals


Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.


GSM 850 CH-Low 9kHz ~ 20GHz




GPRS 850 CH-Low 9kHz ~ 20GHz




GSM 850 CH-Middle 9kHz ~ 20GHz




GPRS 850 CH-Middle 9kHz ~ 20GHz



GSM 850 CH-High 9kHz ~ 20GHz




GPRS 850 CH-High 9kHz ~ 20GHz






EGPRS 850 CH-Low 9kHz ~ 20GHz




14:04:58 12.10.2022

WCDMA BAND V CH-Low 9kHz ~ 20GHz




15:34:06 12.10.2022

EGPRS 850 CH-Middle 9kHz ~ 20GHz




14:05:58 12.10.2022

WCDMA BAND V CH-Middle 9kHz ~ 20GHz




15:39:22 12.10.2022

EGPRS 850 CH-High 9kHz ~ 20GHz




14:03:41 12.10.2022

WCDMA BAND V CH-High 9kHz ~ 20GHz




15:34:44 12.10.2022


LTE Band 5 1.4MHz CH-Low 9kHz~10GHz




LTE Band 5 3MHz CH-Low 9kHz~10GHz




LTE Band 5 1.4MHz CH-Middle 9kHz~10GHz




LTE Band 5 3MHz CH-Middle 9kHz~10GHz




LTE Band 5 1.4MHz CH-High 9kHz~10GHz




LTE Band 5 3MHz CH-High 9kHz~10GHz




LTE Band 5 5MHz CH-Low 9kHz~10GHz




LTE Band 5 10MHz CH-Low 9kHz~10GHz




LTE Band 5 5MHz CH-Middle 9kHz~10GHz




LTE Band 5 10MHz CH-Middle 9kHz~10GHz



LTE Band 5 5MHz CH-High 9kHz~10GHz



LTE Band 5 10MHz CH-High 9kHz~10GHz



6.7. Radiated Spurious Emission

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

Upper Antenna

GSM 850 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.70	-58.40	2.30	12.00	Vertical	-50.85	-13.00	37.85	94
3	2509.45	-46.35	1.70	8.70	Vertical	-41.50	-13.00	28.50	211
4	3346.40	-67.55	2.70	12.70	Vertical	-59.70	-13.00	46.70	67
5	4183.00	-63.63	3.00	12.50	Vertical	-56.28	-13.00	43.28	112
6	5019.60	-62.89	3.40	12.50	Vertical	-55.94	-13.00	42.94	39
7	5856.20	-61.11	3.40	12.80	Vertical	-53.86	-13.00	40.86	51
8	6692.80	-59.76	4.10	11.50	Vertical	-54.51	-13.00	41.51	206
9	7529.40	-54.91	4.20	12.20	Vertical	-49.06	-13.00	36.06	257
10	8366.00	-54.77	4.30	12.50	Vertical	-48.72	-13.00	35.72	162
Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Vertical position.									

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1676.00	-66.81	1.70	8.70	Vertical	-61.96	-13.00	48.96	119
3	2518.80	-66.75	2.30	12.00	Vertical	-59.20	-13.00	46.20	162
4	3346.40	-66.92	2.70	12.70	Vertical	-59.07	-13.00	46.07	112
5	4183.00	-65.00	3.00	12.50	Vertical	-57.65	-13.00	44.65	139
6	5019.60	-60.36	3.40	12.50	Vertical	-53.41	-13.00	40.41	27
7	5856.20	-61.41	3.40	12.80	Vertical	-54.16	-13.00	41.16	68
8	6692.80	-58.41	4.10	11.50	Vertical	-53.16	-13.00	40.16	151
9	7529.40	-56.20	4.20	12.20	Vertical	-50.35	-13.00	37.35	17
10	8366.00	-55.94	4.30	12.50	Vertical	-49.89	-13.00	36.89	72
Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Vertical position.									

LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.00	-65.81	1.70	8.70	Vertical	-60.96	-13.00	47.96	180
3	2509.50	-66.77	2.30	12.00	Vertical	-59.22	-13.00	46.22	311
4	3346.00	-66.65	2.70	12.70	Vertical	-58.80	-13.00	45.80	101
5	4182.50	-65.14	3.00	12.50	Vertical	-57.79	-13.00	44.79	31
6	5019.00	-61.21	3.40	12.50	Vertical	-54.26	-13.00	41.26	59
7	5855.50	-61.31	3.40	12.80	Vertical	-54.06	-13.00	41.06	228
8	6692.00	-59.14	4.10	11.50	Vertical	-53.89	-13.00	40.89	17
9	7528.50	-55.43	4.20	12.20	Vertical	-49.58	-13.00	36.58	162
10	8365.00	-54.37	4.30	12.50	Vertical	-48.32	-13.00	35.32	173

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1668.60	-65.99	1.70	8.70	Vertical	-61.14	-13.00	48.14	90
3	2503.30	-65.58	2.30	12.00	Vertical	-58.03	-13.00	45.03	231
4	3337.50	-66.88	2.70	12.70	Vertical	-59.03	-13.00	46.03	62
5	4171.88	-64.32	3.00	12.50	Vertical	-56.97	-13.00	43.97	39
6	5006.25	-60.65	3.40	12.50	Vertical	-53.70	-13.00	40.70	127
7	5840.63	-60.12	3.40	12.80	Vertical	-52.87	-13.00	39.87	201
8	6675.00	-58.72	4.10	11.50	Vertical	-53.47	-13.00	40.47	314
9	7509.38	-54.62	4.20	12.20	Vertical	-48.77	-13.00	35.77	249
10	8343.75	-55.32	4.30	12.50	Vertical	-49.27	-13.00	36.27	72

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.



LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1664.40	-68.60	1.70	8.70	Vertical	-63.75	-13.00	50.75	11
3	2496.60	-67.54	2.30	12.00	Vertical	-59.99	-13.00	46.99	222
4	3326.00	-66.65	2.70	12.70	Vertical	-58.80	-13.00	45.80	139
5	4157.50	-63.92	3.00	12.50	Vertical	-56.57	-13.00	43.57	237
6	4989.00	-62.74	3.40	12.50	Vertical	-55.79	-13.00	42.79	105
7	5820.50	-60.29	3.40	12.80	Vertical	-53.04	-13.00	40.04	19
8	6652.00	-57.88	4.10	11.50	Vertical	-52.63	-13.00	39.63	264
9	7483.50	-55.03	4.20	12.20	Vertical	-49.18	-13.00	36.18	73
10	8315.00	-55.02	4.30	12.50	Vertical	-48.97	-13.00	35.97	89

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

**Low Antenna****GSM 850 CH-Middle**

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.55	-48.67	1.70	8.70	Horizontal	-43.82	-13.00	30.82	122
3	2509.80	-34.88	2.30	12.00	Horizontal	-27.33	-13.00	14.33	176
4	3346.40	-66.57	2.70	12.70	Horizontal	-58.72	-13.00	45.72	20
5	4183.00	-55.20	3.00	12.50	Horizontal	-47.85	-13.00	34.85	314
6	5019.60	-61.45	3.40	12.50	Horizontal	-54.50	-13.00	41.50	80
7	5856.20	-61.06	3.40	12.80	Horizontal	-53.81	-13.00	40.81	48
8	6692.80	-58.88	4.10	11.50	Horizontal	-53.63	-13.00	40.63	165
9	7529.40	-55.34	4.20	12.20	Horizontal	-49.49	-13.00	36.49	35
10	8366.00	-54.83	4.30	12.50	Horizontal	-48.78	-13.00	35.78	280

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1676.00	-62.91	1.70	8.70	Horizontal	-58.06	-13.00	45.06	277
3	2518.80	-56.20	2.30	12.00	Horizontal	-48.65	-13.00	35.65	13
4	3346.40	-68.42	2.70	12.70	Horizontal	-60.57	-13.00	47.57	280
5	4183.00	-65.31	3.00	12.50	Horizontal	-57.96	-13.00	44.96	318
6	5019.60	-62.18	3.40	12.50	Horizontal	-55.23	-13.00	42.23	5
7	5856.20	-61.87	3.40	12.80	Horizontal	-54.62	-13.00	41.62	188
8	6692.80	-59.77	4.10	11.50	Horizontal	-54.52	-13.00	41.52	322
9	7529.40	-56.23	4.20	12.20	Horizontal	-50.38	-13.00	37.38	24
10	8366.00	-56.67	4.30	12.50	Horizontal	-50.62	-13.00	37.62	181

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.00	-60.63	1.70	8.70	Vertical	-55.78	-13.00	42.78	311
3	2509.50	-59.78	2.30	12.00	Vertical	-52.23	-13.00	39.23	42
4	3346.00	-66.76	2.70	12.70	Vertical	-58.91	-13.00	45.91	46
5	4182.50	-65.04	3.00	12.50	Vertical	-57.69	-13.00	44.69	135
6	5019.00	-62.39	3.40	12.50	Vertical	-55.44	-13.00	42.44	222
7	5855.50	-61.26	3.40	12.80	Vertical	-54.01	-13.00	41.01	135
8	6692.00	-59.36	4.10	11.50	Vertical	-54.11	-13.00	41.11	252
9	7528.50	-55.66	4.20	12.20	Vertical	-49.81	-13.00	36.81	315
10	8365.00	-55.20	4.30	12.50	Vertical	-49.15	-13.00	36.15	181

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.

LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1668.60	-60.06	1.70	8.70	Vertical	-55.21	-13.00	42.21	182
3	2503.30	-59.48	2.30	12.00	Vertical	-51.93	-13.00	38.93	42
4	3337.50	-68.37	2.70	12.70	Vertical	-60.52	-13.00	47.52	12
5	4171.88	-65.45	3.00	12.50	Vertical	-58.10	-13.00	45.10	269
6	5006.25	-63.02	3.40	12.50	Vertical	-56.07	-13.00	43.07	311
7	5840.63	-61.54	3.40	12.80	Vertical	-54.29	-13.00	41.29	68
8	6675.00	-59.09	4.10	11.50	Vertical	-53.84	-13.00	40.84	132
9	7509.38	-56.07	4.20	12.20	Vertical	-50.22	-13.00	37.22	270
10	8343.75	-55.73	4.30	12.50	Vertical	-49.68	-13.00	36.68	180

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.



LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1664.40	-64.33	1.70	8.70	Vertical	-59.48	-13.00	46.48	158
3	2496.60	-61.79	2.30	12.00	Vertical	-54.24	-13.00	41.24	187
4	3326.00	-67.41	2.70	12.70	Vertical	-59.56	-13.00	46.56	10
5	4157.50	-64.98	3.00	12.50	Vertical	-57.63	-13.00	44.63	180
6	4989.00	-63.38	3.40	12.50	Vertical	-56.43	-13.00	43.43	45
7	5820.50	-61.74	3.40	12.80	Vertical	-54.49	-13.00	41.49	135
8	6652.00	-59.82	4.10	11.50	Vertical	-54.57	-13.00	41.57	270
9	7483.50	-57.18	4.20	12.20	Vertical	-51.33	-13.00	38.33	315
10	8315.00	-56.13	4.30	12.50	Vertical	-50.08	-13.00	37.08	186

Note: 1. The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Vertical position.



7. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	150415	2022-05-14	2023-05-13
Spectrum Analyzer	Key sight	N9020A	MY50510203	2021-12-12	2022-12-11
Universal Radio Communication Tester	Key sight	E5515C	GB44400275	2021-12-12	2022-12-11
Signal Analyzer	R&S	FSV3030	101411	2021-12-12	2022-12-11
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	1023	2020-05-05	2023-05-04
Climatic Chamber	ESPEC	SU-242	93000506	2021-12-12	2022-12-11
Spectrum Analyzer	R&S	FSV30	104028	2021-12-12	2022-12-11
Horn Antenna	Schwarzbeck	BBHA 9120D	1594	2020-12-17	2023-12-16
Software	R&S	EMC32	10.35.10	/	/

*****END OF REPORT *****



ANNEX A: The EUT Appearance

The EUT Appearance is submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos is submitted separately.





ANNEX C: Product Change Description

The Product Change Description are submitted separately.