

FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : POCO
MODEL NAME : 2602BPC18G
FCC ID : 2AFZZPC18G
STANDARD : 47 CFR Part 27 Subpart Q
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Dec. 04, 2025 ~ Dec. 13, 2025

We, Sporton International Inc. (KunShan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (KunShan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**

TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Maximum EIRP Power and Emission Designator	6
1.7 Testing Site.....	7
1.8 Test Software.....	8
1.9 Applied Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System.....	10
2.3 Support Unit used in test configuration and system	10
2.4 Measurement Results Explanation Example.....	10
2.5 Frequency List of Low/Middle/High Channels	11
3 CONDUCTED TEST ITEMS	12
3.1 Measuring Instruments	12
3.2 Test Setup	12
3.3 Test Result of Conducted Test	12
3.4 Conducted Output Power Measurement	13
3.5 Peak-to-Average Ratio	14
3.6 EIRP	15
3.7 Occupied Bandwidth.....	16
3.8 Conducted Band Edge Measurement	17
3.9 Conducted Spurious Emission Measurement	18
3.10 Frequency Stability Measurement.....	19
4 RADIATED TEST ITEMS	20
4.1 Measuring Instruments	20
4.2 Test Setup	20
4.3 Test Result of Radiated Test	21
4.4 Radiated Spurious Emission Measurement	22
5 LIST OF MEASURING EQUIPMENT	23
6 MEASUREMENT UNCERTAINTY	24
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG5N1302M	Rev. 01	Initial issue of report	Jan. 12, 2026

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	—	Report Only	-
3.5	§27.50 (k)(4)	Peak-to-Average Ratio	<13dB	PASS	
3.6	§27.50 (k)(3)	EIRP	EIRP < 1W (30dBm)	PASS	-
3.7	§2.1049	Occupied Bandwidth	—	Report Only	-
3.8	§2.1051 §27.53 (n)(2)	Conducted Band Edge Measurement	-13dBm/MHz	PASS	-
3.9	§2.1051 §27.53 (n)(2)	Conducted Spurious Emission	-13dBm/MHz	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (n)(2)	Radiated Spurious Emission	-13dBm/MHz	PASS	Under limit 46.31 dB at 13824 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	POCO
Model Name	2602BPC18G
FCC ID	2AFZZPC18G
IMEI Code	Conducted : 860534080020743/860534080020750 Radiation : 860534080021162
HW Version	13510P10U
SW Version	Xiaomi HyperOS 3.0
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx/Rx Frequency	5G NR n77: 3450 MHz ~ 3550 MHz 5G NR n78: 3450 MHz ~ 3550 MHz
SCS	30kHz
Bandwidth	n77/n78: 10 / 15 / 20 / 25 / 30 / 40 / 50 / 60 / 70 / 80 / 90 / 100MHz
Antenna Gain	<Ant. 1> 5G NR n77: -0.18 dBi 5G NR n78: -0.18 dBi <Ant. 2> 5G NR n77: -2.70 dBi 5G NR n78: -2.70 dBi <Ant. 3> 5G NR n77: -3.00 dBi 5G NR n78: -3.00 dBi <Ant. 6> 5G NR n77: -4.63 dBi 5G NR n78: -5.00 dBi
Type of Modulation	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

Remark:

1. The maximum EIRP is calculated from max output power and max antenna gain, only the maximum EIRP is shown in the report, 5G NR n77/n78 for Antenna 2.
2. 5G NR support SA(n77/n78) and NSA(n78) mode. The whole testing has assessed SA mode for n77/n78 by referring to the higher conducted power for conducted test items.
3. The device supports HPUE mode for 5G NR n77/n78.
4. All the supported EN-DC combinations are verified conducted power, only the EN-DC combination with highest power are shown in the report.
5. The EN-DC mode combination could be referred to the product spec.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP Power and Emission Designator

5G NR n77 SA		PI/2 BPSK / QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
10	3455.01 ~ 3544.98	0.2056	8M56G7D	0.1746	8M59W7D
15	3457.50 ~ 3542.49	0.2051	13M6G7D	0.1592	13M6W7D
20	3460.02 ~ 3540.00	0.2089	18M2G7D	0.1614	18M2W7D
25	3462.51 ~ 3537.48	0.2028	23M2G7D	0.1603	23M2W7D
30	3465.00 ~ 3534.99	0.2084	27M8G7D	0.1694	27M8W7D
40	3470.01 ~ 3529.98	0.2051	37M8G7D	0.1671	37M7W7D
50	3475.02 ~ 3525.00	0.2051	47M3G7D	0.1730	47M3W7D
60	3480.00 ~ 3519.99	0.2056	57M8G7D	0.1667	57M7W7D
70	3485.01 ~ 3514.98	0.2099	67M4G7D	0.1687	67M4W7D
80	3490.02 ~ 3510.00	0.2118	77M4G7D	0.1718	77M5W7D
90	3495.00 ~ 3504.99	0.2084	87M3G7D	0.1714	87M3W7D
100	3500.01	0.2061	97M3G7D	0.1718	97M4W7D

5G NR n78 SA		PI/2 BPSK / QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
10	3455.01 ~ 3544.98	0.2985	8M57G7D	0.2460	8M57W7D
15	3457.50 ~ 3542.49	0.2911	13M6G7D	0.2388	13M6W7D
20	3460.02 ~ 3540.00	0.2972	18M2G7D	0.2404	18M2W7D
25	3462.51 ~ 3537.48	0.2877	23M2G7D	0.2259	23M2W7D
30	3465.00 ~ 3534.99	0.2924	27M8G7D	0.2234	27M8W7D
40	3470.01 ~ 3529.98	0.2938	37M7G7D	0.2328	37M8W7D
50	3475.02 ~ 3525.00	0.2884	47M4G7D	0.2382	47M4W7D
60	3480.00 ~ 3519.99	0.2884	57M9G7D	0.2333	57M8W7D
70	3485.01 ~ 3514.98	0.2891	67M3G7D	0.2291	67M4W7D
80	3490.02 ~ 3510.00	0.2924	77M4G7D	0.2388	77M4W7D
90	3495.00 ~ 3504.99	0.2891	87M3G7D	0.2307	87M3W7D
100	3500.01	0.2877	97M3G7D	0.2312	97M4W7D

Note: All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH04-KS	AUDIX	E3	210616

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 27Q
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.


Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Z Plane)

Test Cases	Band	Bandwidth (MHz)	Modulation	RB #	Test Channel
		eg. 10M, 15M, 20M, 25M, 30M, 40M, 50M, 60M, 70M, 80M, 90M, 100M	eg. PI/2 BPSK, QPSK, 16QAM, 64QAM, 256QAM	1RB, Partial RB, Full RB	L/M/H
Max. Output Power	5G n77	10M, 15M, 20M, 25M, 30M, 40M, 50M, 60M, 70M, 80M, 90M, 100M	All Modulations	1RB, Partial RB, Full RB	L, M, H
	5G n78	10M, 15M, 20M, 25M, 30M, 40M, 50M, 60M, 70M, 80M, 90M, 100M	All Modulations	1RB, Partial RB, Full RB	L, M, H
Peak-to-Average Ratio	5G n77	20M	PI/2 BPSK, QPSK	1RB, Full RB	M
	5G n78	20M	PI/2 BPSK, QPSK	1RB, Full RB	M
E.I.R.P	5G n77	10M, 15M, 20M, 25M, 30M, 40M, 50M, 60M, 70M, 80M, 90M, 100M	All Modulations	1RB, Partial RB, Full RB	L, M, H
	5G n78	10M, 15M, 20M, 25M, 30M, 40M, 50M, 60M, 70M, 80M, 90M, 100M	All Modulations	1RB, Partial RB, Full RB	L, M, H
26dB and 99% Bandwidth	5G n77	10M, 15M, 20M, 25M, 30M, 40M, 50M, 60M, 70M, 80M, 90M, 100M	QPSK, 16QAM	Full RB	M
	5G n78	10M, 15M, 20M, 25M, 30M, 40M, 50M, 60M, 70M, 80M, 90M, 100M	QPSK, 16QAM	Full RB	M
Conducted Band Edge	5G n77	10M, 50M, 100M	PI/2 BPSK, QPSK	1RB, Full RB	L, H
	5G n78	10M, 50M, 100M	PI/2 BPSK, QPSK	1RB, Full RB	L, H
Conducted Spurious Emission	5G n77	10M, 50M, 100M	PI/2 BPSK	1RB	L, M, H
	5G n78	10M, 50M, 100M	PI/2 BPSK	1RB	L, M, H
Frequency Stability	5G n77	20M	QPSK	Full RB	M
	5G n78	20M	QPSK	Full RB	M
Radiated Spurious Emission	5G n77	Worst case from maximum power			M
	5G n78	Worst case from maximum power			M

Note:

- The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.
- Frequency Stability: Normal Voltage = 3.8V ; Low Voltage =3.6V.; High Voltage =4.2V.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 9.41 dB and 20dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 9.41 + 20 = 29.41 (dB)

2.5 Frequency List of Low/Middle/High Channels

5G n77/n78 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	-	633334	-
	Frequency	-	3500.01	-
90	Channel	633000	633334	633666
	Frequency	3495	3500.01	3504.99
80	Channel	632668	633334	634000
	Frequency	3490.02	3500.01	3510
70	Channel	632334	633334	634332
	Frequency	3485.01	3500.01	3514.98
60	Channel	632000	633334	634666
	Frequency	3480	3500.01	3519.99
50	Channel	631668	633334	635000
	Frequency	3475.02	3500.01	3525
40	Channel	631334	633334	635332
	Frequency	3470.01	3500.01	3529.98
30	Channel	631000	633334	635666
	Frequency	3465	3500.01	3534.99
25	Channel	630834	633334	635832
	Frequency	3462.51	3500.01	3537.48
20	Channel	630668	633334	636000
	Frequency	3460.02	3500.01	3540
15	Channel	630500	633334	636166
	Frequency	3457.5	3500.01	3542.49
10	Channel	630334	633334	636332
	Frequency	3455.01	3500.01	3544.98


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth, Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP Limit

§ 27.50 (k)(3)

Mobile devices are limited to 1Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. $EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where
 P_T = transmitter output power in dBm
 G_T = gain of the transmitting antenna in dBi
 L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

§ 27.53 (n)(2)

For mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

Compliance with this paragraph is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed, but limited to a maximum of 200 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW but limited to a maximum of 200 kHz in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz and 5 MHz removed from the band edge, set RBW ≥ 500 KHz.
6. Beyond the 5 MHz removed from the band edge, set RBW = 1MHz.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. Checked that all the results comply with the emission limit line.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. Checked that all the results comply with the emission limit line.

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
$$\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$$
$$\text{ERP (dBm)} = \text{EIRP} - 2.15$$
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 10, 2025	Dec. 13, 2025	Oct. 09, 2026	Radiation (03CH04-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 10, 2025	Dec. 13, 2025	Oct. 09, 2026	Radiation (03CH04-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Dec. 13, 2025	Aug. 09, 2026	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Nov. 22, 2025	Dec. 13, 2025	Nov. 21, 2026	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00227860	1GHz~18GHz	Aug. 22, 2025	Dec. 13, 2025	Aug. 21, 2026	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 11, 2025	Dec. 13, 2025	Jan. 10, 2026	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380826	9KHz-1GHz	Jul. 02, 2025	Dec. 13, 2025	Jul. 01, 2026	Radiation (03CH04-KS)
Amplifier	EM	EM18G40G A	060852	18~40GHz	Jan. 03, 2025	Dec. 13, 2025	Jan. 02, 2026	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060890	1Ghz-18Ghz	May 23, 2025	Dec. 13, 2025	May 22, 2026	Radiation (03CH04-KS)
Amplifier	EM	EM01G18G A	060892	1Ghz-18Ghz	Oct. 11, 2025	Dec. 13, 2025	Oct. 10, 2026	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Dec. 13, 2025	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 13, 2025	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 13, 2025	NCR	Radiation (03CH04-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Jul. 07, 2025	Dec. 04, 2025~Dec. 05, 2025	Jul. 06, 2026	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Dec. 04, 2025~Dec. 05, 2025	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 02, 2025	Dec. 04, 2025~Dec. 05, 2025	Jul. 01, 2026	Conducted (TH01-KS)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	± 2.00 dB
Occupied Channel Bandwidth	$\pm 0.384\%$
Conducted Power	± 0.90 dB
Peak to Average Ratio	± 0.90 dB
Frequency Stability	± 0.38 ppm

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.82 dB
---	---------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Smile Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%



FR1 N77_ANT2

Transmitter Conducted Output Power And EIRP, $(G_T - L_c) = -2.7\text{dB}$

NR Band	SCS	BandWidth	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
77	30	10	630334	3455.01	DFT-s-OFDM PI/2 BPSK	1@1	25.77	23.07	0.2028
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	1@1	25.83	23.13	0.2056
77	30	10	630334	3455.01	DFT-s-OFDM 16 QAM	1@1	25.12	22.42	0.1746
77	30	10	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.45	22.75	0.1884
77	30	10	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.49	22.79	0.1901
77	30	10	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.59	21.89	0.1545
77	30	10	636332	3544.98	DFT-s-OFDM PI/2 BPSK	1@1	25.58	22.88	0.1941
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	1@1	25.64	22.94	0.1968
77	30	10	636332	3544.98	DFT-s-OFDM 16 QAM	1@1	24.83	22.13	0.1633
77	30	15	630500	3457.5	DFT-s-OFDM PI/2 BPSK	1@1	25.82	23.12	0.2051
77	30	15	630500	3457.5	DFT-s-OFDM QPSK	1@1	25.78	23.08	0.2032
77	30	15	630500	3457.5	DFT-s-OFDM 16 QAM	1@1	24.72	22.02	0.1592
77	30	15	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.49	22.79	0.1901
77	30	15	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.52	22.82	0.1914
77	30	15	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.50	21.80	0.1514
77	30	15	636166	3542.49	DFT-s-OFDM PI/2 BPSK	1@1	25.56	22.86	0.1932
77	30	15	636166	3542.49	DFT-s-OFDM QPSK	1@1	25.66	22.96	0.1977
77	30	15	636166	3542.49	DFT-s-OFDM 16 QAM	1@1	24.61	21.91	0.1552
77	30	20	630668	3460.02	DFT-s-OFDM PI/2 BPSK	1@1	25.82	23.12	0.2051
77	30	20	630668	3460.02	DFT-s-OFDM QPSK	1@1	25.90	23.20	0.2089
77	30	20	630668	3460.02	DFT-s-OFDM 16 QAM	1@1	24.77	22.07	0.1611
77	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.55	22.85	0.1928
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.58	22.88	0.1941
77	30	20	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.78	22.08	0.1614
77	30	20	636000	3540	DFT-s-OFDM PI/2 BPSK	1@1	25.55	22.85	0.1928
77	30	20	636000	3540	DFT-s-OFDM QPSK	1@1	25.59	22.89	0.1945
77	30	20	636000	3540	DFT-s-OFDM 16 QAM	1@1	24.56	21.86	0.1535
77	30	25	630834	3462.51	DFT-s-OFDM PI/2 BPSK	1@1	25.77	23.07	0.2028
77	30	25	630834	3462.51	DFT-s-OFDM QPSK	1@1	25.76	23.06	0.2023
77	30	25	630834	3462.51	DFT-s-OFDM 16 QAM	1@1	24.75	22.05	0.1603
77	30	25	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.55	22.85	0.1928
77	30	25	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.61	22.91	0.1954
77	30	25	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.61	21.91	0.1552
77	30	25	635832	3537.48	DFT-s-OFDM PI/2 BPSK	1@1	25.39	22.69	0.1858



NR Band	SCS	BandWidth	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
77	30	25	635832	3537.48	DFT-s-OFDM QPSK	1@1	25.48	22.78	0.1897
77	30	25	635832	3537.48	DFT-s-OFDM 16 QAM	1@1	24.60	21.90	0.1549
77	30	30	631000	3465	DFT-s-OFDM PI/2 BPSK	1@1	25.78	23.08	0.2032
77	30	30	631000	3465	DFT-s-OFDM QPSK	1@1	25.89	23.19	0.2084
77	30	30	631000	3465	DFT-s-OFDM 16 QAM	1@1	24.99	22.29	0.1694
77	30	30	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.60	22.90	0.1950
77	30	30	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.66	22.96	0.1977
77	30	30	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.85	22.15	0.1641
77	30	30	635666	3534.99	DFT-s-OFDM PI/2 BPSK	1@1	25.45	22.75	0.1884
77	30	30	635666	3534.99	DFT-s-OFDM QPSK	1@1	25.44	22.74	0.1879
77	30	30	635666	3534.99	DFT-s-OFDM 16 QAM	1@1	24.51	21.81	0.1517
77	30	40	631334	3470.01	DFT-s-OFDM PI/2 BPSK	1@1	25.73	23.03	0.2009
77	30	40	631334	3470.01	DFT-s-OFDM QPSK	1@1	25.82	23.12	0.2051
77	30	40	631334	3470.01	DFT-s-OFDM 16 QAM	1@1	24.93	22.23	0.1671
77	30	40	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.67	22.97	0.1982
77	30	40	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.69	22.99	0.1991
77	30	40	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.81	22.11	0.1626
77	30	40	635332	3529.98	DFT-s-OFDM PI/2 BPSK	1@1	25.34	22.64	0.1837
77	30	40	635332	3529.98	DFT-s-OFDM QPSK	1@1	25.39	22.69	0.1858
77	30	40	635332	3529.98	DFT-s-OFDM 16 QAM	1@1	24.60	21.90	0.1549
77	30	50	631668	3475.02	DFT-s-OFDM PI/2 BPSK	1@1	25.82	23.12	0.2051
77	30	50	631668	3475.02	DFT-s-OFDM QPSK	1@1	25.81	23.11	0.2046
77	30	50	631668	3475.02	DFT-s-OFDM 16 QAM	1@1	25.08	22.38	0.1730
77	30	50	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.67	22.97	0.1982
77	30	50	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.74	23.04	0.2014
77	30	50	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.78	22.08	0.1614
77	30	50	635000	3525	DFT-s-OFDM PI/2 BPSK	1@1	25.38	22.68	0.1854
77	30	50	635000	3525	DFT-s-OFDM QPSK	1@1	25.38	22.68	0.1854
77	30	50	635000	3525	DFT-s-OFDM 16 QAM	1@1	24.44	21.74	0.1493
77	30	60	632000	3480	DFT-s-OFDM PI/2 BPSK	1@1	25.82	23.12	0.2051
77	30	60	632000	3480	DFT-s-OFDM QPSK	1@1	25.80	23.10	0.2042
77	30	60	632000	3480	DFT-s-OFDM 16 QAM	1@1	24.78	22.08	0.1614
77	30	60	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.66	22.96	0.1977
77	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.83	23.13	0.2056
77	30	60	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.92	22.22	0.1667
77	30	60	634666	3519.99	DFT-s-OFDM PI/2 BPSK	1@1	25.55	22.85	0.1928
77	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@1	25.51	22.81	0.1910
77	30	60	634666	3519.99	DFT-s-OFDM 16 QAM	1@1	24.63	21.93	0.1560



NR Band	SCS	BandWidth	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
77	30	70	632334	3485.01	DFT-s-OFDM PI/2 BPSK	1@1	25.87	23.17	0.2075
77	30	70	632334	3485.01	DFT-s-OFDM QPSK	1@1	25.92	23.22	0.2099
77	30	70	632334	3485.01	DFT-s-OFDM 16 QAM	1@1	24.97	22.27	0.1687
77	30	70	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.80	23.10	0.2042
77	30	70	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.85	23.15	0.2065
77	30	70	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.90	22.20	0.1660
77	30	70	634332	3514.98	DFT-s-OFDM PI/2 BPSK	1@1	25.78	23.08	0.2032
77	30	70	634332	3514.98	DFT-s-OFDM QPSK	1@1	25.85	23.15	0.2065
77	30	70	634332	3514.98	DFT-s-OFDM 16 QAM	1@1	24.83	22.13	0.1633
77	30	80	632668	3490.02	DFT-s-OFDM PI/2 BPSK	1@1	25.96	23.26	0.2118
77	30	80	632668	3490.02	DFT-s-OFDM QPSK	1@1	25.76	23.06	0.2023
77	30	80	632668	3490.02	DFT-s-OFDM 16 QAM	1@1	24.83	22.13	0.1633
77	30	80	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.88	23.18	0.2080
77	30	80	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.84	23.14	0.2061
77	30	80	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.05	22.35	0.1718
77	30	80	634000	3510	DFT-s-OFDM PI/2 BPSK	1@1	25.88	23.18	0.2080
77	30	80	634000	3510	DFT-s-OFDM QPSK	1@1	25.90	23.20	0.2089
77	30	80	634000	3510	DFT-s-OFDM 16 QAM	1@1	25.04	22.34	0.1714
77	30	90	633000	3495	DFT-s-OFDM PI/2 BPSK	1@1	25.87	23.17	0.2075
77	30	90	633000	3495	DFT-s-OFDM QPSK	1@1	25.86	23.16	0.2070
77	30	90	633000	3495	DFT-s-OFDM 16 QAM	1@1	24.71	22.01	0.1589
77	30	90	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.80	23.10	0.2042
77	30	90	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.83	23.13	0.2056
77	30	90	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	24.95	22.25	0.1679
77	30	90	633666	3504.99	DFT-s-OFDM PI/2 BPSK	1@1	25.85	23.15	0.2065
77	30	90	633666	3504.99	DFT-s-OFDM QPSK	1@1	25.89	23.19	0.2084
77	30	90	633666	3504.99	DFT-s-OFDM 16 QAM	1@1	25.04	22.34	0.1714
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	25.84	23.14	0.2061
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@0	22.20	19.50	0.0891
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@271	25.51	22.81	0.1910
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	2@0	22.24	19.54	0.0899
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	135@67	25.54	22.84	0.1923
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	2@271	21.92	19.22	0.0836
77	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	270@0	25.14	22.44	0.1754
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@1	25.79	23.09	0.2037
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	22.32	19.62	0.0916
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@271	25.53	22.83	0.1919
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	2@0	22.42	19.72	0.0938



NR Band	SCS	BandWidth	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	135@67	25.55	22.85	0.1928
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	2@271	22.13	19.43	0.0877
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	270@0	24.63	21.93	0.1560
77	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.05	22.35	0.1718
77	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	1@1	23.82	21.12	0.1294
77	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	1@1	21.02	18.32	0.0679
77	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	270@0	23.63	20.93	0.1239
77	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	270@0	23.13	20.43	0.1104
77	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	270@0	21.18	18.48	0.0705



Frequency Stability

Test Result


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0086	PASS	NV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0064	PASS	LV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0062	PASS	HV
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0000	PASS	-30°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0072	PASS	-20°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0065	PASS	-10°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0083	PASS	0°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0142	PASS	10°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0092	PASS	20°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0087	PASS	30°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0157	PASS	40°C
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0128	PASS	50°C

Peak to Average Ratio

Test Result

NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Result	Limit	Verdict
77	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	50@0	4.7	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@0	5.15	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	6.12	13	PASS
77	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@0	5.91	13	PASS

Test Graphs






Occupied Bandwidth


Test Result


NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	OBW(MHz)	26dB OBW(MHz)
77	30	10	633334	3500.01	CP-OFDM QPSK	24@0	8.56	9.147
77	30	10	633334	3500.01	CP-OFDM 16 QAM	24@0	8.59	9.121
77	30	15	633334	3500.01	CP-OFDM QPSK	38@0	13.57	14.37
77	30	15	633334	3500.01	CP-OFDM 16 QAM	38@0	13.58	14.38
77	30	20	633334	3500.01	CP-OFDM QPSK	51@0	18.21	18.99
77	30	20	633334	3500.01	CP-OFDM 16 QAM	51@0	18.19	18.87
77	30	25	633334	3500.01	CP-OFDM QPSK	65@0	23.17	24.0
77	30	25	633334	3500.01	CP-OFDM 16 QAM	65@0	23.22	24.22
77	30	30	633334	3500.01	CP-OFDM QPSK	78@0	27.8	28.73
77	30	30	633334	3500.01	CP-OFDM 16 QAM	78@0	27.82	28.98
77	30	40	633334	3500.01	CP-OFDM QPSK	106@0	37.82	39.01
77	30	40	633334	3500.01	CP-OFDM 16 QAM	106@0	37.67	39.06
77	30	50	633334	3500.01	CP-OFDM QPSK	133@0	47.34	49.19
77	30	50	633334	3500.01	CP-OFDM 16 QAM	133@0	47.31	49.22
77	30	60	633334	3500.01	CP-OFDM QPSK	162@0	57.77	59.58
77	30	60	633334	3500.01	CP-OFDM 16 QAM	162@0	57.72	59.61
77	30	70	633334	3500.01	CP-OFDM QPSK	189@0	67.44	69.62
77	30	70	633334	3500.01	CP-OFDM 16 QAM	189@0	67.35	69.58
77	30	80	633334	3500.01	CP-OFDM QPSK	217@0	77.35	79.81
77	30	80	633334	3500.01	CP-OFDM 16 QAM	217@0	77.48	79.68
77	30	90	633334	3500.01	CP-OFDM QPSK	245@0	87.27	89.99
77	30	90	633334	3500.01	CP-OFDM 16 QAM	245@0	87.33	90.12
77	30	100	633334	3500.01	CP-OFDM QPSK	273@0	97.29	100.4
77	30	100	633334	3500.01	CP-OFDM 16 QAM	273@0	97.35	100.4



Test Graphs










Conducted Spurious Emissions


Test Result

NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Result	Verdict
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	See graph	---
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	10	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	---
77	30	10	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@0	See graph	---
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	50	631668	3475.02	DFT-s-OFDM BPSK	1@0	See graph	---
77	30	50	631668	3475.02	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	50	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	---
77	30	50	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	50	635000	3525.0	DFT-s-OFDM BPSK	1@0	See graph	---
77	30	50	635000	3525.0	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	---
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	PASS



Test Graphs







Conducted Band Edge

Test Result

NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Result	Verdict
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	1@0	See graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM BPSK	24@0	See graph	PASS
77	30	10	630334	3455.01	DFT-s-OFDM QPSK	24@0	See graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@23	See graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	1@23	See graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM BPSK	24@0	See graph	PASS
77	30	10	636332	3544.98	DFT-s-OFDM QPSK	24@0	See graph	PASS
77	30	50	631668	3475.02	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	50	631668	3475.02	DFT-s-OFDM QPSK	1@0	See graph	PASS
77	30	50	631668	3475.02	DFT-s-OFDM BPSK	128@0	See graph	PASS
77	30	50	631668	3475.02	DFT-s-OFDM QPSK	128@0	See graph	PASS
77	30	50	635000	3525.0	DFT-s-OFDM BPSK	1@132	See graph	PASS
77	30	50	635000	3525.0	DFT-s-OFDM QPSK	1@132	See graph	PASS
77	30	50	635000	3525.0	DFT-s-OFDM BPSK	128@0	See graph	PASS
77	30	50	635000	3525.0	DFT-s-OFDM QPSK	128@0	See graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	See graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@272	See graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@272	See graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM BPSK	270@0	See graph	PASS
77	30	100	633334	3500.01	DFT-s-OFDM QPSK	270@0	See graph	PASS



Conducted Band Edge
Band 77 10MHz/3455.01/Low BPSK 1@0

Conducted Band Edge
Band 77 10MHz/3455.01/Low QPSK 1@0

Conducted Band Edge
Band 77 10MHz/3455.01/Low BPSK 24@0

Conducted Band Edge
Band 77 10MHz/3455.01/Low QPSK 24@0

Conducted Band Edge
Band 77 10MHz/3544.98/High BPSK 1@23


Conducted Band Edge
Band 77 10MHz/3544.98/High QPSK 1@23

Conducted Band Edge
Band 77 10MHz/3544.98/High BPSK 24@0

Conducted Band Edge
Band 77 10MHz/3544.98/High QPSK 24@0

Each screenshot displays a spectral plot with a sharp peak at 3.455 GHz. The plot includes a table of spurs and a 'PASS' status indicator. The spurs table lists the following data:

Spur	Range	Start Freq	Stop Freq	RBW	Frequency	Amplitude	Limit
1	1	3.4500 GHz	3.4550 GHz	1000 kHz	3.454700000 GHz	-10.12 dBm	-27.42 dBm
2	2	3.4450 GHz	3.4500 GHz	1000 kHz	3.448969697 GHz	-36.36 dBm	-23.36 dBm
3	3	3.4480 GHz	3.4500 GHz	1000 kHz	3.449000000 GHz	-31.47 dBm	-18.47 dBm
4	4	3.4500 GHz	3.5000 GHz	1000 kHz	3.490333333 GHz	-16.20 dBm	-13.80 dBm





**FR1 N78_ANT2****Transmitter Conducted Output Power And EIRP, (G_T - L_c)= -2.7dB**

NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
78	30	10	630334	3455.01	DFT-s-OFDM PI/2 BPSK	1@1	27.37	24.67	0.2931
78	30	10	630334	3455.01	DFT-s-OFDM QPSK	1@1	27.45	24.75	0.2985
78	30	10	630334	3455.01	DFT-s-OFDM 16 QAM	1@1	26.61	23.91	0.2460
78	30	10	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.95	24.25	0.2661
78	30	10	633334	3500.01	DFT-s-OFDM QPSK	1@1	26.92	24.22	0.2642
78	30	10	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.18	23.48	0.2228
78	30	10	636332	3544.98	DFT-s-OFDM PI/2 BPSK	1@1	27.12	24.42	0.2767
78	30	10	636332	3544.98	DFT-s-OFDM QPSK	1@1	27.07	24.37	0.2735
78	30	10	636332	3544.98	DFT-s-OFDM 16 QAM	1@1	26.48	23.78	0.2388
78	30	15	630500	3457.5	DFT-s-OFDM PI/2 BPSK	1@1	27.33	24.63	0.2904
78	30	15	630500	3457.5	DFT-s-OFDM QPSK	1@1	27.34	24.64	0.2911
78	30	15	630500	3457.5	DFT-s-OFDM 16 QAM	1@1	26.48	23.78	0.2388
78	30	15	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.02	24.32	0.2704
78	30	15	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.05	24.35	0.2723
78	30	15	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.88	23.18	0.2080
78	30	15	636166	3542.49	DFT-s-OFDM PI/2 BPSK	1@1	27.04	24.34	0.2716
78	30	15	636166	3542.49	DFT-s-OFDM QPSK	1@1	27.07	24.37	0.2735
78	30	15	636166	3542.49	DFT-s-OFDM 16 QAM	1@1	26.17	23.47	0.2223
78	30	20	630668	3460.02	DFT-s-OFDM PI/2 BPSK	1@1	27.34	24.64	0.2911
78	30	20	630668	3460.02	DFT-s-OFDM QPSK	1@1	27.43	24.73	0.2972
78	30	20	630668	3460.02	DFT-s-OFDM 16 QAM	1@1	26.51	23.81	0.2404
78	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	26.97	24.27	0.2673
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.08	24.38	0.2742
78	30	20	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	25.99	23.29	0.2133
78	30	20	636000	3540	DFT-s-OFDM PI/2 BPSK	1@1	26.97	24.27	0.2673
78	30	20	636000	3540	DFT-s-OFDM QPSK	1@1	27.09	24.39	0.2748
78	30	20	636000	3540	DFT-s-OFDM 16 QAM	1@1	25.93	23.23	0.2104
78	30	25	630834	3462.51	DFT-s-OFDM PI/2 BPSK	1@1	27.20	24.50	0.2818
78	30	25	630834	3462.51	DFT-s-OFDM QPSK	1@1	27.29	24.59	0.2877
78	30	25	630834	3462.51	DFT-s-OFDM 16 QAM	1@1	26.24	23.54	0.2259
78	30	25	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.06	24.36	0.2729
78	30	25	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.03	24.33	0.2710
78	30	25	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.19	23.49	0.2234
78	30	25	635832	3537.48	DFT-s-OFDM PI/2 BPSK	1@1	26.89	24.19	0.2624



NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
78	30	25	635832	3537.48	DFT-s-OFDM QPSK	1@1	26.95	24.25	0.2661
78	30	25	635832	3537.48	DFT-s-OFDM 16 QAM	1@1	26.12	23.42	0.2198
78	30	30	631000	3465	DFT-s-OFDM PI/2 BPSK	1@1	27.24	24.54	0.2844
78	30	30	631000	3465	DFT-s-OFDM QPSK	1@1	27.36	24.66	0.2924
78	30	30	631000	3465	DFT-s-OFDM 16 QAM	1@1	26.19	23.49	0.2234
78	30	30	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.19	24.49	0.2812
78	30	30	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.10	24.40	0.2754
78	30	30	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.04	23.34	0.2158
78	30	30	635666	3534.99	DFT-s-OFDM PI/2 BPSK	1@1	26.86	24.16	0.2606
78	30	30	635666	3534.99	DFT-s-OFDM QPSK	1@1	26.90	24.20	0.2630
78	30	30	635666	3534.99	DFT-s-OFDM 16 QAM	1@1	26.03	23.33	0.2153
78	30	40	631334	3470.01	DFT-s-OFDM PI/2 BPSK	1@1	27.31	24.61	0.2891
78	30	40	631334	3470.01	DFT-s-OFDM QPSK	1@1	27.38	24.68	0.2938
78	30	40	631334	3470.01	DFT-s-OFDM 16 QAM	1@1	26.37	23.67	0.2328
78	30	40	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.21	24.51	0.2825
78	30	40	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.15	24.45	0.2786
78	30	40	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.32	23.62	0.2301
78	30	40	635332	3529.98	DFT-s-OFDM PI/2 BPSK	1@1	26.85	24.15	0.2600
78	30	40	635332	3529.98	DFT-s-OFDM QPSK	1@1	26.80	24.10	0.2570
78	30	40	635332	3529.98	DFT-s-OFDM 16 QAM	1@1	25.91	23.21	0.2094
78	30	50	631668	3475.02	DFT-s-OFDM PI/2 BPSK	1@1	27.30	24.60	0.2884
78	30	50	631668	3475.02	DFT-s-OFDM QPSK	1@1	27.29	24.59	0.2877
78	30	50	631668	3475.02	DFT-s-OFDM 16 QAM	1@1	26.47	23.77	0.2382
78	30	50	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.17	24.47	0.2799
78	30	50	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.23	24.53	0.2838
78	30	50	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.38	23.68	0.2333
78	30	50	635000	3525	DFT-s-OFDM PI/2 BPSK	1@1	26.91	24.21	0.2636
78	30	50	635000	3525	DFT-s-OFDM QPSK	1@1	26.85	24.15	0.2600
78	30	50	635000	3525	DFT-s-OFDM 16 QAM	1@1	26.05	23.35	0.2163
78	30	60	632000	3480	DFT-s-OFDM PI/2 BPSK	1@1	27.27	24.57	0.2864
78	30	60	632000	3480	DFT-s-OFDM QPSK	1@1	27.30	24.60	0.2884
78	30	60	632000	3480	DFT-s-OFDM 16 QAM	1@1	26.35	23.65	0.2317
78	30	60	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.26	24.56	0.2858
78	30	60	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.17	24.47	0.2799
78	30	60	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.38	23.68	0.2333
78	30	60	634666	3519.99	DFT-s-OFDM PI/2 BPSK	1@1	27.00	24.30	0.2692
78	30	60	634666	3519.99	DFT-s-OFDM QPSK	1@1	27.04	24.34	0.2716
78	30	60	634666	3519.99	DFT-s-OFDM 16 QAM	1@1	26.16	23.46	0.2218



NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
78	30	70	632334	3485.01	DFT-s-OFDM PI/2 BPSK	1@1	27.31	24.61	0.2891
78	30	70	632334	3485.01	DFT-s-OFDM QPSK	1@1	27.30	24.60	0.2884
78	30	70	632334	3485.01	DFT-s-OFDM 16 QAM	1@1	26.27	23.57	0.2275
78	30	70	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.25	24.55	0.2851
78	30	70	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.22	24.52	0.2831
78	30	70	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.29	23.59	0.2286
78	30	70	634332	3514.98	DFT-s-OFDM PI/2 BPSK	1@1	27.17	24.47	0.2799
78	30	70	634332	3514.98	DFT-s-OFDM QPSK	1@1	27.19	24.49	0.2812
78	30	70	634332	3514.98	DFT-s-OFDM 16 QAM	1@1	26.30	23.60	0.2291
78	30	80	632668	3490.02	DFT-s-OFDM PI/2 BPSK	1@1	27.26	24.56	0.2858
78	30	80	632668	3490.02	DFT-s-OFDM QPSK	1@1	27.36	24.66	0.2924
78	30	80	632668	3490.02	DFT-s-OFDM 16 QAM	1@1	26.30	23.60	0.2291
78	30	80	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.28	24.58	0.2871
78	30	80	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.19	24.49	0.2812
78	30	80	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.48	23.78	0.2388
78	30	80	634000	3510	DFT-s-OFDM PI/2 BPSK	1@1	27.27	24.57	0.2864
78	30	80	634000	3510	DFT-s-OFDM QPSK	1@1	27.30	24.60	0.2884
78	30	80	634000	3510	DFT-s-OFDM 16 QAM	1@1	26.44	23.74	0.2366
78	30	90	633000	3495	DFT-s-OFDM PI/2 BPSK	1@1	27.27	24.57	0.2864
78	30	90	633000	3495	DFT-s-OFDM QPSK	1@1	27.31	24.61	0.2891
78	30	90	633000	3495	DFT-s-OFDM 16 QAM	1@1	26.33	23.63	0.2307
78	30	90	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.20	24.50	0.2818
78	30	90	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.25	24.55	0.2851
78	30	90	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.32	23.62	0.2301
78	30	90	633666	3504.99	DFT-s-OFDM PI/2 BPSK	1@1	27.26	24.56	0.2858
78	30	90	633666	3504.99	DFT-s-OFDM QPSK	1@1	27.25	24.55	0.2851
78	30	90	633666	3504.99	DFT-s-OFDM 16 QAM	1@1	26.21	23.51	0.2244
78	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.26	24.56	0.2858
78	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@0	23.69	20.99	0.1256
78	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@271	27.03	24.33	0.2710
78	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	2@0	23.76	21.06	0.1276
78	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	135@67	27.03	24.33	0.2710
78	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	2@271	23.56	20.86	0.1219
78	30	100	633334	3500.01	DFT-s-OFDM PI/2 BPSK	270@0	26.52	23.82	0.2410
78	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@1	27.29	24.59	0.2877
78	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@0	23.68	20.98	0.1253
78	30	100	633334	3500.01	DFT-s-OFDM QPSK	1@271	27.04	24.34	0.2716
78	30	100	633334	3500.01	DFT-s-OFDM QPSK	2@0	23.82	21.12	0.1294



NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
78	30	100	633334	3500.01	DFT-s-OFDM QPSK	135@67	27.05	24.35	0.2723
78	30	100	633334	3500.01	DFT-s-OFDM QPSK	2@271	23.51	20.81	0.1205
78	30	100	633334	3500.01	DFT-s-OFDM QPSK	270@0	26.10	23.40	0.2188
78	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	1@1	26.34	23.64	0.2312
78	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	1@1	24.78	22.08	0.1614
78	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	1@1	22.55	19.85	0.0966
78	30	100	633334	3500.01	DFT-s-OFDM 16 QAM	270@0	25.05	22.35	0.1718
78	30	100	633334	3500.01	DFT-s-OFDM 64 QAM	270@0	24.59	21.89	0.1545
78	30	100	633334	3500.01	DFT-s-OFDM 256 QAM	270@0	22.60	19.90	0.0977



Frequency Stability

Test Result


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0092	PASS	NV
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0037	PASS	LV
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0086	PASS	HV
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0000	PASS	-30°C
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0051	PASS	-20°C
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0127	PASS	-10°C
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0113	PASS	0°C
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0142	PASS	10°C
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0138	PASS	20°C
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0071	PASS	30°C
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0146	PASS	40°C
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	0.0145	PASS	50°C

Peak to Average Ratio

Test Result

NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Result	Limit	Verdict
78	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	50@0	4.51	13	PASS
78	30	20	633334	3500.01	DFT-s-OFDM PI/2 BPSK	1@0	4.97	13	PASS
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	50@0	6.45	13	PASS
78	30	20	633334	3500.01	DFT-s-OFDM QPSK	1@0	5.68	13	PASS

Test Graphs






Occupied Bandwidth


Test Result


NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	OBW(MHz)	26dB OBW(MHz)
78	30	10	633334	3500.01	CP-OFDM QPSK	24@0	8.57	9.317
78	30	10	633334	3500.01	CP-OFDM 16 QAM	24@0	8.57	9.133
78	30	15	633334	3500.01	CP-OFDM QPSK	38@0	13.56	14.35
78	30	15	633334	3500.01	CP-OFDM 16 QAM	38@0	13.6	14.44
78	30	20	633334	3500.01	CP-OFDM QPSK	51@0	18.18	18.92
78	30	20	633334	3500.01	CP-OFDM 16 QAM	51@0	18.24	19.13
78	30	25	633334	3500.01	CP-OFDM QPSK	65@0	23.16	24.24
78	30	25	633334	3500.01	CP-OFDM 16 QAM	65@0	23.19	24.14
78	30	30	633334	3500.01	CP-OFDM QPSK	78@0	27.8	28.81
78	30	30	633334	3500.01	CP-OFDM 16 QAM	78@0	27.76	28.9
78	30	40	633334	3500.01	CP-OFDM QPSK	106@0	37.71	39.03
78	30	40	633334	3500.01	CP-OFDM 16 QAM	106@0	37.81	39.14
78	30	50	633334	3500.01	CP-OFDM QPSK	133@0	47.36	49.17
78	30	50	633334	3500.01	CP-OFDM 16 QAM	133@0	47.36	49.17
78	30	60	633334	3500.01	CP-OFDM QPSK	162@0	57.85	59.65
78	30	60	633334	3500.01	CP-OFDM 16 QAM	162@0	57.8	59.55
78	30	70	633334	3500.01	CP-OFDM QPSK	189@0	67.32	69.56
78	30	70	633334	3500.01	CP-OFDM 16 QAM	189@0	67.41	69.56
78	30	80	633334	3500.01	CP-OFDM QPSK	217@0	77.4	79.82
78	30	80	633334	3500.01	CP-OFDM 16 QAM	217@0	77.44	79.66
78	30	90	633334	3500.01	CP-OFDM QPSK	245@0	87.32	90.14
78	30	90	633334	3500.01	CP-OFDM 16 QAM	245@0	87.28	89.99
78	30	100	633334	3500.01	CP-OFDM QPSK	273@0	97.33	100.2
78	30	100	633334	3500.01	CP-OFDM 16 QAM	273@0	97.39	100.2



Test Graphs









Conducted Spurious Emissions

Test Result

NR Band	SCS	BandWidth	Arfcn	Freq(MHz)	Modulation	RB	Result	Verdict
78	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	See graph	---
78	30	10	630334	3455.01	DFT-s-OFDM BPSK	1@0	See graph	PASS
78	30	10	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	---
78	30	10	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	PASS
78	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@0	See graph	---
78	30	10	636332	3544.98	DFT-s-OFDM BPSK	1@0	See graph	PASS
78	30	50	631668	3475.02	DFT-s-OFDM BPSK	1@0	See graph	---
78	30	50	631668	3475.02	DFT-s-OFDM BPSK	1@0	See graph	PASS
78	30	50	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	---
78	30	50	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	PASS
78	30	50	635000	3525.0	DFT-s-OFDM BPSK	1@0	See graph	---
78	30	50	635000	3525.0	DFT-s-OFDM BPSK	1@0	See graph	PASS
78	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	---
78	30	100	633334	3500.01	DFT-s-OFDM BPSK	1@0	See graph	PASS



Test Graphs

