

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700332807

Page: 1 of 179

TEST REPORT

Application No.: SZCR2507003328WM
Applicant: Xiaomi Communications Co., Ltd.
Address of Applicant: #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer: Xiaomi Communications Co., Ltd.
Address of Manufacturer: #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Equipment Under Test (EUT):
EUT Description: Mobile Phone
Model No.: 2510EPC8BG
Trade Mark: POCO
FCC ID: 2AFZZPC8BG
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-07-28
Date of Test: 2025-08-19 to 2025-08-27
Date of Issue: 2025-09-04

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kenx. Xu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (EMC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Member of the SGS Group (SGS SA)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700332807

Page: 2 of 179

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2025-09-04		Original

Authorized for issue by:				
		Kevin Lan		
		Kevin Lan/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Peak Output Power		ANSI C63.10 (2020) Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth		ANSI C63.10 (2020) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density		ANSI C63.10 (2020) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Band Edges Measurement		ANSI C63.10 (2020) Section 6.10.4	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Spurious Emissions		ANSI C63.10 (2020) Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass



3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Environment Parameter	7
4.3 Description of Support Units	8
4.4 Measurement Uncertainty	8
4.5 Test Location	9
4.6 Test Facility	9
4.7 Deviation from Standards	9
4.8 Abnormalities from Standard Conditions	9
5 Equipment List	10
6 Radio Spectrum Technical Requirement	12
6.1 Antenna Requirement	12
6.1.1 Test Requirement:	12
7 Radio Spectrum Matter Test Results	13
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	13
7.1.1 E.U.T. Operation	13
7.1.2 Test Mode Description	13
7.1.3 Test Setup Diagram	14
7.1.4 Measurement Procedure and Data	14
7.2 Radiated Emissions which fall in the restricted bands	17
7.2.1 E.U.T. Operation	17
7.2.2 Test Setup Diagram	17
7.2.3 Measurement Procedure and Data	18
7.3 Radiated Spurious Emissions Below 1GHz	51
7.3.1 E.U.T. Operation	51
7.3.2 Test Mode Description	51
7.3.3 Test Setup Diagram	52
7.3.4 Measurement Procedure and Data	52
7.4 Radiated Spurious Emissions Above 1GHz	55
7.4.1 E.U.T. Operation	55
7.4.2 Test Mode Description	55
7.4.3 Test Setup Diagram	55
7.4.4 Measurement Procedure and Data	56
7.5 Conducted Peak Output Power	105
7.5.1 E.U.T. Operation	105
7.5.2 Test Mode Description	105



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700332807

Page: 5 of 179

7.5.3	Test Setup Diagram	105
7.5.4	Measurement Procedure and Data.....	106
7.6	Minimum 6dB Bandwidth	107
7.6.1	E.U.T. Operation	107
7.6.2	Test Mode Description	107
7.6.3	Test Setup Diagram	107
7.6.4	Measurement Procedure and Data.....	107
7.7	Power Spectrum Density	108
7.7.1	E.U.T. Operation	108
7.7.2	Test Mode Description	108
7.7.3	Test Setup Diagram	108
7.7.4	Measurement Procedure and Data.....	108
7.8	Conducted Band Edges Measurement	109
7.8.1	E.U.T. Operation	109
7.8.2	Test Mode Description	109
7.8.3	Test Setup Diagram	109
7.8.4	Measurement Procedure and Data.....	109
7.9	Conducted Spurious Emissions	110
7.9.1	E.U.T. Operation	110
7.9.2	Test Mode Description	110
7.9.3	Test Setup Diagram	110
7.9.4	Measurement Procedure and Data.....	110
8	Test Setup Photo	111
9	EUT Constructional Details (EUT Photos)	111
10	Appendix.....	112



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center (EMC) Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

EUT Description:	Mobile Phone
Model No.:	2510EPC8BG
Trade Mark:	POCO
Hardware Version:	13510P16U
Software Version:	Xiaomi HyperOS 2.0
Power Supply:	DC 3.83V from internal rechargeable battery which can be charge by AC/DC adapter
Operation Frequency:	2400MHz~2483.5MHz fc = 2402 MHz + N * 2 MHz, where: -fc = "Operating Frequency" in MHz, -N = "Channel Number" with the range from 0 to 39.
Bluetooth version:	Bluetooth V5.4
Modulation Type:	GFSK
Number of Channel:	40
Rates Type*:	☒ Provided by client
	125k/500k/1M/2M
Antenna Type:	PIFA Antenna
Antenna Gain:	-3.5dBi(Ant13), -3.3dBi(Ant12)
	Note: The antenna gain are derived from the gain information report provided by the manufacturer.
RF Cable:	2000MHz ~ 3000MHz (1.1dB)
Note: *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , SGS is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.	
Remark: As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.	



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700332807

Page: 7 of 179

Operation Frequency of each channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	10	2422MHz	20	2442MHz	30	2462MHz
1	2404MHz	11	2424MHz	21	2444MHz	31	2464MHz
2	2406MHz	12	2426MHz	22	2446MHz	32	2466MHz
3	2408MHz	13	2428MHz	23	2448MHz	33	2468MHz
4	2410MHz	14	2430MHz	24	2450MHz	34	2470MHz
5	2412MHz	15	2432MHz	25	2452MHz	35	2472MHz
6	2414MHz	16	2434MHz	26	2454MHz	36	2474MHz
7	2416MHz	17	2436MHz	27	2456MHz	37	2476MHz
8	2418MHz	18	2438MHz	28	2458MHz	38	2478MHz
9	2420MHz	19	2440MHz	29	2460MHz	39	2480MHz

Remark:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
BLE 1M:	
The Lowest channel(CH0)	2402MHz
The Middle channel(CH19)	2440MHz
The Highest channel(CH39)	2480MHz
BLE 2M:	
The Lowest channel(CH1)	2404MHz
The Middle channel(CH19)	2440MHz
The Highest channel(CH38)	2478MHz

4.2 Environment Parameter

Environment Parameter	1020 mbar Selected Values During Tests	
Relative Humidity	40.5-61.9 % RH Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	19.7~25.3	3.83

Note:

NV:Normal Voltage LV:Low Extreme Test Voltage HV:High Extreme Test Voltage
NT:Normal Temperature LT:Low Extreme Test Temperature HT:High Extreme Test Temperature



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

4.4 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.1\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Peak Output Power	$\pm 0.75\text{dB}$
Minimum 6dB Bandwidth	$\pm 3\%$
Power Spectrum Density	$\pm 2.84\text{dB}$
Conducted Band Edges Measurement	$\pm 0.75\text{dB}$
Conducted Spurious Emissions	$\pm 0.75\text{dB}$
Remark: The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.	

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700332807

Page: 9 of 179

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-01-08	2026-01-07
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-01-07	2026-01-06
Low Noise Amplifier 30M-8GHz	Tonscend	TAP30M8G30	SZ-WRG-M-050	2025-01-07	2026-01-06
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2023-12-21	2025-12-20
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2023-11-20	2025-11-19
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2023-09-16	2025-09-15
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700332807

Page: 11 of 179

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-01-07	2026-01-06
Low Noise Amplifier 1G-18GHz	Tonscend	TAP01018050	SZ-WRG-M-051	2025-01-07	2026-01-06
Low Noise Amplifier 18G-40GHz	Tonscend	TAP18040048	SZ-WRG-M-052	2025-01-08	2026-01-07
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2023-12-21	2025-12-20
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2023-12-25	2025-12-24
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch Laboratory
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

The antenna is PIFA Antenna and no consideration of replacement. The best case gain of the antenna is -3.5dBi(Ant13); -3.3dBi(Ant12).

Note:

The antenna gain are derived from the gain information report provided by the manufacturer.

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C

Humidity: 40.5 % RH


Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark : Level=Read Level+ Cable Loss+ LISN Factor



Test Mode: 02; Line: Live line




Site : Shielding Room
Condition: Line
Job No. : 03328WM
Test mode: 02

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1565	0.05	10.18	32.08	42.31	65.65	-23.34	QP
2	0.1565	0.05	10.18	19.08	29.31	55.65	-26.34	Average
3	0.5350	0.08	9.56	24.36	34.00	56.00	-22.00	QP
4	0.5350	0.08	9.56	9.80	19.44	46.00	-26.56	Average
5 *	0.6613	0.09	9.63	32.98	42.70	56.00	-13.30	QP
6 *	0.6613	0.09	9.63	21.92	31.64	46.00	-14.36	Average
7	1.0997	0.10	9.58	20.77	30.45	56.00	-25.55	QP
8	1.0997	0.10	9.58	5.63	15.31	46.00	-30.69	Average
9	1.7623	0.11	9.58	14.56	24.25	56.00	-31.75	QP
10	1.7623	0.11	9.58	1.20	10.89	46.00	-35.11	Average
11	4.8480	0.13	9.66	20.74	30.53	56.00	-25.47	QP
12	4.8480	0.13	9.66	10.72	20.51	46.00	-25.49	Average



Test Mode: 02; Line: Neutral Line



Site : Shielding Room
Condition: Neutral
Job No. : 03328WM
Test mode: 02

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1532	0.05	10.15	31.60	41.80	65.82	-24.02	QP
2	0.1532	0.05	10.15	20.35	30.55	55.82	-25.27	Average
3	0.5238	0.08	9.70	25.71	35.49	56.00	-20.51	QP
4	0.5238	0.08	9.70	10.69	20.47	46.00	-25.53	Average
5 *	0.6683	0.09	9.66	33.38	43.13	56.00	-12.87	QP
6 *	0.6683	0.09	9.66	20.09	29.84	46.00	-16.16	Average
7	1.3098	0.11	9.54	21.10	30.75	56.00	-25.25	QP
8	1.3098	0.11	9.54	6.75	16.40	46.00	-29.60	Average
9	1.7716	0.11	9.55	18.23	27.89	56.00	-28.11	QP
10	1.7716	0.11	9.55	4.46	14.12	46.00	-31.88	Average
11	4.6964	0.13	9.56	21.66	31.35	56.00	-24.65	QP
12	4.6964	0.13	9.56	12.06	21.75	46.00	-24.25	Average



7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation


Operating Environment:

Temperature: 24.5 °C


Humidity: 50.8 % RH

Atmospheric Pressure: 1020 mbar

7.2.2 Test Setup Diagram



30MHz-1GHz



Above 1GHz

7.2.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



BLE_1M_TX_CH_00_Horizontal -Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE 1M AMT13

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2355.773	6.81	27.32	30.68	46.98	50.43	74.00	-23.57 peak
2	2390.000	6.83	27.46	30.69	45.14	48.74	74.00	-25.26 peak
3	2402.000	6.84	27.50	30.69	106.35	110.00	74.00	36.00 peak



BLE_1M_TX_CH_00_Vertical -Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE 1M AMT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 2381.168	6.82	27.42	30.69	47.22	50.77	74.00	-23.23	peak
2 2390.000	6.83	27.46	30.69	45.83	49.43	74.00	-24.57	peak
3 pp 2402.000	6.84	27.50	30.69	104.33	107.98	74.00	33.98	peak



BLE_1M_TX_CH_39_Horizontal -Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE 1M AMT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	104.06	108.51	74.00	34.51	peak
2	av 2483.500	7.40	27.80	30.71	35.78	40.27	54.00	-13.73	Average
3	2483.500	7.40	27.80	30.71	54.06	58.55	74.00	-15.45	peak
4	2483.871	7.40	27.80	30.71	34.95	39.44	54.00	-14.56	Average
5	2483.871	7.40	27.80	30.71	52.86	57.35	74.00	-16.65	peak



BLE_1M_TX_CH_39_Vertical -Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE 1M AMT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	99.72	104.17	74.00	30.17	peak
2	av 2483.500	7.40	27.80	30.71	33.88	38.37	54.00	-15.63	Average
3	2483.500	7.40	27.80	30.71	50.38	54.87	74.00	-19.13	peak
4	2483.896	7.40	27.80	30.71	49.47	53.96	74.00	-20.04	peak



BLE_2M_TX_CH_01_Horizontal -Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2404 Band edge

: BLE 2M AMT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2361.371	6.81	27.35	30.68	47.23	50.71	74.00	-23.29	peak
2	2390.000	6.83	27.46	30.69	45.67	49.27	74.00	-24.73	peak
3 pp	2404.000	6.86	27.51	30.69	106.45	110.13	74.00	36.13	peak



BLE_2M_TX_CH_01_Vertical -Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2404 Band edge

: BLE 2M AMT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2376.833	6.82	27.41	30.69	47.01	50.55	74.00	-23.45 peak
2	2390.000	6.83	27.46	30.69	44.81	48.41	74.00	-25.59 peak
3	2404.000	6.86	27.51	30.69	104.32	108.00	74.00	34.00 peak



BLE_2M_TX_CH_38_Horizontal -Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2478 Band edge

: BLE 2M AMT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2478.000	7.36	27.77	30.71	103.26	107.68	74.00	33.68	peak
2	2483.500	7.40	27.80	30.71	46.91	51.40	74.00	-22.60	peak
3	2484.820	7.41	27.81	30.71	47.57	52.08	74.00	-21.92	peak



BLE_2M_TX_CH_38_Vertical -Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2478 Band edge

: BLE 2M AMT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2478.000	7.36	27.77	30.71	102.40	106.82	74.00	32.82	peak
2	2483.500	7.40	27.80	30.71	45.35	49.84	74.00	-24.16	peak
3	2490.871	7.45	27.85	30.71	47.10	51.69	74.00	-22.31	peak



BLE_PHY_S=8_TX_CH_00_Horizontal -Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE PHY S=8 ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 2335.792	6.80	27.27	30.68	47.39	50.78	74.00	-23.22	peak
2 2390.000	6.83	27.46	30.69	44.20	47.80	74.00	-26.20	peak
3 pp 2402.000	6.84	27.50	30.69	104.05	107.70	74.00	33.70	peak



BLE_PHY_S=8_TX_CH_00_Vertical -Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE PHY S=8 ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 2371.500	6.82	27.39	30.68	46.57	50.10	74.00	-23.90	peak
2 2390.000	6.83	27.46	30.69	45.13	48.73	74.00	-25.27	peak
3 pp 2402.000	6.84	27.50	30.69	104.43	108.08	74.00	34.08	peak



BLE_PHY_S=8_TX_CH_39_Horizontal -Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE PHY S=8 ANT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	102.15	106.60	74.00	32.60	peak
2	av 2483.500	7.40	27.80	30.71	34.16	38.65	54.00	-15.35	Average
3	2483.500	7.40	27.80	30.71	52.00	56.49	74.00	-17.51	peak
4	2483.896	7.40	27.80	30.71	33.89	38.38	54.00	-15.62	Average
5	2483.896	7.40	27.80	30.71	50.73	55.22	74.00	-18.78	peak



BLE_PHY_S=8_TX_CH_39_Vertical -Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE PHY S=8 ANT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	101.94	106.39	74.00	32.39	peak
2	2483.500	7.40	27.80	30.71	48.64	53.13	74.00	-20.87	peak
3	av 2483.971	7.40	27.80	30.71	33.88	38.37	54.00	-15.63	Average
4	2483.971	7.40	27.80	30.71	50.20	54.69	74.00	-19.31	peak



BLE_PHY_S=2_TX_CH_00_Horizontal -Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE PHY S=2 ANT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2383.894	6.82	27.44	30.69	46.56	50.13	74.00	-23.87	peak
2	2390.000	6.83	27.46	30.69	44.72	48.32	74.00	-25.68	peak
3 pp	2402.000	6.84	27.50	30.69	105.54	109.19	74.00	35.19	peak



BLE_PHY_S=2_TX_CH_00_Vertical -Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE PHY S=2 ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 2345.016	6.80	27.29	30.68	47.19	50.60	74.00	-23.40	peak
2 2390.000	6.83	27.46	30.69	44.99	48.59	74.00	-25.41	peak
3 pp 2402.000	6.84	27.50	30.69	104.84	108.49	74.00	34.49	peak



BLE_PHY_S=2_TX_CH_39_Horizontal -Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE PHY S=2 ANT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	104.51	108.96	74.00	34.96	peak
2	av 2483.500	7.40	27.80	30.71	34.90	39.39	54.00	-14.61	Average
3	2483.500	7.40	27.80	30.71	55.54	60.03	74.00	-13.97	peak
4	2483.921	7.40	27.80	30.71	34.63	39.12	54.00	-14.88	Average
5	2483.921	7.40	27.80	30.71	52.95	57.44	74.00	-16.56	peak



BLE_PHY_S=2_TX_CH_39_Vertical -Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE PHY S=2 ANT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	100.57	105.02	74.00	31.02	peak
2	2483.500	7.40	27.80	30.71	33.33	37.82	54.00	-16.18	Average
3	2483.500	7.40	27.80	30.71	50.00	54.49	74.00	-19.51	peak
4	av 2484.520	7.41	27.81	30.71	33.49	38.00	54.00	-16.00	Average
5	2484.520	7.41	27.81	30.71	50.98	55.49	74.00	-18.51	peak



BLE_1M_TX_CH_00_Horizontal -Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE 1M ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2378.949	6.82	27.42	30.69	47.00	50.55	74.00	-23.45	peak
2	2390.000	6.83	27.46	30.69	45.79	49.39	74.00	-24.61	peak
3 pp	2402.000	6.84	27.50	30.69	100.73	104.38	74.00	30.38	peak



BLE_1M_TX_CH_00_Vertical -Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE 1M ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2371.701	6.82	27.39	30.68	47.13	50.66	74.00	-23.34	peak
2	2390.000	6.83	27.46	30.69	45.07	48.67	74.00	-25.33	peak
3 pp	2402.000	6.84	27.50	30.69	106.31	109.96	74.00	35.96	peak



BLE_1M_TX_CH_39_Horizontal -Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE 1M ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	98.96	103.41	74.00	29.41	peak
2	2483.500	7.40	27.80	30.71	33.91	38.40	54.00	-15.60	Average
3	2483.500	7.40	27.80	30.71	50.68	55.17	74.00	-18.83	peak
4	av 2483.871	7.40	27.80	30.71	34.03	38.52	54.00	-15.48	Average
5	2483.871	7.40	27.80	30.71	49.55	54.04	74.00	-19.96	peak



BLE_1M_TX_CH_39_Vertical -Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE 1M ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	105.24	109.69	74.00	35.69	peak
2	av 2483.500	7.40	27.80	30.71	35.26	39.75	54.00	-14.25	Average
3	2483.500	7.40	27.80	30.71	55.36	59.85	74.00	-14.15	peak
4	2483.821	7.40	27.80	30.71	35.02	39.51	54.00	-14.49	Average
5	2483.821	7.40	27.80	30.71	54.00	58.49	74.00	-15.51	peak



BLE_2M_TX_CH_01_Horizontal -Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2404 Band edge

: BLE 2M ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2348.198	6.80	27.30	30.68	47.11	50.53	74.00	-23.47 peak
2	2390.000	6.83	27.46	30.69	44.59	48.19	74.00	-25.81 peak
3	pp 2404.000	6.86	27.51	30.69	100.62	104.30	74.00	30.30 peak



BLE_2M_TX_CH_01_Vertical -Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2404 Band edge

: BLE 2M ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2370.696	6.82	27.38	30.68	46.43	49.95	74.00	-24.05 peak
2	2390.000	6.83	27.46	30.69	46.20	49.80	74.00	-24.20 peak
3	pp 2404.000	6.86	27.51	30.69	105.76	109.44	74.00	35.44 peak



BLE_2M_TX_CH_38_Horizontal -Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2478 Band edge

: BLE 2M ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2478.000	7.36	27.77	30.71	99.42	103.84	74.00	29.84	peak
2	2483.500	7.40	27.80	30.71	44.58	49.07	74.00	-24.93	peak
3	2494.328	7.47	27.87	30.71	46.59	51.22	74.00	-22.78	peak



BLE_2M_TX_CH_38_Vertical -Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2478 Band edge

: BLE 2M ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2478.000	7.36	27.77	30.71	106.12	110.54	74.00	36.54	peak
2	2483.500	7.40	27.80	30.71	48.91	53.40	74.00	-20.60	peak
3	2483.846	7.40	27.80	30.71	48.57	53.06	74.00	-20.94	peak



BLE_PHY_S=8_TX_CH_00_Horizontal -Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE PHY S=8 ANT12

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2379.554	6.82	27.42	30.69	47.04	50.59	74.00	-23.41	peak
2	2390.000	6.83	27.46	30.69	45.42	49.02	74.00	-24.98	peak
3 pp	2402.000	6.84	27.50	30.69	99.58	103.23	74.00	29.23	peak



BLE_PHY_S=8_TX_CH_00_Vertical -Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE PHY S=8 ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2385.612	6.82	27.44	30.69	46.31	49.88	74.00	-24.12 peak
2	2390.000	6.83	27.46	30.69	44.82	48.42	74.00	-25.58 peak
3 pp	2402.000	6.84	27.50	30.69	105.53	109.18	74.00	35.18 peak



BLE_PHY_S=8_TX_CH_39_Horizontal -Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE PHY S=8 ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	98.69	103.14	74.00	29.14	peak
2	av 2483.500	7.40	27.80	30.71	33.36	37.85	54.00	-16.15	Average
3	2483.500	7.40	27.80	30.71	50.38	54.87	74.00	-19.13	peak
4	2484.246	7.40	27.81	30.71	46.86	51.36	74.00	-22.64	peak



BLE_PHY_S=8_TX_CH_39_Vertical -Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE PHY S=8 ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	104.86	109.31	74.00	35.31	peak
2	av 2483.500	7.40	27.80	30.71	34.96	39.45	54.00	-14.55	Average
3	2483.500	7.40	27.80	30.71	55.03	59.52	74.00	-14.48	peak
4	2483.871	7.40	27.80	30.71	34.72	39.21	54.00	-14.79	Average
5	2483.871	7.40	27.80	30.71	53.91	58.40	74.00	-15.60	peak



BLE_PHY_S=2_TX_CH_00_Horizontal -Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE PHY S=2 ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.659	6.82	27.46	30.69	46.97	50.56	74.00	-23.44	peak
2	2390.000	6.83	27.46	30.69	45.54	49.14	74.00	-24.86	peak
3 pp	2402.000	6.84	27.50	30.69	100.14	103.79	74.00	29.79	peak



BLE_PHY_S=2_TX_CH_00_Vertical -Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 Band edge

: BLE PHY S=2 ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2365.277	6.81	27.36	30.68	46.99	50.48	74.00	-23.52 peak
2	2390.000	6.83	27.46	30.69	45.10	48.70	74.00	-25.30 peak
3	2402.000	6.84	27.50	30.69	105.72	109.37	74.00	35.37 peak



BLE_PHY_S=2_TX_CH_39_Horizontal -Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 Band edge

: BLE PHY S=2 ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 pp	2480.000	7.38	27.78	30.71	98.37	102.82	74.00	28.82	peak
2	2483.500	7.40	27.80	30.71	46.66	51.15	74.00	-22.85	peak
3	2484.271	7.40	27.81	30.71	47.84	52.34	74.00	-21.66	peak



BLE_PHY_S=2_TX_CH_39_Vertical -Ant12



Condition: 3m VERTICAL

Job No : 03328WM

Mode : 2480 Band edge

: BLE PHY S=2 ANT12

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2480.000	7.38	27.78	30.71	105.17	109.62	74.00	35.62	peak
2	av 2483.500	7.40	27.80	30.71	34.73	39.22	54.00	-14.78	Average
3	2483.500	7.40	27.80	30.71	54.58	59.07	74.00	-14.93	peak
4	2483.821	7.40	27.80	30.71	34.41	38.90	54.00	-15.10	Average
5	2483.821	7.40	27.80	30.71	55.00	59.49	74.00	-14.51	peak



7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23.4 °C

Humidity: 42.5 % RH


Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE)_Keep the EUT in continuously transmitting mode with GFSK modulation.



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 02; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL


Job No. : 03328WM

Test Mode: 02

	Ant	Cable	Preamp	Read		Limit	Over	
Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	30.105	21.15	0.74	27.65	27.45	21.69	40.00	-18.31 QP
2	89.905	11.72	1.18	27.60	28.35	13.65	43.50	-29.85 QP
3	104.170	12.22	1.25	27.61	35.96	21.82	43.50	-21.68 QP
4	311.087	18.41	2.16	27.53	31.75	24.79	46.00	-21.21 QP
5	672.845	25.64	3.33	27.90	26.07	27.14	46.00	-18.86 QP
6 q	766.057	26.59	3.60	27.68	28.23	30.74	46.00	-15.26 QP



Test Mode: 02; Polarity: Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : 03328WM
Test Mode: 02

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	q	30.000	21.20	0.74	27.65	33.57	27.86	40.00	-12.14 QP
2		78.413	10.40	1.08	27.61	39.72	23.59	40.00	-16.41 QP
3		163.182	13.33	1.56	27.74	38.41	25.56	43.50	-17.94 QP
4		400.432	20.60	2.49	27.75	26.58	21.92	46.00	-24.08 QP
5		679.960	25.86	3.35	27.88	25.03	26.36	46.00	-19.64 QP
6		942.131	28.19	4.06	26.72	24.96	30.49	46.00	-15.51 QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209

Test Method: ANSI C63.10 (2020) Section 6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24.5 °C


Humidity: 50.8 % RH

Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $\leq 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.



BLE_1M_TX_CH_00_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE 1M ANT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1155.483	7.15	25.39	54.78	54.76	32.52	74.00	-41.48	peak
2	4304.400	8.45	31.30	55.16	54.39	38.98	74.00	-35.02	peak
3 pp	4804.000	8.90	31.92	55.41	61.17	46.58	74.00	-27.42	peak
4	6432.732	10.56	34.80	56.31	54.92	43.97	74.00	-30.03	peak
5	7206.000	11.10	36.60	56.73	52.31	43.28	74.00	-30.72	peak
6	9608.000	12.38	38.78	55.93	49.53	44.76	74.00	-29.24	peak



BLE_1M_TX_CH_00_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE 1M ANT13

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1494.455	7.22	24.92	54.74	54.74	32.14	74.00	-41.86	peak
2	3196.094	7.70	29.20	54.92	57.26	39.24	74.00	-34.76	peak
3	4804.000	8.90	31.92	55.41	62.21	47.62	74.00	-26.38	peak
4	6285.695	10.55	34.51	56.17	55.49	44.38	74.00	-29.62	peak
5	7206.000	11.10	36.60	56.73	52.25	43.22	74.00	-30.78	peak
6	9608.000	12.38	38.78	55.93	51.61	46.84	74.00	-27.16	peak



BLE_1M_TX_CH_19_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE 1M ANT13

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1175.697	7.17	25.35	54.78	54.32	32.06	74.00	-41.94	peak
2	4495.125	8.56	31.58	55.26	54.31	39.19	74.00	-34.81	peak
3	4880.000	8.98	32.16	55.45	54.55	40.24	74.00	-33.76	peak
4	6640.542	10.85	35.44	56.49	54.02	43.82	74.00	-30.18	peak
5	7320.000	11.12	36.74	56.70	52.67	43.83	74.00	-30.17	peak
6	9760.000	12.84	38.60	55.88	49.23	44.79	74.00	-29.21	peak



BLE_1M_TX_CH_19_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE 1M ANT13

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1122.563	7.12	25.51	54.78	55.07	32.92	74.00 -41.08 peak
2	3186.869	7.70	29.20	54.92	58.26	40.24	74.00 -33.76 peak
3	4880.000	8.98	32.16	55.45	53.94	39.63	74.00 -34.37 peak
4	6776.265	10.94	35.81	56.61	53.84	43.98	74.00 -30.02 peak
5	7320.000	11.12	36.74	56.70	53.13	44.29	74.00 -29.71 peak
6	pp 9760.000	12.84	38.60	55.88	49.38	44.94	74.00 -29.06 peak



BLE_1M_TX_CH_39_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE 1M ANT13

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1175.697	7.17	25.35	54.78	53.91	31.65	74.00	-42.35	peak
2	4379.699	8.52	31.24	55.20	54.00	38.56	74.00	-35.44	peak
3	4960.000	9.07	32.20	55.48	52.38	38.17	74.00	-35.83	peak
4	6698.373	10.81	35.40	56.54	52.75	42.42	74.00	-31.58	peak
5	7440.000	11.08	36.78	56.66	51.46	42.66	74.00	-31.34	peak
6	9920.000	12.73	38.90	55.83	47.35	43.15	74.00	-30.85	peak



BLE_1M_TX_CH_39_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE 1M ANT13

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	7.17	25.36	54.78	53.93	31.68	74.00	-42.32	peak
2	4254.921	8.48	31.12	55.14	53.33	37.79	74.00	-36.21	peak
3	4960.000	9.07	32.20	55.48	52.74	38.53	74.00	-35.47	peak
4	6737.207	10.87	35.62	56.58	52.65	42.56	74.00	-31.44	peak
5	7440.000	11.08	36.78	56.66	51.08	42.28	74.00	-31.72	peak
6	9920.000	12.73	38.90	55.83	47.56	43.36	74.00	-30.64	peak



BLE_2M_TX_CH_01_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2404 TX RSE

: BLE 2M ANT13

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1158.828	7.15	25.38	54.78	54.58	32.33	74.00	-41.67	peak
2	4291.977	8.45	31.27	55.16	54.74	39.30	74.00	-34.70	peak
3	4808.000	8.91	31.93	55.41	59.08	44.51	74.00	-29.49	peak
4	6894.806	10.94	36.18	56.71	53.28	43.69	74.00	-30.31	peak
5	7212.000	11.10	36.60	56.73	53.75	44.72	74.00	-29.28	peak
6	9616.000	12.40	38.77	55.92	49.81	45.06	74.00	-28.94	peak



BLE_2M_TX_CH_01_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2404 TX RSE

: BLE 2M ANT13

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1335.141	7.17	25.13	54.76	56.73	34.27	74.00	-39.73	peak
2	4242.641	8.48	31.06	55.13	54.80	39.21	74.00	-34.79	peak
3	4808.000	8.91	31.93	55.41	61.88	47.31	74.00	-26.69	peak
4	6954.852	10.95	36.11	56.76	53.00	43.30	74.00	-30.70	peak
5	7212.000	11.10	36.60	56.73	52.78	43.75	74.00	-30.25	peak
6	9616.000	12.40	38.77	55.92	50.01	45.26	74.00	-28.74	peak



BLE_2M_TX_CH_19_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE 2M ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1179.100	7.17	25.34	54.78	55.06	32.79	74.00	-41.21 peak
2	4341.886	8.49	31.30	55.18	54.42	39.03	74.00	-34.97 peak
3	4880.000	8.98	32.16	55.45	54.03	39.72	74.00	-34.28 peak
4	6737.207	10.87	35.62	56.58	53.56	43.47	74.00	-30.53 peak
5	7320.000	11.12	36.74	56.70	51.75	42.91	74.00	-31.09 peak
6	pp 9760.000	12.84	38.60	55.88	49.58	45.14	74.00	-28.86 peak



BLE_2M_TX_CH_19_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE 2M ANT13

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1175.697	7.17	25.35	54.78	54.57	32.31	74.00	-41.69	peak
2	4354.454	8.50	31.29	55.19	54.98	39.58	74.00	-34.42	peak
3	4880.000	8.98	32.16	55.45	54.19	39.88	74.00	-34.12	peak
4	6815.551	10.97	35.93	56.64	53.67	43.93	74.00	-30.07	peak
5	7320.000	11.12	36.74	56.70	52.25	43.41	74.00	-30.59	peak
6	9760.000	12.84	38.60	55.88	49.04	44.60	74.00	-29.40	peak



BLE_2M_TX_CH_38_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2478 TX RSE

: BLE 2M ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1162.182	7.16	25.38	54.78	53.80	31.56	74.00	-42.44 peak
2	4254.921	8.48	31.12	55.14	53.94	38.40	74.00	-35.60 peak
3	4956.000	9.06	32.20	55.48	52.39	38.17	74.00	-35.83 peak
4	6934.778	10.95	36.13	56.75	52.33	42.66	74.00	-31.34 peak
5	7434.000	11.09	36.77	56.66	51.30	42.50	74.00	-31.50 peak
6	9912.000	12.71	38.90	55.83	47.87	43.65	74.00	-30.35 peak



BLE_2M_TX_CH_38_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2478 TX RSE

: BLE 2M ANT13

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1162.182	7.16	25.38	54.78	54.08	31.84	74.00	-42.16 peak
2	4254.921	8.48	31.12	55.14	54.54	39.00	74.00	-35.00 peak
3	4956.000	9.06	32.20	55.48	53.18	38.96	74.00	-35.04 peak
4	6914.763	10.94	36.17	56.73	52.95	43.33	74.00	-30.67 peak
5	7434.000	11.09	36.77	56.66	50.58	41.78	74.00	-32.22 peak
6	9912.000	12.71	38.90	55.83	48.01	43.79	74.00	-30.21 peak



BLE_PHY_S=8_TX_CH_00_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE PHY S=8 ANT13

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1192.811	7.18	25.31	54.77	54.80	32.52	74.00 -41.48 peak
2	4495.125	8.56	31.58	55.26	54.37	39.25	74.00 -34.75 peak
3	4804.000	8.90	31.92	55.41	57.23	42.64	74.00 -31.36 peak
4	6776.265	10.94	35.81	56.61	53.44	43.58	74.00 -30.42 peak
5	7206.000	11.10	36.60	56.73	52.95	43.92	74.00 -30.08 peak
6	pp 9608.000	12.38	38.78	55.93	49.84	45.07	74.00 -28.93 peak



BLE_PHY_S=8_TX_CH_00_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE PHY S=8 ANT13

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1175.697	7.17	25.35	54.78	55.23	32.97	74.00 -41.03 peak
2	4456.315	8.55	31.43	55.24	54.29	39.03	74.00 -34.97 peak
3	pp 4804.000	8.90	31.92	55.41	61.11	46.52	74.00 -27.48 peak
4	6815.551	10.97	35.93	56.64	54.06	44.32	74.00 -29.68 peak
5	7206.000	11.10	36.60	56.73	53.39	44.36	74.00 -29.64 peak
6	9608.000	12.38	38.78	55.93	49.23	44.46	74.00 -29.54 peak



BLE_PHY_S=8_TX_CH_19_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE PHY S=8 ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1158.828	7.15	25.38	54.78	54.06	31.81	74.00	-42.19 peak
2	4495.125	8.56	31.58	55.26	54.06	38.94	74.00	-35.06 peak
3	4880.000	8.98	32.16	55.45	52.95	38.64	74.00	-35.36 peak
4	6640.542	10.85	35.44	56.49	52.36	42.16	74.00	-31.84 peak
5	7320.000	11.12	36.74	56.70	51.18	42.34	74.00	-31.66 peak
6	9760.000	12.84	38.60	55.88	48.00	43.56	74.00	-30.44 peak



BLE_PHY_S=8_TX_CH_19_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE PHY S=8 ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1196.264	7.19	25.31	54.77	54.74	32.47	74.00	-41.53 peak
2	4329.354	8.48	31.30	55.18	53.84	38.44	74.00	-35.56 peak
3	4880.000	8.98	32.16	55.45	52.78	38.47	74.00	-35.53 peak
4	6995.172	10.96	36.19	56.80	52.09	42.44	74.00	-31.56 peak
5	7320.000	11.12	36.74	56.70	51.92	43.08	74.00	-30.92 peak
6	9760.000	12.84	38.60	55.88	49.54	45.10	74.00	-28.90 peak



BLE_PHY_S=8_TX_CH_39_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE PHY S=8 ANT13

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1206.682	7.19	25.30	54.77	53.67	31.39	74.00 -42.61 peak
2	4267.237	8.47	31.17	55.14	54.20	38.70	74.00 -35.30 peak
3	4960.000	9.07	32.20	55.48	52.94	38.73	74.00 -35.27 peak
4	6717.762	10.84	35.51	56.56	52.79	42.58	74.00 -31.42 peak
5	7440.000	11.08	36.78	56.66	51.03	42.23	74.00 -31.77 peak
6	9920.000	12.73	38.90	55.83	47.73	43.53	74.00 -30.47 peak



BLE_PHY_S=8_TX_CH_39_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE PHY S=8 ANT13

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1516.210	7.20	24.93	54.74	54.34	31.73	74.00 -42.27 peak
2	4405.090	8.54	31.22	55.22	53.45	37.99	74.00 -36.01 peak
3	4960.000	9.07	32.20	55.48	52.67	38.46	74.00 -35.54 peak
4	6995.172	10.96	36.19	56.80	52.17	42.52	74.00 -31.48 peak
5	7440.000	11.08	36.78	56.66	51.47	42.67	74.00 -31.33 peak
6	9920.000	12.73	38.90	55.83	47.88	43.68	74.00 -30.32 peak



BLE_PHY_S=2_TX_CH_00_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE PHY S=2 ANT13

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1172.303	7.17	25.36	54.78	55.06	32.81	74.00	-41.19 peak
2	4379.699	8.52	31.24	55.20	55.09	39.65	74.00	-34.35 peak
3	4804.000	8.90	31.92	55.41	56.57	41.98	74.00	-32.02 peak
4	6894.806	10.94	36.18	56.71	53.21	43.62	74.00	-30.38 peak
5	7206.000	11.10	36.60	56.73	52.56	43.53	74.00	-30.47 peak
6	9608.000	12.38	38.78	55.93	50.20	45.43	74.00	-28.57 peak



BLE_PHY_S=2_TX_CH_00_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM

Mode : 2402 TX RSE

: BLE PHY S=2 ANT13

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1206.682	7.19	25.30	54.77	55.06	32.78	74.00 -41.22 peak
2	4469.214	8.55	31.48	55.25	55.30	40.08	74.00 -33.92 peak
3	pp 4804.000	8.90	31.92	55.41	61.67	47.08	74.00 -26.92 peak
4	6640.542	10.85	35.44	56.49	53.80	43.60	74.00 -30.40 peak
5	7206.000	11.10	36.60	56.73	52.58	43.55	74.00 -30.45 peak
6	9608.000	12.38	38.78	55.93	49.55	44.78	74.00 -29.22 peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

BLE_PHY_S=2_TX_CH_19_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE PHY S=2 ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1132.340	7.13	25.47	54.78	54.01	31.83	74.00	-42.17 peak
2	3969.767	8.10	30.14	55.00	55.41	38.65	74.00	-35.35 peak
3	4880.000	8.98	32.16	55.45	53.24	38.93	74.00	-35.07 peak
4	6564.209	10.80	35.06	56.42	53.64	43.08	74.00	-30.92 peak
5	7320.000	11.12	36.74	56.70	50.28	41.44	74.00	-32.56 peak
6	pp 9760.000	12.84	38.60	55.88	48.12	43.68	74.00	-30.32 peak



BLE_PHY_S=2_TX_CH_19_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE PHY S=2 ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1644.019	7.14	25.01	54.73	54.83	32.25	74.00	-41.75 peak
2	4456.315	8.55	31.43	55.24	53.78	38.52	74.00	-35.48 peak
3	4880.000	8.98	32.16	55.45	53.45	39.14	74.00	-34.86 peak
4	6815.551	10.97	35.93	56.64	52.78	43.04	74.00	-30.96 peak
5	7320.000	11.12	36.74	56.70	51.48	42.64	74.00	-31.36 peak
6	9760.000	12.84	38.60	55.88	49.12	44.68	74.00	-29.32 peak



BLE_PHY_S=2_TX_CH_39_Horizontal-Ant13



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE PHY S=2 ANT13

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1185.936	7.18	25.33	54.78	54.36	32.09	74.00	-41.91 peak
2	4218.186	8.50	30.91	55.12	53.90	38.19	74.00	-35.81 peak
3	4960.000	9.07	32.20	55.48	53.96	39.75	74.00	-34.25 peak
4	6776.265	10.94	35.81	56.61	52.43	42.57	74.00	-31.43 peak
5	7440.000	11.08	36.78	56.66	50.93	42.13	74.00	-31.87 peak
6	9920.000	12.73	38.90	55.83	48.18	43.98	74.00	-30.02 peak



BLE_PHY_S=2_TX_CH_39_Vertical-Ant13



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE PHY S=2 ANT13

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1533.841	7.18	24.97	54.74	54.30	31.71	74.00	-42.29	peak
2	4279.589	8.46	31.22	55.15	53.78	38.31	74.00	-35.69	peak
3	4960.000	9.07	32.20	55.48	53.83	39.62	74.00	-34.38	peak
4	6855.063	10.96	36.02	56.68	52.29	42.59	74.00	-31.41	peak
5	pp 7440.000	11.08	36.78	56.66	52.04	43.24	74.00	-30.76	peak
6	9920.000	12.73	38.90	55.83	47.33	43.13	74.00	-30.87	peak



BLE_1M_TX_CH_00_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE 1M ANT12

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1362.430	7.19	25.08	54.76	55.00	32.51	74.00	-41.49	peak
2	4279.589	8.46	31.22	55.15	54.81	39.34	74.00	-34.66	peak
3	4804.000	8.90	31.92	55.41	57.03	42.44	74.00	-31.56	peak
4	6322.136	10.56	34.64	56.21	54.61	43.60	74.00	-30.40	peak
5	7206.000	11.10	36.60	56.73	52.86	43.83	74.00	-30.17	peak
6	9608.000	12.38	38.78	55.93	49.36	44.59	74.00	-29.41	peak



BLE_1M_TX_CH_00_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE 1M ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	7.16	25.36	54.78	54.81	32.55	74.00	-41.45 peak
2	4469.214	8.55	31.48	55.25	55.06	39.84	74.00	-34.16 peak
3	4804.000	8.90	31.92	55.41	59.85	45.26	74.00	-28.74 peak
4	6995.172	10.96	36.19	56.80	53.36	43.71	74.00	-30.29 peak
5	7206.000	11.10	36.60	56.73	52.40	43.37	74.00	-30.63 peak
6	pp 9608.000	12.38	38.78	55.93	51.32	46.55	74.00	-27.45 peak



BLE_1M_TX_CH_19_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE 1M ANT12

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1155.483	7.15	25.39	54.78	54.31	32.07	74.00	-41.93	peak
2	4417.841	8.54	31.27	55.22	54.70	39.29	74.00	-34.71	peak
3	4880.000	8.98	32.16	55.45	55.17	40.86	74.00	-33.14	peak
4	6995.172	10.96	36.19	56.80	53.78	44.13	74.00	-29.87	peak
5	7320.000	11.12	36.74	56.70	52.44	43.60	74.00	-30.40	peak
6	9760.000	12.84	38.60	55.88	49.31	44.87	74.00	-29.13	peak



BLE_1M_TX_CH_19_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE 1M ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1362.430	7.19	25.08	54.76	55.28	32.79	74.00	-41.21 peak
2	3196.094	7.70	29.20	54.92	58.12	40.10	74.00	-33.90 peak
3	4880.000	8.98	32.16	55.45	55.16	40.85	74.00	-33.15 peak
4	6795.879	10.97	35.88	56.63	53.21	43.43	74.00	-30.57 peak
5	7320.000	11.12	36.74	56.70	53.91	45.07	74.00	-28.93 peak
6	pp 9760.000	12.84	38.60	55.88	49.63	45.19	74.00	-28.81 peak



BLE_1M_TX_CH_39_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE 1M ANT12

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	7.16	25.36	54.78	53.96	31.70	74.00	-42.30	peak
2	4341.886	8.49	31.30	55.18	53.73	38.34	74.00	-35.66	peak
3	4960.000	9.07	32.20	55.48	53.70	39.49	74.00	-34.51	peak
4	6874.906	10.95	36.10	56.69	52.90	43.26	74.00	-30.74	peak
5	7440.000	11.08	36.78	56.66	51.27	42.47	74.00	-31.53	peak
6	9920.000	12.73	38.90	55.83	48.43	44.23	74.00	-29.77	peak



BLE_1M_TX_CH_39_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE 1M ANT12

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1185.936	7.18	25.33	54.78	53.68	31.41	74.00 -42.59 peak
2	4230.396	8.49	30.98	55.13	54.14	38.48	74.00 -35.52 peak
3	4960.000	9.07	32.20	55.48	52.97	38.76	74.00 -35.24 peak
4	6995.172	10.96	36.19	56.80	52.46	42.81	74.00 -31.19 peak
5	7440.000	11.08	36.78	56.66	51.58	42.78	74.00 -31.22 peak
6	9920.000	12.73	38.90	55.83	47.96	43.76	74.00 -30.24 peak



BLE_2M_TX_CH_01_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2404 TX RSE

: BLE 2M ANT12

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1109.660	7.11	25.56	54.78	54.64	32.53	74.00	-41.47	peak
2	4354.454	8.50	31.29	55.19	55.30	39.90	74.00	-34.10	peak
3	4808.000	8.91	31.93	55.41	56.12	41.55	74.00	-32.45	peak
4	6602.265	10.88	35.21	56.46	53.91	43.54	74.00	-30.46	peak
5	7212.000	11.10	36.60	56.73	52.63	43.60	74.00	-30.40	peak
6	9616.000	12.40	38.77	55.92	49.30	44.55	74.00	-29.45	peak



BLE_2M_TX_CH_01_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2404 TX RSE

: BLE 2M ANT12

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1122.563	7.12	25.51	54.78	54.29	32.14	74.00	-41.86 peak
2	4193.872	8.50	30.76	55.11	54.97	39.12	74.00	-34.88 peak
3	4808.000	8.91	31.93	55.41	61.95	47.38	74.00	-26.62 peak
4	6995.172	10.96	36.19	56.80	52.96	43.31	74.00	-30.69 peak
5	7212.000	11.10	36.60	56.73	52.82	43.79	74.00	-30.21 peak
6	9616.000	12.40	38.77	55.92	49.94	45.19	74.00	-28.81 peak



BLE_2M_TX_CH_19_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE 2M ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1185.936	7.18	25.33	54.78	54.68	32.41	74.00	-41.59 peak
2	4430.628	8.55	31.32	55.23	54.41	39.05	74.00	-34.95 peak
3	4880.000	8.98	32.16	55.45	53.60	39.29	74.00	-34.71 peak
4	6815.551	10.97	35.93	56.64	53.67	43.93	74.00	-30.07 peak
5	7320.000	11.12	36.74	56.70	52.05	43.21	74.00	-30.79 peak
6	pp 9760.000	12.84	38.60	55.88	49.57	45.13	74.00	-28.87 peak



BLE_2M_TX_CH_19_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE 2M ANT12

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1331.288	7.17	25.14	54.76	55.21	32.76	74.00	-41.24 peak
2	3186.869	7.70	29.20	54.92	57.86	39.84	74.00	-34.16 peak
3	4880.000	8.98	32.16	55.45	53.06	38.75	74.00	-35.25 peak
4	6795.879	10.97	35.88	56.63	53.39	43.61	74.00	-30.39 peak
5	7320.000	11.12	36.74	56.70	55.39	46.55	74.00	-27.45 peak
6	9760.000	12.84	38.60	55.88	50.39	45.95	74.00	-28.05 peak



BLE_2M_TX_CH_38_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2478 TX RSE

: BLE 2M ANT12

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1206.682	7.19	25.30	54.77	55.16	32.88	74.00	-41.12	peak
2	4304.400	8.45	31.30	55.16	55.32	39.91	74.00	-34.09	peak
3	4960.000	9.07	32.20	55.48	55.15	40.94	74.00	-33.06	peak
4	6974.982	10.95	36.15	56.78	53.71	44.03	74.00	-29.97	peak
5	7440.000	11.08	36.78	56.66	54.97	46.17	74.00	-27.83	peak
6	9920.000	12.73	38.90	55.83	49.15	44.95	74.00	-29.05	peak



BLE_2M_TX_CH_38_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2478 TX RSE

: BLE 2M ANT12

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1109.660	7.11	25.56	54.78	55.03	32.92	74.00	-41.08	peak
2	4267.237	8.47	31.17	55.14	55.50	40.00	74.00	-34.00	peak
3	4960.000	9.07	32.20	55.48	54.00	39.79	74.00	-34.21	peak
4	6659.763	10.84	35.48	56.51	53.79	43.60	74.00	-30.40	peak
5	7440.000	11.08	36.78	56.66	54.85	46.05	74.00	-27.95	peak
6	9920.000	12.73	38.90	55.83	50.40	46.20	74.00	-27.80	peak



BLE_PHY_S=8_TX_CH_00_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE PHY S=8 ANT12

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1182.513	7.17	25.33	54.78	54.96	32.68	74.00 -41.32 peak
2	4267.237	8.47	31.17	55.14	55.07	39.57	74.00 -34.43 peak
3	4804.000	8.90	31.92	55.41	58.65	44.06	74.00 -29.94 peak
4	6835.278	10.97	35.97	56.66	54.25	44.53	74.00 -29.47 peak
5	7206.000	11.10	36.60	56.73	52.56	43.53	74.00 -30.47 peak
6	pp 9608.000	12.38	38.78	55.93	49.41	44.64	74.00 -29.36 peak



BLE_PHY_S=8_TX_CH_00_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE PHY S=8 ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	7.17	25.36	54.78	55.06	32.81	74.00	-41.19 peak
2	4482.150	8.56	31.53	55.26	54.50	39.33	74.00	-34.67 peak
3	4804.000	8.90	31.92	55.41	62.65	48.06	74.00	-25.94 peak
4	6815.551	10.97	35.93	56.64	53.76	44.02	74.00	-29.98 peak
5	7206.000	11.10	36.60	56.73	53.00	43.97	74.00	-30.03 peak
6	9608.000	12.38	38.78	55.93	49.48	44.71	74.00	-29.29 peak



BLE_PHY_S=8_TX_CH_19_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE PHY S=8 ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1165.546	7.16	25.37	54.78	54.99	32.74	74.00	-41.26 peak
2	4469.214	8.55	31.48	55.25	55.24	40.02	74.00	-33.98 peak
3	4880.000	8.98	32.16	55.45	54.64	40.33	74.00	-33.67 peak
4	6995.172	10.96	36.19	56.80	53.35	43.70	74.00	-30.30 peak
5	7320.000	11.12	36.74	56.70	51.40	42.56	74.00	-31.44 peak
6	pp 9760.000	12.84	38.60	55.88	49.82	45.38	74.00	-28.62 peak



BLE_PHY_S=8_TX_CH_19_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE PHY S=8 ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	7.17	25.36	54.78	54.81	32.56	74.00	-41.44 peak
2	4430.628	8.55	31.32	55.23	55.05	39.69	74.00	-34.31 peak
3	4880.000	8.98	32.16	55.45	54.86	40.55	74.00	-33.45 peak
4	6914.763	10.94	36.17	56.73	53.03	43.41	74.00	-30.59 peak
5	7320.000	11.12	36.74	56.70	52.01	43.17	74.00	-30.83 peak
6	pp 9760.000	12.84	38.60	55.88	49.94	45.50	74.00	-28.50 peak



BLE_PHY_S=8_TX_CH_39_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE PHY S=8 ANT12

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1206.682	7.19	25.30	54.77	55.00	32.72	74.00 -41.28 peak
2	4316.859	8.47	31.30	55.17	54.35	38.95	74.00 -35.05 peak
3	4960.000	9.07	32.20	55.48	53.39	39.18	74.00 -34.82 peak
4	6414.167	10.53	34.80	56.29	54.77	43.81	74.00 -30.19 peak
5	7440.000	11.08	36.78	56.66	52.37	43.57	74.00 -30.43 peak
6	9920.000	12.73	38.90	55.83	48.71	44.51	74.00 -29.49 peak



BLE_PHY_S=8_TX_CH_39_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE PHY S=8 ANT12

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1182.513	7.17	25.33	54.78	54.87	32.59	74.00	-41.41 peak
2	4443.453	8.55	31.37	55.24	54.50	39.18	74.00	-34.82 peak
3	4960.000	9.07	32.20	55.48	54.40	40.19	74.00	-33.81 peak
4	6934.778	10.95	36.13	56.75	53.05	43.38	74.00	-30.62 peak
5	7440.000	11.08	36.78	56.66	52.01	43.21	74.00	-30.79 peak
6	9920.000	12.73	38.90	55.83	49.01	44.81	74.00	-29.19 peak



BLE_PHY_S=2_TX_CH_00_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2402 TX RSE

: BLE PHY S=2 ANT12

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1172.303	7.17	25.36	54.78	54.56	32.31	74.00	-41.69 peak
2	4495.125	8.56	31.58	55.26	55.21	40.09	74.00	-33.91 peak
3	4804.000	8.90	31.92	55.41	54.74	40.15	74.00	-33.85 peak
4	6855.063	10.96	36.02	56.68	53.43	43.73	74.00	-30.27 peak
5 pp	7206.000	11.10	36.60	56.73	53.94	44.91	74.00	-29.09 peak
6	9608.000	12.38	38.78	55.93	49.54	44.77	74.00	-29.23 peak



BLE_PHY_S=2_TX_CH_00_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM

Mode : 2402 TX RSE

: BLE PHY S=2 ANT12

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1125.813	7.12	25.50	54.78	54.88	32.72	74.00 -41.28 peak
2	4304.400	8.45	31.30	55.16	55.06	39.65	74.00 -34.35 peak
3	4804.000	8.90	31.92	55.41	61.80	47.21	74.00 -26.79 peak
4	6914.763	10.94	36.17	56.73	53.48	43.86	74.00 -30.14 peak
5	7206.000	11.10	36.60	56.73	52.82	43.79	74.00 -30.21 peak
6	9608.000	12.38	38.78	55.93	49.52	44.75	74.00 -29.25 peak




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

BLE_PHY_S=2_TX_CH_19_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE PHY S=2 ANT12

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	7.20	25.11	54.72	55.22	32.81	74.00	-41.19 peak
2	8.47	31.17	55.14	55.28	39.78	74.00	-34.22 peak
3	8.98	32.16	55.45	54.46	40.15	74.00	-33.85 peak
4	10.94	36.18	56.71	53.69	44.10	74.00	-29.90 peak
5	11.12	36.74	56.70	52.75	43.91	74.00	-30.09 peak
6 pp	12.84	38.60	55.88	49.33	44.89	74.00	-29.11 peak



BLE_PHY_S=2_TX_CH_19_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM


Mode : 2440 TX RSE

: BLE PHY S=2 ANT12

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1162.182	7.16	25.38	54.78	55.39	33.15	74.00	-40.85	peak
2	4230.396	8.49	30.98	55.13	55.42	39.76	74.00	-34.24	peak
3	4880.000	8.98	32.16	55.45	54.29	39.98	74.00	-34.02	peak
4	6756.708	10.91	35.73	56.59	54.42	44.47	74.00	-29.53	peak
5	7320.000	11.12	36.74	56.70	54.13	45.29	74.00	-28.71	peak
6	9760.000	12.84	38.60	55.88	49.39	44.95	74.00	-29.05	peak



BLE_PHY_S=2_TX_CH_39_Horizontal-Ant12



Condition: 3m HORIZONTAL

Job No : 03328WM


Mode : 2480 TX RSE

: BLE PHY S=2 ANT12

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1165.546	7.16	25.37	54.78	55.37	33.12	74.00 -40.88 peak
2	4495.125	8.56	31.58	55.26	55.53	40.41	74.00 -33.59 peak
3	4960.000	9.07	32.20	55.48	53.92	39.71	74.00 -34.29 peak
4	6894.806	10.94	36.18	56.71	53.06	43.47	74.00 -30.53 peak
5	7440.000	11.08	36.78	56.66	52.15	43.35	74.00 -30.65 peak
6	9920.000	12.73	38.90	55.83	49.00	44.80	74.00 -29.20 peak



BLE_PHY_S=2_TX_CH_39_Vertical-Ant12



Condition: 3m VERTICAL

Job No : 03328WM

Mode : 2480 TX RSE

: BLE PHY S=2 ANT12

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	1103.264	7.10	25.59	54.79	55.29	33.19	74.00 -40.81 peak
2	4482.150	8.56	31.53	55.26	54.32	39.15	74.00 -34.85 peak
3	4960.000	9.07	32.20	55.48	53.78	39.57	74.00 -34.43 peak
4	6717.762	10.84	35.51	56.56	54.12	43.91	74.00 -30.09 peak
5	7440.000	11.08	36.78	56.66	52.54	43.74	74.00 -30.26 peak
6	9920.000	12.73	38.90	55.83	49.28	45.08	74.00 -28.92 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.5 Conducted Peak Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)

Test Method: ANSI C63.10 (2020) Section 11.9.1

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 19.7 °C


Humidity: 61.9 % RH

Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.5.3 Test Setup Diagram



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR250700332807

Page: 106 of 179

7.5.4 Measurement Procedure and Data

Note: Since the verify power the same operating range bandwidth and smaller power can be covered by the higher power.

Please Refer to Appendix for Details



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.6 Minimum 6dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.247a(2)

Test Method: ANSI C63.10 (2020) Section 11.8.1

Limit:

≥500 kHz

7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 19.7 °C


Humidity: 61.9 % RH

Atmospheric Pressure: 1020 mbar

7.6.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.6.3 Test Setup Diagram



7.6.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.7 Power Spectrum Density

Test Requirement 47 CFR Part 15, Subpart C 15.247(e)

Test Method: ANSI C63.10 (2020) Section 11.10.2

Limit:

≤8dBm in any 3 kHz band during any time interval of continuous transmission

7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 19.7 °C


Humidity: 61.9 % RH

Atmospheric Pressure: 1020 mbar

7.7.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.7.3 Test Setup Diagram



7.7.4 Measurement Procedure and Data

Please Refer to Appendix for Details



7.8 Conducted Band Edges Measurement

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)

Test Method: ANSI C63.10 (2020) Section 6.10.4

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.8.1 E.U.T. Operation

Operating Environment:

Temperature: 19.7 °C


Humidity: 61.9 % RH

Atmospheric Pressure: 1020 mbar

7.8.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.8.3 Test Setup Diagram



7.8.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.9 Conducted Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.247(d)
Test Method: ANSI C63.10 (2020) Section 11.11

Limit:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

7.9.1 E.U.T. Operation


Operating Environment:

Temperature: 19.7 °C Humidity: 61.9 % RH Atmospheric Pressure: 1020 mbar

7.9.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	02	TX mode(BLE)_Keep the EUT in continuously transmitting mode with GFSK modulation.

7.9.3 Test Setup Diagram



7.9.4 Measurement Procedure and Data

Please Refer to Appendix for Details



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com
No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

8 Test Setup Photo

Please refer to SZCR2507003328WM Appendix_Setup Photo

9 EUT Constructional Details (EUT Photos)

Refer to External and Internal Photos for SZCR2507003328WM



10 Appendix

1. Duty Cycle

1.1 Test Result


1.1.1 Ant1

Ant13							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
S8	SISO	2402	3.105	4.109	75.57	1.22	0.04
		2440	3.105	4.108	75.58	1.22	0.04
		2480	3.105	4.108	75.58	1.22	0.03
S2	SISO	2402	1.072	1.816	59.03	2.29	0.03
		2440	1.072	1.817	59.00	2.29	0.03
		2480	1.071	1.816	58.98	2.29	0.03
1M	SISO	2402	0.394	0.756	52.12	2.83	0.04
		2440	0.394	0.756	52.12	2.83	0.00
		2480	0.394	0.756	52.12	2.83	0.00
2M	SISO	2404	0.208	0.536	38.81	4.11	0.06
		2440	0.208	0.536	38.81	4.11	0.03
		2478	0.209	0.536	38.99	4.09	0.03




1.2 Test Graph


1.2.1 Ant1




S8_HCH_2480MHz_Ant13_NTNV




S2_LCH_2402MHz_Ant13_NTNV




S2_MCH_2440MHz_Ant13_NTNV




S2_HCH_2480MHz_Ant13_NTNV




1M_LCH_2402MHz_Ant13_NTNV




1M_MCH_2440MHz_Ant13_NTNV




1M_HCH_2480MHz_Ant13_NTNV




2M_LCH_2404MHz_Ant13_NTNV



2M_MCH_2440MHz_Ant13_NTNV



2M_HCH_2478MHz_Ant13_NTNV



2. Bandwidth

2.1 Test Result

2.1.1 OBW


Mode	TX Type	Frequency (MHz)	ANT	99% Occupied Bandwidth (MHz)		Verdict
				Result	Limit	
S8	SISO	2402	13	1.048	/	Pass
		2440	13	1.044	/	Pass
		2480	13	1.044	/	Pass
S2	SISO	2402	13	1.014	/	Pass
		2440	13	1.010	/	Pass
		2480	13	1.012	/	Pass
1M	SISO	2402	13	1.029	/	Pass
		2440	13	1.029	/	Pass
		2480	13	1.030	/	Pass
2M	SISO	2404	13	2.029	/	Pass
		2440	13	2.031	/	Pass
		2478	13	2.030	/	Pass

2.1.2 6dB BW


Mode	TX Type	Frequency (MHz)	ANT	6dB Bandwidth (MHz)		Verdict
				Result	Limit	
S8	SISO	2402	13	0.625	≥ 0.5	Pass
		2440	13	0.624	≥ 0.5	Pass
		2480	13	0.631	≥ 0.5	Pass
S2	SISO	2402	13	0.662	≥ 0.5	Pass
		2440	13	0.663	≥ 0.5	Pass
		2480	13	0.663	≥ 0.5	Pass
1M	SISO	2402	13	0.668	≥ 0.5	Pass
		2440	13	0.667	≥ 0.5	Pass
		2480	13	0.666	≥ 0.5	Pass
2M	SISO	2404	13	1.144	≥ 0.5	Pass
		2440	13	1.142	≥ 0.5	Pass
		2478	13	1.143	≥ 0.5	Pass

2.2 Test Graph


2.2.1 OBW




S8_HCH_2480MHz_Ant13_NTNV




S2_LCH_2402MHz_Ant13_NTNV




S2_MCH_2440MHz_Ant13_NTNV




S2_HCH_2480MHz_Ant13_NTNV




1M_LCH_2402MHz_Ant13_NTNV




1M_MCH_2440MHz_Ant13_NTNV




1M_HCH_2480MHz_Ant13_NTNV




2M_LCH_2404MHz_Ant13_NTNV




2M_MCH_2440MHz_Ant13_NTNV




2M_HCH_2478MHz_Ant13_NTNV




2.2.2 6dB BW




S8_HCH_2480MHz_Ant13_NTNV




S2_LCH_2402MHz_Ant13_NTNV




S2_MCH_2440MHz_Ant13_NTNV




S2_HCH_2480MHz_Ant13_NTNV




1M_LCH_2402MHz_Ant13_NTNV




1M_MCH_2440MHz_Ant13_NTNV




1M_HCH_2480MHz_Ant13_NTNV




2M_LCH_2404MHz_Ant13_NTNV



2M_MCH_2440MHz_Ant13_NTNV



2M_HCH_2478MHz_Ant13_NTNV



3. Maximum Conducted Output Power

3.1 Test Result

3.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)			Verdict
			ANT13	ANT12	Limit	
S8	SISO	2402	11.11	13.53	<=30	Pass
		2440	11.86	13.25	<=30	Pass
		2480	9.83	11.36	<=30	Pass
S2	SISO	2402	11.16	13.65	<=30	Pass
		2440	11.92	13.32	<=30	Pass
		2480	9.88	11.42	<=30	Pass
1M	SISO	2402	15.99	17.75	<=30	Pass
		2440	15.76	17.33	<=30	Pass
		2480	15.94	17.29	<=30	Pass
2M	SISO	2404	15.97	17.63	<=30	Pass
		2440	16.06	17.48	<=30	Pass
		2478	16.24	17.24	<=30	Pass

Note1: Antenna Gain: Ant13: -3.50dBi; Ant12: -3.30dBi;



4. Maximum Power Spectral Density

4.1 Test Result


4.1.1 PSD

Mode	TX Type	Frequency (MHz)	Maximum PSD (dBm/3kHz)			Verdict
			ANT13	ANT12	Limit	
S8	SISO	2402	4.99	7.39	<=8	Pass
		2440	5.74	7.06	<=8	Pass
		2480	3.75	5.17	<=8	Pass
S2	SISO	2402	4.92	6.51	<=8	Pass
		2440	5.74	6.97	<=8	Pass
		2480	3.76	5.17	<=8	Pass
1M	SISO	2402	1.43	2.87	<=8	Pass
		2440	1.07	2.65	<=8	Pass
		2480	1.31	2.58	<=8	Pass
2M	SISO	2404	-1.58	0.02	<=8	Pass
		2440	-1.32	0.09	<=8	Pass
		2478	-1.31	-0.29	<=8	Pass


Note1: Antenna Gain: Ant13: -3.50dBi; Ant12: -3.30dBi;

4.2 Test Graph


4.2.1 PSD




S8_MCH_2440MHz_Ant13_NTNV



S8_MCH_2440MHz_Ant12_NTNV



S8_HCH_2480MHz_Ant13_NTNV



S8_HCH_2480MHz_Ant12_NTNV

