TEST REPORT

Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Equipment Type:	Mobile Phone
Model Name:	25118PC98G
Brand Name:	POCO
FCC ID:	2AFZZPC98G
Test Standard:	47 CFR Part 15 Subpart C ANSI C63.10-2020
Sample Arrival Date:	Jul. 17, 2025
Test Date:	Jul. 19, 2025 - Jul. 22, 2025
Date of Issue:	Sep. 04, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Li JunFeng **Checked by:** Zong Liyao **Approved by:** Tolan Tu

(Testing Director)

Revision History

Version	Issue Date	Revisions
Rev. 01	Sep. 04, 2025	Initial Issue

TABLE OF CONTENTS

1 GENERAL INFORMATION 4

1.1 Test Laboratory 4

1.2 Test Location 4

2 PRODUCT INFORMATION 5

2.1 Applicant Information 5

2.2 Manufacturer Information 5

2.3 General Description for Equipment under Test (EUT) 5

2.4 Technical Information 6

3 SUMMARY OF TEST RESULTS 7

3.1 Test Standards 7

3.2 Verdict 7

3.3 Test Uncertainty 8

4 GENERAL TEST CONFIGURATIONS 9

4.1 Test Environments 9

4.2 Test Setups 9

5 TEST ITEMS 11

5.1 Antenna Requirements 11

5.2 Emission Bandwidth 12

5.3 Field Strength of Fundamental Emissions and Radiated Emissions 14

5.4 Frequency Tolerance 16

5.5 Conducted Emission 17

ANNEX A TEST RESULT 18

A.1 Emission Bandwidth 18

A.2 Field Strength of Fundamental Emissions 21

A.3 Radiated Emissions 23
A.4 Frequency Stability 27
A.5 Conducted Emissions 29
ANNEX B TEST SETUP PHOTOS 32
ANNEX C EUT EXTERNAL PHOTOS 32
ANNEX D EUT INTERNAL PHOTOS 32

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☑ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.The certification body is American Association for Laboratory Accreditation (A2LA).

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Xiaomi Communications Co., Ltd.
Address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

2.2 Manufacturer Information

Manufacturer	Xiaomi Communications Co., Ltd.
Address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

2.3 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	25118PC98G
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	135300P17
Software Version	Xiaomi HyperOS 2.0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
EUT ID	SC-SZ2560531:S48, S49, S56, S62
IMEI Number	SC-SZ2560531-S48: IMEI1:861950070025147; IMEI2:861950070025154
	SC-SZ2560531-S49: IMEI1:861950070040005; IMEI2:861950070040013
	SC-SZ2560531-S56: IMEI1:861950070038322; IMEI2:861950070038330
	SC-SZ2560531-S62: IMEI1:861950070021369; IMEI2:861950070021377

2.4 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/1900 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network FDD LTE Band 2/4/5/7/18/19/26/66/71 TDD LTE Band38/41/42/48 LTE CA Uplink (UL): CA_38C, CA_7C 5G Network SA: NR n2/5/7/38/41/48/66/71/77/78 NSA(EN-DC): DC_7A_n5A, DC_5A_n7A, DC_5A_n66A, DC_18A_n77A, DC_2A_n78A, DC_5A_n78A, DC_7A_n78A, DC_19A_78A, DC_26A_n78A, DC_38A_n78A, DC_41A_n78A Bluetooth (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) 5G WIFI 802.11a, 802.11n(HT20/40), 802.11ac(VHT20/40/80) GPS, GLONASS, Galileo, BDS, NFC

The requirement for the following technical information of the EUT was tested in this report:

Modulation Type	ASK
Frequency Range	13.56 MHz
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Receiver Categorization	3
Number of channel	1
Tested Channel	1
Antenna Type	Coil Antenna

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional Radiators
2	ANSI C63.10-2020	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	Verdict
1	Antenna Requirement	15.203	Pass Note
2	Emissions Bandwidth	15.215	Pass
3	Field Strength of Fundamental Emissions	15.225(a)	Pass
4	Radiated Emissions	15.225(d) / 15.209	Pass
5	Frequency Stability	15.225(e)	Pass
6	Conducted Emission	15.207	Pass

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203

Note 2:

Compared with the EUT of test report BL-SZ2570858-401, the changes of the EUT of this report as below:

1. Changed model name from 25098RA98G to 25118PC98G.
2. Changed brand name form Redmi to POCO.
3. Added LTE B71, NR n71 by software and hardware.
4. Removed LTE band 12/13/17 and NR n12/ 26 by software and hardware.
5. Removed LTE ULCA combination CA_2A-4A, CA_4A-5A, CA_4A-7A, CA_2A-7A by software.
6. Removed ENDC combination DC_4A_n2A, DC_7A_n2A, DC_66A_n2A, DC_2A_n7A, DC_4A_n7A,DC_66A_n7A, DC_4A_n38A, DC_5A_n38A, DC_2A_n38A, DC_66A_n38A, DC_2A_n41A, DC_4A_n41A, DC_5A_n41A, DC_66A_n41A, DC_2A_n66A,DC_7A_n66A, DC_2A_n77A, DC_4A_n78A,DC_66A_n78A by software.
7. LTE B4/66,NR n66 band RF components has adjustments (delete switch SP2T).
8. Changed camera specification form 108M pixel + 8M pixel to 50M pixel + 2M pixel.
9. Changed FCC ID from FCC ID: 2AFZZ98GWQ to FCC ID: 2AFZZPC98G.

Other hardware circuit and software are the same as EUT referred in test report BL-SZ2570858-401.

Therefore, all test data and EUT information are derived from the report BL-SZ2570858-401, which was issued by Shenzhen BALUN Technology Co., Ltd. on Aug. 22, 2025.

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.2 dB
Radiated emissions (9 kHz-30 MHz)	3.9 dB
Radiated emissions (30 MHz-1 GHz)-10m	4.3 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	30% to 60%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+0℃ to +40℃
Working Voltage of the EUT	NV (Normal Voltage)	3.87 V

4.2 Test Setups

Test Setup 1

Radiated Test (Below 30 MHz)



(Diagram 1)

Test Setup 2

Radiated Test (30 MHz-1 GHz)



Test Setup 3

AC Power Supply Port Test



(Diagram 3)

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer EUT internal photos.

5.2 Emission Bandwidth

5.2.1 Definition

15.215(c);

Intentional radiators operating under the alternative provisions to the general emission limits must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

• The transmitter shall be operated at its maximum carrier power measured under normal test conditions.

• The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.

• The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.

• The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

5.2.2 Test Setup

See section 4.2(Diagram 1) for test setup for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The 20dB bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW

RBW = 1% to 5% the OBW

VBW ≥ 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

The 99% emission bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 1.5 to 5 times the OBW

RBW = 1% to 5% OBW

VBW ≥ 3RBW

Sweep = auto

Detector function = peak

Trace = max hold

5.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.1

5.3 Field Strength of Fundamental Emissions and Radiated Emissions

5.3.1 Limit

FCC §15.225(a), (b), (c)

According to FCC section 15.225, for <30 MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 10 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 kHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated spurious emission below 30MHz. The 30m limit was converted to 3m Limit using square factor(x) as it was found by measurements as follows; 3 m Limit(dBμV/m) = 20log(X)+40log(30/3)= 20log(15848)+40log(30/3) = 124dBμV

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency range (MHz)	Field Strength@30m		Field Strength@10m	Field Strength@3m
	μV/m	dBμV/m	dBμV/m	dBμV/m
Below 13.110	30	29.5	48.58	69.5
13.110 ~ 13.410	106	40.5	59.58	80.5
13.410 ~ 13.553	334	50.5	69.58	90.5
13.553 ~13.567	15848	84	103.08	124
13.567 ~ 13.710	334	50.5	69.58	90.5
13.710 ~14.010	106	40.5	59.58	80.5
Above 14.010	30	29.5	48.58	69.5

NOTE:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.

FCC §15.225(d)

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement distance (meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dBμV/m@3m (AV) and 74dBμV/m@3m (PK).

5.3.2 Test Setup

See section 4.2(Diagram 1 and Diagram 2) for test setup for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for 30 MHz < f < 1 GHz, 10 kHz for 150 kHz < f < 30 MHz, 300 Hz for f < 150 kHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

5.3.4 Test Result and Test Equipment List

Please refer to ANNEX A.2 and A.3

NOTE**:**

1. Results (dBμV/m) = Reading (dBμV) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit – Results

5.4 Frequency Tolerance

5.4.1 Limit

FCC §15.225(e)

The frequency tolerance of the carrier signal shall be maintained within ±0.01% of the operating frequency over a temperature variation of −20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

5.4.2 Test Setup

See section 4.2(Diagram 1) for test setup for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

1. The test is performed in a Temperature Chamber.
2. The EUT is configured as MS + DC Power Supply.

5.4.4 Test Result and Test Equipment List

Please refer to ANNEX A.4.

5.5 Conducted Emission

5.5.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.5.2 Test Setup

See section 4.2(Diagram 3) for test setup for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.5.4 Test Result and Test Equipment List

Please refer to ANNEX A.5.

NOTE:

1. Results (dBμV) = Reading (dBμV) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit – Results

ANNEX A TEST RESULT

A.1 Emission Bandwidth

Note: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

Sample No.	S48	Temperature	24.3℃
Humidity	49%RH	Pressure	101kPa
Test Engineer	Zeng Xiaoying	Test Date	2025.07.19

Test Data

Frequency (MHz)	Emission Bandwidth (20dB down) (kHz)	Occupied Bandwidth (99%) (kHz)
13.560	25.619	24.744

Test Plots

Emission Bandwidth



99% Occupied Bandwidth



Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31	☒
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22	☒
Anechoic Chamber（10M）	EMC TECHNOLOGY LTD	20.1m*11.6m*7.35m	130	2024.07.13	2027.07.12	☒

A.2 Field Strength of Fundamental Emissions

Note: Field Strength of Fundamental Emissions tests were performed in X, Y, Z axis direction of EUT. And only the worst axis test condition was recorded in this test report.

Sample No.	S48	Temperature	24.3℃
Humidity	49%RH	Pressure	101kPa
Test Engineer	Zeng Xiaoying	Test Date	2025.07.19

Test Data

Field Strength of Fundamental Emissions Value					
Frequency (MHz)	Detector	Field Strength (dBμV/m)	Limit @3m (dBμV/m)	EUT	Margin (dB)
13.560	PEAK	61.26	124.0	X axis	62.74

Test Plot

Test Antenna-LOOP, EUT X axis



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	13.560	61.26	20.90	124.0	62.74	Peak	0.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31	☒
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22	☒
Anechoic Chamber（10M）	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2024.07.13	2027.07.12	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

A.3 Radiated Emissions

Note 1: This frequency which near 13.560 MHz with circle should be ignored because they are NFC carrier frequency.

(9 kHz ~ 30 MHz)(at 10m chamber)

Sample No.	S48	Temperature	24.3℃
Humidity	49%RH	Pressure	101kPa
Test Engineer	Zeng Xiaoying	Test Date	2025.07.19

The Data and Plots

9KHz – 30MHz, Test Antenna Horizontal



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	0.025	45.77	20.13	119.8	74.03	Peak	18.00	100	Horizontal	Pass
2	0.067	40.08	20.16	111.0	70.92	Peak	140.00	100	Horizontal	Pass
3	0.150	24.66	20.16	104.1	79.44	Peak	280.00	100	Horizontal	Pass
4	0.501	36.40	20.19	73.6	37.20	Peak	112.00	100	Horizontal	Pass
5	2.180	33.54	20.45	69.5	35.96	Peak	293.00	100	Horizontal	Pass
6	13.560	60.59	20.90	69.5	8.91	Peak	350.00	100	Horizontal	N/A

Note 1: This frequency which near 13.560 MHz with circle should be ignored because they are NFC

30 MHz – 1 GHz, Test Antenna Horizontal



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	57.638	23.67	-27.29	29.5	5.83	Peak	85.00	100	Vertical	Pass
2	61.449	23.07	-27.63	29.5	6.43	Peak	112.00	115	Vertical	N/A
2*	61.449	20.62	-27.63	29.5	8.88	QP	112.00	115	Vertical	Pass
3	81.155	24.73	-30.14	29.5	4.77	Peak	47.00	100	Vertical	Pass
4	81.360	24.73	-30.16	29.5	4.77	Peak	47.00	176	Vertical	N/A
4*	81.360	22.77	-30.16	29.5	6.73	QP	47.00	176	Vertical	Pass
5	154.371	21.41	-26.22	33.0	11.59	Peak	360.00	100	Vertical	Pass
6	946.178	29.72	-9.55	35.5	5.78	Peak	20.00	200	Vertical	Pass

30 MHz – 1 GHz, Test Antenna Horizontal



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	62.487	15.81	-27.69	29.5	13.69	Peak	48.00	100	Horizontal	Pass
2	99.823	15.17	-29.96	33.0	17.83	Peak	0.00	200	Horizontal	Pass
3	164.554	15.30	-26.23	33.0	17.70	Peak	360.00	200	Horizontal	Pass
4	287.956	19.03	-25.91	35.5	16.47	Peak	85.00	200	Horizontal	Pass
5	630.765	24.21	-16.35	35.5	11.29	Peak	269.00	200	Horizontal	Pass
6	933.329	29.18	-9.87	35.5	6.32	Peak	253.00	200	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency 9kHz-30MHz						
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31	☒
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2018054558	2024.11.28	2025.11.27	☒
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2026.08.03	☒
Anechoic Chamber（10M）	EMC TECHNOLOGY LTD	20.1m*11.6m*7.35m	130	2024.07.13	2027.07.12	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

A.4 Frequency Stability

Note 1: Because the 85%(3.2895V) of the rated supply voltage value exceeds the cut-off voltage lower(3.6V) limit of the manufacturer, the cut-off voltage of EUT is test here.
Note 2: Because the 115% (4.4505V)of the rated supply voltage value exceeds the cut-off voltage upper(4.3V) limit of the manufacturer, the cut-off voltage of EUT is test here.
Note 3: The operating temperature range of the EUT is 0°C to 40°C.

Sample No.	S48	Temperature	24.3℃
Humidity	49%RH	Pressure	101kPa
Test Engineer	Zeng Xiaoying	Test Date	2025.07.19

OPERATING FREQUENCY:	13560000 Hz
REFERENCE VOLTAGE:	3.87 V
DEVIATION LIMIT:	±0.01%

Test Data

VOLTAGE (%)	Test Conditions		Frequency (Hz)	Deviation (%)	Verdict
	Power (VDC)	Temperature (°C)			
100	3.8700	-20	13559925	-0.000553	Pass
100		-10	13559850	-0.001106	Pass
100		0	13560175	0.001291	Pass
100		+10	13560075	0.000553	Pass
100		+20	13559900	-0.000737	Pass
100		+25	13560200	0.001475	Pass
100		+30	13560250	0.001844	Pass
100		+40	13560325	0.002397	
100		+50	13559875	-0.000922	Pass
MAX(Cut-off Point, 85)	3.6000	+20	13559950	-0.000369	Pass
MIN(Cut-off Point, 115)	4.3000	+20	13559975	-0.000184	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2024.08.01	2025.07.31	☒
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2024.01.23	2027.01.22	☒
Temperature Chamber	AHK	SP20	1412	2024.08.30	2025.08.29	☒
DC Power Supply	ITECH	IT6863A	800014020777070012	2025.01.17	2026.01.16	☒
Description	Supplier	Name	Version	/		Use
Test Software	/	/	/	/		☒

A.5 Conducted Emissions

Sample No.	S48	Temperature	22.1℃
Humidity	58%RH	Pressure	101kPa
Test Engineer	Yu Jiahao	Test Date	2025.07.22

Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.430	46.38	10.58	57.25	10.87	Peak	L	Pass
1**	0.430	32.81	10.58	47.25	14.44	AV	L	Pass
2	0.520	42.39	10.37	56.00	13.61	Peak	L	Pass
2**	0.520	26.41	10.37	46.00	19.59	AV	L	Pass
3	0.824	41.29	10.22	56.00	14.71	Peak	L	Pass
3**	0.824	26.05	10.22	46.00	19.95	AV	L	Pass
4	1.136	41.11	10.38	56.00	14.89	Peak	L	Pass
4**	1.136	26.70	10.38	46.00	19.30	AV	L	Pass
5	15.598	49.37	13.70	60.00	10.63	Peak	L	Pass
5**	15.598	38.28	13.70	50.00	11.72	AV	L	Pass
6	29.974	42.40	17.38	60.00	17.60	Peak	L	Pass
6**	29.974	29.98	17.38	50.00	20.02	AV	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.380	45.06	10.35	58.28	13.22	Peak	N	Pass
1**	0.380	30.22	10.35	48.28	18.06	AV	N	Pass
2	0.480	44.82	10.41	56.34	11.52	Peak	N	Pass
2**	0.480	32.86	10.41	46.34	13.48	AV	N	Pass
3	0.868	41.54	10.42	56.00	14.46	Peak	N	Pass
3**	0.868	29.73	10.42	46.00	16.27	AV	N	Pass
4	1.274	42.89	10.29	56.00	13.11	Peak	N	Pass
4**	1.274	25.37	10.29	46.00	20.63	AV	N	Pass
5	4.932	38.72	10.93	56.00	17.28	Peak	N	Pass
5**	4.932	26.04	10.93	46.00	19.96	AV	N	Pass
6	15.536	43.61	13.75	60.00	16.39	Peak	N	Pass
6**	15.536	30.57	13.75	50.00	19.43	AV	N	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2024.08.01	2025.07.31	☒
LISN	SCHWARZBECK	NSLK 8127	8127-687	2025.04.29	2026.04.28	☒
Shielded Room	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2025.02.14	2028.02.13	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2571545-AE-1.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2571545-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2571545-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the “inspection and testing dedicated stamp” or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--