

FCC TEST REPORT

(PART 24)


Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Product:	Mobile Phone
Brand Name:	POCO
Model Name:	2410FPCC5G
FCC ID:	2AFZZPCC5G
Date of tests:	May. 11, 2024 ~ Jul. 11, 2024 Oct. 16, 2024 ~ Nov.15, 2024

The tests have been carried out according to the requirements of the following standard:

☒ **FCC PART 24, Subpart E** ☒ **FCC PART 2**
☒ **ANSI/TIA/EIA-603-D** ☒ **ANSI/TIA/EIA-603-E** ☒ **ANSI C63.26-2015**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Nov.15, 2024	Date: Nov.15, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS	5
1.1 MEASUREMENT UNCERTAINTY	6
1.2 TEST SITE AND INSTRUMENTS	7
2 GENERAL INFORMATION	9
2.1 GENERAL DESCRIPTION OF EUT	9
2.2 CONFIGURATION OF SYSTEM UNDER TEST	12
2.3 DESCRIPTION OF SUPPORT UNITS	13
2.4 TEST ITEM AND TEST CONFIGURATION	13
2.5 EUT OPERATING CONDITIONS	16
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	16
3 TEST TYPES AND RESULTS	17
3.1 OUTPUT POWER MEASUREMENT	17
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	17
3.1.2 TEST PROCEDURES	17
3.1.3 TEST SETUP	18
3.1.4 TEST RESULTS	18
3.2 FREQUENCY STABILITY MEASUREMENT	46
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	46
3.2.2 TEST PROCEDURE	46
3.2.3 TEST SETUP	46
3.2.4 TEST RESULTS	47
3.3 OCCUPIED BANDWIDTH MEASUREMENT	48
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT	48
3.3.2 TEST SETUP	48
3.3.3 TEST PROCEDURES	48
3.3.4 TEST RESULTS	49
3.4 BAND EDGE MEASUREMENT	50
3.4.1 LIMITS OF BAND EDGE MEASUREMENT	50
3.4.2 TEST SETUP	50
3.4.3 TEST PROCEDURES	51
3.4.4 TEST RESULTS	52
3.5 CONDUCTED SPURIOUS EMISSIONS	53
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	53
3.5.2 TEST PROCEDURE	53
3.5.3 TEST SETUP	53
3.5.4 TEST RESULTS	54
3.6 RADIATED EMISSION MEASUREMENT	55
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	55
3.6.2 TEST PROCEDURES	55



**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

3.6.3 DEVIATION FROM TEST STANDARD	55
3.6.4 TEST SETUP	56
3.6.5 TEST RESULTS	58
3.7 PEAK TO AVERAGE RATIO.....	94
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	94
3.7.2 TEST SETUP	94
3.7.3 TEST PROCEDURES	94
3.7.4 TEST RESULTS	95
4 PHOTOGRAPHS OF THE TEST CONFIGURATION.....	96
5 INFORMATION ON THE TESTING LABORATORIES	97
6 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	98
7 APPENDIX	99
GSM 1900	99
WCDMA BAND 2.....	110
LTE BAND B2.....	121



Test Report No.: W7L-P24100005RF06

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P24050016RF06	Original release	Jul. 11, 2024
W7L-P24100005RF06	Based on the original product add 2 nd materials, 5 th and 6 th screens. This report only verify conducted power and RSE worst case, the verify results of power are similar or lower, So this report only replaces the RSE worse case(EDGE1900(Ant0) (UP)_CH512).	Nov.15, 2024

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2		
STANDARD SECTION	TEST TYPE	RESULT
§2.1046	Conducted Output Power	Compliance
§24.232(c)	Equivalent Isotropic Radiated Power	Compliance
§2.1055 §24.235	Frequency Stability	Compliance
§2.1049	Occupied Bandwidth	Compliance
§24.232(d)	Peak to average ratio	Compliance
§24.238(a)(b)	Band Edge Measurements	Compliance
§2.1051 §24.238(a)(b)	Conducted Spurious Emissions	Compliance
§2.1053 §24.238(a)(b)	Radiated Spurious Emissions	Compliance

Lab A:

BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Address:

Room B37, Warehouse A5, No.3 Chiwan 4th Road, Zhaoshang Street, Nanshan District
Shenzhen, Guangdong, People's Republic of China

Accredited Test Lab Cert 3939.01

The FCC Site Registration No. is 525120; The Designation No. is CN1171.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	$\pm 76.97\text{Hz}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions & Radiated Power (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions & Radiated Power (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Band Edge Measurements	$\pm 4.70\text{dB}$
Peak to average ratio	$\pm 0.76\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



1.2 TEST SITE AND INSTRUMENTS

#1:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,24	Mar. 27,25
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.10,24	May.09,25
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.03,23	Sep.02,24
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Feb. 18,24	Feb. 17,25
Horn Antenna	ETS-LINDGRE N	3117	00168692	Feb. 18,24	Feb. 17,25
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K- SG/QMS-00361	15433	Sep.04, 23	Sep.03, 24
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 14,24	Feb. 13,25
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,24	May. 05,25
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.10,24	May.09,25
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,24	Feb.16,25
3m Semi-anechoic Chamber	ETS-LINDGRE N	9m*6m*6m	Euroshieldpn- CT0001143-121 6	Nov. 14,23	Nov. 13,26
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 06,24	May. 05,25
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,24	Feb. 13,25
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,24	Feb. 13,25
Temperature Chamber	ESPEC	SH-242	93000855	May. 06,24	May. 05,25
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 14,24	Feb. 13,25
Base station R&S CMW500	Rohde&Schwa rz	CMW500	153085	May.10,24	May.09,25
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 11,23	Aug. 10,24

#2:

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,24	Mar. 27,25
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.10,24	May.09,25
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.02,24	Sep.01,25
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Feb. 18,24	Feb. 17,25
Horn Antenna	ETS-LINDGRE N	3117	00168692	Feb. 18,24	Feb. 17,25
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K- SG/QMS-00361	15433	Sep.03, 24	Sep.02, 25
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 14,24	Feb. 13,25
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,24	May. 05,25
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.10,24	May.09,25
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,24	Feb.16,25
3m	ETS-LINDGRE	9m*6m*6m	Euroshieldpn-	Nov. 14,23	Nov. 13,26



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

Semi-anechoic Chamber	N		CT0001143-1216		
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 06,24	May. 05,25
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,24	Feb. 13,25
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,24	Feb. 13,25
Temperature Chamber	ESPEC	SH-242	93000855	May. 06,24	May. 05,25
MXG Analog Microwave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 14,24	Feb. 13,25
Base station R&S CMW500	Rohde&Schwarz	CMW500	153085	May.10,24	May.09,25
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 10,24	Aug. 09,25

- NOTE:** 1. The calibration interval of the above test instruments is 12 months or 36 months, and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile Phone	
BRAND NAME	POCO	
MODEL NAME	2410FPCC5G	
NOMINAL VOLTAGE	5/3.6~11Vdc(adapter or host equipment) 3.84Vdc (Li-ion, battery)	
MODULATION TYPE	GSM/GPRS: GMSK EDGE: 8PSK WCDMA: BPSK, QPSK LTE Band 2: QPSK, 16QAM, 64QAM	
FREQUENCY RANGE	GSM, EDGE	1850.2MHz ~ 1909.8MHz
	WCDMA	1852.4MHz ~ 1907.6MHz
	LTE Band 2 Channel Bandwidth: 1.4MHz	1850.7MHz ~ 1909.3MHz
	LTE Band 2 Channel Bandwidth: 3MHz	1851.5MHz ~ 1908.5MHz
	LTE Band 2 Channel Bandwidth: 5MHz	1852.5MHz ~ 1907.5MHz
	LTE Band 2 Channel Bandwidth: 10MHz	1855.0MHz ~ 1905.0MHz
	LTE Band 2 Channel Bandwidth: 15MHz	1857.5MHz ~ 1902.5MHz
	LTE Band 2 Channel Bandwidth: 20MHz	1860.0MHz ~ 1900.0MHz
MAX. EIRP POWER	GSM	820.35mW
	EDGE	380.19mW
	WCDMA	260.02mW
	LTE Band 2 Channel Bandwidth: 1.4MHz	240.44mW
	LTE Band 2 Channel Bandwidth: 3MHz	240.44mW
	LTE Band 2 Channel Bandwidth: 5MHz	239.33mW
	LTE Band 2 Channel Bandwidth: 10MHz	240.44mW
	LTE Band 2 Channel Bandwidth: 15MHz	237.14mW



	LTE Band 2 Channel Bandwidth: 20MHz	242.66mW
EMISSION DESIGNATOR	GSM	247KGXW
	EDGE	250KG7W
	WCDMA	4M17F9W
	LTE Band 2 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M10W7D
	LTE Band 2 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M69W7D
	LTE Band 2 Channel Bandwidth: 5MHz	QPSK: 4M51G7D
		16QAM: 4M50W7D
	LTE Band 2 Channel Bandwidth: 10MHz	QPSK: 9M01G7D
		16QAM: 9M00W7D
	LTE Band 2 Channel Bandwidth: 15MHz	QPSK: 13M5G7D
		16QAM: 13M5W7D
	LTE Band 2 Channel Bandwidth: 20MHz	QPSK: 18M0G7D
		16QAM: 18M0W7D
ANTENNA TYPE	ANT 0(UP): PIFA Antenna with -0.3dBi gain for GSM1900/ WCDMA II/LTE B2 ANT 1(DOWN): PIFA Antenna with -0.5dBi gain for GSM1900/ WCDMA II/LTE B2	
HW VERSION	135100C3N	
SW VERSION	Xiaomi HyperOS 1.0	
IMEI	864624070035805	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable3: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable4: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable5: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable6: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable7: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable8: non-shielded cable, with w/o ferrite core, 1.0 meter	
EXTREME TEMPERATURE	0-40 °C	
EXTREME VOLTAGE	3.6V - 4.4V	



**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Physically, the EUT provides two completed transmitter and two receiver.





MODULATION MODE	TX FUNCTION
GSM/GPRS/EDGE	2TX/2RX
WCDMA	2TX/2RX
LTE	2TX/2RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in the test report.
4. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.



2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST





2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	Kikusui/JP	PMX18-5A	0000001	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE/ WCDMA/ LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter with GSM or WCDMA or LTE link
B	EUT + DC source with GSM or WCDMA or LTE link

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	512 to 810	512, 661, 810	GSM, EDGE
B	FREQUENCY STABILITY	512 to 810	512, 661, 810	GSM, EDGE
A	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM, EDGE
A	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM, EDGE
A	BAND EDGE	512 to 810	512, 810	GSM, EDGE
A	CONDUCTED EMISSION	512 to 810	512, 661, 810	GSM, EDGE
A	RADIATED EMISSION	512 to 810	512, 661, 810	GSM, EDGE



**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

WCDMA

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
B	FREQUENCY STABILITY	9262 to 9538	9262, 9400, 9538	WCDMA
A	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
A	PEAK TO AVERAGE RATIO	9262 to 9538	9262, 9400, 9538	WCDMA
A	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
A	CONDCUDED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA
A	RADIATED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA

LTE BAND 2 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	18700 to 19100	18700, 18900, 19100	20MHz	QPSK	100 RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM	100 RB / 0 RB Offset
A	PEAK TO AVERAGE RATIO	18700 to 19100	18700, 18900, 19100	20MHz	c	1 RB / 0 RB Offset 100 RB / 0 RB Offset

A	BAND EDGE	18607 to 19193	18607	1.4MHz	QPSK, 16QAM	1 RB / 0 RB Offset
			19193	1.4MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18615 to 19185	18615	3MHz	QPSK, 16QAM	1 RB / 5 RB Offset
			19185	3MHz	QPSK, 16QAM	6 RB / 0 RB Offset
		18625 to 19175	18625	5MHz	QPSK, 16QAM	1 RB / 0 RB Offset
			19175	5MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		18650 to 19150	18650	10MHz	QPSK, 16QAM	1 RB / 14 RB Offset
			19150	10MHz	QPSK, 16QAM	15 RB / 0 RB Offset
		18675 to 19125	18675	15MHz	QPSK, 16QAM	1 RB / 0 RB Offset
			19125	15MHz	QPSK, 16QAM	25 RB / 0 RB Offset
		18700 to 19100	18700	20MHz	QPSK, 16QAM	1 RB / 24 RB Offset
			19100	20MHz	QPSK, 16QAM	25 RB / 0 RB Offset
A	CONDCUDED EMISSION	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18900	20MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	25deg. C, 57%RH	DC 5/3.6~11V By Adapter	Jace Hu
FREQUENCY STABILITY	25deg. C, 57%RH	DC 3.6/3.84/4.4 By DC Source	James Fu
OCCUPIED BANDWIDTH	23deg. C, 61%RH	DC 5/3.6~11V By Adapter	James Fu
PEAK TO AVERAGE RATIO	23deg. C, 61%RH	DC 5/3.6~11V By Adapter	James Fu
BAND EDGE	23deg. C, 61%RH	DC 5/3.6~11V By Adapter	James Fu
CONDCUDED EMISSION	23deg. C, 61%RH	DC 5/3.6~11V By Adapter	James Fu
RADIATED EMISSION	23deg. C, 70%RH	DC 5/3.6~11V By Adapter	Jace Hu

2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled an EUT to export maximum output power under transmission mode and specific channel frequency.

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

3.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

Where:

ERP or EIRP = effective radiated power or equivalent isotopically radiated power, respectively

(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.


CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

EIRP / ERP Measurement:

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Ant 0(UP):

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880	1909.8
GSM	29.30	29.41	29.44
GPRS (GMSK, 1Tx-slot)	29.23	29.40	29.41
GPRS (GMSK, 2Tx-slot)	25.57	25.77	25.99
GPRS (GMSK, 3Tx-slot)	23.73	23.96	24.26
GPRS (GMSK, 4Tx-slot)	22.77	23.00	23.33
EDGE (8PSK, 1Tx-slot)	25.94	26.10	26.05
EDGE (8PSK, 2Tx-slot)	22.89	23.12	23.04
EDGE (8PSK, 3Tx-slot)	21.10	21.46	21.32
EDGE (8PSK, 4Tx-slot)	20.16	20.35	20.28

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880	1907.6
RMC 12.2K	24.28	24.36	24.45
HSDPA Subtest-1	23.41	23.45	23.61
HSDPA Subtest-2	23.39	23.50	23.59
HSDPA Subtest-3	22.91	22.97	23.14
HSDPA Subtest-4	22.98	23.06	23.07
DC-HSDPA Subtest-1	23.48	23.47	23.59
DC-HSDPA Subtest-2	23.45	23.53	23.61
DC-HSDPA Subtest-3	22.88	23.02	23.12
DC-HSDPA Subtest-4	22.95	22.96	23.07
HSUPA Subtest-1	21.59	21.68	21.84
HSUPA Subtest-2	21.32	21.45	21.49
HSUPA Subtest-3	22.21	22.35	22.43
HSUPA Subtest-4	21.17	21.08	21.18
HSUPA Subtest-5	22.22	22.34	22.40
HSPA+ Subtest-1	21.54	21.62	21.74



**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

LTE BAND 2

Band/BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193
				Frequency 1850.7 MHz	Frequency 1880 MHz	Frequency 1909.3 MHz
2/ 1.4	QPSK	1	0	23.68	23.70	23.66
		1	2	24.03	24.11	24.05
		1	5	23.71	23.72	23.69
		3	0	23.63	23.80	23.80
		3	1	23.86	23.80	23.76
		3	3	23.74	23.79	23.72
		6	0	23.05	23.04	22.92
	16QAM	1	0	22.79	22.92	23.02
		1	2	23.35	23.35	23.26
		1	5	23.03	22.91	22.94
		3	0	22.71	22.89	22.74
		3	1	22.79	23.02	22.85
		3	3	22.84	22.86	22.62
		6	0	22.03	22.14	21.96
	64QAM	1	0	21.77	21.94	21.88
		1	2	22.26	22.27	22.31
		1	5	21.96	21.86	21.93
		3	0	21.71	21.89	21.81
		3	1	21.86	21.97	21.82
		3	3	21.90	21.88	21.62
		6	0	20.93	21.13	20.85

Band/BW	Modulation	RB Size	RB Offset	Low CH 18615	Mid CH 18900	High CH 19185
				Frequency 1851.5 MHz	Frequency 1880 MHz	Frequency 1908.5 MHz
2 / 3	QPSK	1	0	23.57	23.70	23.70
		1	7	24.02	24.11	24.04
		1	14	23.60	23.66	23.67
		8	0	22.87	23.02	22.90
		8	3	23.04	22.95	22.99
		8	7	23.03	23.02	23.00
		15	0	23.05	23.02	22.91
	16QAM	1	0	22.86	22.81	23.07
		1	7	23.31	23.44	23.28
		1	14	22.99	22.98	22.92
		8	0	21.90	22.10	22.01
		8	3	22.11	22.09	22.04
		8	7	22.12	22.06	21.77
		15	0	22.04	22.13	21.92
	64QAM	1	0	21.84	21.89	21.84
		1	7	22.25	22.28	22.36
		1	14	21.95	21.80	21.88
		8	0	20.92	21.08	21.00
		8	3	20.99	21.17	21.08
		8	7	21.13	21.10	20.85
		15	0	21.02	21.05	20.88

Band/BW	Modulation	RB Size	RB Offset	Low CH 18625	Mid CH 18900	High CH 19175
				Frequency 1852.5 MHz	Frequency 1880 MHz	Frequency 1907.5 MHz
2/ 5	QPSK	1	0	23.62	23.64	23.70
		1	12	24.09	24.01	23.98
		1	24	23.68	23.71	23.69
		12	0	22.89	23.00	22.88
		12	6	22.97	23.02	23.02
		12	13	23.03	22.95	22.95
		25	0	23.02	22.98	22.94
	16QAM	1	0	22.87	22.90	23.04
		1	12	23.29	23.46	23.25
		1	24	23.03	22.87	22.98
		12	0	21.98	22.19	21.91
		12	6	22.00	22.17	22.10
		12	13	22.00	22.12	21.83
		25	0	21.98	22.03	21.91
	64QAM	1	0	21.77	21.96	21.85
		1	12	22.24	22.34	22.35
		1	24	21.95	21.81	21.88
		12	0	20.97	21.13	20.93
		12	6	20.96	21.08	21.08
		12	13	21.01	21.04	20.82
		25	0	20.92	21.02	20.92

Band/BW	Modulation	RB Size	RB Offset	Low CH 18650	Mid CH 18900	High CH 19150
				Frequency 1855 MHz	Frequency 1880 MHz	Frequency 1905 MHz
2/ 10	QPSK	1	0	23.57	23.66	23.71
		1	24	24.11	23.99	23.99
		1	49	23.71	23.72	23.76
		25	0	22.79	23.01	22.88
		25	12	23.08	23.06	22.92
		25	25	22.95	23.07	22.94
		50	0	23.00	22.91	22.87
	16QAM	1	0	22.86	22.89	22.97
		1	24	23.27	23.40	23.37
		1	49	22.95	22.90	23.02
		25	0	21.96	22.13	21.90
		25	12	22.08	22.11	22.06
		25	25	22.00	22.05	21.79
		50	0	21.97	22.14	21.98
	64QAM	1	0	21.81	21.89	21.97
		1	24	22.15	22.25	22.24
		1	49	21.96	21.85	21.92
		25	0	20.86	21.12	20.94
		25	12	20.95	21.11	21.02
		25	25	21.07	21.06	20.88
		50	0	21.04	21.13	20.89



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

Band/BW	Modulation	RB Size	RB Offset	Low CH 18675	Mid CH 18900	High CH 19125
				Frequency 1857.5 MHz	Frequency 1880 MHz	Frequency 1902.5 MHz
2/ 15	QPSK	1	0	23.61	23.61	23.71
		1	37	24.01	24.05	24.01
		1	74	23.60	23.60	23.69
		36	0	22.90	23.05	23.00
		36	19	23.05	23.01	22.95
		36	39	23.01	23.00	22.97
		75	0	23.04	23.04	22.94
	16QAM	1	0	22.75	22.85	22.97
		1	37	23.26	23.42	23.37
		1	74	22.89	22.88	22.97
		36	0	21.88	22.15	21.95
		36	19	22.00	22.20	22.14
		36	39	22.02	22.00	21.80
		75	0	21.97	22.08	21.95
	64QAM	1	0	21.82	21.99	21.90
		1	37	22.29	22.28	22.24
		1	74	22.01	21.92	21.96
		36	0	20.84	21.09	20.89
		36	19	20.94	21.10	21.01
		36	39	21.05	20.99	20.83
		75	0	20.90	21.06	20.93

Band/BW	Modulation	RB Size	RB Offset	Low CH 18700	Mid CH 18900	High CH 19100
				Frequency 1860 MHz	Frequency 1880 MHz	Frequency 1900 MHz
2/ 20	QPSK	1	0	23.70	23.75	23.77
		1	50	24.15	24.14	24.13
		1	99	23.72	23.73	23.81
		50	0	22.94	23.06	23.02
		50	25	23.10	23.09	23.05
		50	50	23.07	23.08	23.04
		100	0	23.08	23.06	22.97
	16QAM	1	0	22.90	22.96	23.10
		1	50	23.36	23.48	23.40
		1	99	23.04	22.99	23.05
		50	0	22.01	22.21	22.04
		50	25	22.12	22.23	22.16
		50	50	22.13	22.14	21.92
		100	0	22.07	22.16	21.99
	64QAM	1	0	21.87	22.00	21.98
		1	50	22.30	22.39	22.38
		1	99	22.05	21.95	22.03
		50	0	20.98	21.16	21.04
		50	25	21.08	21.20	21.13
		50	50	21.15	21.14	20.91
		100	0	21.05	21.17	20.97



Ant 1(DOWN):

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880	1909.8
GSM	29.31	29.32	29.24
GPRS (GMSK, 1Tx-slot)	29.30	29.31	29.20
GPRS (GMSK, 2Tx-slot)	25.63	25.80	25.85
GPRS (GMSK, 3Tx-slot)	23.80	24.01	24.14
GPRS (GMSK, 4Tx-slot)	22.81	23.04	23.23
EDGE (8PSK, 1Tx-slot)	25.67	25.91	25.89
EDGE (8PSK, 2Tx-slot)	22.60	22.92	22.85
EDGE (8PSK, 3Tx-slot)	20.84	21.10	21.07
EDGE (8PSK, 4Tx-slot)	19.77	19.96	20.01

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880	1907.6
RMC 12.2K	24.31	24.36	24.46
HSDPA Subtest-1	23.48	23.56	23.59
HSDPA Subtest-2	23.47	23.50	23.66
HSDPA Subtest-3	22.98	22.98	23.10
HSDPA Subtest-4	23.00	22.98	23.10
DC-HSDPA Subtest-1	23.42	23.51	23.65
DC-HSDPA Subtest-2	23.47	23.50	23.57
DC-HSDPA Subtest-3	23.00	23.02	23.12
DC-HSDPA Subtest-4	22.95	23.03	23.08
HSUPA Subtest-1	21.61	21.73	21.79
HSUPA Subtest-2	21.39	21.35	21.48
HSUPA Subtest-3	22.24	22.30	22.42
HSUPA Subtest-4	21.15	21.05	21.07
HSUPA Subtest-5	22.22	22.32	22.42
HSPA+ Subtest-1	21.58	21.57	21.73



**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

LTE BAND 2

Band/BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193
				Frequency 1850.7 MHz	Frequency 1880 MHz	Frequency 1909.3 MHz
2/ 1.4	QPSK	1	0	23.70	23.75	23.68
		1	2	24.05	23.97	24.01
		1	5	23.60	23.54	23.70
		3	0	23.75	23.73	23.76
		3	1	23.79	23.76	23.72
		3	3	23.69	23.76	23.57
		6	0	22.97	22.96	22.94
	16QAM	1	0	23.04	23.00	22.98
		1	2	23.26	23.36	23.21
		1	5	22.92	22.86	22.86
		3	0	22.79	22.81	22.80
		3	1	22.77	22.88	22.81
		3	3	22.74	22.88	22.66
		6	0	22.02	22.01	21.90
	64QAM	1	0	21.79	21.92	21.90
		1	2	22.27	22.22	22.19
		1	5	21.86	21.80	21.94
		3	0	21.72	21.84	21.83
		3	1	21.85	21.95	21.88
		3	3	21.82	21.84	21.80
		6	0	20.97	21.06	20.93

Band/BW	Modulation	RB Size	RB Offset	Low CH 18615	Mid CH 18900	High CH 19185
				Frequency 1851.5 MHz	Frequency 1880 MHz	Frequency 1908.5 MHz
2 / 3	QPSK	1	0	23.88	23.89	23.83
		1	7	24.23	24.04	23.84
		1	14	23.81	23.71	23.74
		8	0	23.06	22.96	23.02
		8	3	23.07	22.92	22.90
		8	7	23.16	22.99	22.81
		15	0	23.01	23.03	22.91
	16QAM	1	0	22.69	22.70	22.64
		1	7	23.01	22.82	22.72
		1	14	22.57	22.68	22.53
		8	0	22.00	21.94	21.91
		8	3	21.95	21.86	21.97
		8	7	21.97	22.10	21.87
		15	0	21.97	21.82	21.95
	64QAM	1	0	21.72	21.79	21.62
		1	7	22.00	21.90	22.10
		1	14	21.61	21.65	21.72
		8	0	20.94	20.88	20.74
		8	3	20.85	20.87	20.84
		8	7	21.01	20.88	20.92
		15	0	20.92	20.89	20.79

Band/BW	Modulation	RB Size	RB Offset	Low CH 18625	Mid CH 18900	High CH 19175
				Frequency 1852.5 MHz	Frequency 1880 MHz	Frequency 1907.5 MHz
2/ 5	QPSK	1	0	23.84	23.91	23.75
		1	12	24.18	24.05	23.83
		1	24	23.93	23.74	23.73
		12	0	23.08	22.95	22.91
		12	6	22.99	22.89	22.89
		12	13	23.06	22.99	22.91
		25	0	22.90	23.11	22.90
	16QAM	1	0	22.77	22.77	22.57
		1	12	22.94	22.85	22.83
		1	24	22.69	22.66	22.59
		12	0	21.96	21.94	21.82
		12	6	21.91	21.86	21.93
		12	13	21.99	22.09	21.88
		25	0	22.01	21.94	21.96
	64QAM	1	0	21.65	21.76	21.53
		1	12	22.00	21.90	22.11
		1	24	21.69	21.66	21.64
		12	0	20.87	20.89	20.78
		12	6	20.82	20.90	20.88
		12	13	20.96	20.84	20.93
		25	0	20.92	20.90	20.81

Band/BW	Modulation	RB Size	RB Offset	Low CH 18650	Mid CH 18900	High CH 19150
				Frequency 1855 MHz	Frequency 1880 MHz	Frequency 1905 MHz
2/ 10	QPSK	1	0	23.77	23.79	23.74
		1	24	24.23	24.02	23.87
		1	49	23.91	23.71	23.81
		25	0	23.10	22.92	22.89
		25	12	22.98	22.96	22.81
		25	25	23.12	22.98	22.86
		50	0	22.89	23.01	22.97
	16QAM	1	0	22.66	22.71	22.62
		1	24	23.00	22.82	22.79
		1	49	22.56	22.67	22.54
		25	0	21.91	21.80	21.93
		25	12	21.88	21.94	21.97
		25	25	22.00	22.04	21.83
		50	0	22.08	21.87	22.04
	64QAM	1	0	21.69	21.78	21.65
		1	24	22.09	21.88	22.13
		1	49	21.70	21.70	21.63
		25	0	20.91	20.79	20.76
		25	12	20.88	20.91	20.89
		25	25	21.06	20.85	20.88
		50	0	21.00	20.96	20.80



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

Band/BW	Modulation	RB Size	RB Offset	Low CH 18675	Mid CH 18900	High CH 19125
				Frequency 1857.5 MHz	Frequency 1880 MHz	Frequency 1902.5 MHz
2/ 15	QPSK	1	0	23.88	23.86	23.84
		1	37	24.17	24.12	23.83
		1	74	23.80	23.73	23.67
		36	0	23.07	22.98	22.89
		36	19	23.00	22.95	22.84
		36	39	23.11	22.97	22.83
		75	0	22.90	23.09	22.93
	16QAM	1	0	22.63	22.74	22.68
		1	37	22.99	22.83	22.80
		1	74	22.67	22.65	22.58
		36	0	21.91	21.84	21.82
		36	19	21.95	21.96	22.01
		36	39	21.97	22.00	21.79
		75	0	22.10	21.94	22.04
	64QAM	1	0	21.72	21.65	21.56
		1	37	21.95	21.91	22.04
		1	74	21.70	21.73	21.77
		36	0	20.86	20.79	20.84
		36	19	20.83	20.85	20.80
		36	39	21.07	20.86	20.93
		75	0	20.86	20.89	20.79



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

Band/BW	Modulation	RB Size	RB Offset	Low CH 18700	Mid CH 18900	High CH 19100
				Frequency 1860 MHz	Frequency 1880 MHz	Frequency 1900 MHz
2/ 20	QPSK	1	0	23.71	23.76	23.71
		1	50	24.11	24.10	24.04
		1	99	23.68	23.66	23.76
		50	0	23.04	23.02	23.02
		50	25	23.05	23.03	23.04
		50	50	23.02	23.01	22.88
		100	0	23.07	23.06	22.96
	16QAM	1	0	23.05	23.01	23.08
		1	50	23.37	23.45	23.29
		1	99	23.01	22.98	22.92
		50	0	22.00	22.13	22.05
		50	25	22.09	22.17	22.10
		50	50	22.07	22.11	21.93
		100	0	22.05	22.08	21.99
	64QAM	1	0	21.92	21.96	21.97
		1	50	22.30	22.31	22.33
		1	99	21.90	21.91	21.98
		50	0	20.99	21.11	21.05
		50	25	21.06	21.14	21.09
		50	50	21.08	21.09	21.00
		100	0	21.01	21.10	21.02



**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

EIRP POWER (dBm)

Ant 0(UP):

GSM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	29.3	-0.3	29	794.33	2
661	1880.0	29.41	-0.3	29.11	814.7	2
810	1909.8	29.44	-0.3	29.14	820.35	2

EDGE

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	25.94	-0.3	25.64	366.44	2
661	1880.0	26.1	-0.3	25.8	380.19	2
810	1909.8	26.05	-0.3	25.75	375.84	2

WCDMA

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
9262	1852.4	24.28	-0.3	23.98	250.03	2
9400	1880	24.36	-0.3	24.06	254.68	2
9538	1907.6	24.45	-0.3	24.15	260.02	2



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

LTE BAND 2

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	24.03	-0.3	23.73	236.05	2
18900	1880.0	24.11	-0.3	23.81	240.44	2
19193	1909.3	24.05	-0.3	23.75	237.14	2

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	23.35	-0.3	23.05	201.84	2
18900	1880.0	23.35	-0.3	23.05	201.84	2
19193	1909.3	23.26	-0.3	22.96	197.7	2

CHANNEL BANDWIDTH: 1.4MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	22.26	-0.3	21.96	157.04	2
18900	1880.0	22.27	-0.3	21.97	157.4	2
19193	1908.3	22.31	-0.3	22.01	158.85	2

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	24.02	-0.3	23.72	235.5	2
18900	1880.0	24.11	-0.3	23.81	240.44	2
19185	1908.5	24.04	-0.3	23.74	236.59	2

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	23.31	-0.3	23.01	199.99	2
18900	1880.0	23.44	-0.3	23.14	206.06	2
19185	1908.5	23.28	-0.3	22.98	198.61	2

CHANNEL BANDWIDTH: 3MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	22.25	-0.3	21.95	156.68	2
18900	1880.0	22.28	-0.3	21.98	157.76	2
19185	1908.5	22.36	-0.3	22.06	160.69	2



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	24.09	-0.3	23.79	239.33	2
18900	1880.0	24.01	-0.3	23.71	234.96	2
19175	1907.5	23.98	-0.3	23.68	233.35	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	23.29	-0.3	22.99	199.07	2
18900	1880.0	23.46	-0.3	23.16	207.01	2
19175	1907.5	23.25	-0.3	22.95	197.24	2

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _c (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	22.24	-0.3	21.94	156.31	2
18900	1880.0	22.34	-0.3	22.04	159.96	2
19175	1907.5	22.35	-0.3	22.05	160.32	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	24.11	-0.3	23.81	240.44	2
18900	1880.0	23.99	-0.3	23.69	233.88	2
19150	1905.0	23.99	-0.3	23.69	233.88	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	23.27	-0.3	22.97	198.15	2
18900	1880.0	23.4	-0.3	23.1	204.17	2
19150	1905.0	23.37	-0.3	23.07	202.77	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	22.15	-0.3	21.85	153.11	2
18900	1880.0	22.25	-0.3	21.95	156.68	2
19150	1905.0	22.24	-0.3	21.94	156.31	2



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	24.01	-0.3	23.71	234.96	2
18900	1880.0	24.05	-0.3	23.75	237.14	2
19125	1902.5	24.01	-0.3	23.71	234.96	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	23.26	-0.3	22.96	197.7	2
18900	1880.0	23.42	-0.3	23.12	205.12	2
19125	1902.5	23.37	-0.3	23.07	202.77	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	22.29	-0.3	21.99	158.12	2
18900	1880.0	22.28	-0.3	21.98	157.76	2
19125	1902.5	22.24	-0.3	21.94	156.31	2

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	24.15	-0.3	23.85	242.66	2
18900	1880	24.14	-0.3	23.84	242.1	2
19100	1900	24.13	-0.3	23.83	241.55	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	23.36	-0.3	23.06	202.3	2
18900	1880	23.48	-0.3	23.18	207.97	2
19100	1900	23.4	-0.3	23.1	204.17	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	22.3	-0.3	22	158.49	2
18900	1880	22.39	-0.3	22.09	161.81	2
19100	1900	22.38	-0.3	22.08	161.44	2



**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

Ant 1(DOWN):

GSM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	29.31	-0.5	28.81	760.33	2
661	1880.0	29.32	-0.5	28.82	762.08	2
810	1909.8	29.24	-0.5	28.74	748.17	2

EDGE

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
512	1850.2	25.67	-0.5	25.17	328.85	2
661	1880.0	25.91	-0.5	25.41	347.54	2
810	1909.8	25.89	-0.5	25.39	345.94	2

WCDMA

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
9262	1852.4	24.31	-0.5	23.81	240.44	2
9400	1880	24.36	-0.5	23.86	243.22	2
9538	1907.6	24.46	-0.5	23.96	248.89	2



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

LTE BAND 2

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	24.05	-0.5	23.55	226.46	2
18900	1880.0	23.97	-0.5	23.47	222.33	2
19193	1909.3	24.01	-0.5	23.51	224.39	2

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	23.26	-0.5	22.76	188.8	2
18900	1880.0	23.36	-0.5	22.86	193.2	2
19193	1909.3	23.21	-0.5	22.71	186.64	2

CHANNEL BANDWIDTH: 1.4MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-LC} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18607	1850.7	22.27	-0.5	21.77	150.31	2
18900	1880.0	22.22	-0.5	21.72	148.59	2
19193	1908.3	22.19	-0.5	21.69	147.57	2

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	24.23	-0.5	23.73	236.05	2
18900	1880.0	24.04	-0.5	23.54	225.94	2
19185	1908.5	23.84	-0.5	23.34	215.77	2

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	23.01	-0.5	22.51	178.24	2
18900	1880.0	22.82	-0.5	22.32	170.61	2
19185	1908.5	22.72	-0.5	22.22	166.72	2

CHANNEL BANDWIDTH: 3MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18615	1851.5	22	-0.5	21.5	141.25	2
18900	1880.0	21.9	-0.5	21.4	138.04	2
19185	1908.5	22.1	-0.5	21.6	144.54	2



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	24.18	-0.5	23.68	233.35	2
18900	1880.0	24.05	-0.5	23.55	226.46	2
19175	1907.5	23.83	-0.5	23.33	215.28	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	22.94	-0.5	22.44	175.39	2
18900	1880.0	22.85	-0.5	22.35	171.79	2
19175	1907.5	22.83	-0.5	22.33	171	2

CHANNEL BANDWIDTH: 5MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18625	1852.5	22	-0.5	21.5	141.25	2
18900	1880.0	21.9	-0.5	21.4	138.04	2
19175	1907.5	22.11	-0.5	21.61	144.88	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	24.23	-0.5	23.73	236.05	2
18900	1880.0	24.02	-0.5	23.52	224.91	2
19150	1905.0	23.87	-0.5	23.37	217.27	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	23	-0.5	22.5	177.83	2
18900	1880.0	22.82	-0.5	22.32	170.61	2
19150	1905.0	22.79	-0.5	22.29	169.43	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18650	1855.0	22.09	-0.5	21.59	144.21	2
18900	1880.0	21.88	-0.5	21.38	137.4	2
19150	1905.0	22.13	-0.5	21.63	145.55	2



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	24.17	-0.5	23.67	232.81	2
18900	1880.0	24.12	-0.5	23.62	230.14	2
19125	1902.5	23.84	-0.5	23.34	215.77	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	22.99	-0.5	22.49	177.42	2
18900	1880.0	22.83	-0.5	22.33	171	2
19125	1902.5	22.8	-0.5	22.3	169.82	2

CHANNEL BANDWIDTH: 15MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _{T-Lc} (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18675	1857.5	21.95	-0.5	21.45	139.64	2
18900	1880.0	21.91	-0.5	21.41	138.36	2
19125	1902.5	22.04	-0.5	21.54	142.56	2

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	24.11	-0.5	23.61	229.61	2
18900	1880	24.1	-0.5	23.6	229.09	2
19100	1900	24.04	-0.5	23.54	225.94	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	23.37	-0.5	22.87	193.64	2
18900	1880	23.45	-0.5	22.95	197.24	2
19100	1900	23.29	-0.5	22.79	190.11	2

CHANNEL BANDWIDTH: 20MHz 64QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
18700	1860	22.3	-0.5	21.8	151.36	2
18900	1880	22.31	-0.5	21.81	151.71	2
19100	1900	22.33	-0.5	21.83	152.41	2



3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.2.2 TEST PROCEDURE

- The device is placed in the oven room. The oven room could control the temperatures and humidity. Power warms up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be recording the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be holding $\pm 0.5^{\circ}\text{C}$ during the measurement testing. Each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP





Test Report No.: W7L-P24100005RF06

3.2.4 TEST RESULTS

Please Refer to Appendix Of this test report.

Note: LV = Low voltage (3.6V); NV = Normal voltage (3.84V); HV= High voltage (4.4V).
NT = Normal temperature (25°C)




3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band is such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage.

0.5 % of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.



Test Report No.: W7L-P24100005RF06

3.3.4 TEST RESULTS

Please Refer to Appendix Of this test report.




3.4 BAND EDGE MEASUREMENTC

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

- a) All measurements were done at low and high operational frequency range.
- b) Connect the transmitter to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.
- c) Tune the analyzer to the nominal center frequency of the emission bandwidth (EBW)
- d) Set the resolution bandwidth (RBW) $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
- e) Beyond the 1MHz band from the band edge, RBW=1MHz was used.
- f) Set the video bandwidth (VBW) to $\geq 3 \times$ RBW.
- g) Select the average power (RMS) display detector.
- h) Set the number of measurement points to ≥ 1001 .
- i) Use auto-coupled sweep time.
- j) Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.
- k) The RF fundamental frequency should be excluded against the limit line in the operating frequency band and use RBW is 10KHz or 100KHz.
- l) Record the max trace plot into the test report.



Test Report No.: W7L-P24100005RF06

3.4.4. TEST RESULTS

Please Refer to Appendix Of this test report.



3.5 CONDUCTED SPURIOUS EMISSIONS


3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13dBm .

3.5.2 TEST PROCEDURE

- The EUT makes a phone call to the communication simulator. All measurements were done at low, middle, and high operational frequency range.
- Measuring frequency range is from 30MHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP





Test Report No.: W7L-P24100005RF06

3.5.4 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

Please Refer to Appendix Of this test report.

3.6 RADIATED EMISSION MEASUREMENT

3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13dBm .

3.6.2 TEST PROCEDURES

- a. The substitute method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator exports the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved the receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value” of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

3.6.3 DEVIATION FROM TEST STANDARD


No deviation

3.6.4 TEST SETUP

< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >






BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depending on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

3.6.5 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA


30 MHz – 1GHz data:

GSM1900(Ant0) (UP):

CHANNEL BANDWIDTH: 512 ~ 810


MODE	TX channel 661	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	31.940	-56.31	-53.27	-13.00	-43.31	-3.04 Peak	Horizontal
2		84.320	-63.47	-50.75	-13.00	-50.47	-12.72 Peak	Horizontal
3		125.060	-62.75	-47.03	-13.00	-49.75	-15.72 Peak	Horizontal
4		152.220	-63.15	-48.62	-13.00	-50.15	-14.53 Peak	Horizontal
5		269.590	-65.07	-54.82	-13.00	-52.07	-10.25 Peak	Horizontal
6		540.220	-69.15	-64.43	-13.00	-56.15	-4.72 Peak	Horizontal



MODE	TX channel 661	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	32.910	-72.30	-51.04	-13.00	-59.30	-21.26	Peak	Vertical
2	94.990	-63.38	-46.39	-13.00	-50.38	-16.99	Peak	Vertical
3 PP	178.410	-61.83	-51.30	-13.00	-48.83	-10.53	Peak	Vertical
4	271.530	-63.83	-60.23	-13.00	-50.83	-3.60	Peak	Vertical
5	419.940	-68.04	-63.67	-13.00	-55.04	-4.37	Peak	Vertical
6	567.380	-66.72	-64.32	-13.00	-53.72	-2.40	Peak	Vertical





**BUREAU
VERITAS**

Test Report No.: W7L-P24100005RF06

ABOVE 1GHz DATA

Note: For higher frequency, the emission is too low to be detected.


WORST-CASE DATA

GSM 1900(Ant0) (UP):

CH 512


MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-51.23	-59.63	-13.00	-38.23	8.40	Peak	Horizontal
2 PP	5541.000	-50.97	-62.77	-13.00	-37.97	11.80	Peak	Horizontal



MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-50.79	-59.42	-13.00	-37.79	8.63	Peak	Vertical
2 PP	5550.000	-50.44	-62.77	-13.00	-37.44	12.33	Peak	Vertical



CH 661


MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-51.88	-60.24	-13.00	-38.88	8.36	Peak	Horizontal
2 PP	5640.000	-50.19	-62.00	-13.00	-37.19	11.81	Peak	Horizontal



MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-51.84	-60.47	-13.00	-38.84	8.63	Peak	Vertical
2 PP	5640.000	-49.94	-62.26	-13.00	-36.94	12.32	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CH 810


MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3812.000	-51.03	-59.34	-13.00	-38.03	8.31	Peak	Horizontal
2 PP	5727.000	-50.25	-62.07	-13.00	-37.25	11.82	Peak	Horizontal



MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3818.000	-51.70	-60.33	-13.00	-38.70	8.63	Peak	Vertical
2 PP	5731.000	-50.18	-62.49	-13.00	-37.18	12.31	Peak	Vertical




EDGE 1900(Ant0) (UP):

CH 512


MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3700.000	-51.62	-60.02	-13.00	-38.62	8.40	Peak	Horizontal
2 PP	5541.000	-46.69	-58.49	-13.00	-33.69	11.80	Peak	Horizontal



MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-51.17	-59.80	-13.00	-38.17	8.63	Peak	Vertical
2 PP	5550.000	-49.99	-62.32	-13.00	-36.99	12.33	Peak	Vertical



CH 661


MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-52.25	-60.61	-13.00	-39.25	8.36	Peak	Horizontal
2 PP	5640.000	-43.34	-55.15	-13.00	-30.34	11.81	Peak	Horizontal



MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-52.43	-61.06	-13.00	-39.43	8.63	Peak	Vertical
2 PP	5640.000	-48.01	-60.33	-13.00	-35.01	12.32	Peak	Vertical



CH 810


MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3818.000	-50.31	-58.62	-13.00	-37.31	8.31	Peak	Horizontal
2		5727.000	-51.12	-62.94	-13.00	-38.12	11.82	Peak	Horizontal



MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3812.000	-51.14	-59.77	-13.00	-38.14	8.63	Peak	Vertical
2 PP	5727.000	-49.75	-62.06	-13.00	-36.75	12.31	Peak	Vertical





BUREAU
VERITAS


Test Report No.: W7L-P24100005RF06

WCDMA Band II(Ant0) (UP):

CH 9262


MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3704.800	-50.35	-58.75	-13.00	-37.35	8.40	Peak	Horizontal
2 PP	5560.000	-49.05	-60.85	-13.00	-36.05	11.80	Peak	Horizontal



MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3698.000	-51.38	-60.01	-13.00	-38.38	8.63	Peak	Vertical
2 PP	5557.200	-49.27	-61.60	-13.00	-36.27	12.33	Peak	Vertical



CH 9400


MODE	TX channel 9400	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-51.32	-59.68	-13.00	-38.32	8.36	Peak	Horizontal
2 PP	5640.000	-50.02	-61.83	-13.00	-37.02	11.81	Peak	Horizontal



MODE	TX channel 9400	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-50.82	-59.45	-13.00	-37.82	8.63	Peak	Vertical
2 PP	5636.000	-48.03	-60.35	-13.00	-35.03	12.32	Peak	Vertical



CH 9538


MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3812.000	-51.21	-59.52	-13.00	-38.21	8.31	Peak	Horizontal
2 PP	5722.800	-50.36	-62.18	-13.00	-37.36	11.82	Peak	Horizontal



MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3815.200	-50.03	-58.66	-13.00	-37.03	8.63	Peak	Vertical
2 PP	5731.000	-49.41	-61.72	-13.00	-36.41	12.31	Peak	Vertical




LTE Band 2(Ant0) (UP):

CHANNEL BANDWIDTH: 1.4MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-50.63	-58.98	-13.00	-37.63	8.35	Peak	Horizontal
2 PP	5636.000	-49.58	-61.39	-13.00	-36.58	11.81	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-51.24	-59.87	-13.00	-38.24	8.63	Peak	Vertical
2 PP	5640.000	-49.89	-62.21	-13.00	-36.89	12.32	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CHANNEL BANDWIDTH: 3MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-50.60	-58.96	-13.00	-37.60	8.36	Peak	Horizontal
2 PP	5640.000	-48.67	-60.48	-13.00	-35.67	11.81	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-50.18	-58.81	-13.00	-37.18	8.63	Peak	Vertical
2 PP	5636.000	-48.18	-60.50	-13.00	-35.18	12.32	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CHANNEL BANDWIDTH: 5MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-50.89	-59.24	-13.00	-37.89	8.35	Peak	Horizontal
2 PP	5636.000	-49.62	-61.43	-13.00	-36.62	11.81	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-51.53	-60.16	-13.00	-38.53	8.63	Peak	Vertical
2 PP	5640.000	-49.09	-61.41	-13.00	-36.09	12.32	Peak	Vertical




CHANNEL BANDWIDTH: 10MHz / QPSK

CH18650


MODE	TX channel 18650	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3710.000	-50.86	-59.25	-13.00	-37.86	8.39	Peak	Horizontal
2 PP	5560.000	-49.53	-61.33	-13.00	-36.53	11.80	Peak	Horizontal



MODE	TX channel 18650	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3717.000	-51.42	-60.05	-13.00	-38.42	8.63	Peak	Vertical
2 PP	5565.000	-49.77	-62.10	-13.00	-36.77	12.33	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CH18900


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-52.04	-60.40	-13.00	-39.04	8.36	Peak	Horizontal
2 PP	5640.000	-49.50	-61.31	-13.00	-36.50	11.81	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-51.05	-59.68	-13.00	-38.05	8.63	Peak	Vertical
2 PP	5636.000	-47.66	-59.98	-13.00	-34.66	12.32	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CH19150


MODE	TX channel 19150	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3812.000	-51.27	-59.58	-13.00	-38.27	8.31	Peak	Horizontal
2 PP	5715.000	-49.62	-61.44	-13.00	-36.62	11.82	Peak	Horizontal



MODE	TX channel 19150	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3810.000	-51.44	-60.07	-13.00	-38.44	8.63	Peak	Vertical
2 PP	5712.000	-49.36	-61.67	-13.00	-36.36	12.31	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

CHANNEL BANDWIDTH: 15MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-52.00	-60.35	-13.00	-39.00	8.35	Peak	Horizontal
2 PP	5636.000	-50.44	-62.25	-13.00	-37.44	11.81	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-49.28	-57.91	-13.00	-36.28	8.63	Peak	Vertical
2 PP	5640.000	-48.25	-60.57	-13.00	-35.25	12.32	Peak	Vertical



CHANNEL BANDWIDTH: 20MHz / QPSK


MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3755.000	-51.64	-60.00	-13.00	-38.64	8.36	Peak	Horizontal
2 PP	5640.000	-49.65	-61.46	-13.00	-36.65	11.81	Peak	Horizontal



MODE	TX channel 18900	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60Hz
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	3760.000	-50.39	-59.02	-13.00	-37.39	8.63	Peak	Vertical
2 PP	5636.000	-48.05	-60.37	-13.00	-35.05	12.32	Peak	Vertical




3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth.
2. Set the number of counts to a value that stabilizes the measured CCDF curve.
3. Record the maximum PAPR level associated with a probability of 0.1%.



Test Report No.: W7L-P24100005RF06

3.7.4 TEST RESULTS

Please Refer to Appendix Of this test report.



Test Report No.: W7L-P24100005RF06

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

5 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:

Tel: +86-755-88696566

Fax: +86-755-88696577

Email: customerservice.sw@bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



Test Report No.: W7L-P24100005RF06

6 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

7 APPENDIX


GSM 1900

PEAK-TO-AVERAGE RATIO(CCDF)

Test Result

Band	Channel	Result(dB)	Limit(dB)	Verdict
GSM1900	512	2.61	13	PASS
GSM1900	661	2.62	13	PASS
GSM1900	810	2.63	13	PASS
EGPRS1900	512	5.48	13	PASS
EGPRS1900	661	5.48	13	PASS
EGPRS1900	810	5.41	13	PASS

Test Graphs




26DB BANDWIDTH AND OCCUPIED BANDWIDTH

Test Result

Band	Channel	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit (MHz)	Verdict
GSM1900	512	0.24666	0.3124	---	PASS
GSM1900	661	0.24647	0.3042	---	PASS
GSM1900	810	0.24749	0.3132	---	PASS
EGPRS1900	512	0.24534	0.3142	---	PASS
EGPRS1900	661	0.25047	0.3111	---	PASS
EGPRS1900	810	0.25038	0.3085	---	PASS

Test Graphs






Test Report No.: W7L-P24100005RF06

BAND EDGE

Test Result

Band	Channel	Freq (MHz)	Result (dBm)	Limit(dBm)	Verdict
GSM1900	512	1849.98	-28.31	-13	PASS
GSM1900	810	1910.02	-28.39	-13	PASS
EGPRS1900	512	1849.98	-35.54	-13	PASS
EGPRS1900	810	1910.04	-36.06	-13	PASS

Test Graphs




CONDUCTED SPURIOUS EMISSION

Test Result

Band	Channel	Frequency Range(MHz)	Max.Freq. (MHz)	Result (dBm)	Limit (dBm)	Verdict
GSM1900	512	30~1000MHz	895.14	-49.75	-13	PASS
GSM1900	512	1000~10000MHz	3827.8	-31.69	-13	PASS
GSM1900	512	10000~20000MHz	19346.5	-38.15	-13	PASS
GSM1900	661	30~1000MHz	894.56	-49.73	-13	PASS
GSM1900	661	1000~10000MHz	3838.6	-31.76	-13	PASS
GSM1900	661	10000~20000MHz	19310.5	-38.31	-13	PASS
GSM1900	810	30~1000MHz	868.86	-49.75	-13	PASS
GSM1900	810	1000~10000MHz	3842.65	-31.45	-13	PASS
GSM1900	810	10000~20000MHz	19320.5	-38.28	-13	PASS
EGPRS1900	512	30~1000MHz	895.43	-49.72	-13	PASS
EGPRS1900	512	1000~10000MHz	3836.35	-31.7	-13	PASS
EGPRS1900	512	10000~20000MHz	19334	-38.22	-13	PASS
EGPRS1900	661	30~1000MHz	906.4	-49.76	-13	PASS
EGPRS1900	661	1000~10000MHz	3795.4	-31.73	-13	PASS
EGPRS1900	661	10000~20000MHz	19144.5	-38.31	-13	PASS
EGPRS1900	810	30~1000MHz	906.69	-49.75	-13	PASS
EGPRS1900	810	1000~10000MHz	3817.45	-31.56	-13	PASS
EGPRS1900	810	10000~20000MHz	19343	-38.36	-13	PASS


Test Graphs





BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06



BV 7Layers Communications Technology
(Shenzhen) Co., Ltd


Room B37, Warehouse A5, No.3 Chiwan 4th Road,
Zhaoshang Street, Nanshan District Shenzhen,
Guangdong, People's Republic of China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.sw@bureauveritas.com



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06



FREQUENCY STABILITY

Test Result

Voltage									
Band	Channel	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	FL (MHz)	FH (MHz)	Limit (MHz)	Verdict
GSM1900	512	VN	NT	720.00	0.389147	1850.07983	---	1850-1910	PASS
GSM1900	512	VL	NT	910.00	0.491839	1850.07866	---	1850-1910	PASS
GSM1900	512	VH	NT	1180.00	0.637769	1850.078015	---	1850-1910	PASS
GSM1900	810	VN	NT	660.00	0.345586	---	1909.92227	1850-1910	PASS
GSM1900	810	VL	NT	-360.00	-0.188501	---	1909.92131	1850-1910	PASS
GSM1900	810	VH	NT	0.00	0.000000	---	1909.92187	1850-1910	PASS

Temperature									
Band	Channel	Voltage [Vdc]	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	FL (MHz)	FH (MHz)	Limit (MHz)	Verdict
GSM1900	512	NV	-30	-220.00	-0.118906	1850.076975	---	1850-1910	PASS
GSM1900	512	NV	-20	-610.00	-0.329694	1850.07863	---	1850-1910	PASS
GSM1900	512	NV	-10	900.00	0.486434	1850.07918	---	1850-1910	PASS
GSM1900	512	NV	0	40.00	0.021619	1850.078895	---	1850-1910	PASS
GSM1900	512	NV	10	-120.00	-0.064858	1850.07679	---	1850-1910	PASS
GSM1900	512	NV	20	260.00	0.140525	1850.07816	---	1850-1910	PASS
GSM1900	512	NV	30	1470.00	0.794509	1850.078935	---	1850-1910	PASS
GSM1900	512	NV	40	200.00	0.108096	1850.077405	---	1850-1910	PASS
GSM1900	512	NV	50	1510.00	0.816128	1850.0777	---	1850-1910	PASS
GSM1900	810	NV	-30	1270.00	0.664991	---	1909.924595	1850-1910	PASS
GSM1900	810	NV	-20	-340.00	-0.178029	---	1909.921885	1850-1910	PASS
GSM1900	810	NV	-10	-520.00	-0.272280	---	1909.92226	1850-1910	PASS



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

GSM190 0	810	NV	0	-680.00	-0.35605 8	---	1909.920 995	1850-191 0	PASS
GSM190 0	810	NV	10	1050.00	0.549796	---	1909.924 28	1850-191 0	PASS
GSM190 0	810	NV	20	1280.00	0.670227	---	1909.924 61	1850-191 0	PASS
GSM190 0	810	NV	30	910.00	0.476490	---	1909.923 62	1850-191 0	PASS
GSM190 0	810	NV	40	100.00	0.052362	---	1909.922 41	1850-191 0	PASS
GSM190 0	810	NV	50	720.00	0.377003	---	1909.922 97	1850-191 0	PASS



Test Report No.: W7L-P24100005RF06


WCDMA BAND 2

PEAK-TO-AVERAGE RATIO

Test Result

Band	Channel	Peak-to-Average Ratio(dB)	Limit(dBm)	Verdict
Band2	9262	3.06	13	PASS
Band2	9400	3.06	13	PASS
Band2	9538	2.88	13	PASS

Test Graphs






Test Report No.: W7L-P24100005RF06

26DB BANDWIDTH AND OCCUPIED BANDWIDTH

Test Result

Band	Channel	Occupied Bandwidth (MHz)	26dB Bandwidth (MHz)	Limit(MHz)	Verdict
Band2	9262	4.1693	4.702	---	PASS
Band2	9400	4.1632	4.705	---	PASS
Band2	9538	4.1716	4.711	---	PASS

Test Graphs





Test Report No.: W7L-P24100005RF06

BAND EDGE

Test Result

Band	Channel	Frequency (MHz)	Result (dBm)	Limit(dBm)	Verdict
Band2	9262	1849.89	-30.05	-13	PASS
Band2	9538	1910.12	-29.48	-13	PASS

Test Graphs




CONDUCTED SPURIOUS EMISSION

Test Result

Band	Channel	Frequency Range (Mhz)	Frequency (dBm)	Result (dBm)	Limit (dBm)	Verdict
Band2	9262	30~1000MHz	913.86	-49.03	-13	PASS
Band2	9262	1000~10000MHz	3852.55	-40.64	-13	PASS
Band2	9262	10000~20000MHz	19387	-37.23	-13	PASS
Band2	9400	30~1000MHz	890.78	-49.11	-13	PASS
Band2	9400	1000~10000MHz	3871.45	-40.65	-13	PASS
Band2	9400	10000~20000MHz	19351	-37.15	-13	PASS
Band2	9538	30~1000MHz	864.59	-48.86	-13	PASS
Band2	9538	1000~10000MHz	3831.4	-40.88	-13	PASS
Band2	9538	10000~20000MHz	19259.5	-37.4	-13	PASS


Test Graphs





BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06



FREQUENCY STABILITY

Test Result

Voltage									
Band	Channel	Voltage (Vdc)	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	FL (MHz)	FH (MHz)	Limit (MHz)	Verdict
Band2	9262	VN	NT	-680.00	-0.367091	1850.31387	---	1850-1910	PASS
Band2	9262	VL	NT	2650.00	1.430577	1850.31645	---	1850-1910	PASS
Band2	9262	VH	NT	970.00	0.523645	1850.31637	---	1850-1910	PASS
Band2	9538	VN	NT	-10090.00	-5.289369	---	1909.67351	1850-1910	PASS
Band2	9538	VL	NT	-12180.00	-6.384986	---	1909.67032	1850-1910	PASS
Band2	9538	VH	NT	-7930.00	-4.157056	---	1909.67662	1850-1910	PASS

Temperature									
Band	Channel	Voltage (Vdc)	Temperature (°C)	Deviation (Hz)	Deviation (ppm)	FL (MHz)	FH (MHz)	Limit (MHz)	Verdict
Band2	9262	NV	-30	-470.00	-0.253725	1850.31253	---	1850-1910	PASS
Band2	9262	NV	-20	-390.00	-0.210538	1850.31421	---	1850-1910	PASS
Band2	9262	NV	-10	3800.00	2.051393	1850.31915	---	1850-1910	PASS
Band2	9262	NV	0	3820.00	2.062190	1850.31837	---	1850-1910	PASS
Band2	9262	NV	10	4020.00	2.170158	1850.31777	---	1850-1910	PASS
Band2	9262	NV	20	-3650.00	-1.970417	1850.31345	---	1850-1910	PASS
Band2	9262	NV	30	-860.00	-0.464263	1850.31464	---	1850-1910	PASS
Band2	9262	NV	40	-440.00	-0.237530	1850.31601	---	1850-1910	PASS
Band2	9262	NV	50	5050.00	2.726193	1850.31425	---	1850-1910	PASS
Band2	9538	NV	-30	-7030.00	-3.685259	---	1909.67877	1850-1910	PASS
Band2	9538	NV	-20	-10430.00	-5.467603	---	1909.67212	1850-1910	PASS
Band2	9538	NV	-10	-11190.00	-5.866010	---	1909.67276	1850-1910	PASS
Band2	9538	NV	0	-9950.00	-5.2159	---	1909.6	1850-1910	PASS



BUREAU
VERITAS

Test Report No.: W7L-P24100005RF06

				0	78		746	910	
Band2	9538	NV	10	-8150.0 0	-4.2723 84	---	1909.6 7645	1850-1 910	PASS
Band2	9538	NV	20	-9060.0 0	-4.7494 23	---	1909.6 7469	1850-1 910	PASS
Band2	9538	NV	30	-6780.0 0	-3.5542 04	---	1909.6 8082	1850-1 910	PASS
Band2	9538	NV	40	-8140.0 0	-4.2671 42	---	1909.6 7511	1850-1 910	PASS
Band2	9538	NV	50	-6640.0 0	-3.4808 14	---	1909.6 7821	1850-1 910	PASS



Test Report No.: W7L-P24100005RF06

LTE BAND B2

PEAK-TO-AVERAGE RATIO(CCDF)

Test Result

Band	Bandwidth	Modulation	Channel	RB Configuration	Result(dB)	Limit(dB)	Verdict
Band2	20MHz	QPSK	18700	1RB#0	5.09	13	PASS
Band2	20MHz	QPSK	18700	100RB#0	5.45	13	PASS
Band2	20MHz	QPSK	18900	1RB#0	5.07	13	PASS
Band2	20MHz	QPSK	18900	100RB#0	5.62	13	PASS
Band2	20MHz	QPSK	19100	1RB#0	5.07	13	PASS
Band2	20MHz	QPSK	19100	100RB#0	5.28	13	PASS

Test Graphs

