



RF TEST REPORT

Report No.: SET2021-09572

Product Name: Wi-Fi 6 Router

FCC ID: 2AG32ER2820

IC: 20982-ER2820

Model No. : ER2820

Applicant: Baicells Technologies Co., Ltd.

Address: 9-10F, 1st Bldg., No. 81 Beiqing Road, Haidian District, Beijing, China

Dates of Testing: 07/10/2021 — 08/09/2021

Issued by: CCIC Southern Testing Co., Ltd.

Lab Location: Electronic Testing Building, No. 43 Shahe Road, Xili Street,
Nanshan District, Shenzhen, Guangdong, China.

Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of 73 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 20 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Test Report

Product Name: Wi-Fi 6 Router

Brand Name: Baicells

Trade Name: Baicells

Applicant: Baicells Technologies Co., Ltd.

Applicant Address: 9-10F, 1st Bldg., No. 81 Beiqing Road, Haidian District,
Beijing, China


Manufacturer: Baicells Technologies Co., Ltd.

Manufacturer Address: 9-10F, 1st Bldg., No. 81 Beiqing Road, Haidian District,
Beijing, China

Test Standards: 47 CFR Part 15 Subpart C, 15.247
IC RSS-Gen(Issue 5, April 2018)
IC RSS-247(Issue 2, Feb. 2017)

Test Result: PASS

Tested by:  2021.08.09
Sun, Test Engineer

Reviewed by:  2021.08.09
Chris You, Senior Engineer

Approved by:  2021.08.09
Shuangwen Zhang, Manager

TABLE OF CONTENTS

RF TEST REPORT	1
1. GENERAL INFORMATION	4
1.1. EUT Description	4
1.2. Test Standards and Results	5
1.3. Table for Supporting Units	6
1.4. EUT Operation Test Setup	6
1.5. Facilities and Accreditations	7
2. 47 CFR PART 15C REQUIREMENTS.....	9
2.1. Antenna requirement	9
2.2. Maximum Conducted Output Power	10
2.3. 6dB and 99% Bandwidth	12
2.4. Conducted Band Edges and Spurious Emissions.....	14
2.5. Power spectral density (PSD)	16
2.6. Radiated Band Edge and Spurious Emission	17
2.7. Conducted Emission	41
3. LIST OF MEASURING EQUIPMENT	45
APPENDIX A	46

Change History		
Issue	Date	Reason for change
1.0	2021.08.09	First edition

1. General Information

1.1. EUT Description

EUT Type	Wi-Fi 6 Router
EUT supports Radios application	WLAN 2.4GHz 802.11b/g/n/ax
Hardware Version	BaiCE_ER2820_1.0.0
Software Version	ER2820 V1.00
Frequency Range	802.11b/g/n-HT20/ax-HE20MHz/: 2412~2462MHz 802.11n-HT40/ax-HE40:2422~2452MHz
Channel Number	2.4GHz:11 for 802.11b/g/n-HT20/ax-HE20 9 for 802.11n-HT40/ ax-HE40
Bit Rate of Transmitter	2.4GHz:802.11b: 11/5.5/2/1 Mbps 802.11g: 54/48/36/24/18/12/9/6 Mbps 802.11n: up to 300 Mbps(2x2MIMO) 802.11ax:up to 573.5Mbps(2x2MIMO)
Modulation Type	DSSS, OFDM, OFDMA
MIMO	Support, 2x2MIMO
Antenna Type	Internal
Antenna Gain	Antenna(0): 3dBi Antenna(1): 3dBi

Note 1: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

Note 2: The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

Note 3: The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers for 2.4GHz WLAN.

Note 4: The antenna gain and RF adapter/cable insert loss provided by manufacture.

Frequency	Modulation Mode	TX / RX Function
2.4GHz	802.11b	1TX / 1RX
	802.11g	1TX / 1RX
	802.11n (HT20)	1TX / 1RX or 2TX / 2RX
	802.11n (HT40)	1TX / 1RX or 2TX / 2RX
	802.11ax (HE20)	1TX / 1RX or 2TX / 2RX
	802.11ax (HE40)	1TX / 1RX or 2TX / 2RX

1.2. Test Standards and Results

The objective of the report is to perform testing according to FCC/IC Certification:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart C	Radio Frequency Devices
2	ANSI C63.10 2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB Publication 662911 D01 v02r01	Emission Testing of Transmitters with Multiple Outputs in the same Band(e.g., MIMO, Smart Antenna, etc)
4	RSS-Gen (Issue 5, April 2018) Amendment2 (February 2021)	General Requirements for Compliance Of Radio Apparatus
5	RSS-247 (Issue 2, Feb. 2017)	Digital Transmission System(DTSS) Frequency Hopping System(FHSS) and Licence-Exempt Local Area Network (LE-LAN) Device

Test detailed items/section required by FCC rules and results are as below:

No.	Section in CFR 47	IC Rules	Description	Result
1	15.203	RSS-GEN, 6.8	Antenna Requirement	PASS
2	15.247(b)	RSS-247, 5.4	Peak Output Power and EIRP	PASS
3	15.247(a)	RSS-GEN, 6.7 RSS-247, 5.2	6dB and 99% Occupied Bandwidth	PASS
4	15.247(d)	RSS-247, 5.5	Conducted Band Edges and Spurious Emission	PASS
5	15.247(e)	RSS-247, 5.2	Power spectral density (PSD)	PASS
6	15.207	RSS-GEN, 8.8	Conducted Emission	PASS
7	15.209 15.205 15.247(d)	RSS-247, 5.5	Radiated Band Edges and Spurious Emission	PASS

The tests of Conducted Emission and Radiated Emission were performed according to the method of measurements prescribed in ANSI C63.10-2013.

These RF tests were performed according to the method of measurements prescribed in ANSI C63.10 2013

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

There are two bandwidth systems:

For 20MHz bandwidth systems, use Channel 1~ Channel 11

For 40MHz bandwidth systems, use Channel 3~ Channel 9

Channel No.	Frequency	Channel No.	Frequency	Channel No.	Frequency
1	2412MHz	5	2432MHz	9	2452MHz
2	2417MHz	6	2437MHz	10	2457MHz
3	2422MHz	7	2442MHz	11	2462MHz
4	2427MHz	8	2447MHz		

Test Items	Mode	Data Rate	Channel
Peak Conducted Output Power Power Spectral Density 6dB Bandwidth Conducted and Spurious Emission Radiated and Spurious Emission	11b/DSSS	1 Mbps	1/6/11
	11g/OFDM	6 Mbps	1/6/11
	11n(20MHz)/OFDM 11ax(20MHz)/OFDMA	MCS 0	1/6/11
	11n(40MHz)/OFDM 11ax(40MHz)/OFDMA	MCS 0	3/6/9
Band Edge	11b/DSSS	1 Mbps	1/11
	11g/OFDM	6 Mbps	1/11
	11n(20MHz)/OFDM 11ax(20MHz)/OFDMA	MCS 0	1/11
	11n(40MHz)/OFDM 11ax(40MHz)/OFDMA	MCS 0	3/9

1.3. Table for Supporting Units

No.	Equipment	Brand Name	Model Name	Manufacturer	Serial No.	Note
1	Notebook	DELL	PP11L	DELL	H5914A03	FCC DOC

1.4. EUT Operation Test Setup

For RF test items, an engineering test program was provided and enable to make EUT transmitting.

1.5. Facilities and Accreditations

1.5.1. Facilities

FCC-Registration No.: CN1283

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until April 19th,2023

ISED Registration: 11185A-1

CAB identifier: CN0064

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A-1 on Aug. 04, 2016, valid time is until April 20th,2023

A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

1.5.2. Test Environment Conditions

Operating Environment	
Temperature	24°C
Humidity	57 % RH
Atmospheric Pressure	1010 mbar
Test mode:	
Continuously transmitting mode	Keeps the EUT in 100% duty cycle transmitting with modulation in SISO and MIMO mode, duty cycle factor is not required.

Pretest Test Mode	Description
Mode 1	TX B Mode / CH1, CH6, CH11
Mode 2	TX G Mode / CH1, CH6, CH11
Mode 3	TX N20 Mode / CH1, CH6, CH11
Mode 4	TX N40 Mode / CH3, CH6, CH9
Mode 5	TX AX20 Mode / CH1, CH6, CH11
Mode 6	TX AX 40 Mode / CH3, CH6, CH9
Mode 7	TX Mode

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Test	
Final Test Mode	Description
Mode 5	TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 1	TX B Mode / CH1, CH6, CH11
Mode 2	TX G Mode / CH1, CH6, CH11
Mode 3	TX N20 Mode / CH1, CH6, CH11
Mode 4	TX N40 Mode / CH3, CH6, CH9
Mode 5	TX AX20 Mode / CH1, CH6, CH11
Mode 6	TX AX 40 Mode / CH3, CH6, CH9

2. 47 CFR Part 15C Requirements

2.1. Antenna requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

And according to FCC 47 CFR Section 15.247(c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

2.1.2. Antenna Information

Working Frequency	Antenna type	Chain	Gain(dBi)
2412-2462MHz	Internal	0	3
		1	3
		0+1	6

Note: 1. for 802.11n/ax (20/40MHz) mode, antenna 0, 1 can transmit/receive simultaneously (MIMO mode), for 802.11b/g, both antennas 0, 1 can transmit/receive at single mode (SISO mode)

2. According to KDB662911, If all transmit signals are completely uncorrelated with each other, If all transmit signals are completely correlated with each other, Directional gain = $G_{ANT} + 10 \log(N_{ANT})$ dBi

2.1.3. Result: comply

The EUT has a permanently and irreplaceable attached antenna. Please refer to the EUT internal photos.

2.2. Maximum Conducted Output Power

2.2.1. Limit of Peak Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

2.2.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.2.3. Test Setup



2.2.4. Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10:2013.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.



2.2.5. Test Result

Please refer to Appendix A for detail

2.3. 6dB and 99% Bandwidth


2.3.1. Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

2.3.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.3.3. Test Setup



2.3.4. Test Procedures

1. The testing follows ANSI C63.10 2013.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30 kHz and set the Video bandwidth (VBW) = 100 kHz.
6. Measure and record the results in the test report.

2.3.5. Test Results of 6dB Bandwidth

Please refer to Appendix A for detail

2.4. Conducted Band Edges and Spurious Emissions


2.4.1. Limit of Conducted Band Edges and Spurious Emissions

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

2.4.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.4.3. Test Setup



2.4.4. Test Procedure

1. The testing follows ANSI C63.10 2013.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

2.4.5. Test Results of Conducted Band Edges

Please refer to Appendix A for detail

2.5. Power spectral density (PSD)


2.5.1. Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

2.5.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.5.3. Test Setup



2.5.4. Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of ANSI C63.10 2013.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz.

Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)

5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.

6. Measure and record the results in the test report.

7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

2.5.5. Test Results of Power spectral density

Please refer to Appendix A for detail

2.6. Radiated Band Edge and Spurious Emission

2.6.1. Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Note: Wireless charger configuration was evaluated.


Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

2.6.2. Measuring Instruments


The measuring equipment is listed in the section 3 of this test report.

2.6.3. Test Setup


For radiated emissions from 9 KHz to 30 MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



2.6.4. Test Procedures

1. The EUT was placed on the top of a rotating table 0.8m for below 1GHz/1.5m for above 1GHz above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. Height of receiving antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported.

Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $> 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.
5. Only provide worst-case mode data at report.

2.6.5. Test Results of Radiated Band Edge and Spurious Emission

For 9 kHz to 30MHz


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

For 30MHz to 1000 MHz (MIMO Mode)



30MHz to 1GHz, Antenna Horizontal

Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Corr. Factor (dB/m)	Antenna height (cm)	Limit (dBμV/m)	Margin	Antenna	Verdict
30.00000012	18.70	120.000	10.5	150.0	40.0	21.3	Horizontal	Pass
123.300000	19.32	120.000	11.6	150.0	43.5	24.18	Horizontal	Pass
237.590000	26.83	120.000	11.9	150.0	46.0	19.17	Horizontal	Pass
286.530000	32.00	120.000	13.1	150.0	46.0	14	Horizontal	Pass
311.860000	40.03	120.000	13.1	150.0	46.0	5.97	Horizontal	Pass
362.040000	42.00	120.000	17.5	150.0	46.0	4	Horizontal	Pass



30MHz to 1GHz, Antenna Vertical

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Corr. Factor (dB μ V/m)	Antenna height (cm)	Limit (dB μ V/m)	Margin	Antenna	Verdict
30.000000	21.15	120.000	11.9	100.0	40.0	18.85	Vertical	Pass
42.290000	24.48	120.000	15.8	100.0	40.0	15.52	Vertical	Pass
108.520000	20.29	120.000	17.5	100.0	43.5	23.21	Vertical	Pass
155.350000	24.81	120.000	17.5	100.0	43.5	18.69	Vertical	Pass
311.860000	33.30	120.000	18.5	100.0	46.0	12.7	Vertical	Pass
361.980000	40.58	120.000	24.8	100.0	46.0	5.42	Vertical	Pass

For 1GHz to 25 GHz
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11b_2412MHz, ANT0)

No.	Fre. (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	52.65	PK	74.00	-21.35	1.50	120.00	51.35	5.20	28.60	32.50	1.30
2	2390.00	41.47	AV	54.00	-12.53	1.50	120.00	40.17	5.20	28.60	32.50	1.30
3	4824.00	52.33	PK	74.00	-21.67	1.50	120.00	45.93	7.40	30.40	31.40	6.40
4	4824.00	40.44	AV	54.00	-13.56	1.50	120.00	34.04	7.40	30.40	31.40	6.40
5	7236.00	52.33	PK	74.00	-21.67	1.50	120.00	41.83	11.50	31.20	32.20	10.50
6	7236.00	40.74	AV	54.00	-13.26	1.50	120.00	30.24	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11b_2412MHz, ANT0)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	49.95	PK	74.00	-24.05	1.50	160.00	48.65	5.20	28.60	32.50	1.30
2	2390.00	38.46	AV	54.00	-15.54	1.50	160.00	37.16	5.20	28.60	32.50	1.30
3	4824.00	51.55	PK	74.00	-22.45	1.50	160.00	45.15	7.40	30.40	31.40	6.40
4	4824.00	40.20	AV	54.00	-13.80	1.50	160.00	33.80	7.40	30.40	31.40	6.40
5	7236.00	51.87	PK	74.00	-22.13	1.50	160.00	41.37	11.50	31.20	32.20	10.50
6	7236.00	39.22	AV	54.00	-14.78	1.50	160.00	28.72	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11b_2437MHz, ANT0)

No.	Fre. (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	50.36	PK	74.00	-23.64	1.60	290.00	43.96	6.70	30.40	31.30	6.40
2	4874.00	38.33	AV	54.00	-15.67	1.60	290.00	31.93	6.70	30.40	31.30	6.40
3	7311.00	51.24	PK	74.00	-22.76	1.60	290.00	40.44	11.80	31.20	32.20	10.80
4	7311.00	38.85	AV	54.00	-15.15	1.60	290.00	28.05	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11b_2437MHz, ANT0)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	52.62	PK	74.00	-21.38	1.50	300.00	46.22	6.70	30.40	31.30	6.40
2	4874.00	40.06	AV	54.00	-13.94	1.50	300.00	33.66	6.70	30.40	31.30	6.40
3	7311.00	51.98	PK	74.00	-22.02	1.50	300.00	41.18	11.80	31.20	32.20	10.80
4	7311.00	39.11	AV	54.00	-14.89	1.50	300.00	28.31	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11b_2462MHz, ANT0)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	54.26	PK	74.00	-19.74	1.60	150.00	52.66	5.30	28.70	32.40	1.60
2	2483.50	41.87	AV	54.00	-12.13	1.60	150.00	40.27	5.30	28.70	32.40	1.60
3	4924.00	52.65	PK	74.00	-21.35	1.60	150.00	46.95	6.70	30.50	31.50	5.70
4	4924.00	40.08	AV	54.00	-13.92	1.60	150.00	34.38	6.70	30.50	31.50	5.70
5	7386.00	52.88	PK	74.00	-21.12	1.60	150.00	42.08	11.80	31.20	32.20	10.80
6	7386.00	40.46	AV	54.00	-13.54	1.60	150.00	29.66	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11b_2462MHz, ANT0)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	54.26	PK	74.00	-19.74	1.60	150.00	52.66	5.30	28.70	32.40	1.60
2	2483.50	41.87	AV	54.00	-12.13	1.60	150.00	40.27	5.30	28.70	32.40	1.60
3	4924.00	52.65	PK	74.00	-21.35	1.60	150.00	46.95	6.70	30.50	31.50	5.70
4	4924.00	40.08	AV	54.00	-13.92	1.60	150.00	34.38	6.70	30.50	31.50	5.70
5	7386.00	52.88	PK	74.00	-21.12	1.60	150.00	42.08	11.80	31.20	32.20	10.80
6	7386.00	40.46	AV	54.00	-13.54	1.60	150.00	29.66	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11g_2412MHz, ANT0)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	63.35	PK	74.00	-10.65	1.70	160.00	62.05	5.20	28.60	32.50	1.30
2	2390.00	49.24	AV	54.00	-4.76	1.70	160.00	47.94	5.20	28.60	32.50	1.30
3	4824.00	51.55	PK	74.00	-22.45	1.70	160.00	45.15	7.40	30.40	31.40	6.40
4	4824.00	38.81	AV	54.00	-15.19	1.70	160.00	32.41	7.40	30.40	31.40	6.40
5	7236.00	52.62	PK	74.00	-21.38	1.70	160.00	42.12	11.50	31.20	32.20	10.50
6	7236.00	40.49	AV	54.00	-13.51	1.70	160.00	29.99	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11g_2412MHz, ANT0)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	63.58	PK	74.00	-10.42	1.60	120.00	62.28	5.20	28.60	32.50	1.30
2	2390.00	49.56	AV	54.00	-4.44	1.60	120.00	48.26	5.20	28.60	32.50	1.30
3	4824.00	51.57	PK	74.00	-22.43	1.60	120.00	45.17	7.40	30.40	31.40	6.40
4	4824.00	39.70	AV	54.00	-14.30	1.60	120.00	33.30	7.40	30.40	31.40	6.40
5	7236.00	52.06	PK	74.00	-21.94	1.60	120.00	41.86	11.50	31.20	32.20	10.20
6	7236.00	39.84	AV	54.00	-14.16	1.60	120.00	29.64	11.50	31.20	32.20	10.20

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11g_2437MHz, ANT0)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	50.66	PK	74.00	-23.34	1.80	130.00	44.86	6.70	30.40	31.30	5.80
2	4874.00	38.54	AV	54.00	-15.46	1.80	130.00	32.74	6.70	30.40	31.30	5.80
3	7311.00	51.28	PK	74.00	-22.72	1.80	130.00	40.48	11.80	31.20	32.20	10.80
4	7311.00	39.86	AV	54.00	-14.14	1.80	130.00	29.06	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11g_2437MHz, ANT0)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	50.98	PK	74.00	-23.02	1.50	200.00	45.18	6.70	30.40	31.30	5.80
2	4874.00	39.91	AV	54.00	-14.09	1.50	200.00	34.11	6.70	30.40	31.30	5.80
3	7311.00	51.48	PK	74.00	-22.52	1.50	200.00	40.68	11.80	31.20	32.20	10.80
4	7311.00	39.22	AV	54.00	-14.78	1.50	200.00	28.42	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11g_2462MHz, ANT0)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	62.01	PK	74.00	-11.99	1.50	130.00	60.41	5.30	28.70	32.40	1.60
2	2483.50	48.99	AV	54.00	-5.01	1.50	130.00	47.39	5.30	28.70	32.40	1.60
3	4924.00	52.88	PK	74.00	-21.12	1.50	130.00	47.18	6.70	30.50	31.50	5.70
4	4924.00	41.63	AV	54.00	-12.37	1.50	130.00	35.93	6.70	30.50	31.50	5.70
5	7386.00	52.98	PK	74.00	-21.02	1.50	130.00	42.18	11.80	31.20	32.20	10.80
6	7386.00	40.86	AV	54.00	-13.14	1.50	130.00	30.06	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11g_2462MHz, ANT0)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	61.59	PK	74.00	-12.41	1.80	200.00	59.99	5.30	28.70	32.40	1.60
2	2483.50	49.47	AV	54.00	-4.53	1.80	200.00	47.87	5.30	28.70	32.40	1.60
3	4924.00	52.64	PK	74.00	-21.36	1.80	200.00	46.94	6.70	30.50	31.50	5.70
4	4924.00	40.10	AV	54.00	-13.90	1.80	200.00	34.40	6.70	30.50	31.50	5.70
5	7386.00	52.29	PK	74.00	-21.71	1.80	200.00	41.49	11.80	31.20	32.20	10.80
6	7386.00	39.09	AV	54.00	-14.91	1.80	200.00	28.29	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20_2412MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	62.25	PK	74.00	-11.75	1.50	300.00	60.95	5.20	28.60	32.50	1.30
2	2390.00	48.21	AV	54.00	-5.79	1.50	300.00	46.91	5.20	28.60	32.50	1.30
3	4824.00	51.22	PK	74.00	-22.78	1.50	300.00	44.82	7.40	30.40	31.40	6.40
4	4824.00	39.10	AV	54.00	-14.90	1.50	300.00	32.70	7.40	30.40	31.40	6.40
5	7236.00	52.06	PK	74.00	-21.94	1.50	300.00	41.56	11.50	31.20	32.20	10.50
6	7236.00	40.69	AV	54.00	-13.31	1.50	300.00	30.19	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20_2412MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	54.95	PK	74.00	-19.05	1.80	200.00	53.65	5.20	28.60	32.50	1.30
2	2390.00	40.79	AV	54.00	-13.21	1.80	200.00	39.49	5.20	28.60	32.50	1.30
3	4824.00	50.62	PK	74.00	-23.38	1.80	200.00	44.22	7.40	30.40	31.40	6.40
4	4824.00	39.19	AV	54.00	-14.81	1.80	200.00	32.79	7.40	30.40	31.40	6.40
5	7236.00	53.33	PK	74.00	-20.67	1.80	200.00	42.83	11.50	31.20	32.20	10.50
6	7236.00	42.00	AV	54.00	-12.00	1.80	200.00	31.50	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20_2437MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	52.62	PK	74.00	-21.38	1.50	180.00	46.82	6.70	30.40	31.30	5.80
2	4874.00	41.26	AV	54.00	-12.74	1.50	180.00	35.46	6.70	30.40	31.30	5.80
3	7311.00	51.87	PK	74.00	-22.13	1.50	180.00	41.07	11.80	31.20	32.20	10.80
4	7311.00	40.39	AV	54.00	-13.61	1.50	180.00	29.59	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20_2437MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	52.98	PK	74.00	-21.02	1.70	300.00	46.58	6.70	31.20	31.50	6.40
2	4874.00	40.56	AV	54.00	-13.44	1.70	300.00	34.16	6.70	31.20	31.50	6.40
3	7311.00	53.33	PK	74.00	-20.67	1.70	300.00	42.53	11.80	31.20	32.20	10.80
4	7311.00	41.90	AV	54.00	-12.10	1.70	300.00	31.10	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n20_2462MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	63.25	PK	74.00	-10.75	1.50	300.00	61.65	5.30	28.70	32.40	1.60
2	2483.50	49.94	AV	54.00	-4.06	1.50	300.00	48.34	5.30	28.70	32.40	1.60
3	4924.00	50.99	PK	74.00	-23.01	1.50	300.00	45.29	6.70	30.50	31.50	5.70
4	4924.00	38.81	AV	54.00	-15.19	1.50	300.00	33.11	6.70	30.50	31.50	5.70
5	7386.00	52.84	PK	74.00	-21.16	1.50	300.00	42.04	11.80	31.20	32.20	10.80
6	7386.00	41.04	AV	54.00	-12.96	1.50	300.00	30.24	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n20_2462MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	64.95	PK	74.00	-9.05	1.80	200.00	63.35	5.30	28.70	32.40	1.60
2	2483.50	51.00	AV	54.00	-3.00	1.80	200.00	49.40	5.30	28.70	32.40	1.60
3	4924.00	51.85	PK	74.00	-22.15	1.70	280.00	46.15	6.70	30.50	31.50	5.70
4	4924.00	40.07	AV	54.00	-13.93	1.70	280.00	34.37	6.70	30.50	31.50	5.70
5	7386.00	52.90	PK	74.00	-21.10	1.70	280.00	42.10	11.80	31.20	32.20	10.80
6	7386.00	41.08	AV	54.00	-12.92	1.70	280.00	30.28	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n40_2422MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	65.36	PK	74.00	-8.64	1.50	290.00	64.06	5.20	28.60	32.50	1.30
2	2390.00	50.86	AV	54.00	-3.14	1.50	290.00	49.56	5.20	28.60	32.50	1.30
3	4844.00	51.95	PK	74.00	-22.05	1.50	290.00	45.55	7.40	30.40	31.40	6.40
4	4844.00	39.81	AV	54.00	-14.19	1.50	290.00	33.41	7.40	30.40	31.40	6.40
5	7266.00	51.77	PK	74.00	-22.23	1.50	290.00	41.27	11.50	31.20	32.20	10.50
6	7266.00	39.23	AV	54.00	-14.77	1.50	290.00	28.73	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n40_2422MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	66.52	PK	74.00	-7.48	1.70	250.00	65.22	5.20	28.60	32.50	1.30
2	2390.00	50.63	AV	54.00	-3.37	1.70	250.00	49.33	5.20	28.60	32.50	1.30
3	4824.00	51.28	PK	74.00	-22.72	1.80	190.00	44.88	7.40	30.40	31.40	6.40
4	4824.00	38.99	AV	54.00	-15.01	1.80	190.00	32.59	7.40	30.40	31.40	6.40
5	7266.00	51.88	PK	74.00	-22.12	1.80	190.00	41.38	11.50	31.20	32.20	10.50
6	7266.00	39.53	AV	54.00	-14.47	1.80	190.00	29.03	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n40_2437MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	53.62	PK	74.00	-20.38	1.50	300.00	47.22	6.70	31.20	31.50	6.40
2	4874.00	41.19	AV	54.00	-12.81	1.50	300.00	34.79	6.70	31.20	31.50	6.40
3	7311.00	51.87	PK	74.00	-22.13	1.50	300.00	41.07	11.80	31.20	32.20	10.80
4	7311.00	40.67	AV	54.00	-13.33	1.50	300.00	29.87	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n40_2437MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	52.87	PK	74.00	-21.13	1.50	160.00	46.47	6.70	31.20	31.50	6.40
2	4874.00	40.64	AV	54.00	-13.36	1.50	160.00	34.24	6.70	31.20	31.50	6.40
3	7311.00	53.33	PK	74.00	-20.67	1.50	160.00	42.53	11.80	31.20	32.20	10.80
4	7311.00	42.25	AV	54.00	-11.75	1.50	160.00	31.45	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11n40_2452MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	65.14	PK	74.00	-8.86	1.80	300.00	63.54	5.30	28.70	32.40	1.60
2	2483.50	50.95	AV	54.00	-3.05	1.80	300.00	49.35	5.30	28.70	32.40	1.60
3	4904.00	52.69	PK	74.00	-21.31	1.50	300.00	46.99	6.70	30.50	31.50	5.70
4	4904.00	40.57	AV	54.00	-13.43	1.50	300.00	34.87	6.70	30.50	31.50	5.70
5	7356.00	53.01	PK	74.00	-20.99	1.50	300.00	42.21	11.80	31.20	32.20	10.80
6	7356.00	41.23	AV	54.00	-12.77	1.50	300.00	30.43	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11n40_2452MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	65.25	PK	74.00	-8.75	1.70	250.00	63.65	5.30	28.70	32.40	1.60
2	2483.50	50.77	AV	54.00	-3.23	1.70	250.00	49.17	5.30	28.70	32.40	1.60
3	4904.00	54.33	PK	74.00	-19.67	1.50	160.00	48.63	6.70	30.50	31.50	5.70
4	4904.00	41.98	AV	54.00	-12.02	1.50	160.00	36.28	6.70	30.50	31.50	5.70
5	7356.00	52.98	PK	74.00	-21.02	1.50	160.00	42.18	11.80	31.20	32.20	10.80
6	7356.00	41.72	AV	54.00	-12.28	1.50	160.00	30.92	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ax20_2412MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	65.21	PK	74.00	-8.79	1.50	300.00	63.91	5.20	28.60	32.50	1.30
2	2390.00	51.17	AV	54.00	-2.83	1.50	300.00	49.87	5.20	28.60	32.50	1.30
3	4824.00	51.22	PK	74.00	-22.78	1.50	300.00	44.82	7.40	30.40	31.40	6.40
4	4824.00	39.10	AV	54.00	-14.90	1.50	300.00	32.70	7.40	30.40	31.40	6.40
5	7236.00	52.06	PK	74.00	-21.94	1.50	300.00	41.56	11.50	31.20	32.20	10.50
6	7236.00	40.69	AV	54.00	-13.31	1.50	300.00	30.19	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ax20_2412MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	64.58	PK	74.00	-9.42	1.80	200.00	63.28	5.20	28.60	32.50	1.30
2	2390.00	50.42	AV	54.00	-3.58	1.80	200.00	49.12	5.20	28.60	32.50	1.30
3	4824.00	50.62	PK	74.00	-23.38	1.80	200.00	44.22	7.40	30.40	31.40	6.40
4	4824.00	39.19	AV	54.00	-14.81	1.80	200.00	32.79	7.40	30.40	31.40	6.40
5	7236.00	53.33	PK	74.00	-20.67	1.80	200.00	42.83	11.50	31.20	32.20	10.50
6	7236.00	42.00	AV	54.00	-12.00	1.80	200.00	31.50	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ax 20_2437MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	51.02	PK	74.00	-22.98	1.50	300.00	45.22	6.70	30.40	31.30	5.80
2	4874.00	39.55	AV	54.00	-14.45	1.50	300.00	33.75	6.70	30.40	31.30	5.80
3	7311.00	52.22	PK	74.00	-21.78	1.50	300.00	41.42	11.80	31.20	32.20	10.80
4	7311.00	40.59	AV	54.00	-13.41	1.50	300.00	29.79	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ax 20_2437MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	51.62	PK	74.00	-22.38	1.80	200.00	45.22	6.70	31.20	31.50	6.40
2	4874.00	39.20	AV	54.00	-14.80	1.80	200.00	32.80	6.70	31.20	31.50	6.40
3	7311.00	52.87	PK	74.00	-21.13	1.80	200.00	42.07	11.80	31.20	32.20	10.80
4	7311.00	41.44	AV	54.00	-12.56	1.80	200.00	30.64	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ax 20_2462MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	64.25	PK	74.00	-9.75	1.50	300.00	62.65	5.30	28.70	32.40	1.60
2	2483.50	50.36	AV	54.00	-3.64	1.50	300.00	48.76	5.30	28.70	32.40	1.60
3	4924.00	52.98	PK	74.00	-21.02	1.50	300.00	47.28	6.70	30.50	31.50	5.70
4	4924.00	40.80	AV	54.00	-13.20	1.50	300.00	35.10	6.70	30.50	31.50	5.70
5	7386.00	52.65	PK	74.00	-21.35	1.50	300.00	41.85	11.80	31.20	32.20	10.80
6	7386.00	40.85	AV	54.00	-13.15	1.50	300.00	30.05	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ax 20_2462MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	65.02	PK	74.00	-8.98	1.80	200.00	63.42	5.30	28.70	32.40	1.60
2	2483.50	50.57	AV	54.00	-3.43	1.80	200.00	48.97	5.30	28.70	32.40	1.60
3	4924.00	52.95	PK	74.00	-21.05	1.80	200.00	47.25	6.70	30.50	31.50	5.70
4	4924.00	41.17	AV	54.00	-12.83	1.80	200.00	35.47	6.70	30.50	31.50	5.70
5	7386.00	53.00	PK	74.00	-21.00	1.80	200.00	42.20	11.80	31.20	32.20	10.80
6	7386.00	41.18	AV	54.00	-12.82	1.80	200.00	30.38	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ax 40_2422MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	58.65	PK	74.00	-15.35	1.50	290.00	57.35	5.20	28.60	32.50	1.30
2	2390.00	43.15	AV	54.00	-10.85	1.50	290.00	41.85	5.20	28.60	32.50	1.30
3	4844.00	52.74	PK	74.00	-21.26	1.50	290.00	46.34	7.40	30.40	31.40	6.40
4	4844.00	40.39	AV	54.00	-13.61	1.50	290.00	33.99	7.40	30.40	31.40	6.40
5	7266.00	53.62	PK	74.00	-20.38	1.50	290.00	43.12	11.50	31.20	32.20	10.50
6	7266.00	40.97	AV	54.00	-13.03	1.50	290.00	30.47	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ax 40_2422MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2390.00	58.98	PK	74.00	-15.02	1.70	250.00	57.68	5.20	28.60	32.50	1.30
2	2390.00	43.66	AV	54.00	-10.34	1.70	250.00	42.36	5.20	28.60	32.50	1.30
3	4824.00	52.64	PK	74.00	-21.36	1.70	250.00	46.24	7.40	30.40	31.40	6.40
4	4824.00	39.66	AV	54.00	-14.34	1.70	250.00	33.26	7.40	30.40	31.40	6.40
5	7266.00	52.77	PK	74.00	-21.23	1.70	250.00	42.27	11.50	31.20	32.20	10.50
6	7266.00	38.52	AV	54.00	-15.48	1.70	250.00	28.02	11.50	31.20	32.20	10.50

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ax 40_2437MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	53.97	PK	74.00	-20.03	1.80	300.00	47.57	6.70	31.20	31.50	6.40
2	4874.00	41.54	AV	54.00	-12.46	1.80	300.00	35.14	6.70	31.20	31.50	6.40
3	7311.00	54.02	PK	74.00	-19.98	1.80	300.00	43.22	11.80	31.20	32.20	10.80
4	7311.00	42.82	AV	54.00	-11.18	1.80	300.00	32.02	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ax 40_2437MHz, MIMO)

No.	Frequency (MHz)	Emssion Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	4874.00	53.20	PK	74.00	-20.80	1.70	250.00	46.80	6.70	31.20	31.50	6.40
2	4874.00	40.23	AV	54.00	-13.77	1.70	250.00	33.83	6.70	31.20	31.50	6.40
3	7311.00	53.87	PK	74.00	-20.13	1.70	250.00	43.07	11.80	31.20	32.20	10.80
4	7311.00	41.45	AV	54.00	-12.55	1.70	250.00	30.65	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M (802.11ax 40_2452MHz, MIMO)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	66.02	PK	74.00	-7.98	1.80	300.00	64.42	5.30	28.70	32.40	1.60
2	2483.50	51.43	AV	54.00	-2.57	1.80	300.00	49.83	5.30	28.70	32.40	1.60
3	4904.00	51.24	PK	74.00	-22.76	1.80	300.00	45.54	6.70	30.50	31.50	5.70
4	4904.00	38.91	AV	54.00	-15.09	1.80	300.00	33.21	6.70	30.50	31.50	5.70
5	7356.00	53.62	PK	74.00	-20.38	1.80	300.00	42.82	11.80	31.20	32.20	10.80
6	7356.00	41.33	AV	54.00	-12.67	1.80	300.00	30.53	11.80	31.20	32.20	10.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M (802.11ax 40_2452MHz, MIMO)

No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV/m)	Cab. Loss (dB)	Ant. Factor (dB)	Pre. Amp. (dB)	Cor. Factor (dB/m)
1	2483.50	65.14	PK	74.00	-8.86	1.70	250.00	63.54	5.30	28.70	32.40	1.60
2	2483.50	50.66	AV	54.00	-3.34	1.70	250.00	49.06	5.30	28.70	32.40	1.60
3	4904.00	53.66	PK	74.00	-20.34	1.70	250.00	47.96	6.70	30.50	31.50	5.70
4	4904.00	40.96	AV	54.00	-13.04	1.70	250.00	35.26	6.70	30.50	31.50	5.70
5	7356.00	52.97	PK	74.00	-21.03	1.70	250.00	42.17	11.80	31.20	32.20	10.80
6	7356.00	41.12	AV	54.00	-12.88	1.70	250.00	30.32	11.80	31.20	32.20	10.80

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)
- Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level - Limit value

2.7. Conducted Emission

2.7.1. Limit of Conducted Emission


For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

2.7.2. Measuring Instruments

The measuring equipment is listed in the section 3 of this test report.

2.7.3. Test Setup




2.7.4. Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 micrometry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


2.7.5. Test Results of Conducted Emission

1. The EUT configuration of the emission tests is WLAN Link + adapter



(Plot A: L Phase)

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB μ V)
0.195000	46.34	26.56	0.1	10.1	17.48	63.8	27.26	53.8
0.208500	40.82	28.39	0.1	10.1	22.44	63.3	24.87	53.3
0.289500	41.48	24.89	0.1	10.1	19.06	60.5	25.65	50.5
0.447000	32.68	26.87	0.1	10.1	24.25	56.9	20.06	46.9
1.203000	26.85	20.92	0.2	10.2	29.15	56.0	25.08	46.0
14.113500	34.09	26.27	0.2	10.2	25.91	60.0	23.73	50.0



(Plot B: N Phase)

Frequency (MHz)	QuasiPeak (dB μ V)	Average (dB μ V)	Cabel Loss (dB)	Corr. (dB)	Margin - QPK	Limit - QPK	Margin - AV	Limit - AV (dB μ V)
0.190500	46.55	26.51	0.1	10.1	17.46	64.0	27.50	54.0
0.217500	39.09	25.51	0.1	10.1	23.82	62.9	27.40	52.9
0.258000	37.24	27.10	0.1	10.1	24.26	61.5	24.40	51.5
0.388500	37.78	27.49	0.1	10.1	20.32	58.1	20.61	48.1
0.429000	34.13	27.73	0.2	10.2	23.14	57.3	19.54	47.3
14.221500	35.12	26.71	0.2	10.2	24.88	60.0	23.29	50.0

Test Result: PASS

Note: Correction factor=Cabel loss+ attenuation factor
attenuation factor=10dB

3. List of measuring equipment

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI TEST RECEIVER	KEYSIGHT	N9038A	A141202036	2020.09.21	2021.09.20
2	Power Meter	R&S	NRP-Z31	102872	2021.04.26	2022.04.25
3	TURNTABLE	ETS	2088	2149	N/A	N/A
4	ANTENNA MAST	ETS	2075	2346	N/A	N/A
5	EMI TEST Software	R&S	ESK1	N/A	N/A	N/A
6	Horn antenna (18GHz~26.5GHz)	AR	AT4003A	325306	2020.09.16	2022.09.15
7	Amplifier 30M~1GHz	MILMEGA	80RF1000-10004	A140101634	2021.01.26	2022.01.25
8	Amplifier 1G~18GHz	MILMEGA	AS0104R-800/40 0	A160302517	2021.01.26	2022.01.25
9	High pass filter	Compliance Direction systems	BSU-6	34202	2020.11.10	2021.11.09
10	Horn Antenna	R&S	HF906	A0304225	2019.04.17	2022.04.16
11	Horn Antenna	R&S	ESIB7	A0501375	2020.06.24	2022.06.22
12	ULTRA-BROADBAND ANTENNA	SCHWARZBECK	VULB9160	A0805560	2019.05.24	2022.05.23
13	Passive Loop Antenna	R&S	HFH2-Z2	100047	2019.04.26	2022.04.25
14	Temperature chamber	TABAI	PS-232	A8708054	2020.10.30	2021.10.29
15	Spectrum Analyzer	KEYSIGHT	N9030A	A160702554	2021.04.26	2022.04.25
16	Power Supply	R&S	ESIB26	A0304218	2021.01.04	2022.01.03
17	LISN	ROHDE&SCHW ARZ	ENV216	A140701847	2020.09.22	2021.09.21
18	Test software	ECIT	Eagle	V2.0	N/A	N/A

Appendix A

RF Output Power

Test Result and Data

802.11b Test mode conducted output power and EIRP

Channel	Frequency (MHz)	Output Power (dBm)		EIRP (dBm)		FCC Limits (dBm)	IC (EIRP) Limit (dBm)	Result
		Ant. 0	Ant. 1	Ant. 0	Ant. 1			
1	2412	18.24	17.66	21.24	20.66	30	36	PASS
6	2437	18.32	17.79	21.32	20.79	30	36	PASS
11	2462	17.72	17.47	20.72	20.47	30	36	PASS

802.11g Test mode conducted output power and EIRP

Channel	Frequency (MHz)	Output Power (dBm)		EIRP (dBm)		FCC Limits (dBm)	IC (EIRP) Limit (dBm)	Result
		Ant. 0	Ant. 1	Ant. 0	Ant. 1			
1	2412	17.34	17.24	20.34	20.24	30	36	PASS
6	2437	17.12	17.08	20.12	20.08	30	36	PASS
11	2462	17.01	16.79	20.01	19.79	30	36	PASS

802.11n-20MHz Test mode conducted output power and EIRP

Channel	Frequency (MHz)	Output Power(dBm)			EIRP (dBm)	FCC Limits (dBm)	IC (EIRP) Limit (dBm)	Result
		Ant. 0	Ant. 1	Ant. 0+1	Ant. 0+1			
1	2412	17.33	17.07	20.21	26.21	30	36	PASS
6	2437	17.18	17.05	20.13	26.13	30	36	PASS
11	2462	16.89	16.74	19.83	25.83	30	36	PASS

802.11n-40MHz Test mode conducted output power and EIRP

Channel	Frequency (MHz)	Output Power(dBm)			EIRP (dBm)	FCC Limits (dBm)	IC (EIRP) Limit (dBm)	Result
		Ant. 0	Ant. 1	Ant. 0+1	Ant. 0+1			
3	2422	17.61	17.72	20.68	26.68	30	36	PASS
6	2437	16.18	17.22	19.74	25.74	30	36	PASS
9	2452	16.05	17.52	19.86	25.86	30	36	PASS

802.11ax-20MHz Test mode conducted output power and EIRP

Channel	Frequency (MHz)	Output Power(dBm)			EIRP (dBm)	FCC Limits (dBm)	IC (EIRP) Limit (dBm)	Result
		Ant. 0	Ant. 1	Ant. 0+1	Ant. 0+1			
1	2412	17.86	17.53	20.71	26.71	30	36	PASS
6	2437	17.63	17.49	20.57	26.57	30	36	PASS
11	2462	17.41	17.24	20.34	26.34	30	36	PASS

802.11ax-40MHz Test mode conducted output power and EIRP

Channel	Frequency (MHz)	Output Power(dBm)			EIRP (dBm)	FCC Limits (dBm)	IC (EIRP) Limit (dBm)	Result
		Ant. 0	Ant. 1	Ant. 0+1	Ant. 0+1			
3	2422	18.16	18.20	21.19	27.19	30	36	PASS
6	2437	16.89	18.19	20.60	26.60	30	36	PASS
9	2452	17.89	17.95	20.93	26.93	30	36	PASS

Note: EIRP= Conducted power+Antenna gain

6dB and 99% Bandwidth Test Result and Data

WLAN Occupied 6dB Bandwidth				
Mode	Test Frequency (MHz)	Ant	Occupied Bandwidth (MHz)	Result
802.11b	2412	Ant0	7.08	Pass
802.11b	2412	Ant1	7.07	Pass
802.11b	2437	Ant0	7.01	Pass
802.11b	2437	Ant1	7.08	Pass
802.11b	2462	Ant0	7.08	Pass
802.11b	2462	Ant1	7.08	Pass
802.11g	2412	Ant0	17.61	Pass
802.11g	2412	Ant1	16.38	Pass
802.11g	2437	Ant0	16.37	Pass
802.11g	2437	Ant1	16.38	Pass
802.11g	2462	Ant0	16.38	Pass
802.11g	2462	Ant1	16.38	Pass
802.11n (HT20)	2412	Ant0	17.62	Pass
802.11n (HT20)	2412	Ant1	17.62	Pass
802.11n (HT20)	2437	Ant0	17.62	Pass
802.11n (HT20)	2437	Ant1	17.62	Pass
802.11n (HT20)	2462	Ant0	17.61	Pass
802.11n (HT20)	2462	Ant1	17.62	Pass
802.11n (HT40)	2422	Ant0	36.36	Pass
802.11n (HT40)	2422	Ant1	36.37	Pass
802.11n (HT40)	2437	Ant0	36.37	Pass
802.11n (HT40)	2437	Ant1	36.37	Pass
802.11n (HT40)	2452	Ant0	36.37	Pass
802.11n (HT40)	2452	Ant1	36.36	Pass
802.11ax (HE20)	2412	Ant0	19.02	Pass
802.11ax (HE20)	2412	Ant1	19.62	Pass
802.11ax (HE20)	2437	Ant0	19.03	Pass
802.11ax (HE20)	2437	Ant1	19.02	Pass
802.11ax (HE20)	2462	Ant0	19.03	Pass
802.11ax (HE20)	2462	Ant1	19.05	Pass
802.11ax (HE40)	2422	Ant0	37.21	Pass




802.11ax (HE40)	2422	Ant1	37.42	Pass
802.11ax (HE40)	2437	Ant0	37.49	Pass
802.11ax (HE40)	2437	Ant1	37.48	Pass
802.11ax (HE40)	2452	Ant0	37.41	Pass
802.11ax (HE40)	2452	Ant1	37.58	Pass

WLAN 99% Occupied Bandwidth				
Mode	Test Frequency (MHz)	Ant	99% Occupied Bandwidth (MHz)	Result
802.11b	2412	Ant0	10.378	Pass
802.11b	2412	Ant1	10.430	Pass
802.11b	2437	Ant0	10.538	Pass
802.11b	2437	Ant1	10.380	Pass
802.11b	2462	Ant0	10.380	Pass
802.11b	2462	Ant1	10.417	Pass
802.11g	2412	Ant0	18.169	Pass
802.11g	2412	Ant1	17.156	Pass
802.11g	2437	Ant0	17.108	Pass
802.11g	2437	Ant1	17.166	Pass
802.11g	2462	Ant0	17.128	Pass
802.11g	2462	Ant1	17.158	Pass
802.11n (HT20)	2412	Ant0	18.184	Pass
802.11n (HT20)	2412	Ant1	18.237	Pass
802.11n (HT20)	2437	Ant0	18.172	Pass
802.11n (HT20)	2437	Ant1	18.194	Pass
802.11n (HT20)	2462	Ant0	18.162	Pass
802.11n (HT20)	2462	Ant1	18.178	Pass
802.11n (HT40)	2422	Ant0	37.019	Pass
802.11n (HT40)	2422	Ant1	37.069	Pass
802.11n (HT40)	2437	Ant0	37.012	Pass
802.11n (HT40)	2437	Ant1	37.108	Pass
802.11n (HT40)	2452	Ant0	36.976	Pass
802.11n (HT40)	2452	Ant1	37.089	Pass
802.11ax (HE20)	2412	Ant0	19.128	Pass
802.11ax (HE20)	2412	Ant1	18.417	Pass
802.11ax (HE20)	2437	Ant0	19.134	Pass
802.11ax (HE20)	2437	Ant1	19.128	Pass
802.11ax (HE20)	2462	Ant0	19.166	Pass
802.11ax (HE20)	2462	Ant1	19.113	Pass
802.11ax (HE40)	2422	Ant0	37.822	Pass


802.11ax (HE40)	2422	Ant1	37.843	Pass
802.11ax (HE40)	2437	Ant0	37.823	Pass
802.11ax (HE40)	2437	Ant1	37.825	Pass
802.11ax (HE40)	2452	Ant0	37.806	Pass
802.11ax (HE40)	2452	Ant1	37.846	Pass

To simplify the report, only the maximum bandwidth test plot is provided:

6dB Bandwidth-802.11ax(HE40),2452MHz
,Ant1



99% Bandwidth-802.11ax(HE40),2452MHz
,Ant1



Power Spectral Density

Test Result and Data

802.11b Test mode conducted output power

Channel	Frequency (MHz)	PSD/3kHz (dBm)		Limits (dBm/3K)	Result
		Ant. 0	Ant. 1		
1	2412	-13.300	-13.706	8	PASS
6	2437	-13.406	-13.569	8	PASS
11	2462	-13.623	-13.841	8	PASS

802.11g Test mode conducted output power

Channel	Frequency (MHz)	PSD/3kHz (dBm)		Limits (dBm/3K)	Result
		Ant. 0	Ant. 1		
1	2412	-17.458	-17.717	8	PASS
6	2437	-17.725	-17.697	8	PASS
11	2462	-17.478	-17.801	8	PASS

802.11n-20MHz Test mode conducted output power

Channel	Frequency (MHz)	PSD/3kHz (dBm)			Limits (dBm/3K)	Result
		Ant. 0	Ant. 1	Ant. 0+1		
1	2412	-17.221	-17.525	-14.36	8	PASS
6	2437	-17.500	-17.433	-14.46	8	PASS
11	2462	-17.863	-18.166	-15.00	8	PASS

802.11n-40MHz Test mode conducted output power

Channel	Frequency (MHz)	PSD/3kHz (dBm)			Limits (dBm/3K)	Result
		Ant. 0	Ant. 1	Ant. 0+1		
3	2422	-20.459	-20.355	-17.40	8	PASS
6	2437	-20.564	-20.735	-17.64	8	PASS
9	2452	-20.547	-20.612	-17.57	8	PASS

802.11ax-20MHz Test mode conducted output power

Channel	Frequency (MHz)	PSD/3kHz (dBm)			Limits (dBm/3K)	Result
		Ant. 0	Ant. 1	Ant. 0+1		
1	2412	-18.558	-17.617	-15.05	8	PASS
6	2437	-18.687	-18.843	-15.75	8	PASS
11	2462	-18.919	-18.837	-15.87	8	PASS

802.11ax-40MHz Test mode conducted output power

Channel	Frequency (MHz)	PSD/3kHz (dBm)			Limits (dBm/3K)	Result
		Ant. 0	Ant. 1	Ant. 0+1		
3	2422	-21.143	-21.180	-18.15	8	PASS
6	2437	-21.261	-21.211	-18.23	8	PASS
9	2452	-21.365	-21.392	-18.37	8	PASS

To simplify the report, only the maximum Power spectral density test plot is provided:

Power spectral density-802.11b
,2412MHz,Ant0




Conducted Band Edges and Spurious Emissions

Test Result and Data

,Plot 1,Reference Level-802.11b
,2412MHz,Ant0



,Plot 1,Reference Level-802.11b
,2412MHz,Ant1



,Plot 1,Reference Level-802.11b
,2437MHz,Ant0



,Plot 1,Reference Level-802.11b
,2437MHz,Ant1




,Plot 1,Reference Level-802.11b
,2462MHz,Ant0




,Plot 1,Reference Level-802.11b
,2462MHz,Ant1




,Plot 2,Band Edge-802.11b,2412MHz
,Ant0




,Plot 2,Band Edge-802.11b,2412MHz
,Ant1




,Plot 2,Band Edge-802.11b,2437MHz
,Ant0




,Plot 2,Band Edge-802.11b,2437MHz
,Ant1




,Plot 2,Band Edge-802.11b,2462MHz
,Ant0




,Plot 2,Band Edge-802.11b,2462MHz
,Ant1




,Plot 3,30MHz~2310MHz-802.11b,2412MHz
,Ant0




,Plot 3,30MHz~2310MHz-802.11b,2412MHz
,Ant1




,Plot 3,30MHz~2310MHz-802.11b,2437MHz
,Ant0




,Plot 3,30MHz~2310MHz-802.11b,2437MHz
,Ant1




,Plot 3,30MHz~2310MHz-802.11b,2462MHz
,Ant0




,Plot 3,30MHz~2310MHz-802.11b,2462MHz
,Ant1




,Plot 4,2500MHz~10000MHz-802.11b
,2412MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11b
,2412MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11b
,2437MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11b
,2437MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11b
,2462MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11b
,2462MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11b
,2412MHz,Ant0




,Plot 5,10000MHz~25000MHz-802.11b
,2412MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11b
,2437MHz,Ant0




,Plot 5,10000MHz~25000MHz-802.11b
,2437MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11b
,2462MHz,Ant0




,Plot 5,10000MHz~25000MHz-802.11b
,2462MHz,Ant1




,Plot 1,Reference Level-802.11g
,2412MHz,Ant0




,Plot 1,Reference Level-802.11g
,2412MHz,Ant1




,Plot 1,Reference Level-802.11g
,2437MHz,Ant0




,Plot 1,Reference Level-802.11g
,2437MHz,Ant1



,Plot 1,Reference Level-802.11g
,2462MHz,Ant0




,Plot 1,Reference Level-802.11g
,2462MHz,Ant1




,Plot 2,Band Edge-802.11g,2412MHz
,Ant0




,Plot 2,Band Edge-802.11g,2412MHz
,Ant1



,Plot 2,Band Edge-802.11g,2437MHz
,Ant0



,Plot 2,Band Edge-802.11g,2437MHz
,Ant1



,Plot 2,Band Edge-802.11g,2462MHz
,Ant0




,Plot 2,Band Edge-802.11g,2462MHz
,Ant1




,Plot 3,30MHz~2310MHz-802.11g,2412MHz

,Ant0




,Plot 3,30MHz~2310MHz-802.11g,2412MHz

,Ant1




,Plot 3,30MHz~2310MHz-802.11g,2437MHz

,Ant0




,Plot 3,30MHz~2310MHz-802.11g,2437MHz

,Ant1




,Plot 3,30MHz~2310MHz-802.11g,2462MHz

,Ant0




,Plot 3,30MHz~2310MHz-802.11g,2462MHz

,Ant1




,Plot 4,2500MHz~10000MHz-802.11g
,2412MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11g
,2412MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11g
,2437MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11g
,2437MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11g
,2462MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11g
,2462MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11g
,2412MHz,Ant0




,Plot 5,10000MHz~25000MHz-802.11g
,2412MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11g
,2437MHz,Ant0




,Plot 5,10000MHz~25000MHz-802.11g
,2437MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11g
,2462MHz,Ant0




,Plot 5,10000MHz~25000MHz-802.11g
,2462MHz,Ant1




,Plot 1,Reference Level-802.11n(HT20)
,2412MHz,Ant0




,Plot 1,Reference Level-802.11n(HT20)
,2412MHz,Ant1



,Plot 1,Reference Level-802.11n(HT20)
,2437MHz,Ant0



,Plot 1,Reference Level-802.11n(HT20)
,2437MHz,Ant1



,Plot 1,Reference Level-802.11n(HT20)
,2462MHz,Ant0



,Plot 1,Reference Level-802.11n(HT20)
,2462MHz,Ant1




,Plot 2,Band Edge-802.11n(HT20)
,2412MHz,Ant0




,Plot 2,Band Edge-802.11n(HT20)
,2412MHz,Ant1



,Plot 2,Band Edge-802.11n(HT20)
,2437MHz,Ant0



,Plot 2,Band Edge-802.11n(HT20)
,2437MHz,Ant1




,Plot 2,Band Edge-802.11n(HT20)
,2462MHz,Ant0




,Plot 2,Band Edge-802.11n(HT20)
,2462MHz,Ant1




,Plot 3,30MHz~2310MHz-802.11n(HT20)
,2412MHz,Ant0




,Plot 3,30MHz~2310MHz-802.11n(HT20)
,2412MHz,Ant1




,Plot 3,30MHz~2310MHz-802.11n(HT20)
,2437MHz,Ant0




,Plot 3,30MHz~2310MHz-802.11n(HT20)
,2437MHz,Ant1




,Plot 3,30MHz~2310MHz-802.11n(HT20)
,2462MHz,Ant0




,Plot 3,30MHz~2310MHz-802.11n(HT20)
,2462MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11n(HT20
) ,2412MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11n(HT20
) ,2412MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11n(HT20
) ,2437MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11n(HT20
) ,2437MHz,Ant1









,Plot 4,2500MHz~10000MHz-802.11n(HT20
) ,2462MHz,Ant0



,Plot 4,2500MHz~10000MHz-802.11n(HT20
) ,2462MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11n(HT2
0),2412MHz,Ant0

,Plot 5,10000MHz~25000MHz-802.11n(HT2
0),2412MHz,Ant1

,Plot 5,10000MHz~25000MHz-802.11n(HT2
0),2437MHz,Ant0

,Plot 5,10000MHz~25000MHz-802.11n(HT2
0),2437MHz,Ant1

,Plot 5,10000MHz~25000MHz-802.11n(HT2
0),2462MHz,Ant0

,Plot 5,10000MHz~25000MHz-802.11n(HT2
0),2462MHz,Ant1



,Plot 1,Reference Level-802.11n(HT40)
,2422MHz,Ant0




,Plot 1,Reference Level-802.11n(HT40)
,2422MHz,Ant1




,Plot 1,Reference Level-802.11n(HT40)
,2437MHz,Ant0



,Plot 1,Reference Level-802.11n(HT40)
,2437MHz,Ant1



,Plot 1,Reference Level-802.11n(HT40)
,2452MHz,Ant0



,Plot 1,Reference Level-802.11n(HT40)
,2452MHz,Ant1



,Plot 2,Band Edge-802.11n(HT40)
,2422MHz,Ant0




,Plot 2,Band Edge-802.11n(HT40)
,2422MHz,Ant1



,Plot 2,Band Edge-802.11n(HT40)
,2437MHz,Ant0



,Plot 2,Band Edge-802.11n(HT40)
,2437MHz,Ant1




,Plot 2,Band Edge-802.11n(HT40)
,2452MHz,Ant0




,Plot 2,Band Edge-802.11n(HT40)
,2452MHz,Ant1




,Plot 3,30MHz~2310MHz-802.11n(HT40)
,2422MHz,Ant0




,Plot 3,30MHz~2310MHz-802.11n(HT40)
,2422MHz,Ant1




,Plot 3,30MHz~2310MHz-802.11n(HT40)
,2437MHz,Ant0




,Plot 3,30MHz~2310MHz-802.11n(HT40)
,2437MHz,Ant1




,Plot 3,30MHz~2310MHz-802.11n(HT40)
,2452MHz,Ant0




,Plot 3,30MHz~2310MHz-802.11n(HT40)
,2452MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11n(HT40
) ,2422MHz,Ant0



,Plot 4,2500MHz~10000MHz-802.11n(HT40
) ,2422MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11n(HT40
) ,2437MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11n(HT40
) ,2437MHz,Ant1




,Plot 4,2500MHz~10000MHz-802.11n(HT40
) ,2452MHz,Ant0




,Plot 4,2500MHz~10000MHz-802.11n(HT40
) ,2452MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11n(HT4
0),2422MHz,Ant0




,Plot 5,10000MHz~25000MHz-802.11n(HT4
0),2422MHz,Ant1




,Plot 5,10000MHz~25000MHz-802.11n(HT4
0),2437MHz,Ant0




,Plot 5,10000MHz~25000MHz-802.11n(HT4
0),2437MHz,Ant1



,Plot 5,10000MHz~25000MHz-802.11n(HT4
0),2452MHz,Ant0



,Plot 5,10000MHz~25000MHz-802.11n(HT4
0),2452MHz,Ant1



****END OF REPORT****