

RF exposure evaluation

The RF exposure evaluation was calculated as below:

- 1) The maximum conducted output power is -3.12dBm (0.49mW) at 2402MHz of GFSK mode. (0dBi antenna gain, with 1 numeric antenna gain.)
- 2) For Bluetooth device or fixed location transmitters, no SAR consideration applied.
- 3) Per KDB 447498 D01v05r02, the 1-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR, where

- ž f(GHz) is the RF channel transmit frequency in GHz
- ž Power and distance are rounded to the nearest mW and mm before calculation
- ž When the minimum test separation distance is < 5 mm, a distance of 5 mm according is applied to determine SAR test exclusion.
- ž
- ž The result is rounded to one decimal place for comparison

Channel	Frequency (GHz)	Power (dBm)	Max. Power (mW)	Test distance (mm)	Result	exclusion thresholds for 1-g SAR
CH 00	2.402	-3.12	0.49	5	0.15	3.0

- ž Base on the calculation value, the RF exposure evaluation is not required.
- ž The public is not exposed to radio frequency energy level in excess of the Commission's guideline.