FCC RADIO TEST REPORT
FCC ID: 2AG4D76124H01F4

Product： Navigation System

Trade Name： Aumet

Model Name： 76124H01F4

Serial Model： 76124H02C8,76124H01B9,76124H02B9, 76124H02F4,76228H01B9

Report No.： POCE-2017062718F

Prepared for

FlyAudio Corporation China

Building 2 & 3, No. 11, Nanxiang 3rd Road, High-Tech Industrial Development Zone, Guangzhou,China

Prepared by

Shenzhen POCE Technology Co.,Ltd.

Room 502, Bldg. 1, Xinghua Garden, Baoan Road Xixiang, Baoan District,Shenzhen, China

TEST RESULT CERTIFICATION

Applicant's name ..... : FlyAudio Corporation China

Address ..... : Building 2 & 3, No. 11, Nanxiang 3rd Road, High-Tech Industrial Development Zone, Guangzhou,China

Manufacture's Name..... : FlyAudio Corporation China

Address ..... : Building 2 & 3, No. 11, Nanxiang 3rd Road, High-Tech Industrial Development Zone, Guangzhou,China

Product description

Product name ..... : Navigation System

Model and/or type reference : 76124H01F4, 76124H02C8,76124H01B9,76124H02B9, 76124H02F4,76228H01B9

Standards ..... : FCC 15.247

Test procedure ..... ANSI C63.10-2013

This device described above has been tested by POCE, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of POCE, this document may be altered or revised by POCE, personal only, and shall be noted in the revision of the document.

Date of Test .....:

Date (s) of performance of tests .....: 17 Jun. 2017 ~10 Jul. 2017

Date of Issue.....: 10 Jul. 2017

Test Result.....: **Pass**

Testing Engineer : Jerry Lin

(Jerry Lin)

Technical Manager : Jimmy Yao

(Jimmy Yao)

Authorized Signatory : Terry Yang

(Terry Yang)

Table of Contents

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 DESCRIPTION OF TEST MODES	9
2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	9
2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	10
2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	11
2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS	12
3 . EMC EMISSION TEST	13
3.1 CONDUCTED EMISSION MEASUREMENT	13
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	13
3.1.2 TEST PROCEDURE	14
3.1.3 DEVIATION FROM TEST STANDARD	14
3.1.4 TEST SETUP	14
3.1.5 EUT OPERATING CONDITIONS	14
3.1.6 TEST RESULTS	15
3.2 RADIATED EMISSION MEASUREMENT	16
3.2.1 RADIATED EMISSION LIMITS	16
3.2.2 TEST PROCEDURE	17
3.2.3 DEVIATION FROM TEST STANDARD	17
3.2.4 TEST SETUP	18
3.2.5 EUT OPERATING CONDITIONS	19
3.2.6 TEST RESULTS	20
4 . NUMBER OF HOPPING CHANNEL	25
4.1 APPLIED PROCEDURES / LIMIT	25
4.1.1 TEST PROCEDURE	25
4.1.2 DEVIATION FROM STANDARD	25
4.1.3 TEST SETUP	25
4.1.4 EUT OPERATION CONDITIONS	25
4.1.5 TEST RESULTS	26
5 . AVERAGE TIME OF OCCUPANCY	27
5.1 APPLIED PROCEDURES / LIMIT	27
5.1.1 TEST PROCEDURE	27
5.1.2 DEVIATION FROM STANDARD	27

Table of Contents

Page

5.1.3 TEST SETUP 28
5.1.4 EUT OPERATION CONDITIONS 28
5.1.5 TEST RESULTS 29

6 . HOPPING CHANNEL SEPARATION MEASUREMENT 35

6.1 APPLIED PROCEDURES / LIMIT 35
6.1.1 TEST PROCEDURE 35
6.1.2 DEVIATION FROM STANDARD 35
6.1.3 TEST SETUP 35
6.1.4 EUT OPERATION CONDITIONS 35
6.1.5 TEST RESULTS 36

7 . BANDWIDTH TEST 42

7.1 APPLIED PROCEDURES / LIMIT 42
7.1.1 TEST PROCEDURE 42
7.1.2 DEVIATION FROM STANDARD 42
7.1.3 TEST SETUP 42
7.1.4 EUT OPERATION CONDITIONS 42
7.1.5 TEST RESULTS 43

8 . PEAK OUTPUT POWER TEST 49

8.1 APPLIED PROCEDURES / LIMIT 49
8.1.1 TEST PROCEDURE 49
8.1.2 DEVIATION FROM STANDARD 49
8.1.3 TEST SETUP 49
8.1.4 EUT OPERATION CONDITIONS 49
8.1.5 TEST RESULTS 50

9 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 57
9.1 DEVIATION FROM STANDARD 57
9.2 TEST SETUP 57
9.3 EUT OPERATION CONDITIONS 57
9.4 TEST RESULTS 58

10 . ANTENNA REQUIREMENT 66

10.1 STANDARD REQUIREMENT 66

10.2 EUT ANTENNA 66

11 . EUT TEST PHOTO 67
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	N/A	
15.247(a)(1)	Hopping Channel Separation	PASS	
15.247(b)(1)	Peak Output Power	PASS	
15.247(c)	Radiated Spurious Emission	PASS	
15.247(a)(iii)	Number of Hopping Frequency	PASS	
15.247(a)(iii)	Dwell Time	PASS	
15.247(a)(1)	Bandwidth	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)” N/A” denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen POCE Technology Co.,Ltd.

Add.: Room 502, Bldg. 1, Xinghua Garden, Baoan Road Xixiang, Baoan District, Shenzhen, China

FCC-Registration No.: 222278

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y ± U**，where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

<table>
<tr><td>Equipment</td><td>Navigation System</td></tr>
<tr><td>Trade Name</td><td>N/A</td></tr>
<tr><td>Model Name</td><td>76124H01F4</td></tr>
<tr><td>Serial Model</td><td>76124H02C8,76124H01B9,76124H02B9,
76124H02F4,76228H01B9</td></tr>
<tr><td>Model Difference</td><td>All the model are the same circuit and RF module, except model names.</td></tr>
<tr><td>Product Description</td><td>The EUT is a Navigation System
<table>
<tr><td>Operation Frequency:</td><td>2402~2480 MHz</td></tr>
<tr><td>Modulation Type:</td><td>BT(1Mbps): GFSK
BT EDR(2Mbps): π/4-DQPSK
BT EDR(3Mbps): 8-DPSK</td></tr>
<tr><td>Bit Rate of Transmitter</td><td>1Mbps/2Mbps/3Mbps</td></tr>
<tr><td>Number Of Channel</td><td>79 CH</td></tr>
<tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr>
<tr><td>Output Power(Conducted):</td><td>BT(1Mbps): 1.745dBm
BT EDR(2Mbps): -1.118dBm
BT EDR(3Mbps): -1.152dBm</td></tr>
</table>
Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Adapter</td><td>N/A</td></tr>
<tr><td>Battery</td><td>N/A</td></tr>
<tr><td>Connecting I/O Port(s)</td><td>Please refer to the User's Manual</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
2.

Channel List					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
1	N/A	N/A	PCB ANT	N/A	0.9	BT Antenna

2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78
Mode 4	Normal Link

For Conducted Emission	
Final Test Mode	Description
Mode 4	Normal Link

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH00
Mode 2	CH39
Mode 3	CH78

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) Fully-charged battery is used during the test

(3)The data rate was set in 1Mbps for radiated emission due to the highest RF output power.

2.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS

Test software Version	Test program: BC8615		
Frequency	2402 MHz	2441 MHz	2480 MHz
Parameters(1/2/3Mbps)	DEF	DEF	DEF

2.4 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED



2.5 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Navigation System	N/A	76124H01F4	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.
(3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.

2.6 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2017.07.06	2018.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2017.06.07	2018.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2017.07.06	2018.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2017.06.07	2018.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2017.06.07	2018.06.06	1 year
6	Horn Antenna	EM	EM-AH-10180	2011071402	2017.07.06	2018.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2017.07.06	2018.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2016.12.22	2017.12.21	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2017.06.08	2018.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2017.07.06	2018.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.05	2017.07.06	2018.07.05	1 year

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	101160	2017.06.06	2018.06.05	1 year
2	LISN	R&S	ENV216	101313	2016.08.24	2017.08.23	1 year
3	LISN	EMCO	3816/2	00042990	2016.08.24	2017.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2017.06.07	2018.06.06	1 year
5	Passive Voltage Probe	R&S	ESH2-Z3	100196	2017.06.07	2018.06.06	1 year
6	Absorbing clamp	R&S	MOS-21	100423	2017.06.08	2018.06.07	1 year

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class B (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	56.00	46.00	CISPR
5.0 -30.0	60.00	50.00	CISPR

0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

3.1.6 TEST RESULTS

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase :	L
Test Voltage ：	--	Test Mode：	--

This device was powered by DC 12V, No test need for AC conducted emission.

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or Upper frequency of measurement used in the device or on which the device operates or tunes (MHz)	Range (MHz)
Below 1.705	30
1.705 – 108	1000
108 – 500	2000
500 – 1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter 966 test site. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD

No deviation

3.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS

Radiated Spurious Emission (Below 30MHz)

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	20 ℃	Relative Humidity：	48%
Pressure：	1010 hPa	Polarization :	---
Test Voltage ：	DC 12V		
Test Mode ：	TX		

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:
The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

Radiated Spurious Emission (Between 30MHz – 1GHz)

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010 hPa	Polarization :	Horizontal
Test Voltage ：	AC 120V/60Hz		
Test Mode ：	TX		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
53.8818	32.03	-10.93	21.10	40.00	-18.90	QP
90.8554	37.23	-17.41	19.82	43.50	-23.68	QP
126.7723	43.90	-14.31	29.59	43.50	-13.91	QP
138.8735	39.16	-13.46	25.70	43.50	-17.80	QP
167.8243	40.57	-13.32	27.25	43.50	-16.25	QP
181.2834	34.80	-14.50	20.30	43.50	-23.20	QP

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.



EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	26 ℃	Relative Humidity：	54%
Pressure：	1010 hPa	Polarization :	Vertical
Test Voltage ：	AC 120V/60Hz		
Test Mode ：	TX		

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
30.2111	26.44	-8.05	18.39	40.00	-21.61	QP
51.3005	31.34	-10.50	20.84	40.00	-19.16	QP
126.3286	34.80	-14.33	20.47	43.50	-23.03	QP
162.6106	32.02	-13.02	19.00	43.50	-24.50	QP
945.4399	26.60	-0.56	26.04	46.00	-19.96	QP
989.5355	26.16	-0.32	25.84	54.00	-28.16	QP

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.



Radiated Spurious Emission (1GHz to 10th harmonics)
(Scan with GFSK, π/4-DQPSK,8DPSK,the worst casw is BDR Mode (GFSK)

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
Low Channel (2402 MHz)							
1127.8	68.48	-19.14	49.34	74	-24.66	peak	Vertical
1595.2	61.19	-16.43	44.76	74	-29.24	peak	Vertical
3040.6	60.23	-11.63	48.6	74	-25.4	peak	Vertical
4804.4	54.64	-3.64	51	74	-23	peak	Vertical
1127.5	70.12	-19.14	50.98	74	-23.02	peak	Horizontal
1595.5	67.06	-16.43	50.63	74	-23.37	peak	Horizontal
3040.7	58.73	-11.63	47.1	74	-26.9	peak	Horizontal
4804.6	50.54	-3.64	46.9	74	-27.1	peak	Horizontal
Mid Channel (2441 MHz)							
1340.2	65.21	-17.48	47.73	74	-26.27	peak	Vertical
2020.3	59.06	-12.92	46.14	74	-27.86	peak	Vertical
2827.8	57.13	-11.73	45.4	74	-28.6	peak	Vertical
4882.5	53.88	-3.68	50.2	74	-23.8	peak	Vertical
1127	66.52	-19.14	47.38	74	-26.62	peak	Horizontal
1636.5	61.08	-16.06	45.02	74	-28.98	peak	Horizontal
2488.5	56.29	-12.77	43.52	74	-30.48	peak	Horizontal
4882.8	51.78	-3.68	48.1	74	-25.9	peak	Horizontal
High Channel (2480 MHz)							
1171	62.74	-18.54	44.2	74	-29.80	peak	Vertical
2274	63.07	-12.87	50.2	74	-23.80	peak	Vertical
3126	54.69	-11.43	43.26	74	-30.74	peak	Vertical
4961	50.99	-3.59	47.4	74	-26.60	peak	Vertical
1127	69.24	-19.14	50.1	74	-23.90	peak	Horizontal
1339	66.43	-17.48	48.95	74	-25.05	peak	Horizontal
1851	64.37	-14.64	49.73	74	-24.27	peak	Horizontal
4958	52.62	-3.59	49.03	74	-24.97	peak	Horizontal

Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Emission Level = Meter Reading + Factor
Margin = Emission Level - Limit

Radiated band edge:

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type	Comment
GFSK							
2400	47.68	-13.06	34.62	74	-39.38	peak	Vertical
2400	49.84	-13.06	36.78	74	-37.22	peak	Horizontal
2483.5	47.92	-12.78	35.14	74	-38.86	peak	Vertical
2483.5	49.33	-12.78	36.55	74	-37.45	peak	Horizontal
π/4-DQPSK							
2400	48.25	-13.06	35.19	74	-38.81	peak	Vertical
2400	50.31	-13.06	37.25	74	-36.75	peak	Horizontal
2483.5	47.24	-12.78	34.46	74	-39.54	peak	Vertical
2483.5	49.39	-12.78	36.61	74	-37.39	peak	Horizontal
8DPSK							
2400	48.47	-13.06	34.87	74	-39.13	peak	Vertical
2400	49.84	-13.06	36.78	74	-37.22	peak	Horizontal
2483.5	47.69	-12.78	34.91	74	-39.09	peak	Vertical
2483.5	49.32	-12.78	36.54	74	-37.46	peak	Horizontal

NOTE: 1.The result(PK) less than AV limite,No need shown AV result.
2.Hopping enabled and disabled have evaluated,and the worest data was reported

4. NUMBER OF HOPPING CHANNEL

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Number of Hopping Channel	≥15	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	= the frequency band of operation
RB	RBW ≥ 1% of the span
VB	VBW ≥ RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting : RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.1.5 TEST RESULTS

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	DC 12V
Test Mode ：	Hopping Mode		

Number of Hopping Channel	79



5. AVERAGE TIME OF OCCUPANCY

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)(iii)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

a. The transmitter output (antenna port) was connected to the spectrum analyzer
b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
d. Sweep Time is more than once pulse time.
e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
f. Measure the maximum time duration of one single pulse.
g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
h. Measure the maximum time duration of one single pulse.
i. A Period Time = (channel number)*0.4
DH1 Time Slot: Reading * (1600/2)*31.6/(channel number)
DH3 Time Slot: Reading * (1600/4)*31.6/(channel number)
DH5 Time Slot: Reading * (1600/6)*31.6/(channel number)

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP

5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH39-DH5, 2DH5, 3DH5		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH5	2441 MHz	2.91	0.31	0.4
2DH5	2441 MHz	2.91	0.31	0.4
3DH5	2441 MHz	2.76	0.29	0.4

CH39-DH5



CH39-2DH5



CH39-3DH5



EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH39-DH3, 2DH3, 3DH3		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH3	2441 MHz	1.61	0.26	0.4
2DH3	2441 MHz	1.63	0.26	0.4
3DH3	2441 MHz	1.61	0.26	0.4

CH39-DH3



CH39-2DH3



CH39-3DH3



EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH39-DH1, 2DH1, 3DH1		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (s)	Limits (s)
DH1	2441 MHz	0.43	0.14	0.4
2DH1	2441 MHz	0.44	0.14	0.4
3DH1	2441 MHz	0.43	0.14	0.4

CH39-DH1



CH39-2DH1



CH39-3DH1



6. HOPPING CHANNEL SEPARATION MEASUREMENT

6.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	100 kHz (Channel Separation)
VB	300 kHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

6.1.1 TEST PROCEDURE

a. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

b. The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised for channel separation measurement.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

6.1.5 TEST RESULTS

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH00 / CH39 /CH78 (1Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.002	**Complies**
2441 MHz	1.002	**Complies**
2480 MHz	1.002	**Complies**

Ch. Separation Limits: > 20dB bandwidth

CH00 -1Mbps

CH39 -1Mbps

CH78 -1Mbps

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH00 / CH39 /CH78 (2Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.002	**Complies**
2441 MHz	1.002	**Complies**
2480 MHz	1.002	**Complies**

Ch. Separation Limits: >2/3 of 20dB bandwidth

CH00 -2Mbps

CH39 -2Mbps



CH78 -2Mbps

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH00 / CH39 /CH78 (3Mbps Mode)		

Frequency	Ch. Separation (MHz)	Result
2402 MHz	1.002	**Complies**
2441 MHz	1.002	**Complies**
2480 MHz	1.002	**Complies**

Ch. Separation Limits: >2/3 of 20dB bandwidth

CH00 -3Mbps

CH39 -3Mbps

CH78 -3Mbps

7. BANDWIDTH TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (a)(1)	Bandwidth	(20dB bandwidth)	2400-2483.5	PASS

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RB	1% of the 20 dB bandwidth
VB	≥RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

7.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
b. Spectrum Setting : RBW= 1% of the 20 dB bandwidth, VBW≥ RBW, Sweep time = Auto.

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 TEST RESULTS

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH00 / CH39 /C78**(1Mbps)**		

Frequency	20dB Bandwidth (kHz)	Result
2402 MHz	950.993	**PASS**
2441 MHz	996.062	**PASS**
2480 MHz	997.512	**PASS**

CH00 -1Mbps



CH39 -1Mbps



CH78 -1Mbps



EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH00 / CH39 /C78**(2Mbps)**		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.322	**PASS**
2441 MHz	1.326	**PASS**
2480 MHz	1.269	**PASS**

CH00 -2Mbps



CH39 -2Mbps



CH78 -2Mbps



EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH00 / CH39 /C78**(3Mbps)**		

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.348	**PASS**
2441 MHz	1.318	**PASS**
2480 MHz	1.328	**PASS**

CH00 -3Mbps



CH39 -3Mbps



CH78 -3Mbps



8. PEAK OUTPUT POWER TEST

8.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247 (b)(i)	Peak Output Power	30Bm or 20.96dBm	2400-2483.5	PASS

8.1.1 TEST PROCEDURE

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,

b. Spectrum Setting : RBW > the 20 dB bandwidth of the emission being measured

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

8.1.2 DEVIATION FROM STANDARD

No deviation.

8.1.3 TEST SETUP

8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.1.5 TEST RESULTS

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH00/ CH39 /CH78 (1M/2M/3Mbps Mode)		

1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	LIMIT (dBm)
CH00	2402	1.745	20.96
CH39	2441	0.869	20.96
CH78	2480	0.605	20.96
2Mbps			
CH00	2402	-1.118	20.96
CH39	2441	-2.085	20.96
CH78	2480	-2.049	20.96
3Mbps			
CH00	2402	-1.152	20.96
CH39	2441	-2.085	20.96
CH78	2480	-2.040	20.96

CH00 -1Mbps


Agilent
R T
Mkr1 2.4020000 GHz
Ref 10 dBm #Atten 20 dB Ext PG -20 dB 1.745 dBm
Peak
Log
10
dB/
M1 S2
S3 FC
AA
Center 2.402 GHz
Span 5 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 5 ms (401 pts)
Trace/View
Trace
1 2 3
Clear Write
Max Hold
Min Hold
View
Blank
More
1 of 2
C:PICTURE.GIF file saved

CH39 -1Mbps



CH78 -1Mbps



CH00 -2Mbps


Agilent
R T
Trace/View
Mkr1 2.4020000 GHz
Ref 10 dBm #Atten 20 dB Ext PG -20 dB -1.118 dBm
Peak
Log
10
dB/
1
Trace
1 2 3
Clear Write
Max Hold
Min Hold
View
Blank
More
1 of 2
M1 S2
S3 FC
AA
Center 2.402 GHz
Span 5 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 5 ms (401 pts)
C:PICTURE.GIF file saved

CH39 -2Mbps



CH78 -2Mbps



CH00 -3Mbps


Agilent
R T
Trace/View
Mkr1 2.4020000 GHz
Ref 10 dBm #Atten 20 dB Ext PG -20 dB -1.152 dBm
Peak
Log
10
dB/
1
Trace
1 2 3
Clear Write
Max Hold
Min Hold
View
Blank
More
1 of 2
M1 S2
S3 FC
AA
Center 2.402 GHz
Span 5 MHz
#Res BW 3 MHz
VBW 3 MHz
Sweep 5 ms (401 pts)
C:PICTURE.GIF file saved

CH39 -3Mbps



CH78 -3Mbps



9. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

TEST PROCEDURE

a) Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
b) Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
c) Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
d) Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
e) Repeat above procedures until all measured frequencies were complete.

9.1 DEVIATION FROM STANDARD

No deviation.

9.2 TEST SETUP



9.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.4 TEST RESULTS

EUT：	Navigation System	Model Name ：	76124H01F4
Temperature：	25 ℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	DC 12V
Test Mode ：	CH00/ CH78 (1M/2M/3Mbps Mode)		

hopping mode:

Frequency Band	Delta Peak to band emission (dBc)	＞Limit (dBc)	Result
BDR mode (GFSK)			
Left-band	49.89	20	Pass
Right-band	50.74	20	Pass
EDR mode (π/4-DQPSK)			
Left-band	25.41	20	Pass
Right-band	40.25	20	Pass
EDR mode(8DPSK)			
Left-band	24.70	20	Pass
Right-band	41.07	20	Pass

BDR mode (GFSK): Band Edge-Left Side



BDR mode (GFSK): Band Edge-Right Side



EDR mode (π /4-DQPSK): Band Edge-Left Side



EDR mode (π /4-DQPSK): Band Edge-Right Side



EDR mode(8DPSK): Band Edge-Left Side



EDR mode(8DPSK): Band Edge-Right Side



Non-hopping mode::

Frequency Band	Delta Peak to band emission (dBc)	＞Limit (dBc)	Result
BDR mode (GFSK)			
Left-band	55.89	20	Pass
Right-band	53.19	20	Pass
EDR mode (π /4-DQPSK)			
Left-band	53.50	20	Pass
Right-band	53.99	20	Pass
EDR mode(8DPSK)			
Left-band	55.43	20	Pass
Right-band	55.93	20	Pass

BDR mode (GFSK): Band Edge-Left Side



BDR mode (GFSK): Band Edge-Right Side



EDR mode (π /4-DQPSK): Band Edge-Left Side



EDR mode (π /4-DQPSK): Band Edge-Right Side



EDR mode(8DPSK): Band Edge-Left Side



EDR mode(8DPSK): Band Edge-Right Side



10. ANTENNA REQUIREMENT

10.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

10.2 EUT ANTENNA

The EUT antenna is PCB ANT,It's permanent attached antenna. It comply with the standard requirement.

11. EUT TEST PHOTO

Radiated Measurement Photos