

FCC TEST REPORT

For

Plus One Marketing Ltd.

Smart phone

Test Model: FTU152D

Prepared for : Plus One Marketing Ltd.
Address : Sumitomofudosan Hibiya building 2F, 2-8-6 Shinbashi, Minatoku,
Tokyo, Japan

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.
Address : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, China

Tel : (+86)755-82591330
Fax : (+86)755-82591332
Web : www.LCS-cert.com
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : December 21, 2015
Number of tested samples : 1
Sample number : 15121720
Date of Test : January 04, 2016 - January 20, 2016
Date of Report : January 20, 2016

FCC TEST REPORT**FCC CFR 47 PART 15 E(15.407): 2015****Report Reference No. : LCS1512211981E**

Date of Issue..... : January 20, 2016

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.Address..... : 1/F., Xingyuan Industrial Park, Tongda Road, Bao'an Avenue,
Bao'an District, Shenzhen, Guangdong, ChinaTesting Location/ Procedure : Full application of Harmonised standards ☒
Partial application of Harmonised standards ☐
Other standard testing method ☐**Applicant's Name..... : Plus One Marketing Ltd.**Address..... : Sumitomofudosan Hibiya building 2F, 2-8-6 Shinbashi,
Minatoku, Tokyo, Japan**Test Specification**

Standard : FCC CFR 47 PART 15 E(15.407): 2015 / ANSI C63.10: 2013

Test Report Form No..... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description..... : Smart phone

Trade Mark..... : FREETEL

Test Model : FTU152D

Ratings : DC 3.8V by Li-ion Battery(3450mAh)


Recharge Voltage: DC 5V/1500mA or DC 7V/1500mA

Result : **Positive****Compiled by:**

Leo Lee/ File administrators

Supervised by:

Glin Lu/ Technique principal

Approved by:

Gavin Liang/ Manager

FCC -- TEST REPORT

Test Report No. : LCS1512211981E	<u>January 20, 2016</u> Date of issue
---	--

Test Model.....	: FTU152D
EUT.....	: Smart phone
Applicant.....	: Plus One Marketing Ltd.
Address.....	: Sumitomofudosan Hibiya building 2F, 2-8-6 Shinbashi, Minatoku, Tokyo, Japan
Telephone.....	: /
Fax.....	: /
Manufacturer.....	: Toro-tech Company Limited
Address.....	: A802, Block2, Tianan Cyberpark, Longgang, Shenzhen, China
Telephone.....	: /
Fax.....	: /
Factory.....	: Toro-tech Company Limited
Address.....	: A802, Block2, Tianan Cyberpark, Longgang, Shenzhen, China
Telephone.....	: /
Fax.....	: /

Test Result	Positive
--------------------	-----------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
1.1. DESCRIPTION OF DEVICE (EUT)	5
1.2. SUPPORT EQUIPMENT LIST	6
1.3. EXTERNAL I/O	6
1.4. DESCRIPTION OF TEST FACILITY	6
1.5. LIST OF MEASURING EQUIPMENT	7
1.6. STATEMENT OF THE MEASUREMENT UNCERTAINTY	8
1.7. MEASUREMENT UNCERTAINTY	8
1.8. DESCRIPTION OF TEST MODES	8
2. TEST METHODOLOGY	10
2.1. EUT CONFIGURATION	10
2.2. EUT EXERCISE	10
2.3. GENERAL TEST PROCEDURES	10
3. SYSTEM TEST CONFIGURATION	11
3.1. JUSTIFICATION	11
3.2. EUT EXERCISE SOFTWARE	11
3.3. SPECIAL ACCESSORIES	11
3.4. BLOCK DIAGRAM/SCHEMATICS	11
3.5. EQUIPMENT MODIFICATIONS	11
3.6. TEST SETUP	11
4. SUMMARY OF TEST RESULTS	12
5. TEST RESULT	13
5.1. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT	13
5.2. POWER SPECTRAL DENSITY MEASUREMENT	16
5.3. 6DB & 26DB BANDWIDTH MEASUREMENT	33
5.4. RADIATED EMISSIONS MEASUREMENT	50 50
5.5. POWER LINE CONDUCTED EMISSIONS	71 71
5.6. ANTENNA REQUIREMENTS	73 73

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	: Smart phone
Test Model	: FTU152D
Hardware Version	: Y991_MB_V3.1
Software Version	: Freetel_FTU152D_20151208
Power Supply	: DC 3.8V by Li-ion Battery(3450mAh) Recharge Voltage: DC 5V/1500mA or DC 7V/1500mA
EUT Supports	: GSM/GPRS/EGPRS/WCDMA/HSDPA/HSUPA/LTE/
Radios Application	2.4GHz WIFI/5GHz WIFI/Bluetooth/GPS(RX Only)/NFC
WIFI(5GHz Band)	:
Operating Frequency	: 5180.00-5240.00MHz / 5745.00-5825.00MHz
Channel Number	: 9 Channel for 20MHz Bandwidth 4 channels for 40MHz Bandwidth 2 channels for 80MHz Bandwidth
Modulation Type	: 802.11a/n/ac: OFDM
Antenna Description	: PIFA Antenna, -3.26dBi(Max.)

1.2. Support Equipment List

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN LIANXUNFA TECHNOLOG Y CO.,LTD	Adapter	LX15026R	/	VOC

1.3. External I/O

I/O Port Description	Quantity	Cable
Earphone Jack	1	1.2m, unshielded
USB Port	1	1.2m, unshielded

1.4. Description of Test Facility

CNAS Registration Number. is L4595.

FCC Registration Number. is 899208.

Industry Canada Registration Number. is 9642A-1.

VCCI Registration Number. is C-4260 and R-3804.

ESMD Registration Number. is ARCB0108.

UL Registration Number. is 100571-492.

TUV SUD Registration Number. is SCN1081.

TUV RH Registration Number. is UA 50296516-001

1.5. List Of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Cal Date	Due Date
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	June 18,2015	June 17,2016
Signal analyzer	Agilent	E4448A(External mixers to 40GHz)	US44300469	9kHz~40GHz	July 16,2015	July 15,2016
LISN	MESS Tec	NNB-2/16Z	99079	9KHz-30MHz	June 18,2015	June 17,2016
LISN (Support Unit)	EMCO	3819/2NM	9703-1839	9KHz-30MHz	June 18,2015	June 17,2016
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9KHz-30MHz	June 18,2015	June 17,2016
ISN	SCHAFFNER	ISN ST08	21653	9KHz-30MHz	June 18,2015	June 17,2016
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30M-1GHz 3m	June 18,2015	June 17,2016
Amplifier	SCHAFFNER	COA9231A	18667	9kHz-2GHz	June 18,2015	June 17,2016
Amplifier	Agilent	8449B	3008A02120	1GHz-26.5GHz	July 16,2015	July 15,2016
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5GHz-40GHz	July 16,2015	July 15,2016
Spectrum Analyzer	Agilent	E4407B	MY41440292	9k-26.5GHz	July 16,2015	July 15,2016
MAX Signal Analyzer	Agilent	N9020A	MY50510140	20Hz~26.5GHz	Oct. 27, 2015	Oct. 26, 2016
Loop Antenna	R&S	HFH2-Z2	860004/001	9k-30MHz	June 18,2015	June 17,2016
By-log Antenna	SCHWARZBECK	VULB9163	9163-470	30MHz-1GHz	June 10,2015	June 09,2016
Horn Antenna	EMCO	3115	6741	1GHz-18GHz	June 10,2015	June 09,2016
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz-40GHz	June 10,2015	June 09,2016
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz-1GHz	June 18,2015	June 17,2016
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz-40GHz	June 18,2015	June 17,2016
Spectrum Meter	R&S	FSP 30	100023	9kHz-30GHz	July 16,2015	July 15,2016
Power Meter	R&S	NRVS	100444	DC-40GHz	June 18,2015	June 17,2016
Power Sensor	R&S	NRV-Z51	100458	DC-30GHz	June 18,2015	June 17,2016
Power Sensor	R&S	NRV-Z32	10057	30MHz-6GHz	June 18,2015	June 17,2016
RF CABLE-1m	JYE Bao	RG142	CB034-1m	20MHz-7GHz	June 18,2015	June 17,2016
RF CABLE-2m	JYE Bao	RG142	CB035-2m	20MHz-1GHz	June 18,2015	June 17,2016

Note: All equipment through GRGT EST calibration

1.6. Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

1.7. Measurement Uncertainty

Test Item		Frequency Range	Uncertainty	Note
Radiation Uncertainty	:	9KHz~30MHz	3.10dB	(1)
		30MHz~200MHz	2.96dB	(1)
		200MHz~1000MHz	3.10dB	(1)
		1GHz~26.5GHz	3.80dB	(1)
		26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	:	150kHz~30MHz	1.63dB	(1)
Power disturbance	:	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.8. Description Of Test Modes

The EUT has been tested under operating condition.

The EUT was set to transmit at 100% duty cycle. This test was performed with EUT in X, Y, Z position and the worse case was found when EUT in Y position.

For pre-testing, when performed power line conducted emission measurement, the input Voltage/Frequency AC 120V/60Hz and AC 240V/60Hz were used. Only recorded the worst case in this report.

Worst-case mode and channel used for 150kHz-30 MHz power line conducted emissions was determined to be 802.11a mode(High Channel, 5745-5825MHz Band).

Worst-case mode and channel used for 9kHz-1000 MHz radiated emissions was determined to be 802.11a mode(High Channel, 5745-5825MHz Band).

Worst-Case data rates were utilized from preliminary testing of the Chipset, worst-case data rates used during the testing are as follows:

802.11a Mode: 6 Mbps, OFDM.

802.11n(HT20) Mode: MCS0, OFDM.

802.11n(HT40) Mode: MCS0, OFDM.

802.11ac(VHT20) Mode: MCS0, OFDM.

802.11ac(VHT40) Mode: MCS0, OFDM.

802.11ac(VHT80) Mode: MCS0, OFDM.

Support Bandwidth For 5G WIFI Part:

Bandwidth Mode	20MHz	40MHz	80MHz
802.11a	☒	☐	☐
802.11n(HT20)	☒	☐	☐
802.11n(HT40)	☐	☒	☐
802.11ac(VHT20)	☒	☐	☐
802.11ac(VHT40)	☐	☒	☐
802.11ac(VHT80)	☐	☐	☒

Channel & Frequency:

Frequency Band	Channel No.	Frequency(MHz)	Channel No.	Frequency(MHz)
5180~5240MHz	36	5180	44	5220
	38	5190	46	5230
	40	5200	48	5240
	42	5210	/	/

For 802.11a/n(HT20)/ac(VHT20), Channel 36, 40 and 48 were tested.

For 802.11n(HT40)/ac(VHT40), Channel 38 and 46 were tested.

For 802.11ac(VHT80), Channel 42 was tested.

5745~5825MHz	149	5745	155	5775
	151	5755	159	5795
	153	5765	161	5805
	157	5785	165	5825

For 802.11a/n(HT20)/ac(VHT20), Channel 149, 157 and 165 were tested.

For 802.11n(HT40)/ac(VHT40), Channel 151 and 159 were tested.

For 802.11ac(VHT80), Channel 155 was tested.

2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10: 2013, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd..

2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to FCC's request, Test Procedure 789033 D02 General UNII Test Procedures New Rules v01 is required to be used for this kind of FCC 15.407 UII device.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.407 under the FCC Rules Part 15 Subpart E

2.3. General Test Procedures

2.3.1 Conducted Emissions

According to the requirements in Section 6.2 of ANSI C63.10: 2013, AC power-line conducted emissions shall be measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

2.3.2 Radiated Emissions

The EUT is placed on a turn table and the turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10: 2013

3. SYSTEM TEST CONFIGURATION

3.1. Justification

The system was configured for testing in a continuous transmit condition.

3.2. EUT Exercise Software

N/A

3.3. Special Accessories

N/A

3.4. Block Diagram/Schematics

Please refer to the related document

3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

3.6. Test Setup

Please refer to the test setup photo.

4. SUMMARY OF TEST RESULTS

Applied Standard: FCC Part 15 Subpart E		
FCC Rules	Description of Test	Result
§15.407(a)	Maximum Conducted Output Power	Compliant
§15.407(a)	Power Spectral Density	Compliant
§15.407(e)	6dB & 26dB Bandwidth	Compliant
§15.205, §15.407(b)	Radiated Spurious Emissions and Band Edge	Compliant
§15.407(g)	Frequency Stability	N/A
§15.407(h)	Transmit Power Control (TPC)	N/A
§15.207(a)	Line Conducted Emissions	Compliant
§15.203	Antenna Requirements	Compliant

Note: The customer declared frequency stability is better than 20ppm which ensures that the signal remains in the allocated bands under all operational conditions stated in the user manual.

5. TEST RESULT

5.1. Maximum Conducted Output Power Measurement

5.1.1. Standard Applicable

According to §15.407(a)(1)(i), For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

According to §15.407(a)(1)(ii), For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi.


According to §15.407(a)(1)(iv), For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi.

According to §15.407(a)(3), For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

5.1.2. Test Procedures

The transmitter output (antenna port) was connected to the power meter.

5.1.3. Test Setup Layout



5.1.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.1.5. Test Result of Maximum Conducted Output Power

Temperature	25°C	Humidity	60%
Test Engineer	Leo	Configurations	802.11a/n/ac

Maximum Conducted Output Power Measurement Result For 5180~5240MHz Band

Mode	Channel	Frequency (MHz)	Conducted Power (dBm, Average)	Max. Limit (dBm)	Result
802.11a	36	5180	14.03	24	Complies
	40	5200	13.63	24	Complies
	48	5240	13.60	24	Complies
802.11n(HT20)	36	5180	13.60	24	Complies
	40	5200	13.43	24	Complies
	48	5240	13.45	24	Complies
802.11n(HT40)	38	5190	13.50	24	Complies
	46	5230	13.42	24	Complies
802.11ac(VHT20)	36	5180	14.57	24	Complies
	40	5200	14.06	24	Complies
	48	5240	13.70	24	Complies
802.11ac(VHT40)	38	5190	13.43	24	Complies
	46	5230	13.48	24	Complies
802.11ac(VHT80)	42	5210	14.06	24	Complies

Maximum Conducted Output Power Measurement Result For 5745~5825MHz Band

Mode	Channel	Frequency (MHz)	Conducted Power (dBm, Average)	Max. Limit (dBm)	Result
802.11a	149	5745	14.17	30	Complies
	157	5785	14.45	30	Complies
	165	5825	14.37	30	Complies
802.11n(HT20)	149	5745	14.03	30	Complies
	157	5785	14.22	30	Complies
	165	5825	14.22	30	Complies
802.11n(HT40)	151	5755	14.00	30	Complies
	159	5795	14.08	30	Complies
802.11ac(VHT20)	149	5745	13.83	30	Complies
	157	5785	13.86	30	Complies
	165	5825	14.44	30	Complies
802.11ac(VHT40)	151	5755	14.44	30	Complies
	159	5795	13.89	30	Complies
802.11ac(VHT80)	155	5775	13.98	30	Complies

5.2. Power Spectral Density Measurement

5.2.1. Standard Applicable

According to §15.407(a)(1)(i), For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.

According to §15.407(a)(1)(ii), For an indoor access point operating in the band 5.15-5.25 GHz, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band.


According to §15.407(a)(1)(iv), For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

According to §15.407(a)(3), For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

5.2.2. Test Procedures

- 1) The transmitter was connected directly to a Spectrum Analyzer through a directional couple.
- 2) The power was monitored at the coupler port with a Spectrum Analyzer. The power level was set to the maximum level.
- 3) Set the RBW/VBW = 1MHz/3MHz For the 5.15-5.25GHz band;
Set the RBW/VBW = 100KHz/300KHz For the 5.725-5.85GHz band.
- 4) Set the span to encompass the entire emission bandwidth of the signal.
- 5) Detector = RMS.
- 6) Sweep time = auto couple.
- 7) Trace mode = max hold.
- 8) Allow trace to fully stabilize.
- 9) Use the peak marker function to determine the maximum amplitude level.

5.2.3. Test Setup Layout



5.2.4. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

5.2.5. Test Result of Power Spectral Density

Temperature	25°C	Humidity	60%
Test Engineer	Leo	Configurations	802.11a/n/ac

Power Spectral Density Measurement Result For 5180~5240MHz Band


Mode	Channel	Frequency (MHz)	Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
802.11a	36	5180	4.94	11	Complies
	40	5200	4.56	11	Complies
	48	5240	4.69	11	Complies
802.11n(HT20)	36	5180	4.51	11	Complies
	40	5200	4.24	11	Complies
	48	5240	4.27	11	Complies
802.11n(HT40)	38	5190	1.99	11	Complies
	46	5230	1.68	11	Complies
802.11ac(VHT20)	36	5180	4.94	11	Complies
	40	5200	5.06	11	Complies
	48	5240	4.27	11	Complies
802.11ac(VHT40)	38	5190	2.05	11	Complies
	46	5230	1.99	11	Complies
802.11ac(VHT80)	42	5210	-2.88	11	Complies

Power Spectral Density Measurement Result For 5745~5825MHz Band


Mode	Channel	Frequency (MHz)	Power Density (dBm/500KHz)	Max. Limit (dBm/500KHz)	Result
802.11a	149	5745	2.85	30	Complies
	157	5785	2.84	30	Complies
	165	5825	3.06	30	Complies
802.11n(HT20)	149	5745	2.38	30	Complies
	157	5785	2.22	30	Complies
	165	5825	2.93	30	Complies
802.11n(HT40)	151	5755	-1.09	30	Complies
	159	5795	-1.20	30	Complies
802.11ac(VHT20)	149	5745	2.46	30	Complies
	157	5785	2.61	30	Complies
	165	5825	2.76	30	Complies
802.11ac(VHT40)	151	5755	-1.09	30	Complies
	159	5795	-0.76	30	Complies
802.11ac(VHT80)	155	5775	-4.84	30	Complies

Note: BW correction factor = $10\log(500\text{kHz}/\text{RBW}) = 10\log(500\text{kHz}/100\text{KHz})$

The measured power density (dBm) has the offset with cable loss already.



Test Plot For 802.11a-5180M



Test Plot For 802.11a-5200M



Test Plot For 802.11a-5240M




Test Plot For 802.11n(HT20)-5180M



Test Plot For 802.11n(HT20)-5200M



Test Plot For 802.11n(HT20)-5240M



Test Plot For 802.11n(HT40)-5190M



Test Plot For 802.11n(HT40)-5230M



Test Plot For 802.11ac(VHT20)-5180M




Test Plot For 802.11ac(VHT20)-5200M




Test Plot For 802.11ac(VHT20)-5240M




Test Plot For 802.11ac(VHT40)-5190M



Test Plot For 802.11ac(VHT40)-5230M



Test Plot For 802.11ac(VHT80)-5210M



Test Plot For 802.11a-5745M




Test Plot For 802.11a-5785M



Test Plot For 802.11a-5825M




Test Plot For 802.11n(HT20)-5745M




Test Plot For 802.11n(HT20)-5785M



Test Plot For 802.11n(HT20)-5825M



Test Plot For 802.11n(HT40)-5755M



Test Plot For 802.11n(HT40)-5795M




Test Plot For 802.11ac(VHT20)-5745M




Test Plot For 802.11ac(VHT20)-5785M




Test Plot For 802.11ac(VHT20)-5825M



Test Plot For 802.11ac(VHT40)-5755M



Test Plot For 802.11ac(VHT40)-5795M



Test Plot For 802.11ac(VHT80)-5775M

5.3. 6dB & 26dB Bandwidth Measurement

5.3.1. Standard Applicable

According to §15.407(e): Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

There is no restriction limits for 26dB & 99% occupied bandwidth, report only for reference.

5.3.2. Instruments Setting

The following table is the setting of the Spectrum Analyzer.

6dB Bandwidth Measurement (Only For 5745~5825MHz Band)	
Spectrum Parameter	Setting
Attenuation	Auto
RBW	100KHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold


26dB & 99%Bandwidth Measurement (Only For 5180~5240MHz Band)	
Spectrum Parameter	Setting
Attenuation	Auto
RBW	approximately 1% of the emission bandwidth
VBW	$\geq \text{RBW}$
Detector	Peak
Trace	Max Hold

5

5.3.3. Test Procedures

- 1) The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
- 2) The resolution bandwidth and the video bandwidth were set according to KDB 789033 D02 General UNII Test Procedures New Rules v01
- 3) For 5745~5825MHz Band, Measured the maximum width of the emission that is 6dB down from the peak of the emission.
- 4) For 5180~5240MHz Band, Measured the maximum width of the emission that is 26dB down from the peak of the emission. Record the 26dB & 99% Bandwidth.

5.3.4. Test Setup Layout



5.3.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


5.3.6. Test Result of Spectrum Bandwidth

Temperature	25°C	Humidity	60%
Test Engineer	Leo	Configurations	802.11a/n/ac

Mode	Channel	Frequency	6dB Bandwidth (MHz)	Min. Limit (kHz)	Result
802.11a	149	5745	16.32	500	Complies
	157	5785	16.35	500	Complies
	165	5825	16.36	500	Complies
802.11n(HT20)	149	5745	17.57	500	Complies
	157	5785	17.57	500	Complies
	165	5825	17.58	500	Complies
802.11n(HT40)	151	5755	35.79	500	Complies
	159	5795	36.27	500	Complies
802.11ac(VHT20)	149	5745	17.59	500	Complies
	157	5785	17.58	500	Complies
	165	5825	17.58	500	Complies
802.11ac(VHT40)	151	5755	35.90	500	Complies
	159	5795	36.27	500	Complies
802.11ac(VHT80)	155	5775	76.34	500	Complies



Test Plot For 802.11a-6dB BW-5745M



Test Plot For 802.11a-6dB BW-5785M



Test Plot For 802.11a-6dB BW-5825M



Test Plot For 802.11n(HT20)-6dB BW-5745M



Test Plot For 802.11n(HT20)-6dB BW-5785M



Test Plot For 802.11n(HT20)-6dB BW-5825M




Test Plot For 802.11n(HT40)-6dB BW-5755M



Test Plot For 802.11n(HT40)-6dB BW-5795M



Test Plot For 802.11ac(VHT20)-6dB BW-5745M



Test Plot For 802.11ac(VHT20)-6dB BW-5785M



Test Plot For 802.11ac(VHT20)-6dB BW-5825M



Test Plot For 802.11ac(VHT40)-6dB BW-5755M