FCC REPORT
(WIFI)

Applicant: Plus One Marketing Ltd.

Address of Applicant: 2-8-6 Nishi-Shimbashi, Minatoku, Tokyo, JAPAN

Equipment Under Test (EUT)

Product Name: Mobile Phone

Model No.: FTU18A00

FCC ID: 2AG5L-FTU18A00

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: 23 Oct., 2017

Date of Test: 25 Oct., to 12 Dec., 2017

Date of report issued: 13 Dec., 2017

Test Result: PASS*

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	*13 Dec., 2017*	*Original*

Tested by: Carey Chen ***Date:*** *13 Dec., 2017*

Test Engineer

Reviewed by: Winner Zhang ***Date:*** *13 Dec., 2017*

Project Engineer

3 Contents

Page

1 COVER PAGE 1
2 VERSION 2
3 CONTENTS 3
4 TEST SUMMARY 4
5 GENERAL INFORMATION 5
5.1 CLIENT INFORMATION 5
5.2 GENERAL DESCRIPTION OF E.U.T. 5
5.3 TEST ENVIRONMENT AND TEST MODE 6
5.4 DESCRIPTION OF SUPPORT UNITS 6
5.5 MEASUREMENT UNCERTAINTY 6
5.6 LABORATORY FACILITY 7
5.7 LABORATORY LOCATION 7
5.8 TEST INSTRUMENTS LIST 8
6 TEST RESULTS AND MEASUREMENT DATA 9
6.1 ANTENNA REQUIREMENT 9
6.2 CONDUCTED EMISSION 10
6.3 CONDUCTED OUTPUT POWER 13
6.4 OCCUPY BANDWIDTH 14
6.5 POWER SPECTRAL DENSITY 19
6.6 BAND EDGE 22
6.6.1 Conducted Emission Method 22
6.6.2 Radiated Emission Method 25
6.7 SPURIOUS EMISSION 42
6.7.1 Conducted Emission Method 42
6.7.2 Radiated Emission Method 45
7 TEST SETUP PHOTO 53
8 EUT CONSTRUCTIONAL DETAILS 54

4 Test Summary

Test Items	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
6dB Emission Bandwidth 99% Occupied Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Conducted and Radiated Spurious Emission	15.205/15.209	Pass
Pass: The EUT complies with the essential requirements in the standard.		

5 General Information

5.1 Client Information

Applicant:	Plus One Marketing Ltd.
Address:	2-8-6 Nishi-Shimbashi, Minatoku, Tokyo, JAPAN
Manufacturer:	Plus one marketing Ltd.
Address:	2-8-6 Nishi-Shimbashi, Minatoku, Tokyo, JAPAN
Factory:	Shenzhen Zhenhua Communication Equipment Co., Ltd
Address:	NO.2, NO.3 building, Zhenhua industrial park, NO.44, TieZai Rd, XiXiang town, BaoAn Area, ShenZhen, Guangdong, China.

5.2 General Description of E.U.T.

Product Name:	Mobile Phone
Model No.:	FTU18A00
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(H20)) 2422MHz~2452MHz (802.11n(H40))
Channel numbers:	11 for 802.11b/802.11g/802.11(H20) 7 for 802.11n(H40)
Channel separation:	5MHz
Modulation technology: (IEEE 802.11b)	Direct Sequence Spread Spectrum (DSSS)
Modulation technology: (IEEE 802.11g/802.11n)	Orthogonal Frequency Division Multiplexing(OFDM)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	Internal Antenna
Antenna gain:	1dBi
Power supply:	Rechargeable Li-ion Battery DC3.8V-2500mAh
AC adapter with two plugs :	Model: A8A-050150U-US2 Input: AC100-240V, 50/60Hz, 0.35A Output: DC 5.0V, 1.5A

Operation Frequency each of channel for 802.11b/g/n(H20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:
1. For 802.11n-HT40 mode, the channel number is from 3 to 9;
2. Channel 1, 6 & 11 selected for 802.11b/g/n-HT20 as Lowest, Middle and Highest channel, Channel; 3, 6 & 9 selected for 802.11n-HT40 as Lowest, Middle and Highest channel, Channel.

5.3 Test environment and test mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test mode:	
Transmitting mode	Keep the EUT in continuous transmitting with modulation

The sample was placed 0.8m (below 1GHz)/1.5m (above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate, the follow list were the worst case.

Mode	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(H20)	6.5Mbps
802.11n(H40)	13.5Mbps

5.4 Description of Support Units

The EUT has been tested as an independent unit.

5.5 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	2.14 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	4.24 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	4.35 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	4.44 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	4.56 dB (k=2)

5.6 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **FCC - Registration No.: 727551**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC (Federal Communications Commission). The Registration No. is 727551.

- **IC - Registration No.: 10106A-1**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

- **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

- **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf

5.7 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.
Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,
Bao'an District, Shenzhen, Guangdong, China
Tel: +86-755-23118282, Fax: +86-755-23116366
Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.8 Test Instruments list

Radiated Emission:					
Test Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Date (mm-dd-yy)**	**Cal. Due date (mm-dd-yy)**
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	02-25-2017	02-24-2018
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	02-25-2017	02-24-2018
Horn Antenna	SCHWARZBECK	BBHA9120D	916	02-25-2017	02-24-2018
EMI Test Software	AUDIX	E3	6.110919b	N/A	N/A
Pre-amplifier	HP	8447D	2944A09358	02-25-2017	02-24-2018
Pre-amplifier	CD	PAP-1G18	11804	02-25-2017	02-24-2018
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	02-25-2017	02-24-2018
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	02-25-2017	02-24-2018
Cable	ZDECL	Z108-NJ-NJ-81	1608458	02-25-2017	02-24-2018
Cable	MICRO-COAX	MFR64639	K10742-5	02-25-2017	02-24-2018
Cable	SUHNER	SUCOFLEX100	58193/4PE	02-25-2017	02-24-2018

Conducted Emission:					
Test Equipment	**Manufacturer**	**Model No.**	**Serial No.**	**Cal. Date (mm-dd-yy)**	**Cal. Due date (mm-dd-yy)**
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	02-25-2017	02-24-2018
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	02-25-2017	02-24-2018
LISN	CHASE	MN2050D	1447	02-25-2017	02-24-2018
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2017	07-20-2018
Cable	HP	10503A	N/A	02-25-2017	02-24-2018
EMI Test Software	AUDIX	E3	6.110919b	N/A	N/A

6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part 15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The WiFi antenna is an internal antenna which cannot replace by end-user, the best case gain of the antenna is 1dBi.	



6.2 Conducted Emission

Test Requirement:	FCC Part 15 C Section 15.207
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	150 kHz to 30 MHz
Class / Severity:	Class B
Receiver setup:	RBW=9 kHz, VBW=30 kHz
Limit:	

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
* Decreases with the logarithm of the frequency.		

Test procedure

1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.), which provides a 50ohm/50uH coupling impedance for the measuring equipment.
2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).
3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.

Test setup:



Remark:
E.U.T: Equipment Under Test
LISN: Line Impedence Stabilization Network
Test table height=0.8m

Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Neutral:



Trace: 1

Site : CCIS Shielding Room
Condition : FCC PART15 B QP LISN NEUTRAL
EUT : Mobile Phone
Model : FTU18A00
Test Mode : WIFI mode
Power Rating : AC 120/60Hz
Environment : Temp: 23 ℃ Huni:56% Atmos:101KPa
Test Engineer: Carey
Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	24.30	-0.38	10.78	34.70	56.00	-21.30	Average
2	0.154	39.33	-0.38	10.78	49.73	65.78	-16.05	QP
3	0.182	36.80	-0.35	10.77	47.22	64.42	-17.20	QP
4	0.186	21.84	-0.35	10.76	32.25	54.20	-21.95	Average
5	0.222	36.01	-0.33	10.76	46.44	62.74	-16.30	QP
6	0.226	21.84	-0.33	10.75	32.26	52.61	-20.35	Average
7	0.258	31.47	-0.33	10.75	41.89	61.51	-19.62	QP
8	0.561	20.43	-0.30	10.76	30.89	46.00	-15.11	Average
9	0.598	20.67	-0.30	10.77	31.14	46.00	-14.86	Average
10	0.634	32.53	-0.30	10.77	43.00	56.00	-13.00	QP
11	0.634	26.88	-0.30	10.77	37.35	46.00	-8.65	Average
12	9.654	27.77	0.30	10.92	38.99	60.00	-21.01	QP

Notes:

1. *An initial pre-scan was performed on the live and neutral lines with peak detector.*
2. *Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.*
3. *Final Level =Receiver Read level + LISN Factor + Cable Loss.*

Line:



Trace: 3

Site : CCIS Shielding Room
Condition : FCC PART15 B QP LISN LINE
EUT : Mobile Phone
Model : FTU18A00
Test Mode : WIFI mode
Power Rating : AC 120/60Hz
Environment : Temp: 23 ℃ Huni:56% Atmos:101KPa
Test Engineer: Carey
Remark :

	Freq	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.150	35.47	-0.56	10.78	45.69	66.00	-20.31	QP
2	0.150	20.98	-0.56	10.78	31.20	56.00	-24.80	Average
3	0.190	34.77	-0.53	10.76	45.00	64.02	-19.02	QP
4	0.190	19.95	-0.53	10.76	30.18	54.02	-23.84	Average
5	0.226	33.49	-0.52	10.75	43.72	62.61	-18.89	QP
6	0.226	20.93	-0.52	10.75	31.16	52.61	-21.45	Average
7	0.258	30.67	-0.51	10.75	40.91	61.51	-20.60	QP
8	0.527	20.26	-0.49	10.76	30.53	46.00	-15.47	Average
9	0.561	21.19	-0.49	10.76	31.46	46.00	-14.54	Average
10	0.567	29.81	-0.49	10.76	40.08	56.00	-15.92	QP
11	0.637	35.68	-0.48	10.77	45.97	56.00	-10.03	QP
12	0.637	28.05	-0.48	10.77	38.34	46.00	-7.66	Average

Notes:

1. *An initial pre-scan was performed on the live and neutral lines with peak detector.*
2. *Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.*
3. *Final Level =Receiver Read level + LISN Factor + Cable Loss.*

6.3 Conducted Output Power

Test Requirement:	FCC Part 15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v04 section 9.2.2.2
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Test CH	Maximum Conducted Output Power (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	15.78	14.82	13.77	11.16	30.00	Pass
Middle	13.63	13.00	12.98	12.04		
Highest	12.87	12.27	11.92	11.39		

6.4 Occupy Bandwidth

Test Requirement:	FCC Part 15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v04 section 8.1
Limit:	>500kHz
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Test CH	6dB Emission Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	8.64	16.56	17.76	35.52	>500	Pass
Middle	8.32	16.64	17.76	35.52		
Highest	8.24	16.48	17.76	35.84		
Test CH	99% Occupy Bandwidth (MHz)				Limit(kHz)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	13.04	16.64	17.76	36.00	N/A	N/A
Middle	13.12	16.64	17.76	36.00		
Highest	13.12	16.56	17.76	36.00		

Test plot as follows:

802.11b

6dB EBW



Date: 27.OCT.2017 18:30:41

Lowest channel



Date: 27.OCT.2017 18:35:00

Middle channel



Date: 27.OCT.2017 18:36:22

Highest channel

99% OBW



Date: 27.OCT.2017 18:22:50

Lowest channel



Date: 27.OCT.2017 18:22:26

Middle channel



Date: 27.OCT.2017 18:23:16

Highest channel

802.11g

6dB EBW



Date: 27.OCT.2017 18:37:47

Lowest channel



Date: 27.OCT.2017 18:40:55

Middle channel



Date: 27.OCT.2017 18:41:44

Highest channel

99% OBW



Date: 27.OCT.2017 18:29:30

Lowest channel



Date: 27.OCT.2017 18:24:31

Middle channel



Date: 27.OCT.2017 18:25:03

Highest channel

802.11n(H20)

6dB EBW



Date: 27.OCT.2017 18:43:51

Lowest channel



Date: 27.OCT.2017 18:44:43

Middle channel



Date: 27.OCT.2017 18:45:57

Highest channel

99% OBW



Date: 27.OCT.2017 18:26:10

Lowest channel



Date: 27.OCT.2017 18:26:34

Middle channel



Date: 27.OCT.2017 18:26:53

Highest channel

802.11n(H40)

6dB EBW



Date: 27.OCT.2017 18:47:32

Lowest channel



Date: 27.OCT.2017 18:48:34

Middle channel



Date: 27.OCT.2017 18:49:23

Highest channel

99% OBW



Date: 27.OCT.2017 18:27:43

Lowest channel



Date: 27.OCT.2017 18:28:07

Middle channel



Date: 27.OCT.2017 18:28:38

Highest channel

6.5 Power Spectral Density

Test Requirement:	FCC Part 15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v04 section 10.2
Limit:	8dBm
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data:

Test CH	Power Spectral Density (dBm)				Limit(dBm)	Result
	802.11b	802.11g	802.11n(H20)	802.11n(H40)		
Lowest	7.26	2.11	2.27	-0.34	8.00	Pass
Middle	4.68	0.48	0.48	-1.71		
Highest	4.38	-0.56	-0.33	-3.01		

Test plot as follows:

Test mode: 802.11b



Date: 27.OCT.2017 18:58:33

Test mode: 802.11g



Date: 27.OCT.2017 19:00:42

Lowest channel



Date: 27.OCT.2017 18:59:24

Lowest channel



Date: 27.OCT.2017 19:01:47

Middle channel



Date: 27.OCT.2017 18:59:52

Middle channel



Date: 27.OCT.2017 19:02:14

Highest channel

Highest channel

Test mode: 802.11n(H20)



Date: 27.OCT.2017 19:02:49

Test mode: 802.11n(H40)



Date: 27.OCT.2017 19:04:28

Lowest channel



Date: 27.OCT.2017 19:03:20

Lowest channel



Date: 27.OCT.2017 19:04:47

Middle channel



Date: 27.OCT.2017 19:03:42

Middle channel



Date: 27.OCT.2017 19:05:18

Highest channel

Highest channel

6.6 Band Edge

6.6.1 Conducted Emission Method

Test Requirement:	FCC Part 15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v04 section 13
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Test plot as follows:

802.11b



Date: 2.NOV.2017 15:49:52

Lowest channel



Date: 2.NOV.2017 16:03:55

Highest channel

802.11g



Date: 2.NOV.2017 15:51:03

Lowest channel



Date: 2.NOV.2017 16:03:01

Highest channel

802.11n(H20)



Date: 2.NOV.2017 15:52:01

Lowest channel



Date: 2.NOV.2017 16:01:50

Highest channel

802.11n(H40)



Date: 2.NOV.2017 15:59:15

Lowest channel



Date: 2.NOV.2017 16:00:40

Highest channel

6.6.2 Radiated Emission Method

Test Requirement:	FCC Part 15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance v04 section 12.1
Test Frequency Range:	2.3GHz to 2.5GHz
Test Distance:	3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Remark
Above 1GHz	Peak	1MHz	3MHz	Peak Value
	RMS	1MHz	3MHz	Average Value

Limit:

Frequency	Limit (dBuV/m @3m)	Remark
Above 1GHz	54.00	Average Value
	74.00	Peak Value

Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Test setup:



Test Instruments:	Refer to section 5.8 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

802.11b

Test channel: Lowest

Horizontal:




```
Site          : 3m chamber
Condition     : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT           : Mobile Phone
Model         : FTU18A00
Test mode     : 802.11B-L mode
Power Rating  : AC 120V/60Hz
Environment   : Temp:25.5℃  Huni:55%  101KPa
Test Engineer: Carey
REMARK        :
                 ReadAntenna  Cable Preamp         Limit   Over
           Freq  Level Factor   Loss Factor  Level   Line  Limit Remark
        --------- ------ ------ ------ ------ ------ ------ ------ ----------
               MHz   dBuV   dB/m     dB     dB dBuV/m dBuV/m     dB

  1    2390.000  18.82  25.45   4.69   0.00  48.96  74.00 -25.04 Peak
  2    2390.000   7.53  25.45   4.69   0.00  37.67  54.00 -16.33 Average
```

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Vertical:




```
Site         : 3m chamber
Condition    : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
EUT          : Mobile Phone
Model        : FTU18A00
Test mode    : 802.11B-L mode
Power Rating : AC 120V/60Hz
Environment  : Temp:25.5℃  Huni:55%  101KPa
Test Engineer: Carey
REMARK       :
```

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	2390.000	16.46	25.45	4.69	0.00	46.60	74.00	-27.40	Peak
2	2390.000	7.45	25.45	4.69	0.00	37.59	54.00	-16.41	Average

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test channel: Highest

Horizontal:




```
Site          : 3m chamber
Condition     : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT           : Mobile Phone
Model         : FTU18A00
Test mode     : 802.11B-H mode
Power Rating  : AC 120V/60Hz
Environment   : Temp:25.5℃  Huni:55%  101KPa
Test Engineer: Carey
REMARK        :
                  ReadAntenna  Cable Preamp         Limit   Over
            Freq  Level Factor   Loss Factor  Level   Line  Limit Remark
         --------- ------ ------ ------ ------ ------ ------ ------ ----------
                MHz   dBuV   dB/m     dB     dB dBuV/m dBuV/m     dB

   1    2483.500  18.06  25.66   4.81   0.00  48.53  74.00 -25.47 Peak
   2    2483.500   8.13  25.66   4.81   0.00  38.60  54.00 -15.40 Average
```

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Vertical:




```
Site          : 3m chamber
Condition     : FCC PART 15 (PK) 3m BBHA9120(1G18G) VERTICAL
EUT           : Mobile Phone
Model         : FTU18A00
Test mode     : 802.11B-H mode
Power Rating  : AC 120V/60Hz
Environment   : Temp:25.5'C  Huni:55%  101KPa
Test Engineer: Carey
REMARK        :
                 ReadAntenna  Cable Preamp         Limit   Over
          Freq  Level Factor   Loss Factor  Level   Line  Limit Remark
       --------- ------ ------ ------ ------ ------ ------ ------ ----------
             MHz   dBuV   dB/m     dB     dB dBuV/m dBuV/m     dB

  1    2483.500  18.28  25.66   4.81   0.00  48.75  74.00 -25.25 Peak
  2    2483.500   8.14  25.66   4.81   0.00  38.61  54.00 -15.39 Average
```

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

802.11g

Test channel: Lowest

Horizontal:




```
Site          : 3m chamber
Condition     : FCC PART 15 (PK) 3m BBHA9120(1G18G) HORIZONTAL
EUT           : Mobile Phone
Model         : FTU18A00
Test mode     : 802.11G-L mode
Power Rating  : AC 120V/60Hz
Environment   : Temp:25.5℃  Huni:55%  101KPa
Test Engineer: Carey
REMARK        :
                 ReadAntenna  Cable Preamp         Limit   Over
           Freq  Level Factor   Loss Factor  Level   Line  Limit Remark
        --------- ------ ------ ------ ------ ------ ------ ------ ----------
               MHz   dBuV   dB/m     dB     dB dBuV/m dBuV/m     dB

  1    2390.000  16.86  25.45   4.69   0.00  47.00  74.00 -27.00 Peak
  2    2390.000   7.77  25.45   4.69   0.00  37.91  54.00 -16.09 Average
```

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*