

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 14:20:25
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	10.30	dBm	INFO
Ref. frequency	---	---	5241.400	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	5.48	MHz	INFO
T1 26dB	---	---	5237.3600	MHz	INFO
T2 26dB	---	---	5242.8400	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.30 12.83 25
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	6.45	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	6.45	dBm	PASS
LIMIT: 11 dBm + 10 log 5.48					
Max output power DC corrected cond	---	18.39	6.45	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	0.64	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	0.64	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 14:19:58
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5240 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	10.52	dBm	INFO
Ref. frequency	---	---	5240.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.52 12.83 25
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	16.11	dBm	INFO
Peak Power	---	---	40.831939	mW	INFO
Frequency at Peak	---	---	5239.95	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 14:10:28
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 14:10:31
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5240 Information:

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 14:09:50
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5200 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	9.13	dBm	INFO
Ref. frequency	---	---	5200.800	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.13 12.93 20
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	4.446	MHz	INFO
T1 99%	5150.000000	---	5197.8521	MHz	PASS
T2 99%	---	5250.000000	5202.2977	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	5.55	MHz	INFO
T1 26dB	5150.000000	---	5197.3000	MHz	PASS
T2 26dB	---	5250.000000	5202.8500	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 14:08:15
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	10.11	dBm	INFO
Ref. frequency	---	---	5198.600	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	4.436	MHz	INFO
T1 99%	---	---	5197.8422	MHz	INFO
T2 99%	---	---	5202.2777	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5200 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	22.11 12.93 25
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	5.11	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	5.11	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	11.89	dBm	PASS
LIMIT: 10 dBm + 10 log 4.436					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	16.47	11.89	dBm	PASS
Power spectral density eirp	---		6.41	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	6.41	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	5.11	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 14:06:42
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	9.78	dBm	INFO
Ref. frequency	---	---	5201.400	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	5.36	MHz	INFO
T1 26dB	---	---	5197.3600	MHz	INFO
T2 26dB	---	---	5202.7200	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	21.78 12.93 25
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	5.38	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	5.38	dBm	PASS
LIMIT: 11 dBm + 10 log 5.36					
Max output power DC corrected cond	---	18.29	5.38	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-0.36	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-0.36	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 14:06:15
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5200 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	9.71	dBm	INFO
Ref. frequency	---	---	5198.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	21.71 12.93 25
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	14.31	dBm	INFO
Peak Power	---	---	26.977394	mW	INFO
Frequency at Peak	---	---	5199.301	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 13:53:23
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 13:53:25
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5200 , Information:

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:52:44
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5180 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	9.21	dBm	INFO
Ref. frequency	---	---	5181.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.21 12.57 20
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	4.496	MHz	INFO
T1 99%	5150.000000	---	5177.8022	MHz	PASS
T2 99%	---	5250.000000	5182.2977	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	5.5	MHz	INFO
T1 26dB	5150.000000	---	5177.3500	MHz	PASS
T2 26dB	---	5250.000000	5182.8500	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:51:06
Ambit temp (test rack) [°C] humidity [rel%]	23.3 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	8.46	dBm	INFO
Ref. frequency	---	---	5181.400	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	4.396	MHz	INFO
T1 99%	---	---	5177.8422	MHz	INFO
T2 99%	---	---	5182.2378	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5180 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.46 12.57 25
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	4.25	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	4.25	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	11.03	dBm	PASS
LIMIT: 10 dBm + 10 log 4.396					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	16.43	11.03	dBm	PASS
Power spectral density eirp	---		5.63	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	5.63	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	4.25	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:49:30
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	8.95	dBm	INFO
Ref. frequency	---	---	5178.600	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	5.52	MHz	INFO
T1 26dB	---	---	5177.2800	MHz	INFO
T2 26dB	---	---	5182.8000	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.95 12.57 25
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	4.56	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	4.56	dBm	PASS
LIMIT: 11 dBm + 10 log 5.52					
Max output power DC corrected cond	---	18.42	4.56	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-1.15	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-1.15	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:49:03
Ambit temp (test rack) [°C] humidity [rel%]	23.2 46
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5180 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	8.49	dBm	INFO
Ref. frequency	---	---	5181.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.49 12.57 25
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	14.08	dBm	INFO
Peak Power	---	---	25.585859	mW	INFO
Frequency at Peak	---	---	5180.05	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 13:48:13
Ambit temp (test rack) [°C] humidity [rel%]	23.2 46
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 13:48:15
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5180 , Information:

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:19:15
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5240 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.68	dBm	INFO
Ref. frequency	---	---	5240.400	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.68 12.4 20
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.691	MHz	INFO
T1 99%	5150.000000	---	5235.7043	MHz	PASS
T2 99%	---	5250.000000	5244.3956	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.95	MHz	INFO
T1 26dB	5150.000000	---	5234.5000	MHz	PASS
T2 26dB	---	5250.000000	5245.4500	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:17:40
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.70	dBm	INFO
Ref. frequency	---	---	5243.600	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.631	MHz	INFO
T1 99%	---	---	5235.7243	MHz	INFO
T2 99%	---	---	5244.3556	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5240 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.70 12.4 25
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	4.37	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	4.37	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	11.15	dBm	PASS
LIMIT: 10 dBm + 10 log 8.631					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	19.36	11.15	dBm	PASS
Power spectral density eirp	---		2.95	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	2.95	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	4.37	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:16:06
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.79	dBm	INFO
Ref. frequency	---	---	5236.600	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.96	MHz	INFO
T1 26dB	---	---	5234.5200	MHz	INFO
T2 26dB	---	---	5245.4800	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.79 12.4 25
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	4.52	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	4.52	dBm	PASS
LIMIT: 11 dBm + 10 log 10.96					
Max output power DC corrected cond	---	21.4	4.52	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-3.82	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-3.82	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:15:39
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5240 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.29	dBm	INFO
Ref. frequency	---	---	5239.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.29 12.4 25
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	14.06	dBm	INFO
Peak Power	---	---	25.468303	mW	INFO
Frequency at Peak	---	---	5240	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 13:08:23
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001
Message start	28.05.2026 13:08:25
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5240 Information: U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:07:44
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5200 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.32	dBm	INFO
Ref. frequency	---	---	5202.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.32 12.65 20
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.691	MHz	INFO
T1 99%	5150.000000	---	5195.7043	MHz	PASS
T2 99%	---	5250.000000	5204.3956	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.8	MHz	INFO
T1 26dB	5150.000000	---	5194.6000	MHz	PASS
T2 26dB	---	5250.000000	5205.4000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:06:09
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.07	dBm	INFO
Ref. frequency	---	---	5203.000	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.671	MHz	INFO
T1 99%	---	---	5195.6843	MHz	INFO
T2 99%	---	---	5204.3556	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5200 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.07 12.65 20
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	3.4	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	3.4	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	10.18	dBm	PASS
LIMIT: 10 dBm + 10 log 8.671					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	19.38	10.18	dBm	PASS
Power spectral density eirp	---		1.93	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	1.93	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	3.4	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:04:35
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	5.85	dBm	INFO
Ref. frequency	---	---	5202.800	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.84	MHz	INFO
T1 26dB	---	---	5194.5600	MHz	INFO
T2 26dB	---	---	5205.4000	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.85 12.65 20
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	3.53	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	3.53	dBm	PASS
LIMIT: 11 dBm + 10 log 10.84					
Max output power DC corrected cond	---	21.35	3.53	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-4.86	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-4.86	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 13:04:09
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5200 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.91	dBm	INFO
Ref. frequency	---	---	5202.800	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.91 12.65 25
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	12.93	dBm	INFO
Peak Power	---	---	19.633603	mW	INFO
Frequency at Peak	---	---	5199.7	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 12:48:18
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001
Message start	28.05.2026 12:48:21
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5200 , Information: U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:47:40
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5180 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.49	dBm	INFO
Ref. frequency	---	---	5182.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.49 12.36 20
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.691	MHz	INFO
T1 99%	5150.000000	---	5175.7043	MHz	PASS
T2 99%	---	5250.000000	5184.3956	MHz	PASS



BW 26dB



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.65	MHz	INFO
T1 26dB	5150.000000	---	5174.6500	MHz	PASS
T2 26dB	---	5250.000000	5185.3000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:46:02
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.33	dBm	INFO
Ref. frequency	---	---	5178.600	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.671	MHz	INFO
T1 99%	---	---	5175.7243	MHz	INFO
T2 99%	---	---	5184.3956	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5180 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.33 12.36 25
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	3.87	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	3.87	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	10.65	dBm	PASS
LIMIT: 10 dBm + 10 log 8.671					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC --- corrected eirp		19.38	10.65	dBm	PASS
Power spectral density eirp	---		2.48	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	2.48	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC --- corrected cond		24	3.87	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:44:26
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.90	dBm	INFO
Ref. frequency	---	---	5182.400	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	11.08	MHz	INFO
T1 26dB	---	---	5174.4800	MHz	INFO
T2 26dB	---	---	5185.5600	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.90 12.36 25
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	4.01	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	4.01	dBm	PASS
LIMIT: 11 dBm + 10 log 11.08					
Max output power DC corrected cond	---	21.45	4.01	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-4.31	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-4.31	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:43:59
Ambit temp (test rack) [°C] humidity [rel%]	23.1 46
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5180 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.67	dBm	INFO
Ref. frequency	---	---	5180.000	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.67 12.36 25
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	13.26	dBm	INFO
Peak Power	---	---	21.183611	mW	INFO
Frequency at Peak	---	---	5179.85	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 12:43:38
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001
Message start	28.05.2026 12:43:41
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5180 , Information: U-NII-1_OFDM_a-mode_10Mhz_ANT2_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:39:49
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5240 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	8.09	dBm	INFO
Ref. frequency	---	---	5240.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.09 12.83 20
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.541	MHz	INFO
T1 99%	5150.000000	---	5235.8042	MHz	PASS
T2 99%	---	5250.000000	5244.3457	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.7	MHz	INFO
T1 26dB	5150.000000	---	5234.7000	MHz	PASS
T2 26dB	---	5250.000000	5245.4000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:38:16
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	9.36	dBm	INFO
Ref. frequency	---	---	5236.600	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.511	MHz	INFO
T1 99%	---	---	5235.8042	MHz	INFO
T2 99%	---	---	5244.3157	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5240 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	21.36 12.83 25
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	5.24	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	5.24	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	12.02	dBm	PASS
LIMIT: 10 dBm + 10 log 8.511					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	19.3	12.02	dBm	PASS
Power spectral density eirp	---		3.71	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	3.71	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	5.24	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:36:42
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.79	dBm	INFO
Ref. frequency	---	---	5242.600	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.56	MHz	INFO
T1 26dB	---	---	5234.7200	MHz	INFO
T2 26dB	---	---	5245.2800	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.79 12.83 25
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	5.42	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	5.42	dBm	PASS
LIMIT: 11 dBm + 10 log 10.56					
Max output power DC corrected cond	---	21.24	5.42	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-3.06	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-3.06	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:36:15
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5240 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.81	dBm	INFO
Ref. frequency	---	---	5243.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.81 12.83 25
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	15.35	dBm	INFO
Peak Power	---	---	34.276779	mW	INFO
Frequency at Peak	---	---	5239.5	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 12:35:08
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 12:35:11
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5240 Information: U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:34:29
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5200 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	8.19	dBm	INFO
Ref. frequency	---	---	5198.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.19 12.93 20
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.541	MHz	INFO
T1 99%	5150.000000	---	5195.8042	MHz	PASS
T2 99%	---	5250.000000	5204.3457	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.95	MHz	INFO
T1 26dB	5150.000000	---	5194.5500	MHz	PASS
T2 26dB	---	5250.000000	5205.5000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:32:54
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.38	dBm	INFO
Ref. frequency	---	---	5198.000	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.511	MHz	INFO
T1 99%	---	---	5195.8042	MHz	INFO
T2 99%	---	---	5204.3157	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5200 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.38 12.93 25
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	3.71	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	3.71	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	10.49	dBm	PASS
LIMIT: 10 dBm + 10 log 8.511					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	19.3	10.49	dBm	PASS
Power spectral density eirp	---		2.32	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	2.32	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	3.71	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:31:21
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.29	dBm	INFO
Ref. frequency	---	---	5203.200	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.6	MHz	INFO
T1 26dB	---	---	5194.8400	MHz	INFO
T2 26dB	---	---	5205.4400	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.29 12.93 25
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	3.87	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	3.87	dBm	PASS
LIMIT: 11 dBm + 10 log 10.6					
Max output power DC corrected cond	---	21.25	3.87	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-4.51	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-4.51	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:30:54
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5200 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.21	dBm	INFO
Ref. frequency	---	---	5199.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.21 12.93 25
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	13.2	dBm	INFO
Peak Power	---	---	20.892961	mW	INFO
Frequency at Peak	---	---	5199.85	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 12:19:07
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 12:19:10
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5200 , Information: U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:18:28
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5180 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.57	dBm	INFO
Ref. frequency	---	---	5183.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	14.57 12.57 20
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.541	MHz	INFO
T1 99%	5150.000000	---	5175.8042	MHz	PASS
T2 99%	---	5250.000000	5184.3457	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.85	MHz	INFO
T1 26dB	5150.000000	---	5174.4500	MHz	PASS
T2 26dB	---	5250.000000	5185.3000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:16:52
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.59	dBm	INFO
Ref. frequency	---	---	5176.400	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	8.551	MHz	INFO
T1 99%	---	---	5175.8042	MHz	INFO
T2 99%	---	---	5184.3556	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5180 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.59 12.57 25
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	3.31	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	3.31	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	10.09	dBm	PASS
LIMIT: 10 dBm + 10 log 8.551					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC --- corrected eirp		19.32	10.09	dBm	PASS
Power spectral density eirp	---		2.07	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	2.07	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC --- corrected cond		24	3.31	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:15:15
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.67	dBm	INFO
Ref. frequency	---	---	5176.600	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	10.64	MHz	INFO
T1 26dB	---	---	5174.7600	MHz	INFO
T2 26dB	---	---	5185.4000	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.67 12.57 25
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	3.47	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	3.47	dBm	PASS
LIMIT: 11 dBm + 10 log 10.64					
Max output power DC corrected cond	---	21.27	3.47	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-4.69	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-4.69	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:14:48
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5180 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.59	dBm	INFO
Ref. frequency	---	---	5181.400	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.59 12.57 25
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	11.79	dBm	INFO
Peak Power	---	---	15.100802	mW	INFO
Frequency at Peak	---	---	5179.75	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 12:14:32
Ambit temp (test rack) [°C] humidity [rel%]	23.2 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 12:14:35
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5180 , Information: U-NII-1_OFDM_a-mode_10Mhz_ANT1_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:10:54
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5240 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.75	dBm	INFO
Ref. frequency	---	---	5234.010	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.75 12.4 20
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.833	MHz	INFO
T1 99%	5150.000000	---	5231.6084	MHz	PASS
T2 99%	---	5250.000000	5248.4416	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.6	MHz	INFO
T1 26dB	5150.000000	---	5229.6000	MHz	PASS
T2 26dB	---	5250.000000	5250.2000	MHz	DFS required

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:09:20
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.02	dBm	INFO
Ref. frequency	---	---	5235.200	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.823	MHz	INFO
T1 99%	---	---	5231.6084	MHz	INFO
T2 99%	---	---	5248.4316	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5240 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.02 12.4 25
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	7.86	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	7.86	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	14.64	dBm	PASS
LIMIT: 10 dBm + 10 log 16.823					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	22.26	14.64	dBm	PASS
Power spectral density eirp	---		3.55	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	3.55	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	7.86	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:07:45
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.74	dBm	INFO
Ref. frequency	---	---	5235.200	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.72	MHz	INFO
T1 26dB	---	---	5229.5600	MHz	INFO
T2 26dB	---	---	5250.2800	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.74 12.4 25
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	7.95	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	7.95	dBm	PASS
LIMIT: 11 dBm + 10 log 20.72					
Max output power DC corrected cond	---	24.16	7.95	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-3.25	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-3.25	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:07:17
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5240 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.46	dBm	INFO
Ref. frequency	---	---	5234.410	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.46 12.4 20
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	10.61	dBm	INFO
Peak Power	---	---	11.508004	mW	INFO
Frequency at Peak	---	---	5236.454	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 12:06:31
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001
Message start	28.05.2026 12:06:34
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5240 Information: U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:05:52
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5200 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	3.92	dBm	INFO
Ref. frequency	---	---	5194.810	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.92 12.65 15
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.833	MHz	INFO
T1 99%	5150.000000	---	5191.6583	MHz	PASS
T2 99%	---	5250.000000	5208.4915	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.75	MHz	INFO
T1 26dB	5150.000000	---	5189.6500	MHz	PASS
T2 26dB	---	5250.000000	5210.4000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:04:15
Ambit temp (test rack) [°C] humidity [rel%]	23.1 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	5.57	dBm	INFO
Ref. frequency	---	---	5195.200	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.823	MHz	INFO
T1 99%	---	---	5191.6484	MHz	INFO
T2 99%	---	---	5208.4715	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5200 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.57 12.65 20
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	6.95	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	6.95	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	13.73	dBm	PASS
LIMIT: 10 dBm + 10 log 16.823					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	22.26	13.73	dBm	PASS
Power spectral density eirp	---		2.6	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	2.6	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	6.95	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:02:41
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.18	dBm	INFO
Ref. frequency	---	---	5203.000	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.68	MHz	INFO
T1 26dB	---	---	5189.6800	MHz	INFO
T2 26dB	---	---	5210.3600	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.18 12.65 20
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	7.03	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	7.03	dBm	PASS
LIMIT: 11 dBm + 10 log 20.68					
Max output power DC corrected cond	---	24.16	7.03	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-4.16	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-4.16	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:02:14
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5200 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	3.94	dBm	INFO
Ref. frequency	---	---	5194.810	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.94 12.65 20
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	10.02	dBm	INFO
Peak Power	---	---	10.046158	mW	INFO
Frequency at Peak	---	---	5197.353	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 12:01:23
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001
Message start	28.05.2026 12:01:25
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5200 , Information: U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 12:00:43
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5180 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.14	dBm	INFO
Ref. frequency	---	---	5175.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.14 12.36 15
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.833	MHz	INFO
T1 99%	5150.000000	---	5171.6084	MHz	PASS
T2 99%	---	5250.000000	5188.4416	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.5	MHz	INFO
T1 26dB	5150.000000	---	5169.7000	MHz	PASS
T2 26dB	---	5250.000000	5190.2000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:59:06
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	3.71	dBm	INFO
Ref. frequency	---	---	5187.390	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.823	MHz	INFO
T1 99%	---	---	5171.6084	MHz	INFO
T2 99%	---	---	5188.4316	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5180 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.71 12.36 20
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	7.18	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	7.18	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	13.96	dBm	PASS
LIMIT: 10 dBm + 10 log 16.823					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	22.26	13.96	dBm	PASS
Power spectral density eirp	---		2.85	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	2.85	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	7.18	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:57:27
Ambit temp (test rack) [°C] humidity [rel%]	23.0 46
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.09	dBm	INFO
Ref. frequency	---	---	5175.000	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.44	MHz	INFO
T1 26dB	---	---	5169.6800	MHz	INFO
T2 26dB	---	---	5190.1200	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.09 12.36 20
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	7.26	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	7.26	dBm	PASS
LIMIT: 11 dBm + 10 log 20.44					
Max output power DC corrected cond	---	24.1	7.26	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-3.91	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-3.91	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:56:59
Ambit temp (test rack) [°C] humidity [rel%]	23.0 46
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5180 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.39	dBm	INFO
Ref. frequency	---	---	5182.800	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.39 12.36 20
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	10.56	dBm	INFO
Peak Power	---	---	11.376273	mW	INFO
Frequency at Peak	---	---	5176.653	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 11:56:35
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001
Message start	28.05.2026 11:56:38
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5180 , Information: U-NII-1_OFDM_a-mode_20MHz_ANT2_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:55:25
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5240 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	5.81	dBm	INFO
Ref. frequency	---	---	5234.810	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	13.81 12.83 20
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.683	MHz	INFO
T1 99%	5150.000000	---	5231.7083	MHz	PASS
T2 99%	---	5250.000000	5248.3916	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.6	MHz	INFO
T1 26dB	5150.000000	---	5229.7000	MHz	PASS
T2 26dB	---	5250.000000	5250.3000	MHz	DFS required

Verdict
PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:53:50
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.17	dBm	INFO
Ref. frequency	---	---	5245.590	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.663	MHz	INFO
T1 99%	---	---	5231.7283	MHz	INFO
T2 99%	---	---	5248.3916	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5240 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.17 12.83 20
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	8.7	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	8.7	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	15.48	dBm	PASS
LIMIT: 10 dBm + 10 log 16.663					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	22.22	15.48	dBm	PASS
Power spectral density eirp	---		4.2	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	4.2	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	8.7	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:52:14
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5240 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	6.09	dBm	INFO
Ref. frequency	---	---	5245.390	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.6	MHz	INFO
T1 26dB	---	---	5229.7600	MHz	INFO
T2 26dB	---	---	5250.3600	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	18.09 12.83 20
Start [MHz] Stop [MHz]	5220.000 5260.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	8.81	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	8.81	dBm	PASS
LIMIT: 11 dBm + 10 log 20.6					
Max output power DC corrected cond	---	24.14	8.81	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-2.57	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-2.57	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:51:46
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	True Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5240 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	5.73	dBm	INFO
Ref. frequency	---	---	5234.810	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.73 12.83 20
Start [MHz] Stop [MHz]	5215.000 5265.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	11.81	dBm	INFO
Peak Power	---	---	15.170504	mW	INFO
Frequency at Peak	---	---	5239.65	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 11:51:04
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 11:51:06
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5240 Information: U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:50:24
Ambit temp (test rack) [°C] humidity [rel%]	23.0 45
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5200 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.22	dBm	INFO
Ref. frequency	---	---	5207.390	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	12.22 12.93 15
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.633	MHz	INFO
T1 99%	5150.000000	---	5191.7582	MHz	PASS
T2 99%	---	5250.000000	5208.3916	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20	MHz	INFO
T1 26dB	5150.000000	---	5190.1000	MHz	PASS
T2 26dB	---	5250.000000	5210.1000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:48:46
Ambit temp (test rack) [°C] humidity [rel%]	22.9 45
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.36	dBm	INFO
Ref. frequency	---	---	5195.200	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.583	MHz	INFO
T1 99%	---	---	5191.7682	MHz	INFO
T2 99%	---	---	5208.3516	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5200 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.36 12.93 20
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	7.49	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	7.49	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	14.27	dBm	PASS
LIMIT: 10 dBm + 10 log 16.583					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	22.2	14.27	dBm	PASS
Power spectral density eirp	---		3.14	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	3.14	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	7.49	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:47:10
Ambit temp (test rack) [°C] humidity [rel%]	22.9 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5200 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.16	dBm	INFO
Ref. frequency	---	---	5204.000	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.08	MHz	INFO
T1 26dB	---	---	5190.0400	MHz	INFO
T2 26dB	---	---	5210.1200	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.16 12.93 20
Start [MHz] Stop [MHz]	5180.000 5220.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	7.6	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	7.6	dBm	PASS
LIMIT: 11 dBm + 10 log 20.08					
Max output power DC corrected cond	---	24.03	7.6	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-3.66	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-3.66	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:46:42
Ambit temp (test rack) [°C] humidity [rel%]	22.9 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5180
Frequency mid to test	True Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5200 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.54	dBm	INFO
Ref. frequency	---	---	5198.800	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.54 12.93 20
Start [MHz] Stop [MHz]	5175.000 5225.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



Peak output power

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	10.89	dBm	INFO
Peak Power	---	---	12.274392	mW	INFO
Frequency at Peak	---	---	5196.603	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 11:45:25
Ambit temp (test rack) [°C] humidity [rel%]	22.9 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 11:45:28
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5200 , Information: U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 26dB (UNII-3 20dB) ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:44:45
Ambit temp (test rack) [°C] humidity [rel%]	22.9 46
System version	6.0.7.5
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5180 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	3.56	dBm	INFO
Ref. frequency	---	---	5187.390	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.56 12.57 15
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.583	MHz	INFO
T1 99%	5150.000000	---	5171.7582	MHz	PASS
T2 99%	---	5250.000000	5188.3417	MHz	PASS



BW 26dB



BW within band 26dB

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.3	MHz	INFO
T1 26dB	5150.000000	---	5170.0000	MHz	PASS
T2 26dB	---	5250.000000	5190.3000	MHz	PASS

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:43:06
Ambit temp (test rack) [°C] humidity [rel%]	22.9 46
System version	6.0.7.5
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	4.06	dBm	INFO
Ref. frequency	---	---	5184.000	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	16.623	MHz	INFO
T1 99%	---	---	5171.7283	MHz	INFO
T2 99%	---	---	5188.3516	MHz	INFO


Maximum Output Power

Antenna gain

Considered antenna gain [dBi]: 6.78 @ 5180 MHz

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	16.06 12.57 20
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Vehicular use: No					
Max output power cond	---	---	6.7	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
Max output power DC corrected cond	---	---	6.7	dBm	INFO
LIMIT absolute eirp					
Max output power DC corrected eirp	---	23	13.48	dBm	PASS
LIMIT: 10 dBm + 10 log 16.623					

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power DC corrected eirp	---	22.21	13.48	dBm	PASS
Power spectral density eirp	---		2.32	dBm/1MHz	INFO
Power spectral density DC corrected eirp	---	10	2.32	dBm/1MHz	PASS
LIMIT absolute cond (RSS-247 §6.2.1)					
Max output power DC corrected cond	---	24	6.7	dBm	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:41:24
Ambit temp (test rack) [°C] humidity [rel%]	22.9 45
System version	6.0.7.5
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001

Test at TX 5180 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	3.15	dBm	INFO
Ref. frequency	---	---	5183.200	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	20.12	MHz	INFO
T1 26dB	---	---	5170.0000	MHz	INFO
T2 26dB	---	---	5190.1200	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.15 12.57 20
Start [MHz] Stop [MHz]	5160.000 5200.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	6.82	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	24	6.82	dBm	PASS
LIMIT: 11 dBm + 10 log 20.12					
Max output power DC corrected cond	---	24.04	6.82	dBm	na

Power spectral density

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-4.45	dBm/1MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	11	-4.45	dBm/1MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx a mode U-NII-1

References

TC start	28.05.2026 11:40:54
Ambit temp (test rack) [°C] humidity [rel%]	22.9 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx a mode U-NII-1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

EUT Common Settings WLAN5Gx

Number of antenna ports	2
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx a mode
EUT port	EUT1
Temperature	nom
Voltage	nom
Frequency low to test	True Freq [MHz] 5180
Frequency mid to test	False Freq [MHz] 5200
Frequency high to test	False Freq [MHz] 5240
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001


Test at TX 5180 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	3.62	dBm	INFO
Ref. frequency	---	---	5184.200	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	15.62 12.57 20
Start [MHz] Stop [MHz]	5155.000 5205.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	9.86	dBm	INFO
Peak Power	---	---	9.682779	mW	INFO
Frequency at Peak	---	---	5177.303	MHz	INFO

Verdict

PASS

NA # Message with SA scan ~

References

TC start	28.05.2026 11:39:57
Ambit temp (test rack) [°C] humidity [rel%]	22.9 45
System version	6.0.7.5
Standard Version	NA NI
Method	
Description	Message with SA Scan a_mode_U_NII_1
Information	U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Full path type	EUT_SA_GEN_SIG
Full path name	EUT1.MP.SIG1/EUT1.SA/EUT1.GEN1/EUT1.GEN2/
Switch bits	00010001:00010001:00000000:00000001
Message start	28.05.2026 11:40:00
Message	set WLAN5Gx to a_mode_U_NII_1, Frequency [MHz] 5180 , Information: U-NII-1_OFDM_a-mode_20MHz_ANT1_PS10 avg

Verdict

INFO

FCC 15.407, ISED RSS247 # Emission mask (eirp) ~ WLAN5Gx ac-VHT20 mode U-NII-3

References

TC start	21.05.2026 07:14:00
Ambit temp (test rack) [°C] humidity [rel%]	21.9 47
System version	6.0.7.2
Standard Version	FCC 15.407, ISED RSS247 NI
Method	NI
Description	FCC 15.407 Emission mask - WLAN5Gx ac-VHT20 mode U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	1
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx ac-VHT20 mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5745
Frequency mid to test	False Freq [MHz] 5785
Frequency high to test	True Freq [MHz] 5825
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5825 MHz

Number of antenna ports: 1

reduction of limit due to number of antenna ports [dB]: 0

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	8.08	dBm	INFO
Ref. frequency	---	---	5816.810	MHz	INFO

Antenna gain

Considered antenna gain [dBi]:	6.09 / max found in range 5625 to 5950 MHz
--------------------------------	--

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	11.08 12.56 15
Start [MHz] Stop [MHz]	5625.000 5950.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE



Emission Mask (e.i.r.p)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
cetecom advanced GmbH Untertürkheimer Str. 6-10, 66117 Saarbrücken			Document No. 1-1335-25-01-05_TR1-A201-R01 Release 1 - Page 1448 of 1467		

Verdict

PASS

FCC 15.407, ISED RSS247 # Minimum emission bandwidth ~ WLAN5Gx ac-VHT20 mode U-NII-3

References

TC start	21.05.2026 07:13:22
Ambit temp (test rack) [°C] humidity [rel%]	22.0 47
System version	6.0.7.2
Standard Version	FCC 15.407, ISED RSS247 NI
Method	KDB789033 D02, C.2.
Description	FCC 15.407 Min Emission Bandwidth - WLAN5Gx ac-VHT20 mode U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	1
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx ac-VHT20 mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5745
Frequency mid to test	False Freq [MHz] 5785
Frequency high to test	True Freq [MHz] 5825
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5825 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	8.45	dBm	INFO
Ref. frequency	---	---	5819.810	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.45 12.56 25
Start [MHz] Stop [MHz]	5800.000 5850.000
RBW [MHz] VBW [MHz]	0.100000 0.300000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	2 1500 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth (6dB)	0.500	---	19.15	MHz	PASS

Verdict

PASS

FCC 15.407, ISED RSS247 # Bandwidths 99PCT and 20dB ~ WLAN5Gx ac-VHT20 mode U-NII-3

References

TC start	21.05.2026 07:12:42
Ambit temp (test rack) [°C] humidity [rel%]	21.9 47
System version	6.0.7.2
Standard Version	FCC 15.407, ISED RSS247 NI
Method	26dB Bandwidth KDB789033 D02, C.1 / ISED RSS-GEN
Description	FCC 15.407 Bandwidths - WLAN5Gx ac-VHT20 mode U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	1
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx ac-VHT20 mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5745
Frequency mid to test	False Freq [MHz] 5785
Frequency high to test	True Freq [MHz] 5825
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5825 MHz


RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	9.64	dBm	INFO
Ref. frequency	---	---	5829.600	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	17.64 12.56 25
Start [MHz] Stop [MHz]	5800.000 5850.000
RBW [MHz] VBW [MHz]	0.300000 1.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	1 2500 1001 SWE







BW within band 99PCT

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	19.181	MHz	INFO
T1 99%	5725.000000	---	5815.4595	MHz	PASS
T2 99%	---	5850.000000	5834.6404	MHz	PASS since U-NII-4 is supported



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 20dB	---	---	20.65	MHz	INFO
T1 20dB	5725.000000	---	5814.7500	MHz	PASS

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
T2 20dB	--	5850.000000	5835.4000	MHz	PASS since U-NII-4 is supported

Verdict

PASS

ISED RSS247 # Max output power and psd ~ WLAN5Gx ac-VHT20 mode U-NII-3

References

TC start	21.05.2026 07:10:05
Ambit temp (test rack) [°C] humidity [rel%]	21.9 47
System version	6.0.7.2
Standard Version	ISED RSS247 NI
Method	
Description	ISED Max Output Power & PSD - WLAN5Gx ac-VHT20 mode U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	1
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx ac-VHT20 mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5745
Frequency mid to test	False Freq [MHz] 5785
Frequency high to test	True Freq [MHz] 5825
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5825 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.62	dBm	INFO
Ref. frequency	---	---	5833.790	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 99%	---	---	19.101	MHz	INFO
T1 99%	---	---	5815.4895	MHz	INFO
T2 99%	---	---	5834.5904	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.62 12.56 25
Start [MHz] Stop [MHz]	5805.000 5845.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE




Max OP and PSD (without antenna gain)

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Max output power cond	---	---	10.6	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute cond					
Max output power DC corrected cond	---	30	10.6	dBm	PASS

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.62 12.56 25
Start [MHz] Stop [MHz]	5805.000 5845.000
RBW [MHz] VBW [MHz]	0.500000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



PSD UNII-3

RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Power spectral density cond	---		-4	dBm/0.5MHz	INFO
Power spectral density DC corrected cond	---	30	-4	dBm/0.5MHz	PASS

Verdict

PASS

FCC 15.407 # Max output power and psd ~ WLAN5Gx ac-VHT20 mode U-NII-3

References

TC start	21.05.2026 07:07:27
Ambit temp (test rack) [°C] humidity [rel%]	21.9 47
System version	6.0.7.2
Standard Version	FCC 15.407 NI
Method	KDB789033 D02, F., E.2.e.
Description	FCC 15.407 Max Output Power & PSD - WLAN5Gx ac-VHT20 mode U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	1
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx ac-VHT20 mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5745
Frequency mid to test	False Freq [MHz] 5785
Frequency high to test	True Freq [MHz] 5825
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001

Test at TX 5825 MHz

RESULT: Reference power cond.


DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	7.68	dBm	INFO
Ref. frequency	---	---	5827.400	MHz	INFO

Evaluation max. duty cycle

Duty cycle evaluation

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Duty cycle min	---	---	0	dB	DC > 98% defined

Evaluation bandwidth




RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Bandwidth 26dB	---	---	22.08	MHz	INFO
T1 26dB	---	---	5814.1200	MHz	INFO
T2 26dB	---	---	5836.2000	MHz	INFO

Maximum Output Power

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.68 12.56 25
Start [MHz] Stop [MHz]	5805.000 5845.000
RBW [MHz] VBW [MHz]	1.000000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



Max OP and PSD

RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Max output power cond	---	---	10.71	dBm	INFO
Duty cycle correction	---	---	0	dB	INFO
LIMIT absolute:					
Max output power DC corrected cond	---	30	10.71	dBm	PASS
LIMIT: 11 dBm + 10 log 22.08					
Max output power DC corrected cond	---	24.44	10.71	dBm	na


Power Spectral Density U-NII-3

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	19.68 12.56 25
--	--------------------

READ SA SETTINGS:

Start [MHz] Stop [MHz]	5805.000 5845.000
RBW [MHz] VBW [MHz]	0.500000 3.000000
Detector TraceMode	RMS MAXH
Sweep: time [ms] count points per Section type	59600 1 161 SWE



RESULT

CONDUCTED LIMITS FOR MAX ANTENNA GAIN OF 6 D BI

Description	Lower Limit	Upper Limit	Measured	Unit	Verdict
Power spectral density cond	---	---	-4	dBm/0.5MHz	INFO
Duty cycle correction	---	---	0	dB	INFO
Power spectral density DC corrected cond	---	30	-4	dBm/0.5MHz	PASS

Verdict

PASS

NA # Peak output power 3MHz/3MHz ~ WLAN5Gx ac-VHT20 mode U-NII-3

References

TC start	21.05.2026 07:06:59
Ambit temp (test rack) [°C] humidity [rel%]	21.9 47
System version	6.0.7.2
Standard Version	NA NI
Method	
Description	Peak OP 3MHz/3MHz - WLAN5Gx ac-VHT20 mode U-NII-3
Information	

EUT Common Settings WLAN5Gx

Number of antenna ports	1
User Interaction	No
Device class U-NII-1 (FCC)	Client
Limit W52 japan	Standard
TPC supported	No
Vehicle use (ISED)	No

Equipment

Signal analyzer,Rohde&Schwarz,FSV-40,1307.9002K40/101042,3.71
Switch matrix,cetecom advanced GmbH,USM,B002,1.0.0

Test Parameter

Technology to test	WLAN5Gx ac-VHT20 mode
EUT port	EUT2
Temperature	nom
Voltage	nom
Frequency low to test	False Freq [MHz] 5745
Frequency mid to test	False Freq [MHz] 5785
Frequency high to test	True Freq [MHz] 5825
Auto control enabled power supply Climatic Box	No No
Additional path loss [dB]	0
Full path type	EUT_SA_GEN_SIG
Full path name	EUT2.MP.SIG1/EUT2.SA/EUT2.GEN1/EUT2.GEN2/
Switch bits	00100010:00010001:00000000:00000001


Test at TX 5825 MHz

RESULT: Reference power cond.

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Ref. power 1MHz/1MHz cond.	---	---	8.88	dBm	INFO
Ref. frequency	---	---	5832.390	MHz	INFO

READ SA SETTINGS:

RefLevel [dBm] RefLevelOffset [dB] InpAtt [dB]	20.88 12.56 25
Start [MHz] Stop [MHz]	5800.000 5850.000
RBW [MHz] VBW [MHz]	3.000000 3.000000
Detector TraceMode	POS MAXH
Sweep: time [ms] count points per Section type	300 20 1001 SWE



RESULT

DESCRIPTION	LOWER LIMIT	UPPER LIMIT	MEASURED	UNIT	VERDICT
Peak Power	---	---	14.92	dBm	INFO
Peak Power	---	---	31.045596	mW	INFO
Frequency at Peak	---	---	5830.544	MHz	INFO

Verdict

PASS

- END OF DOCUMENT -