



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan
District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM151200805101

Page: 1 of 19

FCC Test Report

Application No.: SZEM1512008051PS
Applicant: Parrot Drones SAS
Manufacturer: Fujikon Industrial Company Limited
Factory: Charter Media (Dongguan) Company Limited
Equipment Under Test (EUT):
EUT Name: Wireless Charger
Model No.: WCH01
Trade Mark: Parrot
FCC ID: 2AG6IWCH01
Standards: 47 CFR PART 18: 2015
Date of Receipt: 2015-12-29
Date of Test: 2016-01-04 to 2016-01-12
Date of Issue: 2016-01-27

Test Result :	PASS*
----------------------	--------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101

Page: 2 of 19

2 Test Summary

Test	Test Requirement	Test Method	Class / Severity	Result
Conducted Emission (150 kHz to 30 MHz)	47 CFR PART 18: 2015	FCC OST/ MP-5:1986	18.307(a)	Pass
Radiated Emission (9 kHz to 30MHz)	47 CFR PART 18: 2015	FCC OST/ MP-5:1986	18.305(b)	Pass



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101
Page: 3 of 19

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	2
3 CONTENTS	3
4 GENERAL INFORMATION	4
4.1 CLIENT INFORMATION	4
4.2 GENERAL DESCRIPTION OF EUT	4
4.3 DESCRIPTION OF SUPPORT UNITS	4
4.4 TEST LOCATION	5
4.5 TEST FACILITY	5
4.6 DEVIATION FROM STANDARDS	5
4.7 ABNORMALITIES FROM STANDARD CONDITIONS	5
5 EQUIPMENT LIST	6
6 TEST RESULTS	8
6.1 CONDUCTED EMISSIONS	8
6.2 RADIATED EMISSIONS	12
7 PHOTOGRAPHS	16
7.1 CONDUCTED EMISSION TEST SETUP	16
7.2 RADIATED EMISSION TEST SETUP	16
7.3 EUT CONSTRUCTIONAL DETAILS	17-19



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101
Page: 4 of 19

4 General Information

4.1 Client Information

Applicant:	Parrot Drones SAS
Address of Applicant:	174 Quai de Jemmapes Pairs 75010 France
Manufacturer:	Fujikon Industrial Company Limited
Address of Manufacturer:	16/F., Tower 1, Grand Central Plaza, 138 Shatin Rural Committee Road, New Territories, Hong Kong
Factory:	Charter Media (Dongguan) Company Limited
Address of Factory:	Daibandi Industrial Zone, Daning District, Humen Town, Dongguan City, Guangdong Province, P.R.C.

4.2 General Description of EUT

Product Name:	Wireless Charger
Model No.:	WCH01
Trade Mark:	Parrot
Sample Type:	Wireless Charger
Operation Frequency:	105kHz-205kHz
Power Supply:	Input voltage: DC5V 1A Output voltage: DC5V 1A
Test Voltage:	AC120V 60Hz
EUT Cable:	USB cable: 130cm,unshielded

4.3 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.
Adapter	Apple	A1357 W010A051
Earphone	Supplied by client	N/A



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM151200805101

Page: 5 of 19

4.4 Test Location

Only the Radiate emission(9kHz-30MHz) was test in SGS GZ, the other tests were performed at:
SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,
No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

The 3m Semi-anechoic chambers and the 10m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2, 4620C-3.

4.6 Deviation from Standards

None.

4.7 Abnormalities from Standard Conditions

None.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101
Page: 6 of 19

5 Equipment List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2016-05-13
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2016-10-09
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2016-05-13
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	EMC0120	2016-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	EMC0121	2016-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	EMC0122	2016-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2016-05-13
8	Coaxial Cable	SGS	N/A	SEL0025	2016-05-13



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101

Page: 7 of 19

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	10m Semi-Anechoic Chamber	SAEMC	FSAC1018	SEL0303	2016-08-01
2	EMI Test Receiver (9k-3GHz)	Rohde & Schwarz	ESCI	SEL0175	2016-05-13
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	Coaxial cable	SGS	N/A	SEL0288	2016-05-13
5	Coaxial cable	SGS	N/A	SEL0275	2016-05-13
6	Coaxial cable	SGS	N/A	SEL0274	2016-05-13
7	BiConiLog Antenna (30M-1GHz)	Schwarzbeck	VULB9160	SEL0309	2018-10-17
8	Pre-amplifier	Sonoma Instrument Co	310N	SEL0298	2016-05-13
9	Loop Antenna	ETS-LINDGREN	6502	SEL0802	2016-08-14


General used equipment					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Humidity/ Temperature Indicator	Shang Hai Meteorological Industry Factory	ZJ1-2B	SEL0101	2016-10-12
2	Humidity/ Temperature Indicator	Shang Hai Meteorological Industry Factory	ZJ1-2B	SEL0102	2016-10-12
3	Humidity/ Temperature Indicator	Shang Hai Meteorological Industry Factory	ZJ1-2B	SEL0103	2016-10-12
4	Barometer	Chang Chun Meteorological Industry Factory	DYM3	SEL0088	2016-05-13



6 Test Results

6.1 Conducted Emissions

Test Requirement:	47 CFR PART 18		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed on conducted measurement.		

Test Setup:	
Test Mode:	Wireless charge mode. Keep EUT charging with full load and half load to find the worst case. The compliance test performed at full load since no worst case was found.
Instruments Used:	Refer to section 5 for details
Test Results:	Pass

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.


Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101
Page: 10 of 19

Live Line:



Site : Shielding Room
Condition: CE Line
Job No. : 8051PS
Test Mode: a


	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.23	0.06	9.84	28.94	38.84	52.35	-13.51	Peak
2	0.88	0.03	9.89	28.00	37.92	46.00	-8.08	Peak
3	1.75	0.04	9.94	28.32	38.30	46.00	-7.70	Peak
4	3.64	0.09	10.06	29.39	39.54	46.00	-6.46	Peak
5	8.46	0.38	10.15	27.58	38.11	50.00	-11.89	Peak
6	17.38	1.23	10.23	27.05	38.51	50.00	-11.49	Peak



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101
Page: 11 of 19

Neutral Line:



Site : Shielding Room
Condition: CE Neutral
Job No. : 8051PS
Test Mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.36	0.05	9.87	28.69	38.61	48.83	-10.22	Peak
2	0.87	0.03	10.00	28.00	38.03	46.00	-7.97	Peak
3	1.44	0.04	10.07	25.66	35.77	46.00	-10.23	Peak
4	3.74	0.09	10.13	27.05	37.27	46.00	-8.73	Peak
5	7.25	0.26	10.13	30.41	40.80	50.00	-9.20	Peak
6	17.29	1.22	10.30	29.35	40.87	50.00	-9.13	Peak



6.2 Radiated Emissions

Test Requirement:	47 CFR PART 18			
Test Site:	Measurement Distance: 10m (Semi-Anechoic Chamber)			
Receiver Setup:	Frequency	Detector	RBW	VBW
	9kHz~150kHz	Quasi-peak	200Hz	≥RBW
	150kHz~30MHz	Quasi-peak	9kHz	≥RBW
	30MHz~1GHz	Quasi-peak	100kHz	≥RBW
Limit:	Frequency	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009-30MHz	53.0	Quasi-peak	10
	30MHz-88MHz	40.0	Quasi-peak	3
	88MHz-216MHz	43.5	Quasi-peak	3
	216MHz-1000MHz	46.0	Quasi-peak	3
	Remark:According to the article 18.305(b), The operating frequency is non-ISM frequency;the RF Power generated by equipment is below 500(watts); According to the clause 18.305(c), the EUT belongs to Consumer equipment.			
Test Setup:				




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz

Test Procedure:	a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber(30MHz-1000MHz) and 10 meter semi-anechoic chamber(9kHz-30MHz). The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters(30MHz-1000MHz) and 10 meter(9kHz-30MHz) away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. Above 30MHz:The Analyzer/Receiver scanned from 30MHz to 1000MHz.The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. Below 30MHz: The Analyzer/Receiver scanned from 9kHz to 30MHz.The antenna height is 2 meters above the ground to determine the maximum value of the field strength.
-----------------	--



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101

Page: 13 of 19


	e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 2 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. h. Repeat above procedures until all frequencies measured was complete. i. Measurement Requirement: According to the clause 18.305(c)notes 2. At frequencies at or above 30MHz: $\text{Limit}_{3m}(\text{dBuV}) = \text{Limit}_{xm}(\text{dBuV}) + 20\log(xm/3m)$ At frequencies below 30MHz: $\text{Limit}_{10m}(\text{dBuV}) = \text{Limit}_{xm}(\text{dBuV}) + 20\log(xm/3m)$ Remark: x replace the number 10,30,300.
Test Mode:	Wireless charge mode. Keep EUT charging with full load and half load to find the worst cass. The compliance test performed at full load since no worst case was found.
Instruments Used:	Refer to section 5 for details
Test Results:	Pass



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101
Page: 14 of 19

0.009MHz-30MHz



Condition: 10m

Job No. : 8051PS


Test Mode: Wireless charge mode

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	0.01	0.29	21.63	0.00	20.56	42.48	53.06	-10.58
2	0.02	0.24	18.43	0.00	20.49	39.16	53.06	-13.90
3	0.05	0.12	12.71	0.00	17.50	30.33	53.06	-22.73
4	0.07	0.09	12.87	0.00	12.87	25.83	53.06	-27.23
5	0.08	0.07	12.94	0.00	12.59	25.60	53.06	-27.46
6 pp	0.14	0.06	12.85	0.00	30.52	43.43	53.06	-9.63



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Report No.: SZEM151200805101
Page: 15 of 19



Condition: 10m

Job No. : 8051PS

Test Mode: Wireless charge mode

		Cable	Ant	Preamp	Read		Limit	Over
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	0.20	0.08	12.80	0.00	32.94	45.82	53.06	-7.24
2	0.27	0.09	12.77	0.00	30.05	42.91	53.06	-10.15
3	0.57	0.13	12.53	0.00	23.35	36.01	53.06	-17.05
4	1.04	0.24	12.78	0.00	17.26	30.28	53.06	-22.78
5	2.38	0.36	12.37	0.00	13.55	26.28	53.06	-26.78
6	3.78	0.40	12.04	0.00	12.59	25.03	53.06	-28.03

Remark:

1:The loop antenna rotated about both Vertical and Horizontal to find the maximum emission,So only the worst position(Horizontal) was report.

2:According to the clause 2.3 of MP-5:1986, the highest frequency is 205kHz, So the Range of frequency measurements is 9kHz to 30MHz.


7 Photographs

Test Model No.: WCH01

7.1 Conducted Emission Test Setup



7.2 Radiated Emission Test Setup



7.3 EUT Constructional Details



