

TEST REPORT

Applicant: Fujian LANDI Commercial Equipment Co.,Ltd.

FCC: Building 17, Section A, Software Park, No. 89 Software Road,
Gulou District, Fuzhou Municipality, Fujian Province, China

Address: IC: Building 17, Section A, Software Park, No. 89 Software Road,
Gulou District, Fuzhou Municipality, Fujian Province, P.R. 350003
China

Product Name: POS Terminal

FCC ID: 2AG6N-C20SE

IC: 23725-C20SE

HVIN: C20SES1, C20SED1

47 CFR Part 15, Subpart C(15.247)

RSS-247 Issue 3, August 2023

Standard(s): RSS-Gen, Issue 5, February 2021 Amendment 2

ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

Report Number: XMDN240206-08078E-RF-00BA1

Report Date: 2025/4/25

The above device has been tested and found compliant with the requirement of the relative standards by Bay Area Compliance Laboratories Corp. (Dongguan).

Pedro Yun

Reviewed By: Pedro Yun

Title: Project Engineer

Gavin Xu

Approved By: Gavin Xu

Title: RF Supervisor

Bay Area Compliance Laboratories Corp. (Dongguan)
No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China

Tel: +86-769-86858888

Fax: +86-769-86858891

www.baclcorp.com.cn

Note: The information marked ▲ is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report cannot be reproduced except in full, without prior written approval of the Company. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0. This report may contain data that are not covered by the accreditation scope and shall be marked with ★. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government. Each test item follows the test standard(s) without deviation.

CONTENTS

DOCUMENT REVISION HISTORY	4
1. GENERAL INFORMATION	5
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
1.2 ACCESSORY INFORMATION.....	5
1.3 ANTENNA INFORMATION DETAIL▲.....	6
1.4 EQUIPMENT MODIFICATIONS	6
2. SUMMARY OF TEST RESULTS	7
3. DESCRIPTION OF TEST CONFIGURATION	8
3.1 OPERATION FREQUENCY DETAIL.....	8
3.2 EUT OPERATION CONDITION.....	8
3.3 SUPPORT EQUIPMENT LIST AND DETAILS	9
3.4 SUPPORT CABLE LIST AND DETAILS	9
3.5 BLOCK DIAGRAM OF TEST SETUP	10
3.6 TEST FACILITY.....	12
3.7 MEASUREMENT UNCERTAINTY	12
4. REQUIREMENTS AND TEST PROCEDURES	13
4.1 AC LINE CONDUCTED EMISSIONS.....	13
4.1.1 Applicable Standard.....	13
4.1.2 EUT Setup.....	15
4.1.3 EMI Test Receiver Setup	15
4.1.4 Test Procedure	16
4.1.5 Corrected Amplitude & Margin Calculation.....	16
4.1.6 Test Result	16
4.2 RADIATION SPURIOUS EMISSIONS.....	17
4.2.1 Applicable Standard.....	17
4.2.2 EUT Setup.....	17
4.2.3 EMI Test Receiver & Spectrum Analyzer Setup	19
4.2.4 Test Procedure	19
4.2.5 Corrected Amplitude & Margin Calculation.....	20
4.2.6 Test Result	20
4.3 MAXIMUM CONDUCTED OUTPUT POWER.....	21
4.3.1 Applicable Standard.....	21
4.3.2 EUT Setup.....	21
4.3.3 Test Procedure	21
4.3.4 Test Result	21
4.4 ANTENNA REQUIREMENT.....	22
4.4.1 Applicable Standard.....	22
4.4.2 Judgment.....	22
5. Test DATA AND RESULTS.....	23
5.1 AC LINE CONDUCTED EMISSIONS.....	23
5.2 RADIATION SPURIOUS EMISSIONS	28

5.3 SPOT CHECK WITH MAXIMUM CONDUCTED OUTPUT POWER.....	63
EXHIBIT A - EUT PHOTOGRAPHS.....	64
EXHIBIT B - TEST SETUP PHOTOGRAPHS	65
EXHIBIT C - RF EXPOSURE EVALUATION	66
MAXIMUM PERMISSIBLE EXPOSURE (MPE)	66
Applicable Standard.....	66
Calculation formula:	66
Calculated Data:	66

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	XMDN240206-08078E-RF-00B	Original Report	2024/4/11
2.0	XMDN240206-08078E-RF-00BA1	Class II Permissive Change Report	2025/4/25

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	POS Terminal
EUT Model:	C20SE
Operation Frequency:	2412-2462MHz (802.11b/g/n ht20/802.11ax he20) 2422-2452MHz(802.11n ht40/802.11ax he40)
Maximum Peak Output Power (Conducted):	23.84dBm
Modulation Type:	802.11b:DSSS-DBPSK, DQPSK, CCK 802.11g/n: OFDM-BPSK, QPSK, 16QAM, 64QAM 802.11ax: OFDMA-BPSK, QPSK, 16QAM, 64QAM,256QAM,1024QAM
Rated Input Voltage:	DC 19Vdc from adapter
Serial Number:	RF Conducted Test: 2VU3-8(Configuration1#) For Radiated spurious emission below 1GHz test and AC line conducted Emission tests: 2VU3-3(Configuration1#) 2VU3-5(Configuration2#) For Radiated spurious emission above 1GHz test: 2VU3-3(Configuration1#)
EUT Received Date:	2024/12/11
EUT Received Status:	Good
Note: test was performed with Configuration 1#~2# except Radiated spurious emission above 1GHz and power spot check only test with configuration 1#.	

Configuration Information:

Configuration No.	HVIN	10.1 inch Screen
1#	C20SED1	√
2#	C20SES1	×

1.2 Accessory Information

Adapter Information:

Adapter No.	Manufacturer	Model	Parameters
1#	Lite-On Technology(Europe)BV	PA-1400-76	Input:100-240Vac, 50/60Hz ,1.2A Output: 19Vdc, 2.1A
2#	Lite-On Electronics (Europe) Ltd.	PA-1650-90	Input:100-240Vac, 50/60Hz ,1.6A Output: 19Vdc, 3.42A
3#(New)	Lite-On Technology Corp.	PA-1650-57	Input:100-240Vac, 50/60Hz ,1.6A Output: 19Vdc, 3.42A

AC Power Cable Information:

Cable No.	Manufacturer
1#	EA Cable Assemblies GmbH
2#(New)	Fund Resources Electric Industry Co. Ltd. Shanghang

1.3 Antenna Information Detail ▲

Antenna Manufacturer	Antenna Type	input impedance (Ohm)	Frequency Range	Antenna Gain
Shanghai Jersoncom Communication Engineering Co., Ltd	FPC	50	2.4~2.5GHz	4.55 dBi
The design of compliance with §15.203:				
☒ Unit uses a permanently attached antenna.				
☐ Unit uses a unique coupling to the intentional radiator.				
☐ Unit was professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.				

1.4 Equipment Modifications

No modifications are made to the EUT during all test items.

2. SUMMARY OF TEST RESULTS

Standard(s) Section	Test Items	Result
§15.207(a) RSS-Gen Clause 8.8	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d) RSS-Gen Clause 8.10	Spurious Emissions	Compliant
§15.247 (a)(2) RSS-247 Clause 5.2 a)	Minimum 6 dB Bandwidth	Compliant*
RSS-Gen Clause 6.7	99% Occupied Bandwidth	Compliant*
§15.247(b)(3) RSS-247 Clause 5.4 d)	Maximum Conducted Output Power	Reporting
§15.247(d) RSS-247 Clause 5.5	100 kHz Bandwidth Of Frequency Band Edge	Compliant*
§15.247(e) RSS-247 Clause 5.2 b)	Power Spectral Density	Compliant*
FCC §15.203 RSS-Gen Clause 6.8	Antenna Requirement	Compliant
Purpose: This is Class II permissive change application based on the original device, model: C20SE, FCC ID: 2AG6N-C20SE, IC: 23725-C20SE, HVIN: C20SES, C20SED. Differences between the previous device and the current one are stated and guaranteed by the manufacturer, as following: 1. Add one Adapter (model: PA-1650-57) for single and dual screens. 2. Change the WIFI/Bluetooth antenna. 3. Change MIC position. 4. Change the layout and routing of S&J board. The S board is only available with dual screens, and the J board is available with single and dual screens 5. Change to dual 5W speakers. 6. Change the version to V110 and the USB signal of C board. 7. Change the HVIN (HVIN:C20SED1,HVIN:C20SES1). 8. Change the internal circuit of the 15.6 inch LCD. Per Spot check with RF output power, the RF parameters are identical with the original device. Therefore, AC line conducted emissions and Radiated Spurious Emissions was tested based on the change. The other items please refer to the original report, report No.: XMDN240206-08078E-RF-00B, issued by Bay Area Compliance Laboratories Corp.(Dongguan). Note 1: For AC line conducted emissions and Radiated Spurious Emissions 9kHz~ 1GHz and 18-25GHz, the maximum output power mode and channel was tested. Note 2: Per BLE report, Powered by Adapter 3# was the worst, so only performed it.		

3. DESCRIPTION OF TEST CONFIGURATION

3.1 Operation Frequency Detail

For 802.11b/g/n ht20/ax he20:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11n ht40/ax he40:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	7	2442
4	2427	8	2447
5	2432	9	2452
6	2437	/	/

Note: The above frequencies in bold were performed the test.

3.2 EUT Operation Condition

The EUT was configured for testing in Engineering Mode, which was provided by the manufacturer. The EUT configuration as below:

EUT Exercise Software:	cmd			
The software was provided by manufacturer. The maximum power was configured as below, that was provided by the manufacturer▲:				
Test Modes	Data Rate	Power Level Setting		
		Lowest Channel	Middle Channel	Highest Channel
802.11b	1Mbps	12	12	12
802.11g	6Mbps	15	15	15
802.11n ht20	MCS0	15	15	15
802.11n ht40	MCS0	15	15	15
802.11ax he20	MCS0	15	15	15
802.11ax he40	MCS0	15	15	15
The above are the worst-case data rates, which are determined for each mode based upon investigations by measuring the peak power and PSD across all data rates, bandwidths, and modulations. For 802.11ax mode, the device not support partial RU mode.				

3.3 Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ZIONCOM	Router	MB-R210-00	EMZBWR21103004
Kingston	USB Flash Disk	32G	EMZBUD21103001
SanDisk	Micro TF Card	UHS-I-16G	9292DVDSV0XZ
Unkonwn	RS232 Load	Unknown	EZF23GF4543
LANDI	Cashbox	Unknown	EZ240214F212
PHILIPS	Keyboard	SPK6234	K234210510742
PHILIPS	Mouse	SPK7214	M214BQ210411113
Keenion	Earphone	KDM-911	EMZBEP21103003B
Lenovo	Laptop	G510	EMZBPC21103006
SANDisk	USB Flash Disk	16G	BL201111386N
Baiyius	U-Disk-32GB	BA32GB	TJX21062632GB

3.4 Support Cable List and Details


Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
DC Cable	No	No	0.8	Adapter	EUT
RJ45 Cable	No	No	10	Router	EUT
RS232 Cable	No	No	3	RS232 Load	EUT
Cashbox Cable	No	No	1.2	Cashbox	EUT
Keyboard Cable	No	No	1.5	Keyboard	EUT
Mouse Cable	No	No	1.5	Mouse	EUT
Earphone Cable	No	No	1.2	Earphone	EUT
USB Cable	Yes	No	1.2	Laptop	EUT

3.5 Block Diagram of Test Setup

AC line conducted emissions:



Spurious Emissions:



3.6 Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.12, Pulong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 829273, the FCC Designation No. : CN5044.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0022.

3.7 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	9kHz~30MHz: 3.3dB, 30MHz~200MHz: 4.55 dB, 200MHz~1GHz: 5.92 dB, 1GHz~6GHz: 4.98 dB, 6GHz~18GHz: 5.89 dB, 18GHz~26.5GHz:5.47 dB, 26.5GHz~40GHz:5.63 dB
Unwanted Emissions, conducted	±2.47 dB
Temperature	±1 °C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
AC Power Lines Conducted Emission	3.11 dB (150 kHz to 30 MHz)

4. REQUIREMENTS AND TEST PROCEDURES

4.1 AC Line Conducted Emissions

4.1.1 Applicable Standard

FCC§15.207(a).

(a) Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

(b) The limit shown in paragraph (a) of this section shall not apply to carrier current systems operating as intentional radiators on frequencies below 30 MHz. In lieu thereof, these carrier current systems shall be subject to the following standards:

(1) For carrier current system containing their fundamental emission within the frequency band 535-1705 kHz and intended to be received using a standard AM broadcast receiver: no limit on conducted emissions.

(2) For all other carrier current systems: 1000 μ V within the frequency band 535-1705 kHz, as measured using a 50 μ H/50 ohms LISN.

(3) Carrier current systems operating below 30 MHz are also subject to the radiated emission limits in §15.205, §15.209, §15.221, §15.223, or §15.227, as appropriate.

(c) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provisions for, the use of battery chargers which permit operating while charging, AC adapters or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.

RSS-Gen Clause 8.8

Unless stated otherwise in the applicable RSS, for radio apparatus that are designed to be connected to the public utility AC power network, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the range 150 kHz to 30 MHz shall not exceed the limits in table 4, as measured using a 50 μ H / 50 Ω line impedance stabilization network. This requirement applies for the radio frequency voltage measured between each power line and the ground terminal of each AC power-line mains cable of the EUT.

For an EUT that connects to the AC power lines indirectly, through another device, the requirement for compliance with the limits in table 4 shall apply at the terminals of the AC power-line mains cable of a representative support device, while it provides power to the EUT. The lower limit applies at the boundary between the frequency ranges. The device used to power the EUT shall be representative of typical applications.

Table 4 – AC power-line conducted emissions limits

Frequency (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 ¹	56 to 46 ¹
0.5 – 5	56	46
5 – 30	60	50


Note 1: The level decreases linearly with the logarithm of the frequency.

For an EUT with a permanent or detachable antenna operating between 150 kHz and 30 MHz, the AC power-line conducted emissions must be measured using the following configurations:

(a) Perform the AC power-line conducted emissions test with the antenna connected to determine compliance with the limits of table 4 outside the transmitter's fundamental emission band.

(b) Retest with a dummy load instead of the antenna to determine compliance with the limits of table 4 within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network that simulates the antenna in the fundamental frequency band.

4.1.2 EUT Setup



The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207, RSS-Gen limits.

The spacing between the peripherals was 10 cm.

The adapter or EUT was connected to the main LISN with a 120 V/60 Hz AC power source.

4.1.3 EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

4.1.4 Test Procedure

The frequency and amplitude of the six highest ac power-line conducted emissions relative to the limit, measured over all the current-carrying conductors of the EUT power cords, and the operating frequency or frequency to which the EUT is tuned (if appropriate), should be reported, unless such emissions are more than 20 dB below the limit. AC power-line conducted emissions measurements are to be separately carried out only on each of the phase (“hot”) line(s) and (if used) on the neutral line(s), but not on the ground [protective earth] line(s). If less than six emission frequencies are within 20 dB of the limit, then the noise level of the measuring instrument at representative frequencies should be reported. The specific conductor of the power-line cord for each of the reported emissions should be identified. Measure the six highest emissions with respect to the limit on each current-carrying conductor of each power cord associated with the EUT (but not the power cords of associated or peripheral equipment that are part of the test configuration). Then, report the six highest emissions with respect to the limit from among all the measurements identifying the frequency and specific current-carrying conductor identified with the emission. The six highest emissions should be reported for each of the current-carrying conductors, or the six highest emissions may be reported over all the current-carrying conductors.

4.1.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = attenuation caused by cable loss + voltage division factor of AMN

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

4.1.6 Test Result

Please refer to section 5.1.

4.2 Radiation Spurious Emissions

4.2.1 Applicable Standard

FCC §15.247 (d);


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).



RSS-247 Clause 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required

4.2.2 EUT Setup

9kHz~30MHz:



30MHz~1GHz:**Above 1GHz:**

The radiated emissions were performed in the 3 meters distance, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247, RSS-247, RSS-Gen limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

For 9kHz-30MHz test, the lowest height of the magnetic antenna shall be 1 m above the ground and three antenna orientations (parallel, perpendicular, and ground-parallel) shall be measured.

4.2.3 EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 9 kHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

9kHz-1000MHz:

Frequency Range	Measurement	RBW	Video B/W	IF B/W	Detector
9 kHz – 150 kHz	QP/AV	300Hz	1 kHz	200 Hz	QP/AV
150 kHz – 30 MHz	QP/AV	10 kHz	30 kHz	9 kHz	QP/AV
30MHz – 1000 MHz	PK	100 kHz	300 kHz	/	PK
	QP	/	/	120kHz	QP

1GHz- 25GHz:

Pre-scan:

Measurement	Detector	RBW	Video B/W
PK	PK	1MHz	3 MHz
Ave.	PK	1MHz	5kHz

Final measurement for emission identified during the pre-scan:

Measurement	Detector	Duty cycle	RBW	Video B/W
PK	PK	Any	1MHz	3 MHz
Ave.	PK	>98%	1MHz	10 Hz
		<98%	1MHz	1/T

Note: T is minimum transmission duration

4.2.4 Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 9 kHz-1 GHz except 9-90 kHz, 110-490 kHz, employing an average detector, peak and Average detection modes for frequencies above 1 GHz.

If the maximized peak measured value is under the QP/Average limit by more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

4.2.5 Corrected Amplitude & Margin Calculation

The basic equation is as follows:

Result = Reading + Factor

Factor = Antenna Factor + Cable Loss- Amplifier Gain

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. The equation for margin calculation is as follows:

Margin = Limit – Result

For the spurious emission below 30MHz, the limit was convert from dBμA/m to dBμV/m by adding 51.5 dB.

4.2.6 Test Result

Please refer to section 5.2.

4.3 Maximum Conducted Output Power

4.3.1 Applicable Standard


FCC §15.247 (b)(3)

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

RSS-247 Clause 5.4 d

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

4.3.2 EUT Setup



A short RF cable with low cable loss connected to the EUT antenna port, which was provided by manufacturer. The insert loss of this RF cable/attenuator was offset into the setting of test equipment.

4.3.3 Test Procedure

According to ANSI C63.10-2013 Section 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

- Set the EUT in transmitting mode.
- Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
- Add a correction factor to the display.
- Set the power meter to test peak output power, record the result.

According to ANSI C63.10-2013 Section 11.9.2.3.2

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

4.3.4 Test Result

Please refer to section 5.3.

4.4 Antenna Requirement

4.4.1 Applicable Standard

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §§15.211, 15.213, 15.217, 15.219, 15.221, or §15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

RSS-Gen Clause 6.8

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device.

Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

4.4.2 Judgment

Compliant. Please refer to the Antenna Information detail in Section 1.3.

5. Test DATA AND RESULTS

5.1 AC Line Conducted Emissions

Serial Number:	2VU3-3,2VU3-5	Test Date:	2025/1/9
Test Site:	CE	Test Mode:	Transmitting
Tester:	Yukin Qiu	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	21.3	Relative Humidity: (%)	40	ATM Pressure: (kPa)	101.5
----------------------	------	------------------------------	----	------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	LISN	ENV216	101614	2024/9/5	2025/9/4
MICRO-COAX	Coaxial Cable	C-NJNJ-50	C-0200-01	2024/9/5	2025/9/4
R&S	EMI Test Receiver	ESCI	100035	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

** Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).*


Note: The maximum output power mode: 802.11n40 High channel was tested.

Configuration 1#:

Project No.: XMDN240206-08078E-RF-A1
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 2VU3-3
Tester: Yukin Qiu

Date: 2025-01-09




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.155	36.91	10.76	47.67	65.74	18.07	QP
2	0.155	26.75	10.76	37.51	55.74	18.23	Average
3	0.249	29.56	10.84	40.40	61.79	21.39	QP
4	0.249	21.49	10.84	32.33	51.79	19.46	Average
5	0.277	28.15	10.83	38.98	60.90	21.92	QP
6	0.277	19.24	10.83	30.07	50.90	20.83	Average
7	0.361	29.30	10.83	40.13	58.71	18.58	QP
8	0.361	21.49	10.83	32.32	48.71	16.39	Average
9	0.447	33.72	10.84	44.56	56.93	12.37	QP
10	0.447	23.83	10.84	34.67	46.93	12.26	Average
11	0.462	37.36	10.84	48.20	56.66	8.46	QP
12	0.462	32.37	10.84	43.21	46.66	3.45	Average

Project No.: XMDN240206-08078E-RF-A1
Port: neutral
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 2VU3-3
Tester: Yukin Qiu

Date: 2025-01-09




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.158	36.11	10.85	46.96	65.57	18.61	QP
2	0.158	26.23	10.85	37.08	55.57	18.49	Average
3	0.174	33.35	10.85	44.20	64.77	20.57	QP
4	0.174	23.71	10.85	34.56	54.77	20.21	Average
5	0.360	28.83	10.78	39.61	58.73	19.12	QP
6	0.360	20.64	10.78	31.42	48.73	17.31	Average
7	0.392	27.67	10.78	38.45	58.02	19.57	QP
8	0.392	22.59	10.78	33.37	48.02	14.65	Average
9	0.456	36.79	10.75	47.54	56.77	9.23	QP
10	0.456	28.74	10.75	39.49	46.77	7.28	Average
11	0.462	37.37	10.75	48.12	56.65	8.53	QP
12	0.462	32.56	10.75	43.31	46.65	3.34	Average

Configuration 2#:

Project No.: XMDN240206-08078E-RF-A1
Port: Line
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 2VU3-5
Tester: Yukin Qiu

Date: 2025-01-09




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB)	Result (dBUV)	Limit (dBUV)	Margin (dB)	Detector
1	0.152	38.40	10.75	49.15	65.88	16.73	QP
2	0.152	27.63	10.75	38.38	55.88	17.50	Average
3	0.155	37.31	10.76	48.07	65.75	17.68	QP
4	0.155	26.83	10.76	37.59	55.75	18.16	Average
5	0.276	28.26	10.83	39.09	60.93	21.84	QP
6	0.276	20.72	10.83	31.55	50.93	19.38	Average
7	0.403	29.64	10.84	40.48	57.79	17.31	QP
8	0.403	24.17	10.84	35.01	47.79	12.78	Average
9	0.450	35.98	10.84	46.82	56.87	10.05	QP
10	0.450	31.59	10.84	42.43	46.87	4.44	Average
11	0.467	36.05	10.84	46.89	56.57	9.68	QP
12	0.467	27.92	10.84	38.76	46.57	7.81	Average

Project No.: XMDN240206-08078E-RF-A1
Port: neutral
Test Mode: Transmitting
IF B/W 9kHz PK/AV

Serial No.: 2VU3-5
Tester: Yukin Qiu

Date: 2025-01-09



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB)	Result (dBμV)	Limit (dBμV)	Margin (dB)	Detector
1	0.153	37.92	10.85	48.77	65.84	17.07	QP
2	0.153	27.37	10.85	38.22	55.84	17.62	Average
3	0.261	28.85	10.81	39.66	61.41	21.75	QP
4	0.261	20.48	10.81	31.29	51.41	20.12	Average
5	0.374	28.29	10.77	39.06	58.41	19.35	QP
6	0.374	18.36	10.77	29.13	48.41	19.28	Average
7	0.407	30.29	10.77	41.06	57.71	16.65	QP
8	0.407	25.76	10.77	36.53	47.71	11.18	Average
9	0.457	36.22	10.75	46.97	56.75	9.78	QP
10	0.457	29.73	10.75	40.48	46.75	6.27	Average
11	0.466	36.35	10.75	47.10	56.58	9.48	QP
12	0.466	30.93	10.75	41.68	46.58	4.90	Average

5.2 Radiation Spurious Emissions

1) 9kHz - 1GHz

Serial Number:	2VU3-3,2VU3-5	Test Date:	2025/1/8
Test Site:	Chamber10m	Test Mode:	Transmitting
Tester:	Leesin Xiang	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	21.8	Relative Humidity: (%)	42	ATM Pressure: (kPa)	101.4
----------------------	------	---------------------------	----	---------------------------	-------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
EMCO	Passive Loop Antenna	6512	9706-1206	2023/10/25	2026/10/24
Sunol Sciences	Hybrid Antenna	JB3	A060611-1	2023/9/6	2026/9/5
Narda	Coaxial Attenuator	779-6dB	04269	2023/9/6	2026/9/5
Unknown	Coaxial Cable	C-NJNJ-50	C-1000-01	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0400-04	2024/7/1	2025/6/30
Unknown	Coaxial Cable	C-NJNJ-50	C-0530-01	2024/7/1	2025/6/30
Sonoma	Amplifier	310N	185914	2024/8/26	2025/8/25
R&S	EMI Test Receiver	ESCI	100224	2024/8/26	2025/8/25
Audix	Test Software	E3	191218 V9	N/A	N/A

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table and plots.

Note: The maximum output power mode: 802.11n40 High channel was tested.

9kHz~30MHz


Three antenna orientations (parallel, perpendicular, and ground-parallel) was measured, the worst orientations was below:

Configuration 1#:

Project No.: XMDN240206-08078E-RF-A1
Polarization: Parallel
Test Mode: Transmitting
RBW:300Hz VBW:1kHz

Serial No.: 2VU3-3
Tester: Leesin Xiang

Date: 2025-01-08




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.024	8.13	49.13	57.26	120.12	62.86	Peak
2	0.035	23.88	46.67	70.55	116.74	46.19	Peak
3	0.049	6.55	44.26	50.81	113.84	63.03	Peak
4	0.066	6.65	41.34	47.99	111.26	63.27	Peak
5	0.071	10.19	40.46	50.65	110.61	59.96	Peak
6	0.088	5.03	37.50	42.53	108.72	66.19	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Parallel
Test Mode: Transmitting
RBW:10kHz VBW:30kHz

Serial No.: 2VU3-3
Tester: Leeson Xiang

Date: 2025-01-08




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.576	19.72	22.71	42.43	72.36	29.93	Peak
2	0.720	19.17	21.29	40.46	70.39	29.93	Peak
3	0.909	20.15	18.39	38.54	68.32	29.78	Peak
4	1.184	26.06	15.74	41.80	65.97	24.17	Peak
5	1.236	24.84	15.51	40.35	65.60	25.25	Peak
6	1.418	21.77	14.71	36.48	64.37	27.89	Peak

Configuration 2#:

Project No.: XMDN240206-08078E-RF-A1
Polarization: Parallel
Test Mode: Transmitting
RBW:300Hz VBW:1kHz

Serial No.: 2VU3-5
Tester: Leesin Xiang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.024	7.44	49.13	56.57	120.12	63.55	Peak
2	0.035	24.17	46.67	70.84	116.74	45.90	Peak
3	0.056	4.73	43.10	47.83	112.71	64.88	Peak
4	0.071	8.89	40.46	49.35	110.61	61.26	Peak
5	0.125	4.09	34.00	38.09	105.63	67.54	Peak
6	0.139	5.14	33.23	38.37	104.73	66.36	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Parallel
Test Mode: Transmitting
RBW:10kHz VBW:30kHz

Serial No.: 2VU3-5
Tester: Leeson Xiang

Date: 2025-01-08




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	0.507	18.98	23.45	42.43	73.49	31.06	Peak
2	0.800	18.26	20.56	38.82	69.45	30.63	Peak
3	0.844	18.93	19.68	38.61	68.98	30.37	Peak
4	1.184	25.64	15.74	41.38	65.97	24.59	Peak
5	1.249	24.47	15.45	39.92	65.50	25.58	Peak
6	1.345	21.78	15.03	36.81	64.84	28.03	Peak

30MHz-1GHz

Configuration 1#:

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
RBW:100kHz VBW:300kHz

Serial No.: 2VU3-3
Tester: Leesin Xiang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	255.04	46.12	-11.27	34.85	46.00	11.15	Peak
2	282.20	42.79	-9.70	33.09	46.00	12.91	Peak
3	445.16	44.78	-5.65	39.13	46.00	6.87	Peak
4	516.94	41.88	-3.98	37.90	46.00	8.10	Peak
5	765.26	39.18	-0.08	39.10	46.00	6.90	Peak
6	825.40	34.61	0.68	35.29	46.00	10.71	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
RBW:100kHz VBW:300kHz

Serial No.: 2VU3-3
Tester: Leeson Xiang

Date: 2025-01-08




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	33.88	32.39	-6.62	25.77	40.00	14.23	Peak
2	449.04	40.87	-5.51	35.36	46.00	10.64	Peak
3	516.94	39.70	-3.98	35.72	46.00	10.28	Peak
4	588.72	36.32	-3.03	33.29	46.00	12.71	Peak
5	615.88	35.53	-2.59	32.94	46.00	13.06	Peak
6	765.26	40.61	-0.08	40.53	46.00	5.47	QP

Configuration 2#:

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
RBW:100kHz VBW:300kHz

Serial No.: 2VU3-5
Tester: Leesin Xiang




No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	152.22	40.73	-11.08	29.65	43.50	13.85	Peak
2	171.62	45.08	-11.87	33.21	43.50	10.29	Peak
3	383.08	39.49	-7.50	31.99	46.00	14.01	Peak
4	447.10	41.13	-5.57	35.56	46.00	10.44	Peak
5	520.82	43.69	-3.92	39.77	46.00	6.23	QP
6	765.26	33.50	-0.08	33.42	46.00	12.58	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
RBW:100kHz VBW:300kHz

Serial No.: 2VU3-5
Tester: Leesin Xiang

Date: 2025-01-08



No.	Frequency (MHz)	Reading (dBμV)	Factor (dB/m)	Result (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector
1	154.16	41.80	-11.09	30.71	43.50	12.79	Peak
2	181.32	43.74	-12.33	31.41	43.50	12.09	Peak
3	445.16	40.30	-5.65	34.65	46.00	11.35	Peak
4	480.08	39.38	-4.71	34.67	46.00	11.33	Peak
5	741.98	33.84	-0.46	33.38	46.00	12.62	Peak
6	765.26	34.33	-0.08	34.25	46.00	11.75	Peak

2) 1-25GHz:

Serial Number:	2VU3-3	Test Date:	2025/2/6~2025/2/8
Test Site:	Chamber B	Test Mode:	Transmitting
Tester:	Bill Yang, Leo Xiao	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	18.9-23.9	Relative Humidity: (%)	33-57	ATM Pressure: (kPa)	100.9-102
----------------------	-----------	---------------------------	-------	---------------------------	-----------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ETS-Lindgren	Horn Antenna	3115	000 527 35	2023/9/7	2026/9/6
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-02 1304	2023/2/22	2026/2/21
Xinhang Macrowave	Coaxial Cable	XH750A-N/J-SMA/J-10M	20231117004 #0001	2024/11/17	2025/11/16
Xinhang Macrowave	Coaxial Cable	XH360A-2.92/J-2.92/J-6M-A	20231208001 #0001	2024/12/9	2025/12/8
AH	Preamplifier	PAM-0118P	469	2024/4/15	2025/4/14
AH	Preamplifier	PAM-1840VH	191	2024/9/5	2025/9/4
R&S	Spectrum Analyzer	FSV40	101589	2024/9/5	2025/9/4
Audix	Test Software	E3	191218 V9	N/A	N/A
Decentest	Multiplex Switch Test Control Set & Filter Switch Unit	DT7220SCU & DT7220FCU	DC79902 & DC79905	2024/8/27	2025/8/26

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Please refer to the below plots.

1-18GHz:

802.11b, Low Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3376.00	53.39	-5.38	48.01	74.00	25.99	Peak

802.11b, Low Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3375.40	52.21	-5.38	46.83	74.00	27.17	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4824.00	59.63	-8.58	51.05	74.00	22.95	Peak
2	4824.00	59.16	-8.58	50.58	54.00	3.42	Average
3	7236.00	48.02	-3.67	44.35	74.00	29.65	Peak
4	17941.20	48.32	11.03	59.35	74.00	14.65	Peak
5	17941.20	36.44	11.03	47.47	54.00	6.53	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b low channel 2412MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4824.00	55.26	-8.58	46.68	74.00	27.32	Peak
2	7236.00	48.98	-3.67	45.31	74.00	28.69	Peak
3	17997.20	47.91	11.38	59.29	74.00	14.71	Peak
4	17997.20	36.27	11.38	47.65	54.00	6.35	Average

802.11b, Middle Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2688.40	54.45	-7.64	46.81	74.00	27.19	Peak

802.11b, Middle Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3410.20	52.03	-5.46	46.57	74.00	27.43	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4874.00	61.08	-8.50	52.58	74.00	21.42	Peak
2	4874.00	60.41	-8.50	51.91	54.00	2.09	Average
3	7311.00	49.87	-3.27	46.60	74.00	27.40	Peak
4	17999.00	47.69	11.38	59.07	74.00	14.93	Peak
5	17999.00	36.50	11.38	47.88	54.00	6.12	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4874.00	60.49	-8.50	51.99	74.00	22.01	Peak
2	4874.00	59.85	-8.50	51.35	54.00	2.65	Average
3	7311.00	48.96	-3.27	45.69	74.00	28.31	Peak
4	17955.20	48.51	11.12	59.63	74.00	14.37	Peak
5	17955.20	36.21	11.12	47.33	54.00	6.67	Average

802.11b, High Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2689.00	54.21	-7.65	46.56	74.00	27.44	Peak

802.11b, High Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3732.40	50.65	-4.39	46.26	74.00	27.74	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4924.00	59.43	-8.47	50.96	74.00	23.04	Peak
2	4924.00	59.00	-8.47	50.53	54.00	3.47	Average
3	7386.00	49.57	-2.71	46.86	74.00	27.14	Peak
4	17994.40	48.66	11.37	60.03	74.00	13.97	Peak
5	17994.40	36.33	11.37	47.70	54.00	6.30	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11b high channel 2462MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4924.00	56.33	-8.47	47.86	74.00	26.14	Peak
2	7386.00	49.20	-2.71	46.49	74.00	27.51	Peak
3	17997.20	48.96	11.38	60.34	74.00	13.66	Peak
4	17997.20	36.30	11.38	47.68	54.00	6.32	Average

802.11g, Low Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2692.60	54.76	-7.68	47.08	74.00	26.92	Peak

802.11g, Low Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	3914.20	50.08	-3.72	46.36	74.00	27.64	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4824.00	61.45	-8.58	52.87	74.00	21.13	Peak
2	4824.00	57.50	-8.58	48.92	54.00	5.08	Average
3	7236.00	63.27	-3.67	59.60	74.00	14.40	Peak
4	7236.00	54.64	-3.67	50.97	54.00	3.03	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g low channel 2412MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4824.00	63.37	-8.58	54.79	74.00	19.21	Peak
2	4824.00	58.58	-8.58	50.00	54.00	4.00	Average
3	7236.00	52.70	-3.67	49.03	74.00	24.97	Peak
4	17991.60	47.93	11.35	59.28	74.00	14.72	Peak
5	17991.60	36.34	11.35	47.69	54.00	6.31	Average

802.11g, Middle Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2689.00	54.36	-7.65	46.71	74.00	27.29	Peak

802.11g, Middle Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2575.00	56.58	-7.91	48.67	74.00	25.33	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Leo Xiao



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4874.00	63.19	-8.50	54.69	74.00	19.31	Peak
2	4874.00	59.04	-8.50	50.54	54.00	3.46	Average
3	7311.00	59.40	-3.27	56.13	74.00	17.87	Peak
4	7311.00	51.04	-3.27	47.77	54.00	6.23	Average
5	17988.40	48.11	11.30	59.41	74.00	14.59	Peak
6	17988.40	36.34	11.30	47.64	54.00	6.36	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Leo Xiao




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4874.00	60.85	-8.50	52.35	74.00	21.65	Peak
2	4874.00	56.84	-8.50	48.34	54.00	5.66	Average
3	7311.00	56.90	-3.27	53.63	74.00	20.37	Peak
4	7311.00	48.33	-3.27	45.06	54.00	8.94	Average
5	17994.40	47.55	11.37	58.92	74.00	15.08	Peak
6	17994.40	36.46	11.37	47.83	54.00	6.17	Average

802.11g, High Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g high channel 2462MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Leo Xiao

Date: 2025-02-08




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2566.00	59.37	-8.04	51.33	74.00	22.67	Peak

802.11g, High Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g high channel 2462MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Leo Xiao

Date: 2025-02-08




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2554.60	57.65	-8.12	49.53	74.00	24.47	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11g high channel 2462MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Leo Xiao

Date: 2025-02-07




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4924.00	66.65	-8.47	58.18	74.00	15.82	Peak
2	4924.00	60.06	-8.47	51.59	54.00	2.41	Average
3	7386.00	62.06	-2.71	59.35	74.00	14.65	Peak
4	7386.00	53.67	-2.71	50.96	54.00	3.04	Average
5	17999.00	48.58	11.38	59.96	74.00	14.04	Peak
6	17999.00	36.45	11.38	47.83	54.00	6.17	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11g high channel 2462MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Leo Xiao

Date: 2025-02-07






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4924.00	65.77	-8.47	57.30	74.00	16.70	Peak
2	4924.00	59.33	-8.47	50.86	54.00	3.14	Average
3	7386.00	60.91	-2.71	58.20	74.00	15.80	Peak
4	7386.00	52.60	-2.71	49.89	54.00	4.11	Average
5	17994.40	48.39	11.37	59.76	74.00	14.24	Peak
6	17994.40	36.33	11.37	47.70	54.00	6.30	Average


802. 11n20, Low Channel, Horizontal






802. 11n20, Low Channel, Vertical




802. 11n20, Middle Channel, Horizontal






802. 11n20, Middle Channel, Vertical



802. 11n20, High Channel, Horizontal




802. 11n20, High Channel, Vertical



802.11n40, Low Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 low channel 2422MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2524.00	59.52	-8.19	51.33	74.00	22.67	Peak

802.11n40, Low Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 low channel 2422MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2693.80	56.12	-7.68	48.44	74.00	25.56	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 low channel 2422MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4844.00	60.51	-8.53	51.98	74.00	22.02	Peak
2	4844.00	49.25	-8.53	40.72	54.00	13.28	Average
3	7266.00	51.34	-3.52	47.82	74.00	26.18	Peak
4	7266.00	39.26	-3.52	35.74	54.00	18.26	Average
5	17994.40	48.01	11.37	59.38	74.00	14.62	Peak
6	17994.40	36.27	11.37	47.64	54.00	6.36	Average


Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 low channel 2422MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Bill Yang






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4844.00	61.31	-8.53	52.78	74.00	21.22	Peak
2	4844.00	50.63	-8.53	42.10	54.00	11.90	Average
3	7266.00	50.45	-3.52	46.93	74.00	27.07	Peak
4	7266.00	38.78	-3.52	35.26	54.00	18.74	Average
5	17946.80	48.10	11.06	59.16	74.00	14.84	Peak
6	17946.80	36.35	11.06	47.41	54.00	6.59	Average

802.11n40, Middle Channel, Horizontal




802. 11n40, Middle Channel, Vertical



802.11n40, High Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2693.20	52.86	-7.68	45.18	74.00	28.82	Peak
2	3886.00	50.32	-3.83	46.49	74.00	27.51	Peak

802.11n40, High Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2689.00	55.95	-7.65	48.30	74.00	25.70	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4904.00	62.36	-8.46	53.90	74.00	20.10	Peak
2	4904.00	51.31	-8.46	42.85	54.00	11.15	Average
3	7356.00	49.34	-2.92	46.42	74.00	27.58	Peak
4	7356.00	37.99	-2.92	35.07	54.00	18.93	Average
5	17999.00	49.47	11.38	60.85	74.00	13.15	Peak
6	17999.00	36.51	11.38	47.89	54.00	6.11	Average


Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Bill Yang






No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4904.00	61.31	-8.46	52.85	74.00	21.15	Peak
2	4904.00	50.11	-8.46	41.65	54.00	12.35	Average
3	7356.00	48.62	-2.92	45.70	74.00	28.30	Peak
4	7356.00	37.17	-2.92	34.25	54.00	19.75	Average
5	17994.40	48.42	11.37	59.79	74.00	14.21	Peak
6	17994.40	36.25	11.37	47.62	54.00	6.38	Average


802.11ax20, Low Channel, Horizontal






802.11ax20, Low Channel, Vertical




802. 11ax20, Middle Channel, Horizontal






802. 11ax20, Middle Channel, Vertical



802.11ax20, High Channel, Horizontal




802.11ax20, High Channel, Vertical



802.11ax40, Low Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40 low channel 2422MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2592.40	53.60	-7.78	45.82	74.00	28.18	Peak

802.11ax40, Low Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40 low channel 2422MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2688.40	55.38	-7.64	47.74	74.00	26.26	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40 low channel 2422MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4844.00	63.58	-8.53	55.05	74.00	18.95	Peak
2	4844.00	51.64	-8.53	43.11	54.00	10.89	Average
3	7266.00	49.20	-3.52	45.68	74.00	28.32	Peak
4	7266.00	37.80	-3.52	34.28	54.00	19.72	Average
5	17963.60	47.81	11.18	58.99	74.00	15.01	Peak
6	17963.60	35.92	11.18	47.10	54.00	6.90	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40 low channel 2422MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4844.00	61.58	-8.53	53.05	74.00	20.95	Peak
2	4844.00	50.28	-8.53	41.75	54.00	12.25	Average
3	7266.00	48.81	-3.52	45.29	74.00	28.71	Peak
4	7266.00	37.66	-3.52	34.14	54.00	19.86	Average
5	17966.40	47.96	11.20	59.16	74.00	14.84	Peak
6	17966.40	36.35	11.20	47.55	54.00	6.45	Average

802.11ax40, Middle Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40 middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2699.80	52.35	-7.71	44.64	74.00	29.36	Peak

802.11ax40, Middle Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40 middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2698.00	55.89	-7.72	48.17	74.00	25.83	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40 middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4874.00	61.33	-8.50	52.83	74.00	21.17	Peak
2	4874.00	50.00	-8.50	41.50	54.00	12.50	Average
3	7311.00	47.99	-3.27	44.72	74.00	29.28	Peak
4	7311.00	37.13	-3.27	33.86	54.00	20.14	Average
5	17988.00	48.85	11.33	60.18	74.00	13.82	Peak
6	17988.00	36.22	11.33	47.55	54.00	6.45	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40 middle channel 2437MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4874.00	60.99	-8.50	52.49	74.00	21.51	Peak
2	4874.00	50.20	-8.50	41.70	54.00	12.30	Average
3	7311.00	49.09	-3.27	45.82	74.00	28.18	Peak
4	7311.00	37.84	-3.27	34.57	54.00	19.43	Average
5	17991.60	48.48	11.35	59.83	74.00	14.17	Peak
6	17991.60	36.51	11.35	47.86	54.00	6.14	Average

802.11ax40, High Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2619.40	56.26	-7.80	48.46	74.00	25.54	Peak

802.11ax40, High Channel, Vertical

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2695.60	55.57	-7.70	47.87	74.00	26.13	Peak

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11ax40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz


Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4904.00	61.56	-8.46	53.10	74.00	20.90	Peak
2	4904.00	50.30	-8.46	41.84	54.00	12.16	Average
3	7356.00	48.33	-2.92	45.41	74.00	28.59	Peak
4	7356.00	37.67	-2.92	34.75	54.00	19.25	Average
5	17871.20	48.75	10.57	59.32	74.00	14.68	Peak
6	17871.20	36.91	10.57	47.48	54.00	6.52	Average

Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11ax40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz Ave:RBW:1MHz,VBW:5kHz

Serial No.: 2VU3-3
Tester: Bill Yang



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	4904.00	60.60	-8.46	52.14	74.00	21.86	Peak
2	4904.00	49.64	-8.46	41.18	54.00	12.82	Average
3	7356.00	48.63	-2.92	45.71	74.00	28.29	Peak
4	7356.00	37.45	-2.92	34.53	54.00	19.47	Average
5	17972.00	47.71	11.24	58.95	74.00	15.05	Peak
6	17972.00	36.43	11.24	47.67	54.00	6.33	Average


18-25GHz:

No Emission was detected in the range 18-25GHz, test was performed on the mode and channel which with the maximum power.

802.11n40, High Channel, Horizontal

Project No.: XMDN240206-08078E-RF-A1
Polarization: Horizontal
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	24497.40	44.21	9.01	53.22	74.00	20.78	Peak





802.11n40, High Channel, Vertical





Project No.: XMDN240206-08078E-RF-A1
Polarization: Vertical
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak:RBW:1MHz,VBW:3MHz

Serial No.: 2VU3-3
Tester: Bill Yang




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	24113.80	44.01	8.98	52.99	74.00	21.01	Peak

Bandedge:**802.11b, Low Channel, Bandedge, Horizontal****802.11b, Low Channel, Bandedge, Vertical****802.11b, High Channel, Bandedge, Horizontal****802.11b, High Channel, Bandedge, Vertical**

802.11g, Low Channel, Bandedge, Horizontal**802.11g, Low Channel, Bandedge, Vertical****802.11g, High Channel, Bandedge, Horizontal****802.11g, High Channel, Bandedge, Vertical**

**802.11n20, Low Channel, Bandedge,
Horizontal**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Horizontal Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11n20 low channel 2412MHz
Peak: RBW:1MHz, VBW:30Hz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2389.81	64.83	-0.49	64.34	74.00	9.66	Peak
2	2389.81	48.12	-0.49	47.63	54.00	6.37	Average
3	2390.00	60.69	-0.49	60.20	74.00	13.80	Peak
4	2390.00	48.34	-0.49	47.85	54.00	6.15	Average

**802.11n20, Low Channel, Bandedge,
Vertical**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Vertical Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11n20 low channel 2412MHz
Peak: RBW:1MHz, VBW:30Hz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2389.95	72.83	-0.49	72.34	74.00	1.66	Peak
2	2389.95	51.74	-0.49	51.25	54.00	2.75	Average
3	2390.00	69.35	-0.49	68.86	74.00	5.14	Peak
4	2390.00	51.81	-0.49	51.32	54.00	2.68	Average

**802.11n20, High Channel, Bandedge,
Horizontal**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Horizontal Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11n20 high channel 2462MHz
Peak: RBW:1MHz, VBW:30Hz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	60.75	-0.05	60.70	74.00	13.30	Peak
2	2483.50	45.17	-0.05	45.12	54.00	8.88	Average
3	2484.33	64.58	-0.05	64.53	74.00	9.47	Peak
4	2484.33	43.60	-0.05	43.55	54.00	10.45	Average

**802.11n20, High Channel, Bandedge,
Vertical**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Vertical Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11n20 high channel 2462MHz
Peak: RBW:1MHz, VBW:30Hz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	65.58	-0.05	65.53	74.00	8.47	Peak
2	2483.50	49.65	-0.05	49.60	54.00	4.40	Average
3	2483.66	69.50	-0.05	69.45	74.00	4.55	Peak
4	2483.66	49.75	-0.05	49.70	54.00	4.30	Average
5	2487.65	66.39	-0.03	66.36	74.00	7.64	Peak
6	2487.65	44.09	-0.03	44.06	54.00	9.94	Average

**802. 11n40, Low Channel, Bandedge,
Horizontal**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Horizontal Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11n40 low channel 2422MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2388.47	62.45	-0.50	61.95	74.00	12.05	Peak
2	2388.47	44.86	-0.50	44.36	54.00	9.64	Average
3	2390.00	58.93	-0.49	58.44	74.00	15.56	Peak
4	2390.00	45.98	-0.49	45.49	54.00	8.51	Average

**802. 11n40, Low Channel, Bandedge,
Vertical**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Vertical Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11n40 low channel 2422MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2388.84	68.07	-0.50	67.57	74.00	6.43	Peak
2	2388.84	51.68	-0.50	51.18	54.00	2.82	Average
3	2390.00	67.13	-0.49	66.64	74.00	7.36	Peak
4	2390.00	52.44	-0.49	51.95	54.00	2.05	Average

**802. 11n40, High Channel, Bandedge,
Horizontal**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Horizontal Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz







No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	53.24	-0.05	53.19	74.00	20.81	Peak
2	2483.50	41.25	-0.05	41.20	54.00	12.80	Average
3	2504.63	55.28	0.06	55.34	74.00	18.66	Peak
4	2504.63	38.23	0.06	38.29	54.00	15.71	Average

**802. 11n40, High Channel, Bandedge,
Vertical**

Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Vertical Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11n40 high channel 2452MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	55.68	-0.05	55.63	74.00	18.37	Peak
2	2483.50	45.08	-0.05	45.03	54.00	8.97	Average
3	2484.17	61.58	-0.05	61.53	74.00	12.47	Peak
4	2484.17	43.27	-0.05	43.22	54.00	10.78	Average

802.11ax20, Low Channel, Bandedge, Horizontal**802.11ax20, Low Channel, Bandedge, Vertical****802.11ax20, High Channel, Bandedge, Horizontal****802.11ax20, High Channel, Bandedge, Vertical**

**802. 11ax40, Low Channel, Bandedge,
Horizontal**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Horizontal Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11ax40 low channel 2422MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2388.53	61.13	-0.50	60.63	74.00	13.37	Peak
2	2388.53	46.07	-0.50	45.57	54.00	8.43	Average
3	2390.00	56.72	-0.49	56.23	74.00	17.77	Peak
4	2390.00	46.37	-0.49	45.88	54.00	8.12	Average

**802. 11ax40, Low Channel, Bandedge,
Vertical**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Vertical Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11ax40 low channel 2422MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2386.71	65.11	-0.52	64.59	74.00	9.41	Peak
2	2386.71	48.51	-0.52	47.99	54.00	6.01	Average
3	2390.00	62.64	-0.49	62.15	74.00	11.85	Peak
4	2390.00	49.62	-0.49	49.13	54.00	4.87	Average

**802. 11ax40, High Channel, Bandedge,
Horizontal**


Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Horizontal Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11ax40 high channel 2452MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	52.18	-0.05	52.13	74.00	21.87	Peak
2	2483.50	42.56	-0.05	42.51	54.00	11.49	Average
3	2483.77	59.13	-0.05	59.08	74.00	14.92	Peak
4	2483.77	42.56	-0.05	42.51	54.00	11.49	Average

**802. 11ax40, High Channel, Bandedge,
Vertical**

Project No.: XMDN240206-08078E-RF-A1 Serial No.: 2VU3-3
Polarization: Vertical Tester: Bill Yang
Test Mode: Transmitting
Note: 802.11ax40 high channel 2452MHz
Peak: RBW:1MHz, VBW:3MHz Ave: RBW:1MHz, VBW:5kHz



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	2483.50	61.24	-0.05	61.19	74.00	12.81	Peak
2	2483.50	43.66	-0.05	43.61	54.00	10.39	Average
3	2484.17	64.17	-0.05	64.12	74.00	9.88	Peak
4	2484.17	43.17	-0.05	43.12	54.00	10.88	Average

5.3 Spot Check With Maximum Conducted Output Power

Test Information:

Serial No.:	2VU3-8	Test Date:	2025/2/8
Test Site:	RF	Test Mode:	Transmitting
Tester:	Tower Qing	Test Result:	Pass

Environmental Conditions:

Temperature: (°C):	20.1	Relative Humidity: (%)	26	ATM Pressure: (kPa)	102
-----------------------	------	------------------------------	----	------------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Coaxial Attenuator	10dB	F-08-EM512	2024/6/13	2025/6/12
Anritsu	Microwave Peak Power Sensor	MA24418A	12618	2024/8/27	2025/8/26

* Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Test Modes	Test Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)	Limit (dBm)
802.11b	2412	14.31	30
	2437	15.33	30
	2462	13.58	30
802.11g	2412	23.2	30
	2437	23.38	30
	2462	23.67	30
802.11n ht20	2412	23.22	30
	2437	23.43	30
	2462	23.37	30
802.11n ht40	2422	23.44	30
	2437	23.55	30
	2452	23.47	30
802.11ax hew20	2412	23.26	30
	2437	23.58	30
	2462	23.61	30
802.11ax hew40	2422	23.44	30
	2437	23.48	30
	2452	23.33	30
Max EIRP		28.22	36

Note: The Spot Check data were similar to the original data.

EXHIBIT A - EUT PHOTOGRAPHS

Please refer to the attachment XMDN240206-08078E-RF-A1-EXP EUT EXTERNAL PHOTOGRAPHS and XMDN240206-08078E-RF-A1-INP EUT INTERNAL PHOTOGRAPHS.

EXHIBIT B - TEST SETUP PHOTOGRAPHS

Please refer to the attachment XMDN240206-08078E-RF-00BA1-TSP TEST SETUP PHOTOGRAPHS.

EXHIBIT C - RF EXPOSURE EVALUATION

Maximum Permissible Exposure (MPE)

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculation formula:

Prediction of power density at the distance of the applicable MPE limit

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Operation Modes	Frequency (MHz)	Antenna Gain		Conducted output power including Tune-up Tolerance		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
WiFi 2.4G	2412-2462	4.55	2.85	24	251.19	20.00	0.1425	1.0
WiFi 5.2G	5150-5250	4.19	2.62	15	31.62	20.00	0.0165	1.0
WiFi 5.3G	5250-5350	4.19	2.62	15	31.62	20.00	0.0165	1.0
WiFi 5.6G	5470-5725	5.71	3.72	15	31.62	20.00	0.0234	1.0
WiFi 5.8G	5725-5850	5.43	3.49	15	31.62	20.00	0.0220	1.0
Bluetooth	2402-2480	4.55	2.85	7	5.01	20.00	0.0028	1.0
BLE	2402-2480	4.55	2.85	7	5.01	20.00	0.0028	1.0

1. The Conducted output power including Tune-up Tolerance provided by manufacturer
2. BT/BLE/WiFi can't transmit simultaneously.

Result: The device meet FCC MPE at 20 cm distance

Exemption Limits For Routine Evaluation-RF Exposure Evaluation

Applicable Standard

RSS-102, Issue 6, Clause 6.6:

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $4.49/f^{0.5}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than $1.31 \times 10^{-2} f^{0.6834}$ W (adjusted for tune-up tolerance), where f is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the e.i.r.p. was derived.

Calculated Data:

Mode	Frequency (MHz)	Antenna Gain	Conducted output power including Tune-up Tolerance	EIRP		Exemption limits (mW)
		(dBi)	(dBm)	(dBm)	(mW)	
WiFi 2.4G	2412-2462	4.55	24	28.55	716.14	2684
WiFi 5.2G	5150-5250	4.19	15	19.19	82.99	4507
WiFi 5.3G	5250-5350	4.19	15	19.19	82.99	4567
WiFi 5.6G	5470-5725	5.71	15	20.71	117.76	4697
WiFi 5.8G	5725-5850	5.43	15	20.43	110.41	4845
Bluetooth	2402-2480	4.55	7	11.55	14.29	2676
BLE	2402-2480	4.55	7	11.55	14.29	2676

Note: 1. The Conducted output power including Tune-up Tolerance was provided by manufacturer.
2. BT/BLE/WiFi can't transmit simultaneously.

Result: Compliant, the device is compliance exemption from Routine Evaluation Limits –RF exposure Evaluation.

***** END OF REPORT *****