

TEST REPORT

Application No.: SZCR2512005589AT
Applicant: Fujian Landi Commercial Equipment Co.,Ltd.
Address of Applicant: Building 17, Area A, Software Park, No.89 Software Road, Gulou District, Fuzhou, 350003, Fujian, China
Equipment Under Test (EUT):
EUT Name: payment terminal
Model No.: P20R01
Trade Mark: Landi
FCC ID: 2AG6N-P2R
Standard(s) : 47 CFR Part 15, Subpart C 15.247
Date of Receipt: 2025-12-17
Date of Test: 2025-12-19 to 2026-01-03
Date of Issue: 2026-01-08

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

Kenxu

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558904

Page: 2 of 49

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2026-01-08		Original

Authorized for issue by:				
		Calvin Weng		
		Calvin Weng/Project Engineer		
		Eric Fu		
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Below 1GHz		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Radiated Spurious Emissions Above 1GHz		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.205 & 15.209	Pass
Conducted Output Power		ANSI C63.10 (2020) Section 11.9.2	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass

Remark:

Model No.: P20R01

This test report (Ref. No.: SZCR251200558904) is only valid with the modular test report (Ref. No.: PD20240152-R3D, FCC ID:XMR2024SC200ENA)

According to the declaration from the applicant, the RF module used in this report and the one in original report were identical (Smart Module, model No.: SC200E-NA, SC206E-NA), only change the antenna.

Therefore in this report the section 2 items were fully retested on model and shown the data in this report, other tests please refer to modular test report PD20240152-R3D.

Remark: The EUT contains three different HVINs, for the difference, please refer to below table:

1.	HVIN:P2R-A	No external backup power function - the device will shut down immediately after the adapter is unplugged.
2.	HVIN:P2R-C	With built in super capacitor backup power function.
3.	HVIN:P2R-B	With external battery backup power function - the device will continue to work as intended for several minutes after the adapter in unplugged. It's the same design with HVIN:P2R-A, only add external battery.

Therefore, all tests were performed on P2R-C.

3 Contents

	Page
1 Cover Page	1
2 Test Summary	3
3 Contents	4
4 General Information	6
4.1 Details of E.U.T.	6
4.2 Description of Support Units	6
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Test Facility	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement	10
6.1 Antenna Requirement	10
6.1.1 Test Requirement:	10
6.1.2 Conclusion	10
7 Radio Spectrum Matter Test Results	11
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	11
7.1.1 E.U.T. Operation	11
7.1.2 Test Mode Description	11
7.1.3 Test Setup Diagram	12
7.1.4 Measurement Procedure and Data	12
7.2 Radiated Emissions which fall in the restricted bands	15
7.2.1 E.U.T. Operation	15
7.2.2 Test Mode Description	15
7.2.3 Test Setup Diagram	16
7.2.4 Measurement Procedure and Data	17
7.3 Radiated Spurious Emissions Below 1GHz	24
7.3.1 E.U.T. Operation	24
7.3.2 Test Mode Description	24
7.3.3 Test Setup Diagram	25
7.3.4 Measurement Procedure and Data	25
7.4 Radiated Spurious Emissions Above 1GHz	28
7.4.1 E.U.T. Operation	28
7.4.2 Test Mode Description	28
7.4.3 Test Setup Diagram	28
7.4.4 Measurement Procedure and Data	29
7.5 Conducted Output Power	39
7.5.1 E.U.T. Operation	39



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558904

Page: 5 of 49

7.5.2	Test Mode Description	39
7.5.3	Test Setup Diagram	39
7.5.4	Measurement Procedure and Data.....	40
8	Test Setup Photo	41
9	EUT Constructional Details (EUT Photos)	41
10	Appendix.....	42



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing Center (CCC Laboratory)

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

4 General Information

4.1 Details of E.U.T.

Power supply:	DC5V/2A by AC/DC power adapter Adapter Manufacturer: Something High Electric(Xiamen) Company Inc. Adapter M/N:P24C050400 US Adapter Input:AC100-240V, 50/60Hz, 0.6A Adapter Output: DC5V/4A
Cable Loss (for RF conducted test):	0.7dB
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (DBPSK, DQPSK, CCK); 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	PIFA Antenna
Antenna Gain:	2.51dBi

Remark:The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--

The EUT has been tested as an independent unit.

4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Conducted Emissions at AC Power Line (150kHz-30MHz)	$\pm 3.2\text{dB}$
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (Below 1GHz); $\pm 4.6\text{dB}$ (Above 1GHz)
Radiated Spurious Emissions Below 1GHz	$\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m
Radiated Spurious Emissions Above 1GHz	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Conducted Output Power	$\pm 0.4\text{dB}$

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558904

Page: 7 of 49

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2025-05-07	2028-05-06
EMI Test Receiver	Rohde&Schwarz	ESR	SZ-WRG-M-047	2025-12-15	2026-12-14
Measurement Software	AUDIX	e3 V8.2014-6-27a	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2025-07-05	2026-07-04
LISN	Rohde&Schwarz	ENV216	SEM007-01	2025-07-25	2026-07-24
LISN	ETS-LINDGREN	3816/2	SEM007-02	2025-03-03	2026-03-02

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-12-16	2026-12-15
Low Noise Amplifier 30M-8GHz	Tonscend	TAP30M8G30	SZ-WRG-M-050	2025-12-16	2026-12-15
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2025-12-13	2026-12-12
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22

Radiated Spurious Emissions Below 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Loop Antenna	ETS-Lindgren	6502	SEM003-08	2025-11-17	2027-11-16
3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEM001-01	2023-06-19	2026-06-18
MXE EMI Receiver	Agilent Technologies	N9038A	SEM004-15	2025-07-25	2026-07-24
BiConiLog Antenna	ETS-LINDGREN	3142C	SEM003-01	2025-08-29	2027-08-28
Pre-Amplifier	Agilent Technologies	8447D	SEM005-01	2025-03-04	2026-03-03
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM025-01	2025-07-05	2026-07-04



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558904

Page: 9 of 49

Radiated Spurious Emissions Above 1GHz					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Signal & Spectrum Analyzer	Rohde & Schwarz	FSV	SZ-WRG-M-048	2025-12-16	2026-12-15
Low Noise Amplifier 1G-18GHz	Tonscend	TAP01018050	SZ-WRG-M-051	2025-12-16	2026-12-15
Low Noise Amplifier 18G-40GHz	Tonscend	TAP18040048	SZ-WRG-M-052	2025-12-16	2026-12-15
Double Ridge Horn Antenna 1GHz-18GHz	SCHWARZBECK	BBHA 9120 D	SZ-WRG-M-055	2025-12-13	2026-12-12
SHF-EHF Horn 15GHz-40GHz	SCHWARZBECK	BBHA 9170	SZ-WRG-M-056	2025-12-13	2026-12-12
RSE Test Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Chamber	CRTSGSSAC966	N/A	SZ-WRG-C-063	2025-01-06	2028-01-05
Humidity and Temperature Indicator	deli	8838	SEM002-46	2025-07-23	2026-07-22

RF Conducted Test					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Power Sensor	TST PASS	TSPS2023R	SEM009-26	2025-03-04	2026-03-03
Power Sensor	KEYSIGHT	U2021XA	SEM009-16	2025-03-04	2026-03-03
DC Power Supply	Chroma	62012P-80-60	SEM011-11	2025-07-24	2026-07-23
MXA Signal Analyzer	KEYSIGHT	N9020A	SEM004-19	2025-03-04	2026-03-03
Measurement Software	TST PASS	TST PASS V2.0	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM031-01	2025-07-05	2026-07-04
Attenuator	Huber+Suhner	6620_SMA-50-1	SEM021-09	2025-03-03	2026-03-02

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2025-07-23	2026-07-22
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2025-07-23	2026-07-22
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2025-03-03	2026-03-02



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203 & 15.247(b)(4)

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.51dBi.

Antenna location: Refer to internal photos



7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207
 Test Method: ANSI C63.10 (2020) Section 6.2
 Test Engineer: Mason Wu

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		
Detector: Peak for pre-scan (9kHz resolution bandwidth) 0.15M to 30MHz		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C Humidity: 40.5 % RH Atmospheric Pressure: 1020 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558904

Page: 13 of 49

Test Mode: 03; Line: Live line



Site : Shielding Room
Condition: Line
Job No. : 05589AT/05590AT
Test mode: 03
: 1#

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 *	0.1540	0.06	10.19	14.50	24.75	65.78	-41.03	QP
2 *	0.1540	0.06	10.19	2.51	12.76	55.78	-43.02	Average
3	0.3791	0.08	9.71	1.76	11.55	58.30	-46.75	QP
4	0.3791	0.08	9.71	-7.13	2.66	48.30	-45.64	Average
5	0.9944	0.11	9.58	-0.68	9.01	56.00	-46.99	QP
6	0.9944	0.11	9.58	-7.99	1.70	46.00	-44.30	Average
7	1.9182	0.12	9.58	-3.28	6.42	56.00	-49.58	QP
8	1.9182	0.12	9.58	-9.24	0.46	46.00	-45.54	Average
9	4.2018	0.14	9.66	-1.21	8.59	56.00	-47.41	QP
10	4.2018	0.14	9.66	-7.49	2.31	46.00	-43.69	Average
11	22.0629	0.21	10.22	6.19	16.62	60.00	-43.38	QP
12	22.0629	0.21	10.22	-3.63	6.80	50.00	-43.20	Average




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch (Shenzhen) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 03; Line: Neutral Line



Site : Shielding Room
 Condition: Neutral
 Job No. : 05589AT/05590AT
 Test mode: 03
 : 1#

	Freq	Cable Loss	LISN Factor	Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1 *	0.1540	0.06	10.14	14.50	24.70	65.78	-41.08	QP
2 *	0.1540	0.06	10.14	3.48	13.68	55.78	-42.10	Average
3	0.4564	0.09	9.72	1.93	11.74	56.76	-45.02	QP
4	0.4564	0.09	9.72	-6.41	3.40	46.76	-43.36	Average
5	1.1114	0.11	9.54	0.31	9.96	56.00	-46.04	QP
6	1.1114	0.11	9.54	-7.71	1.94	46.00	-44.06	Average
7	1.5193	0.12	9.55	-4.68	4.99	56.00	-51.01	QP
8	1.5193	0.12	9.55	-10.78	-1.11	46.00	-47.11	Average
9	2.5400	0.13	9.54	-0.22	9.45	56.00	-46.55	QP
10	2.5400	0.13	9.54	-6.91	2.76	46.00	-43.24	Average
11	15.3883	0.17	9.88	5.66	15.71	60.00	-44.29	QP
12	15.3883	0.17	9.88	-4.18	5.87	50.00	-44.13	Average



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558904

Page: 15 of 49

7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.10.5
 Measurement Distance: 3m
 Test Engineer: Mihawk Li

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22.6 °C Humidity: 50.8 % RH Atmospheric Pressure: 1020 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.




SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch Inspection & Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Remark 3: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.

Remark 4: For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.




11b_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2387.428	6.82	27.45	31.54	47.95	50.68	74.00	-23.32	Peak
2	2390.000	6.83	27.46	31.54	45.31	48.06	74.00	-25.94	Peak
3 pp	2412.000	6.91	27.52	31.54	99.84	102.73	74.00	28.73	Peak


11b_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.637	6.82	27.45	31.54	33.71	36.44	54.00	-17.56	Average
2	2390.000	6.83	27.46	31.54	33.43	36.18	54.00	-17.82	Average
3 pp	2412.000	6.91	27.52	31.54	95.91	98.88	54.00	44.88	Average


11b_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2333.989	6.80	27.27	31.53	47.99	50.53	74.00	-23.47	Peak
2	2390.000	6.83	27.46	31.54	45.46	48.21	74.00	-25.79	Peak
3 pp	2412.000	6.91	27.52	31.54	99.44	102.33	74.00	28.33	Peak

11b_TX_CH_01_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11b

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.605	6.82	27.46	31.54	33.89	36.63	54.00	-17.37	Average
2	2390.000	6.83	27.46	31.54	33.78	36.53	54.00	-17.47	Average
3 pp	2412.000	6.91	27.52	31.54	95.85	98.74	54.00	44.74	Average




11b_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2462.000	7.25	27.67	31.55	98.99	102.36	74.00	28.36	Peak
2	2483.500	7.40	27.80	31.55	45.49	49.14	74.00	-24.86	Peak
3	2488.360	7.43	27.83	31.55	47.76	51.47	74.00	-22.53	Peak


11b_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2462.000	7.25	27.67	31.55	95.07	98.44	54.00	44.44	Average
2	2483.500	7.40	27.80	31.55	33.89	37.54	54.00	-16.46	Average
3	2487.556	7.43	27.83	31.55	34.27	37.98	54.00	-16.02	Average


11b_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2462.000	7.25	27.67	31.55	99.83	103.20	74.00	29.20	Peak
2	2483.500	7.40	27.80	31.55	46.14	49.79	74.00	-24.21	Peak
3	2486.400	7.42	27.82	31.55	47.32	51.01	74.00	-22.99	Peak

11b_TX_CH_11_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2462 Band edge
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	pp 2462.000	7.25	27.67	31.55	95.99	99.36	54.00	45.36	Average
2	2483.500	7.40	27.80	31.55	33.47	37.12	54.00	-16.88	Average
3	2487.707	7.43	27.83	31.55	35.08	38.79	54.00	-15.21	Average




11n_HT(20M)_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2343.939	6.80	27.29	31.53	47.82	50.38	74.00	-23.62	Peak
2	2390.000	6.83	27.46	31.54	45.37	48.12	74.00	-25.88	Peak
3 pp	2412.000	6.91	27.52	31.54	101.38	104.27	74.00	30.27	Peak


11n_HT(20M)_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2380.426	6.82	27.42	31.54	33.81	36.51	54.00	-17.49	Average
2	2390.000	6.83	27.46	31.54	33.60	36.35	54.00	-17.65	Average
3 pp	2412.000	6.91	27.52	31.54	90.98	93.87	54.00	39.87	Average


11n_HT(20M)_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11N20


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2356.198	6.81	27.32	31.54	47.98	50.57	74.00	-23.43	Peak
2	2390.000	6.83	27.46	31.54	45.24	47.99	74.00	-26.01	Peak
3 pp	2412.000	6.91	27.52	31.54	101.36	104.25	74.00	30.25	Peak

11n_HT(20M)_TX_CH_01_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2412 Band edge
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.968	6.83	27.46	31.54	33.85	36.60	54.00	-17.40	Average
2	2390.000	6.83	27.46	31.54	33.85	36.60	54.00	-17.40	Average
3 pp	2412.000	6.91	27.52	31.54	90.82	93.71	54.00	39.71	Average




11n_HT(40M)_TX_CH_03_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2338.862	6.80	27.28	31.53	47.78	50.33	74.00	-23.67	Peak
2	2390.000	6.83	27.46	31.54	48.71	51.46	74.00	-22.54	Peak
3 pp	2422.000	6.98	27.54	31.54	99.04	102.02	74.00	28.02	Peak


11n_HT(40M)_TX_CH_03_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2338.895	6.83	27.46	31.54	35.07	37.82	54.00	-16.18	Average
2	2390.000	6.83	27.46	31.54	35.10	37.85	54.00	-16.15	Average
3 pp	2422.000	6.98	27.54	31.54	87.90	90.88	54.00	36.88	Average


11n_HT(40M)_TX_CH_03_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2325.061	6.79	27.25	31.53	47.90	50.41	74.00	-23.59	Peak
2	2390.000	6.83	27.46	31.54	46.61	49.36	74.00	-24.64	Peak
3 pp	2422.000	6.98	27.54	31.54	97.93	100.91	74.00	26.91	Peak


11n_HT(40M)_TX_CH_03_Vertical-Avg



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2422 Band edge
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2338.895	6.83	27.46	31.54	34.65	37.40	54.00	-16.60	Average
2	2390.000	6.83	27.46	31.54	34.70	37.45	54.00	-16.55	Average
3 pp	2422.000	6.98	27.54	31.54	87.13	90.11	54.00	36.11	Average





7.3 Radiated Spurious Emissions Below 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.4,6.5
 Measurement Distance: 3m
 Test Engineer: Mason Wu

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 23.3 °C Humidity: 47.6 % RH Atmospheric Pressure: 1020 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.



7.3.3 Test Setup Diagram



7.3.4 Measurement Procedure and Data


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel, the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- Repeat above procedures until all frequencies measured was complete.

Remark:

- Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
- Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.



Test Mode: 03; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL


Job No. : 05589AT/05590AT

Test Mode: 03

	Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB
1	30.105	21.15	0.74	27.65	24.86	19.10	40.00	-20.90 QP
2	88.342	11.52	1.17	27.61	27.50	12.58	43.50	-30.92 QP
3	154.821	13.52	1.52	27.73	31.44	18.75	43.50	-24.75 QP
4	312.179	18.41	2.16	27.53	30.45	23.49	46.00	-22.51 QP
5	696.857	25.88	3.40	27.84	27.77	29.21	46.00	-16.79 QP
6 q	760.704	26.47	3.58	27.69	28.72	31.08	46.00	-14.92 QP



Test Mode: 03; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : 05589AT/05590AT

Test Mode: 03

		Ant	Cable	Preamp	Read		Limit	Over	
	Freq	Factor	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB/m	dB	dB	dBuV	dBuV/m	dBuV/m	dB	
1	31.071	20.71	0.75	27.65	26.12	19.93	40.00	-20.07	QP
2	76.781	10.39	1.06	27.61	38.25	22.09	40.00	-17.91	QP
3	120.277	11.09	1.35	27.65	38.58	23.37	43.50	-20.13	QP
4	382.588	20.90	2.43	27.71	25.42	21.04	46.00	-24.96	QP
5	687.151	25.71	3.37	27.86	25.48	26.70	46.00	-19.30	QP
6 q	942.131	28.19	4.06	26.72	25.15	30.68	46.00	-15.32	QP



7.4 Radiated Spurious Emissions Above 1GHz

Test Requirement 47 CFR Part 15, Subpart C 15.205 & 15.209
 Test Method: ANSI C63.10 (2020) Section 6.6
 Measurement Distance: 3m
 Test Engineer: Mihawk Li

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1000	500	3

7.4.1 E.U.T. Operation


Operating Environment:

Temperature: 22.3 °C Humidity: 58.1 % RH Atmospheric Pressure: 1020 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 25GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
- 4: The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
- 5:For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.




11b_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	57.31	41.93	74.00	-32.07	Peak
2	8814.957	12.36	38.50	55.17	53.14	48.83	74.00	-25.17	Peak
3	11108.160	14.13	39.51	53.53	49.78	49.89	74.00	-24.11	Peak
4	13599.130	15.81	40.00	54.44	49.40	50.77	74.00	-23.23	Peak
5	16891.040	19.64	39.60	54.27	47.20	52.17	74.00	-21.83	Peak
6	pp17844.590	19.02	42.77	54.47	48.39	55.71	74.00	-18.29	Peak


11b_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6432.732	10.56	34.80	56.81	45.05	33.60	54.00	-20.40	Average
2	7943.838	11.48	37.69	55.94	41.25	34.48	54.00	-19.52	Average
3	11302.480	14.39	39.70	53.59	36.99	37.49	54.00	-16.51	Average
4	14242.800	16.83	39.80	54.38	35.92	38.17	54.00	-15.83	Average
5	16891.040	19.64	39.60	54.27	34.73	39.70	54.00	-14.30	Average
6	pp18000.000	18.64	43.80	54.50	35.29	43.23	54.00	-10.77	Average


11b_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	65.49	50.11	74.00	-23.89	Peak
2	7966.832	11.47	37.73	55.93	54.93	48.20	74.00	-25.80	Peak
3	11204.900	14.25	39.60	53.56	49.80	50.09	74.00	-23.91	Peak
4	14366.840	16.99	39.67	54.36	48.62	50.92	74.00	-23.08	Peak
5	16842.290	18.46	39.60	54.25	47.60	51.41	74.00	-22.59	Peak
6	pp18000.000	18.64	43.80	54.50	47.65	55.59	74.00	-18.41	Peak

11b_TX_CH_01_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4804.110	8.90	31.92	56.16	45.66	30.32	54.00	-23.68	Average
2	7943.838	11.48	37.69	55.94	41.39	34.62	54.00	-19.38	Average
3	11140.310	14.17	39.54	53.54	37.32	37.49	54.00	-16.51	Average
4	14201.690	16.67	39.80	54.38	36.10	38.19	54.00	-15.81	Average
5	16891.040	19.64	39.60	54.27	34.72	39.69	54.00	-14.31	Average
6	pp18000.000	18.64	43.80	54.50	35.20	43.14	54.00	-10.86	Average




11b_TX_CH_06_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	57.98	42.60	74.00	-31.40	Peak
2	7519.349	10.92	36.80	56.28	55.05	46.49	74.00	-27.51	Peak
3	11012.250	14.21	39.41	53.50	49.60	49.72	74.00	-24.28	Peak
4	14242.800	16.83	39.80	54.38	48.96	51.21	74.00	-22.79	Peak
5	16793.680	17.45	39.59	54.24	48.52	51.32	74.00	-22.68	Peak
6	pp17948.050	18.75	43.44	54.49	47.14	54.84	74.00	-19.16	Peak


11b_TX_CH_06_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6001.626	10.05	33.80	56.90	43.08	30.03	54.00	-23.97	Average
2	7920.911	11.48	37.64	55.96	42.30	35.46	54.00	-18.54	Average
3	11302.480	14.39	39.70	53.59	37.77	38.27	54.00	-15.73	Average
4	14242.800	16.83	39.80	54.38	36.61	38.86	54.00	-15.14	Average
5	16891.040	19.64	39.60	54.27	35.61	40.58	54.00	-13.42	Average
6	pp18000.000	18.64	43.80	54.50	36.26	44.20	54.00	-9.80	Average


11b_TX_CH_06_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	62.32	46.94	74.00	-27.06	Peak
2	7989.893	11.46	37.78	55.91	55.97	49.30	74.00	-24.70	Peak
3	10729.480	13.53	39.37	53.66	50.73	49.97	74.00	-24.03	Peak
4	14242.800	16.83	39.80	54.38	48.68	50.93	74.00	-23.07	Peak
5	16891.040	19.64	39.60	54.27	46.66	51.63	74.00	-22.37	Peak
6	pp18000.000	18.64	43.80	54.50	47.11	55.05	74.00	-18.95	Peak

11b_TX_CH_06_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4804.110	8.90	31.92	56.16	46.32	30.98	54.00	-23.02	Average
2	8814.957	12.36	38.50	55.17	41.01	36.70	54.00	-17.30	Average
3	11302.480	14.39	39.70	53.59	37.82	38.32	54.00	-15.68	Average
4	14242.800	16.83	39.80	54.38	36.62	38.86	54.00	-15.14	Average
5	16891.040	19.64	39.60	54.27	35.38	40.35	54.00	-13.65	Average
6	pp18000.000	18.64	43.80	54.50	35.89	43.83	54.00	-10.17	Average




11b_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4776.419	8.87	31.85	56.14	58.50	43.08	74.00	-30.92	Peak
2	7943.838	11.48	37.69	55.94	54.83	47.26	74.00	-26.74	Peak
3	11269.860	14.35	39.67	53.58	49.77	50.21	74.00	-23.79	Peak
4	14838.450	16.47	39.90	54.40	49.02	50.99	74.00	-23.01	Peak
5	16891.040	19.64	39.60	54.27	48.36	53.33	74.00	-20.67	Peak
6	pp18000.000	18.64	43.80	54.50	47.75	55.69	74.00	-18.31	Peak


11b_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6564.209	10.80	35.06	56.79	44.25	33.32	54.00	-20.68	Average
2	8789.516	12.33	38.50	55.19	40.98	36.62	54.00	-17.38	Average
3	11302.480	14.39	39.70	53.59	37.83	38.33	54.00	-15.67	Average
4	14201.690	16.67	39.80	54.38	36.91	39.00	54.00	-15.00	Average
5	16891.040	19.64	39.60	54.27	35.36	40.33	54.00	-13.67	Average
6	pp18000.000	18.64	43.80	54.50	35.98	43.92	54.00	-10.08	Average


11b_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	66.23	50.85	74.00	-23.15	Peak
2	7966.832	11.47	37.73	55.93	53.26	46.53	74.00	-27.47	Peak
3	11204.900	14.25	39.60	53.56	50.30	50.59	74.00	-23.41	Peak
4	14916.940	16.97	38.88	54.31	49.29	50.83	74.00	-23.17	Peak
5	16648.690	17.87	39.30	54.19	49.01	51.99	74.00	-22.01	Peak
6	pp17896.250	18.87	43.08	54.48	47.46	54.93	74.00	-19.07	Peak

11b_TX_CH_11_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	46.92	31.54	54.00	-22.46	Average
2	7943.838	11.48	37.69	55.94	42.14	35.37	54.00	-18.63	Average
3	11302.480	14.39	39.70	53.59	37.74	38.24	54.00	-15.76	Average
4	14079.080	16.38	39.90	54.39	36.96	38.85	54.00	-15.15	Average
5	16891.040	19.64	39.60	54.27	35.46	40.43	54.00	-13.57	Average
6	pp18000.000	18.64	43.80	54.50	35.90	43.84	54.00	-10.16	Average




11n_20M_TX_CH_01_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5932.638	10.00	33.57	56.86	54.50	41.21	74.00	-32.79	Peak
2	7989.893	11.46	37.78	55.91	54.20	47.53	74.00	-26.47	Peak
3	11335.190	14.29	39.70	53.60	48.70	49.09	74.00	-24.91	Peak
4	14038.450	16.47	39.90	54.40	48.15	50.12	74.00	-23.88	Peak
5	16842.290	18.46	39.60	54.25	46.09	49.90	74.00	-24.10	Peak
6	pp17948.050	18.75	43.44	54.49	45.80	53.50	74.00	-20.50	Peak


11n_20M_TX_CH_01_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6432.732	10.56	34.80	56.81	44.15	32.70	54.00	-21.30	Average
2	7920.911	11.48	37.64	55.96	41.50	34.66	54.00	-19.34	Average
3	11302.480	14.39	39.70	53.59	36.54	37.04	54.00	-16.96	Average
4	14160.710	16.53	39.84	54.38	35.66	37.65	54.00	-16.35	Average
5	16891.040	19.64	39.60	54.27	33.75	38.72	54.00	-15.28	Average
6	pp18000.000	18.64	43.80	54.50	33.86	41.80	54.00	-12.20	Average


11n_20M_TX_CH_01_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	61.45	46.07	74.00	-27.93	Peak
2	7943.838	11.48	37.69	55.94	52.55	45.78	74.00	-28.22	Peak
3	10484.230	13.32	39.08	53.81	50.13	48.72	74.00	-25.28	Peak
4	13249.930	15.91	40.25	54.40	48.13	49.81	74.00	-24.19	Peak
5	16891.040	19.64	39.60	54.27	45.08	50.05	74.00	-23.95	Peak
6	pp17948.050	18.75	43.44	54.49	45.57	53.27	74.00	-20.73	Peak


11n_20M_TX_CH_01_Vertical-Avg



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2412 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	46.99	31.61	54.00	-22.39	Average
2	6432.732	10.56	34.80	56.81	47.79	36.34	54.00	-17.66	Average
3	11302.480	14.39	39.70	53.59	36.71	37.21	54.00	-16.79	Average
4	14119.830	16.40	39.88	54.39	35.77	37.66	54.00	-16.34	Average
5	16891.040	19.64	39.60	54.27	33.84	38.81	54.00	-15.19	Average
6	pp18000.000	18.64	43.80	54.50	33.71	41.65	54.00	-12.35	Average


11n_20M_TX_CH_06_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4894.110	8.99	31.92	56.16	57.48	42.14	74.00	-31.86	Peak
2	7784.729	11.21	37.14	56.07	54.33	46.61	74.00	-27.39	Peak
3	10363.710	13.51	39.00	53.88	50.20	48.83	74.00	-25.17	Peak
4	14618.170	16.62	39.28	54.34	48.07	49.63	74.00	-24.37	Peak
5	16891.040	19.64	39.60	54.27	45.18	50.15	74.00	-23.85	Peak
6	pp18000.000	18.64	43.80	54.50	45.38	53.32	74.00	-20.68	Peak


11n_20M_TX_CH_06_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5984.305	10.04	33.74	56.89	42.62	29.51	54.00	-24.49	Average
2	7943.838	11.48	37.69	55.94	41.41	34.64	54.00	-19.36	Average
3	11302.480	14.39	39.70	53.59	36.81	37.31	54.00	-16.69	Average
4	14079.080	16.38	39.90	54.39	35.83	37.72	54.00	-16.28	Average
5	16891.040	19.64	39.60	54.27	33.94	38.91	54.00	-15.09	Average
6	pp18000.000	18.64	43.80	54.50	34.05	41.99	54.00	-12.01	Average


11n_20M_TX_CH_06_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	62.39	47.01	74.00	-26.99	Peak
2	7898.049	11.48	37.59	55.98	52.95	46.04	74.00	-27.96	Peak
3	10948.780	13.91	39.35	53.53	49.04	48.77	74.00	-25.23	Peak
4	13326.750	15.92	40.30	54.47	47.51	49.26	74.00	-24.74	Peak
5	16891.040	19.64	39.60	54.27	45.04	50.01	74.00	-23.99	Peak
6	pp18000.000	18.64	43.80	54.50	45.18	53.12	74.00	-20.88	Peak

11n_20M_TX_CH_06_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	45.54	30.16	54.00	-23.84	Average
2	6507.536	10.68	34.92	56.80	46.30	35.10	54.00	-18.90	Average
3	11335.190	14.29	39.70	53.60	36.81	37.20	54.00	-16.80	Average
4	14079.080	16.38	39.90	54.39	35.83	37.72	54.00	-16.28	Average
5	16891.040	19.64	39.60	54.27	34.03	39.00	54.00	-15.00	Average
6	pp18000.000	18.64	43.80	54.50	33.74	41.68	54.00	-12.32	Average




11n_20M_TX_CH_11_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	56.89	41.51	74.00	-32.49	Peak
2	7943.838	11.48	37.69	55.94	53.78	47.81	74.00	-26.99	Peak
3	11735.250	14.46	39.54	53.72	48.58	48.86	74.00	-25.14	Peak
4	14533.910	16.36	39.43	54.35	48.68	50.12	74.00	-23.88	Peak
5	16891.040	19.64	39.60	54.27	45.57	50.54	74.00	-23.46	Peak
6	pp17948.050	18.75	43.44	54.49	45.49	53.19	74.00	-20.81	Peak


11n_20M_TX_CH_11_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5284.902	9.33	32.67	56.47	45.73	31.26	54.00	-22.74	Average
2	7943.838	11.48	37.69	55.94	41.71	34.94	54.00	-19.06	Average
3	11302.480	14.39	39.70	53.59	36.70	37.20	54.00	-16.80	Average
4	14242.800	16.83	39.80	54.38	35.53	37.78	54.00	-16.22	Average
5	16891.040	19.64	39.60	54.27	33.90	38.87	54.00	-15.13	Average
6	pp18000.000	18.64	43.80	54.50	33.78	41.72	54.00	-12.28	Average


11n_20M_TX_CH_11_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	65.46	50.88	74.00	-23.92	Peak
2	7920.911	11.48	37.64	55.96	52.81	45.97	74.00	-28.03	Peak
3	10514.580	13.30	39.13	53.79	49.93	48.57	74.00	-25.43	Peak
4	13326.750	15.92	40.30	54.47	47.83	49.58	74.00	-24.42	Peak
5	16842.290	18.46	39.60	54.25	46.19	50.00	74.00	-24.00	Peak
6	pp18000.000	18.64	43.80	54.50	44.99	52.93	74.00	-21.07	Peak

11n_20M_TX_CH_11_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2462 TX RSE
: 2.4G Wi-Fi 11N20

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	46.96	31.58	54.00	-22.42	Average
2	7943.838	11.48	37.69	55.94	41.56	34.79	54.00	-19.21	Average
3	11302.480	14.39	39.70	53.59	36.67	37.17	54.00	-16.83	Average
4	13404.010	15.67	40.29	54.46	36.14	37.64	54.00	-16.36	Average
5	16891.040	19.64	39.60	54.27	33.93	38.90	54.00	-15.10	Average
6	pp18000.000	18.64	43.80	54.50	33.92	41.86	54.00	-12.14	Average




11n_40M_TX_CH_03_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2422 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	59.27	43.89	74.00	-30.11	Peak
2	7943.838	11.48	37.69	55.94	54.01	47.24	74.00	-26.76	Peak
3	11906.070	14.62	39.71	53.77	49.51	50.07	74.00	-23.93	Peak
4	14284.030	17.00	39.80	54.37	48.44	50.87	74.00	-23.13	Peak
5	16939.940	19.22	39.64	54.28	46.97	51.55	74.00	-22.45	Peak
6	pp18000.000	18.64	43.80	54.50	47.73	55.67	74.00	-18.33	Peak


11n_40M_TX_CH_03_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2422 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6451.353	10.59	34.80	56.81	45.70	34.28	54.00	-19.72	Average
2	8713.630	12.01	38.57	55.26	41.61	36.93	54.00	-17.07	Average
3	11302.480	14.39	39.70	53.59	37.79	38.29	54.00	-15.71	Average
4	14079.080	16.38	39.90	54.39	36.82	38.71	54.00	-15.29	Average
5	16891.040	19.64	39.60	54.27	35.39	40.36	54.00	-13.64	Average
6	pp18000.000	18.64	43.80	54.50	35.84	43.78	54.00	-10.22	Average


11n_40M_TX_CH_03_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2422 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	63.38	48.00	74.00	-26.00	Peak
2	7989.893	11.46	37.78	55.91	57.72	51.05	74.00	-22.95	Peak
3	11735.250	14.46	39.54	53.72	49.74	50.02	74.00	-23.98	Peak
4	13957.530	16.22	39.90	54.40	48.82	50.54	74.00	-23.46	Peak
5	16891.040	19.64	39.60	54.27	46.33	51.30	74.00	-22.70	Peak
6	pp17948.050	18.75	43.44	54.49	48.11	55.81	74.00	-18.19	Peak

11n_40M_TX_CH_03_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2422 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6451.353	10.59	34.80	56.81	45.75	34.33	54.00	-19.67	Average
2	8713.630	12.01	38.57	55.26	41.37	36.69	54.00	-17.31	Average
3	11140.310	14.17	39.54	53.54	38.13	38.30	54.00	-15.70	Average
4	14242.800	16.83	39.80	54.38	36.41	38.66	54.00	-15.34	Average
5	16891.040	19.64	39.60	54.27	35.32	40.29	54.00	-13.71	Average
6	pp18000.000	18.64	43.80	54.50	35.95	43.89	54.00	-10.11	Average




11n_40M_TX_CH_06_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	61.04	45.66	74.00	-28.34	Peak
2	7943.838	11.48	37.69	55.94	54.44	47.67	74.00	-26.33	Peak
3	11044.130	14.18	39.44	53.51	49.78	49.89	74.00	-24.11	Peak
4	13677.970	16.04	40.00	54.43	48.95	50.56	74.00	-23.44	Peak
5	16891.040	19.64	39.60	54.27	47.11	52.08	74.00	-21.92	Peak
6	pp17948.050	18.75	43.44	54.49	48.66	56.36	74.00	-17.64	Peak


11n_40M_TX_CH_06_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6001.626	10.05	33.80	56.90	43.13	30.08	54.00	-23.92	Average
2	7943.838	11.48	37.69	55.94	42.10	35.33	54.00	-18.67	Average
3	11302.480	14.39	39.70	53.59	37.76	38.26	54.00	-15.74	Average
4	14079.080	16.38	39.90	54.39	36.88	38.77	54.00	-15.23	Average
5	16891.040	19.64	39.60	54.27	35.73	40.70	54.00	-13.30	Average
6	pp18000.000	18.64	43.80	54.50	35.85	43.79	54.00	-10.21	Average


11n_40M_TX_CH_06_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	66.02	50.64	74.00	-23.36	Peak
2	7920.911	11.48	37.64	55.96	53.97	47.13	74.00	-26.87	Peak
3	11400.910	14.10	39.70	53.62	50.36	50.54	74.00	-23.46	Peak
4	13326.750	15.92	40.30	54.47	49.35	51.10	74.00	-22.90	Peak
5	16891.040	19.64	39.60	54.27	46.43	51.40	74.00	-22.60	Peak
6	pp17948.050	18.75	43.44	54.49	47.03	54.73	74.00	-19.27	Peak

11n_40M_TX_CH_06_Vertical-Avg




Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2437 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	48.06	32.68	54.00	-21.32	Average
2	7966.832	11.47	37.73	55.93	42.10	35.37	54.00	-18.63	Average
3	11302.480	14.39	39.70	53.59	37.65	38.15	54.00	-15.85	Average
4	14119.830	16.40	39.88	54.39	37.00	38.89	54.00	-15.11	Average
5	16891.040	19.64	39.60	54.27	35.51	40.48	54.00	-13.52	Average
6	pp18000.000	18.64	43.80	54.50	36.00	43.94	54.00	-10.06	Average




11n_40M_TX_CH_09_Horizontal-Peak



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2452 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	57.73	42.35	74.00	-31.65	Peak
2	7966.832	11.47	37.73	55.93	53.89	47.16	74.00	-26.84	Peak
3	10791.690	13.49	39.31	53.62	51.06	50.24	74.00	-23.76	Peak
4	14242.800	16.83	39.80	54.38	48.65	50.90	74.00	-23.10	Peak
5	16891.040	19.64	39.60	54.27	46.87	51.84	74.00	-22.16	Peak
6	pp17948.050	18.75	43.44	54.49	47.01	54.71	74.00	-19.29	Peak


11n_40M_TX_CH_09_Horizontal-Avg



Condition: 3m HORIZONTAL
Job No : 05589AT/05590AT
Mode : 2452 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6545.263	10.76	34.99	56.79	44.78	33.74	54.00	-20.26	Average
2	8789.516	12.33	38.50	55.19	41.14	36.78	54.00	-17.22	Average
3	11302.480	14.39	39.70	53.59	37.72	38.22	54.00	-15.78	Average
4	14201.690	16.67	39.80	54.38	36.85	38.94	54.00	-15.06	Average
5	16891.040	19.64	39.60	54.27	35.66	40.63	54.00	-13.37	Average
6	pp18000.000	18.64	43.80	54.50	35.94	43.88	54.00	-10.12	Average


11n_40M_TX_CH_09_Vertical-Peak



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2452 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	4790.245	8.89	31.88	56.15	63.85	48.47	74.00	-25.53	Peak
2	7989.893	11.46	37.78	55.91	55.67	49.00	74.00	-25.00	Peak
3	11302.480	14.39	39.70	53.59	49.51	50.01	74.00	-23.99	Peak
4	14242.800	16.83	39.80	54.38	49.51	51.76	74.00	-22.24	Peak
5	16891.040	19.64	39.60	54.27	46.39	51.36	74.00	-22.64	Peak
6	pp18000.000	18.64	43.80	54.50	47.44	55.38	74.00	-18.62	Peak

11n_40M_TX_CH_09_Vertical-Avg



Condition: 3m VERTICAL
Job No : 05589AT/05590AT
Mode : 2452 TX RSE
: 2.4G Wi-Fi 11N40

	Freq	Cable Loss	Ant Factor	Preamp	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	6001.626	10.05	33.80	56.90	43.39	30.34	54.00	-23.66	Average
2	7943.838	11.48	37.69	55.94	42.16	35.39	54.00	-18.61	Average
3	11204.900	14.25	39.60	53.56	37.88	38.17	54.00	-15.83	Average
4	14079.080	16.38	39.90	54.39	36.85	38.74	54.00	-15.26	Average
5	16891.040	19.64	39.60	54.27	35.30	40.27	54.00	-13.73	Average
6	pp18000.000	18.64	43.80	54.50	36.03	43.97	54.00	-10.03	Average



7.5 Conducted Output Power

Test Requirement 47 CFR Part 15, Subpart C 15.247(b)(3)
 Test Method: ANSI C63.10 (2020) Section 11.9.2
 Test Engineer: Linvo Ding

Limit:

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

7.5.1 E.U.T. Operation


Operating Environment:

Temperature: 21.1 °C Humidity: 63.3 % RH Atmospheric Pressure: 1020 mbar

7.5.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	03	TX mode_Keep the EUT in continuously transmitting mode with all modulation types. Only the data of worst case is recorded in the report.

7.5.3 Test Setup Diagram



7.5.4 Measurement Procedure and Data

Please Refer to Appendix for Details



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2512005589AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix – External and Internal Photos for SZCR2512005589AT

10 Appendix

1. Duty Cycle


1.1 Test Result

1.1.1 Ant1

Ant1							
Mode	TX Type	Frequency (MHz)	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
802.11b	SISO	2412	12.210	12.497	97.70	0.10	1.24
		2437	12.210	12.367	98.73	0.06	0.29
		2462	12.210	12.350	98.87	0.05	0.13
802.11g	SISO	2412	2.029	2.064	98.30	0.07	0.00
		2437	2.029	2.064	98.30	0.07	0.00
		2462	2.029	2.064	98.30	0.07	0.00
802.11n (HT20)	SISO	2412	1.890	1.925	98.18	0.08	0.00
		2437	1.889	1.924	98.18	0.08	0.00
		2462	1.890	1.925	98.18	0.08	0.03
802.11n (HT40)	SISO	2422	0.930	0.979	94.99	0.22	0.00
		2437	0.929	0.979	94.89	0.23	0.03
		2452	0.929	0.979	94.89	0.23	0.03

1.2 Test Graph


1.2.1 Ant1




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com


802.11b_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11g_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11g_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11g_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_LCH_2412MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_MCH_2437MHz_Ant1 (SISO)_NTNV




802.11n(HT20)_HCH_2462MHz_Ant1 (SISO)_NTNV




802.11n(HT40)_LCH_2422MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_MCH_2437MHz_Ant1 (SISO)_NTNV



802.11n(HT40)_HCH_2452MHz_Ant1 (SISO)_NTNV



2. Maximum Conducted Output Power

2.1 Test Result

2.1.1 Power

Mode	TX Type	Frequency (MHz)	Maximum Average Conducted Output Power (dBm)		Verdict
			ANT1	Limit	
802.11b	SISO	2412	15.92	<=30	Pass
		2437	16.34	<=30	Pass
		2462	15.77	<=30	Pass
802.11g	SISO	2412	16.29	<=30	Pass
		2437	16.36	<=30	Pass
		2462	15.88	<=30	Pass
802.11n (HT20)	SISO	2412	15.18	<=30	Pass
		2437	15.22	<=30	Pass
		2462	14.78	<=30	Pass
802.11n (HT40)	SISO	2422	15.21	<=30	Pass
		2437	15.16	<=30	Pass
		2452	14.90	<=30	Pass

Note1: Antenna Gain: Ant1: 2.51dBi;

- End of the Report -