

# TEST REPORT

**Application No.:** SZCR2512005589AT  
**Applicant:** Fujian Landi Commercial Equipment Co.,Ltd.  
**Address of Applicant:** Building 17, Area A, Software Park, No.89 Software Road, Gulou District, Fuzhou, 350003, Fujian, China  
**Equipment Under Test (EUT):**  
**EUT Name:** payment terminal  
**Model No.:** P20R01  
**Trade Mark:** Landi  
**FCC ID:** 2AG6N-P2R  
**Standard(s) :** 47 CFR Part 15, Subpart C 15.225  
**Date of Receipt:** 2025-12-17  
**Date of Test:** 2025-12-19 to 2025-12-23  
**Date of Issue:** 2026-01-08

|                     |              |
|---------------------|--------------|
| <b>Test Result:</b> | <b>Pass*</b> |
|---------------------|--------------|

\* In the configuration tested, the EUT complied with the standards specified above.

*Kenx. Xu*

Kenx. Xu  
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn  
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558906  
Page: 2 of 34

| Revision Record |         |            |          |          |
|-----------------|---------|------------|----------|----------|
| Version         | Chapter | Date       | Modifier | Remark   |
| 01              |         | 2026-01-08 |          | Original |
|                 |         |            |          |          |
|                 |         |            |          |          |

|                          |  |                              |  |  |
|--------------------------|--|------------------------------|--|--|
| Authorized for issue by: |  |                              |  |  |
|                          |  | Calvin Weng                  |  |  |
|                          |  | Calvin Weng/Project Engineer |  |  |
|                          |  | Eric Fu                      |  |  |
|                          |  | Eric Fu/Reviewer             |  |  |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 2 Test Summary

| Radio Spectrum Technical Requirement |                                  |        |                                  |        |
|--------------------------------------|----------------------------------|--------|----------------------------------|--------|
| Item                                 | Standard                         | Method | Requirement                      | Result |
| Antenna Requirement                  | 47 CFR Part 15, Subpart C 15.225 | N/A    | 47 CFR Part 15, Subpart C 15.203 | Pass   |

| Radio Spectrum Matter Part                            |                                  |                                |                                              |        |
|-------------------------------------------------------|----------------------------------|--------------------------------|----------------------------------------------|--------|
| Item                                                  | Standard                         | Method                         | Requirement                                  | Result |
| Conducted Emissions at Mains Terminals (150kHz-30MHz) | 47 CFR Part 15, Subpart C 15.225 | ANSI C63.10 (2020) Section 6.2 | 47 CFR Part 15, Subpart C 15.207             | Pass   |
| 20dB Bandwidth                                        |                                  | ANSI C63.10 (2020) Section 6.9 | 47 CFR Part 15, Subpart C 15.215             | Pass   |
| Emission Mask                                         |                                  | ANSI C63.10 (2020) Section 6.4 | 47 CFR Part 15, Subpart C 15.225(a)&(b)&(C ) | Pass   |
| Frequency tolerance                                   |                                  | ANSI C63.10 (2020) Section 6.8 | 47 CFR Part 15, Subpart C 15.225(e)          | Pass   |
| Radiated Emissions (9kHz-30MHz)                       |                                  | ANSI C63.10 (2020) Section 6.4 | 47 CFR Part 15, Subpart C 15.225(d) & 15.209 | Pass   |
| Radiated Emissions (30MHz-1GHz)                       |                                  | ANSI C63.10 (2020) Section 6.5 | 47 CFR Part 15, Subpart C 15.225(d) & 15.209 | Pass   |

Remark: The EUT contains three different HVINs, for the difference, please refer to below table:

|    |            |                                                                                                                                                                                                                 |
|----|------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1. | HVIN:P2R-A | No external backup power function - the device will shut down immediately after the adapter is unplugged.                                                                                                       |
| 2. | HVIN:P2R-C | With built in super capacitor backup power function.                                                                                                                                                            |
| 3. | HVIN:P2R-B | With external battery backup power function - the device will continue to work as intended for several minutes after the adapter in unplugged. It's the same design with HVIN:P2R-A, only add external battery. |

Therefore, all tests were performed on P2R-C.



### 3 Contents

|                                                                 | Page |
|-----------------------------------------------------------------|------|
| 1 Cover Page .....                                              | 1    |
| 2 Test Summary .....                                            | 3    |
| 3 Contents .....                                                | 4    |
| 4 General Information .....                                     | 6    |
| 4.1 Details of E.U.T. ....                                      | 6    |
| 4.2 Description of Support Units .....                          | 6    |
| 4.3 Measurement Uncertainty .....                               | 6    |
| 4.4 Test Location .....                                         | 7    |
| 4.5 Test Facility .....                                         | 7    |
| 4.6 Deviation from Standards .....                              | 7    |
| 4.7 Abnormalities from Standard Conditions .....                | 7    |
| 5 Equipment List .....                                          | 8    |
| 6 Radio Spectrum Technical Requirement .....                    | 11   |
| 6.1 Antenna Requirement .....                                   | 11   |
| 6.1.1 Test Requirement: .....                                   | 11   |
| 7 Radio Spectrum Matter Test Results .....                      | 12   |
| 7.1 Conducted Emissions at Mains Terminals (150kHz-30MHz) ..... | 12   |
| 7.1.1 E.U.T. Operation .....                                    | 12   |
| 7.1.2 Test Mode Description .....                               | 12   |
| 7.1.3 Test Setup Diagram .....                                  | 12   |
| 7.1.4 Measurement Procedure and Data .....                      | 13   |
| 7.2 20dB Bandwidth .....                                        | 16   |
| 7.2.1 E.U.T. Operation .....                                    | 16   |
| 7.2.2 Test Mode Description .....                               | 16   |
| 7.2.3 Test Setup Diagram .....                                  | 16   |
| 7.2.4 Measurement Procedure and Data .....                      | 16   |
| 7.3 Emission Mask .....                                         | 18   |
| 7.3.1 E.U.T. Operation .....                                    | 18   |
| 7.3.2 Test Mode Description .....                               | 18   |
| 7.3.3 Test Setup Diagram .....                                  | 19   |
| 7.3.4 Measurement Procedure and Data .....                      | 19   |
| 7.4 Frequency tolerance .....                                   | 22   |
| 7.4.1 E.U.T. Operation .....                                    | 22   |
| 7.4.2 Test Mode Description .....                               | 22   |
| 7.4.3 Test Setup Diagram .....                                  | 22   |
| 7.4.4 Measurement Procedure and Data .....                      | 22   |
| 7.5 Radiated Emissions (9kHz-30MHz) .....                       | 24   |
| 7.5.1 E.U.T. Operation .....                                    | 24   |
| 7.5.2 Test Mode Description .....                               | 24   |



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558906

Page: 5 of 34

|       |                                               |    |
|-------|-----------------------------------------------|----|
| 7.5.3 | Test Setup Diagram .....                      | 25 |
| 7.5.4 | Measurement Procedure and Data.....           | 25 |
| 7.6   | Radiated Emissions (30MHz-1GHz) .....         | 30 |
| 7.6.1 | E.U.T. Operation .....                        | 30 |
| 7.6.2 | Test Mode Description .....                   | 30 |
| 7.6.3 | Test Setup Diagram .....                      | 31 |
| 7.6.4 | Measurement Procedure and Data.....           | 31 |
| 8     | Test Setup Photo .....                        | 34 |
| 9     | EUT Constructional Details (EUT Photos) ..... | 34 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



## 4 General Information

### 4.1 Details of E.U.T.

|                      |                                                                                                                                                                                                         |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:        | DC5V/2A by AC/DC power adapter<br>Adapter Manufacturer: Something High Electric(Xiamen) Company Inc.<br>Adapter M/N:P24C050400 US<br>Adapter Input:AC100-240V, 50/60Hz, 0.6A<br>Adapter Output: DC5V/4A |
| Operation Frequency: | 13.56MHz                                                                                                                                                                                                |
| Modulation Type:     | ASK                                                                                                                                                                                                     |
| Antenna Type:        | Coil Antenna                                                                                                                                                                                            |

Remark:The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

### 4.2 Description of Support Units

| Description | Manufacturer | Model No. | Serial No. |
|-------------|--------------|-----------|------------|
| --          | --           | --        | --         |

The EUT has been tested as an independent unit.

### 4.3 Measurement Uncertainty

| Test Item                                             | Measurement Uncertainty                               |
|-------------------------------------------------------|-------------------------------------------------------|
| Conducted Emissions at Mains Terminals (150kHz-30MHz) | $\pm 3.1\text{dB}$                                    |
| 20dB Bandwidth                                        | $\pm 3\%$                                             |
| Emission Mask                                         | $\pm 4.5\text{dB}$ (Below 1GHz)                       |
| Frequency tolerance                                   | $\pm 3\%$                                             |
| Radiated Emissions (9kHz-30MHz)                       | $\pm 3.6\text{dB}$                                    |
| Radiated Emissions (30MHz-1GHz)                       | $\pm 6.0\text{dB}$ for 3m; $\pm 5.0\text{dB}$ for 10m |

Remark:

The  $U_{\text{lab}}$  (lab Uncertainty) is less than  $U_{\text{CISPR/ETSI}}$  (CISPR/ETSI Uncertainty), so the test results  
 – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;  
 – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558906

Page: 7 of 34

### 4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

#### • VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

#### • FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

#### • Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

### 4.6 Deviation from Standards

None

### 4.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 5 Equipment List

| Conducted Emissions at Mains Terminals (150kHz-30MHz) |                  |                  |               |            |              |
|-------------------------------------------------------|------------------|------------------|---------------|------------|--------------|
| Equipment                                             | Manufacturer     | Model No.        | Inventory No. | Cal Date   | Cal Due Date |
| Shielding Room                                        | ZhongYu Electron | GB-88            | SEM001-06     | 2025-05-07 | 2028-05-06   |
| EMI Test Receiver                                     | Rohde&Schwarz    | ESR              | SZ-WRG-M-047  | 2025-12-15 | 2026-12-14   |
| Measurement Software                                  | AUDIX            | e3 V8.2014-6-27a | N/A           | N/A        | N/A          |
| Coaxial Cable                                         | SGS              | N/A              | SEM024-01     | 2025-07-05 | 2026-07-04   |
| LISN                                                  | Rohde&Schwarz    | ENV216           | SEM007-01     | 2025-07-25 | 2026-07-24   |
| LISN                                                  | ETS-LINDGREN     | 3816/2           | SEM007-02     | 2025-03-03 | 2026-03-02   |

| 20dB Bandwidth       |                 |               |               |            |              |
|----------------------|-----------------|---------------|---------------|------------|--------------|
| Equipment            | Manufacturer    | Model No.     | Inventory No. | Cal Date   | Cal Due Date |
| DC Power Supply      | Zhao Xin        | PS-305D       | SEM011-13     | 2025-07-24 | 2026-07-23   |
| Spectrum Analyzer    | Rohde & Schwarz | FSP30         | SEM004-06     | 2025-09-10 | 2026-09-09   |
| Measurement Software | TST PASS        | TST PASS V2.0 | N/A           | N/A        | N/A          |
| Coaxial Cable        | SGS             | N/A           | SEM031-01     | 2025-07-05 | 2026-07-04   |
| Attenuator           | Huber+Suhner    | 6620_SMA-50-1 | SEM021-09     | 2025-03-03 | 2026-03-02   |

| Emission Mask             |                      |                 |               |            |              |
|---------------------------|----------------------|-----------------|---------------|------------|--------------|
| Equipment                 | Manufacturer         | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| 10m Semi-Anechoic Chamber | SAEMC                | FSAC1018        | SEM001-03     | 2025-03-21 | 2026-03-20   |
| MXE EMI receiver          | KEYSIGHT             | N9038A          | SEM004-16     | 2025-07-25 | 2026-07-24   |
| Trilog-Broadband Antenna  | Schwarzbeck          | VULB9168        | SEM003-18     | 2025-08-29 | 2027-08-28   |
| Pre-amplifier             | Sonoma Instrument Co | 310N            | SEM005-04     | 2025-03-04 | 2026-03-03   |
| Loop Antenna              | ETS-Lindgren         | 6502            | SEM003-08     | 2025-11-17 | 2027-11-16   |
| Measurement Software      | AUDIX                | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Coaxial Cable             | SGS                  | N/A             | SEM029-01     | 2025-07-05 | 2026-07-04   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch  
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558906

Page: 9 of 34

| Frequency tolerance                         |                              |               |               |            |              |
|---------------------------------------------|------------------------------|---------------|---------------|------------|--------------|
| Equipment                                   | Manufacturer                 | Model No.     | Inventory No. | Cal Date   | Cal Due Date |
| DC Power Supply                             | Zhao Xin                     | PS-305D       | SEM011-13     | 2025-07-24 | 2026-07-23   |
| Spectrum Analyzer                           | Rohde & Schwarz              | FSP30         | SEM004-06     | 2025-09-10 | 2026-09-09   |
| Measurement Software                        | TST PASS                     | TST PASS V2.0 | N/A           | N/A        | N/A          |
| Coaxial Cable                               | SGS                          | N/A           | SEM031-01     | 2025-07-05 | 2026-07-04   |
| Attenuator                                  | Huber+Suhner                 | 6620_SMA-50-1 | SEM021-09     | 2025-03-03 | 2026-03-02   |
| Programmable Temperature & Humidity Chamber | Votsch Industrietechnik GmbH | VT 4002       | SEM002-15     | 2025-02-26 | 2026-02-25   |

| Radiated Emissions (9kHz-30MHz) |                      |                 |               |            |              |
|---------------------------------|----------------------|-----------------|---------------|------------|--------------|
| Equipment                       | Manufacturer         | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| 10m Semi-Anechoic Chamber       | SAEMC                | FSAC1018        | SEM001-03     | 2025-03-21 | 2026-03-20   |
| MXE EMI receiver                | KEYSIGHT             | N9038A          | SEM004-16     | 2025-07-25 | 2026-07-24   |
| Trilog-Broadband Antenna        | Schwarzbeck          | VULB9168        | SEM003-18     | 2025-08-29 | 2027-08-28   |
| Pre-amplifier                   | Sonoma Instrument Co | 310N            | SEM005-04     | 2025-03-04 | 2026-03-03   |
| Loop Antenna                    | ETS-Lindgren         | 6502            | SEM003-08     | 2025-11-17 | 2027-11-16   |
| Measurement Software            | AUDIX                | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Coaxial Cable                   | SGS                  | N/A             | SEM029-01     | 2025-07-05 | 2026-07-04   |

| Radiated Emissions (30MHz-1GHz) |                      |                 |               |            |              |
|---------------------------------|----------------------|-----------------|---------------|------------|--------------|
| Equipment                       | Manufacturer         | Model No.       | Inventory No. | Cal Date   | Cal Due Date |
| 3m Semi-Anechoic Chamber        | ETS-LINDGREN         | N/A             | SEM001-01     | 2023-06-19 | 2026-06-18   |
| MXE EMI Receiver                | Agilent Technologies | N9038A          | SEM004-15     | 2025-07-25 | 2026-07-24   |
| BiConiLog Antenna               | ETS-LINDGREN         | 3142C           | SEM003-01     | 2025-08-29 | 2027-08-28   |
| Pre-Amplifier                   | Agilent Technologies | 8447D           | SEM005-01     | 2025-03-04 | 2026-03-03   |
| Measurement Software            | AUDIX                | e3 V8.2014-6-27 | N/A           | N/A        | N/A          |
| Coaxial Cable                   | SGS                  | N/A             | SEM025-01     | 2025-07-05 | 2026-07-04   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558906

Page: 10 of 34

| General used equipment          |                                           |           |               |            |              |
|---------------------------------|-------------------------------------------|-----------|---------------|------------|--------------|
| Equipment                       | Manufacturer                              | Model No. | Inventory No. | Cal Date   | Cal Due Date |
| Humidity/ Temperature Indicator | deli                                      | 8838      | SEM002-32     | 2025-07-23 | 2026-07-22   |
| Humidity/ Temperature Indicator | deli                                      | 8838      | SEM002-33     | 2025-07-23 | 2026-07-22   |
| Barometer                       | Changchun Meteorological Industry Factory | DYM3      | SEM002-01     | 2025-03-03 | 2026-03-02   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (Shenzhen) Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

#### 6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement.

Antenna location: Refer to Internal photos



## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at Mains Terminals (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2020) Section 6.2

Test Engineer: Mason Wu

Limit:

| Frequency range (MHz) | Limit (dBuV) |           |
|-----------------------|--------------|-----------|
|                       | Quasi-peak   | Average   |
| 0.15-0.5              | 66 to 56*    | 56 to 46* |
| 0.5-5                 | 56           | 46        |
| 5-30                  | 60           | 50        |

\* Decreases with the logarithm of the frequency.

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25.3 °C


Humidity: 40.5 % RH

Atmospheric Pressure: 1020 mbar

#### 7.1.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description             |
|-----------------------|-----------|-------------------------|
| Final test            | 09        | TX mode with modulation |

#### 7.1.3 Test Setup Diagram






## 7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: Level=Read Level+ Cable Loss+ LISN Factor



Test Mode: 09; Line: Live line




Site : Shielding Room  
Condition: Line  
Job No. : 05589AT/05590AT  
Test mode: 09  
: 1#

|     | Freq    | Cable Loss | LISN Factor | Read Level | Limit Level | Limit Line | Over Limit | Remark  |
|-----|---------|------------|-------------|------------|-------------|------------|------------|---------|
|     | MHz     | dB         | dB          | dBuV       | dBuV        | dBuV       | dB         |         |
| 1 * | 0.1641  | 0.06       | 10.17       | 14.01      | 24.24       | 65.25      | -41.01     | QP      |
| 2 * | 0.1641  | 0.06       | 10.17       | 2.42       | 12.65       | 55.25      | -42.60     | Average |
| 3   | 0.4837  | 0.09       | 9.56        | 0.82       | 10.47       | 56.27      | -45.80     | QP      |
| 4   | 0.4837  | 0.09       | 9.56        | -8.40      | 1.25        | 46.27      | -45.02     | Average |
| 5   | 1.2488  | 0.11       | 9.58        | -0.63      | 9.06        | 56.00      | -46.94     | QP      |
| 6   | 1.2488  | 0.11       | 9.58        | -8.82      | 0.87        | 46.00      | -45.13     | Average |
| 7   | 1.8386  | 0.12       | 9.58        | -4.55      | 5.15        | 56.00      | -50.85     | QP      |
| 8   | 1.8386  | 0.12       | 9.58        | -10.37     | -0.67       | 46.00      | -46.67     | Average |
| 9   | 3.9639  | 0.14       | 9.66        | -1.10      | 8.70        | 56.00      | -47.30     | QP      |
| 10  | 3.9639  | 0.14       | 9.66        | -7.01      | 2.79        | 46.00      | -43.21     | Average |
| 11  | 22.5354 | 0.22       | 10.23       | 5.28       | 15.73       | 60.00      | -44.27     | QP      |
| 12  | 22.5354 | 0.22       | 10.23       | -5.14      | 5.31        | 50.00      | -44.69     | Average |



Test Mode: 09; Line: Neutral Line



Site : Shielding Room  
Condition: Neutral  
Job No. : 05589AT/05590AT  
Test mode: 09  
: 1#

|     | Freq    | Cable Loss | LISN Factor | Read Level | Limit Level | Limit Line | Over Limit | Remark  |
|-----|---------|------------|-------------|------------|-------------|------------|------------|---------|
|     | MHz     | dB         | dB          | dBuV       | dBuV        | dBuV       | dB         |         |
| 1 * | 0.1904  | 0.07       | 10.09       | 11.03      | 21.19       | 64.02      | -42.83     | QP      |
| 2 * | 0.1904  | 0.07       | 10.09       | 0.71       | 10.87       | 54.02      | -43.15     | Average |
| 3   | 0.3872  | 0.09       | 9.74        | 1.54       | 11.37       | 58.12      | -46.75     | QP      |
| 4   | 0.3872  | 0.09       | 9.74        | -4.96      | 4.87        | 48.12      | -43.25     | Average |
| 5   | 1.0050  | 0.11       | 9.54        | -0.08      | 9.57        | 56.00      | -46.43     | QP      |
| 6   | 1.0050  | 0.11       | 9.54        | -7.22      | 2.43        | 46.00      | -43.57     | Average |
| 7   | 1.6363  | 0.12       | 9.55        | -3.98      | 5.69        | 56.00      | -50.31     | QP      |
| 8   | 1.6363  | 0.12       | 9.55        | -10.69     | -1.02       | 46.00      | -47.02     | Average |
| 9   | 5.0046  | 0.14       | 9.56        | -0.51      | 9.19        | 60.00      | -50.81     | QP      |
| 10  | 5.0046  | 0.14       | 9.56        | -7.55      | 2.15        | 50.00      | -47.85     | Average |
| 11  | 22.2979 | 0.21       | 10.29       | 6.14       | 16.64       | 60.00      | -43.36     | QP      |
| 12  | 22.2979 | 0.21       | 10.29       | -3.88      | 6.62        | 50.00      | -43.38     | Average |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

### 7.2 20dB Bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.215  
 Test Method: ANSI C63.10 (2020) Section 6.9  
 Test Engineer: Linvo Ding


#### 7.2.1 E.U.T. Operation

Operating Environment:  
 Temperature: 21.1 °C Humidity: 63.3 % RH Atmospheric Pressure: 1020 mbar

#### 7.2.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description             |
|-----------------------|-----------|-------------------------|
| Final test            | 09        | TX mode with modulation |

#### 7.2.3 Test Setup Diagram



#### 7.2.4 Measurement Procedure and Data

The useful radiated emission from the EUT was detected by the spectrum analyser with peak detector.






## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558906

Page: 17 of 34

| $f_L$ (MHz) | $f_H$ (MHz) | $f_c$ (MHz) | Limit(MHz)       | Result |
|-------------|-------------|-------------|------------------|--------|
| 13.559600   | 13.560380   | 13.559988   | 13.553 to 13.567 | PASS   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Inspection & Testing Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



### 7.3 Emission Mask

Test Requirement 47 CFR Part 15, Subpart C 15.225(a)&(b)&(C )  
 Test Method: ANSI C63.10 (2020) Section 6.4  
 Measurement Distance: 3m  
 Test Engineer: Ted Wu

Limit:

The field strength of any emission shall not exceed the following limits:

- (a) 15.848 millivolts/m (84 dB  $\mu$  V/m) at 30 m, within the band 13.553-13.567 MHz.
- (b) 334 microvolts/m (50.5 dB  $\mu$  V/m) at 30 m, within the bands 13.410-13.553 MHz and 13.567-13.710 MHz.
- (c) 106 microvolts/m (40.5 dB  $\mu$  V/m) at 30 m, within the bands 13.110-13.410 MHz and 13.710-14.010 MHz.
- (d) 30 microvolts/m (29.5 dB  $\mu$  V/m) at 30 m, outside the band 13.110-14.010 MHz.

#### Below 30MHz

The limit at 3m test distance is below:

$$FS_{\text{limit}} = FS_{\text{max}} - 40 \log \left( \frac{d_{\text{limit}}}{d_{\text{measure}}} \right)$$

where

$FS_{\text{limit}}$  is the calculation of field strength at the limit distance, expressed in dB $\mu$ V/m  
 $FS_{\text{max}}$  is the measured field strength, expressed in dB $\mu$ V/m  
 $d_{\text{measure}}$  is the distance of the measurement point from the EUT  
 $d_{\text{limit}}$  is the reference distance or the distance of the  $\lambda/2\pi$  point

The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 124dB $\mu$ V/m at 3 meters.

#### 7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 23.6  $^{\circ}$ C Humidity: 46.5 % RH Atmospheric Pressure: 1020 mbar

#### 7.3.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description             |
|-----------------------|-----------|-------------------------|
| Final test            | 09        | TX mode with modulation |




### 7.3.3 Test Setup Diagram



### 7.3.4 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.





Condition: 3m


Job No. : 05589AT

Test Mode: 09

: coplanar

|   |      | Read   | Ant    | Cable | Preamp |        | Limit  | Over   |           |
|---|------|--------|--------|-------|--------|--------|--------|--------|-----------|
|   | Freq | Level  | Factor | Loss  | Factor | Level  | Line   | Limit  | Remark    |
|   | MHz  | dBuV   | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |           |
| 1 | pp   | 13.560 | 87.57  | 8.55  | 1.00   | 32.46  | 64.66  | 124.00 | -59.34 QP |





Condition: 3m

Job No. : 05589AT

Test Mode: 09

: coaxial

|   |      | Read   | Ant    | Cable | Preamp |        | Limit  | Over             |
|---|------|--------|--------|-------|--------|--------|--------|------------------|
|   | Freq | Level  | Factor | Loss  | Factor | Level  | Line   | Limit Remark     |
|   | MHz  | dBuV   | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB               |
| 1 | pp   | 13.560 | 89.36  | 8.55  | 1.00   | 32.46  | 66.45  | 124.00 -57.55 QP |





### 7.4 Frequency tolerance

Test Requirement 47 CFR Part 15, Subpart C 15.225(e)  
 Test Method: ANSI C63.10 (2020) Section 6.8  
 Test Engineer: Linvo Ding

Limit:  
 $\pm 0.01\%$


#### 7.4.1 E.U.T. Operation

Operating Environment:  
 Temperature: 21.1 °C Humidity: 63.3 % RH Atmospheric Pressure: 1020 mbar

#### 7.4.2 Test Mode Description

| Pre-scan /<br>Final test | Mode<br>Code | Description             |
|--------------------------|--------------|-------------------------|
| Final test               | 09           | TX mode with modulation |

#### 7.4.3 Test Setup Diagram



#### 7.4.4 Measurement Procedure and Data

The EUT was placed in an environmental test chamber and powered such that control element received normal voltage and the transmitter provided maximum RF output.



## SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558906

Page: 23 of 34

| Temperature (°C) | Voltage(VAC) | Measurement Frequency(MHz) | Frequency Tolerance (%) | Limit (%) | Result |
|------------------|--------------|----------------------------|-------------------------|-----------|--------|
| 50               | 120          | 13.559989                  | -0.000081               | ±0.01     | Pass   |
| 40               |              | 13.559986                  | -0.000103               |           | Pass   |
| 30               |              | 13.559988                  | -0.000088               |           | Pass   |
| 20               |              | 13.559988                  | -0.000088               |           | Pass   |
| 10               |              | 13.559988                  | -0.000088               |           | Pass   |
| 0                |              | 13.559988                  | -0.000088               |           | Pass   |
| -10              |              | 13.559989                  | -0.000081               |           | Pass   |
| -20              |              | 13.559988                  | -0.000088               |           | Pass   |
| 20               | 138          | 13.559989                  | -0.000081               |           | Pass   |
|                  | 102          | 13.559989                  | -0.000081               |           | Pass   |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch Testing & Calibration Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

## 7.5 Radiated Emissions (9kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209  
 Test Method: ANSI C63.10 (2020) Section 6.4  
 Measurement Distance: 3m  
 Test Engineer: Ted Wu

Limit:

| Frequency(MHz) | Field strength (microvolts/meter) | Limit (dBuV/m) | Detector | Measurement Distance (meters) |
|----------------|-----------------------------------|----------------|----------|-------------------------------|
| 0.009-0.490    | 2400/F(kHz)                       | -              | -        | 300                           |
| 0.490-1.705    | 24000/F(kHz)                      | -              | -        | 30                            |
| 1.705-30       | 30                                | -              | -        | 30                            |

Note:

At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Remark:

1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

### 7.5.1 E.U.T. Operation

Operating Environment:


Temperature: 23.6 °C Humidity: 46.5 % RH Atmospheric Pressure: 1020 mbar

### 7.5.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description             |
|-----------------------|-----------|-------------------------|
| Final test            | 09        | TX mode with modulation |



### 7.5.3 Test Setup Diagram




### 7.5.4 Measurement Procedure and Data

For testing performed with the loop antenna, the center of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT. During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane. Only the worst position of vertical was shown in the report.







Condition: 3m


Job No. : 05589AT

Test Mode: 09

: coaxial

|      |       | Read  | Ant    | Cable | Preamp |        | Limit  | Over   |         |
|------|-------|-------|--------|-------|--------|--------|--------|--------|---------|
|      | Freq  | Level | Factor | Loss  | Factor | Level  | Line   | Limit  | Remark  |
|      | MHz   | dBuV  | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |         |
| 1    | 0.012 | 69.67 | 17.45  | 0.10  | 31.28  | 55.94  | 126.23 | -70.29 | Average |
| 2 pp | 0.013 | 70.64 | 16.84  | 0.11  | 31.36  | 56.23  | 125.28 | -69.05 | Average |
| 3    | 0.014 | 70.15 | 16.47  | 0.11  | 31.40  | 55.33  | 124.74 | -69.41 | Average |





Condition: 3m

Job No. : 05589AT


Test Mode: 09

: coaxial

|      |       | Read  | Ant    | Cable | Preamp |        | Limit  | Over   |         |
|------|-------|-------|--------|-------|--------|--------|--------|--------|---------|
|      | Freq  | Level | Factor | Loss  | Factor | Level  | Line   | Limit  | Remark  |
|      | MHz   | dBuV  | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |         |
| 1 av | 0.154 | 71.37 | 10.50  | 0.14  | 32.40  | 49.61  | 103.85 | -54.24 | Average |
| 2 pp | 0.518 | 62.91 | 10.37  | 0.28  | 32.51  | 41.05  | 73.31  | -32.26 | QP      |
| 3    | 0.595 | 61.53 | 10.36  | 0.30  | 32.53  | 39.66  | 72.11  | -32.45 | QP      |

| Frequency (MHz) | Level @ 3m (dBuV/m) | Factor (dB) | Level @ 300m (dBuV/m) | Level @ 30m (dBuV/m) | Limit @ 300m (dBuV/m) | Limit @ 30m (dBuV/m) | Margin (dB) |
|-----------------|---------------------|-------------|-----------------------|----------------------|-----------------------|----------------------|-------------|
| 0.012           | 55.94               | 80.00       | -24.06                | -                    | 46.02                 | -                    | -70.08      |
| 0.013           | 56.23               | 80.00       | -23.77                | -                    | 45.33                 | -                    | -69.10      |
| 0.014           | 55.33               | 80.00       | -24.67                | -                    | 44.68                 | -                    | -69.35      |
| 0.154           | 49.61               | 80.00       | -30.39                | -                    | 23.85                 | -                    | -54.24      |
| 0.518           | 41.05               | 40.00       | -                     | 1.05                 | -                     | 33.32                | -32.27      |
| 0.595           | 39.66               | 40.00       | -                     | -0.34                | -                     | 32.11                | -32.45      |





Condition: 3m


Job No. : 05589AT

Test Mode: 09

: coplanar

|      |       | Read  | Ant    | Cable | Preamp |        | Limit  | Over   |         |
|------|-------|-------|--------|-------|--------|--------|--------|--------|---------|
|      | Freq  | Level | Factor | Loss  | Factor | Level  | Line   | Limit  | Remark  |
|      | MHz   | dBuV  | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |         |
| 1    | 0.012 | 70.68 | 17.46  | 0.10  | 31.28  | 56.96  | 126.25 | -69.29 | Average |
| 2    | 0.015 | 69.87 | 16.10  | 0.11  | 31.44  | 54.64  | 124.23 | -69.59 | Average |
| 3 pp | 0.023 | 70.67 | 13.26  | 0.11  | 31.76  | 52.28  | 120.34 | -68.06 | Average |





Condition: 3m

Job No. : 05589AT

Test Mode: 09

: coplanar

|   |      | Read  | Ant    | Cable | Preamp |        | Limit  | Over   |                |
|---|------|-------|--------|-------|--------|--------|--------|--------|----------------|
|   | Freq | Level | Factor | Loss  | Factor | Level  | Line   | Limit  | Remark         |
|   | MHz  | dBuV  | dB/m   | dB    | dB     | dBuV/m | dBuV/m | dB     |                |
| 1 | av   | 0.159 | 72.14  | 10.49 | 0.15   | 32.40  | 50.38  | 103.57 | -53.19 Average |
| 2 |      | 0.582 | 60.66  | 10.36 | 0.30   | 32.52  | 38.80  | 72.29  | -33.49 QP      |
| 3 | pp   | 0.739 | 59.46  | 10.35 | 0.32   | 32.56  | 37.57  | 70.21  | -32.64 QP      |

| Frequency (MHz) | Level @ 3m (dBuV/m) | Factor (dB) | Level @ 300m (dBuV/m) | Level @ 30m (dBuV/m) | Limit @ 300m (dBuV/m) | Limit @ 30m (dBuV/m) | Margin (dB) |
|-----------------|---------------------|-------------|-----------------------|----------------------|-----------------------|----------------------|-------------|
| 0.012           | 56.96               | 80.00       | -23.04                | -                    | 46.02                 | -                    | -69.06      |
| 0.015           | 54.64               | 80.00       | -25.36                | -                    | 44.08                 | -                    | -69.44      |
| 0.023           | 52.28               | 80.00       | -27.72                | -                    | 40.37                 | -                    | -68.09      |
| 0.159           | 50.38               | 80.00       | -29.62                | -                    | 23.58                 | -                    | -53.20      |
| 0.582           | 38.80               | 40.00       | -                     | -1.20                | -                     | 32.31                | -33.51      |
| 0.739           | 37.57               | 40.00       | -                     | -2.43                | -                     | 30.23                | -32.66      |





# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/2

Report No.: SZCR251200558906

Page: 30 of 34

## 7.6 Radiated Emissions (30MHz-1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.225(d) & 15.209  
 Test Method: ANSI C63.10 (2020) Section 6.5  
 Measurement Distance: 3m  
 Test Engineer: Mason Wu

Limit:

| Frequency(MHz) | Field strength(microvolts/meter) | Measurement distance(meters) |
|----------------|----------------------------------|------------------------------|
| 30-88          | 100                              | 3                            |
| 88-216         | 150                              | 3                            |
| 216-960        | 200                              | 3                            |
| Above 960      | 500                              | 3                            |

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 23.3 °C Humidity: 47.5 % RH Atmospheric Pressure: 1020 mbar

### 7.6.2 Test Mode Description

| Pre-scan / Final test | Mode Code | Description             |
|-----------------------|-----------|-------------------------|
| Final test            | 09        | TX mode with modulation |



SGS-CSTC Standards Technical Services Co., Ltd.  
 Shenzhen Branch Inspection & Testing Laboratory


Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



### 7.6.3 Test Setup Diagram




### 7.6.4 Measurement Procedure and Data

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground for below 1GHz at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report. Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Test Mode: 09; Polarity: Horizontal



Site : chamber

Condition: 3m HORIZONTAL


Job No. : 05589AT/05590AT

Test Mode: 09

|      | Ant     | Cable | Preamp | Read  |        | Limit  | Over  |           |
|------|---------|-------|--------|-------|--------|--------|-------|-----------|
| Freq | Factor  | Loss  | Factor | Level | Level  | Line   | Limit | Remark    |
| MHz  | dB/m    | dB    | dB     | dBuV  | dBuV/m | dBuV/m | dB    |           |
| 1    | 30.638  | 20.90 | 0.75   | 27.65 | 23.95  | 17.95  | 40.00 | -22.05 QP |
| 2    | 88.964  | 11.61 | 1.17   | 27.61 | 28.02  | 13.19  | 43.50 | -30.31 QP |
| 3    | 152.130 | 13.28 | 1.51   | 27.72 | 33.05  | 20.12  | 43.50 | -23.38 QP |
| 4    | 271.325 | 17.09 | 2.01   | 27.57 | 31.71  | 23.24  | 46.00 | -22.76 QP |
| 5    | 696.857 | 25.88 | 3.40   | 27.84 | 27.66  | 29.10  | 46.00 | -16.90 QP |
| 6 q  | 932.272 | 28.16 | 4.04   | 26.78 | 24.69  | 30.11  | 46.00 | -15.89 QP |



Test Mode: 09; Polarity: Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : 05589AT/05590AT

Test Mode: 09

|     | Ant     | Cable  | Preamp | Read   |       | Limit  | Over   |              |
|-----|---------|--------|--------|--------|-------|--------|--------|--------------|
|     | Freq    | Factor | Loss   | Factor | Level | Level  | Line   | Limit Remark |
|     | MHz     | dB/m   | dB     | dB     | dBuV  | dBuV/m | dBuV/m | dB           |
| 1   | 30.211  | 21.10  | 0.74   | 27.65  | 27.14 | 21.33  | 40.00  | -18.67 QP    |
| 2   | 76.781  | 10.39  | 1.06   | 27.61  | 37.48 | 21.32  | 40.00  | -18.68 QP    |
| 3   | 121.549 | 11.03  | 1.36   | 27.66  | 38.50 | 23.23  | 43.50  | -20.27 QP    |
| 4   | 382.588 | 20.90  | 2.43   | 27.71  | 25.16 | 20.78  | 46.00  | -25.22 QP    |
| 5   | 679.960 | 25.86  | 3.35   | 27.88  | 25.21 | 26.54  | 46.00  | -19.46 QP    |
| 6 q | 881.407 | 27.76  | 3.93   | 27.08  | 25.74 | 30.35  | 46.00  | -15.65 QP    |



## 8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2512005589AT

## 9 EUT Constructional Details (EUT Photos)

Refer to Appendix – External and Internal Photos for SZCR2512005589AT

- End of the Report -