

1. Effective (Isotropic) Radiated Power Output Data

1.1 Test Result

1.1.1 Band4_EIRP

Band: 4								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	EIRP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	RMC	12.2kbps RMC	1712.4	24.32	3.57	27.89	<=30	Pass
			1732.6	23.94	3.57	27.51	<=30	Pass
			1752.6	23.71	3.57	27.28	<=30	Pass
	HSDPA	Subtest 1	1712.4	22.72	3.57	26.29	<=30	Pass
		Subtest 2	1712.4	22.60	3.57	26.17	<=30	Pass
		Subtest 3	1712.4	22.61	3.57	26.18	<=30	Pass
		Subtest 4	1712.4	22.63	3.57	26.20	<=30	Pass
		Subtest 1	1732.6	22.28	3.57	25.85	<=30	Pass
		Subtest 2	1732.6	22.40	3.57	25.97	<=30	Pass
		Subtest 3	1732.6	22.34	3.57	25.91	<=30	Pass
		Subtest 4	1732.6	22.33	3.57	25.90	<=30	Pass
		Subtest 1	1752.6	21.91	3.57	25.48	<=30	Pass
		Subtest 2	1752.6	21.88	3.57	25.45	<=30	Pass
		Subtest 3	1752.6	21.78	3.57	25.35	<=30	Pass
		Subtest 4	1752.6	21.82	3.57	25.39	<=30	Pass
	HSUPA	Subtest 1	1712.4	20.41	3.57	23.98	<=30	Pass
		Subtest 2	1712.4	20.75	3.57	24.32	<=30	Pass
		Subtest 3	1712.4	20.73	3.57	24.30	<=30	Pass
		Subtest 4	1712.4	19.96	3.57	23.53	<=30	Pass
		Subtest 5	1712.4	19.45	3.57	23.02	<=30	Pass
		Subtest 1	1732.6	19.83	3.57	23.40	<=30	Pass
		Subtest 2	1732.6	20.35	3.57	23.92	<=30	Pass
		Subtest 3	1732.6	20.41	3.57	23.98	<=30	Pass
		Subtest 4	1732.6	19.63	3.57	23.20	<=30	Pass
		Subtest 5	1732.6	19.14	3.57	22.71	<=30	Pass
		Subtest 1	1752.6	19.24	3.57	22.81	<=30	Pass
		Subtest 2	1752.6	22.15	3.57	25.72	<=30	Pass
		Subtest 3	1752.6	22.13	3.57	25.70	<=30	Pass
		Subtest 4	1752.6	21.46	3.57	25.03	<=30	Pass
		Subtest 5	1752.6	21.08	3.57	24.65	<=30	Pass

Note1: EIRP=Conducted Power+Antenna Gain