

1. Effective (Isotropic) Radiated Power Output Data

1.1 Test Result

1.1.1 Band5_ERP

Band: 5								
ENV	Mode		Frequency (MHz)	Conducted Power (dBm)	Gain (dBi)	ERP (dBm)		Verdict
	Network	Subset				Result	Limit	
NTNV	RMC	12.2kbps RMC	826.4	23.34	-0.36	20.83	<=38.45	Pass
			836.6	23.26	-0.36	20.75	<=38.45	Pass
			846.6	23.16	-0.36	20.65	<=38.45	Pass
	HSDPA	Subtest 1	826.4	21.49	-0.36	18.98	<=38.45	Pass
		Subtest 2	826.4	21.41	-0.36	18.90	<=38.45	Pass
		Subtest 3	826.4	21.54	-0.36	19.03	<=38.45	Pass
		Subtest 4	826.4	21.58	-0.36	19.07	<=38.45	Pass
		Subtest 1	836.6	21.54	-0.36	19.03	<=38.45	Pass
		Subtest 2	836.6	21.50	-0.36	18.99	<=38.45	Pass
		Subtest 3	836.6	21.48	-0.36	18.97	<=38.45	Pass
		Subtest 4	836.6	21.44	-0.36	18.93	<=38.45	Pass
		Subtest 1	846.6	21.38	-0.36	18.87	<=38.45	Pass
		Subtest 2	846.6	21.44	-0.36	18.93	<=38.45	Pass
		Subtest 3	846.6	21.34	-0.36	18.83	<=38.45	Pass
		Subtest 4	846.6	21.48	-0.36	18.97	<=38.45	Pass
	HSUPA	Subtest 1	826.4	18.74	-0.36	16.23	<=38.45	Pass
		Subtest 2	826.4	19.31	-0.36	16.80	<=38.45	Pass
		Subtest 3	826.4	19.02	-0.36	16.51	<=38.45	Pass
		Subtest 4	826.4	18.90	-0.36	16.39	<=38.45	Pass
		Subtest 5	826.4	18.34	-0.36	15.83	<=38.45	Pass
		Subtest 1	836.6	19.25	-0.36	16.74	<=38.45	Pass
		Subtest 2	836.6	19.83	-0.36	17.32	<=38.45	Pass
		Subtest 3	836.6	19.21	-0.36	16.70	<=38.45	Pass
		Subtest 4	836.6	18.51	-0.36	16.00	<=38.45	Pass
		Subtest 5	836.6	18.82	-0.36	16.31	<=38.45	Pass
		Subtest 1	846.6	19.15	-0.36	16.64	<=38.45	Pass
		Subtest 2	846.6	19.10	-0.36	16.59	<=38.45	Pass
		Subtest 3	846.6	19.08	-0.36	16.57	<=38.45	Pass
		Subtest 4	846.6	18.77	-0.36	16.26	<=38.45	Pass
		Subtest 5	846.6	18.16	-0.36	15.65	<=38.45	Pass

Note1: ERP=Conducted Power+Antenna Gain-2.15