

# TEST REPORT

**Applicant:** FUJIAN LANDI COMMERCIAL EQUIPMENT CO., LTD.

**Address:** Building 17, Area A, Software Park, No. 89, Software Avenue, Gulou District, Fuzhou, Fujian, China. 350003

**Equipment Type:** Portable Data Terminal

**Model Name:** P30

**Brand Name:** LANDI

**FCC ID:** 2AG6N-P30A

**Test Standard:** 47 CFR Part 15 Subpart C  
ANSI C63.10-2020

**Sample Receipt Date:** Oct. 17, 2025

**Test Date:** Oct. 21, 2025 - Oct. 22, 2025

**Date of Issue:** Feb. 10, 2026

**ISSUED BY:**

Shanghai Tejet Communications Technology Co., Ltd. Testing Center



**Prepared by:** Tong Yingying    **Reviewed by:** Huang Chengkun    **Approved by:** Zhang Yanqing  
(Laboratory Manager)

Tong Yingying

Huang Chengkun

Zhang Yanqing

### Revision History

| Version        | Issue Date           | Revisions            |
|----------------|----------------------|----------------------|
| <u>Rev. 01</u> | <u>Feb. 10, 2026</u> | <u>Initial Issue</u> |

## TABLE OF CONTENTS

|                                                                          |    |
|--------------------------------------------------------------------------|----|
| 1 GENERAL INFORMATION .....                                              | 4  |
| 1.1 Test Laboratory .....                                                | 4  |
| 1.2 Test Location .....                                                  | 4  |
| 2 PRODUCT INFORMATION .....                                              | 5  |
| 2.1 Applicant Information .....                                          | 5  |
| 2.2 Manufacturer Information .....                                       | 5  |
| 2.3 General Description for Equipment under Test (EUT) .....             | 5  |
| 2.4 Technical Information .....                                          | 6  |
| 3 SUMMARY OF TEST RESULTS .....                                          | 7  |
| 3.1 Test Standards .....                                                 | 7  |
| 3.2 Verdict .....                                                        | 7  |
| 3.3 Decision Rule .....                                                  | 8  |
| 3.4 Test Uncertainty .....                                               | 8  |
| 4 GENERAL TEST CONFIGURATIONS .....                                      | 9  |
| 4.1 Test Environments .....                                              | 9  |
| 4.2 Description of Test Setup .....                                      | 10 |
| 5 TEST ITEMS .....                                                       | 12 |
| 5.1 Antenna Requirements .....                                           | 12 |
| 5.2 Emission Bandwidth .....                                             | 13 |
| 5.3 Field Strength of Fundamental Emissions and Radiated Emissions ..... | 15 |
| 5.4 Frequency Tolerance .....                                            | 17 |
| 5.5 Conducted Emission .....                                             | 18 |
| ANNEX A TEST RESULT .....                                                | 19 |
| A.1 Emission Bandwidth .....                                             | 19 |

|                                                   |    |
|---------------------------------------------------|----|
| A.2 Field Strength of Fundamental Emissions ..... | 21 |
| A.3 Radiated Emissions .....                      | 23 |
| A.4 Frequency Stability .....                     | 27 |
| A.5 Conducted Emissions .....                     | 29 |
| ANNEX B TEST SETUP PHOTOS .....                   | 32 |
| ANNEX C EUT EXTERNAL PHOTOS .....                 | 32 |
| ANNEX D EUT INTERNAL PHOTOS .....                 | 32 |

# 1 GENERAL INFORMATION

## 1.1 Test Laboratory

|         |                                                                                          |
|---------|------------------------------------------------------------------------------------------|
| Name    | Shanghai Tejet Communications Technology Co., Ltd. Testing Center                        |
| Address | 1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China |

## 1.2 Test Location

|                           |                                                                                                                                  |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Name                      | Shanghai Tejet Communications Technology Co., Ltd. Testing Center                                                                |
| Location                  | 1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China                                         |
| Accreditation Certificate | The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. |

## 2 PRODUCT INFORMATION

### 2.1 Applicant Information

|           |                                                                                                            |
|-----------|------------------------------------------------------------------------------------------------------------|
| Applicant | FUJIAN LANDI COMMERCIAL EQUIPMENT CO., LTD.                                                                |
| Address   | Building 17, Area A, Software Park, No. 89, Software Avenue, Gulou District, Fuzhou, Fujian, China. 350003 |

### 2.2 Manufacturer Information

|              |                                                                                                            |
|--------------|------------------------------------------------------------------------------------------------------------|
| Manufacturer | FUJIAN LANDI COMMERCIAL EQUIPMENT CO., LTD.                                                                |
| Address      | Building 17, Area A, Software Park, No. 89, Software Avenue, Gulou District, Fuzhou, Fujian, China. 350003 |

### 2.3 General Description for Equipment under Test (EUT)

|                                                                                                                                                                                     |                        |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| EUT Name                                                                                                                                                                            | Portable Data Terminal |
| Model Name Under Test                                                                                                                                                               | P30                    |
| Series Model Name                                                                                                                                                                   | N/A                    |
| Description of Model name differentiation                                                                                                                                           | N/A                    |
| Hardware Version                                                                                                                                                                    | FCC_V1.0.0             |
| Software Version                                                                                                                                                                    | FCC_V1.0.0             |
| Dimensions (Approx.)                                                                                                                                                                | N/A                    |
| Weight (Approx.)                                                                                                                                                                    | N/A                    |
| Note: The EUT has two configurations:<br>Configuration 1: with battery(2600mAh/3350mAh), adapter(5V 2A).<br>Configuration 2: without battery(adapter power supply), adapter(5V 4A). |                        |

## 2.4 Technical Information

|                                   |                                                                                                                                                              |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network and Wireless connectivity | 2G Network GSM 850/1900 MHz<br>3G Network WCDMA Band 2/4/5<br>4G Network FDD LTE Band 2/4/5/7<br>TDD LTE Band 38<br>Bluetooth, 2.4G WIFI, 5G WIFI, GNSS, NFC |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|

The requirement for the following technical information of the EUT was tested in this report:

|                         |                                                                                                                          |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Modulation Type         | ASK                                                                                                                      |
| Product Type            | <input checked="" type="checkbox"/> Mobile<br><input type="checkbox"/> Portable<br><input type="checkbox"/> Fix Location |
| Frequency Range         | 13.56 MHz                                                                                                                |
| Receiver Categorization | 3                                                                                                                        |
| Number of Channel       | 1                                                                                                                        |
| Tested Channel          | 1                                                                                                                        |
| Antenna Type            | Coil Antenna                                                                                                             |

### 3 SUMMARY OF TEST RESULTS

#### 3.1 Test Standards

| No. | Identity                 | Document Title                                                                                 |
|-----|--------------------------|------------------------------------------------------------------------------------------------|
| 1   | 47 CFR Part 15 Subpart C | Intentional Radiators                                                                          |
| 2   | ANSI C63.10-2020         | American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices |

#### 3.2 Verdict

| No. | Description                             | FCC Part No.        | Test Result | Verdict                |
|-----|-----------------------------------------|---------------------|-------------|------------------------|
| 1   | Antenna Requirement                     | 15.203              | --          | Pass <sup>Note 1</sup> |
| 2   | Emissions Bandwidth                     | 15.215              | ANNEX A.1   | Pass                   |
| 3   | Field Strength of Fundamental Emissions | 15.225(a)           | ANNEX A.2   | Pass                   |
| 4   | Radiated Emissions                      | 15.225(d)<br>15.209 | ANNEX A.3   | Pass                   |
| 5   | Frequency Stability                     | 15.225(e)           | ANNEX A.4   | Pass                   |
| 6   | Conducted Emission                      | 15.207              | ANNEX A.5   | Pass                   |

Note 1: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

Note 2: The EUT has two configurations. The configuration 1 has two batteries, the configuration 2 has no battery. And there's no changes of the PCB Layout. All configurations are tested, only the worst test data as the main in this report. After verification, the test data of configuration 1 is the worst.

### 3.3 Decision Rule

- ☐ No Need
- ☒ Use General Conformity Decision Rule (Consider uncertainty or not ☒ No ☐ Yes)
- ☐ Use Special Conformity Decision Rule (Consider uncertainty or not ☐ No ☐ Yes)

### 3.4 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

| Measurement                          | Value  |
|--------------------------------------|--------|
| Conducted emissions (150 kHz-30 MHz) | 2.6 dB |
| Radiated emissions (9 kHz-30 MHz)    | 4.3 dB |
| Radiated emissions (30 MHz-1 GHz)    | 4.4 dB |

## 4 GENERAL TEST CONFIGURATIONS


### 4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

|                            |                         |                |
|----------------------------|-------------------------|----------------|
| Relative Humidity          | 30% to 60%              |                |
| Atmospheric Pressure       | 100 kPa to 102 kPa      |                |
| Temperature                | NT (Normal Temperature) | +22°C to +24°C |
| Working Voltage of the EUT | NV (Normal Voltage)     | 7.2 V          |


## 4.2 Description of Test Setup

### 4.2.1 For Radiated Test (Below 30 MHz)




(Diagram 1)

### 4.2.2 For Radiated Test (30 MHz-1 GHz)



(Diagram 2)

## 4.2.3 For AC Power Supply Port Test



(Diagram 3)

## 5 TEST ITEMS

### 5.1 Antenna Requirements

#### 5.1.1 Relevant Standards

FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### 5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

| Protected Method                        | Description                            |
|-----------------------------------------|----------------------------------------|
| The antenna is embedded in the product. | An embedded-in antenna design is used. |

| Reference Documents | Item                              |
|---------------------|-----------------------------------|
| Photo               | Please refer EUT internal photos. |

## 5.2 Emission Bandwidth

### 5.2.1 Definition

15.215(c);

Intentional radiators operating under the alternative provisions to the general emission limits must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to "Sample". However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or "Max Hold") may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

### 5.2.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.2.3 Test Procedure

The 20dB bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 2 to 5 times the OBW

RBW = 1% to 5% the OBW

VBW  $\geq$  3RBW

Sweep = auto

Detector function = peak

Trace = max hold

The 99% emission bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while the EUT is operating in transmission mode.

Use the following spectrum analyzer settings:

Span = between 1.5 to 5 times the OBW

RBW = 1% to 5% OBW

VBW  $\geq$  3RBW

Sweep = auto

Detector function = peak

Trace = max hold

#### 5.2.4 Test Result

Please refer to ANNEX A.1

## 5.3 Field Strength of Fundamental Emissions and Radiated Emissions

### 5.3.1 Limit

FCC §15.225(a), (b), (c)

According to FCC section 15.225, for <30 MHz, Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 10 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 kHz. (Note: During testing the receive antenna was rotated about its axis to maximize the emission from the EUT)

There was no detected Restricted bands and Radiated spurious emission below 30MHz. The 30m limit was converted to 3m Limit using square factor(x) as it was found by measurements as follows; 3 m Limit(dBμV/m) = 20log(X)+40log(30/3)= 20log(15848)+40log(30/3) = 124dBμV

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency range<br>(MHz) | Field Strength@30m |        | Field Strength@10m | Field Strength@3m |
|--------------------------|--------------------|--------|--------------------|-------------------|
|                          | μV/m               | dBμV/m | dBμV/m             | dBμV/m            |
| Below 13.110             | 30                 | 29.5   | 48.58              | 69.5              |
| 13.110 ~ 13.410          | 106                | 40.5   | 59.58              | 80.5              |
| 13.410 ~ 13.553          | 334                | 50.5   | 69.58              | 90.5              |
| 13.553 ~13.567           | 15848              | 84     | 103.08             | 124               |
| 13.567 ~ 13.710          | 334                | 50.5   | 69.58              | 90.5              |
| 13.710 ~14.010           | 106                | 40.5   | 59.58              | 80.5              |
| Above 14.010             | 30                 | 29.5   | 48.58              | 69.5              |

NOTE:

1. Field Strength (dBμV/m) = 20\*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.

FCC §15.225(d)

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (μV/m) | Measurement distance (meters) |
|-----------------|-----------------------|-------------------------------|
| 0.009 - 0.490   | 2400/F(kHz)           | 300                           |
| 0.490 - 1.705   | 24000/F(kHz)          | 30                            |
| 1.705 - 30.0    | 30                    | 30                            |
| 30 - 88         | 100                   | 3                             |
| 88 - 216        | 150                   | 3                             |
| 216 - 960       | 200                   | 3                             |
| Above 960       | 500                   | 3                             |

Note:

1. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit.
2. For above 1000 MHz, limit field strength of harmonics: 54dB $\mu$ V/m@3m (AV) and 74dB $\mu$ V/m@3m (PK).

### 5.3.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.3.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented. The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz, 100 kHz for  $f < 1$  GHz

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

### 5.3.4 Test Result

Please refer to ANNEX A.2 and A.3

NOTE:

1. Results (dB $\mu$ V/m) = Reading (dB $\mu$ V/m) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Over limit = Results – Limit.

## 5.4 Frequency Tolerance

### 5.4.1 Limit

FCC §15.225(e)

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 5.4.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.4.3 Test Procedure

1. The test is performed in a Temperature Chamber.
2. The EUT is configured as MS + DC Power Supply.

### 5.4.4 Test Result

Please refer to ANNEX A.4.

## 5.5 Conducted Emission

### 5.5.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

| Frequency range (MHz) | Conducted Limit (dBμV) |          |
|-----------------------|------------------------|----------|
|                       | Quai-peak              | Average  |
| 0.15 - 0.50           | 66 to 56               | 56 to 46 |
| 0.50 - 5              | 56                     | 46       |
| 0.50 - 30             | 60                     | 50       |

### 5.5.2 Test Setup

See section 4.1.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

### 5.5.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

### 5.5.4 Test Result

Please refer to ANNEX A.5.

NOTE:

1. Results (dBμV) = Reading (dBμV) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Over limit = Results – Limit.

## ANNEX A TEST RESULT

### A.1 Emission Bandwidth

|               |                  |              |              |
|---------------|------------------|--------------|--------------|
| Sample No.    | SC-SZ2590837-S13 | Temperature  | 23.9°C       |
| Humidity      | 51%RH            | Test Voltage | AC 120V/60Hz |
| Test Engineer | Hao Longda       | Test Date    | 2025.10.21   |

#### Test Data

| Frequency<br>(MHz) | Emission Bandwidth(20dB down)<br>(kHz) | Occupied Bandwidth(99%)<br>(kHz) |
|--------------------|----------------------------------------|----------------------------------|
| 13.56075           | 31.64                                  | 23.626                           |

#### Test plots

##### Emission Bandwidth



##### 99% Occupied Bandwidth



| Equipment Information |              |               |               |            |            |                                     |
|-----------------------|--------------|---------------|---------------|------------|------------|-------------------------------------|
| Description           | Manufacturer | Model         | Equipment No. | Cal. Date  | Cal. Due   | Use                                 |
| EMI Receiver          | KEYSIGHT     | N9038A        | BH-EMC-L127   | 2025.02.12 | 2026.02.11 | <input checked="" type="checkbox"/> |
| Test Antenna-<br>Loop | SCHWARZBECK  | FMZB<br>1519B | BH-EMC-L067   | 2024.03.11 | 2027.03.10 | <input checked="" type="checkbox"/> |
| Anechoic<br>Chamber   | YiHeng       | 9m*6m*6m      | BH-EMC-L001   | 2024.04.18 | 2027.04.17 | <input checked="" type="checkbox"/> |

## A.2 Field Strength of Fundamental Emissions

Note: Field Strength of Fundamental Emissions tests were performed in X, Y, Z axis direction of EUT. And only the worst axis test condition was recorded in this test report.

|               |                  |              |              |
|---------------|------------------|--------------|--------------|
| Sample No.    | SC-SZ2590837-S13 | Temperature  | 23.9°C       |
| Humidity      | 51%RH            | Test Voltage | AC 120V/60Hz |
| Test Engineer | Hao Longda       | Test Date    | 2025.10.21   |


### Test Data

| Field Strength of Fundamental Emissions Value |          |                               |                          |        |             |
|-----------------------------------------------|----------|-------------------------------|--------------------------|--------|-------------|
| Frequency (MHz)                               | Detector | Field Strength (dB $\mu$ V/m) | Limit @3m (dB $\mu$ V/m) | EUT    | Margin (dB) |
| 13.560                                        | PEAK     | 82.86                         | 124.0                    | X axis | 41.14       |

### Test Plot

#### Test Antenna-LOOP, EUT X axis

RE Test case\_FCC 15.225\_FCC 15.225\_Mask



| Equipment Information |              |               |               |            |            |                                     |
|-----------------------|--------------|---------------|---------------|------------|------------|-------------------------------------|
| Description           | Manufacturer | Model         | Equipment No. | Cal. Date  | Cal. Due   | Use                                 |
| EMI Receiver          | KEYSIGHT     | N9038A        | BH-EMC-L127   | 2025.02.12 | 2026.02.11 | <input checked="" type="checkbox"/> |
| Test Antenna-<br>Loop | SCHWARZBECK  | FMZB<br>1519B | BH-EMC-L067   | 2024.03.11 | 2027.03.10 | <input checked="" type="checkbox"/> |
| Anechoic<br>Chamber   | YiHeng       | 9m*6m*6m      | BH-EMC-L001   | 2024.04.18 | 2027.04.17 | <input checked="" type="checkbox"/> |

## A.3 Radiated Emissions

Note 1: This frequency which near 13.560 MHz with circle should be ignored because they are NFC carrier frequency.


Note 2: All Radiated Emissions tests were performed in X, Y, Z axis direction of EUT. And only the worst axis test condition was recorded in this test report.

|               |                  |              |              |
|---------------|------------------|--------------|--------------|
| Sample No.    | SC-SZ2590837-S13 | Temperature  | 23.9°C       |
| Humidity      | 51%RH            | Test Voltage | AC 120V/60Hz |
| Test Engineer | Hao Longda       | Test Date    | 2025.10.21   |

### The Data and Plots (9 kHz ~ 30 MHz)(at 3m chamber)

Below 30 MHz, Test Antenna LOOP, EUT X axis

RE Test case\_FCC 15.225\_FCC 15.225\_9kHz-30MHz




| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Margin (dB) | Detector | Table (Degree) | Height (cm) | Antenna  | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|----------------|-------------|----------|---------|
| 1   | 0.058           | 73.22            | 19.19       | 112.3          | 39.08       | Peak     | 96.00          | 100         | Vertical | Pass    |
| 2   | 0.117           | 65.97            | 19.09       | 106.2          | 40.23       | Peak     | 87.00          | 100         | Vertical | Pass    |
| 3   | 0.239           | 56.68            | 19.01       | 100.0          | 43.32       | Peak     | 95.00          | 100         | Vertical | Pass    |
| 4   | 0.667           | 46.50            | 19.01       | 71.1           | 24.60       | Peak     | 81.00          | 100         | Vertical | Pass    |
| 5   | 2.203           | 36.98            | 19.31       | 69.5           | 32.52       | Peak     | 266.00         | 100         | Vertical | Pass    |
| 6   | 13.560          | 82.31            | 19.21       | 69.5           | -12.81      | Peak     | 175.00         | 100         | Vertical | N/A     |

| Equipment Information |              |            |              |            |            |                                     |
|-----------------------|--------------|------------|--------------|------------|------------|-------------------------------------|
| Description           | Manufacturer | Model      | Equipment No | Cal. Date  | Cal. Due   | Use                                 |
| EMI Receiver          | KEYSIGHT     | N9038A     | BH-EMC-L127  | 2025.02.12 | 2026.02.11 | <input checked="" type="checkbox"/> |
| Test Antenna-Loop     | SCHWARZBECK  | FMZB 1519B | BH-EMC-L067  | 2024.03.11 | 2027.03.10 | <input checked="" type="checkbox"/> |
| Anechoic Chamber      | YiHeng       | 9m*6m*6m   | BH-EMC-L001  | 2024.04.18 | 2027.04.17 | <input checked="" type="checkbox"/> |
| Description           | Manufacturer | Name       | Version      | /          |            | Use                                 |
| Test Software         | BALUN        | BL410-E    | V21.919      | /          |            | <input checked="" type="checkbox"/> |

## Test Data and Plots (30 MHz ~ 10th Harmonic)


### 30 MHz to 1 GHz, Test Antenna Vertical, EUT X axis

RE Test case\_FCC 15.225\_FCC 15.225\_30MHz-1GHz



| No. | Frequency (MHz) | Results (dBUV/m) | Factor (dB) | Limit (dBUV/m) | Margin (dB) | Detector | Table (Degree) | Height (cm) | Antenna  | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|----------------|-------------|----------|---------|
| 1   | 31.309          | 34.51            | -29.01      | 40.0           | 5.49        | Peak     | 198.00         | 100         | Vertical | Pass    |
| 2   | 51.049          | 35.49            | -24.61      | 40.0           | 4.51        | Peak     | 163.00         | 100         | Vertical | Pass    |
| 3   | 73.068          | 36.69            | -29.96      | 40.0           | 3.31        | Peak     | 0.00           | 100         | Vertical | Pass    |
| 4   | 133.839         | 29.33            | -29.26      | 43.5           | 14.17       | Peak     | 251.00         | 200         | Vertical | Pass    |
| 5   | 221.333         | 30.55            | -25.71      | 46.0           | 15.45       | Peak     | 194.00         | 100         | Vertical | Pass    |
| 6   | 887.044         | 30.57            | -9.77       | 46.0           | 15.43       | Peak     | 142.00         | 200         | Vertical | Pass    |

30 MHz to 1 GHz, Test Antenna Horizontal, EUT X axis



| No. | Frequency (MHz) | Results (dBuV/m) | Factor (dB) | Limit (dBuV/m) | Margin (dB) | Detector | Table (Degree) | Height (cm) | Antenna    | Verdict |
|-----|-----------------|------------------|-------------|----------------|-------------|----------|----------------|-------------|------------|---------|
| 1   | 72.292          | 30.04            | -29.78      | 40.0           | 9.96        | Peak     | 203.00         | 200         | Horizontal | Pass    |
| 2   | 130.395         | 33.29            | -29.08      | 43.5           | 10.21       | Peak     | 99.00          | 200         | Horizontal | Pass    |
| 3   | 225.358         | 37.10            | -25.36      | 46.0           | 8.90        | Peak     | 110.00         | 100         | Horizontal | Pass    |
| 4   | 289.087         | 25.22            | -23.21      | 46.0           | 20.78       | Peak     | 251.00         | 100         | Horizontal | Pass    |
| 5   | 539.977         | 27.72            | -17.18      | 46.0           | 18.28       | Peak     | 221.00         | 100         | Horizontal | Pass    |
| 6   | 898.829         | 30.87            | -9.31       | 46.0           | 15.13       | Peak     | 83.00          | 100         | Horizontal | Pass    |

| Radiated Emissions  |              |           |             |            |            |                                     |
|---------------------|--------------|-----------|-------------|------------|------------|-------------------------------------|
| Description         | Manufacturer | Model     | Serial No.  | Cal. Date  | Cal. Due   | Use                                 |
| EMI Receiver        | KEYSIGHT     | N9038A    | BH-EMC-L127 | 2025.02.12 | 2026.02.11 | <input checked="" type="checkbox"/> |
| Test Antenna-Bi-Log | SCHWARZBECK  | VULB 9163 | BH-EMC-L132 | 2024.03.11 | 2027.03.10 | <input checked="" type="checkbox"/> |
| Anechoic Chamber    | YiHeng       | 9m*6m*6m  | BH-EMC-L001 | 2024.04.18 | 2027.04.17 | <input checked="" type="checkbox"/> |
| Description         | Manufacturer | Name      |             | Version    |            | Use                                 |
| Test Software       | BALUN        | BL410-E   |             | V21.919    |            | <input checked="" type="checkbox"/> |

## A.4 Frequency Stability

Note 1: Because the 85%(6.12V) and 115% (8.28V)of the rated supply voltage value exceeds the cut-off voltage upper(8.4V) and lower(6V) limit of the manufacturer, the cut-off voltage of EUT is test here.

Note 2: The operating temperature range of the EUT is -20°C to 60°C.

|               |                  |              |              |
|---------------|------------------|--------------|--------------|
| Sample No.    | SC-SZ2590837-S13 | Temperature  | 23.9°C       |
| Humidity      | 51%RH            | Test Voltage | AC 120V/60Hz |
| Test Engineer | Hao Longda       | Test Date    | 2025.10.21   |

|                      |             |
|----------------------|-------------|
| OPERATING FREQUENCY: | 13560000 Hz |
| REFERENCE VOLTAGE:   | 7.2 V       |
| DEVIATION LIMIT:     | ±0.01%      |

| VOLTAGE (%)                 | Test Conditions |                  | Frequency(Hz) | Deviation(%) | Verdict |
|-----------------------------|-----------------|------------------|---------------|--------------|---------|
|                             | Power (VDC)     | Temperature (°C) |               |              |         |
| 100                         | 7.2             | -20              | 13560025      | 0.000184     | Pass    |
| 100                         |                 | -10              | 13559792      | -0.001534    |         |
| 100                         |                 | 0                | 13560000      | 0.000000     |         |
| 100                         |                 | +10              | 13559792      | -0.001534    |         |
| 100                         |                 | +20              | 13560000      | 0.000000     |         |
| 100                         |                 | +15              | 13560000      | 0.000000     |         |
| 100                         |                 | +30              | 13560000      | 0.000000     |         |
| 100                         |                 | +15              | 13560000      | 0.000000     |         |
| 100                         |                 | +60              | 13560000      | 0.000000     |         |
| 100                         |                 | +30              | 13560025      | 0.000184     |         |
| MAX(Battery End Point, 85)  | 6.12            | +20              | 13560025      | 0.000184     |         |
| MIN(Battery End Point, 115) | 8.28            | +60              | 13560000      | 0.000000     |         |

| Equipment Information  |              |               |               |            |            |                                     |
|------------------------|--------------|---------------|---------------|------------|------------|-------------------------------------|
| Description            | Manufacturer | Model         | Equipment No. | Cal. Date  | Cal. Due   | Use                                 |
| EMI Receiver           | KEYSIGHT     | N9038A        | BH-EMC-L127   | 2025.02.12 | 2026.02.11 | <input checked="" type="checkbox"/> |
| Test Antenna-<br>Loop  | SCHWARZBECK  | FMZB<br>1519B | BH-EMC-L067   | 2024.03.11 | 2027.03.10 | <input checked="" type="checkbox"/> |
| Temperature<br>Chamber | YOMA         | DTL-0035      | TJ8980-012    | 2025.04.12 | 2026.04.11 | <input checked="" type="checkbox"/> |
| Anechoic<br>Chamber    | YiHeng       | 9m*6m*6m      | BH-EMC-L001   | 2024.04.18 | 2027.04.17 | <input checked="" type="checkbox"/> |


## A.5 Conducted Emissions

Note 1: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz ) shown here.

|               |                  |              |              |
|---------------|------------------|--------------|--------------|
| Sample No.    | SC-SZ2590837-S13 | Temperature  | 22.2°C       |
| Humidity      | 52%RH            | Test Voltage | AC 120V/60Hz |
| Test Engineer | Tong Yingying    | Test Date    | 2025.10.22   |

### Test Data and Plots


#### PHASE L



| No. | Frequency (MHz) | Results (dBUV) | Factor (dB) | Limit (dBUV) | Margin (dB) | Detector | Line | Verdict |
|-----|-----------------|----------------|-------------|--------------|-------------|----------|------|---------|
| 1   | 0.178           | 52.37          | 10.09       | 64.58        | 12.21       | Peak     | L    | Pass    |
| 1** | 0.178           | 31.71          | 10.09       | 54.58        | 22.87       | AV       | L    | Pass    |
| 2   | 0.366           | 44.62          | 10.13       | 58.59        | 13.97       | Peak     | L    | Pass    |
| 2** | 0.366           | 25.55          | 10.13       | 48.59        | 23.04       | AV       | L    | Pass    |
| 3   | 0.682           | 43.36          | 10.22       | 56.00        | 12.64       | Peak     | L    | Pass    |
| 3** | 0.682           | 26.10          | 10.22       | 46.00        | 19.90       | AV       | L    | Pass    |
| 4   | 1.400           | 40.14          | 10.25       | 56.00        | 15.86       | Peak     | L    | Pass    |
| 4** | 1.400           | 24.23          | 10.25       | 46.00        | 21.77       | AV       | L    | Pass    |
| 5   | 3.780           | 39.18          | 10.41       | 56.00        | 16.82       | Peak     | L    | Pass    |
| 5** | 3.780           | 23.27          | 10.41       | 46.00        | 22.73       | AV       | L    | Pass    |
| 6   | 17.888          | 39.83          | 11.19       | 60.00        | 20.17       | Peak     | L    | Pass    |
| 6** | 17.888          | 22.27          | 11.19       | 50.00        | 27.73       | AV       | L    | Pass    |

## PHASE N

CE Test case\_FCC\_CE\_FCC PART 15C



| No. | Frequency (MHz) | Results (dBuV) | Factor (dB) | Limit (dBuV) | Margin (dB) | Detector | Line | Verdict |
|-----|-----------------|----------------|-------------|--------------|-------------|----------|------|---------|
| 1   | 0.178           | 55.78          | 10.15       | 64.58        | 8.80        | Peak     | N    | Pass    |
| 1** | 0.178           | 36.37          | 10.15       | 54.58        | 18.21       | AV       | N    | Pass    |
| 2   | 0.344           | 48.06          | 10.16       | 59.11        | 11.05       | Peak     | N    | Pass    |
| 2** | 0.344           | 28.50          | 10.16       | 49.11        | 20.61       | AV       | N    | Pass    |
| 3   | 0.648           | 46.31          | 10.21       | 56.00        | 9.69        | Peak     | N    | Pass    |
| 3** | 0.648           | 29.15          | 10.21       | 46.00        | 16.85       | AV       | N    | Pass    |
| 4   | 2.080           | 39.44          | 10.25       | 56.00        | 16.56       | Peak     | N    | Pass    |
| 4** | 2.080           | 23.23          | 10.25       | 46.00        | 22.77       | AV       | N    | Pass    |
| 5   | 4.654           | 39.57          | 10.41       | 56.00        | 16.43       | Peak     | N    | Pass    |
| 5** | 4.654           | 23.54          | 10.41       | 46.00        | 22.46       | AV       | N    | Pass    |
| 6   | 17.400          | 43.41          | 11.25       | 60.00        | 16.59       | Peak     | N    | Pass    |
| 6** | 17.400          | 27.92          | 11.25       | 50.00        | 22.08       | AV       | N    | Pass    |

| Equipment Information |              |                |               |            |            |                                     |
|-----------------------|--------------|----------------|---------------|------------|------------|-------------------------------------|
| Description           | Manufacturer | Model          | Equipment No. | Cal. Date  | Cal. Due   | Use                                 |
| EMI Receiver          | KEYSIGHT     | N9038A         | TJEMC144      | 2025.02.12 | 2026.02.11 | <input checked="" type="checkbox"/> |
| LISN                  | SCHWARZBECK  | NSLK 8127      | BH-EMC-L011   | 2025.02.11 | 2026.02.10 | <input checked="" type="checkbox"/> |
| 10dB Limiter          | SCHWARZBECK  | VTSD<br>9561-F | BH-EMC-L014   | 2025.02.11 | 2026.02.10 | <input checked="" type="checkbox"/> |
| Shielded Room         | YiHeng       | 5m*4m*3.2m     | BH-EMC-L006   | 2024.02.22 | 2027.02.21 | <input checked="" type="checkbox"/> |
| Description           | Manufacturer | Name           |               | Version    |            | Use                                 |
| Test Software         | BALUN        | BL410-E        |               | V19.618    |            | <input checked="" type="checkbox"/> |

## **ANNEX B TEST SETUP PHOTOS**

Please refer the document “BL-SZ25A0385-AE-1.PDF”.

## **ANNEX C EUT EXTERNAL PHOTOS**

Please refer the document “BL-SZ25A0385-AW.PDF”.

## **ANNEX D EUT INTERNAL PHOTOS**

Please refer the document “BL-SZ25A0385-AI.PDF”.

## Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--