

客户承认书

SPECIFICATION FOR APPROVAL

CUSTOMER/PROJECT 客户/机型: JSC-5U093B-WIFI

CUSTOMER P.N./ 客户物料号: _____

PRODUCT NAME./ 物料名称: WIFI Antenna

MODEL NO./ 物料型号: 5U093B

ANTENNA TYPE./ 天线类型: Cable+FPC Antenna

SPECIFICATION/ 物料规格: _____

VERSION 版本	DATE 日期	REVISION DESCRIPTION 修订说明
T:A	2026-05-08	新建/newly added
T:B	2026-05-15	更新图纸/Update drawings

SUPPLIER AUTHORIZED SIGNATURE/供应商承认签核			
制作/PREPARED	测试/TEST	审核/CHECKED	批准/APPROVED
徐海军 /XUHAIJUN	卓杨宁 /ZHUOYANGNING		

CUSTOMER AUTHORIZED SIGNATURE/客户承认签核			
项目 /Project		质量 /Quality	

Please return to us one copy of "SPECIFICATION FOR APPROVAL" with your approved signature./ 客户确认签字，盖章后请回传一份承认书给我司。

ADD: No.358 Liuyuan RD., Baoshan Urban Industrial District., Shanghai, PR.China.

杰盛康机密，未经允许，请勿转载

地址：上海市宝山城市工业园区柳园路358号2号楼1楼

TEL: +86-21-66276925(26/29/35) - 615

目录 content

目录/content	2
1 名词解释/Noun explanation	3
2 测试设备/Test equipment	4
3 适用频段/Working frequency band	5
4 基本测试项目/Test project	4
4.1 驻波比图/VSWR plot	5
4.2 史密斯阻抗图/Simth plot	5
4.3 辐射方向图/Radiation pattern	5
4.4 增益和效率/Gain & Efficiency	5
4.5 TRP&TIS测试	5
5 测试指标和数据图表/Antenna parameter	5
5.1 驻波比/VSWR	5
5.1.1 驻波比图/VSWR plot	5
5.1.2 驻波比数据/VSWR data	6
5.2 史密斯阻抗圆图/Simth plot	7
5.3 辐射方向图/Radiation pattern	8
5.3.1 H-plane	8
5.3.2 E-plane	9
5.4 增益和效率/UGain & Efficiency	11
5.5 TRP&TIS	11

杰盛康机密，未经允许，请勿转载

6_环境处理建议/Environmental treatment suggestions	12
7_阻抗匹配要求/Impedance matching	12
8_天线外形图/Antenna plan	12
8.1.天线尺寸图/ Antenna dimensional drawing	13
8.2 馈线尺寸图/Coaxial cable length drawing	13
8.3 射频端尺寸图/Connector drawing	13
9_天线安装指导/Antenna installation guide	14
9.1.天线安装说明/Antenna installation instructions	14
9.2 馈线走线说明/Coaxial routing	14
10_ 其他/Other	14

1 名词解释/Noun explanation

dBi	Decibel relative isotropic antenna
Tx	Transmit frequency
Rx	Receive frequency
TRP	Total Radiated Power
TIS	Total Isotropic Sensitivity
VSWR	Voltage Standing Wave Ratio
GSM	Global Service for Mobile communication
DCS	Digital Communication System
CDMA	Code Division Multiple Access
WCDMA	Wideband Code Division Multiple Access

杰盛康机密，未经允许，请勿转载

2 测试设备/Test equipment

测试系统/Test system: Rayzone 1800 OTA System

测试环境/Test environment: 温度/Temperature $22^{\circ}\text{C}\pm 3^{\circ}\text{C}$, 湿度/Humidity $50\%\pm 15\%$

测试设备/Test equipment: 测试无源数据时, 使用网络分析仪 Agilent E5071C

/When testing passive data, use the network analyzer Agilent E5071C

测试有源数据时, 使用综测仪 CMW500, Agilent 8960

/When testing active data, use the comprehensive tester CMW500 and Agilent 8960

设备校准日期/Equipment calibration date: 2025-06-12

到期日/Due date: 2026-06-11



3 适用频段/Working frequency band

将适用的频段用其他颜色标出/ The yellow Identification is the using band

制式/Standard	上行	下行
GSM850	824MHz~849MHz	869MHz~894MHz
GSM900	890MHz~915MHz	935MHz~960MHz
DCS1800	1710MHz~1785MHz	1805MHz~1880MHz
PCS1900	1850MHz~1910MHz	1930MHz~1990MHz
CDMA800	825MHz~835MHz	870MHz~880 MHz
CDMA2000	824MHz ~849MHz	869MHz ~894MHz
WCDMA2100	1920MHz~1980MHz	2110MHz~2170MHz
WIFI (2. 4G/5G)	2400MHz~5850MHz	2400MHz~5850MHz

4 基本测试项目/Test project

4.1 驻波比图/VSWR plot

4.2 史密斯阻抗图/Simth plot

4.3 辐射方向图/Radiation pattern

4.4 增益和效率/Gain & Efficiency


4.5 TRP&TIS

5 测试指标和数据图表/Antenna parameter

5.1 驻波比/VSWR

5.1.1 驻波比图/VSWR plot

杰盛康机密，未经允许，请勿转载



5.1.2 驻波比数据/VSWR data


Freq/MHz	2400	2500	5150	5850
VSWR	1.3	1.2	1.3	1.2

史密斯阻抗圆图/Smith impedance circle diagram




5.3 辐射方向图/Radiation pattern

5.3.1H-plane




5.4.2E-plane

E1



E2




5.4 增益和效率/Gain & Efficiency

Freq (MHZ)	Eff (%)	GAIN(DB i)		Freq (MHZ)	Eff (%)	GAIN(DB i)
2400	59.33	3.34		5150	44.49	1.48
2410	54.88	2.92		5250	48.76	2.33
2420	52.89	2.68		5350	46.89	0.67
2430	55.12	2.88		5450	50.09	1.26
2440	55.53	2.80		5550	47.30	1.16
2450	55.65	2.64		5650	52.66	1.32
2460	53.47	2.24		5750	52.68	1.58
2470	51.98	2.19		5850	56.28	2.94
2480	54.15	2.48				
2490	54.95	2.53				
2500	52.79	2.30				

6 环境处理建议/Environmental treatment suggestions


7 阻抗匹配要求/Impedance matching

8 天线外形图/Antenna plan



9 天线安装指导/Antenna installation guide

9.1 天线安装及馈线走线说明/Antenna installation instructions



10 其他/Other