



RF Exposure evaluation

Report Reference No..... GTS20250807004-4-06A

FCC ID. 2AG7C-BABY11-RAD

Compiled by

(position+printed File administrators Peter Xiao
name+signature)

Peter Xiao

Supervised by

(position+printed Test Engineer Evan Ouyang
name+signature)

Evan Ouyang

Approved by

(position+printed Manager Jason Hu
name+signature)

Jason Hu

Date of issue Dec.24, 2025



Representative Laboratory Name..... Shenzhen Global Test Service Co., Ltd.

Address No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden,
No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang
District, Shenzhen, Guangdong

Applicant's name..... Hangzhou Meari Technology Co., Ltd.

Address Building 4, Huiding Intelligent Innovation Center, No. 825, Ruquan Road,
Changhe Street, Binjiang District, Hangzhou, Zhejiang, China

Test specification

Standard..... **47CFR §1.1310 Basis and purpose**
47CFR §2.1091 Radiofrequency radiation exposure evaluation: mobile
devices
KDB447498 D01 General RF Exposure Guidance v06
TRF Originator..... Shenzhen Global Test Service Co.,Ltd.
Master TRF Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the
Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material.
Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages
resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description Baby Monitor

Trade Mark N/A

Manufacturer Hangzhou Meari Technology Co., Ltd.

Model/Type reference Baby 11Q

Listed Models Baby 11T, Baby 11F, Baby 11S, Baby 11TM, Baby 11QM, Baby 11FM, Baby
11SM, Baby 10Q, Baby 10F, Baby 10T, Baby 10S, Baby 10QM, Baby 10TM,
Baby 10SM, Baby 1Q, Baby 1T, Baby 1QM, Baby 1TM, Baby 6Q, Baby 6T,
Baby 6QM, Baby 6TM, Baby 2Q, Baby 2T, Baby 2QM, Baby 2TM, Baby 5T,
Baby 5F, Baby B8Q, Speed 31Q, Speed 31F, Alnanny-Cam, Alnanny D3,
Alnanny A4, Alnanny F2, Baby B7F, Baby B7FM, Baby B8QM

Hardware Version BABY11Q-T18MB-MIS4-REV1_0

Software Version N/A

Rating DC 5.0V by Adapter

Result **PASS**

Note: From the date of issue of this report, the original report GTS20250807004-4-06 is invalid.

TEST REPORT

Test Report No. :	GTS20250807004-4-06A	Dec.24, 2025
		Date of issue

Equipment under Test : Baby Monitor

Model /Type : Baby 11Q

Listed model : Baby 11T, Baby 11F, Baby 11S, Baby 11TM, Baby 11QM, Baby 11FM, Baby 11SM, Baby 10Q, Baby 10F, Baby 10T, Baby 10S, Baby 10QM, Baby 10TM, Baby 10SM, Baby 1Q, Baby 1T, Baby 1QM, Baby 1TM, Baby 6Q, Baby 6T, Baby 6QM, Baby 6TM, Baby 2Q, Baby 2T, Baby 2QM, Baby 2TM, Baby 5T, Baby 5F, Baby B8Q, Speed 31Q, Speed 31F, Alnanny-Cam, Alnanny D3, Alnanny A4, Alnanny F2, Baby B7F, Baby B7FM, Baby B8QM

Applicant : Hangzhou Meari Technology Co., Ltd.

Address : Building 4, Huiding Intelligent Innovation Center, No. 825, Ruquan Road, Changhe Street, Binjiang District, Hangzhou, Zhejiang, China

Manufacturer : Hangzhou Meari Technology Co., Ltd.

Address : 2nd to 4th Floor, Building 2 and 3rd to 4th Floor, Building 1, No. 91, Chutian Road, Xixing Street, Binjiang District, Hangzhou, Zhejiang, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY 4

1.1 EUT CONFIGURATION..... 4

1.2 PRODUCT DESCRIPTION 4

2. TEST ENVIRONMENT 5

2.1 ADDRESS OF THE TEST LABORATORY 5

2.2 TEST FACILITY 5

2.3 ENVIRONMENTAL CONDITIONS 5

2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY 5

3. METHOD OF MEASUREMENT 6

3.1 APPLICABLE STANDARD..... 6

3.2 REQUIREMENT 6

3.3 LIMIT 6

3.4 MPE CALCULATION METHOD 7

3.5 ANTENNA INFORMATION 7

4. CONDUCTED POWER RESULTS..... 8

5. MANUFACTURING TOLERANCE 10

6. MEASUREMENT RESULTS 12

6.1 STANDALONE MPE EVALUATION..... 12

6.2 SIMULTANEOUS TRANSMISSION MPE 14

7. CONCLUSION 15

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

● Adapter	Length (m) :	/
	Shield :	/
	Detachable :	/

1.2 Product Description

Product Name	Baby Monitor
Trade Mark	N/A
Model/Type reference	Baby 11Q
List Models	Baby 11T, Baby 11F, Baby 11S, Baby 11TM, Baby 11QM, Baby 11FM, Baby 11SM, Baby 10Q, Baby 10F, Baby 10T, Baby 10S, Baby 10QM, Baby 10TM, Baby 10SM, Baby 1Q, Baby 1T, Baby 1QM, Baby 1TM, Baby 6Q, Baby 6T, Baby 6QM, Baby 6TM, Baby 2Q, Baby 2T, Baby 2QM, Baby 2TM, Baby 5T, Baby 5F, Baby B8Q, Speed 31Q, Speed 31F, Alnanny-Cam, Alnanny D3, Alnanny A4, Alnanny F2, Baby B7F, Baby B7FM, Baby B8QM
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different , So no additional models were tested.
Power supply:	DC 5.0V by Adapter
Sample ID	GTS20250807004-4-S001-1#>S20250807004-4-S001-2#
Bluetooth	
Operation frequency	2402-2480MHz
Channel Number	40 channels for Bluetooth (DTS)
Channel Spacing	2MHz for Bluetooth (DTS)
Modulation Type	GFSK for Bluetooth (DTS)
WIFI(2.4G Band)	
Frequency Range	2412MHz ~ 2462MHz
Channel Spacing	5MHz
Channel Number	11 Channel for 20MHz bandwidth(2412~2462MHz)
Modulation Type	802.11b: DSSS; 802.11g/n: OFDM
WIFI(5.2G/5.3G/5.7G Band)	
Frequency Range	5150MHz ~ 5250MHz, 5250MHz ~ 5350MHz, 5500MHz ~ 5700MHz
Channel Number	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz)
Modulation Type	802.11a/n: OFDM
WIFI (5.8G Band)	
Frequency Range	5745MHz ~ 5825MHz
Channel Number	5 channels for 20MHz bandwidth(5745-5825MHz)
Modulation Type	802.11a/n: OFDM
Antenna Description	FPC Antenna: 2.86dBi(Max.) for 2.4G Band and 2.84dBi(Max.) for 5G Band
SRD	
Frequency Range	905-925MHz
Channel Number	11Channel
Channel Spacing	2MHz
Modulation Type	OFDM
Antenna Description	FPC Antenna:1.61 dBi(Max.)
Radar	
Frequency Range	57.5-63.5GHz
Modulation Type	FMCW
Antenna Description	Integrated microstrip patch array antenna with 2TX4RX and gain 7.0dBi(Max.)

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1401.

FCC Registered Test Site Number is 684561.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum source-based Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna is 2.86dBi for BT&2.4G WLAN, 2.84dBi for 5G WLAN & 1.61dBi for SRD, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

Baby 11Q can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	BT&WLAN ANT	FPC antenna	2.4 – 2.5 GHz 5.0 – 6.0 GHz	2.86 dBi(Max.) for 2.4G band 2.84 dBi(Max.) for 5G band
Antenna 2	SRD ANT	FPC antenna	0.905 – 0.925 GHz	1.61 dBi(Max.) for SRD
Antenna 3	Radar ANT	Integrated microstrip patch array antenna with 2TX4RX	57.5 - 63.5 GHz	7.0dBi(Max.) for Radar

4. Conducted Power Results

BLE

Mode	Channel	Frequency (MHz)	Peak Power (dBm)
GFSK(BT LE)	0	2402	13.99
	19	2440	13.72
	39	2480	13.52

SRD

Mode	Channel	Frequency (MHz)	Peak Power (dBm)
SRD	0	905	27.14
	5	915	28.4
	10	925	28.73

2.4GWLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	23.39
	06	2437	23.61
	11	2462	23.08
802.11g	01	2412	23.53
	06	2437	23.47
	11	2462	23.21
802.11n(HT20)	01	2412	22.24
	06	2437	22.99
	11	2462	22.78

5.2GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	36	5180	17.11
	40	5200	17.56
	48	5240	17.37
802.11n20	36	5180	17.96
	40	5200	17.55
	48	5240	17.01

5.3GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	52	5260	17.69
	56	5280	17.59
	64	5320	17.47
802.11n20	52	5260	17.46
	56	5280	17.43
	64	5320	17.35

5.7GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	100	5500	17.33
	120	5600	17.13
	140	5700	17.63
802.11n20	100	5500	17.29
	120	5600	17.07
	140	5700	17.53

5.8GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	149	5745	17.89
	157	5785	17.13
	165	5825	17.81
802.11n20	149	5745	17.67
	157	5785	17.89
	165	5825	17.99

RADAR

Mode	Frequency (GHz)	EIRP Power (dBm)
Radar	60.166G	4.84

5. Manufacturing Tolerance

Bluetooth

GFSK BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	13.0	13.0	13.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

SRD

SRD (Peak)			
Channel	Channel 0	Channel 5	Channel 10
Target (dBm)	27.0	28.0	28.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	23.00	23.00	23.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	23.00	23.00	23.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	22.00	22.00	22.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.2GWLAN

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	17.00	17.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	17.00	17.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.3GWLAN

IEEE 802.11a (Average)			
Channel	Channel 52	Channel 56	Channel 64
Target (dBm)	17.00	17.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 52	Channel 56	Channel 64
Target (dBm)	17.00	17.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.7GWLAN

IEEE 802.11a (Average)			
Channel	Channel 100	Channel 120	Channel 140
Target (dBm)	17.00	17.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 100	Channel 120	Channel 140
Target (dBm)	17.00	17.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.8GWLAN

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	17.00	17.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	17.00	17.00	17.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

RADAR

RADAR (EIRP)	
Target (dBm)	4.00
Tolerance $\pm$ (dB)	1.0

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

Bluetooth

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
GFSK(BT LE)	14.0	25.1189	2.86	1.9320	0.0097	1.0000

SRD

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
SRD	29.0	794.3282	1.61	1.4488	0.2289	0.6033

2.4G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
802.11b	24.00	251.1886	2.86	1.9320	0.0965	1.0000
802.11g	24.00	251.1886	2.86	1.9320	0.0965	1.0000
802.11n(HT20)	23.00	199.5262	2.86	1.9320	0.0767	1.0000

5.2G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
802.11a	18.00	63.0957	2.84	1.9231	0.0241	1.0000
802.11n20	18.00	63.0957	2.84	1.9231	0.0241	1.0000

5.3G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
802.11a	18.00	63.0957	2.84	1.9231	0.0241	1.0000
802.11n20	18.00	63.0957	2.84	1.9231	0.0241	1.0000

5.7G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm^2)	MPE Limits (mW/cm^2)
	dBm	mW				
802.11a	18.00	63.0957	2.84	1.9231	0.0241	1.0000
802.11n20	18.00	63.0957	2.84	1.9231	0.0241	1.0000

5.8G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	18.00	63.0957	2.84	1.9231	0.0241	1.0000
802.11n20	18.00	63.0957	2.84	1.9231	0.0241	1.0000

RADAR

Modulation Type	Output power (EIRP)		MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW		
FMCW(Radar)	5	3.1623	0.0006	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

6.2 Simultaneous Transmission MPE

The sample support one BT&WLAN modular, one SRD modular and one radar modular, and one BT*WLAN antenna, one SRD antenna and Integrated microstrip patch array antenna with 2 (two) transmitters for radar modular, Need consider simultaneous transmission;

According to KDB447498 D01 General RF Exposure Guidance v06 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;
 $\sum$ of MPE ratios ≤ 1.0

6.2.1 Summary simultaneous transmission results

Maximum Simultaneous transmission MPE Ratios for **2.4GWLAN+SRD+Radar**

Maximum MPE ratio 2.4GWLAN	Maximum MPE ratio SRD	Maximum MPE ratio Radar	$\sum$ MPE ratios	Limit	Results
0.0965	0.3794	0.0006	0.4765	1.0	PASS

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....End of Report.....