



FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.407

Report Reference No..... : GTS20250807004-4-03A

FCC ID..... : 2AG7C-BABY11-RAD

Compiled by

(position+printed name+signature) .: File administrators Peter Xiao

Supervised by

(position+printed name+signature) .: Test Engineer Evan Ouyang

Approved by

(position+printed name+signature) .: Manager Jason Hu

Date of issue : Dec.24, 2025

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address : No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative
Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu
Street, Longgang District, Shenzhen, Guangdong,China

Applicant's name.....: Hangzhou Meari Technology Co., Ltd.

Address : Building 4, Huiding Intelligent Innovation Center,No. 825,Ruquan
Road, Changhe Street, Binjiang District, Hangzhou, Zhejiang, China

Test specification

Standard..... : **FCC Part 15.407: General technical requirements**

TRF Originator..... : Shenzhen Global Test Service Co.,Ltd.

Master TRF : Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description **Baby Monitor**

Trade Mark..... : N/A

Manufacturer : Hangzhou Meari Technology Co., Ltd.

Model/Type reference : Baby 11Q

Listed Models : Baby 11T, Baby 11F, Baby 11S, Baby 11TM, Baby 11QM, Baby
11FM, Baby 11SM, Baby 10Q, Baby 10F, Baby 10T, Baby 10S, Baby
10QM, Baby 10TM, Baby 10SM, Baby 1Q, Baby 1T, Baby 1QM, Baby
1TM, Baby 6Q, Baby 6T, Baby 6QM, Baby 6TM, Baby 2Q, Baby 2T,
Baby 2QM, Baby 2TM, Baby 5T, Baby 5F, Baby B8Q, Speed 31Q,
Speed 31F, Alnanny-Cam, Alnanny D3, Alnanny A4, Alnanny F2,
Baby B7F, Baby B7FM, Baby B8QM

Operation Frequency..... : From 2412MHz to 2462MHz

Hardware Version : BABY11Q-T18MB-MIS4-REV1_0

Software Version..... : N/A

Rating : DC 5.0V by Adapter

Result : **PASS**

Note: From the date of issue of this report, the original report GTS20250807004-4-03 is invalid.

TEST REPORT

Test Report No. :	GTS20250807004-4-03A	Dec.24, 2025
		Date of issue

Equipment under Test : Baby Monitor

Model /Type : Baby 11Q

Listed model : Baby 11T, Baby 11F, Baby 11S, Baby 11TM, Baby 11QM, Baby 11FM, Baby 11SM, Baby 10Q, Baby 10F, Baby 10T, Baby 10S, Baby 10QM, Baby 10TM, Baby 10SM, Baby 1Q, Baby 1T, Baby 1QM, Baby 1TM, Baby 6Q, Baby 6T, Baby 6QM, Baby 6TM, Baby 2Q, Baby 2T, Baby 2QM, Baby 2TM, Baby 5T, Baby 5F, Baby B8Q, Speed 31Q, Speed 31F, Alnanny-Cam, Alnanny D3, Alnanny A4, Alnanny F2, Baby B7F, Baby B7FM, Baby B8QM

Applicant : Hangzhou Meari Technology Co., Ltd.

Address : Building 4, Huiding Intelligent Innovation Center, No. 825, Ruquan Road, Changhe Street, Binjiang District, Hangzhou, Zhejiang, China

Manufacturer : Hangzhou Meari Technology Co., Ltd.

Address : 2nd to 4th Floor, Building 2 and 3rd to 4th Floor, Building 1, No. 91, Chutian Road, Xixing Street, Binjiang District, Hangzhou, Zhejiang, China

Test Result:	PASS
--------------	------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS	4
2. SUMMARY	5
2.1. General Remarks	5
2.2. Product Description	5
2.3. Equipment Under Test	6
2.4. Short description of the Equipment under Test (EUT)	6
2.5. EUT operation mode	6
2.6. Block Diagram of Test Setup	7
2.7. Related Submittal(s) / Grant (s)	7
2.8. EUT Exercise Software	7
2.9. Special Accessories	7
2.10. External I/O Cable	7
2.11. Modifications	7
3. TEST ENVIRONMENT	8
3.1. Address of the test laboratory	8
3.2. Test Facility	8
3.3. Environmental conditions	8
3.4. Statement of the measurement uncertainty	8
3.5. Test Description	9
3.6. Equipments Used during the Test.....	11
4. TEST CONDITIONS AND RESULTS	12
4.1. AC Power Conducted Emission	12
4.2. Radiated Emission	16
4.3. Duty Cycle	25
4.4. Maximum Average Output Power	26
4.5. Power Spectral Density	27
4.6. 99% and 6dB Bandwidth	28
4.7. 99% and 26dB Bandwidth	29
4.8. Conducted Spurious Emissions and Band Edge Compliance	30
4.9. Frequency Stability	32
4.10. Antenna Requirement	36
5. TEST SETUP PHOTOS OF THE EUT	37
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	37

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.407](#): General technical requirements.

[ANSI C63.10-2020+Cor.1-2023+C63.10a-2024](#): American National Standard for Testing Unlicensed Wireless Devices

[KDB 789033 D02 General U-NII Test Procedures New Rules v02r01](#): UNII, U-NII, U-NII Test Procedures

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Aug.13, 2025
	:	
Testing commenced on	:	Aug.13, 2025
	:	
Testing concluded on	:	Aug.28, 2025

2.2. Product Description

Product Name	Baby Monitor
Trade Mark	N/A
Model/Type reference	Baby 11Q
List Models	Baby 11T, Baby 11F, Baby 11S, Baby 11TM, Baby 11QM, Baby 11FM, Baby 11SM, Baby 10Q, Baby 10F, Baby 10T, Baby 10S, Baby 10QM, Baby 10TM, Baby 10SM, Baby 1Q, Baby 1T, Baby 1QM, Baby 1TM, Baby 6Q, Baby 6T, Baby 6QM, Baby 6TM, Baby 2Q, Baby 2T, Baby 2QM, Baby 2TM, Baby 5T, Baby 5F, Baby B8Q, Speed 31Q, Speed 31F, Alnanny-Cam, Alnanny D3, Alnanny A4, Alnanny F2, Baby B7F, Baby B7FM, Baby B8QM
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different , So no additional models were tested.
Power supply:	DC 5.0V by Adapter
Sample ID	GTS20250807004-4-S001-1#>S20250807004-4-S001-2#
Bluetooth	
Operation frequency	2402-2480MHz
Channel Number	40 channels for Bluetooth (DTS)
Channel Spacing	2MHz for Bluetooth (DTS)
Modulation Type	GFSK for Bluetooth (DTS)
WIFI(2.4G Band)	
Frequency Range	2412MHz ~ 2462MHz
Channel Spacing	5MHz
Channel Number	11 Channel for 20MHz bandwidth(2412~2462MHz)
Modulation Type	802.11b: DSSS; 802.11g/n: OFDM
WIFI(5.2G/5.3G/5.7G Band)	
Frequency Range	5150MHz ~ 5250MHz, 5250MHz ~ 5350MHz, 5500MHz ~ 5700MHz
Channel Number	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz)
Modulation Type	802.11a/n: OFDM
WIFI (5.8G Band)	
Frequency Range	5745MHz ~ 5825MHz
Channel Number	5 channels for 20MHz bandwidth(5745-5825MHz)
Modulation Type	802.11a/n: OFDM
Antenna Description	FPC Antenna: 2.86dBi(Max.) for 2.4G Band and 2.84dBi(Max.) for 5G Band
SRD	
Frequency Range	905-925MHz
Channel Number	11Channel
Channel Spacing	2MHz
Modulation Type	OFDM
Antenna Description	FPC Antenna:1.61 dBi(Max.)

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	☐ 230V / 50 Hz	☐ 120V / 60Hz
		☐ 12 V DC	☐ 24 V DC
		☒ Other (specified in blank below)	

DC 5.0V

2.4. Short description of the Equipment under Test (EUT)

This is a Baby Monitor.

For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX.

Antenna	Chain0 (ANT0)			Chain1 (ANT1)			Simultaneously
Bandwidth Mode	20MHz	40MHz	80MHz	20MHz	40MHz	80MHz	/
IEEE 802.11a	☒	☐	☐	☐	☐	☐	☐
IEEE 802.11n	☒	☐	☐	☐	☐	☐	☐

IEEE 802.11a/n20:

UNII-1		UNII-1		UNII-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

U-NI-2A		U-NI-2A		U-NI-2A	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

U-NI-2C		U-NI-2C		U-NI-2C	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590		
112	5560	126	5630		
116	5580	134	5670		
120	5600				
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				


U-NI-3		U-NI-3		U-NI-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11a VHT20 mode (HCH).

2.6. Block Diagram of Test Setup



2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AG7C-BABY11-RAD** filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.8. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software provided by application.

2.9. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
SHENZHEN TIANYIN ELECTRONICS CO.,LTD.	Adapter	TPA-46B050100UU	--	SDOC
Zhuzhou Dachuan Electronic Technology Co.,Ltd.	Adapter	DCT07W050100US-C1	--	SDOC
Zhuzhou Dachuan Electronic Technology Co.,Ltd.	Adapter	DCT10W050200US-C0	--	SDOC

2.10. External I/O Cable

I/O Port Description	Quantity	Cable
Type-C Port	1	1.0M, Unscreened Cable
SD Card	1	N/A

2.11. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong, China.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1401.

FCC Registered Test Site Number is 684561.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.5. Test Description

Applied Standard: FCC Part 15 Subpart E				
FCC Rules	Description of Test	Test Sample	Result	Remark
/	On Time and Duty Cycle	GTS20250807004-4-S001-1#	Compliant	Appendix C Appendix D Appendix E Appendix F
§15.407(a)	Maximum Conducted Output Power	GTS20250807004-4-S001-1#	Compliant	Appendix C Appendix D Appendix E Appendix F
§15.407(a)	Power Spectral Density	GTS20250807004-4-S001-1#	Compliant	Appendix C Appendix D Appendix E Appendix F
§15.407(a)	26dB&6dB Bandwidth and 99% Bandwidth	GTS20250807004-4-S001-1#	Compliant	Appendix C Appendix D Appendix E Appendix F
§15.209, §15.407(b)	Radiated Emissions	GTS20250807004-4-S001-1#	Compliant	Note 1
§15.209, §15.407(b)	Conducted Spurious Emissions and Band Edges Test	GTS20250807004-4-S001-1#	Compliant	Appendix C Appendix D Appendix E Appendix F
§15.209, §15.407(b)	Emissions at Restricted Band	GTS20250807004-4-S001-1# GTS20250807004-4-S001-2#	Compliant	Appendix C Appendix D Appendix E Appendix F
§15.407(g)	Frequency Stability	GTS20250807004-4-S001-1#	Compliant	Note 1
§15.207(a)	AC Mians Line Conducted Emissions	GTS20250807004-4-S001-2#	Compliant	Note 1
§15.203 §15.407(h)	Antenna Requirements	GTS20250807004-4-S001-1#	Compliant	Note 1
§15.407 §2.1091	RF Exposure	/	Compliant	Note 2

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed
3. Note 1 – Test results inside test report;
4. Note 2 – Test results in other test report (MPE Report).
5. We tested all test mode and recorded worst case in report

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth 26dB Bandwidth Radiated Emission30M~1GHz& Radiated Emission 1GHz~10 th Harmonic	802.11a	6 Mbps
	802.11n HT20	MCS0
Band Edge	802.11a	6 Mbps
	802.11n HT20	MCS0

3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Artificial Mains	CYBERTEK	EM5040A	E1850400205	2025/07/07	2026/07/06
LISN	R&S	ESH2-Z5	893606/008	2025/07/07	2026/07/06
EMI Test Receiver	R&S	ESPI 3	/	2025/07/04	2026/07/03
Test Receiver	R&S	ESCI 7	101102	2025/07/04	2026/07/03
Spectrum Analyzer	Agilent	N9020A	MY48010425	2025/07/04	2026/07/03
Spectrum Analyzer	R&S	FSV40-N	101800	2025/07/04	2026/07/03
Vector Signal generator	Agilent	N5181A	MY49060502	2025/07/15	2026/07/14
Signal generator	Agilent	N5182A	MY50141550	2025/07/04	2026/07/03
Climate Chamber	ESPEC	EL-10KA	A20120523	2025/07/15	2026/07/14
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2024/12/16	2025/12/15
Active Loop Antenna	Beijing Da Ze Technology Co.,Ltd.	ZN30900C	/	2025/07/04	2026/07/03
By-log Antenna	SCHWARZBECK	VULB9163	00976	2025/07/15	2026/07/14
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2025/07/15	2026/07/14
Amplifier	SKET	LAPA_30M01G-32	SK20240104001	2025/01/21	2026/01/20
Amplifier	EMCI	EMC012645SE	980340	2025/01/21	2026/01/20
Amplifier	Schwarzbeck	BBV9179	9719-025	2025/01/21	2026/01/20
Temperature/Humidity Meter	HUATU	HTC-1	/	2025/07/16	2026/07/15
High-Pass Filter	Stest	1	/	2025/07/04	2026/07/03
High-Pass Filter	Stest	2	/	2025/07/04	2026/07/03
RF Cable(below 1GHz)	HUBER+SUHNER	RG214	RE01	2025/07/15	2026/07/14
RF Cable(above 1GHz)	HUBER+SUHNER	RG214	RE02	2025/07/15	2026/07/14
Data acquisition card	Agilent	U2531A	TW53323507	2025/07/15	2026/07/14
Power Sensor	Keysight	E9301A	MY41495308	2025/07/04	2026/07/03
Control Unit	Tonscend	JS0806-2	/	2025/07/07	2026/07/06
Control Unit	Tonscend	JS0806-2	/	2025/07/07	2026/07/06
integrated measuring instrument	R&S	CMW500	107519	2025/07/04	2026/07/03
EMI Test Software	Tonscend	JS1120-1	Ver 2.6.8.0518	/	/
EMI Test Software	Tonscend	JS1120-3	Ver 2.5.77.0418	/	/
EMI Test Software	Tonscend	JS32-CE	Ver 2.5	/	/
EMI Test Software	Tonscend	JS32-RE	Ver 2.5.1.8	/	/

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSIC63.10-2020+Cor.1-2023+C63.10a-2024.
- 2 Support equipment, if needed, was placed as per ANSIC63.10-2020+Cor.1-2023+C63.10a-2024
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSIC63.10-2020+Cor.1-2023+C63.10a-2024
- 4 The EUT received DC 5.0V power, the adapter received AC120V/60Hz or AC 240V/50Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

DISTURBANCE Calculation

The AC mains conducted disturbance is calculated by adding the 10dB Pulse Limiter and Cable Factor and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$CD \text{ (dBuV)} = RA \text{ (dBuV)} + PL \text{ (dB)} + CL \text{ (dB)}$$

Where CD = Conducted Disturbance	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	PL = 10 dB Pulse Limiter Factor


TEST RESULTS

Remark: We measured Conducted Emission at all mode in AC 120V/60Hz, the worst case was recorded .

Temperature	25.3℃	Humidity	50%
Test Engineer	Evan Ouyang	Configurations	IEEE 802.11ac20 HCH

Adapter: TPA-46B050100UU

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---




NO.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.1635	31.46	14.01	10.29	41.75	24.30	65.28	55.28	23.53	30.98	L1	PASS
2	0.4245	32.10	27.45	10.19	42.29	37.64	57.36	47.36	15.07	9.72	L1	PASS
3	0.8205	25.33	16.07	10.24	35.57	26.31	56.00	46.00	20.43	19.69	L1	PASS
4	1.2615	24.45	11.72	10.22	34.67	21.94	56.00	46.00	21.33	24.06	L1	PASS
5	2.5305	23.25	7.57	10.31	33.56	17.88	56.00	46.00	22.44	28.12	L1	PASS
6	3.9165	22.48	10.25	10.37	32.85	20.62	56.00	46.00	23.15	25.38	L1	PASS

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---




NO.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.159	31.06	14.30	10.31	41.37	24.61	65.52	55.52	24.15	30.91	N	PASS
2	0.4245	33.74	24.10	10.19	43.93	34.29	57.36	47.36	13.43	13.07	N	PASS
3	0.8295	28.04	15.46	10.24	38.28	25.70	56.00	46.00	17.72	20.30	N	PASS
4	1.581	34.62	16.83	10.24	44.86	27.07	56.00	46.00	11.14	18.93	N	PASS
5	3.525	23.89	3.67	10.36	34.25	14.03	56.00	46.00	21.75	31.97	N	PASS
6	4.929	22.68	2.93	10.35	33.03	13.28	56.00	46.00	22.97	32.72	N	PASS

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Adapter: DCT07W050100US-C1

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---




Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1725	30.89	12.26	10.24	41.13	22.50	64.84	54.84	23.71	32.34	L1	PASS
2	0.4245	32.24	25.75	10.19	42.43	35.94	57.36	47.36	14.93	11.42	L1	PASS
3	0.8565	27.50	15.55	10.24	37.74	25.79	56.00	46.00	18.26	20.21	L1	PASS
4	1.2885	25.61	11.90	10.22	35.83	22.12	56.00	46.00	20.17	23.88	L1	PASS
5	2.7375	23.46	9.44	10.32	33.78	19.76	56.00	46.00	22.22	26.24	L1	PASS
6	4.0965	23.65	9.39	10.37	34.02	19.76	56.00	46.00	21.98	26.24	L1	PASS

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---



Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.2085	32.15	14.90	10.15	42.30	25.05	63.26	53.26	20.96	28.21	N	PASS
2	0.429	31.84	19.37	10.19	42.03	29.56	57.27	47.27	15.24	17.71	N	PASS
3	0.735	26.46	13.17	10.23	36.69	23.40	56.00	46.00	19.31	22.60	N	PASS
4	1.6035	31.94	17.07	10.24	42.18	27.31	56.00	46.00	13.82	18.69	N	PASS
5	2.6025	26.99	6.81	10.31	37.30	17.12	56.00	46.00	18.70	28.88	N	PASS
6	4.776	25.71	3.04	10.35	36.06	13.39	56.00	46.00	19.94	32.61	N	PASS

Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Adapter: DCT10W050200US-C0

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

NO.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.15	29.91	12.01	10.35	40.26	22.36	66.00	56.00	25.74	33.64	L1	PASS
2	0.4245	31.46	20.97	10.19	41.65	31.16	57.36	47.36	15.71	16.20	L1	PASS
3	0.735	26.56	13.34	10.23	36.79	23.57	56.00	46.00	19.21	22.43	L1	PASS
4	1.149	23.39	11.95	10.21	33.60	22.16	56.00	46.00	22.40	23.84	L1	PASS
5	2.247	22.73	11.18	10.29	33.02	21.47	56.00	46.00	22.98	24.53	L1	PASS
6	3.5115	22.87	8.98	10.36	33.23	19.34	56.00	46.00	22.77	26.66	L1	PASS


Note: 1. Result (dBμV) = Reading (dBμV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing above 1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 24MHz and maximum operation frequency was 5825MHz.so radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

$$Transd=AF +CL-AG$$

RADIATION LIMIT

According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBμV/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 (beyond 10MHz of the bandedge)	68.2
	-17 (within 10 MHz of band edge)	78.2

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: We measured Radiated Emission at all mode from 9KHz to 25GHz in AC 120V/60Hz and the worst case was recorded.

Temperature	24.5°C	Humidity	48%
Test Engineer	Evan Ouyang	Configurations	IEEE 802.11ac20 HCH

For 9 KHz~30MHz

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

Adapter: TPA-46B050100UU

For 30MHz-1GHz

Horizontal




Suspected List

NO.	Frequency [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	73.65	31.89	-14.08	17.81	40.00	22.19	100	189	PK	Horizontal	PASS
2	219.15	34.49	-9.60	24.89	46.00	21.11	100	97	PK	Horizontal	PASS
3	275.895	51.53	-7.82	43.71	46.00	2.29	100	312	PK	Horizontal	PASS
4	390.84	40.06	-5.49	34.57	46.00	11.43	100	169	PK	Horizontal	PASS
5	529.065	35.35	-2.05	33.30	46.00	12.70	100	134	PK	Horizontal	PASS
6	865.17	42.17	1.55	43.72	46.00	2.28	100	332	PK	Horizontal	PASS

Note: 1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical



Suspected List

NO.	Frequency [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	45.52	36.21	-11.34	24.87	40.00	15.13	100	25	PK	Vertical	PASS
2	74.135	32.67	-14.11	18.56	40.00	21.44	100	140	PK	Vertical	PASS
3	147.855	33.50	-14.23	19.27	43.50	24.23	100	358	PK	Vertical	PASS
4	275.895	49.27	-7.82	41.45	46.00	4.55	100	146	PK	Vertical	PASS
5	549.92	30.32	-1.49	28.83	46.00	17.17	100	238	PK	Vertical	PASS
6	866.625	41.81	1.54	43.35	46.00	2.65	100	204	PK	Vertical	PASS


Note: 1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Adapter: DCT07W050100US-C1

For 30MHz-1GHz

Horizontal




Suspected List

NO.	Frequency [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	45.035	32.27	-11.38	20.89	40.00	19.11	100	293	PK	Horizontal	PASS
2	73.65	33.78	-14.08	19.70	40.00	20.30	100	317	PK	Horizontal	PASS
3	275.895	51.78	-7.82	43.96	46.00	2.04	100	313	PK	Horizontal	PASS
4	350.1	34.87	-6.19	28.68	46.00	17.32	100	324	PK	Horizontal	PASS
5	864.685	40.95	1.55	42.50	46.00	3.50	100	286	PK	Horizontal	PASS
6	930.16	33.42	2.35	35.77	46.00	10.23	100	218	PK	Horizontal	PASS

Note: 1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical



Suspected List

NO.	Frequency [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	44.55	37.13	-11.41	25.72	40.00	14.28	100	2	PK	Vertical	PASS
2	73.65	33.17	-14.08	19.09	40.00	20.91	100	327	PK	Vertical	PASS
3	275.895	49.10	-7.82	41.28	46.00	4.72	100	160	PK	Vertical	PASS
4	549.92	29.84	-1.49	28.35	46.00	17.65	100	266	PK	Vertical	PASS
5	866.14	41.66	1.54	43.20	46.00	2.80	100	61	PK	Vertical	PASS
6	931.13	34.89	2.36	37.25	46.00	8.75	100	129	PK	Vertical	PASS


Note: 1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Adapter: DCT10W050200US-C0

For 30MHz-1GHz

Horizontal




Suspected List

NO.	Frequency [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	45.035	33.16	-11.38	21.78	40.00	18.22	100	275	PK	Horizontal	PASS
2	72.68	31.84	-14.01	17.83	40.00	22.17	100	239	PK	Horizontal	PASS
3	275.895	51.53	-7.82	43.71	46.00	2.29	100	316	PK	Horizontal	PASS
4	350.1	35.87	-6.19	29.68	46.00	16.32	100	333	PK	Horizontal	PASS
5	845.77	39.01	1.72	40.73	46.00	5.27	100	340	PK	Horizontal	PASS
6	866.14	42.00	1.54	43.54	46.00	2.46	100	170	PK	Horizontal	PASS

Note: 1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical



Suspected List

NO.	Frequency [MHz]	Reading [dBμV/m]	Factor [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	45.035	38.24	-11.38	26.86	40.00	13.14	100	357	PK	Vertical	PASS
2	72.68	32.62	-14.01	18.61	40.00	21.39	100	198	PK	Vertical	PASS
3	250.19	34.77	-8.70	26.07	46.00	19.93	100	354	PK	Vertical	PASS
4	275.895	49.39	-7.82	41.57	46.00	4.43	100	160	PK	Vertical	PASS
5	549.92	29.91	-1.49	28.42	46.00	17.58	100	245	PK	Vertical	PASS
6	930.645	35.47	2.35	37.82	46.00	8.18	100	4	PK	Vertical	PASS

Note: 1. Result (dBμV/m) = Reading(dBμV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

For Greater than 1GHz

5150-5250MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 36_5180 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10360	40.25	38.55	33.13	11.26	56.93	68.20	-11.27	Peak	Horizontal
1	10360	31.62	38.55	33.13	11.26	48.30	54.00	-5.70	AV	Horizontal
1	10360	41.38	38.55	33.13	11.26	58.06	68.20	-10.14	Peak	Vertical
1	10360	29.72	38.55	33.13	11.26	46.40	54.00	-7.60	AV	Vertical

802.11a Mode_Channel 40_5200 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10400	39.66	38.55	33.13	11.26	56.34	68.20	-11.86	Peak	Horizontal
1	10400	30.29	38.55	33.13	11.26	46.97	54.00	-7.03	AV	Horizontal
1	10400	40.56	38.55	33.13	11.26	57.24	68.20	-10.96	Peak	Vertical
1	10400	29.16	38.55	33.13	11.26	45.84	54.00	-8.16	AV	Vertical

802.11a Mode_Channel 48_5240 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10480	40.02	38.55	33.13	11.26	56.70	68.20	-11.50	Peak	Horizontal
1	10480	31.38	38.55	33.13	11.26	48.06	54.00	-5.94	AV	Horizontal
1	10480	41.37	38.55	33.13	11.26	58.05	68.20	-10.15	Peak	Vertical
1	10480	29.06	38.55	33.13	11.26	45.74	54.00	-8.26	AV	Vertical

5260-5320MHz:**IEEE 802.11a (Worst Case)****802.11a Mode_Channel 52_ 5260 MHz**

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10520	40.11	38.55	33.13	11.26	56.79	68.20	-11.41	Peak	Horizontal
1	10520	30.08	38.55	33.13	11.26	46.76	54.00	-7.24	AV	Horizontal
1	10520	41.35	38.55	33.13	11.26	58.03	68.20	-10.17	Peak	Vertical
1	10520	29.28	38.55	33.13	11.26	45.96	54.00	-8.04	AV	Vertical

802.11a Mode_Channel 56_ 5280 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10560	40.76	38.55	33.13	11.26	57.44	68.20	-10.76	Peak	Horizontal
1	10560	31.35	38.55	33.13	11.26	48.03	54.00	-5.97	AV	Horizontal
1	10560	40.78	38.55	33.13	11.26	57.46	68.20	-10.74	Peak	Vertical
1	10560	28.11	38.55	33.13	11.26	44.79	54.00	-9.21	AV	Vertical

802.11a Mode_Channel 64_ 5320 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10640	40.61	38.55	33.13	11.26	57.29	68.20	-10.91	Peak	Horizontal
1	10640	31.51	38.55	33.13	11.26	48.19	54.00	-5.81	AV	Horizontal
1	10640	41.80	38.55	33.13	11.26	58.48	68.20	-9.72	Peak	Vertical
1	10640	29.54	38.55	33.13	11.26	46.22	54.00	-7.78	AV	Vertical

5500-5700MHz:**IEEE 802.11a (Worst Case)****802.11a Mode_Channel 100_ 5500 MHz**

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11000	39.45	38.55	33.13	11.26	56.13	68.20	-12.07	Peak	Horizontal
1	11000	31.69	38.55	33.13	11.26	48.37	54.00	-5.63	AV	Horizontal
1	11000	40.12	38.55	33.13	11.26	56.80	68.20	-11.40	Peak	Vertical
1	11000	29.65	38.55	33.13	11.26	46.33	54.00	-7.67	AV	Vertical

802.11a Mode_Channel 120_ 5600 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11200	40.46	38.55	33.13	11.26	57.14	68.20	-11.06	Peak	Horizontal
1	11200	30.14	38.55	33.13	11.26	46.82	54.00	-7.18	AV	Horizontal
1	11200	40.90	38.55	33.13	11.26	57.58	68.20	-10.62	Peak	Vertical
1	11200	28.15	38.55	33.13	11.26	44.83	54.00	-9.17	AV	Vertical

802.11a Mode_Channel 140_ 5700 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11400	39.86	38.55	33.13	11.26	56.54	68.20	-11.66	Peak	Horizontal
1	11400	30.42	38.55	33.13	11.26	47.10	54.00	-6.90	AV	Horizontal
1	11400	40.40	38.55	33.13	11.26	57.08	68.20	-11.12	Peak	Vertical
1	11400	28.34	38.55	33.13	11.26	45.02	54.00	-8.98	AV	Vertical

5725-5850MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 149 _ 5745 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11490	39.99	38.55	33.13	11.26	56.67	68.20	-11.53	Peak	Horizontal
1	11490	31.19	38.55	33.13	11.26	47.87	54.00	-6.13	AV	Horizontal
1	11490	40.63	38.55	33.13	11.26	57.31	68.20	-10.89	Peak	Vertical
1	11490	28.59	38.55	33.13	11.26	45.27	54.00	-8.73	AV	Vertical

802.11a Mode_Channel 157 _ 5785 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11570	40.19	38.55	33.13	11.26	56.87	68.20	-11.33	Peak	Horizontal
1	11570	31.85	38.55	33.13	11.26	48.53	54.00	-5.47	AV	Horizontal
1	11570	40.12	38.55	33.13	11.26	56.80	68.20	-11.40	Peak	Vertical
1	11570	28.06	38.55	33.13	11.26	44.74	54.00	-9.26	AV	Vertical

802.11a Mode_Channel 165 _ 5825 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	11650	40.47	38.55	33.13	11.26	57.15	68.20	-11.05	Peak	Horizontal
1	11650	30.31	38.55	33.13	11.26	46.99	54.00	-7.01	AV	Horizontal
1	11650	40.38	38.55	33.13	11.26	57.06	68.20	-11.14	Peak	Vertical
1	11650	29.37	38.55	33.13	11.26	46.05	54.00	-7.95	AV	Vertical


REMARKS:

1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. Margin = Result Level - Limit
3. The other emission levels were very low against the limit.
4. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak;

NOTE: All the modes have been tested and recorded worst mode in the report.

4.3. Duty Cycle

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Duty Cycle (x),
Transmission Duration (T):

- a. A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on and off times of the transmitted signal
- b. The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq EBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zerospan measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in section II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST RESULTS

For reporting purpose only.

Please refer to Appendix C.3.


Please refer to Appendix D.3.

Please refer to Appendix E.3.

Please refer to Appendix F.3.

4.4. Maximum Average Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Measurement using a Power Meter (PM):

- a. Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied
 1. The EUT is configured to transmit continuously or to transmit with a constant duty cycle
 2. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 3. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b. If the transmitter does not transmit continuously, measure the duty cycle, x , of the transmitter output signal as described in section II.B
- c. Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Fixed: 1 Watt (30dBm) Mobile and portable: 250mW (24dBm)
5250-5350	250mW (24dBm)
5470-5725	250mW (24dBm)
5725-5850	1 Watt (30dBm)
Note: The maximum e.i.r.p at any elevation angle above 30 degrees as measured from the horizon must not exceed 125mW(21dBm)	

TEST RESULTS

For reporting purpose only.

Please refer to Appendix C.4.


Please refer to Appendix D.4.

Please refer to Appendix E.4.

Please refer to Appendix F.4.

4.5. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01: The rules requires “maximum power spectral density” measurements where the intent is to measure the maximum value of the time average of the power spectral density measured during a period of continuous transmission

- a. Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, “Compute power...”. (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- b. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- c. Make the following adjustments to the peak value of the spectrum, if applicable:
 1. If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum.
 2.) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- d. The result is the Maximum PSD over 1 MHz reference bandwidth.
- e. For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:
 1. Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
 2. Set $VBW \geq 3$ RBW.
 3. If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas $RBW (< 500 \text{ KHz})$ is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 4. If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas $RBW (< 1 \text{ MHz})$ is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 5. Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since $RBW=100 \text{ KHz}$ is available on nearly all spectrum analyzers.
- f. Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Other then Mobile and portable:17dBm/MHz Mobile and portable:11dBm/MHz
5250-5350	11dBm/MHz
5470-5725	11dBm/MHz
5725-5850	30dBm/500kHz


TEST RESULTS

For reporting purpose only.

Please refer to Appendix C.5.
Please refer to Appendix D.5.
Please refer to Appendix E.5.
Please refer to Appendix F.5.

4.6. 99% and 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 for one of the following procedures may be used for section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a. Set RBW = 100 kHz.
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

LIMIT

For Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz

TEST RESULTS


For reporting purpose only.

Please refer to Appendix F.1.

Please refer to Appendix F.2.

4.7. 99% and 26dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 for one of the following procedures may be used for Emission Bandwidth (EBW) measurement:

- Set RBW = 220 kHz/430 kHz /820 kHz (approximately 1% of the emission bandwidth).
- Set the video bandwidth (VBW) = 3* RBW
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize
- Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

LIMIT

No Limits for 26dBc Bandwidth

TEST RESULTS

For reporting purpose only.

Please refer to Appendix C.1.

Please refer to Appendix C.2.

Please refer to Appendix D.1.


Please refer to Appendix D.2.

Please refer to Appendix E.1.

Please refer to Appendix E.2.

4.8. Conducted Spurious Emissions and Band Edge Compliance

TEST CONFIGURATION



LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Distance (Meters)	Radiated (dBμV/m)	Radiated (μV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	$2400/F(KHz)$
0.49-1.705	3	$20\log(24000/F(KHz))+40\log(30/3)$	$24000/F(KHz)$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBμV/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 (beyond 10MHz of the band edge)	68.2
	-17 (within 10 MHz of band edge)	78.2

TEST PROCEDURE

1. The EUT was placed on a turn table which is 1.5m above 1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed..
5. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
1GHz-18GHz	Double Ridged Horn Antenna	3

6. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
1GHz-18GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

TEST RESULTS**For Conducted at Restricted Band Measurement**

For reporting purpose only.

Please refer to Appendix C.8.

Please refer to Appendix D.8.

Please refer to Appendix E.8.

Please refer to Appendix F.8.

For Conducted Band edge Measurement

For reporting purpose only.

Please refer to Appendix C.6.

Please refer to Appendix D.6.

Please refer to Appendix E.6.

Please refer to Appendix F.6.

For Conducted Spurious Emissions Measurement

For reporting purpose only.

Please refer to Appendix C.7.

Please refer to Appendix D.7.

Please refer to Appendix E.7.

Please refer to Appendix F.7.

4.9. Frequency Stability

Standard Applicable

According to FCC §15.407(g) "Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user manual."


According to FCC §2.1055(a) "The frequency stability shall be measured with variation of ambient temperature as follows:"

(1) From -30° to + 50° centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.

(2) From -20° to + 50° centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radiobeacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter.

(3) From 0° to + 50° centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.

Test Configuration



Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20 degree operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30 degree. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10 degree increased per stage until the highest temperature of +50 degree reached.

Test Results

PASS

Remark:

1. Measured all conditions and recorded worst case.

IEEE 802.11a Mode / 5180 – 5240 MHz / 5180 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 5.5V	5171.569952	5150 – 5250	PASS
20	DC 4.5V	5171.609804	5150 – 5250	PASS
50	DC 5.0V	5171.600035	5150 – 5250	PASS
40	DC 5.0V	5171.664055	5150 – 5250	PASS
30	DC 5.0V	5171.671590	5150 – 5250	PASS
20	DC 5.0V	5171.694090	5150 – 5250	PASS
10	DC 5.0V	5171.684393	5150 – 5250	PASS
0	DC 5.0V	5171.661991	5150 – 5250	PASS
-10	DC 5.0V	5171.642308	5150 – 5250	PASS
-20	DC 5.0V	5171.630166	5150 – 5250	PASS
-30	DC 5.0V	5171.686057	5150 – 5250	PASS

IEEE 802.11a Mode / 5180 – 5240 MHz / 5240 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 5.5V	5248.549822	5150 – 5250	PASS
20	DC 4.5V	5248.520893	5150 – 5250	PASS
50	DC 5.0V	5248.668155	5150 – 5250	PASS
40	DC 5.0V	5248.561573	5150 – 5250	PASS
30	DC 5.0V	5248.667491	5150 – 5250	PASS
20	DC 5.0V	5248.503579	5150 – 5250	PASS
10	DC 5.0V	5248.683070	5150 – 5250	PASS
0	DC 5.0V	5248.692428	5150 – 5250	PASS
-10	DC 5.0V	5248.556066	5150 – 5250	PASS
-20	DC 5.0V	5248.537532	5150 – 5250	PASS
-30	DC 5.0V	5248.600453	5150 – 5250	PASS

IEEE 802.11a Mode / 5260 – 5320 MHz / 5260 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 5.5V	5251.514070	5250 – 5350	PASS
20	DC 4.5V	5251.568306	5250 – 5350	PASS
50	DC 5.0V	5251.657942	5250 – 5350	PASS
40	DC 5.0V	5251.611338	5250 – 5350	PASS
30	DC 5.0V	5251.692195	5250 – 5350	PASS
20	DC 5.0V	5251.541503	5250 – 5350	PASS
10	DC 5.0V	5251.659969	5250 – 5350	PASS
0	DC 5.0V	5251.541626	5250 – 5350	PASS
-10	DC 5.0V	5251.553785	5250 – 5350	PASS
-20	DC 5.0V	5251.689811	5250 – 5350	PASS
-30	DC 5.0V	5251.698888	5250 – 5350	PASS

IEEE 802.11a Mode / 5260 – 5320 MHz / 5320 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 5.5V	5328.627676	5250 – 5350	PASS
20	DC 4.5V	5328.565627	5250 – 5350	PASS
50	DC 5.0V	5328.673217	5250 – 5350	PASS
40	DC 5.0V	5328.641156	5250 – 5350	PASS
30	DC 5.0V	5328.697308	5250 – 5350	PASS
20	DC 5.0V	5328.598613	5250 – 5350	PASS
10	DC 5.0V	5328.624523	5250 – 5350	PASS
0	DC 5.0V	5328.587716	5250 – 5350	PASS
-10	DC 5.0V	5328.650467	5250 – 5350	PASS
-20	DC 5.0V	5328.594708	5250 – 5350	PASS
-30	DC 5.0V	5328.684417	5250 – 5350	PASS

IEEE 802.11a Mode / 5500 – 5700 MHz / 5500 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 5.5V	5491.590797	5470 – 5725	PASS
20	DC 4.5V	5491.680773	5470 – 5725	PASS
50	DC 5.0V	5491.671630	5470 – 5725	PASS
40	DC 5.0V	5491.528691	5470 – 5725	PASS
30	DC 5.0V	5491.515250	5470 – 5725	PASS
20	DC 5.0V	5491.548711	5470 – 5725	PASS
10	DC 5.0V	5491.585048	5470 – 5725	PASS
0	DC 5.0V	5491.693565	5470 – 5725	PASS
-10	DC 5.0V	5491.582183	5470 – 5725	PASS
-20	DC 5.0V	5491.600815	5470 – 5725	PASS
-30	DC 5.0V	5491.559808	5470 – 5725	PASS

IEEE 802.11a Mode / 5500 – 5700 MHz / 5700 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 5.5V	5708.631110	5470 – 5725	PASS
20	DC 4.5V	5708.560636	5470 – 5725	PASS
50	DC 5.0V	5708.664994	5470 – 5725	PASS
40	DC 5.0V	5708.690249	5470 – 5725	PASS
30	DC 5.0V	5708.591109	5470 – 5725	PASS
20	DC 5.0V	5708.551975	5470 – 5725	PASS
10	DC 5.0V	5708.607547	5470 – 5725	PASS
0	DC 5.0V	5708.556337	5470 – 5725	PASS
-10	DC 5.0V	5708.562985	5470 – 5725	PASS
-20	DC 5.0V	5708.513310	5470 – 5725	PASS
-30	DC 5.0V	5708.530771	5470 – 5725	PASS

IEEE 802.11a Mode / 5745 – 5825 MHz / 5745 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 5.5V	5736.690962	5725 – 5850	PASS
20	DC 4.5V	5736.580555	5725 – 5850	PASS
50	DC 5.0V	5736.615919	5725 – 5850	PASS
40	DC 5.0V	5736.674392	5725 – 5850	PASS
30	DC 5.0V	5736.572411	5725 – 5850	PASS
20	DC 5.0V	5736.605139	5725 – 5850	PASS
10	DC 5.0V	5736.568910	5725 – 5850	PASS
0	DC 5.0V	5736.637017	5725 – 5850	PASS
-10	DC 5.0V	5736.649596	5725 – 5850	PASS
-20	DC 5.0V	5736.673838	5725 – 5850	PASS
-30	DC 5.0V	5736.624511	5725 – 5850	PASS

IEEE 802.11a Mode / 5745 – 5825 MHz / 5825 MHz

Enviroment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 5.5V	5833.527827	5725 – 5850	PASS
20	DC 4.5V	5833.618513	5725 – 5850	PASS
50	DC 5.0V	5833.634621	5725 – 5850	PASS
40	DC 5.0V	5833.521954	5725 – 5850	PASS
30	DC 5.0V	5833.660129	5725 – 5850	PASS
20	DC 5.0V	5833.553037	5725 – 5850	PASS
10	DC 5.0V	5833.520607	5725 – 5850	PASS
0	DC 5.0V	5833.634204	5725 – 5850	PASS
-10	DC 5.0V	5833.544999	5725 – 5850	PASS
-20	DC 5.0V	5833.699749	5725 – 5850	PASS
-30	DC 5.0V	5833.520141	5725 – 5850	PASS

4.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Information

The antenna is FPC Aantenna, through the buckle stretched out, The directional gains of antenna used for transmitting is 2.84 dBi.

Reference to the Test Report: **GTS20250807004-4-01A.**

5. TEST SETUP PHOTOS OF THE EUT

Reference to the test report No. GTS20250807004-4-01A.

6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the test report No. GTS20250807004-4-01A.

.....**End of Report**.....