

Case No. : <u>GTS20250902002-8-02</u>
Ambient Condition: <u>22</u> °C, <u>48</u> %RH
According Standard: ■Part15C
Test Date: <u>2025.9.09-2025.10.21</u> Test Engineer: <u>Evan ouyang</u>


AppendixA.1: DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	0.704	2401.644	2402.348	0.5	PASS
		2440	0.692	2439.644	2440.336	0.5	PASS
		2480	0.672	2479.660	2480.332	0.5	PASS

Test Graphs


BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480



AppendixA.2: Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	1.0408	2401.4839	2402.5247	---	---
		2440	1.0277	2439.4869	2440.5146	---	---
		2480	1.0367	2479.4768	2480.5135	---	---

Test Graphs


BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480



AppendixA.3: Maximum conducted output power

Test Result Peak

TestMode	Antenna	Freq(MHz)	Conducted Peak Power[dBm]	Conducted Limit[dBm]	Verdict
BLE	Ant1	2402	12.57	≤30	PASS
		2440	12.60	≤30	PASS
		2480	12.45	≤30	PASS


AppendixA.4: Maximum power spectral density

Test Result


TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE	Ant1	2402	-8.42	≤8.00	PASS
		2440	-8.35	≤8.00	PASS
		2480	-8.47	≤8.00	PASS

Test Graphs


BLE_Ant1_2402



BLE_Ant1_2440



BLE_Ant1_2480




Appendix A.5: Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	Low	2402	7.35	-46.89	≤-12.65	PASS
		High	2480	7.47	-47.96	≤-12.53	PASS

Test Graphs



Appendix A.6: Conducted Spurious Emission

Test Result


TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	2402	Reference	6.78	6.78	---	PASS
			30~1000	6.78	-60.45	≤ -13.22	PASS
			1000~26500	6.78	-43.32	≤ -13.22	PASS
		2440	Reference	7.27	7.27	---	PASS
			30~1000	7.27	-60.82	≤ -12.73	PASS
			1000~26500	7.27	-44.95	≤ -12.73	PASS
		2480	Reference	7.01	7.01	---	PASS
			30~1000	7.01	-60.16	≤ -12.99	PASS
			1000~26500	7.01	-46.62	≤ -12.99	PASS

Test Graphs


BLE_Ant1_2402_0-Reference



BLE_Ant1_2402_30-1000




BLE_Ant1_2402_1000-26500




BLE_Ant1_2440_0-Reference



BLE_Ant1_2440_30~1000




BLE_Ant1_2440_1000~26500




BLE_Ant1_2480_0~Reference



BLE_Ant1_2480_30~1000



BLE_Ant1_2480_1000~26500



Appendix A.7: Emissions in Restricted Bands

Test Result


TestMode	Antenna	ChName	Freq(MHz)	Detector	Freq [MHz]	Result [dBm]	Limit [dBm]	Result [dBuV/m]	Limit [dBuV/m]	Verdict
BLE	Ant1	Low	2402	AV	2310.000	-49.2	≤-41.20	46.00	≤54	PASS
				AV	2389.985	-48.65	≤-41.20	46.55	≤54	PASS
				AV	2390.000	-48.65	≤-41.20	46.55	≤54	PASS
				Peak	2310.000	-40.84	≤-21.20	54.36	≤74	PASS
				Peak	2340.425	-38.44	≤-21.20	56.76	≤74	PASS
				Peak	2390.000	-41.29	≤-21.20	53.91	≤74	PASS
		High	2480	AV	2483.500	-45.65	≤-41.20	49.55	≤54	PASS
				AV	2483.520	-45.65	≤-41.20	49.55	≤54	PASS
				AV	2500.000	-48.5	≤-41.20	46.70	≤54	PASS
				Peak	2483.500	-37.74	≤-21.20	57.46	≤74	PASS
				Peak	2484.240	-36	≤-21.20	59.20	≤74	PASS
				Peak	2500.000	-40.77	≤-21.20	54.43	≤74	PASS

Note:


1. The Antenna Gain is compensated in the graph.
2. The Duty Cycle Factor and RBW Factor is compensated in the graph.
3. The limit in dBm for average detector is conversion from 54dBuV/m, according to 15.209(a). The limit in dBm for peak detector is 20dB above the limit of average detector in dBm.

Test Graphs

BLE_Ant1_Low_2402_AV



BLE_Ant1_Low_2402_Peak



BLE_Ant1_High_2480_AV

