

RF EXPOSURE Test Report

Product: Base Station

Trade Mark: N/A

Model Number: Base 5E

FCC ID: 2AG7C-BASE5

Prepared for

Hangzhou Meari Technology Co., Ltd.

Building 4,Huiding Intelligent Innovation Center,No. 825,Ruquan
Road,Changhe Street,Binjiang District,Hangzhou,Zhejiang,China

Prepared by

Shenzhen HongBiao Certification& Testing Co., Ltd

Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan
Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen,
China

Tel.: +86-755-2998 9321 Fax.: +86-755-2998 5110

Website: <http://www.sz-hongbiao.com>

Table of Contents

1	GENERAL DESCRIPTION	5
1.1	DESCRIPTION OF EUT	5
1.2	TEST MODE.....	5
1.3	TEST SETUP	6
1.4	ANCILLARY EQUIPMENT	6
2	TEST FACILITIES AND ACCREDITATIONS	7
2.1	TEST LABORATORY	7
2.2	ENVIRONMENTAL CONDITIONS	7
2.3	MEASUREMENT UNCERTAINTY	7
2.4	TEST SOFTWARE	7
3	LIST OF TEST EQUIPMENT	8
4	RF EXPOSURE.....	9
4.1	STANDALONE SAR TEST EXCLUSION CONSIDERATIONS.....	9
4.1.1.	<i>Limit</i>	9
4.1.2.	<i>Test Result</i>	9

TEST RESULT CERTIFICATION

Applicant's Name..... : Hangzhou Meari Technology Co., Ltd.
Building 4,Huiding Intelligent Innovation Center,No. 825,Ruquan
Address : Road,Changhe Street,Binjiang District,Hangzhou,Zhejiang,
China

Manufacturer's Name : Hangzhou Meari Technology Co., Ltd.
Building 4,Huiding Intelligent Innovation Center,No. 825,Ruquan
Address : Road,Changhe Street,Binjiang District,Hangzhou,Zhejiang,
China

Product description

Product name : Base Station

Model Number : Base 5E

Standards : FCC CFR 47 PART 1 , 1.1310

Test procedure..... : KDB 447498 D01 General RF Exposure Guidance v06


This device described above has been tested by Shenzhen HongBiao Certification& Testing Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the EMC requirements. And it is applicable only to the tested sample identified in the report.

Date of Test..... :

Date (s) of performance of tests..... : July 22, 2026~Aug. 25, 2026


Test Result..... : **Pass**

Testing Engineer :




(Z o e S u)

Technical Manager :



(Ming L i u)

Authorized Signatory :



(L e o S u)

[illegible]

1 General Description

1.1 Description of EUT

Product name:	Base Station
Model name:	Base 5E
Series Model:	Base B5E, Base 1, Base 1E
Different of series model:	All the models are the same circuit and module, except the model No..
Operation frequency:	802.11b/g/n20: 2412-2462MHz 802.11n40: 2422-2452MHz
Modulation type:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g/n(HT20/H40): OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Bit Rate of transmitter:	IEEE 802.11b: 1/2/5.5/11Mbps IEEE 802.11g: 6/9/12/18/24/36/48/54Mbps IEEE 802.11n(20MHz): MCS0-7, up to 72.2Mbps IEEE 802.11n(40MHz): MCS0-7, up to 150Mbps
Antenna type:	ANT1: PCB Antenna ANT2: PCB Antenna
Antenna gain:	ANT1: 4.65dBi ANT2: 4.65dBi MINO: 7.66dBi
Max. output power:	21.8dBm
Hardware version:	BASE5-DW2-REV1_1
Software version:	V1.0
Battery:	N/A
Power supply:	Input: 100-240VAC Output: 12V=1A
Adapter information:	Model: DCT12W120100US-AL Input: 100-240VAC Output: 12V=1A

1.2 Test Mode

Pretest Test Mode	Description of Mode
1	TX
2	/

1.3 Test Setup

See photographs of the test setup in the report for the actual setup and connections between EUT and support equipment.

1.4 Ancillary Equipment

Equipment	Model	S/N	Manufacturer
/	/	/	/

2 Test Facilities and Accreditations

2.1 Test Laboratory

Test Site	Shenzhen HongBiao Certification& Testing Co., Ltd
Test Site Location	Room 102, 201, Building 2, Yuanwanggu RFID Industrial Park, Tongguan Road, Tianliao Community, Yutang Street, Guangming District, Shenzhen, China
Telephone:	(86-755) 2998 9321
Fax:	(86-755) 2998 5110
Designation Number:	848916
FCC Registration No.:	CN1341
A2LA Certificate No.:	6765.01

2.2 Environmental Conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15°C~35°C
Relative Humidity:	20%~75%
Air Pressure:	98kPa~101kPa

2.3 Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

The data and results quoted in this document are true and accurate values, and uncertainties are not involved in the calculations.

In addition, components and mass production processes that are similar to testing equipment may introduce additional deviations, and the manufacturer is solely responsible for the continued compliance of the equipment.

Measurement Frequency Range	U, (dB)	Note
RF frequency	2×10^{-5}	
RF power, conducted	± 0.57 dB	
Temperature	± 1 degree	
Humidity	± 5 %	

2.4 Test Software

Software name	Manufacturer	Model	Version
RF Test System	MWRF	MTS 8310	V2.0.0.0

3 List of Test Equipment

RF							
Item	Equipment No.	Equipment name	Manufacturer	Model	Serial No.	Calibration date	Due date
1	HB-E041	MXG Anaioog Signal Generator	Agilent	N5181A	MY47070421	2026-04-27	2027-04-26
2	HB-E042	WIDEBAND RADIO COMMUNICATION TESTER	R&S	CMW500	132108	2026-04-27	2027-04-26
3	HB-E043	MXG Anaioog Signal Generator	Agilent	N5182A	US46240335	2026-04-28	2027-04-27
4	HB-E044	Signal& spectrum Analyzer	R&S	FSV3044	101264	2026-04-28	2027-04-27
5	HB-E045	RF Control Box	Noyetec	NY100-R FCB	N/A	2026-04-28	2027-04-27
6	HB-E058	Thermometer Clock Humidity Monitor	N/A	HTC-1S	N/A	2026-04-30	2027-04-29

Note: the calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

4 RF Exposure

4.1 Standalone SAR test exclusion considerations

4.1.1. Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b).

Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = Numeric gain of the antenna relative to isotropic antenna

π = 3.1415926

R = distance between observation point and center of the radiator in cm (20cm)

P_d the limit of MPE, 1mW/cm².

If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

4.1.2. Test Result

2.4GHz WIFI:

Operation Frequency:

802.11b/g/n20: 2412-2462MHz

802.11n40: 2422-2452MHz

Antenna Type: PCB Antenna

Antenna gain: 4.65dBi

Power density limited: 1mW/ cm²

Antenna gain Numeric = $10^{(dBi/10)} = 10^{(4.65/10)} = 2.92$

2.4GHz WIFI(Worst):

Chann el Freq. (MHz)	modulatio n	Conduct ed Power (dBm)	Tune- up power (dBm)	Max		Antenna		Evaluation result	Power density Limits
		(dBm)		tune-up power		Gain		(mW/cm2)	(mW/cm2)
				(dBm)	(mW)	(dBi)	Num eric		
2437	802.11b	21.8	21±1	22	158.489	4.65	2.92	0.0920	1

According to KDB 447498 D01 General RF Exposure Guidance v06, At the transmit simultaneously calculation method is as follows:

Transmit simultaneously MPE = Σ of MPE ratios

MPE ratios = Field strengths or power density / MPE limit at the test frequency

For the max result: $0.0920 \leq 1g$ SAR, No SAR is required.

***** END OF REPORT *****