

**Shenzhen Global Test Service Co.,Ltd.**

Room No. 101, Building 1, and Room No. 101, Building 3, No. 88 Jinkang Road, Jinsha Community,
Kengzi Sub-district, Pingshan District, Shenzhen City, Guangdong ,China

RF Exposure evaluation**Report Reference No.....: GTS20260408009-2-06****FCC ID.....: 2AG7C-SFW24**

Compiled by

(position+printed name+signature)..: File administrators Peter Xiao

Supervised by

(position+printed name+signature)..: Test Engineer Evan Ouyang

Approved by

(position+printed name+signature)..: Manager Jason Hu



Date of issue.....: May 26, 2026

Representative Laboratory Name. : Shenzhen Global Test Service Co., Ltd.Address.....: Room No. 101, Building 1, and Room No. 101, Building 3, No. 88
Jinkang Road, Jinsha Community, Kengzi Sub-district, Pingshan
District, Shenzhen City, Guangdong ,China**Applicant's name.....: Hangzhou Meari Technology Co., Ltd.**Address.....: Building 4, Huiding Intelligent Innovation Center, No. 825, Ruquan
Road, Changhe Street, Binjiang District, Hangzhou, Zhejiang, China**Test specification.....:**Standard.....: **47CFR §1.1310 Basis and purpose**
47CFR §2.1091 Radiofrequency radiation exposure evaluation:
mobile devices**KDB447498 D01 General RF Exposure Guidance v06**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description.....: Baby Monitor

Trade Mark.....: N/A

Manufacturer.....: Hangzhou Meari Technology Co., Ltd.

Model/Type reference.....: Baby 14T

Listed Models: Baby 14Q, Baby 14TM, Baby 14QM, Baby 16T, Baby 16Q, Baby
12T, Baby 3Q, Baby 3T, Baby 12Q, Alnanny C3, Alnanny C3 Kit,
Alnanny B3, Alnanny B3 Kit, Alnanny F3, Alnanny B2, Alnanny B2
Kit, Alnanny C3-2Cam Kit, Alnanny-Cam, Alnanny A4

Hardware Version: BABY12T-A12MB-MIS9-REV1_0

Software Version.....: N/A

Rating.....: DC 5.0V by Adapter

Result.....: **PASS**

TEST REPORT

Test Report No. :	GTS20260408009-2-06	May 26, 2026
		Date of issue

Equipment under Test : Baby Monitor

Model /Type : Baby 14T

Listed model : Baby 14Q, Baby 14TM, Baby 14QM, Baby 16T, Baby 16Q, Baby 12T, Baby 3Q, Baby 3T, Baby 12Q, Alnanny C3, Alnanny C3 Kit, Alnanny B3, Alnanny B3 Kit, Alnanny F3, Alnanny B2, Alnanny B2 Kit, Alnanny C3-2Cam Kit, Alnanny-Cam, Alnanny A4

Applicant : **Hangzhou Meari Technology Co., Ltd.**

Address : Building 4, Huiding Intelligent Innovation Center, No. 825, Ruquan Road, Changhe Street, Binjiang District, Hangzhou, Zhejiang, China

Manufacturer : **Hangzhou Meari Technology Co., Ltd.**

Address : 2nd to 4th Floor, Building 2 and 3rd to 4th Floor, Building 1, No. 91, Chutian Road, Xixing Street, Binjiang District, Hangzhou, Zhejiang, China

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. SUMMARY 4

1.1 EUT CONFIGURATION 4

1.2 PRODUCT DESCRIPTION 4

2. TEST ENVIRONMENT 5

2.1 ADDRESS OF THE TEST LABORATORY 5

2.2 TEST FACILITY 5

2.3 ENVIRONMENTAL CONDITIONS 5

2.4 STATEMENT OF THE MEASUREMENT UNCERTAINTY 5

3. METHOD OF MEASUREMENT 6

3.1 APPLICABLE STANDARD 6

3.2 REQUIREMENT 6

3.3 LIMIT 6

3.4 MPE CALCULATION METHOD 7

3.5 ANTENNA INFORMATION 7

4. CONDUCTED POWER RESULTS 8

5. MANUFACTURING TOLERANCE 10

6. MEASUREMENT RESULTS 12

6.1 STANDALONE MPE EVALUATION 12

6.2 SIMULTANEOUS TRANSMISSION MPE 13

7. CONCLUSION 14

1. SUMMARY

1.1 EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

● Adapter	Length (m) :	/
	Shield :	/
	Detachable :	/

1.2 Product Description

Product Name	Baby Monitor
Trade Mark	N/A
Model/Type reference	Baby 14T
List Models	Baby 14Q, Baby 14TM, Baby 14QM, Baby 16T, Baby 16Q, Baby 12T, Baby 3Q, Baby 3T, Baby 12Q, Alnanny C3, Alnanny C3 Kit, Alnanny B3, Alnanny B3 Kit, Alnanny F3, Alnanny B2, Alnanny B2 Kit, Alnanny C3-2Cam Kit, Alnanny-Cam, Alnanny A4
Model Declaration	PCB board, structure and internal of these model(s) are the same, Only the model name different , So no additional models were tested.
Power supply:	DC 5.0V by Adapter
Sample ID	GTS20260408009-2-S001-1#>S20260408009-2-S001-2#
Bluetooth Low Energy	
Operation frequency	2402-2480MHz
Channel Number	40 channels for Bluetooth (DTS)
Channel Spacing	2MHz for Bluetooth (DTS)
Modulation Type	GFSK for Bluetooth (DTS)
WIFI(2.4G Band)	
Frequency Range	2412MHz ~ 2462MHz
Channel Spacing	5MHz
Channel Number	11 Channel for 20MHz bandwidth(2412~2462MHz) 7 Channel for 40MHz bandwidth(2422-2452MHz)
Modulation Type	802.11b: DSSS; 802.11g/n: OFDM; 802.11ax: OFDMA (it does not support partial RU for 802.11 ax mode)
WIFI(5.2G Band)	
Frequency Range	5180MHz ~ 5240MHz
Channel Number	4 Channels for 20MHz bandwidth(5180-5240MHz)
Modulation Type	802.11a/n: OFDM
WIFI (5.8G Band)	
Frequency Range	5745MHz ~ 5825MHz
Channel Number	5 channels for 20MHz bandwidth(5745-5825MHz)
Modulation Type	802.11a/n: OFDM
Antenna Description	FPC Antenna: 3.82dBi(Max.) for 2.4G Band and 3.18dBi(Max.) for 5G Band
SRD	
Operation frequency	2402-2480MHz
Channel Number	40 channels
Channel Bandwidth	2MHz, 4MHz
Modulation Type	GFSK
Antenna Description	Metal Antenna, 4.18dBi(Max.) for SRD

2. TEST ENVIRONMENT

2.1 Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

Room No. 101, Building 1, and Room No. 101, Building 3, No. 88 Jinkang Road, Jinsha Community, Kengzi Sub-district, Pingshan District, Shenzhen City, Guangdong, China

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1401.

FCC Registered Test Site Number is 684561.

2.3 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

2.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the Shenzhen Global Test Service Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

3. METHOD OF MEASUREMENT

3.1 Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

3.2 Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498 D01 General RF Exposure Guidance v06 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

3.3 Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3.4 MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna listed in below table, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained.

3.5 Antenna Information

Baby 14T can only use antennas certificated as follows provided by manufacturer;

Internal Identification	Antenna Identification in Internal photos	Antenna type and antenna number	Operate frequency band	Maximum antenna gain
Antenna 1	BLE&WLAN ANT	FPC antenna	2.4 – 2.5 GHz 5.0 – 6.0 GHz	3.82 dBi(Max.) for 2.4G band 3.18 dBi(Max.) for 5G band
Antenna 2	SRD ANT	Metal antenna	2.4 – 2.5 GHz	4.18 dBi(Max.) for 2.4G band

4. Conducted Power Results

BLE

Mode	Channel	Frequency (MHz)	Peak Power (dBm)
GFSK(BT LE)	0	2402	10.30
	19	2440	10.72
	39	2480	10.28

2.4GWLAN

Mode	Channel	Frequency (MHz)	Peak Conducted Output Power (dBm)
802.11b	01	2412	20.84
	06	2437	20.56
	11	2462	20.45
802.11g	01	2412	21.05
	06	2437	22.71
	11	2462	22.43
802.11n(HT20)	01	2412	20.96
	06	2437	22.54
	11	2462	22.39
802.11n(HT40)	03	2422	20.75
	06	2437	22.55
	09	2452	22.28
802.11ax(HE20)	01	2412	22.28
	06	2437	22.58
	11	2462	22.72
802.11ax(HE40)	03	2422	21.63
	06	2437	22.69
	09	2452	21.96

5.2GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	36	5180	14.55
	40	5200	15.05
	48	5240	15.23
802.11n20	36	5180	14.14
	40	5200	14.77
	48	5240	15.42

5.8GWLAN

Mode	Channel	Frequency (MHz)	Average Conducted Output Power (dBm)
802.11a	149	5745	15.82
	157	5785	15.19
	165	5825	15.42
802.11n20	149	5745	15.79
	157	5785	15.11
	165	5825	15.59

SRD

Mode	Channel	Frequency (MHz)	Peak Power (dBm)
GFSK(2MHz)	0	2402	16.09
	19	2440	16.69
	39	2480	10.34

Mode	Channel	Frequency (MHz)	Peak Power (dBm)
GFSK(4MHz)	0	2402	16.06
	19	2440	16.66
	39	2480	10.40

5. Manufacturing Tolerance

BLE

GFSK BT LE (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	10.0	10.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

2.4GWLAN

IEEE 802.11b (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	20.00	20.00	20.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11g (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	21.00	22.00	22.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	20.00	22.00	22.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT40 (Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	20.00	22.00	22.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE20 (Peak)			
Channel	Channel 01	Channel 06	Channel 11
Target (dBm)	22.00	22.00	22.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11ax HE40 (Peak)			
Channel	Channel 03	Channel 06	Channel 09
Target (dBm)	21.00	22.00	21.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.2GWLAN

IEEE 802.11a (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.00	15.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 36	Channel 40	Channel 48
Target (dBm)	14.00	14.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

5.8GWLAN

IEEE 802.11a (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	15.00	15.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0
IEEE 802.11n HT20 (Average)			
Channel	Channel 149	Channel 157	Channel 165
Target (dBm)	15.00	15.00	15.00
Tolerance $\pm$ (dB)	1.0	1.0	1.0

SRD

GFSK (Peak)			
Channel	Channel 0	Channel 19	Channel 39
Target (dBm)	16.0	16.0	10.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0

6. Measurement Results

6.1 Standalone MPE Evaluation

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$, as well as the gain of the used antenna refer to antenna information, the RF power density can be obtained.

BLE

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK(BT LE)	11.0	12.5893	3.82	2.4099	0.0060	1.0000

2.4G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11b	21.00	125.8925	3.82	2.4099	0.0604	1.0000
802.11g	23.00	199.5262	3.82	2.4099	0.0957	1.0000
802.11n(HT20)	23.00	199.5262	3.82	2.4099	0.0957	1.0000
802.11n(HT40)	23.00	199.5262	3.82	2.4099	0.0957	1.0000
802.11ax(HE20)	23.00	199.5262	3.82	2.4099	0.0957	1.0000
802.11ax(HE40)	23.00	199.5262	3.82	2.4099	0.0957	1.0000

5.2G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	16.00	39.8107	3.18	2.0797	0.0165	1.0000
802.11n20	16.00	39.8107	3.18	2.0797	0.0165	1.0000

5.8G WLAN

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
802.11a	16.00	39.8107	3.18	2.0797	0.0165	1.0000
802.11n20	16.00	39.8107	3.18	2.0797	0.0165	1.0000

SRD

Modulation Type	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	dBm	mW				
GFSK(SRD)	17.00	50.1187	4.18	2.6182	0.0261	1.0000

Remark:

1. Output power including tune-up tolerance;
2. MPE evaluate distance is 20cm from user manual provide by manufacturer;

6.2 Simultaneous Transmission MPE

The sample support one SRD modular and one BT&WLAN modular, and one SRD antenna and one BT&WLAN antenna, Need consider simultaneous transmission ;

According to KDB447498 D01 General RF Exposure Guidance v06 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;
 Σ of MPE ratios ≤ 1.0

8.2.1 Summary simultaneous transmission results

Maximum Simultaneous transmission MPE Ratios for 2.4GWLAN,5GWLAN,SRD

Maximum MPE ratio 2.4GWLAN	Maximum MPE ratio 5.2GWLAN	Maximum MPE ratio 5.8GWLAN	Maximum MPE ratio SRD	Σ MPE ratios	Limit	Results
0.0957	0.0165	0.0165	0.0261	0.1548	1.0	PASS

7. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB447498 D01 General RF Exposure Guidance v06, No SAR is required.

.....End of Report.....