FCC PART 15.247

TEST REPORT

For

Hangzhou Meari Technology Co., Ltd.

No.91, Chutian Road, Xixing Block, Binjiang, Hangzhou, China

FCC ID: 2AG7CMINI5C

Report Type:	**Product Type:**
Original Report	IP CAMERA

Test Engineer:	Chris Wang
Report Number:	RSHA171116007-00A
Report Date:	2017-11-28
Reviewed By:	Oscar Ye RF Leader
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road,Kunshan,Jiangsu province,China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION **4**
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
OBJECTIVE 4
RELATED SUBMITTAL(S)/GRANT(S) 4
TEST METHODOLOGY 4
MEASUREMENT UNCERTAINTY 5
TEST FACILITY 5
SYSTEM TEST CONFIGURATION **6**
DESCRIPTION OF TEST CONFIGURATION 6
EQUIPMENT MODIFICATIONS 6
EUT EXERCISE SOFTWARE 6
SUPPORT EQUIPMENT LIST AND DETAILS 9
EXTERNAL I/O CABLE 9
BLOCK DIAGRAM OF TEST SETUP 9
SUMMARY OF TEST RESULTS **11**
TEST EQUIPMENT LIST **12**
FCC §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE) **13**
APPLICABLE STANDARD 13
CALCULATED FORMULARY: 13
CALCULATED DATA: 13
FCC §15.203 - ANTENNA REQUIREMENT **14**
APPLICABLE STANDARD 14
ANTENNA CONNECTOR CONSTRUCTION 14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS **15**
APPLICABLE STANDARD 15
EUT SETUP 15
EMI TEST RECEIVER SETUP 15
TEST PROCEDURE 15
CORRECTED FACTOR & MARGIN CALCULATION 16
TEST RESULTS SUMMARY 16
TEST DATA 16
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS **19**
APPLICABLE STANDARD 19
EUT SETUP 19
EMI TEST RECEIVER SETUP 20
TEST PROCEDURE 20
CORRECTED AMPLITUDE & MARGIN CALCULATION 20
TEST RESULTS SUMMARY 20
TEST DATA 21
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH **44**
APPLICABLE STANDARD 44
TEST PROCEDURE 44
TEST DATA 44
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER **52**

FINAL

APPLICABLE STANDARD 52
TEST PROCEDURE 52
TEST DATA 52

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....54

APPLICABLE STANDARD 54
TEST PROCEDURE 54
TEST DATA 54

FCC §15.247(e) - POWER SPECTRAL DENSITY 59

APPLICABLE STANDARD 59
TEST PROCEDURE 59
TEST DATA 59

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Hangzhou Meari Technology Co., Ltd.
Tested Model	Mini 5C
Product Type	IP CAMERA
Dimension	53 mm(L)×32 mm(W)×280 mm(H)
Power Supply	DC 5.0V from Adapter

Adapter Information:
Model: TEKA006-0501000UK
Input: AC100-240V, 50/60Hz, 0.3A MAX
Output:5.0V, 1000mA

**All measurement and test data in this report was gathered from production sample serial number: 20171116007. (Assigned by BACL, Kunshan). The EUT was received on 2017-11-16.*

Objective

This report is prepared on behalf of Hangzhou Meari Technology Co., Ltd. in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

No Related Submittal(s)/Grant(s).

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and FCC KDB558074 D01 DTS Meas Guidance v04.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

FINAL

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road,Kunshan,Jiangsu province,China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

FINAL

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Channel List for 802.11b, 802.11g and 802.11n-HT20 mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

EUT was tested with Channel 1, 6 and 11.

Channel List for 802.11n-HT40 mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
3	2422	8	2447
4	2427	9	2452
5	2432	/	/
6	2437	/	/
7	2442	/	/

EUT was tested with Channel 3, 6 and 9.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

RF test tool : MP Tool

Pre-scan with all the data rates, and the worst case was performed as below:

Mode	Data rate	Power level
802.11b	1 Mbps	38
802.11g	6 Mbps	38
802.11n-HT20	MCS0	38
802.11n-HT40	MCS0	38

FINAL

Duty Cycle:

802.11b Mode Middle Channel



802.11g Mode Middle Channel



802.11n-HT20 Mode Middle Channel



Date: 19.NOV.2017 19:07:39

802.11n-HT40 Mode Middle Channel



Date: 19.NOV.2017 19:08:34

Mode	Duty Cycle	T(ms)	1/T(kHz)	10log(1/x)
802.11b	100%	/	/	0.0
802.11g	100%	/	/	0.0
802.11n-HT20	100%	/	/	0.0
802.11n-HT40	100%	/	/	0.0

Note: "x" means the Duty Cycle.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Shielding Type	Length (m)	From Port	To
USB Cable	Un-shielding	0.8	EUT	Adapter

Block Diagram of Test Setup

For Conducted Emissions:



For Radiated Emissions(Below 1GHz):



For Radiated Emissions(Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FINAL

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test（Chamber 1#）					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Sunol Sciences	Broadband Antenna	JB3	A040914-2	2016-01-09	2019-01-08
Sonoma Instrunent	Pre-amplifier	310N	171205	2017-08-15	2018-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-8	008	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2017-08-15	2018-08-14
Radiated Emission Test（Chamber 2#）					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2017-08-27	2018-08-26
ETS-LINDGREN	Horn Antenna	3115	6229	2016-01-11	2019-01-10
ETS-LINDGREN	Horn Antenna	3116	00084159	2016-10-18	2019-10-17
Narda	Pre-amplifier	AFS42-00101800	2001270	2016-12-12	2017-12-11
Heatsink Required	Amplifier	QLW-18405536-J0	15964001009	2016-12-12	2017-12-11
SINOSCITE	Band Reject Filter	BSF2402-2480MN-0898	/	/	/
Narda	Attenuator/10dB	10dB	/	/	/
Rohde & Schwarz	Auto test Software	EMC32	100361	/	/
MICRO-COAX	Coaxial Cable	Cable-6	006	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-11	011	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2017-08-15	2018-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2017-08-15	2018-08-14
RF Conducted Test					
Rohde & Schwarz	Signal Analyzer	FSIQ26	836131/009	2017-09-21	2018-09-20
Picosecond	DC Block	5500A-110	131047	2017-09-23	2018-09-22
Agilent	Power Meter	N1912A	MY5000492	2017-11-18	2018-11-17
Agilent	Power Sensor	N1921A	MY54210024	2017-11-18	2018-11-17
Meari	RF Cable	/	/	/	/
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2017-11-12	2018-11-11
Rohde & Schwarz	LISN	ESH3-Z5	862770/011	2017-11-12	2018-11-11
Rohde & Schwarz	LISN	ENV216	3560655016	2017-11-12	2018-11-11
BACL	BACL-EMC	V1.0	CE001	/	/
Narda	Attenuator/6dB	10690812-2	26850-6	2017-01-10	2018-01-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2017-08-15	2018-08-14

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310& §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247(i)and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	**Electric Field Strength (V/m)**	**Magnetic Field Strength (A/m)**	**Power Density (mW/cm²)**	**Averaging Time (minutes)**
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance
$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm^2);
P = power input to the antenna (in appropriate units, e.g., mW);
G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;
R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range	Antenna Gain		Output Power		Evaluation Distance	Power Density	MPE Limit
	(MHz)	(dBi)	(numeric)	(dBm)	(mW)	(cm)	(mW/cm^2)	(mW/cm^2)
802.11b	2412~2462	3.00	2.00	18.50	70.79	20	0.0281	1.0
802.11g		3.00	2.00	18.50	70.79	20	0.0281	1.0
802.11n-HT20		3.00	2.00	18.50	70.79	20	0.0281	1.0
802.11n-HT40	2422~2452	3.00	2.00	16.00	39.81	20	0.0158	1.0

Note: For the above target output power are all declared by the manufacturer.

Result: The device meet FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

a. Antenna must be permanently attached to the unit.
b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.
And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an on-board antenna arrangement for Wi-Fi, which the antenna gain is 3.0 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FINAL

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

Correction Factor = LISN VDF + Cable Loss

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit –Reading

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data

Environmental Conditions

Temperature:	24.2℃
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Chris Wang on 2017-11-21.

EUT operation mode: Transmitting in 802.11n-HT20 mode Middle channel

FINAL

AC 120V/60 Hz, Line



Frequency (MHz)	Reading (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corr. (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	39.16	QP	9.000	L1	16.06	66.00	26.84	Compliance
0.150	22.17	AV	9.000	L1	16.06	56.00	33.83	Compliance
0.230	35.09	QP	9.000	L1	16.02	63.71	28.62	Compliance
0.230	19.30	AV	9.000	L1	16.02	53.71	34.41	Compliance
0.710	31.18	QP	9.000	L1	15.95	56.00	24.82	Compliance
0.710	23.89	AV	9.000	L1	15.95	46.00	22.11	Compliance
3.200	22.31	QP	9.000	L1	15.85	56.00	33.69	Compliance
3.200	16.37	AV	9.000	L1	15.85	46.00	29.63	Compliance
9.150	19.72	QP	9.000	L1	16.04	60.00	40.28	Compliance
9.150	12.55	AV	9.000	L1	16.04	50.00	37.45	Compliance
18.600	30.61	QP	9.000	L1	16.38	60.00	29.39	Compliance
18.600	18.15	AV	9.000	L1	16.38	50.00	31.85	Compliance

AC 120V/60 Hz, Neutral



Frequency (MHz)	Reading (dBμV)	Detector (PK/AV/QP)	Bandwidth (kHz)	Line	Corr. (dB)	Limit (dBμV)	Margin (dB)	Comment
0.150	39.55	QP	9.000	N	16.06	66.00	26.45	Compliance
0.150	22.36	AV	9.000	N	16.06	56.00	33.64	Compliance
0.210	36.73	QP	9.000	N	16.05	64.29	27.56	Compliance
0.210	19.66	AV	9.000	N	16.05	54.29	34.63	Compliance
0.710	31.08	QP	9.000	N	15.99	56.00	24.92	Compliance
0.710	23.64	AV	9.000	N	15.99	46.00	22.36	Compliance
4.500	21.82	QP	9.000	N	15.88	56.00	34.18	Compliance
4.500	15.66	AV	9.000	N	15.88	46.00	30.34	Compliance
8.350	22.39	QP	9.000	N	15.95	60.00	37.61	Compliance
8.350	15.57	AV	9.000	N	15.95	50.00	34.43	Compliance
17.350	30.29	QP	9.000	N	16.08	60.00	29.71	Compliance
17.350	16.69	AV	9.000	N	16.08	50.00	33.31	Compliance

Note:
1) Corr.=LISN VDF (Voltage Division Factor) + Cable Loss
2) Margin = Limit – Reading

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude = Meter Reading + Antenna Factor + Cable Loss - Amplifier Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	24.2℃
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Chris Wang on 2017-11-24.

EUT operation mode: Transmitting(Scan with X-Axis, Y-Axis and Z-Axis position, the worst case X-Axis was recorded)

30MHz-1G



Frequency (MHz)	Corrected Amplitude QuasiPeak (dBµV/m)	Rx Antenna Height (cm)	Rx Antenna Polar (H/V)	Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
958.290000	35.22	100.0	H	104.0	1.4	46.00	10.78
200.720000	22.65	100.0	V	296.0	-12.8	43.50	20.85
30.000000	28.93	100.0	V	355.0	-4.4	40.00	11.07
120.210000	21.90	200.0	H	34.0	-11.6	43.50	21.60
538.280000	27.82	200.0	H	351.0	-5.8	46.00	18.18
62.010000	16.97	200.0	V	193.0	-18.2	40.00	23.03

802.11b Mode:

Note:
1. This test is performed with the 2.4-2.4835GHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
   Corrected Amplitude = Corrected Factor + Reading
   Margin = Limit - Corrected. Amplitude
3. The emission in 18-25GHz which is 20dB below the limit was not recorded.

1G-25G

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1598.400000	36.53	---	200.0	V	188.0	-9.8	74.00	37.47
1598.400000	---	25.29	200.0	V	188.0	-9.8	54.00	28.71
3597.600000	36.24	---	150.0	V	327.0	-3.6	74.00	37.76
3597.600000	---	34.80	150.0	V	327.0	-3.6	54.00	19.20
4821.600000	48.17	---	100.0	V	357.0	-0.5	74.00	25.83
4821.600000	---	39.64	100.0	V	357.0	-0.5	54.00	14.36
7235.600000	---	47.50	250.0	V	7.0	6.4	54.00	6.50
7235.600000	52.36	---	250.0	V	7.0	6.4	74.00	21.64
11104.800000	---	42.97	250.0	V	342.0	11.8	54.00	11.03
11104.800000	52.59	---	150.0	V	109.0	11.8	74.00	21.41
14392.600000	---	46.79	100.0	V	0.0	16.7	54.00	7.21
14392.600000	56.76	---	200.0	V	278.0	16.7	74.00	17.24

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1595.000000	---	25.33	200.0	V	194.0	-9.8	54.00	28.67
1595.000000	36.55	---	200.0	V	194.0	-9.8	74.00	37.45
3376.600000	---	28.55	150.0	V	0.0	-4.1	54.00	25.45
3376.600000	39.34	---	200.0	V	90.0	-4.1	74.00	34.66
4872.600000	---	38.24	100.0	V	0.0	-0.4	54.00	15.76
4872.600000	48.26	---	100.0	V	0.0	-0.4	74.00	25.74
7310.400000	---	45.34	100.0	V	0.0	6.6	54.00	8.66
7310.400000	51.62	---	250.0	V	353.0	6.6	74.00	22.38
10016.800000	49.07	---	100.0	V	7.0	9.1	74.00	24.93
10016.800000	---	42.02	150.0	V	248.0	9.1	54.00	11.98
14215.800000	---	44.75	150.0	V	270.0	16.7	54.00	9.25
14215.800000	56.67	---	150.0	V	270.0	16.7	74.00	17.33

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1591.600000	---	26.17	150.0	V	210.0	-9.8	54.00	27.83
1591.600000	34.62	---	150.0	V	210.0	-9.8	74.00	39.38
3070.600000	---	29.52	200.0	V	172.0	-4.6	54.00	24.48
3070.600000	38.81	---	250.0	V	158.0	-4.6	74.00	35.19
4923.600000	45.79	---	100.0	H	343.0	-0.3	74.00	28.21
4923.600000	---	36.78	100.0	H	343.0	-0.3	54.00	17.22
7385.200000	50.64	---	250.0	V	0.0	6.8	74.00	23.36
7385.200000	---	44.72	250.0	V	0.0	6.8	54.00	9.28
9374.200000	---	39.75	100.0	V	9.0	8.6	54.00	14.25
9374.200000	50.41	---	250.0	V	173.0	8.6	74.00	23.59
14447.000000	54.50	---	150.0	H	90.0	16.7	74.00	19.50
14447.000000	---	47.18	100.0	H	181.0	16.7	54.00	6.82

Radiation Spurious Restricted Band Edge:

Note:
1. This test is performed with a 10dB Attenuator.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
3. Corrected Amplitude = Corrected Factor + Reading
4. Margin = Limit - Corrected. Amplitude

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.00	---	39.18	150.0	V	219.0	2.6	54.00	14.82
2390.00	46.87	---	200.0	V	216.0	2.6	74.00	27.13
High Channel: 2462MHz								
2483.50	---	38.79	250.0	V	14.0	2.8	54.00	15.21
2483.50	48.29	---	250.0	V	14.0	2.8	74.00	25.71

FINAL

802.11g Mode:

Note:
1. This test is performed with the 2.4-2.4835GHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
   Corrected Amplitude = Corrected Factor + Reading
   Margin = Limit - Corrected. Amplitude
3. The emission in 18-25GHz which is 20dB below the limit was not recorded.

1G-25G

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1771.800000	38.32	---	150.0	V	322.0	-9.1	74.00	35.68
1771.800000	---	24.56	150.0	V	322.0	-9.1	54.00	29.44
3070.600000	39.61	---	200.0	V	167.0	-4.6	74.00	34.39
3070.600000	---	30.50	250.0	V	164.0	-4.6	54.00	23.50
4821.600000	---	33.25	250.0	V	271.0	-0.5	54.00	20.75
4821.600000	40.96	---	200.0	V	229.0	-0.5	74.00	33.04
7235.600000	46.12	---	100.0	V	12.0	6.4	74.00	27.88
7235.600000	---	37.98	250.0	V	119.0	6.4	54.00	16.02
8867.600000	49.04	---	100.0	H	270.0	8.4	74.00	24.96
8867.600000	---	41.13	200.0	H	0.0	8.4	54.00	12.87
14246.400000	---	45.49	150.0	V	233.0	16.7	54.00	8.51
14246.400000	56.49	---	250.0	V	50.0	16.7	74.00	17.51

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1496.400000	33.40	---	100.0	V	224.0	-10.3	74.00	40.60
1496.400000	---	25.56	100.0	V	224.0	-10.3	54.00	28.44
3407.200000	38.05	---	250.0	V	105.0	-4.0	74.00	35.95
3407.200000	---	30.75	250.0	V	105.0	-4.0	54.00	23.25
4876.000000	43.56	---	150.0	H	0.0	-0.4	74.00	30.44
4876.000000	---	33.92	100.0	H	264.0	-0.4	54.00	20.08
7310.400000	---	37.46	150.0	H	193.0	6.6	54.00	16.54
7310.400000	47.54	---	250.0	H	340.0	6.6	74.00	26.46
9231.400000	49.65	---	200.0	V	218.0	8.5	74.00	24.35
9234.800000	---	38.77	200.0	V	75.0	8.5	54.00	15.23
13559.600000	---	45.57	100.0	V	5.0	17.2	54.00	8.43
13559.600000	55.88	---	150.0	V	0.0	17.2	74.00	18.12

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1598.400000	---	24.64	100.0	V	107.0	-9.8	54.00	29.36
1598.400000	36.07	---	150.0	V	195.0	-9.8	74.00	37.93
3070.600000	---	29.57	250.0	V	168.0	-4.6	54.00	24.43
3070.600000	37.92	---	200.0	V	77.0	-4.6	74.00	36.08
4923.600000	40.93	---	250.0	H	127.0	-0.3	74.00	33.07
4923.600000	---	33.55	100.0	H	0.0	-0.3	54.00	20.45
7385.200000	45.59	---	150.0	H	15.0	6.8	74.00	28.41
7385.200000	---	37.91	200.0	H	343.0	6.8	54.00	16.09
9377.600000	---	39.86	150.0	V	255.0	8.6	54.00	14.14
9377.600000	50.57	---	100.0	V	2.0	8.6	74.00	23.43
13682.000000	---	45.37	150.0	V	104.0	17.1	54.00	8.63
13682.000000	55.51	---	100.0	V	328.0	17.1	74.00	18.49

Radiation Spurious Restricted Band Edge:

Note:
1. This test is performed with a 10dB Attenuator.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
3. Corrected Amplitude = Corrected Factor + Reading
4. Margin = Limit - Corrected. Amplitude

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.00	---	39.75	150.0	V	353.0	2.6	54.00	14.25
2390.00	46.66	---	250.0	V	353.0	2.6	74.00	27.34
High Channel: 2462MHz								
2483.50	---	40.42	200.0	V	225.0	2.8	54.00	13.58
2483.50	46.13	---	150.0	V	188.0	2.8	74.00	27.87

FINAL

802.11n-HT20 Mode:

Note:
1. This test is performed with the 2.4-2.4835GHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
   Corrected Amplitude = Corrected Factor + Reading
   Margin = Limit - Corrected. Amplitude
3. The emission in 18-25GHz which is 20dB below the limit was not recorded.

1G-25G

Low Channel: 2412MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1595.000000	---	28.77	250.0	V	173.0	-9.8	54.00	25.23
1595.000000	37.84	---	250.0	V	173.0	-9.8	74.00	36.16
3070.600000	38.31	---	200.0	V	171.0	-4.6	74.00	35.69
3070.600000	---	29.80	200.0	V	171.0	-4.6	54.00	24.20
4821.600000	---	33.09	200.0	H	255.0	-0.5	54.00	20.91
4821.600000	42.31	---	250.0	H	0.0	-0.5	74.00	31.69
7235.600000	47.77	---	100.0	V	0.0	6.4	74.00	26.23
7235.600000	---	38.85	100.0	V	0.0	6.4	54.00	15.15
9435.400000	---	39.90	200.0	H	270.0	8.6	54.00	14.10
9435.400000	48.10	---	100.0	H	238.0	8.6	74.00	25.90
14022.000000	---	45.58	250.0	V	356.0	16.7	54.00	8.42
14022.000000	56.60	---	250.0	V	356.0	16.7	74.00	17.40

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
2122.000000	---	25.76	100.0	V	142.0	-8.0	54.00	28.24
2122.000000	37.40	---	100.0	V	142.0	-8.0	74.00	36.60
3475.200000	38.51	---	100.0	H	97.0	-3.9	74.00	35.49
3475.200000	---	30.55	150.0	H	8.0	-3.9	54.00	23.45
4876.000000	41.46	---	100.0	V	326.0	-0.4	74.00	32.54
4876.000000	---	34.19	200.0	V	142.0	-0.4	54.00	19.81
7307.000000	47.06	---	250.0	V	0.0	6.6	74.00	26.94
7307.000000	---	38.22	100.0	V	0.0	6.6	54.00	15.78
10020.200000	---	41.53	200.0	V	172.0	9.1	54.00	12.47
10020.200000	51.50	---	200.0	V	172.0	9.1	74.00	22.50
13705.800000	---	45.47	100.0	V	247.0	17.0	54.00	8.53
13705.800000	55.66	---	100.0	V	247.0	17.0	74.00	18.34

High Channel: 2462MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1843.200000	---	24.72	150.0	V	309.0	-8.9	54.00	29.28
1843.200000	37.73	---	150.0	V	309.0	-8.9	74.00	36.27
3597.600000	38.20	---	100.0	V	173.0	-3.6	74.00	35.80
3597.600000	---	37.03	100.0	V	173.0	-3.6	54.00	16.97
4923.600000	40.43	---	250.0	H	269.0	-0.3	74.00	33.57
4923.600000	---	33.21	100.0	H	357.0	-0.3	54.00	20.79
7385.200000	45.77	---	100.0	V	17.0	6.8	74.00	28.23
7385.200000	---	39.84	150.0	V	359.0	6.8	54.00	14.16
9846.800000	---	40.96	200.0	V	205.0	9.0	54.00	13.04
9846.800000	51.59	---	200.0	V	205.0	9.0	74.00	22.41
14124.000000	---	46.21	250.0	V	355.0	16.7	54.00	7.79
14124.000000	56.65	---	250.0	V	355.0	16.7	74.00	17.35

Radiation Spurious Restricted Band Edge:

Note:
1. This test is performed with a 10dB Attenuator.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
3. Corrected Amplitude = Corrected Factor + Reading
4. Margin = Limit - Corrected. Amplitude

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.00	47.03	---	150.0	V	130.0	2.6	74.00	26.97
2390.00	---	39.25	150.0	V	130.0	2.6	54.00	14.75
High Channel: 2462MHz								
2483.50	---	40.63	200.0	V	342.0	2.8	54.00	13.37
2483.50	48.34	---	250.0	V	0.0	2.8	74.00	25.66

FINAL

802.11n-HT40 Mode:

Note:
1. This test is performed with the 2.4-2.4835GHz band reject filter.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
   Corrected Amplitude = Corrected Factor + Reading
   Margin = Limit - Corrected. Amplitude
3. The emission in 18-25GHz which is 20dB below the limit was not recorded.

1G-25G

Low Channel: 2422MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1676.600000	35.58	---	100.0	V	19.0	-9.5	74.00	38.42
1676.600000	---	25.62	150.0	V	219.0	-9.5	54.00	28.38
3488.800000	38.66	---	250.0	H	113.0	-3.9	74.00	35.34
3488.800000	---	28.82	100.0	H	80.0	-3.9	54.00	25.18
4845.400000	---	33.90	200.0	V	194.0	-0.5	54.00	20.10
4845.400000	40.01	---	200.0	V	194.0	-0.5	74.00	33.99
7269.600000	46.98	---	150.0	H	313.0	6.5	74.00	27.02
7269.600000	---	38.33	200.0	H	184.0	6.5	54.00	15.67
9007.000000	---	39.16	150.0	V	65.0	8.5	54.00	14.84
9007.000000	49.90	---	150.0	V	65.0	8.5	74.00	24.10
11098.000000	53.95	---	250.0	V	125.0	11.8	74.00	20.05
11098.000000	---	42.38	250.0	V	125.0	11.8	54.00	11.62

Middle Channel: 2437MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1574.600000	35.09	---	250.0	V	202.0	-9.9	74.00	38.91
1574.600000	---	26.67	250.0	V	202.0	-9.9	54.00	27.33
3692.800000	---	29.51	150.0	V	0.0	-3.3	54.00	24.49
3692.800000	39.36	---	200.0	V	233.0	-3.3	74.00	34.64
4876.000000	40.71	---	150.0	V	59.0	-0.4	74.00	33.29
4876.000000	---	33.28	150.0	V	59.0	-0.4	54.00	20.72
7317.200000	---	37.74	250.0	V	127.0	6.6	54.00	16.26
7317.200000	48.30	---	250.0	V	127.0	6.6	74.00	25.70
10003.200000	---	41.64	100.0	H	127.0	9.1	54.00	12.36
10003.200000	50.33	---	200.0	H	353.0	9.1	74.00	23.67
13964.200000	---	45.03	200.0	V	97.0	16.7	54.00	8.97
13964.200000	55.77	---	200.0	V	97.0	16.7	74.00	18.23

High Channel: 2452MHz



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV /m)	Average (dBµV /m)	Height (cm)	Polar (H/V)				
1595.000000	---	26.73	250.0	V	216.0	-9.8	54.00	27.27
1595.000000	37.42	---	250.0	V	216.0	-9.8	74.00	36.58
3509.200000	---	29.31	200.0	H	288.0	-3.9	54.00	24.69
3509.200000	39.22	---	200.0	H	288.0	-3.9	74.00	34.78
4903.200000	---	33.34	250.0	H	34.0	-0.4	54.00	20.66
4903.200000	40.71	---	100.0	H	4.0	-0.4	74.00	33.29
7358.000000	45.18	---	100.0	V	352.0	6.8	74.00	28.82
7358.000000	---	38.13	100.0	V	352.0	6.8	54.00	15.87
9904.600000	---	41.28	200.0	V	269.0	9.0	54.00	12.72
9904.600000	47.73	---	200.0	V	269.0	9.0	74.00	26.27
14229.400000	55.93	---	200.0	V	299.0	16.7	74.00	18.07
14229.400000	---	45.18	200.0	V	299.0	16.7	54.00	8.82

Radiation Spurious Restricted Band Edge:

Note:
1. This test is performed with a 10dB Attenuator.
2. Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor
3. Corrected Amplitude = Corrected Factor + Reading
4. Margin = Limit - Corrected. Amplitude

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corr. (dB)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
Low Channel: 2422MHz								
2390.00	---	39.48	200.0	V	143.0	2.6	54.00	14.52
2390.00	48.73	---	200.0	V	143.0	2.6	74.00	25.27
High Channel: 2452MHz								
2483.50	47.56	---	200.0	V	141.0	2.8	74.00	26.44
2483.50	---	41.43	200.0	V	141.0	2.8	54.00	12.57

FINAL

Conducted Spurious Emissions at Antenna Port

802.11b Low Channel



802.11b Middle Channel



802.11b High Channel



802.11g Low Channel



802.11g Middle Channel



802.11g High Channel



802.11n-HT20 Low Channel



802.11n-HT20 Middle Channel



802.11n-HT20 High Channel



802.11n-HT40 Low Channel



802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3xRBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Test Data

Environmental Conditions

Temperature:	24.2℃
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Chris Wang on 2017-11-19 to 2017-11-22.

Test Result: Pass.

FINAL

EUT operation mode: Transmitting

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b mode			
Low	2412	9.08	≥0.5
Middle	2437	9.08	≥0.5
High	2462	9.08	≥0.5
802.11g mode			
Low	2412	16.59	≥0.5
Middle	2437	16.59	≥0.5
High	2462	16.59	≥0.5
802.11n-HT20 mode			
Low	2412	17.86	≥0.5
Middle	2437	17.86	≥0.5
High	2462	17.80	≥0.5
802.11n-HT40 mode			
Low	2422	36.55	≥0.5
Middle	2437	36.55	≥0.5
High	2452	36.55	≥0.5

FINAL

802.11b Low Channel



802.11b Middle Channel



802.11b High Channel



802.11g Low Channel



802.11g Middle Channel



802.11g High Channel



802.11n-HT20 Low Channel



802.11n-HT20 Middle Channel



802.11n-HT20 High Channel



802.11n-HT40 Low Channel



802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	24.2℃
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Chris Wang on 2017-11-20.

EUT operation mode: Transmitting

FINAL

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
802.11b				
Low	2412	17.25	30	Pass
Middle	2437	17.59	30	Pass
High	2462	17.27	30	Pass
802.11g				
Low	2412	17.30	30	Pass
Middle	2437	17.50	30	Pass
High	2462	17.70	30	Pass
802.11n-HT20				
Low	2412	17.30	30	Pass
Middle	2437	18.00	30	Pass
High	2462	17.50	30	Pass
802.11n-HT40				
Low	2422	14.91	30	Pass
Middle	2437	15.29	30	Pass
High	2452	15.24	30	Pass

FINAL

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24.2℃
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Chris Wang on 2017-11-20 to 2017-11-22.

Test Result: *Compliance*

FINAL

Band Edge

802.11b Mode Left Side



802.11b Mode Right Side



802.11g Mode Left Side



802.11g Mode Right Side



802.11n-HT20 Mode Left Side



802.11n-HT20 Mode Right Side



802.11n-HT40 Mode Left Side



802.11n-HT40 Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB558074 D01 DTS Meas Guidance v04 sub-clause 10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: 3kHz≤ RBW≤100 kHz.
3. Set the VBW ≥ 3×RBW.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	24.2℃
Relative Humidity:	51 %
ATM Pressure:	101.2 kPa

The testing was performed by Chris Wang on 2017-11-19.

EUT operation mode: Transmitting

Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b mode			
Low	2412	-16.12	≤8
Middle	2437	-16.93	≤8
High	2462	-17.72	≤8
802.11g mode			
Low	2412	-19.31	≤8
Middle	2437	-20.09	≤8
High	2462	-20.17	≤8
802.11n-HT20 mode			
Low	2412	-18.82	≤8
Middle	2437	-19.72	≤8
High	2462	-20.16	≤8
802.11n-HT40 mode			
Low	2422	-21.38	≤8
Middle	2437	-22.63	≤8
High	2452	-21.54	≤8

FINAL

802.11b Low Channel



802.11b Middle Channel



802.11b High Channel



802.11g Low Channel



802.11g Middle Channel



802.11g High Channel



802.11n-HT20 Low Channel



802.11n-HT20 Middle Channel



802.11n-HT20 High Channel



802.11n-HT40 Low Channel



802.11n-HT40 Middle Channel



802.11n-HT40 High Channel



******* END OF REPORT *******