

TEST REPORT

FCC ID: 2AG86-SAU40T1

Product: WiFi Gateway Thermostat

Model No.: SAU40T1

Additional Model No.: ST910WZ, HHT10WZ, SAU41T1

Trade Mark: N/A

Report No.: TCT171017E035

Issued Date: Oct. 20, 2017

Issued for:

Salus North America, Inc.

850 Main Street, Redwood City, California 94063

Issued By:

Shenzhen Tongce Testing Lab.

**1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District,
Shenzhen, Guangdong, China**

TEL: +86-755-27673339

FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. Test Certification	3
2. Test Result Summary	4
3. EUT Description.....	5
4. General Information.....	6
4.1. Test environment and mode.....	6
4.2. Description of Support Units.....	6
5. Facilities and Accreditations	7
5.1. Facilities	7
5.2. Location	7
5.3. Measurement Uncertainty	7
6. Test Results and Measurement Data	8
6.1. Antenna requirement.....	8
6.2. Conducted Emission	9
6.3. Conducted Output Power	13
6.4. Emission Bandwidth	16
6.5. Power Spectral Density.....	19
6.6. Test Specification	19
6.7. Conducted Band Edge and Spurious Emission Measurement	22
6.8. Radiated Spurious Emission Measurement	25

Appendix A: Photographs of Test Setup

Appendix B: Photographs of EUT

1. Test Certification

Product:	WiFi Gateway Thermostat
Model No.:	SAU40T1
Additional Model No.:	ST910WZ, HHT10WZ, SAU41T1
Trade Mark:	N/A
Applicant:	Salus North America, Inc.
Address:	850 Main Street, Redwood City, California 94063
Manufacturer:	Salus North America, Inc.
Address:	850 Main Street, Redwood City, California 94063
Factory 1:	Computime Electronics(shenzhen) Company Limited
Address of Factory 1:	Yuekenguangyu Industrial Park, kangqiao Road 88#, Danzhutou Community, Nanwan Street Office, Longgang District, Shenzhen 518114
Factory 2:	Asia Electronic Dongguan
Address of Factory 2:	Zhen'an Science and Technology Industrial Park, Chang'an Dongguan Guangdong, PRC
Date of Test:	Sep. 15, 2017 – Sep. 28, 2017
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 KDB 558074 D01 DTS Meas Guidance v04

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By:



Beryl Zhao

Date:

Sep. 28, 2017

Reviewed By:



Joe Zhou

Date:

Oct. 20, 2017


Approved By:



Tomsin

Date:

Oct. 20, 2017



2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(3) §2.1046	PASS
6dB Emission Bandwidth	§15.247 (a)(2) §2.1049	PASS
Power Spectral Density	§15.247 (e)	PASS
Band Edge	§15.247(d) §2.1051, §2.1057	PASS
Spurious Emission	§15.205/§15.209 §2.1053, §2.1057	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. EUT Description

Product:	WiFi Gateway Thermostat
Model No.:	SAU40T1
Additional Model No.:	ST910WZ, HHT10WZ, SAU41T1
Trade Mark:	N/A
Operation Frequency:	2405MHz~2480MHz
Channel Separation:	5MHz
Number of Channel:	16
Modulation Technology:	O-QPSK
Antenna Type:	Integral Antenna
Antenna Gain:	5.2dBi
Power Supply:	AC 24V
Remark:	All above models are identical in the same PCB layout, interior structure and electrical circuits. The only differences are the model name and color for commercial purpose.

Operation Frequency each of channel

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2405MHz	5	2425MHz	9	2445MHz	13	2465MHz
2	2410MHz	6	2430MHz	10	2450MHz	14	2470MHz
3	2415MHz	7	2435MHz	11	2455MHz	15	2475MHz
4	2420MHz	8	2440MHz	12	2460MHz	16	2480 MHz

Remark: Channel 1, 8 & 16 have been tested.

4. Genera Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	25.0 °C
Humidity:	56 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Engineering mode:	Keep the EUT in continuous transmitting by select channel and modulations(The value of duty cycle is 98.46%) with Fully-charged battery.
The sample was placed (0.1m below 1GHz, 1.5m above 1GHz) above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
AC Adapter	AH66-2403AC	N/A	N/A	N/A

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. For conducted measurements (Output Power, 6dB Emission Bandwidth, Power Spectral Density, Spurious Emissions), the antenna of EUT is connected to the test equipment via temporary antenna connector, the antenna connector is soldered on the antenna port of EUT, and the temporary antenna connector is listed in the Test Instruments.

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 645098

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1B/F., Building 1, Yibaolai Industrial Park, Qiaotou, Fuyong, Baoan District, Shenzhen, Guangdong, China

TEL: +86-755-27673339

5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^{\circ}\text{C}$
7	Humidity	$\pm 1.0\%$

6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:

FCC Part15 C Section 15.203 /247(c)

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.


E.U.T Antenna:

The antenna is a integral antenna which permanently attached, and the best case gain of the antenna is 5.2dBi.



6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.10:2013														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane  <i>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</i>														
Test Mode:	Charging + Transmitting Mode														
Test Procedure:	1. The E.U.T is connected to an adapter through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.														
Test Result:	PASS														

6.2.2. Test Instruments


Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	R&S	ESPI	101401	Jun. 12, 2018
LISN	Schwarzbeck	NSLK 8126	8126453	Sep. 27, 2018
Coax cable (9KHz-30MHz)	TCT	CE-05	N/A	Sep. 27, 2018
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)




Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.234	24.96	0.43	0.12	25.51	62.30	-36.79	QP
0.320	28.95	0.44	0.10	29.49	59.71	-30.22	QP
0.634	30.94	0.30	0.13	31.37	56.00	-24.63	QP
0.708	26.31	0.28	0.13	26.72	56.00	-29.28	QP
0.839	22.73	0.26	0.13	23.12	56.00	-32.88	QP
2.384	18.60	0.20	0.15	18.95	56.00	-37.05	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)




Freq MHz	Reading level dBuV	LISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.234	25.03	0.42	0.12	25.57	62.30	-36.73	QP
0.320	28.43	0.42	0.10	28.95	59.71	-30.76	QP
0.634	27.30	0.26	0.13	27.69	56.00	-28.31	QP
0.708	23.65	0.24	0.13	24.02	56.00	-31.98	QP
1.568	21.44	0.20	0.14	21.78	56.00	-34.22	QP
6.420	18.32	0.21	0.16	18.69	60.00	-41.31	QP

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

6.3. Conducted Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074
Limit:	30dBm
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Refer to item 4.1
Test Procedure:	- The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v04. - Set spectrum analyzer as following: - Set the RBW $\geq$ DTS bandwidth. - Set VBW $\geq 3 \times$ RBW. - Set span $\geq 3 \times$ RBW - Sweep time = auto couple. - Detector = peak. - Trace mode = max hold. - Allow trace to fully stabilize. - Use peak marker function to determine the peak amplitude level.
Test Result:	PASS

6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 27, 2018
RF cable (9kHz-26.5GHz)	TCT	RE-06	N/A	Sep. 27, 2018
Antenna Connector	TCT	RFC-01	N/A	Sep. 27, 2018


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.3.3. Test Data


Test channel	Maximum Conducted Output Power (dBm)	Limit (dBm)	Result
Lowest	18.68	30.00	PASS
Middle	18.67	30.00	PASS
Highest	18.61	30.00	PASS

Test plots as follows:


Lowest channel



Middle channel




Highest channel



6.4. Emission Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074
Limit:	>500kHz
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Refer to item 4.1
Test Procedure:	1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v04. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz. 4. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 27, 2018
RF cable (9kHz-26.5GHz)	TCT	RE-06	N/A	Sep. 27, 2018
Antenna Connector	TCT	RFC-01	N/A	Sep. 27, 2018


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.4.3. Test data


Test channel	6dB Emission Bandwidth (kHz)		
	O-QPSK mode	Limit	Result
Lowest	1606.00	>500k	PASS
Middle	1598.00	>500k	
Highest	1645.00	>500k	

Test plots as follows:


Lowest channel



Middle channel




Highest channel



6.5. Power Spectral Density

6.6. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074
Limit:	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Refer to item 4.1
Test Procedure:	1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v04 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$. Video bandwidth VBW $\geq 3 \times \text{RBW}$. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW) 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level. 6. Measure and record the results in the test report.
Test Result:	PASS

6.6.1. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 27, 2018
RF cable (9kHz-26.5GHz)	TCT	RE-06	N/A	Sep. 27, 2018
Antenna Connector	TCT	RFC-01	N/A	Sep. 27, 2018


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.6.2. Test data


Test channel	Power Spectral Density (dBm/3kHz)		
	O-QPSK mode	Limit	Result
Lowest	3.80	8 dBm/3kHz	PASS
Middle	2.74	8 dBm/3kHz	
Highest	2.18	8 dBm/3kHz	

Test plots as follows:


Lowest channel



Middle channel




Highest channel



6.7. Conducted Band Edge and Spurious Emission Measurement

6.7.1. Test Specification


Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074
Limit:	In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).
Test Setup:	 The diagram illustrates the test setup. On the left is a green box representing the Spectrum Analyzer. A cable connects it to a small white box representing an attenuator. Another cable connects the attenuator to a yellow box representing the EUT (Equipment Under Test).
Test Mode:	Refer to item 4.1
Test Procedure:	1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d). 4. Measure and record the results in the test report. 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS

6.7.2. Test Instruments


RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Sep. 27, 2018
Spectrum Analyzer	ROHDE&SCHWARZ	FSQ	200061	Sep. 27, 2018
RF cable (9kHz-26.5GHz)	TCT	RE-06	N/A	Sep. 27, 2018
Antenna Connector	TCT	RFC-01	N/A	Sep. 27, 2018

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.7.3. Test Data




Spurious emission




Middle Channel

Band Edge




Spurious emission




Highest Channel


6.8. Radiated Spurious Emission Measurement

6.8.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10: 2013				
Frequency Range:	9 kHz to 25 GHz				
Measurement Distance:	3 m				
Antenna Polarization:	Horizontal & Vertical				
Operation mode:	Refer to item 4.1				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz- 150kHz	Quasi-peak	200Hz	1kHz	Quasi-peak Value
	150kHz- 30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		Peak	1MHz	10Hz	Average Value
Limit:	Frequency		Field Strength (microvolts/meter)		Measurement Distance (meters)
	0.009-0.490		2400/F(KHz)		300
	0.490-1.705		24000/F(KHz)		30
	1.705-30		30		30
	30-88		100		3
	88-216		150		3
	216-960		200		3
	Above 960		500		3
	Frequency		Field Strength (microvolts/meter)	Measurement Distance (meters)	Detector
	Above 1GHz	500	3	Average	
	5000	3	Peak		
Test setup:	For radiated emissions below 30MHz				
					
Test setup:	30MHz to 1GHz				



Above 1GHz



Test Procedure:

- For the radiated emission test below 1GHz:
The EUT was placed on a turntable with 0.8 meter above ground. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high PASS filter are used for the test in order to get better signal level.
- For the radiated emission test above 1GHz:
Place the measurement antenna on a turntable with 1.5 meter above ground, which is away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final

	measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. 2. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level 3. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported. 4. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$; $\text{VBW} \geq \text{RBW}$; Sweep = auto; Detector function = peak; Trace = max hold; (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1 \text{ GHz}$ for peak measurement. For average measurement: VBW = 10 Hz, when duty cycle is no less than 98 percent. $\text{VBW} \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Test mode:	Refer to section 4.1 for details
Test results:	PASS

6.8.2. Test Instruments

Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Test Receiver	ROHDE&SCHW ARZ	ESVD	100008	Sep. 27, 2018
Spectrum Analyzer	ROHDE&SCHW ARZ	FSQ	200061	Sep. 27, 2018
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Sep. 27, 2018
Pre-amplifier	HP	8447D	2727A05017	Sep. 27, 2018
Loop antenna	ZHINAN	ZN30900A	12024	Sep. 27, 2018
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep. 27, 2018
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Sep. 27, 2018
Horn Antenna	Schwarzbeck	BBH 9170	582	Jun. 07, 2018
Antenna Mast	Keleto	CC-A-4M	N/A	N/A
Coax cable (9KHz-1GHz)	TCT	RE-low-01	N/A	Sep. 27, 2018
Coax cable (9KHz-40GHz)	TCT	RE-high-02	N/A	Sep. 27, 2018
Coax cable (9KHz-1GHz)	TCT	RE-low-03	N/A	Sep. 27, 2018
Coax cable (9KHz-40GHz)	TCT	RE-high-04	N/A	Sep. 27, 2018
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.8.3. Test Data

Please refer to following diagram for individual


Below 1GHz

Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
64.887	36.13	12.71	0.90	29.89	19.85	40.00	-20.15	QP
89.276	37.61	13.76	1.10	29.75	22.72	43.50	-20.78	QP
108.267	37.44	14.39	1.26	29.64	23.45	43.50	-20.05	QP
197.893	44.07	12.57	1.83	29.21	29.26	43.50	-14.24	QP
265.676	45.05	14.26	2.20	29.76	31.75	46.00	-14.25	QP
375.939	44.13	16.56	2.75	29.61	33.83	46.00	-12.17	QP

Vertical:




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
34.276	42.38	14.30	0.60	30.07	27.21	40.00	-12.79	QP
46.995	35.43	15.44	0.74	30.01	21.60	40.00	-18.40	QP
89.276	39.39	13.76	1.10	29.75	24.50	43.50	-19.00	QP
197.893	40.88	12.57	1.83	29.21	26.07	43.50	-17.43	QP
225.308	37.84	13.41	1.99	29.44	23.80	46.00	-22.20	QP
396.242	34.29	16.97	2.83	29.52	24.57	46.00	-21.43	QP

- Note:** 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported
2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Band Edge


Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test channel:	2405MHz	Antenna Polarity:	Horizontal
---------------	---------	-------------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	25.86	27.91	5.30	36.64	22.43	54.00	-31.57	Average
2310.000	39.29	27.91	5.30	36.64	35.86	74.00	-38.14	Peak
2390.000	30.43	27.59	5.38	36.71	26.69	54.00	-27.31	Average
2390.000	40.16	27.59	5.38	36.71	36.42	74.00	-37.58	Peak

Test channel:	2405MHz	Antenna Polarity:	Vertical
---------------	---------	-------------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2310.000	26.45	27.91	5.30	36.64	23.02	54.00	-30.98	Average
2310.000	38.88	27.91	5.30	36.64	35.45	74.00	-38.55	Peak
2390.000	30.08	27.59	5.38	36.71	26.34	54.00	-27.66	Average
2390.000	39.82	27.59	5.38	36.71	36.08	74.00	-37.92	Peak

Test channel:	2480MHz	Antenna Polarity:	Horizontal
---------------	---------	-------------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	56.30	27.53	5.47	36.78	52.52	54.00	-1.48	Average
2483.500	65.39	27.53	5.47	36.78	61.61	74.00	-12.39	Peak
2500.000	28.13	27.55	5.49	36.79	24.38	54.00	-29.62	Average
2500.000	37.89	27.55	5.49	36.79	34.14	74.00	-39.86	Peak

Test channel:	2480MHz	Antenna Polarity:	Vertical
---------------	---------	-------------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
2483.500	54.72	27.53	5.47	36.78	50.94	54.00	-3.06	Average
2483.500	63.74	27.53	5.47	36.78	59.96	74.00	-14.04	Peak
2500.000	28.02	27.55	5.49	36.79	24.27	54.00	-29.73	Average
2500.000	38.78	27.55	5.49	36.79	35.03	74.00	-38.97	Peak

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.


■ Above 1GHz

Test channel:	2405MHz	Antenna Polarity:	Horizontal
---------------	---------	-------------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4810.000	28.12	31.78	8.60	37.66	30.84	54.00	-23.16	Average
4810.000	36.41	31.78	8.60	37.66	39.13	74.00	-34.87	Peak
7215.000	28.41	36.15	11.66	35.69	40.53	54.00	-13.47	Average
7215.000	37.31	36.15	11.66	35.69	49.43	74.00	-24.57	Peak
9620.000	22.54	38.01	14.14	34.91	39.78	54.00	-14.22	Average
9620.000	30.31	38.01	14.14	34.91	47.55	74.00	-26.45	Peak
12025.000	22.12	39.08	15.03	36.13	40.10	54.00	-13.90	Average
12025.000	28.14	39.08	15.03	36.13	46.12	74.00	-27.88	Peak
14430.000	16.78	42.46	17.17	36.01	40.40	54.00	-13.60	Average
14430.000	27.15	42.46	17.17	36.01	50.77	74.00	-23.23	Peak
16835.000	15.55	42.13	18.82	36.08	40.42	54.00	-13.58	Average
16835.000	23.68	42.13	18.82	36.08	48.55	74.00	-25.45	Peak

Test channel:	2405MHz	Antenna Polarity:	Vertical
---------------	---------	-------------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4810.000	28.00	31.78	8.60	37.66	30.72	54.00	-23.28	Average
4810.000	35.28	31.78	8.60	37.66	38.00	74.00	-36.00	Peak
7215.000	36.14	36.15	11.66	35.69	48.26	54.00	-5.74	Average
7215.000	43.74	36.15	11.66	35.69	55.86	74.00	-18.14	Peak
9620.000	22.12	38.01	14.14	34.91	39.36	54.00	-14.64	Average
9620.000	32.88	38.01	14.14	34.91	50.12	74.00	-23.88	Peak
12025.000	21.55	39.08	15.03	36.13	39.53	54.00	-14.47	Average
12025.000	27.56	39.08	15.03	36.13	45.54	74.00	-28.46	Peak
14430.000	16.54	42.46	17.17	36.01	40.16	54.00	-13.84	Average
14430.000	26.91	42.46	17.17	36.01	50.53	74.00	-23.47	Peak
16835.000	15.90	42.13	18.82	36.08	40.77	54.00	-13.23	Average
16835.000	26.03	42.13	18.82	36.08	50.90	74.00	-23.10	Peak

Test channel:	2440MHz	Antenna Polarity:	Horizontal
---------------	---------	-------------------	------------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4880.000	27.40	31.85	8.66	37.68	30.23	54.00	-23.77	Average
4880.000	35.57	31.85	8.66	37.68	38.40	74.00	-35.60	Peak
7320.000	29.66	36.37	11.72	35.64	42.11	54.00	-11.89	Average
7320.000	38.20	36.37	11.72	35.64	50.65	74.00	-23.35	Peak
9760.000	21.51	38.35	14.25	34.98	39.13	54.00	-14.87	Average
9760.000	28.90	38.35	14.25	34.98	46.52	74.00	-27.48	Peak
12200.000	22.10	38.92	15.14	36.26	39.90	54.00	-14.10	Average
12200.000	26.31	38.92	15.14	36.26	44.11	74.00	-29.89	Peak
14640.000	17.95	42.21	17.28	35.72	41.72	54.00	-12.28	Average
14640.000	27.18	42.21	17.28	35.72	50.95	74.00	-23.05	Peak
17080.000	12.70	44.30	18.99	36.19	39.80	54.00	-14.20	Average
17080.000	26.60	44.30	18.99	36.19	53.70	74.00	-20.30	Peak

Test channel:	2440MHz	Antenna Polarity:	Vertical
---------------	---------	-------------------	----------




Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4880.000	26.58	31.85	8.66	37.68	29.41	54.00	-24.59	Average
4880.000	35.75	31.85	8.66	37.68	38.58	74.00	-35.42	Peak
7320.000	37.35	36.37	11.72	35.64	49.80	54.00	-4.20	Average
7320.000	44.75	36.37	11.72	35.64	57.20	74.00	-16.80	Peak
9760.000	21.07	38.35	14.25	34.98	38.69	54.00	-15.31	Average
9760.000	34.45	38.35	14.25	34.98	52.07	74.00	-21.93	Peak
12200.000	21.25	38.92	15.14	36.26	39.05	54.00	-14.95	Average
12200.000	26.46	38.92	15.14	36.26	44.26	74.00	-29.74	Peak
14640.000	17.42	42.21	17.28	35.72	41.19	54.00	-12.81	Average
14640.000	26.65	42.21	17.28	35.72	50.42	74.00	-23.58	Peak
17080.000	15.47	44.30	18.99	36.19	42.57	54.00	-11.43	Average
17080.000	25.38	44.30	18.99	36.19	52.48	74.00	-21.52	Peak

Test channel:	2480MHz	Antenna Polarity:	Horizontal
---------------	---------	-------------------	------------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4960.000	25.80	31.93	8.73	37.69	28.77	54.00	-25.23	Average
4960.000	31.44	31.93	8.73	37.69	34.41	74.00	-39.59	Peak
7440.000	25.13	36.59	11.79	35.58	37.93	54.00	-16.07	Average
7440.000	35.33	36.59	11.79	35.58	48.13	74.00	-25.87	Peak
9920.000	18.25	38.81	14.38	35.07	36.37	54.00	-17.63	Average
9920.000	30.04	38.81	14.38	35.07	48.16	74.00	-25.84	Peak
12400.000	18.97	38.76	15.27	36.43	36.57	54.00	-17.43	Average
12400.000	27.37	38.76	15.27	36.43	44.97	74.00	-29.03	Peak
14880.000	15.15	41.52	17.39	35.39	38.67	54.00	-15.33	Average
14880.000	23.63	41.52	17.39	35.39	47.15	74.00	-26.85	Peak
17360.000	12.48	46.19	18.98	36.16	41.49	54.00	-12.51	Average
17360.000	23.48	46.19	18.98	36.16	52.49	74.00	-21.51	Peak

Test channel:	2480MHz	Antenna Polarity:	Vertical
---------------	---------	-------------------	----------



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV	Limit level dBuV/m	Over limit dB	Remark
4960.000	26.64	31.93	8.73	37.69	29.61	54.00	-24.39	Average
4960.000	34.68	31.93	8.73	37.69	37.65	74.00	-36.35	Peak
7440.000	25.87	36.59	11.79	35.58	38.67	54.00	-15.33	Average
7440.000	40.07	36.59	11.79	35.58	52.87	74.00	-21.13	Peak
9920.000	18.26	38.81	14.38	35.07	36.38	54.00	-17.62	Average
9920.000	35.05	38.81	14.38	35.07	53.17	74.00	-20.83	Peak
12400.000	21.41	38.76	15.27	36.43	39.01	54.00	-14.99	Average
12400.000	26.81	38.76	15.27	36.43	44.41	74.00	-29.59	Peak
14880.000	17.66	41.52	17.39	35.39	41.18	54.00	-12.82	Average
14880.000	27.15	41.52	17.39	35.39	50.67	74.00	-23.33	Peak
17360.000	11.32	46.19	18.98	36.16	40.33	54.00	-13.67	Average
17360.000	22.31	46.19	18.98	36.16	51.32	74.00	-22.68	Peak

Remark: 1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor

Note:

- Emission Level = Peak Reading + Correction Factor; Correction Factor = Antenna Factor + Cable loss – Pre-amplifier
- Margin (dB) = Emission Level (dBμV/m) - limit (dBμV/m) For above 18GHz , no emission found

Appendix A: Photographs of Test Setup

Refer to test report TCT171017E040

Appendix B: Photographs of EUT

Refer to test report TCT171017E040

*******END OF REPORT*******