



RF EXPOSURE REPORT



Report No.: 16071296-FCC-H2

Supersede Report No.: N/A

Applicant	Posh Mobile Limited	
Product Name	Revel Max LTE	
Model No.	L551	
Serial No.	L551A,L551B,L551C	
Test Standard	FCC 2.1093:2015	
Test Date	November 18 to December 04, 2016	
Issue Date	December 05, 2016	
Test Result	☒ Pass ☐ Fail	
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		
		
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	16071296-FCC-H2
Page	3 of 11

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.	9
5.1 RF EXPOSURE.....	9
5.2 TEST RESULT	10

1. Report Revision History

Report No.	Report Version	Description	Issue Date
16071296-FCC-H2	NONE	Original	December 05, 2016

2. Customer information

Applicant Name	Posh Mobile Limited
Applicant Add	1011A, 10/F., Harbour Centre Tower 1, No.1 Hok Cheung Street, Hung Hom, Kowloon, Hong Kong
Manufacturer	Shenzhen Posh Mobile Limited
Manufacturer Add	Room 6H, Block C, NEO Building, Chegongmiao, Futian District, Shenzhen, P.R. China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao' an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Revel Max LTE
Main Model:	L551
Serial Model:	L551A,L551B,L551C
Date EUT received:	November 17, 2016
Test Date(s):	November 18 to December 04, 2016
Antenna Gain:	GSM850: -1.27dBi PCS1900: 0.84dBi UMTS-FDD Band V: -1.27dBi UMTS-FDD Band IV: 0.84dBi UMTS-FDD Band II: 0.84dBi LTE Band II: 0.54dBi LTE Band IV: 0.84dBi LTE Band VII: 0.9dBi LTE Band XII: -2.02dBi LTE Band XVII: -2.06dBi WIFI: 0.87dBi Bluetooth/BLE: 0.87dBi GPS: 0.89dBi
Antenna Type:	PIFA antenna
Type of Modulation:	GSM / GPRS: GMSK EGPRS: GMSK,8PSK UMTS-FDD: QPSK LTE Band: QPSK, 16QAM 802.11b/g/n: DSSS, OFDM Bluetooth: GFSK, π /4DQPSK, 8DPSK BLE: GFSK GPS: BPSK

	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz UMTS-FDD Band IV TX:1712.4 ~ 1752.6 MHz; RX : 2112.4 ~ 2152.6 MHz UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz; RX: 1932.4 ~ 1987.6 MHz
RF Operating Frequency (ies):	LTE Band II TX: 1850.7 ~ 1909.3MHz; RX : 1930.7 ~ 1989.3 MHz LTE Band IV TX: 1710.7 ~ 1754.3 MHz; RX : 2110.7~ 2154.3 MHz LTE Band VII TX: 2502.5 ~ 2567.5 MHz; RX : 2622.5 ~ 2687.5 MHz LTE Band XII TX:699.7 ~ 715.3 MHz; RX : 729.7~ 745.3MHz LTE Band XVII TX: 706.5 ~ 713.5 MHz; RX : 736.5 ~ 743.5 MHz WIFI: 802.11b/g/n(20M): 2412-2462 MHz WIFI: 802.11n(40M): 2422-2452 MHz Bluetooth& BLE: 2402-2480 MHz GPS: 1575.42 MHz
Number of Channels:	GSM 850: 124CH PCS1900: 299CH UMTS-FDD Band V: 102CH UMTS-FDD Band IV: 202CH UMTS-FDD Band II: 277CH WIFI :802.11b/g/n(20M): 11CH WIFI :802.11n(40M): 7CH Bluetooth: 79CH BLE: 40CH GPS:1CH
Port:	USB Port, Earphone Port
Input Power:	Adapter: Model: A88-501500 Input: AC100-240V~50/60Hz,0.35A Output: DC 5.0V,1.5A Battery: Spec: 3.85V,2820mAh
Trade Name :	Posh

Test Report	16071296-FCC-H2
Page	8 of 11

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2AG8KL551

5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

5.1 RF Exposure

Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

5.2 Test Result

Bluetooth Mode:

Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	4.568	4.5±1	5.5	3.548	1.10	3
	Mid	2441	5.108	4.5±1	5.5	3.548	1.11	3
	High	2480	2.779	3±1	4	2.512	0.79	3
π /4 DQPSK	Low	2402	3.784	4±1	5	3.162	0.98	3
	Mid	2441	4.292	4±1	5	3.162	0.99	3
	High	2480	1.924	2±1	3	1.995	0.63	3
8-DPSK	Low	2402	3.965	4±1	5	3.162	0.98	3
	Mid	2441	4.392	4±1	5	3.162	0.99	3
	High	2480	2.073	2±1	3	1.995	0.63	3

WIFI Mode:

Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
802.11b	Low	2412	8.35	8.5±1	9.5	8.913	2.77	3
	Mid	2437	8.45	8.5±1	9.5	8.913	2.78	3
	High	2462	8.88	8.5±1	9.5	8.913	2.80	3
802.11g	Low	2412	8.94	8.5±1	9.5	8.913	2.77	3
	Mid	2437	8.05	8.5±1	9.5	8.913	2.78	3
	High	2462	8.37	8.5±1	9.5	8.913	2.80	3
802.11n (20M)	Low	2412	8.50	8.5±1	9.5	8.913	2.77	3
	Mid	2437	8.60	8.5±1	9.5	8.913	2.78	3
	High	2462	8.16	8.5±1	9.5	8.913	2.80	3
802.11n (40M)	Low	2422	8.86	8.5±1	9.5	8.913	2.77	3
	Mid	2437	8.41	8.5±1	9.5	8.913	2.78	3
	High	2452	8.37	8.5±1	9.5	8.913	2.79	3

BLE Mode:

Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-2.303	-2±1	-1	0.794	0.25	3
	Mid	2440	-2.276	-2±1	-1	0.794	0.25	3
	High	2480	-4.544	-4.5±1	-3.5	0.447	0.14	3

Result: Compliance

No SAR measurement is required.