



TS2501 Wi-Fi Smart Thermostat

Installation Guide





Table of Contents

1 Preparation

- What is in the box?	5
- Tools needed for installation	6
- Accessories (Sold separately)	6
- Quick Start Guide for Homeowner Installation	7
- Quick Start Guide for Contractor Installation	8
- Precautionary measures	9
- Let's get started!	11
- With or without C-Wire?	12

2 Installation With a C-Wire

- Step 1: Disconnect and label old thermostat wires	13
- Step 2: Remove old jumper wire	14
- Step 3: Unscrew old Mounting Plate	15
- Step 4: Replace with new Thermostat Mounting Plate	16
- Step 5: If the Trim Plate is used (Optional)	17
- Step 6: Pull the labeled wires through the hole of the Mounting Plate	18
- Step 7: Attach the Mounting Plate on the wall	19
- Step 8: Connect the wires	20
- Step 9: Set the jumpers on the back of your Thermostat	22
- Step 10: Attach the Thermostat onto its Mounting Plate until it clicks	23
- Step 11: Turn on the power	24
- Installation done!	25

3 Installation Without a C-Wire

- Step 1: Check if there are 3 or 4 wires	27
- Step 2: Prepare the necessary tools	29
- Step 3: Open your HVAC system's cover	30
- Step 4: Label the wires	31
- Step 5: Disconnect the wires from the HVAC control board	32
- Step 6: Connect the wires from the C-Wire Kit to the HVAC control board	33
- Step 7: Connect the disconnected wires from the HVAC control board to the C-Wire Kit	34
- Step 8: Mount the C-Wire Kit inside your HVAC system	35



- Step 9: Disconnect and label old thermostat wires	36
- Step 10: Unscrew old Mounting Plate	37
- Step 11: Replace with new Thermostat Mounting Plate	38
- Step 12: If the Trim Plate is used (Optional)	39
- Step 13: Pull the labeled wires through the hole of the Mounting Plate	40
- Step 14: Attach the Mounting Plate on the wall	41
- Step 15: Connect the wires	42
- Step 16: Set the jumpers on the back of your Thermostat	43
- Step 17: Attach the Thermostat onto its Mounting Plate until it clicks	44
- Step 18: Turn on the power	45
- Installation done!	46
4 Start-Up Configuration	
- Option 1: Configuration using the TrickleStar Portal	48
- Option 2: Configuration without using the TrickleStar Portal	49
5 Thermostat Features	54
6 Thermostat LCD Display	55
7 Wiring Diagrams	
- Conventional heating and cooling systems	56
- Heat pump with auxiliary heat	57
- Boiler and radiant system	58
- C-Wire Kit wiring	59
- With one accessory wire (humidifier/dehumidifier/ventilator)	60
- With two accessory wire (humidifier/dehumidifier/ventilator)	61
8 Troubleshooting	62
9 Legal	63
10 Warranty	65



Welcome!

Thank you for choosing the TrickleStar TS2501 Wi-Fi Smart Thermostat.

We are your smart partner in optimizing comfort and maximizing savings for your Heating, Ventilation, and Air Conditioning (HVAC) systems. You can now remotely control and monitor the heating and cooling systems in your home and business from anywhere.

If you have any inquiries about TrickleStar products or need technical support, visit our website for tutorials, videos and Frequently Asked Questions (FAQ). You can also contact us by email or phone.

Website: www.tricklestar.com

Email: customer.service@tricklestar.com

Toll Free: 1-888-700-1098

Instruction Videos


If you want to see the Installation Instructions as videos, visit our YouTube channel:

<https://www.youtube.com/user/TrickleStarUS/>




Preparation

What is in the box?




Thermostat with
Mounting Plate




Trim Plate




Extra jumpers




Screws (4 pcs)



Drywall plugs (4 pcs)



Wire labels




Quick Start Guide


Tools needed for installation



Phillips screwdriver



Drill with 3/16 in. (3.3 mm) drill bit



Pencil

Mobile devices with Wi-Fi connection (to access to TrickleStar Portal):



Laptop

or



Tablet

or




Smartphone

Accessories (Sold separately)

For more information on these accessories, scan the QR code or visit our website at: www.tricklestar.com



TS1921 Occupancy Sensor



TS2104 C-Wire Kit





Quick Start Guide for Homeowner Installation

Before you start the installation, be sure to check the Thermostat compatibility and create a Portal account.



A. Check compatibility

- Is the TrickleStar Thermostat compatible with your HVAC system?
- Is the C-Wire Kit needed?

<https://portal.tricklestar.com/tstat/compatibility>

B. Create and log in to Portal

Create a Portal account using the QR code or through the website: portal.tricklestar.com

Then, log in to the Portal.



C. Add your device and start the Thermostat Setup Wizard

Installation Workflow



Step 1

Install the TrickleStar Thermostat.



Step 2

Connect the TrickleStar Thermostat to Wi-Fi via the Portal and complete the Start-Up Configuration.



Step 3

Select the settings for the TrickleStar Thermostat. (Optional)



Step 4

Add the TrickleStar App. (Optional)



Quick Start Guide for Contractor Installation

Before you start the installation, be sure to check the Thermostat compatibility and create a Portal account.



A. Check compatibility

- Is the TrickleStar Thermostat compatible with your HVAC system?
- Is the C-Wire Kit needed?

<https://portal.tricklestar.com/tstat/compatibility>



B. Create and log in to Portal

Create a Portal account using the QR code or through the website: portal.tricklestar.com

Then, log in to the Portal.



D. At Thermostat Setup Wizard, create a new site for homeowner



C. Add your device and start the Thermostat Setup Wizard

Installation Workflow



Step 1

Install the TrickleStar Thermostat.




Step 2

Connect the TrickleStar Thermostat to Wi-Fi via the Portal and complete the Start-Up Configuration.



Step 3

Select the settings for the TrickleStar Thermostat. (Optional)



Step 4

Transfer ownership to homeowner.





Step 5

Add the TrickleStar App on homeowner's smartphone. (Optional)




Precautionary measures

- Read all instructions carefully before starting the installation.
- Before installing the Thermostat, be sure to turn off the power for your HVAC system either at the Circuit Breaker Box or at the Main Switch.
- Leave the power OFF until you have finished the installation.




Hint: Your system should not make any noise and you should not feel any air exiting your vents when the power is OFF.

- Remove the front cover of your old thermostat from its base.
- Your system is not compatible with the TrickleStar Thermostat if you see:
 - thick black wires with wire nuts.
 - the base on the old thermostat has “L1” and “L2” on the terminal blocks.
 - “120 - 240 V AC” or “High Voltage” labels.
- The TrickleStar Thermostat is **ONLY** designed for 24 V AC with a total switching current of 3 A maximum.



120-240 V AC/
High voltage




Alert: If you have any doubts about installing the Thermostat, contact a professional contractor.




Let's get started!

Before you start the installation, we recommend that you take a photo of the label attached at the bottom of your Thermostat. You may need to refer to the information when you connect your Thermostat to Wi-Fi via the TrickleStar Portal.



After removing the front cover of your old thermostat from its base, we recommend that you take a photo of the wires connected to the terminals at the base. You may need to refer to the photo at a later stage.






With or without C-Wire?


The TrickleStar Thermostat supports installation for both with and without C-Wire, but the installation is a little different.

Do you have a C-Wire connected to your old thermostat? Check the wires connected to the terminals on the base of your old thermostat.

- If a wire is connected to the “C” terminal, then your system has a C-Wire to power your new TrickleStar Thermostat.
- If there is no wire connected to the “C” terminal, then you need to install a C-Wire Kit to power your new TrickleStar Thermostat.



Yes, with C-Wire.
Continue to page 13.



No, without C-Wire.
Continue to page 26.




Note: Make sure that the C-Wire at your old thermostat is directly connected to the HVAC Control Board.



Installation With a C-Wire


If your system has a C-Wire, it will power your new TrickleStar Thermostat. You do not need a C-Wire Kit (sold separately as an accessory).



Step 1: Disconnect and label old thermostat wires

Disconnect and label the wire from your old thermostat carefully, one wire at a time, using the wire labels provided.

Make sure the wires do not fall back into the wall when released from the terminals and that the labels are fastened to the wires securely.




Note: Make sure that the C-Wire at your old thermostat is directly connected to the HVAC Control Board.



Step 2: Remove old jumper wire


If the terminals on your old thermostat has a jumper wire between R_H, R_C or R, remove the jumper wire. Your new TrickleStar Thermostat does not need this jumper wire.





Step 3: Unscrew old Mounting Plate


Unscrew the Mounting Plate of your old thermostat to remove it from the wall. When you remove the Mounting Plate, be sure not to tear off the labels on the wires.






Step 4: Replace with new Thermostat Mounting Plate

Decide if you want to mount the TrickleStar Thermostat directly to the wall or you want to use the Trim Plate. The Trim Plate helps you to hide marks or holes left on the wall by your old thermostat.



Mounting Plate


OR



Trim Plate


Step 5: If the Trim Plate is used (Optional)

If you use the Trim Plate, align the mounting holes on the Trim Plate and Mounting Plate, then press them together into place.




Step 6: Pull the labeled wires through the hole of the Mounting Plate

Pull the labeled wires carefully through the hole of the Mounting Plate.



Step 7: Attach the Mounting Plate on the wall


Attach the Mounting Plate on the wall using the drywall plugs and screws provided. Use the built-in bubble level to make sure the base is level.



Use a drill with 3/16 in. (3.3 mm) drill bit to drill a hole for the drywall plugs.


Step 8: Connect the wires

Connect the labeled wires to their corresponding terminals on the Thermostat Mounting Plate.




Connect the R or RC wire to the RC terminal.

Do you have more than one R wire? (That includes R, Rc, and RH)



Connect the R or Rc wire to the Rc terminal and the RH wire to the RH terminal.



Do not connect the R or Rc wire to the RH terminal
or the RH wire to the Rc terminal.




Note:

- You can refer to “Wiring Diagrams” from pages 58 to 63 for some common HVAC equipments.
- Connect the remaining wires to their corresponding terminals. Pull the wires gently to ensure that they are connected securely.
- Tape the ends of any excess wires and push the wires back into the wall carefully.
- Make sure there is no draft coming from the hole in the wall as it may affect the temperature readings.

Step 9: Set the jumpers on the back of your Thermostat

The Accessory (ACC) wires are used to power devices such as humidifier or dehumidifier. If your system does not have any ACC wires, you can leave the black jumper in either position.



⚠ Jumper Position for Accessory & RH Wire

2 ACC wires with RH Wire (Default position)	2 ACC wires without RH wire	1 ACC wire with RH wire	1 ACC wire without RH wire

ACC wire

RH wire

Note : If there is no ACC wire, the black jumper can be in either position.


If your system has two ACC wires with an RH wire, set the jumpers as illustrated. This is the default position.

If your system has two ACC wires without an RH wire, set the jumpers as illustrated.

If your system has one ACC wire with an RH wire, set the jumpers as illustrated.

If your system has one ACC wire without an RH wire, set the jumpers as illustrated.



Step 10: Attach the Thermostat onto its Mounting Plate until it clicks





Step 11: Turn on the power


Turn the power back to ON for your HVAC system either at the Circuit Breaker Box or at the Main Switch.





Installation done!


Congratulations! You have completed your installation. Proceed to page 47 for details on how to configure and set up your Thermostat.





Installation Without a C-Wire

If your system does not have a C-Wire, it will not power your new TrickleStar Thermostat. You need the TrickleStar C-Wire Kit (sold separately as an accessory). For more information on the TS2104 C-Wire Kit, visit our website at: www.tricklestar.com







Step 1: Check if there are 3 or 4 wires

The TrickleStar C-Wire Kit requires your system to have either three or four wires:


3 wires
Y/Y1, G, and R (or Rc or RH)



3 wires
W/W1/E, G, and R (or Rc or RH)



4 wires
W/W1/E, Y/Y1, G, and R (or Rc or RH)



Yes

Continue to the next page

No

Email or call our technical support:


Email: customer.service@tricklestar.com

Toll Free: 1-888-700-1098



Step 2: Prepare the necessary tools

Bring along your TrickleStar C-Wire Kit, wire labels, Phillips screwdriver and your mobile devices with Wi-Fi connection to your HVAC system.




TrickleStar C-Wire Kit

Label the wires at your control board.					
R	R	G	G		
Rc	Rc	W	W		
		Y1	Y1		
RH	RH	W	W		
		W1	W1		

Wire Labels



Phillips screwdriver



HVAC System



Laptop

or



Tablet

or



Smartphone




Note:

The HVAC system is usually located at the basement or the attic.

Step 3: Open your HVAC system's cover

Open your HVAC system's cover to reveal the control board.

We recommend that you take a photo of the wires connected to the HVAC control board. You may need to refer to the photo at a later stage.




Note:

The HVAC system contains high voltage circuitry and wires. Before you open your HVAC system's cover, be sure to check that you have turned off the power for your HVAC system.

Step 4: Label the wires

- Label only the R, Y/Y1, G, and W/W1 wires with the matching wire labels provided.
- If you have more than one wire going into these terminals, label only those wires going to your thermostat.



Note:

If you have wires connected to both R_c and R_H terminals at the HVAC control board, you may have a two-transformer system. Contact our technical support to help you with the installation:


Email: customer.service@tricklestar.com

Toll Free: 1-888-700-1098



Step 5: Disconnect the wires from the HVAC control board


Disconnect the wires labeled R, Y/Y1, G, and W/W1 from the HVAC control board.





Step 6: Connect the wires from the C-Wire Kit to the HVAC control board

Connect the five white wires from your TrickleStar C-Wire Kit to their corresponding terminals on the HVAC control board.




Note:

Pull the wires gently to ensure that they are connected securely.



Step 7: Connect the disconnected wires from the HVAC control board to the C-Wire Kit


Connect the wires you disconnected from the HVAC control board in Step 5 to their corresponding terminals on the TrickleStar C-Wire Kit.





Step 8: Mount the C-Wire Kit inside your HVAC system

- Mount the TrickleStar C-Wire Kit inside your HVAC system. Be sure not to strain the wires.
- Close your HVAC system's cover securely.
- You can now return to your thermostat.




Note: Make sure your HVAC system's cover is fully closed. Some HVAC systems will not turn on if the cover has not been closed properly.



Step 9: Disconnect and label old thermostat wires

Disconnect and label the wire from your old thermostat carefully, one wire at a time, using the wire labels provided. If you have connected the C-Wire Kit, label the wire connected to the G terminal with the GK wire label and label the wire connected to the Y/Y1 terminal with the YK wire label.

Make sure the wires do not fall back into the wall when released from the terminals and that the labels are fastened to the wires securely.



Jumper wire




Note: If the terminals on your old thermostat has a jumper wire between RH, Rc or R, remove the jumper wire. Your new TrickleStar Thermostat does not need this jumper wire.




Step 10: Unscrew old Mounting Plate

Unscrew the Mounting Plate of your old thermostat to remove it from the wall. When you remove the Mounting Plate, be sure not to tear off the labels on the wires.




Step 11: Replace with new Thermostat Mounting Plate

Decide if you want to mount the TrickleStar Thermostat directly to the wall or you want to use the Trim Plate. The Trim Plate helps you to hide marks or holes left on the wall by your old thermostat.



Mounting Plate


OR



Trim Plate


Step 12: If the Trim Plate is used (Optional)

If you use the Trim Plate, align the mounting holes on the Trim Plate and Mounting Plate, then press them together into place.




Step 13: Pull the labeled wires through the hole of the Mounting Plate

Pull the labeled wires carefully through the hole of the Mounting Plate.



Step 14: Attach the Mounting Plate on the wall


Attach the Mounting Plate on the wall using the drywall plugs and screws provided. Use the built-in bubble level to make sure the base is level.



Use a drill with 3/16 in. (3.3 mm) drill bit to drill a hole for the drywall plugs.

Step 15: Connect the wires

- Connect the Rc, GK, YK and W/W1/E wires to their corresponding terminals on the Thermostat Mounting Plate as shown below.
- Connect the remaining wires to their corresponding terminals on the Thermostat Mounting Plate.




Note:

- You can refer to "Wiring Diagrams" from pages 58 to 63 for some common HVAC equipments.
- Connect the remaining wires to their corresponding terminals. Pull the wires gently to ensure that they are connected securely.
- Tape the ends of any excess wires and push the wires back into the wall carefully.
- Make sure there is no draft coming from the hole in the wall as it may affect the temperature readings.

Step 16: Set the jumpers on the back of your Thermostat

The Accessory (ACC) wires are used to power devices such as humidifier or dehumidifier. If your system does not have any ACC wires, you can leave the black jumper in either position.



Jumper Position for Accessory & RH Wire



2 ACC wires
with RH Wire
(Default position)



2 ACC wires
without RH wire



1 ACC wire
with RH wire



1 ACC wire
without
RH wire

■ ACC wire
■ RH wire

Note : If there is no ACC wire, the black jumper can be in either position.


If your system has two ACC wires with an RH wire, set the jumpers as illustrated. This is the default position.

If your system has two ACC wires without an RH wire, set the jumpers as illustrated.

If your system has one ACC wire with an RH wire, set the jumpers as illustrated.

If your system has one ACC wire without an RH wire, set the jumpers as illustrated.



Step 17: Attach the Thermostat onto its Mounting Plate until it clicks





Step 18: Turn on the power


Turn the power back to ON for your HVAC system either at the Circuit Breaker Box or at the Main Switch.





Installation done!

Congratulations! You have completed your installation. Proceed to page 47 for details on how to configure and set up your Thermostat.





Start-Up Configuration

If you have Wi-Fi connection, we recommend that you connect your TrickleStar Thermostat to Wi-Fi via the TrickleStar Portal. Your TrickleStar Thermostat will support a wide range of features and you can monitor and control your HVAC system from anywhere. Proceed to “Option 1: Configuration using the TrickleStar Portal” on page 48.

If you do not have Wi-Fi connection, your TrickleStar Thermostat can only support a limited range of features and will work as a simple non-programmable Thermostat. Proceed to “Option 2: Configuration without using the TrickleStar Portal” on page 51.



Option 1: Configuration using the TrickleStar Portal

If you have not created a portal account via the TrickleStar Portal, refer to the supplied Quick Start Guide. You can also access the Portal at: portal.tricklestar.com. Then, refer to the guided instructions to complete the Start-Up Configuration.

Start-Up Configuration Mode

When you begin the Start-Up Configuration via the TrickleStar Portal, you will see this display on the Thermostat.



Ready to use

When you have completed the Start-Up Configuration via the TrickleStar Portal, the Thermostat will enter Normal Operation and you will see this display on the Thermostat. Your Thermostat is now ready to use.





Option 2: Configuration without using the TrickleStar Portal

Start-Up Configuration on the Thermostat

When you turn on the power for your TrickleStar Thermostat for the first time, the steps on the LCD display will guide you through the basic Start-Up Configuration.

Step 01 - Wi-Fi provisioning

Press the jog dial to skip this step.






Step 02 - Select your HVAC system

1. Rotate the jog dial to select:
 - “HC” for conventional system.
 - “HP” for heat pump system.
2. Press the jog dial to confirm your selection.



Step 03 – Select fan control option

1. Rotate the jog dial to select:
 - “HG” for gas heating.
 - “HE” for electric heating.
2. Press the jog dial to confirm your selection.



Step 04 – Select heat pump reversing valve option

If you have selected “HP” for heat pump system in Step 02, this option will be displayed.

1. Rotate the jog dial to select:
 - “o” for a system in which the reversing valve is energized in cooling.
 - “b” for a system in which the reversing valve is energized in heating.
2. Press the jog dial to confirm your selection.



Step 05 – Test the connection of each output

This step helps you to check if the output terminals were connected correctly and securely. During the connection test, check if your HVAC equipment connected to the respective output terminal is turned on.

1. Rotate the jog dial clockwise to turn on the output as follows:

- -- : All outputs off
- 11 : Only Y1 is on, all others off
- 12 : Only Y2 is on, all others off
- 11 : Only W1 is on, all others off
- 12 : Only W2 is on, all others off
- 1 : Only G is on, all others off
- ob : Only O/B is on, all others off
- AC : Only ACC is on, all others off

After you rotate the jog dial, there may be a few seconds delay before the HVAC equipment turns on. This is not a malfunction.

2. Press the jog dial to end the connection test.
All the outputs will be turned off.





Note:

- To stop and exit the Start-Up Configuration, press and hold the Side button for approximately 5 seconds. The Thermostat will apply default settings as follows:
 - HVAC type: HC (conventional system)
 - Fan control option: HG (gas heating)
 - Output test
- The output terminals are tested in a predefined sequence to ensure the safety of your HVAC equipment. As such, after you have tested a specific output and proceeded to the next, you are not allowed to test the previous output again. If you need to retest the previous output, reenter the Start-Up Configuration as follows: Press and hold the Side button for approximately 10 seconds. It will restart from Step 01.





Ready to use

When you have completed the Start-Up Configuration on the Thermostat, the Thermostat will enter Normal Operation and you will see this display on the Thermostat. Your Thermostat is now ready to use.



Note: If there is no input for more than one minute in Step 02 to Step 05, the Thermostat will exit the Start-Up Configuration and return to Normal Operation.

Thermostat Features



Thermostat LCD Display



Set Temperature Speedometer



Home Indicator
Occupancy type: Home



Away Indicator
Occupancy type: Away



Sleep Indicator
Occupancy type: Sleep



Off Indicator
System mode: Off



Heat Indicator
System mode: Heat



Cool Indicator
System mode: Cool



Auto Indicator
System mode: Auto



E.Heat Indicator
System mode: Emergency Heating



Fan On Indicator
Fan mode: On



Fan Auto Indicator
Fan mode: Auto



Wi-Fi Indicator
Indicates Wi-Fi connection and its signal strength



Bluetooth Indicator
When connected to one or more occupancy sensors.
Flashes: Thermostat is scanning for occupancy sensor



Key-Lock Indicator
Indicates the input is locked



Hold Indicator
Indicates Permanent Hold / Vacation Hold.
Flashes: Temporary Hold



Schedule Indicator
Indicates a schedule is in progress

58%

Humidity Indicator
Display the room humidity in percentage

79

Room Temperature Indicator
Display the room temperature

74

Set Temperature Indicator
Display the set temperature


TrickleStar

TrickleStar Logo
Brand (Always on)

Wiring Diagrams

Conventional heating and cooling systems

Wire the conventional heating and cooling systems up to 2 stages each as shown below.




Note:

- Connect the R wire to the Rc terminal on your TrickleStar Thermostat.
- Do not connect any jumper wire between Rc and RH terminals.
- Refer pages 22 or 43 for details on setting the jumpers on the Thermostat.

Heat pump with auxiliary heat

Wire the heat pump (air or geothermal) with auxiliary heat as shown below.




Note:

- Connect the R wire to the Rc terminal on your TrickleStar Thermostat.
- Do not connect any jumper wire between Rc and RH terminals.
- Refer pages 22 or 43 for details on setting the jumpers on the Thermostat.

Boiler and radiant system

Wire the boiler or radiant system with air handler and conventional cooling and heating system as shown below.




Note:


- Connect the R wire to the RC terminal and the other R wire from your boiler to the RH terminal on your TrickleStar Thermostat.
- Do not connect any jumper wire between RC and RH terminals.
- Refer pages 22 or 43 for details on setting the jumpers on the Thermostat.

C-Wire Kit wiring

Wire the TrickleStar C-Wire Kit as shown below.



With one accessory wire (humidifier/dehumidifier/ventilator)



Black jumper

Place the black jumper at the back of your Thermostat as illustrated.




Note:

- If there is only one accessory wire, connect it to the ACC+ terminal on the Thermostat to control the accessory.
- Do not connect any jumper wire between Rc and RH terminals.
- Refer pages 22 or 43 for details on setting the jumpers on the Thermostat.



Warning! If you connect the accessory wire to the ACC- terminal, it may damage your Thermostat or HVAC system.

With two accessory wire (humidifier/dehumidifier/ventilator)



Black jumper



Place the black jumper at the back of your Thermostat as illustrated.



Note:

- If there are two accessory wires, connect it to the ACC+ and ACC- terminal on the Thermostat to control the accessory.
- Do not connect any jumper wire between Rc and RH terminals.
- Refer pages 22 or 43 for details on setting the jumpers on the Thermostat.

Troubleshooting

Symptom	Solution
Your Thermostat does not turn on after installation.	• Check that all wires are connected correctly to the terminals on the Thermostat. Pull the wires gently to ensure that they are connected securely. • Make sure your HVAC system's cover is fully closed. Some HVAC systems will not turn on if the cover has not been closed properly. • If you installed a C-Wire Kit, make sure that all the wires are connected correctly. Pull the wires gently to ensure that they are connected securely. • If there is only one R wire (R, Rc, or Rh), make sure that it is connected to the Rc terminal on the Thermostat.
Your Thermostat cannot be registered via the TrickleStar Portal.	If the TrickleStar Portal request for the DSN number, refer to your photo of the label at the bottom of the Thermostat (page 11). You will find the DSN number at the label.

If the problem persists, you can refer to the Frequently Asked Questions (FAQ) section on our website, or email or call our technical support:

Website: www.tricklestar.com
 Email: customer.service@tricklestar.com
 Toll Free: 1-888-700-1098



Legal

FCC STATEMENT

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.



IC STATEMENT

This device complies with Industry Canada's licence-exempt RSSs.

Operation is subject to the following two conditions:

- (1) This device may not cause interference; and
- (2) This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

RF EXPOSURE INFORMATION

The distance between user and device should be no less than 8 inches.

la distance entre l'utilisation et l'appareil ne doit pas être inférieure à 8 pouces.



Warranty

THREE-YEAR LIMITED PRODUCT WARRANTY

TrickleStar Inc. ("TrickleStar"), of 251 Little Falls Drive, Wilmington, DE 19808 warrants to the purchaser this TrickleStar TS2501 Wi-Fi Smart Thermostat ("Product") will be free from defects in materials and workmanship for a period of three (3) years ("Warranty Period") from the date of purchase, under normal use and service, and provided the Product is installed and used according to manufacturer's instructions.

If the Product fails to conform to this Limited Warranty during the Warranty Period, TrickleStar at its sole discretion, will either:

- (a) repair or replace any defective Product or component. The repair or replacement may be made with a new or refurbished Product or components; or
- (b) accept the return of the Product and refund the money paid by the original purchaser for the Product.

If the Product or a component incorporated within is no longer available, TrickleStar at its sole discretion, may replace the Product with a similar product of similar function. This is your sole and exclusive remedy for breach of this Limited Warranty.

Any Product that has either been repaired or replaced under this Limited Warranty will be covered by the terms of this Limited Warranty for the longer of: (a) ninety (90) days from the date of delivery of the repaired Product or replacement Product; or (b) the remaining Warranty Period.

This Limited Warranty is transferable from the original purchaser to subsequent owners, but the Warranty Period will not be extended in duration or expanded in coverage for any such transfer. A proof-of-purchase is



required from the owner for TrickleStar to provide a replacement and/or repaired Product.

HOW TO CLAIM UNDER THIS LIMITED WARRANTY

Before making a claim under this Limited Warranty, the owner of the Product must

- (a) notify TrickleStar of the intention to claim by visiting TrickleStar.com/support during the Warranty Period and providing a description of the alleged failure; and
- (b) comply with TrickleStar's return shipping instructions.

TrickleStar will have no warranty obligations to a returned Product if it determines, in its reasonable discretion after examining of the returned Product, that the Product is an Ineligible Product (defined below). TrickleStar will bear all costs of return shipping to owner and will reimburse any shipping costs incurred by the owner, except to any Ineligible Product, for which the owner will bear all shipping costs.

WHAT THIS LIMITED WARRANTY DOES NOT COVER

This Limited Warranty does not cover the following (collectively "Ineligible Products"):

- (i) Products that have been subject to: (a) modifications, alterations, tampering, or improper maintenance or repairs; (b) handling, storage, installation, testing, or use, not in accordance with the Installation Manual or other instructions provided by TrickleStar; (c) abuse or misuse of the Product; (d) breakdowns, fluctuations, or interruptions in electric power or telecommunications network; or (e) Acts of God, including but not limited to lightning, flood, tornado, earthquake, or hurricane;



- (ii) Any non-TrickleStar branded products, even if packaged or sold with TrickleStar Product.
- (iii) This Limited Warranty does not cover consumable parts, including batteries, unless damage is due to defects in materials or workmanship of the Product, or software (even if packaged or sold with the Product).
- (iv) Installation or dismantling costs.

DISCLAIMER OF WARRANTIES

EXCEPT AS STATED ABOVE IN THIS LIMITED WARRANTY, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, TRICKLESTAR DISCLAIMS ALL EXPRESS, IMPLIED, AND STATUTORY WARRANTIES AND CONDITIONS WITH RESPECT TO THE PRODUCT, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, TRICKLESTAR ALSO LIMITS THE DURATION OF ANY APPLICABLE IMPLIED WARRANTIES OR CONDITIONS TO THE DURATION OF THIS LIMITED WARRANTY.

LIMITATION OF DAMAGES

In addition to the above warranty disclaimers, in no event will TrickleStar be liable for any consequential, incidental, exemplary, or special damages, including any damages for lost data or lost profits, arising from or relating to this limited warranty or the Product. TrickleStar's total cumulative liability arising from or related to this limited warranty or the Product will not exceed the amount paid for the Product by the original purchaser.

LIMITATION OF LIABILITY

The TrickleStar website, TrickleStar Portal, and/or TrickleStar App (iOS and Android) online services ("Services") provide information ("Product Information") on TrickleStar Products or other peripherals connected to your products ("Product Peripherals"). The type of Product Peripherals that may



be connected to your product may change from time to time. Without limiting the generality of the disclaimers above, all Product Information is provided for your convenience, “as is”, and “as available”. TrickleStar does not represent, warrant, or guarantee that Product Information will be available, accurate, or reliable; or that Product Information or use of the Services or Product will provide safety in your premises. You will use all Product Information, Services, and the Product at your own discretion and risk. You will be solely responsible for (and TrickleStar disclaims) any and all losses, liabilities, or damages, including those to your wiring, fixtures, electricity, home, office, product, product peripherals, computer, mobile device, and all other items and pets in your home, resulting from your use of TrickleStar’s Product Information, Services, or Product. Product Information provided by the Services is not intended to be a substitute for direct means of obtaining the information. For example, a notification provided through the Services is not intended to substitute the audible and visible indications in the premises and on the Product.

JURISDICTION

This Limited Warranty shall be governed by the laws of the state of Delaware.

YOUR RIGHTS AND THIS LIMITED WARRANTY

This Limited Warranty gives you specific legal rights. You may also have other legal rights that vary by state or jurisdiction. Likewise, some of the limitations in this Limited Warranty may not apply in certain states or jurisdictions. The terms of this Limited Warranty will apply to the extent permitted by applicable law.

CHANGES TO THIS POLICY

TrickleStar may revise this Policy from time to time. The latest version of the policy will govern our use of your information and will always be published on the TrickleStar website (www.tricklestar.com). By continuing to access or by using the TrickleStar website, TrickleStar Portal and/or TrickleStar App



(iOS or Android) after those changes become effective, you agree to be bound by the revised Policy.

HOW TO CONTACT US IF YOU WISH TO DISCUSS THIS POLICY

If you wish to discuss any aspect of this policy, contact us by email at: customer.service@tricklestar.com.



For technical support, go to:
Website: www.tricklestar.com
Email: customer.service@tricklestar.com
Toll Free: 1-888-700-1098

© 2021 TrickleStar Inc.

TrickleStar® is a registered trademark of TrickleStar Ltd. All other trademarks are the property of their respective owners. The information in this document is subject to change without notice. TrickleStar assumes no responsibility for any errors that may appear in this document.