



## FCC §15.247 (i), §2.1091 – RF Exposure

# FCC ID: 2AG8WSJ9000

### Applied procedures / limit

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

### Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|-------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                   | 6                                                                 |
| 3.0-30                | 1842 / f                          | 4.89 / f                          | (900 / f)*                               | 6                                                                 |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | 6                                                                 |
| 300-1500              |                                   |                                   | F/300                                    | 6                                                                 |
| 1500-100,000          |                                   |                                   | 5                                        | 6                                                                 |

Note: f is frequency in MHz

\* = Power density limit is applicable at frequencies greater than 100 MHz

### Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|-------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                   | 30                                                                |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                 | 30                                                                |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | 30                                                                |
| 300-1500              |                                   |                                   | F/1500                                   | 30                                                                |
| 1500-100,000          |                                   |                                   | 1.0                                      | 30                                                                |

Note: f = frequency in MHz

\* = Plane-wave equivalent power density



## MPE PREDICTION

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna, R=0.2m

## TEST RESULTS

|                                | Tune up<br>Produce<br>power | Maximum<br>peak<br>output<br>power<br>(dBm) | Output<br>power<br>to antenna<br>(mW) | Antenna<br>Gain<br>(numeric) | Power<br>Density (S)<br>(mW/ cm2) | Limit of Power<br>Density (S)<br>(mW/ cm2) | Result |
|--------------------------------|-----------------------------|---------------------------------------------|---------------------------------------|------------------------------|-----------------------------------|--------------------------------------------|--------|
| WIFI 2.4G<br>802.11b           | 17±1                        | 18                                          | 63.10                                 | 1.38(1.4dBi)                 | 0.01733                           | 1                                          | Pass   |
| WIFI 2.4G<br>802.11g           | 15±1                        | 16                                          | 39.81                                 | 1.38(1.4dBi)                 | 0.01093                           | 1                                          | Pass   |
| WIFI 2.4G<br>802.11n(HT<br>20) | 14±1                        | 15                                          | 31.62                                 | 1.38(1.4dBi)                 | 0.00868                           | 1                                          | Pass   |
| WIFI 2.4G<br>802.11n(HT<br>40) | 13±1                        | 14                                          | 25.12                                 | 1.38(1.4dBi)                 | 0.00690                           | 1                                          | Pass   |