



**CFR 47 FCC PART 15 SUBPART C
ISED RSS-247 ISSUE 2**

CERTIFICATION TEST REPORT

For

HUE Smart plug

MODEL: 9290022406A

FCC ID: 2AGBW9290022406AX

IC: 20812-22406AX

REPORT NUMBER: 4789870985-4

ISSUE DATE: April 8, 2021

Prepared for

**Signify (China) Investment Co., Ltd.
Building no.9, Lane 888, Tianlin Road, Minhang District Shanghai China**

Prepared by

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China**

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	04/08/2021	Initial Issue	



Summary of Test Results			
Clause	Test Items	FCC/ISED Rules	Test Results
1	6dB Bandwidth and 99% Occupied Bandwidth	FCC Part 15.247 (a) (2) RSS-247 Clause 5.2 (a) ISED RSS-Gen Clause 6.7	Pass
2	Peak Conducted Output Power	FCC Part 15.247 (b) (3) RSS-247 Clause 5.4 (d)	Pass
3	Power Spectral Density	FCC Part 15.247 (e) RSS-247 Clause 5.2 (b)	Pass
4	Conducted Bandedge and Spurious Emission	FCC Part 15.247 (d) RSS-247 Clause 5.5	Pass
5	Radiated Bandedge and Spurious Emission	FCC Part 15.247 (d) FCC Part 15.209 FCC Part 15.205 RSS-247 Clause 5.5 RSS-GEN Clause 8.9	Pass
6	Conducted Emission Test for AC Power Port	FCC Part 15.207 RSS-GEN Clause 8.8	Pass
7	Antenna Requirement	FCC Part 15.203 RSS-GEN Clause 6.8	Pass
Note: 1. This test report is only published to and used by the applicant, and it is not for evidence purpose in China. 2. The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C >< ISED RSS-247 > when <Accuracy Method> decision rule is applied.			

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS	6
2. TEST METHODOLOGY	7
3. FACILITIES AND ACCREDITATION	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. MEASURING INSTRUMENT CALIBRATION	8
4.2. MEASUREMENT UNCERTAINTY	8
5. EQUIPMENT UNDER TEST	9
5.1. DESCRIPTION OF EUT	9
5.2. CHANNEL LIST	9
5.3. MAXIMUM PEAK OUTPUT POWER	9
5.4. TEST CHANNEL CONFIGURATION	10
5.5. THE WORSE CASE POWER SETTING PARAMETER	10
5.6. DESCRIPTION OF AVAILABLE ANTENNAS	10
5.7. DESCRIPTION OF TEST SETUP	11
6. MEASURING INSTRUMENT AND SOFTWARE USED	12
7. ANTENNA PORT TEST RESULTS	14
7.1. ON TIME AND DUTY CYCLE	14
7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH	15
7.3. CONDUCTED OUTPUT POWER	17
7.4. POWER SPECTRAL DENSITY	18
7.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS	20
8. RADIATED TEST RESULTS	22
8.1. RESTRICTED BANDEDGE	28
8.1.1. LE 1M MODE	28
8.1.2. LE 2M MODE	32
8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)	36
8.2.1. LE 1M MODE	36
8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)	42
8.3.1. LE 1M MODE	42
8.3.2. LE 2M MODE	48
8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)	54
8.4.1. LE 2M MODE	54
8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)	56
8.5.1. LE 2M MODE	56



8.6.	SPURIOUS EMISSIONS BELOW 30 MHz	58
8.6.1.	LE 2M MODE.....	58
9.	AC POWER LINE CONDUCTED EMISSIONS	61
9.1.	LE 2M MODE.....	62
10.	ANTENNA REQUIREMENTS	64
10.1.	Appendix A: DTS Bandwidth	65
10.1.1.	Test Result.....	65
10.1.2.	Test Graphs	66
10.2.	Appendix B: Occupied Channel Bandwidth	70
10.2.1.	Test Result.....	70
10.2.2.	Test Graphs	71
10.3.	Appendix C: Maximum conducted output power.....	75
10.3.1.	Test Result.....	75
10.4.	Appendix D: Maximum power spectral density	76
10.4.1.	Test Result.....	76
10.4.2.	Test Graphs	77
10.5.	Appendix E: Band edge measurements	81
10.5.1.	Test Result.....	81
10.5.2.	Test Graphs	82
10.6.	Appendix F: Conducted Spurious Emission.....	85
10.6.1.	Test Result.....	85
10.6.1.	Test Graphs	86
10.7.	Appendix G: Duty Cycle	104
10.7.1.	Test Result.....	104
10.7.2.	Test Graphs	105



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Signify (China) Investment Co., Ltd.
Address: Building no.9, Lane 888, Tianlin Road, Minhang District Shanghai
China

Manufacturer Information

Company Name: Signify (China) Investment Co., Ltd.
Address: Building no.9, Lane 888, Tianlin Road, Minhang District Shanghai
China

EUT Information

EUT Name: HUE Smart plug
Model: 9290022406A
Brand: PHILIPS
Sample Received Date: March 29, 2021
Sample Status: Normal
Sample ID: 3750387
Date of Tested: March 29 ~ May 31, 2021

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART C	PASS
ISED RSS-247 Issue 2	PASS
ISED RSS-GEN Issue 5	PASS

Prepared By:

Kebo Zhang
Project Engineer

Checked By:

Shawn Wen
Laboratory Leader

Approved By:

Stephen Guo
Laboratory Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 15.247 Meas Guidance v05r02, 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011
---------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.



4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognize national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 26 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
Duty Cycle	±0.028%
DTS and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.686 dB
Maximum Power Spectral Density Level	±0.743 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	HUE Smart plug	
Model	9290022406A	
Technology	Bluetooth - Low Energy	
Transmit Frequency Range	2402 MHz ~ 2480 MHz	
Modulation	GFSK	
Data Rate	LE	125 kbps
	LE	500 kbps
	LE	1 Mbps
	LE 2M	2 Mbps
Bluetooth version	5.1LE	
Rated Input	AC120 V,60 Hz	

5.2. CHANNEL LIST

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	11	2424	22	2446	33	2468
1	2404	12	2426	23	2448	34	2470
2	2406	13	2428	24	2450	35	2472
3	2408	14	2430	25	2452	36	2474
4	2410	15	2432	26	2454	37	2476
5	2412	16	2434	27	2456	38	2478
6	2414	17	2436	28	2458	39	2480
7	2416	18	2438	29	2460	/	/
8	2418	19	2440	30	2462	/	/
9	2420	20	2442	31	2464	/	/
10	2422	21	2444	32	2468	/	/

5.3. MAXIMUM PEAK OUTPUT POWER

Test Mode	Frequency (MHz)	Channel Number	Maximum Peak Output Power (dBm)	Maximum EIRP (dBm)
LE 125k	2402 ~ 2480	0-39[40]	9.12	10.62
LE 500k	2402 ~ 2480	0-39[40]	9.12	10.62
LE 1M	2402 ~ 2480	0-39[40]	9.14	10.64
LE 2M	2402 ~ 2480	0-39[40]	9.23	10.73

5.4. TEST CHANNEL CONFIGURATION

Test Mode	Test Channel	Frequency
LE 125k	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 500k	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 1M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz
LE 2M	CH 0(Low Channel), CH 19(MID Channel), CH 39(High Channel)	2402 MHz, 2440 MHz, 2480 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band				
Test Software		UartAssist		
Modulation Type	Transmit Antenna Number	Test Channel Power Setting		
		CH 0	CH 19	CH 39
GFSK (125 kbps)	1	10	10	10
GFSK (500 kbps)	1	10	10	10
GFSK (1 Mbps)	1	10	10	10
GFSK (2 Mbps)	1	10	10	10

5.6. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna	Frequency (MHz)	Antenna Type	MAX Antenna Gain (dBi)
1	2402-2480	Built-in	1.5

Test Mode	Transmit and Receive Mode	Description
LE 125k	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
LE 500k	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
LE 1M	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.
LE 2M	☒1TX, 1RX	Antenna 1 can be used as transmitting/receiving antenna.

Note: 1. The value of the antenna gain was declared by customer.

5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	ThinkPad	X230i	/
2	USB TO UART	/	/	/
3	LED Lamp	N/A	N/A	100W

I/O CABLES

Item	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	NA	NA	1	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in an engineer mode with a software through a PC.

SETUP DIAGRAM FOR TESTS





6. MEASURING INSTRUMENT AND SOFTWARE USED

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Nov. 12, 2020	Nov. 11, 2021
Two-Line V-Network	R&S	ENV216	101983	Nov. 12, 2020	Nov. 11, 2021
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Nov. 12, 2020	Nov. 11, 2021
Software					
Description			Manufacturer	Name	Version
Test Software for Conducted Emissions			Farad	EZ-EMC	Ver. UL-3A1

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Nov. 12, 2020	Nov. 11, 2021
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130960	Aug. 11, 2018	Aug. 10, 2021
Preamplifier	HP	8447D	2944A09099	Nov. 12, 2020	Nov. 11, 2021
EMI Measurement Receiver	R&S	ESR26	101377	Nov. 12, 2020	Nov. 11, 2021
Horn Antenna	TDK	HRN-0118	130939	Sept. 17, 2018	Sept. 17, 2021
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Nov. 20, 2020	Nov. 19, 2021
Horn Antenna	Schwarzbeck	BBHA9170	#691	Aug. 11, 2018	Aug. 11, 2021
Preamplifier	TDK	PA-02-2	TRS-307-00003	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	TDK	PA-02-3	TRS-308-00002	Nov. 12, 2020	Nov. 11, 2021
Loop antenna	Schwarzbeck	1519B	00008	Jan.17, 2019	Jan.17,2022
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Nov. 12, 2020	Nov. 11, 2021
Preamplifier	Mini-Circuits	ZX60-83LN-S+	SUP01201941	Nov. 20, 2020	Nov. 19, 2021
High Pass Filter	Wi	WHKX10-2700-3000-18000-40SS	23	Nov. 12, 2020	Nov. 11, 2021
Band Reject Filter	Wainwright	WRCJV8-2350-2400-2483.5-2533.5-40SS	4	Nov. 12, 2020	Nov. 11, 2021



Software			
Description	Manufacturer	Name	Version
Test Software for Radiated Emissions	Farad	EZ-EMC	Ver. UL-3A1

Other instruments					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Spectrum Analyzer	Keysight	N9030A	MY55410512	Nov. 20, 2020	Nov. 19, 2021
Dual Channel Power Meter	Keysight	N1912A	MY55416024	Nov. 20, 2020	Nov. 19, 2021
Power Sensor	Keysight	USB Wideband Power Sensor	MY5100022	Nov. 20, 2020	Nov. 19, 2021

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE


LIMITS

None; for reporting purposes only.

PROCEDURE

Refer to ANSI C63.10-2013 clause 11.6 Zero – Span Spectrum Analyzer method.

TEST SETUP



TEST ENVIRONMENT

Temperature	26.9 °C	Relative Humidity	54.8 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix G.

7.2. 6 dB DTS BANDWIDTH AND 99 % OCCUPIED BANDWIDTH

LIMITS

CFR 47FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(a)(2) ISED RSS-247 5.2 (a)	6 dB Bandwidth	≥ 500 kHz	2400-2483.5
ISED RSS-Gen Clause 6.7	99 % Occupied Bandwidth	None; for reporting purposes only.	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.8 for DTS bandwidth and clause 6.9 for Occupied Bandwidth.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Frequency Span	For 6 dB Bandwidth: Enough to capture all products of the modulation carrier emission For 99 % Occupied Bandwidth: Between 1.5 times and 5.0 times the OBW
Detector	Peak
RBW	For 6 dB Bandwidth: 100 kHz For 99 % Occupied Bandwidth: 1 % to 5 % of the occupied bandwidth
VBW	For 6 dB Bandwidth: $\geq 3 \times$ RBW For 99 % Occupied Bandwidth: $\geq 3 \times$ RBW
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

TEST SETUP





TEST ENVIRONMENT

Temperature	26.9 °C	Relative Humidity	54.8 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix A & B.



7.3. CONDUCTED OUTPUT POWER

LIMITS


CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC 15.247(b)(3) ISED RSS-247 5.4 (d)	Peak Conducted Output Power	1 watt or 30 dBm	2400-2483.5

TEST PROCEDURE

Connect the EUT to a low loss RF cable from the antenna port to the power sensor (video bandwidth is greater than the occupied bandwidth).

Measure peak emission level, the indicated level is the peak output power, after any corrections for external attenuators and cables.

TEST SETUP



TEST ENVIRONMENT

Temperature	26.9 °C	Relative Humidity	54.8 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix C.



7.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2			
Section	Test Item	Limit	Frequency Range (MHz)
CFR 47 FCC §15.247 (e) ISED RSS-247 5.2 (b)	Power Spectral Density	8 dBm in any 3 kHz band	2400-2483.5

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.10.


Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
VBW	$\geq 3 \times \text{RBW}$
Span	$1.5 \times \text{DTS bandwidth}$
Trace	Max hold
Sweep time	Auto couple

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST SETUP



TEST ENVIRONMENT

Temperature	26.9 °C	Relative Humidity	54.8 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V, 60 Hz



RESULTS

Please refer to appendix D.

7.5. CONDUCTED BANDEGE AND SPURIOUS EMISSIONS

LIMITS

CFR 47 FCC Part15 (15.247) Subpart C ISED RSS-247 ISSUE 2		
Section	Test Item	Limit
CFR 47 FCC §15.247 (d) ISED RSS-247 5.5	Conducted Bandedge and Spurious Emissions	at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power

TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 11.11 and 11.13.

Connect the EUT to the spectrum analyser and use the following settings for reference level measurement:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	1.5 x DTS bandwidth
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level.


Change the settings for emission level measurement:

Span	Set the center frequency and span to encompass frequency range to be measured
Detector	Peak
RBW	100 kHz
VBW	$\geq 3 \times \text{RBW}$
measurement points	$\geq \text{span}/\text{RBW}$
Trace	Max hold
Sweep time	Auto couple.

Allow trace to fully stabilize and use the peak marker function to determine the maximum PSD level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified in 11.11.



TEST SETUP



TEST ENVIRONMENT

Temperature	26.9 °C	Relative Humidity	54.8 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

Please refer to appendix E & F.

8. RADIATED TEST RESULTS

LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209.

Please refer to ISSED RSS-GEN Clause 8.9 and Clause 8.10.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz-1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (μA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.



ISED Restricted bands please refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	399.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2690 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.69475 - 16.69525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5460	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):


MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

TEST SETUP AND PROCEDURE

Below 30 MHz




The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz) / 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30 m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz




The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1GHz




The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST ENVIRONMENT

Temperature	23.5 °C	Relative Humidity	61.2 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz


RESULTS

8.1. RESTRICTED BANDEDGE

8.1.1. LE 1M MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2382.910	19.62	33.30	52.92	74.00	-21.08	peak
2	2390.000	13.38	33.35	46.73	74.00	-27.27	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2382.910	1.21	33.30	34.51	54.00	-19.49	AVG
2	2390.000	1.06	33.35	34.41	54.00	-19.59	AVG


Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	26.48	33.71	60.19	74.00	-13.81	peak
2	2483.525	26.26	33.71	59.97	74.00	-14.03	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	7.04	33.71	40.75	54.00	-13.25	AVG
2	2483.525	6.49	33.71	40.20	54.00	-13.80	AVG

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: Both Horizontal and Vertical had been tested, only the worst data was recorded in the report.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.

8.1.2. LE 2M MODE

RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)

PEAK



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2382.450	27.61	33.30	60.91	74.00	-13.09	peak
2	2390.000	19.59	33.35	52.94	74.00	-21.06	peak


Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2382.450	1.24	33.30	34.54	54.00	-19.46	AVG
2	2390.000	1.40	33.35	34.75	54.00	-19.25	AVG


- Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)****PEAK**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	25.63	33.71	59.34	74.00	-14.66	peak
2	2499.325	28.56	33.76	62.32	74.00	-11.68	peak

Note: 1. Measurement = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.

AVG



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2483.500	8.17	33.71	41.88	54.00	-12.12	AVG
2	2499.325	1.41	33.76	35.17	54.00	-18.83	AVG

Note: 1. Measurement = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.


Note: Both Horizontal and Vertical had been tested, only the worst data was recorded in the report.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.

8.2. SPURIOUS EMISSIONS (1 GHz ~ 3 GHz)

8.2.1. LE 1M MODE


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1250.000	51.93	-12.92	39.01	74.00	-34.99	peak
2	1874.000	56.70	-10.10	46.60	74.00	-27.40	peak
3	2132.000	57.94	-9.43	48.51	74.00	-25.49	peak
4	2344.000	59.27	-8.58	50.69	74.00	-23.31	peak
5	2402.000	58.74	-8.39	50.35	/	/	fundamental
6	2576.000	47.34	-7.96	39.38	74.00	-34.62	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1062.000	56.50	-13.67	42.83	74.00	-31.17	peak
2	1662.000	52.53	-11.09	41.44	74.00	-32.56	peak
3	1998.000	52.04	-10.19	41.85	74.00	-32.15	peak
4	2130.000	57.78	-9.46	48.32	74.00	-25.68	peak
5	2402.000	48.86	-8.39	40.47	/	/	fundamental
6	2654.000	49.71	-7.51	42.20	74.00	-31.80	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1072.000	55.29	-13.63	41.66	74.00	-32.34	peak
2	1260.000	51.81	-12.90	38.91	74.00	-35.09	peak
3	1992.000	47.83	-10.19	37.64	74.00	-36.36	peak
4	2346.000	54.20	-8.58	45.62	74.00	-28.38	peak
5	2442.000	52.77	-8.32	44.45	/	/	fundamental
6	2578.000	48.54	-7.95	40.59	74.00	-33.41	peak


Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1072.000	54.41	-13.63	40.78	74.00	-33.22	peak
2	1876.000	53.15	-10.10	43.05	74.00	-30.95	peak
3	1996.000	52.98	-10.19	42.79	74.00	-31.21	peak
4	2346.000	49.25	-8.58	40.67	74.00	-33.33	peak
5	2442.000	49.39	-8.32	41.07	/	/	fundamental
6	2664.000	47.96	-7.44	40.52	74.00	-33.48	peak

Note: 1. Peak Result = Reading Level + Correct Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.

5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1066.000	54.20	-13.65	40.55	74.00	-33.45	peak
2	1666.000	51.25	-11.06	40.19	74.00	-33.81	peak
3	2270.000	48.35	-8.82	39.53	74.00	-34.47	peak
4	2326.000	50.64	-8.64	42.00	74.00	-32.00	peak
5	2480.000	50.33	-8.26	42.07	/	/	fundamental
6	2558.000	50.05	-8.01	42.04	74.00	-31.96	peak

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1262.000	50.45	-12.90	37.55	74.00	-36.45	peak
2	1664.000	51.23	-11.08	40.15	74.00	-33.85	peak
3	1994.000	53.57	-10.18	43.39	74.00	-30.61	peak
4	2480.000	51.02	-8.26	42.76	/	/	fundamental
5	2596.000	49.70	-7.88	41.82	74.00	-32.18	peak
6	2666.000	51.36	-7.43	43.93	74.00	-30.07	peak


- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. Filter losses were only considered in then spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.

8.3. SPURIOUS EMISSIONS (3 GHz ~ 18 GHz)

8.3.1. LE 1M MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7200.000	46.22	7.36	53.58	74.00	-20.42	peak
2	7200.000	34.30	7.36	41.66	54.00	-12.34	AVG
3	11505.000	35.49	14.66	50.15	74.00	-23.85	peak
4	12015.000	42.20	15.53	57.73	74.00	-16.27	peak
5	12015.000	31.27	15.53	46.80	54.00	-7.20	AVG
6	13920.000	32.57	17.55	50.12	74.00	-23.88	peak
7	14820.000	32.58	17.91	50.49	74.00	-23.51	peak
8	16815.000	35.12	20.84	55.96	74.00	-18.04	peak
9	16815.000	22.28	20.84	43.12	54.00	-10.88	AVG

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.


HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	6645.000	40.31	5.95	46.26	74.00	-27.74	peak
2	7200.000	45.31	7.36	52.67	74.00	-21.33	peak
3	7200.000	29.44	7.36	36.80	54.00	-17.20	AVG
4	11685.000	35.27	15.26	50.53	74.00	-23.47	peak
5	12015.000	40.98	15.53	56.51	74.00	-17.49	peak
6	12015.000	29.70	15.53	45.23	54.00	-8.77	AVG
7	13920.000	32.60	17.55	50.15	74.00	-23.85	peak
8	16815.000	34.23	20.84	55.07	74.00	-18.93	peak
9	16815.000	20.94	20.84	41.78	54.00	-12.22	AVG

Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4140.000	46.74	-1.85	44.89	74.00	-29.11	peak
2	4875.000	43.70	1.32	45.02	74.00	-28.98	peak
3	7320.000	47.68	7.28	54.96	74.00	-19.04	peak
4	7320.000	39.69	7.28	46.97	54.00	-7.03	AVG
5	12210.000	44.40	15.97	60.37	74.00	-13.63	peak
6	12210.000	31.55	15.97	47.52	54.00	-6.48	AVG
7	14820.000	33.38	17.91	51.29	74.00	-22.71	peak
8	17685.000	28.42	23.36	51.78	74.00	-22.22	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4875.000	44.73	1.32	46.05	74.00	-27.95	peak
2	7320.000	44.83	7.28	52.11	74.00	-21.89	peak
3	7320.000	36.17	7.28	43.45	54.00	-10.55	AVG
4	11880.000	34.34	15.46	49.80	74.00	-24.20	peak
5	12210.000	45.42	15.97	61.39	74.00	-12.61	peak
6	12210.000	34.45	15.97	50.42	54.00	-3.58	AVG
7	14805.000	33.20	18.00	51.20	74.00	-22.80	peak
8	17100.000	33.98	21.90	55.88	74.00	-18.12	peak
9	17100.000	28.52	21.90	50.42	54.00	-3.58	AVG

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	43.46	1.71	45.17	74.00	-28.83	peak
2	7440.000	47.03	8.13	55.16	74.00	-18.84	peak
3	7440.000	34.63	8.13	42.76	54.00	-11.24	AVG
4	11505.000	36.39	14.66	51.05	74.00	-22.95	peak
5	12405.000	38.06	15.94	54.00	74.00	-20.00	peak
6	12405.000	26.92	15.94	42.86	54.00	-11.14	AVG
7	14835.000	33.68	17.80	51.48	74.00	-22.52	peak
8	17760.000	27.30	23.82	51.12	74.00	-22.88	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7440.000	43.98	8.13	52.11	74.00	-21.89	peak
2	7440.000	30.54	8.13	38.67	54.00	-15.33	AVG
3	11835.000	35.25	15.34	50.59	74.00	-23.41	peak
4	12405.000	40.54	15.94	56.48	74.00	-17.52	peak
5	12405.000	28.38	15.94	44.32	54.00	-9.68	AVG
6	13545.000	34.03	17.16	51.19	74.00	-22.81	peak
7	15210.000	33.99	16.86	50.85	74.00	-23.15	peak
8	16995.000	29.85	21.26	51.11	74.00	-22.89	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.


6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.


8.3.2. LE 2M MODE

HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4950.000	44.29	1.71	46.00	74.00	-28.00	peak
2	7440.000	46.57	8.13	54.70	74.00	-19.30	peak
3	7440.000	31.10	8.13	39.23	54.00	-14.77	AVG
4	12405.000	40.29	15.94	56.23	74.00	-17.77	peak
5	12405.000	31.88	15.94	47.82	54.00	-6.18	AVG
6	13470.000	34.52	17.15	51.67	74.00	-22.33	peak
7	14835.000	33.54	17.80	51.34	74.00	-22.66	peak
8	16905.000	29.69	21.55	51.24	74.00	-22.76	peak

- Note: 1. Peak Result = Reading Level + Correct Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Peak: Peak detector.
4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4095.000	45.81	-2.37	43.44	74.00	-30.56	peak
2	7440.000	44.97	8.13	53.10	74.00	-20.90	peak
3	7440.000	36.08	8.13	44.21	54.00	-9.79	AVG
4	11685.000	35.33	15.26	50.59	74.00	-23.41	peak
5	12405.000	41.82	15.94	57.76	74.00	-16.24	peak
6	12405.000	33.73	15.94	49.67	54.00	-4.33	AVG
7	14775.000	33.96	17.95	51.91	74.00	-22.09	peak
8	17340.000	28.66	22.31	50.97	74.00	-23.03	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7320.000	47.37	7.28	54.65	74.00	-19.35	peak
2	7320.000	39.54	7.28	46.82	54.00	-7.18	AVG
3	9345.000	37.64	10.66	48.30	74.00	-25.70	peak
4	11835.000	35.06	15.34	50.40	74.00	-23.60	peak
5	12210.000	43.33	15.97	59.30	74.00	-14.70	peak
6	12210.000	35.49	15.97	51.46	54.00	-2.54	AVG
7	14820.000	33.76	17.91	51.67	74.00	-22.33	peak
8	15660.000	33.39	17.77	51.16	74.00	-22.84	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. AVG: VBW=1/Ton, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7320.000	43.99	7.28	51.27	74.00	-22.73	peak
2	8145.000	37.62	10.01	47.63	74.00	-26.37	peak
3	11895.000	34.54	15.50	50.04	74.00	-23.96	peak
4	12210.000	45.65	15.97	61.62	74.00	-12.38	peak
5	12210.000	30.73	15.97	46.70	54.00	-7.30	AVG
6	14340.000	33.43	17.84	51.27	74.00	-22.73	peak
7	17100.000	28.79	21.90	50.69	74.00	-23.31	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.


4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7440.000	45.49	8.13	53.62	74.00	-20.38	peak
2	7440.000	29.81	8.13	37.94	54.00	-16.06	AVG
3	11610.000	35.22	14.79	50.01	74.00	-23.99	peak
4	12405.000	40.33	15.94	56.27	74.00	-17.73	peak
5	12405.000	25.30	15.94	41.24	54.00	-12.76	AVG
6	13935.000	33.56	17.58	51.14	74.00	-22.86	peak
7	14820.000	33.13	17.91	51.04	74.00	-22.96	peak
8	18000.000	26.81	24.27	51.08	74.00	-22.92	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.

**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7440.000	43.64	8.13	51.77	74.00	-22.23	peak
2	9390.000	37.02	10.92	47.94	74.00	-26.06	peak
3	11745.000	34.89	15.30	50.19	74.00	-23.81	peak
4	12405.000	40.54	15.94	56.48	74.00	-17.52	peak
5	12405.000	28.32	15.94	44.26	54.00	-9.74	AVG
6	13905.000	33.32	17.54	50.86	74.00	-23.14	peak
7	16860.000	30.04	21.22	51.26	74.00	-22.74	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.

5. For the transmitting duration, please refer to clause 7.1.

6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.

7. Proper operation of the transmitter prior to adding the filter to the measurement chain.


Note: All the modes and channels have been tested, only the worst data was recorded in the report.



8.4. SPURIOUS EMISSIONS (18 GHz ~ 26 GHz)

8.4.1. LE 2M MODE

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18592.000	50.25	-5.31	44.94	74.00	-29.06	peak
2	20024.000	51.25	-5.47	45.78	74.00	-28.22	peak
3	20560.000	50.73	-5.30	45.43	74.00	-28.57	peak
4	23064.000	48.99	-3.42	45.57	74.00	-28.43	peak
5	24248.000	48.82	-2.83	45.99	74.00	-28.01	peak
6	25072.000	47.67	-1.97	45.70	74.00	-28.30	peak

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Peak: Peak detector.

**SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**

Note: 1. Peak Result = Reading Level + Correct Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Peak: Peak detector.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.

8.5. SPURIOUS EMISSIONS (30 MHz ~ 1 GHz)

8.5.1. LE 2M MODE

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	57.1600	41.87	-20.58	21.29	40.00	-18.71	QP
2	206.5399	38.06	-16.97	21.09	43.50	-22.41	QP
3	214.3000	46.41	-17.66	28.75	43.50	-14.75	QP
4	250.1900	35.03	-18.91	16.12	46.00	-29.88	QP
5	311.3000	32.40	-15.04	17.36	46.00	-28.64	QP
6	950.5300	28.16	-4.42	23.74	46.00	-22.26	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

SPURIOUS EMISSIONS (MID CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	34.8500	45.53	-19.40	26.13	40.00	-13.87	QP
2	48.4300	42.99	-20.63	22.36	40.00	-17.64	QP
3	79.4700	40.21	-21.30	18.91	40.00	-21.09	QP
4	136.7000	38.20	-19.02	19.18	43.50	-24.32	QP
5	215.2700	41.54	-17.76	23.78	43.50	-19.72	QP
6	931.1300	27.43	-4.76	22.67	46.00	-23.33	QP

Note: 1. Result Level = Read Level + Correct Factor.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto


Note: All the modes and channels have been tested, only the worst data was recorded in the report.

8.6. SPURIOUS EMISSIONS BELOW 30 MHz

8.6.1. LE 2M MODE

SPURIOUS EMISSIONS (MID CHANNEL, LOOP ANTENNA FACE ON TO THE EUT, WORST-CASE CONFIGURATION)

9 kHz~ 150 kHz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.0100	74.72	-101.40	-26.68	47.6	-78.18	-3.90	-74.28	peak
2	0.0151	68.71	-101.37	-32.66	44.02	-84.16	-7.48	-76.68	peak
3	0.0279	65.67	-101.38	-35.71	38.69	-87.21	-12.81	-74.40	peak
4	0.0514	61.18	-101.48	-40.3	33.38	-91.80	-18.12	-73.68	peak
5	0.0675	59.64	-101.56	-41.92	31.02	-93.42	-20.48	-72.94	peak
6	0.0981	56.27	-101.78	-45.51	27.77	-97.01	-23.73	-73.28	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

150 kHz ~ 490 kHz


No.	Frequency	Reading	Correct	FCC Result	FCC Limit	ISED Result	ISED Limit	Margin	Remark
	(MHz)	(dBuV)	(dB/m)	(dBuV/m)	(dBuV/m)	(dBuA/m)	(dBuA/m)	(dB)	
1	0.1554	74.77	-101.65	-26.88	23.77	-78.38	-27.73	-50.65	peak
2	0.1630	72.99	-101.65	-28.66	23.36	-80.16	-28.14	-52.02	peak
3	0.2053	66.79	-101.73	-34.94	21.35	-86.44	-30.15	-56.29	peak
4	0.2494	63.96	-101.80	-37.84	19.66	-89.34	-31.84	-57.50	peak
5	0.2972	62.16	-101.85	-39.69	18.14	-91.19	-33.36	-57.83	peak
6	0.3234	61.48	-101.88	-40.4	17.41	-91.90	-34.09	-57.81	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120 π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

490 kHz ~ 30 MHz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	FCC Result (dBuV/m)	FCC Limit (dBuV/m)	ISED Result (dBuA/m)	ISED Limit (dBuA/m)	Margin (dB)	Remark
1	0.5039	64.94	-62.07	2.87	33.56	-48.63	-17.94	-30.69	peak
2	0.8296	63.94	-62.17	1.77	29.23	-49.73	-22.27	-27.46	peak
3	1.3810	58.47	-62.10	-3.63	24.8	-55.13	-26.70	-28.43	peak
4	2.0939	56.89	-61.79	-4.9	29.54	-56.40	-21.96	-34.44	peak
5	3.7100	54.70	-61.41	-6.71	29.54	-58.21	-21.96	-36.25	peak
6	10.7299	52.98	-60.83	-7.85	29.54	-59.35	-21.96	-37.39	peak

Note: 1. Measurement = Reading Level + Correct Factor (dBuA/m= dBuV/m- 20Log10[120π] = dBuV/m- 51.5).

2. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.

3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.

9. AC POWER LINE CONDUCTED EMISSIONS


LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

TEST SETUP AND PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.



The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.


TEST ENVIRONMENT

Temperature	26.9 °C	Relative Humidity	54.8 %
Atmosphere Pressure	101 kPa	Test Voltage	AC120 V,60 Hz

RESULTS

9.1. LE 2M MODE

LINE L RESULTS (MID CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1593	23.79	9.59	33.38	65.50	-32.12	QP
2	0.1593	5.58	9.59	15.17	55.50	-40.33	AVG
3	0.1806	21.97	9.59	31.56	64.46	-32.90	QP
4	0.1806	6.03	9.59	15.62	54.46	-38.84	AVG
5	0.1956	18.99	9.59	28.58	63.80	-35.22	QP
6	0.1956	6.45	9.59	16.04	53.80	-37.76	AVG
7	1.0907	19.58	9.61	29.19	56.00	-26.81	QP
8	1.0907	9.94	9.61	19.55	46.00	-26.45	AVG
9	2.7507	21.62	9.62	31.24	56.00	-24.76	QP
10	2.7507	17.67	9.62	27.29	46.00	-18.71	AVG
11	5.5000	18.66	9.63	28.29	60.00	-31.71	QP
12	5.5000	13.02	9.63	22.65	50.00	-27.35	AVG


Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

LINE N RESULTS (MID CHANNEL, WORST-CASE CONFIGURATION)



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1771	20.55	9.59	30.14	64.62	-34.48	QP
2	0.1771	-0.66	9.59	8.93	54.62	-45.69	AVG
3	0.2143	18.03	9.59	27.62	63.04	-35.42	QP
4	0.2143	-2.49	9.59	7.10	53.04	-45.94	AVG
5	0.2533	12.68	9.59	22.27	61.65	-39.38	QP
6	0.2533	-3.12	9.59	6.47	51.65	-45.18	AVG
7	0.3991	3.61	9.59	13.20	57.87	-44.67	QP
8	0.3991	-3.04	9.59	6.55	47.87	-41.32	AVG
9	1.1193	3.09	9.61	12.70	56.00	-43.30	QP
10	1.1193	-3.23	9.61	6.38	46.00	-39.62	AVG
11	2.7508	7.46	9.62	17.08	56.00	-38.92	QP
12	2.7508	2.66	9.62	12.28	46.00	-33.72	AVG

Note: 1. Result = Reading + Correct Factor.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).

4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.



10. ANTENNA REQUIREMENTS

APPLICABLE REQUIREMENTS

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

RESULTS

Complies

**10.1. Appendix A: DTS Bandwidth****10.1.1. Test Result**

Test Mode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_125K	Ant1	2402	0.729	2401.682	2402.411	0.5	PASS
		2442	0.747	2441.670	2442.417	0.5	PASS
		2480	0.741	2479.673	2480.414	0.5	PASS
BLE_500K	Ant1	2402	0.747	2401.661	2402.408	0.5	PASS
		2442	0.756	2441.667	2442.423	0.5	PASS
		2480	0.696	2479.700	2480.396	0.5	PASS
BLE_1M	Ant1	2402	0.660	2401.715	2402.375	0.5	PASS
		2442	0.648	2441.715	2442.363	0.5	PASS
		2480	0.657	2479.718	2480.375	0.5	PASS
BLE_2M	Ant1	2402	1.116	2401.492	2402.608	0.5	PASS
		2442	1.108	2441.492	2442.600	0.5	PASS
		2480	1.116	2479.492	2480.608	0.5	PASS



10.1.2. Test Graphs







BLE 1M Ant1 2402



BLE 1M Ant1 2442



BLE 1M Ant1 2480



10.2. Appendix B: Occupied Channel Bandwidth

10.2.1. Test Result

Test Mode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Verdict
BLE_125K	Ant1	2402	1.1226	2401.483	2402.605	PASS
		2442	1.1223	2441.482	2442.604	PASS
		2480	1.1136	2479.488	2480.602	PASS
BLE_500K	Ant1	2402	1.0903	2401.502	2402.592	PASS
		2442	1.0835	2441.505	2442.589	PASS
		2480	1.0745	2479.509	2480.583	PASS
BLE_1M	Ant1	2402	1.0269	2401.533	2402.560	PASS
		2442	1.0313	2441.534	2442.565	PASS
		2480	1.0277	2479.533	2480.561	PASS
BLE_2M	Ant1	2402	2.0534	2401.035	2403.089	PASS
		2442	2.0698	2441.029	2443.099	PASS
		2480	2.0852	2479.018	2481.103	PASS

10.2.2. Test Graphs











10.3. Appendix C: Maximum conducted output power

10.3.1. Test Result

Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE_125K	Ant1	2402	9.01	<=30	PASS
		2442	9.12	<=30	PASS
		2480	9.09	<=30	PASS
BLE_500K	Ant1	2402	9.11	<=30	PASS
		2442	9.12	<=30	PASS
		2480	9.11	<=30	PASS
BLE_1M	Ant1	2402	9.13	<=30	PASS
		2442	9.14	<=30	PASS
		2480	9.11	<=30	PASS
BLE_2M	Ant1	2402	9.18	<=30	PASS
		2442	9.23	<=30	PASS
		2480	9.13	<=30	PASS





10.4. Appendix D: Maximum power spectral density


10.4.1. Test Result

Test Mode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_125K	Ant1	2402	3.86	<=8	PASS
		2442	3.84	<=8	PASS
		2480	3.64	<=8	PASS
BLE_500K	Ant1	2402	3.66	<=8	PASS
		2442	3.66	<=8	PASS
		2480	3.44	<=8	PASS
BLE_1M	Ant1	2402	-6.13	<=8	PASS
		2442	-6.12	<=8	PASS
		2480	-6.15	<=8	PASS
BLE_2M	Ant1	2402	-7.3	<=8	PASS
		2442	-7.14	<=8	PASS
		2480	-7.39	<=8	PASS

10.4.2. Test Graphs











10.5. Appendix E: Band edge measurements

10.5.1. Test Result

Test Mode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_125K	Ant1	Low	2402	4.42	-45.47	<=-15.58	PASS
		High	2480	4.83	-47.79	<=-15.17	PASS
BLE_500K	Ant1	Low	2402	7.42	-45.49	<=-12.58	PASS
		High	2480	6.81	-47.99	<=-13.19	PASS
BLE_1M	Ant1	Low	2402	8.47	-39.69	<=-11.53	PASS
		High	2480	8.49	-45.47	<=-11.51	PASS
BLE_2M	Ant1	Low	2402	8.29	-25.59	<=-11.71	PASS
		High	2480	8.25	-44.79	<=-11.75	PASS




10.5.2. Test Graphs






BLE 500K Ant1 High 2480



BLE 1M Ant1 Low 2402



BLE 1M Ant1 High 2480





**10.6. Appendix F: Conducted Spurious Emission****10.6.1. Test Result**


Test Mode	Antenna	Channel	FreqRange [MHz]	Result[dBm]	Limit[dBm]	Verdict
BLE_125K	Ant1	2402	Reference	5.23	---	PASS
			30~1000	-58.56	<=-14.77	PASS
			1000~26500	-56.06	<=-14.77	PASS
		2442	Reference	5.13	---	PASS
			30~1000	-59.23	<=-14.87	PASS
			1000~26500	-54.77	<=-14.87	PASS
		2480	Reference	5.23	---	PASS
			30~1000	-59.27	<=-14.77	PASS
			1000~26500	-56.43	<=-14.77	PASS
BLE_500K	Ant1	2402	Reference	5.20	---	PASS
			30~1000	-59.33	<=-14.8	PASS
			1000~26500	-56.39	<=-14.8	PASS
		2442	Reference	7.69	---	PASS
			30~1000	-59.04	<=-12.31	PASS
			1000~26500	-55.98	<=-12.31	PASS
		2480	Reference	7.78	---	PASS
			30~1000	-59.10	<=-12.22	PASS
			1000~26500	-56.54	<=-12.22	PASS
BLE_1M	Ant1	2402	Reference	7.74	---	PASS
			30~1000	-59.24	<=-12.26	PASS
			1000~26500	-56.66	<=-12.26	PASS
		2442	Reference	7.02	---	PASS
			30~1000	-58.9	<=-12.98	PASS
			1000~26500	-56.44	<=-12.98	PASS
		2480	Reference	7.08	---	PASS
			30~1000	-58.9	<=-12.92	PASS
			1000~26500	-56.2	<=-12.92	PASS
BLE_2M	Ant1	2402	Reference	7.12	---	PASS
			30~1000	-58.68	<=-12.88	PASS
			1000~26500	-57.13	<=-12.88	PASS
		2442	Reference	7.02	---	PASS
			30~1000	-59.08	<=-12.98	PASS
			1000~26500	-56.17	<=-12.98	PASS
		2480	Reference	6.85	---	PASS
			30~1000	-58.37	<=-13.15	PASS
			1000~26500	-55.95	<=-13.15	PASS





10.6.1. Test Graphs


















































**10.7. Appendix G: Duty Cycle****10.7.1. Test Result**

Mode	On Time (msec)	Period (msec)	Duty Cycle x (Linear)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	1/T Minimum VBW (kHz)	Final setting For VBW (kHz)
BLE_1M	0.38	0.63	0.6032	60.32	2.20	2.63	3
BLE_2M	0.20	0.63	0.3175	31.75	4.98	5.00	5

Note:

Duty Cycle Correction Factor= $10\log(1/x)$.

Where: x is Duty Cycle (Linear)

Where: T is On Time

If that calculated VBW is not available on the analyzer then the next higher value should be used.

Note: All the modes and channels have been tested, only the worst data was recorded in the report.

10.7.2. Test Graphs



END OF REPORT