

FCC/ISED - TEST REPORT

Report Number : **709502203709-00A** Date of Issue: January 26, 2022

Model : 9290031345, 9290031347

Product Type : LED light

Trademark : PHILIPS

FCC ID: : 9290031345: 2AGBW9290031345X
9290031347: 2AGBW9290031347X

IC: : 9290031345: 20812-31345X
9290031347: 20812-31347X

Applicant : Signify (China) Investment Co., Ltd.


Address : Building no.9, Lane 888, Tianlin Road, Minhang District Shanghai,
200233 China

Production Facility : Ningbo Klite Electric Manufacture Co., Ltd

Address : No.5 Dapu River, Beilun, 315800 Ningbo
PEOPLE'S REPUBLIC OF CHINA

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including
Appendices : 81



TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.

TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.

This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards	6
5	Summary of Test Results.....	7
6	General Remarks.....	8
7	Test Setups.....	10
8	Systems test configuration	13
9	Technical Requirement	14
9.1	Conducted Emission	14
9.2	Conducted peak output power	19
9.3	6dB bandwidth and 99% Occupied Bandwidth	25
9.4	Power spectral density	35
9.5	Spurious RF conducted emissions.....	40
9.6	Band edge	58
9.7	Spurious radiated emissions for transmitter	64
10	Test Equipment List	78
11	System Measurement Uncertainty.....	79
12	Photographs of Test Set-ups.....	80
13	Photographs of EUT	81



2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch
No.16 Lane, 1951 Du Hui Road,
Shanghai 201108,
P.R. China

Telephone: +86 21 6141 0123

Fax: +86 21 6140 8600

FCC Registration No.: 820234

FCC Designation Number: CN1183

ISED#: 25988

CAB identifier CN0101

3 Description of the Equipment under Test

Description of the Equipment Under Test

Product: LED light

Model no.: 9290031345, 9290031347

FCC ID: 9290031345: 2AGBW9290031345X
9290031347: 2AGBW9290031347X

IC: 9290031345: 20812-31345X
9290031347: 20812-31347X

Options and accessories: 4" metal can

Rating: 120 Vac, 60Hz

RF Transmission Frequency: 2402~2480MHz for BT 5.0 LE

No. of Operated Channel: 40 for Bluetooth

Bluetooth Working Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz	03	2408 MHz
04	2410 MHz	05	2412 MHz	06	2414 MHz	06	2416 MHz
08	2418 MHz	09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz	15	2432 MHz
16	2434 MHz	17	2436 MHz	18	2438 MHz	19	2440 MHz
20	2442 MHz	21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz	27	2456 MHz
28	2458 MHz	29	2460 MHz	30	2462 MHz	31	2464 MHz
32	2466 MHz	33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz	39	2480 MHz

Modulation: GFSK PHY for BT 5.0 LE (LE Coded S=2/8, LE 1M, LE 2M)

Data transmission rate: 2 Mbit/s Max for BT 5.0 LE (125 Kbit/s, 500 Kbit/s, 1Mbit/s, 2Mbit/s)

Antenna Type: Integral PCB Antenna

Antenna Gain: 0.76dBi

Description of the EUT: The Equipment Under Test (EUT) is a LED light support Bluetooth 5.0 and Zigbee.



We tested it and listed the worst data in this report.

Test sample no.: SHA-616767-5 (9290031345) for RF conducted test
SHA-616767-6 (9290031345), SHA-616767-7 (9290031347) for
RF radiated test and Conducted emission AC power port test.

The sample's mentioned in this report is supplied by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2014 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 Amendment 1 March 2019	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 2 February 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207 & RSS-GEN 8.8	Conducted emission AC power port	14-18	Site 1	☒	☐	☐
§15.247 (b) (3) & RSS-247 5.4(d)	Conducted peak output power	19-24	Site 1	☒	☐	☐
§15.247(a)(1) & RSS-247 5.1(b)	20dB bandwidth	---	---	☐	☐	☒
§15.247(a)(1) & RSS-247 5.1(b)	Carrier frequency separation	---	---	☐	☐	☒
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Number of hopping frequencies	---	---	☐	☐	☒
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Dwell Time	---	---	☐	☐	☒
§15.247(a)(2) & RSS-247 5.2(a) & RSSGEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	25-34	Site 1	☒	☐	☐
§15.247(e) & RSS-247 5.2(b)	Power spectral density	35-39	Site 1	☒	☐	☐
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	40-57	Site 1	☒	☐	☐
§15.247(d) & RSS-247 5.5	Band edge	58-63	Site 1	☒	☐	☐
§15.247(d) & §15.209 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	64-77	Site 1	☒	☐	☐
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 1		☒	☐	☐

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses an Integral PCB Antenna, which gain is 0.76dBi. In accordance to §15.203 and RSS-Gen 6.8, It is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AGBW9290031345X and 2AGBW9290031347X, IC: 20812-31345X and 20812-31347X complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules and RSS-247, RSS-GEN.

According to the client's declaration, 9290031345 and 9290031347 are use same Bluetooth and Zigbee module. So we chose the 9290031345 to perform the conductive RF tests and chose 9290031345 and 9290031347 to perform the conducted emission AC power port test and radiated emission test.

Model No	Input Voltage	Wattage	Frequency
9290031345	120VAC	10W	60Hz
9290031347	120VAC	10W	60Hz
Wireless control	PCB layout		
BT 5.0/Zigbee	The driver and the wireless board are the same, the light source board is different.		
BT 5.0/Zigbee			

This report is only for the 2.4GHz BLE test report, for the 2.4GHz Zigbee test report please refer to 709502203709-00B.

SUMMARY: All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: November 18, 2021

Testing Start Date: November 19, 2021


Testing End Date: January 6, 2022

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:



Hui TONG
EMC Section Manager




Zhining ZHANG
EMC Project Engineer



Chengjie GUO
EMC Test Engineer


7 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



18GHz ~ 25GHz Test Setup:



7.2 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	E470	PF-OU5TS7 17/09

Test software: HueApprobationTool, which used to control the EUT in continues transmitting mode.

Power level setting at 10dBm.

The system was configured to channel 0, 19, and 39 for the test.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line


Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

Conducted Emission


Product Type : LED light
 M/N : 9290031345
 Operating Condition : Mode 1: Tx_2440MHz BLE_1Mbit/s
 Test Specification : L-Line
 Comment : AC 120V 60Hz



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.298500	---	32.60	50.28	17.68	1000.0	9.000	L1	19.5
0.357000	46.69	---	58.80	12.11	1000.0	9.000	L1	19.5
0.820500	47.47	---	56.00	8.53	1000.0	9.000	L1	19.5
0.843000	---	31.81	46.00	14.19	1000.0	9.000	L1	19.5
0.969000	48.18	---	56.00	7.82	1000.0	9.000	L1	19.5
0.978000	---	32.20	46.00	13.80	1000.0	9.000	L1	19.5
4.353000	50.54	---	56.00	5.46	1000.0	9.000	L1	19.6
4.380000	---	32.03	46.00	13.97	1000.0	9.000	L1	19.6
5.595000	51.11	---	60.00	8.89	1000.0	9.000	L1	19.6
5.595000	---	33.82	50.00	16.18	1000.0	9.000	L1	19.6
12.412500	31.63	---	60.00	28.37	1000.0	9.000	L1	19.7
20.238000	---	30.04	50.00	19.96	1000.0	9.000	L1	19.8


Product Type : LED light
 M/N : 9290031345
 Operating Condition : Mode 1: Tx_2440MHz BLE_1Mbit/s
 Test Specification : N-Line
 Comment : AC 120V 60Hz



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.298500	---	34.27	50.28	16.01	1000.0	9.000	N	19.5
0.325500	48.78	---	59.57	10.79	1000.0	9.000	N	19.5
0.838500	49.35	---	56.00	6.65	1000.0	9.000	N	19.5
0.870000	---	32.46	46.00	13.54	1000.0	9.000	N	19.5
0.955500	---	33.44	46.00	12.56	1000.0	9.000	N	19.5
1.446000	51.62	---	56.00	4.38	1000.0	9.000	N	19.5
4.312500	52.15	---	56.00	3.85	1000.0	9.000	N	19.5
4.380000	---	33.55	46.00	12.45	1000.0	9.000	N	19.5
5.554500	52.62	---	60.00	7.38	1000.0	9.000	N	19.6
5.608500	---	34.87	50.00	15.13	1000.0	9.000	N	19.6
12.448500	30.97	---	60.00	29.03	1000.0	9.000	N	19.7
20.238000	---	30.00	50.00	20.00	1000.0	9.000	N	19.8


Product Type : LED light
 M/N : 9290031347
 Operating Condition : Mode 1: Tx_2440MHz BLE_1Mbit/s
 Test Specification : L-Line
 Comment : AC 120V 60Hz



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.190500	---	41.16	54.01	12.85	1000.0	9.000	L1	19.5
0.195000	48.64	---	63.82	15.18	1000.0	9.000	L1	19.5
0.694500	44.36	---	56.00	11.64	1000.0	9.000	L1	19.5
0.861000	---	36.19	46.00	9.81	1000.0	9.000	L1	19.5
0.942000	---	33.76	46.00	12.24	1000.0	9.000	L1	19.5
1.392000	41.78	---	56.00	14.22	1000.0	9.000	L1	19.5
3.903000	---	33.03	46.00	12.97	1000.0	9.000	L1	19.6
4.537500	44.35	---	56.00	11.65	1000.0	9.000	L1	19.6
5.212500	44.27	---	60.00	15.73	1000.0	9.000	L1	19.6
5.212500	---	33.38	50.00	16.62	1000.0	9.000	L1	19.6
14.334000	---	27.30	50.00	22.70	1000.0	9.000	L1	19.8
28.270500	31.29	---	60.00	28.71	1000.0	9.000	L1	20.0

Product Type : LED light
 M/N : 9290031347
 Operating Condition : Mode 1: Tx_2440MHz BLE_1Mbit/s
 Test Specification : N-Line
 Comment : AC 120V 60Hz



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.190500	---	40.42	54.01	13.59	1000.0	9.000	N	19.5
0.348000	42.29	---	59.01	16.72	1000.0	9.000	N	19.5
0.469500	---	37.20	46.52	9.32	1000.0	9.000	N	19.5
0.469500	49.14	---	56.52	7.38	1000.0	9.000	N	19.5
0.942000	---	33.67	46.00	12.33	1000.0	9.000	N	19.5
1.050000	43.46	---	56.00	12.54	1000.0	9.000	N	19.5
2.791500	41.55	---	56.00	14.45	1000.0	9.000	N	19.5
3.916500	---	31.54	46.00	14.46	1000.0	9.000	N	19.5
5.185500	---	32.88	50.00	17.12	1000.0	9.000	N	19.6
5.212500	43.00	---	60.00	17.00	1000.0	9.000	N	19.6
14.334000	---	27.71	50.00	22.29	1000.0	9.000	N	19.7
29.665500	32.28	---	60.00	27.72	1000.0	9.000	N	20.1

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

9.2 Conducted peak output power

Test Method

1. Use the following spectrum analyzer settings:
RBW > the 6 dB bandwidth of the emission being measured, VBW $\geq$ 3RBW, Span $\geq$ 3RBW
Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

Limits

According to §15.247 (b) (1) & RSS-247 5.4(d), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤ 1	≤ 30

Frequency Range MHz	Limit (EIRP) W	Limit dBm
2400-2483.5	≤ 4	≤ 36


Test result

TestMode	Channel	Conducted Peak Output Power Result[dBm]	Limit[dBm]	Verdict
BLE_125K	2402	9.41	≤ 30	PASS
	2440	9.49	≤ 30	PASS
	2480	9.47	≤ 30	PASS
BLE_500K	2402	9.42	≤ 30	PASS
	2440	9.51	≤ 30	PASS
	2480	9.48	≤ 30	PASS
BLE_1M	2402	9.46	≤ 30	PASS
	2440	9.53	≤ 30	PASS
	2480	9.51	≤ 30	PASS
BLE_2M	2402	9.45	≤ 30	PASS
	2440	9.52	≤ 30	PASS
	2480	9.50	≤ 30	PASS

TestMode	Channel	EIRP Result[dBm]	Limit[dBm]	Verdict
BLE_125K	2402	10.17	<=36	PASS
	2440	10.25	<=36	PASS
	2480	10.23	<=36	PASS
BLE_500K	2402	10.18	<=36	PASS
	2440	10.27	<=36	PASS
	2480	10.24	<=36	PASS
BLE_1M	2402	10.22	<=36	PASS
	2440	10.29	<=36	PASS
	2480	10.27	<=36	PASS
BLE_2M	2402	10.17	<=36	PASS
	2440	10.25	<=36	PASS
	2480	10.23	<=36	PASS


Test Graphs

BLE_125K_Ant1_2402




Date: 9 DEC 2021 13:39:03

BLE_125K_Ant1_2440




Date: 9 DEC 2021 13:40:12

BLE 125K Ant1 2480




Date: 9 DEC 2021 13:41:12

BLE 500K Ant1 2402




Date: 9 DEC 2021 13:31:02

BLE 500K Ant1 2440




Date: 9 DEC 2021 13:33:18

BLE 500K Ant1 2480




Date: 9 DEC 2021 13:34:15

BLE 1M Ant1 2402




Date: 9 DEC 2021 12:57:11

BLE 1M Ant1 2440




Date: 9 DEC 2021 13:06:09

BLE_1M_Ant1_2480




Date: 9 DEC 2021 13:07:31

BLE_2M_Ant1_2402



Date: 9 DEC 2021 13:09:17


BLE_2M_Ant1_2440



Date: 9 DEC 2021 13:10:39



China



9.3 6dB bandwidth and 99% Occupied Bandwidth

Test Method

1. Use the following spectrum analyzer settings:
RBW=100K, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq$ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Test Method for 99 % Bandwidth

1. Use the following spectrum analyzer settings:
RBW=1% to 5% of the actual occupied, VBW $\geq$ 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be $\geq$ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit

Limit [kHz]


≥ 500

Test result

6dB Bandwidth


TestMode	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_125K	2402	0.74	0.5	PASS
	2440	0.74	0.5	PASS
	2480	0.718	0.5	PASS
BLE_1M	2402	0.667	0.5	PASS
	2440	0.712	0.5	PASS
	2480	0.696	0.5	PASS
BLE_2M	2402	1.349	0.5	PASS
	2440	1.351	0.5	PASS
	2480	1.344	0.5	PASS
BLE_500K	2402	0.813	0.5	PASS
	2440	0.752	0.5	PASS
	2480	0.752	0.5	PASS

BLE 125K Ant1 2402




Date: 9 DEC 2021 13:39:15

BLE 125K Ant1 2440




Date: 9 DEC 2021 13:40:24

BLE 125K Ant1 2480




Date: 9 DEC 2021 13:41:23

BLE_1M_Ant1_2402




Date: 9 DEC 2021 12:57:20

BLE_1M_Ant1_2440




Date: 9 DEC 2021 13:06:20

BLE_1M_Ant1_2480




Date: 9 DEC 2021 13:07:42

BLE_2M_Ant1_2402




Date: 9 DEC 2021 13:09:28

BLE_2M_Ant1_2440




Date: 9 DEC 2021 13:10:50

BLE_2M_Ant1_2480




Date: 9 DEC 2021 13:12:00

BLE 500K_Ant1_2402




Date: 9 DEC 2021 13:31:12

BLE 500K_Ant1_2440



Date: 9 DEC 2021 13:33:28

BLE 500K_Ant1_2480




Date: 9 DEC 2021 13:34:25

99% Occupied Bandwidth


TestMode	Channel	OCB [MHz]	Limit[MHz]	Verdict
BLE_125K	2402	1.128	---	PASS
	2440	1.125	---	PASS
	2480	1.123	---	PASS
BLE_1M	2402	1.035	---	PASS
	2440	1.036	---	PASS
	2480	1.033	---	PASS
BLE_2M	2402	2.084	---	PASS
	2440	2.09	---	PASS
	2480	2.092	---	PASS
BLE_500K	2402	1.083	---	PASS
	2440	1.081	---	PASS
	2480	1.082	---	PASS

BLE_125K_Ant1_2402



Date: 9 DEC 2021 13:39:09

BLE_125K_Ant1_2440



Date: 9 DEC 2021 13:40:18

BLE 125K Ant1 2480




BLE 1M Ant1 2402



BLE 1M Ant1 2440




BLE_1M_Ant1_2480




Date: 9 DEC 2021 13:07:36

BLE_2M_Ant1_2402




Date: 9 DEC 2021 13:09:22

BLE_2M_Ant1_2440




Date: 9 DEC 2021 13:10:44

BLE 2M_Ant1_2480



Date: 9 DEC 2021 13:11:54

BLE 500K_Ant1_2402



Date: 9 DEC 2021 13:31:07

BLE 500K_Ant1_2440



Date: 9 DEC 2021 13:33:23

BLE 500K Ant1 2480



Date: 9 DEC 2021 13:34:19

9.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.
RBW=3kHz, VBW $\geq$ 3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3kHz]


≤ 8

Test result


TestMode	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_125K	2402	3.87	≤ 8	PASS
	2440	3.94	≤ 8	PASS
	2480	3.90	≤ 8	PASS
BLE_1M	2402	-6.39	≤ 8	PASS
	2440	-6.36	≤ 8	PASS
	2480	-6.36	≤ 8	PASS
BLE_2M	2402	-8.36	≤ 8	PASS
	2440	-8.26	≤ 8	PASS
	2480	-8.29	≤ 8	PASS
BLE_500K	2402	-9.12	≤ 8	PASS
	2440	-8.94	≤ 8	PASS
	2480	-9.00	≤ 8	PASS

Test Graphs


BLE 125K_Ant1_2402




BLE 125K_Ant1_2440



BLE 125K_Ant1_2480




BLE_1M_Ant1_2402




Date: 9 DEC 2021 12:57:23

BLE_1M_Ant1_2440




Date: 9 DEC 2021 13:06:25

BLE_1M_Ant1_2480




Date: 9 DEC 2021 13:07:46

BLE_2M_Ant1_2402




Date: 9 DEC 2021 13:09:33

BLE_2M_Ant1_2440




Date: 9 DEC 2021 13:10:55

BLE_2M_Ant1_2480




Date: 9 DEC 2021 13:12:05

BLE 500K_Ant1_2402




Date: 9 DEC 2021 13:31:16

BLE 500K_Ant1_2440



Date: 9 DEC 2021 13:33:32

BLE 500K_Ant1_2480



Date: 9 DEC 2021 13:34:29

9.5 Spurious RF conducted emissions

Test Method

1. Establish a reference level by using the following procedure:
 - a. Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
 - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
 - a. Set the center frequency and span to encompass frequency range to be measured.
 - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

Limit

Frequency Range MHz	Limit (dBc)
30-26500	-20

TestMode	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE_125K	2402	Reference	6.04	6.04	---	PASS
		30~1000	6.04	-64.64	<=-13.96	PASS
		1000~5000	6.04	-62.87	<=-13.96	PASS
		5000~26500	6.04	-53.36	<=-13.96	PASS
	2440	Reference	6.11	6.11	---	PASS
		30~1000	6.11	-65.11	<=-13.89	PASS
		1000~5000	6.11	-62.28	<=-13.89	PASS
		5000~26500	6.11	-50.54	<=-13.89	PASS
	2480	Reference	6.05	6.05	---	PASS
		30~1000	6.05	-65.26	<=-13.95	PASS
		1000~5000	6.05	-61.30	<=-13.95	PASS
		5000~26500	6.05	-51.67	<=-13.95	PASS
BLE_1M	2402	Reference	8.25	8.25	---	PASS
		30~1000	8.25	-67.23	<=-11.75	PASS
		1000~5000	8.25	-64.45	<=-11.75	PASS
		5000~26500	8.25	-54.07	<=-11.75	PASS
	2440	Reference	8.10	8.10	---	PASS
		30~1000	8.10	-64.47	<=-11.90	PASS
		1000~5000	8.10	-48.81	<=-11.90	PASS
		5000~26500	8.10	-67.76	<=-11.90	PASS
	2480	Reference	8.34	8.34	---	PASS
		30~1000	8.34	-67.76	<=-11.66	PASS
		1000~5000	8.34	-61.41	<=-11.66	PASS
		5000~26500	8.34	-52.71	<=-11.66	PASS
BLE_2M	2402	Reference	6.39	6.39	---	PASS
		30~1000	6.39	-65.43	<=-13.61	PASS
		1000~5000	6.39	-62.08	<=-13.61	PASS
		5000~26500	6.39	-53.46	<=-13.61	PASS
	2440	Reference	5.69	5.69	---	PASS
		30~1000	5.69	-64.12	<=-14.31	PASS
		1000~5000	5.69	-61.85	<=-14.31	PASS
		5000~26500	5.69	-49.55	<=-14.31	PASS
	2480	Reference	6.38	6.38	---	PASS
		30~1000	6.38	-65.01	<=-13.62	PASS
		1000~5000	6.38	-62.1	<=-13.62	PASS
		5000~26500	6.38	-53.67	<=-13.62	PASS
BLE_500K	2402	Reference	7.97	7.97	---	PASS
		30~1000	7.97	-66.6	<=-12.03	PASS
		1000~5000	7.97	-64.37	<=-12.03	PASS
		5000~26500	7.97	-55.43	<=-12.03	PASS
	2440	Reference	8.73	8.73	---	PASS
		30~1000	8.73	-68.17	<=-11.27	PASS
		1000~5000	8.73	-63.83	<=-11.27	PASS
		5000~26500	8.73	-48.27	<=-11.27	PASS
	2480	Reference	8.48	8.48	---	PASS
		30~1000	8.48	-67.43	<=-11.52	PASS
		1000~5000	8.48	-62.48	<=-11.52	PASS
		5000~26500	8.48	-53.23	<=-11.52	PASS


Test Graphs

BLE 125K_Ant1_2402_0~Reference




Date: 9 DEC 2021 13:39:32

BLE 125K_Ant1_2402_30~1000



Date: 9 DEC 2021 13:39:35


BLE 125K_Ant1_2402_1000~5000




Date: 9 DEC 2021 13:39:37

Note: The emission which exceed the limit is the fundamental.


BLE_125K_Ant1_2402_5000~26500




BLE_125K_Ant1_2440_0~Reference



BLE_125K_Ant1_2440_30~1000




BLE_125K_Ant1_2440_1000~5000



Date: 9 DEC 2021 13:40:39


Note: The emission which exceed the limit is the fundamental.

BLE_125K_Ant1_2440_5000~26500




Date: 9 DEC 2021 13:40:48

BLE_125K_Ant1_2480_0~Reference




Date: 9 DEC 2021 13:41:42

BLE 125K Ant1 2480 30~1000



Date: 9 DEC 2021 13:41:44


BLE 125K Ant1 2480 1000~5000



Date: 9 DEC 2021 13:41:47


Note: The emission which exceed the limit is the fundamental.

BLE 125K Ant1 2480 5000~26500




Date: 9 DEC 2021 13:41:56

BLE_1M_Ant1_2402_0~Reference




Date: 9 DEC.2021 12:57:34

BLE_1M_Ant1_2402_30~1000



Date: 9 DEC.2021 12:57:36


BLE_1M_Ant1_2402_1000~5000



Date: 9 DEC.2021 12:57:39


Note: The emission which exceed the limit is the fundamental.

BLE 1M Ant1 2402 5000~26500




Date: 9 DEC 2021 12:57:48

BLE 1M Ant1 2440 0~Reference




Date: 9 DEC 2021 13:06:29

BLE 1M Ant1 2440 30~1000



Date: 9 DEC 2021 13:06:31


BLE 1M Ant1 2440 1000~5000



Date: 9 DEC 2021 13:06:34


Note: The emission which exceed the limit is the fundamental.

BLE 1M Ant1 2440 5000~26500




Date: 9 DEC 2021 13:06:43

BLE 1M Ant1 2480 0~Reference




Date: 9 DEC 2021 13:07:59

BLE 1M Ant1 2480 30~1000



Date: 9 DEC 2021 13:08:01


BLE 1M Ant1 2480 1000~5000



Date: 9 DEC 2021 13:08:04


Note: The emission which exceed the limit is the fundamental.

BLE 1M Ant1 2480 5000~26500




Date: 9 DEC 2021 13:08:13

BLE_2M_Ant1_2402_0~Reference




Date: 9 DEC.2021 13:09:45

BLE_2M_Ant1_2402_30~1000



Date: 9 DEC.2021 13:09:47


BLE_2M_Ant1_2402_1000~5000



Date: 9 DEC.2021 13:09:50


Note: The emission which exceed the limit is the fundamental.

BLE 2M Ant1 2402 5000~26500




Date: 9 DEC 2021 13:09:59

BLE 2M Ant1 2440 0~Reference




Date: 9 DEC 2021 13:11:00

BLE 2M Ant1 2440 30~1000



Date: 9 DEC 2021 13:11:02


BLE 2M Ant1 2440 1000~5000



Date: 9 DEC 2021 13:11:05


Note: The emission which exceed the limit is the fundamental.

BLE 2M Ant1 2440 5000~26500




Date: 9 DEC 2021 13:11:14

BLE 2M Ant1 2480 0~Reference




Date: 9 DEC 2021 13:12:18

BLE 2M Ant1 2480 30~1000



Date: 9 DEC 2021 13:12:21


BLE 2M Ant1 2480 1000~5000



Date: 9 DEC 2021 13:12:23


Note: The emission which exceed the limit is the fundamental.

BLE 2M Ant1 2480 5000~26500




Date: 9 DEC 2021 13:12:32

BLE_500K_Ant1_2402_0~Reference




Date: 9 DEC.2021 13:31:27

BLE_500K_Ant1_2402_30~1000



Date: 9 DEC.2021 13:31:29


BLE_500K_Ant1_2402_1000~5000



Date: 9 DEC.2021 13:31:32


Note: The emission which exceed the limit is the fundamental.

BLE_500K_Ant1_2402_5000~26500




Date: 9 DEC 2021 13:31:41

BLE_500K_Ant1_2440_0~Reference




Date: 9 DEC 2021 13:33:36

BLE_500K_Ant1_2440_30~1000



Date: 9 DEC 2021 13:33:36


BLE_500K_Ant1_2440_1000~5000



Date: 9 DEC 2021 13:33:41


Note: The emission which exceed the limit is the fundamental.

BLE_500K_Ant1_2440_5000~26500




Date: 9 DEC 2021 13:33:50

BLE_500K_Ant1_2480_0~Reference




Date: 9 DEC 2021 13:34:41

BLE 500K Ant1 2480 30~1000



Date: 9 DEC 2021 13:34:43


BLE 500K Ant1 2480 1000~5000



Date: 9 DEC 2021 13:34:45

Note: The emission which exceed the limit is the fundamental.

BLE 500K Ant1 2480 5000~26500



Date: 9 DEC 2021 13:34:54

9.6 Band edge

Test Method

- 1 Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.


Limit


According to §15.247(d) and RSS-247 5.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.

Test result

TestMode	ChName	Channel	Result[dBm]	Limit (dBc)	Verdict
BLE_125K	Low	2402	-50.80	-20	PASS
	High	2480	-56.28	-20	PASS
BLE_1M	Low	2402	-52.82	-20	PASS
	High	2480	-58.39	-20	PASS
BLE_2M	Low	2402	-31.56	-20	PASS
	High	2480	-53.17	-20	PASS
BLE_500K	Low	2402	-53.50	-20	PASS
	High	2480	-57.49	-20	PASS


Test Graphs








China






China






China





China



9.7 Spurious radiated emissions for transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) $VBW \geq [3 \times RBW]$.
- c) Detector = RMS (power averaging), if $[\text{span} / (\# \text{ of points in sweep})] \leq RBW / 2$.
 Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of $1 / D$, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
 1) If power averaging (rms) mode was used in the preceding step e), then the correction

factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10 must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBuV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Model: 9290031345 Transmitting spurious emission test result as below:

Test mode: GFSK (125 kbit/s)
Channel (2402MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2389.8	41.26	74.0	32.74	Peak	Horizontal
7205.3	46.25	74.0	27.75	Peak	Horizontal
2382.8	42.17	74.0	31.83	Peak	Vertical
7205.3	50.13	74.0	23.87	Peak	Vertical
7205.3	45.26	54.0	8.74	AV	Vertical

Test mode: GFSK (125 kbit/s)
Channel (2440MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
7319.8	49.27	74.0	24.73	Peak	Horizontal
7319.8	49.63	74.0	24.37	Peak	Vertical

Test mode: GFSK (125 kbit/s)
Channel (2480MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2483.5	45.21	74.0	28.79	Peak	Horizontal
7440.7	48.12	74.0	25.88	Peak	Horizontal
2483.5	47.74	74.0	26.26	Peak	Vertical
7439.6	49.35	74.0	24.65	Peak	Vertical

Test mode: GFSK (500 kbit/s)**Channel (2402MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2389.7	41.75	74.0	32.25	Peak	Horizontal
7205.5	46.27	74.0	27.73	Peak	Horizontal
2382.8	43.15	74.0	30.85	Peak	Vertical
7205.4	49.64	74.0	24.36	Peak	Vertical

Test mode: GFSK (500 kbit/s)**Channel (2440MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
7319.7	47.62	74.0	26.38	Peak	Horizontal
7319.7	53.28	74.0	20.72	Peak	Vertical
7319.7	49.16	54.0	4.84	AV	Vertical

Test mode: GFSK (500 kbit/s)**Channel (2480MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2483.5	46.26	74.0	27.74	Peak	Horizontal
7440.4	50.26	74.0	23.74	Peak	Horizontal
7440.4	45.12	54.0	8.88	AV	Horizontal
2483.5	48.15	74.0	25.85	Peak	Vertical
7439.4	49.75	74.0	24.25	Peak	Vertical



Test mode: GFSK (1 Mbit/s)
Channel (2402MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2389.8	42.46	74.0	31.54	Peak	Horizontal
7205.5	48.05	74.0	25.95	Peak	Horizontal
2382.8	44.53	74.0	29.47	Peak	Vertical
7205.8	51.37	74.0	22.63	Peak	Vertical
7205.8	46.75	54.0	7.25	AV	Vertical

Test mode: GFSK (1 Mbit/s)
Channel (2440MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
7319.8	48.65	74.0	25.35	Peak	Horizontal
7319.8	54.85	74.0	19.15	Peak	Vertical
7319.8	51.64	54.0	2.36	AV	Vertical

Test mode: GFSK (1 Mbit/s)
Channel (2480MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2483.5	47.75	74.0	26.25	Peak	Horizontal
7440.5	50.89	74.0	23.11	Peak	Horizontal
7440.5	46.27	54.0	7.73	AV	Horizontal
2483.5	50.62	74.0	23.38	Peak	Vertical
2483.5	42.15	54.0	11.85	AV	Vertical
7439.8	54.39	74.0	19.61	Peak	Vertical
7439.8	50.43	54.0	3.57	AV	Vertical

Test mode: GFSK (2 Mbit/s)
Channel (2402MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2389.6	42.73	74.0	31.27	Peak	Horizontal
7205.6	48.19	74.0	25.81	Peak	Horizontal
2382.6	44.39	74.0	29.61	Peak	Vertical
7205.5	51.49	74.0	22.51	Peak	Vertical
7205.5	46.82	54.0	7.18	AV	Vertical

Test mode: GFSK (2 Mbit/s)
Channel (2440MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
7319.4	49.88	74.0	24.12	Peak	Horizontal
7319.4	55.06	74.0	18.94	Peak	Vertical
7319.4	51.87	54.0	2.13	AV	Vertical

Test mode: GFSK (2 Mbit/s)
Channel (2480MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2483.5	47.93	74.0	26.07	Peak	Horizontal
7440.7	51.23	74.0	22.77	Peak	Horizontal
7440.7	46.71	54.0	7.29	AV	Horizontal
2483.5	50.85	74.0	23.15	Peak	Vertical
2483.5	42.53	54.0	11.47	AV	Vertical
7439.6	54.92	74.0	19.08	Peak	Vertical
7439.6	51.26	54.0	2.74	AV	Vertical

Model: 9290031347 Transmitting spurious emission test result as below:**Test mode: GFSK (125 kbit/s)****Channel (2402MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2389.9	40.82	74.0	33.18	Peak	Horizontal
7205.9	45.19	74.0	28.81	Peak	Horizontal
2382.9	43.69	74.0	30.31	Peak	Vertical
7205.8	51.21	74.0	22.79	Peak	Vertical
7205.8	47.82	54.0	6.18	AV	Vertical

Test mode: GFSK (125 kbit/s)**Channel (2440MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
7319.8	48.12	74.0	25.88	Peak	Horizontal
7319.8	49.68	74.0	24.32	Peak	Vertical

Test mode: GFSK (125 kbit/s)**Channel (2480MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2483.5	46.94	74.0	27.06	Peak	Horizontal
7440.7	48.51	74.0	25.49	Peak	Horizontal
2483.5	48.17	74.0	25.83	Peak	Vertical
7439.6	49.93	74.0	24.07	Peak	Vertical

Test mode: GFSK (500 kbit/s)**Channel (2402MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2389.7	40.89	74.0	33.11	Peak	Horizontal
7205.9	47.20	74.0	26.8	Peak	Horizontal
2382.8	44.28	74.0	29.72	Peak	Vertical
7205.9	48.25	74.0	25.75	Peak	Vertical

Test mode: GFSK (500 kbit/s)**Channel (2440MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
7319.8	48.57	74.0	25.43	Peak	Horizontal
7319.8	49.92	74.0	24.08	Peak	Vertical

Test mode: GFSK (500 kbit/s)**Channel (2480MHz)**

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2483.5	45.19	74.0	28.81	Peak	Horizontal
7440.1	50.32	74.0	23.68	Peak	Horizontal
7440.1	46.63	54.0	7.37	AV	Horizontal
2483.5	47.45	74.0	26.55	Peak	Vertical
7439.2	48.89	74.0	25.11	Peak	Vertical

Test mode: GFSK (1 Mbit/s)
Channel (2402MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2389.9	43.17	74.0	30.83	Peak	Horizontal
7205.5	48.51	74.0	25.49	Peak	Horizontal
2382.8	45.18	74.0	28.82	Peak	Vertical
7205.8	50.92	74.0	23.08	Peak	Vertical
7205.8	46.53	54.0	7.47	AV	Vertical

Test mode: GFSK (1 Mbit/s)
Channel (2440MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
7319.8	47.29	74.0	26.71	Peak	Horizontal
7319.8	54.26	74.0	19.74	Peak	Vertical
7319.8	50.81	54.0	3.19	AV	Vertical

Test mode: GFSK (1 Mbit/s)
Channel (2480MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2483.5	48.16	74.0	25.84	Peak	Horizontal
7440.2	50.92	74.0	23.08	Peak	Horizontal
7440.2	46.51	54.0	7.49	AV	Horizontal
2483.5	50.79	74.0	23.21	Peak	Vertical
2483.5	43.42	54.0	10.58	AV	Vertical
7439.9	54.82	74.0	19.18	Peak	Vertical
7439.9	51.65	54.0	2.35	AV	Vertical

Test mode: GFSK (2 Mbit/s)
Channel (2402MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2389.8	42.18	74.0	31.82	Peak	Horizontal
7205.9	48.57	74.0	25.43	Peak	Horizontal
2382.8	43.45	74.0	30.55	Peak	Vertical
7205.8	50.84	74.0	23.16	Peak	Vertical
7205.8	46.25	54.0	7.75	AV	Vertical

Test mode: GFSK (2 Mbit/s)
Channel (2440MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
7319.8	48.73	74.0	5.16	Peak	Horizontal
7319.8	53.03	74.0	5.16	Peak	Vertical
7319.8	48.84	54.0	5.16	AV	Vertical

Test mode: GFSK (2 Mbit/s)
Channel (2480MHz)

Frequency	Mmission Level	Limit	Margin	Detector	Polarization
MHz	dBuV/m	dBuV/m	dB		
2483.5	48.24	74.0	25.76	Peak	Horizontal
7440.9	50.81	74.0	23.19	Peak	Horizontal
7440.9	47.26	54.0	6.74	AV	Horizontal
2483.5	50.72	74.0	23.28	Peak	Vertical
2483.5	41.03	54.0	12.97	AV	Vertical
7439.8	54.07	74.0	19.93	Peak	Vertical
7439.8	51.89	54.0	2.11	Peak	Vertical


Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading

The worst case of Radiated Emission below 1GHz:

Site: 3 meter chamber	Time: 2022/01/06 - 15:54
Limit: FCC Part15.209 and RSS-GEN 8.8_RE(3m)	Engineer: Chengjie Guo
Probe: VULB9168	Polarity: Horizontal
EUT: LED light, Model no: 9290031345	Power: AC 120V, 60Hz
Note: Transmit by at channel 2440MHz BLE_1Mbit/s.	

RE_VULB9168_pre_Cont_30-1000




Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
36.920000	20.1	1000.0	120.000	100.0	H	142.0	19.8	19.9	40.0
57.880000	21.8	1000.0	120.000	150.0	H	237.0	20.3	18.3	40.0
115.400000	30.9	1000.0	120.000	200.0	H	352.0	17.7	12.6	43.5
133.600000	24.9	1000.0	120.000	150.0	H	129.0	19.7	18.6	43.5
239.280000	21.0	1000.0	120.000	100.0	H	81.0	19.5	25.0	46.0
294.920000	23.5	1000.0	120.000	150.0	H	216.0	21.3	22.5	46.0

Site: 3 meter chamber	Time: 2022/01/06 - 16:02
Limit: FCC Part15.209 and RSS-GEN 8.8_RE(3m)	Engineer: Chengjie Guo
Probe: VULB9168	Polarity: Vertical
EUT: LED light, Model no: 9290031345	Power: AC 120V, 60Hz
Note: Transmit by at channel 2440MHz BLE_1Mbit/s.	

RE_VULB9168_pre_Cont_30-1000




Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
31.600000	30.5	1000.0	120.000	100.0	V	286.0	19.4	9.5	40.0
37.560000	28.5	1000.0	120.000	100.0	V	152.0	19.7	11.5	40.0
53.120000	24.9	1000.0	120.000	150.0	V	142.0	20.4	15.1	40.0
115.560000	33.7	1000.0	120.000	100.0	V	16.0	17.8	9.8	43.5
165.960000	21.8	1000.0	120.000	100.0	V	229.0	20.5	21.7	43.5
276.520000	22.6	1000.0	120.000	100.0	V	347.0	20.8	23.4	46.0

Site: 3 meter chamber	Time: 2022/01/06 - 16:07
Limit: FCC Part15.209 and RSS-GEN 8.8 RE(3m)	Engineer: Chengjie Guo
Probe: VULB9168	Polarity: Horizontal
EUT: LED light, Model no: 9290031347	Power: AC 120V, 60Hz
Note: Transmit by at channel 2440MHz BLE_1Mbit/s.	

RE_VULB9168_pre_Cont_30-1000




Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
50.960000	19.4	1000.0	120.000	100.0	H	321.0	20.6	20.6	40.0
114.000000	28.3	1000.0	120.000	150.0	H	347.0	17.6	15.2	43.5
123.800000	32.6	1000.0	120.000	100.0	H	11.0	18.4	10.9	43.5
130.400000	34.1	1000.0	120.000	150.0	H	154.0	19.3	9.4	43.5
166.920000	20.6	1000.0	120.000	150.0	H	53.0	20.5	22.9	43.5
327.320000	21.4	1000.0	120.000	150.0	H	164.0	22.5	24.6	46.0

Site: 3 meter chamber	Time: 2022/01/06 - 16:14
Limit: FCC Part15.209 and RSS-GEN 8.8_RE(3m)	Engineer: Chengjie Guo
Probe: VULB9168	Polarity: Vertical
EUT: LED light, Model no: 9290031347	Power: AC 120V, 60Hz
Note: Transmit by at channel 2440MHz BLE_1Mbit/s.	

RE_VULB9168_pre_Cont_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
31.760000	28.3	1000.0	120.000	100.0	V	292.0	19.4	11.7	40.0
36.360000	28.0	1000.0	120.000	100.0	V	260.0	19.7	12.0	40.0
51.000000	25.2	1000.0	120.000	200.0	V	227.0	20.6	14.8	40.0
114.840000	27.7	1000.0	120.000	100.0	V	199.0	17.7	15.8	43.5
131.560000	28.1	1000.0	120.000	200.0	V	170.0	19.4	15.4	43.5
308.240000	22.8	1000.0	120.000	100.0	V	11.0	21.7	23.2	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 26.5GHz), therefore no data appear in the report.

10 Test Equipment List

List of Test Instruments

Test Site1

TEST ITEM	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2021-8-2	2022-8-1
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2021-8-2	2022-8-1
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2021-8-2	2022-8-1
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2019-3-16	2022-3-15
	Horn Antenna	Rohde & Schwarz	HF907	102393	2021-3-15	2022-3-14
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2021-8-2	2022-8-1
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2021-5-21	2022-5-20
	DOUBLE-RIDGED WAVEGUIDE HORN WITH PRE-AMPLIFIER (18 GHZ - 40 GHZ)	ETS-Lindgren	3116C-PA	002222727	2020-9-23	2023-9-22
	3m Semi-anechoic chamber	TDK	9X6X6	----	2021-5-8	2024-5-7
	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2021-8-2	2022-8-1
	LISN	Rohde & Schwarz	ENV216	101924	2021-8-2	2022-8-1

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	Bluetooth and WiFi Test System	Shenzhen JS tonscent co.,ltd	2.6.77.0518
RE	EMC 32	Rohde & Schwarz	V9.15.00
CE	EMC 32	Rohde & Schwarz	V9.15.03

C - Conducted RF tests

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density*
- Spurious RF conducted emissions
- Band edge

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, $\pm 3.16\text{dB}$
Radiated Disturbance	30MHz to 1GHz, $\pm 5.03\text{dB}$ (Horizontal) $\pm 5.12\text{dB}$ (Vertical) 1GHz to 18GHz, $\pm 5.49\text{dB}$ 18GHz to 40GHz, $\pm 5.63\text{dB}$
Carrier power conducted measurement	50MHz~18GHz, $\pm 1.238\text{dB}$
Spurious Emission Conducted Measurement	9kHz ~40GHz, $\pm 1.224\text{dB}$



12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

THE END