



SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

588 West Jindu Road, Songjiang District, Shanghai, China
Telephone: +86 (0) 21 6191 5666
Fax: +86 (0) 21 6191 5678
ee.shanghai@sgs.com

Report No.: SHEM151100413802
Page: 1 of 75

1 Cover Page

RF TEST REPORT

Application No.:	SHEM1511004138CR
Applicant:	Camec Pty Ltd
FCC ID:	2AGDW0006V1
Equipment Under Test (EUT): NOTE: The following sample(s) was/were submitted and identified by the client as	
Product Name:	BLUETOOTH SPEAKER
Model No.(EUT):	RVM1000(043438)
Add Model No.:	RVM1001(043439)
Standards:	FCC PART 15 Subpart C: 2014
Date of Receipt:	November 11, 2015
Date of Test:	November 20, 2015 to November 21, 2015
Date of Issue:	December 04, 2015
Test Result:	Pass*

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.



The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.


The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.



2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00	/	December 04, 2015	/	Original

Authorized for issue by:				
Engineer		Eddy Zong _____ Print Name		 _____
Clerk		Susie Liu _____ Print Name		 _____
Reviewer		Keny Xu _____ Print Name		 _____

3 Test Summary

Test Item	FCC Requirement	Test method	Result
Antenna Requirement	FCC Part 15, Subpart C Section 15.203/15.247 (c)	---	PASS
AC Power Line Conducted Emission	FCC Part 15, Subpart C Section 15.207	ANSI C63.10 (2013) Section 6.2	PASS
20dB Occupied Bandwidth	FCC Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013) Section 6.9.2	PASS
Conducted Peak Output Power	FCC Part 15, Subpart C Section 15.247 (b)(1)	ANSI C63.10 (2013) Section 7.8.5	PASS
Carrier Frequencies Separation	FCC Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013) Section 7.8.2	PASS
Hopping Channel Number	FCC Part 15, Subpart C Section 15.247 (b)	ANSI C63.10 (2013) Section 7.8.3	PASS
Dwell Time	FCC Part 15, Subpart C Section 15.247 (a)(1)	ANSI C63.10 (2013) Section 7.8.4	PASS
Conducted Spurious Emissions and Band-edge	FCC Part 15, Subpart C Section 15.247(d)	ANSI C63.10 (2013) Section 7.8.6&7.8.8	PASS
Radiated Spurious Emissions and Band-edge	FCC Part 15, Subpart C Section 15.209&15.205	ANSI C63.10 (2013) Section 6.4&6.5&6.6&6.10	PASS

4 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENTS.....	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.1 GENERAL DESCRIPTION OF E.U.T.....	5
5.2 TECHNICAL SPECIFICATIONS.....	5
5.3 DESCRIPTION OF SUPPORT UNITS.....	5
5.4 TEST MODE.....	6
5.5 TEST LOCATION	6
5.6 TEST FACILITY	7
5.7 MEASUREMENT UNCERTAINTY	7
6 EQUIPMENTS USED DURING TEST	8
7 TEST RESULTS	9
7.1 E.U.T. TEST CONDITIONS	9
7.2 FREQUENCY HOPPING SYSTEM REQUIREMENT	10
7.3 ANTENNA REQUIREMENT.....	12
7.4 CONDUCTED EMISSIONS ON MAINS TERMINALS	13
7.5 20dB OCCUPIED BANDWIDTH.....	16
7.6 CONDUCTED PEAK OUTPUT POWER	22
7.7 CARRIER FREQUENCIES SEPARATED	28
7.8 HOPPING CHANNEL NUMBER	31
7.9 DWELL TIME	35
7.10 CONDUCTED SPURIOUS EMISSIONS AND BAND-EDGE	45
7.10.1 Conducted spurious emission.....	46
7.10.2 Conducted Band-edge	55
7.11 RADIATED SPURIOUS EMISSIONS AND BAND-EDGE	61
7.11.1 Radiated Spurious Emissions.....	64
7.11.2 Radiated Band edge	68
8 TEST SETUP PHOTOGRAPHS.....	75
9 EUT CONSTRUCTIONAL DETAILS.....	75

5 General Information

5.1 Client Information

Applicant:	Camec Pty Ltd
Address of Applicant:	47-63 Remington Drive Dandenong South, Victoria. 3175. Australia
Manufacturer:	NINGBO CODE LIGHTING TECHNOLOGY CO., LTD
Address of Manufacturer:	Building #3, No.181-197, Shanshan Road, Wangchun Industrial Zone, Yinzhou District, Ningbo, China
Factory:	NINGBO CODE LIGHTING TECHNOLOGY CO., LTD
Address of Factory:	Building #3, No.181-197, Shanshan Road, Wangchun Industrial Zone, Yinzhou District, Ningbo, China

5.1 General Description of E.U.T.

Product Description:	Fixed product with BT function
Brand Name:	RV Media
Rate Voltage:	DC 12V

5.2 Technical Specifications

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	4.0 Dual mode
Modulation Technique:	FHSS (GFSK, $\pi/4$ DQPSK, 8DPSK)
Number of Channel:	79
Antenna Type:	PIFA Antenna
Antenna Gain:	0 dBi

5.3 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Supplied by
Laptop	Lenovo	ThinkPad X100e	SGS
BT test board	/	/	SGS
Adapter	Acepower	BSW0127-1210002W	SGS

Adapter:	Rated Input:	AC 100V-240V 50/60Hz 500mA	
	Rated Output:	DC 12V 1A	
	Cable length:	AC port:	2 wires
		DC port:	150 cm

Software name	Manufacturer	Version	Supplied By
Blue Test3 (For CSR)	/	2.5.0	SGS

5.4 Test Mode

Test Mode	Description of Test Mode
Hopping disabled mode	Using test software to control EUT working in continuous transmitting, and select channel and modulation type.
Hopping enabled mode	Using test software to control EUT working in continuous transmitting, and hopping on status.

The packet type used for the final test:

Test Item	Packet Type									Hopping Status	
	DH1	DH3	DH5	2DH1	2DH3	2DH5	3DH1	3DH3	3DH5	Disabled	Enabled
CE	-	-	√	-	-	√	-	-	√	√	√
20dB OBW	-	-	√	-	-	√	-	-	√	√	-
Peak Power	-	-	√	-	-	√	-	-	√	√	-
CFS	-	-	√	-	-	√	-	-	√	-	√
HCN	-	-	√	-	-	√	-	-	√	-	√
Dwell Time	√	√	√	√	√	√	√	√	√	-	√
CSE	-	-	√	-	-	√	-	-	√	√	-
Conducted Band-edge	-	-	√	-	-	√	-	-	√	√	√
RSE & Band-edge	-	-	√	-	-	√	-	-	√	√	-

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

No.588 West Jindu Road, Songjiang District, Shanghai, China.201612.

Tel: +86 21 6191 5666

Fax: +86 21 6191 5678

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing. Date of expiry: 2017-07-14.

- **FCC – Registration No.: 402683**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered and fully described in a report filed with the Federal Communications Commission (FCC). The acceptance letter from the FCC is maintained in our files. Registration No.: 402683, Expiry Date: 2017-09-16.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1. Expiry Date: 2017-06-18.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868, C-4336, T-2221, G-830 respectively. Date of Expiry: 2017-11-16.

5.7 Measurement Uncertainty

No.	Parameter	Measurement Uncertainty
1	Radio Frequency	$< \pm 1 \times 10^{-5}$
2	Total RF power, conducted	$< \pm 1.5 \text{ dB}$
3	RF power density, conducted	$< \pm 3 \text{ dB}$
4	Spurious emissions, conducted	$< \pm 3 \text{ dB}$
5	All emissions, radiated	$< \pm 6 \text{ dB}$ (Below 1GHz) $< \pm 6 \text{ dB}$ (Above 1GHz)
6	Temperature	$< \pm 1^{\circ}\text{C}$
7	Humidity	$< \pm 5 \%$
8	DC and low frequency voltages	$< \pm 3 \%$

6 Equipments Used during Test

Item	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due date
1	Power meter	Rohde & Schwarz	NRP	101641	2015-01-22	2016-01-21
2	Power Sensor	Rohde & Schwarz	NRP-Z22	101096	2015-08-06	2016-08-05
3	Spectrum Analyzer	Rohde & Schwarz	FSP-30	2705121009	2015-01-22	2016-01-21
4	EMI test receiver	Rohde & Schwarz	ESU40	100109	2015-02-13	2016-02-12
5	Active Loop Antenna (9kHz to 30MHz)	Rohde & Schwarz	FMZB1519	1519-034	2015-02-07	2016-02-06
6	Broadband UHF-VHF ANTENNA (25MHz to 2GHz)	SCHWARZBECK	VULB9168	9168-313	2015-02-07	2016-02-06
7	Ultra broadband antenna (25MHz to 3GHz)	Rohde & Schwarz	HL562	100227	2015-08-30	2016-08-29
8	Horn Antenna (1GHz to 18GHz)	Rohde & Schwarz	HF906	100284	2015-02-07	2016-02-06
9	Horn Antenna (1GHz to 18GHz)	SCHWARZBECK	BBHA9120D	9120D-679	2015-02-07	2016-02-06
10	Horn Antenna (14GHz to 40GHz)	SCHWARZBECK	BBHA 9170	BBHA917-0373	2015-02-13	2016-02-12
11	Pre-amplifier (9KHz – 2GHz)	LNA6900	TESEQ	71033	2014-12-27	2015-12-26
12	Pre-amplifier (1GHz – 26.5GHz)	SCHWARZBECK	SCU-F0118- G40-BZ4- CSS(F)	10001	2015-01-22	2016-01-21
13	Pre-amplifier (14GHz – 40GHz)	SCHWARZBECK	SCU-F1840- G35-BZ3- CSS(F)	10001	2015-01-22	2016-01-21
14	Tunable Notch Filter	Wainwright instruments GmbH	WRCT800.0/880 .0-0.2/40-5SSK	170397 169777 169780 192507	/	/
15	High pass Filter	FSCW	HP 12/2800- 5AA2	19A45-02	/	/
16	High-low temperature cabinet	Suzhou Zhihe	TL-40	50110050	2015-09-11	2016-09-10
17	AC power stabilizer	WOCEN	6100	51122	2015-01-02	2016-01-01
18	DC power	QJE	QJ30003SII	3573/4/3	2015-01-02	2016-01-01
19	Signal Generator (Interferer)	Rohde & Schwarz	SMR40	100555	2015-08-13	2016-08-12
20	Signal Generator (Blocker)	Rohde & Schwarz	SMJ100A	101394	2015-01-22	2016-01-21
21	Splitter	Anritsu	MA1612A	M12265	/	/
22	Coupler	e-meca	803-S-1	900-M01	/	/

7 Test Results

7.1 E.U.T. test conditions

Requirements: 15.31(e) For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

Operating Environment:

Temperature:	20.0 -25.0 °C
Humidity:	35-75 % RH
Atmospheric Pressure:	99.2 -102 kPa

Test frequencies: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Pursuant to Part 15.31(c) For swept frequency equipment, measurements shall be made with the frequency sweep stopped at those frequencies chosen for the measurements to be reported.

Test frequency is the lowest channel: 0 channel (2402MHz), middle channel: 39 channel (2441MHz) and highest channel: 78 channel (2480MHz) with fixed at channel.

7.2 Frequency Hopping System Requirement

Test Requirement: Section 15.247 (a)(1), (g), (h) requirement:

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hop sets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)


According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONES; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinate with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

7.3 Antenna Requirement

Standard requirement:

15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited

15.247(b) (4) requirement:

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

EUT Antenna:

The BT antenna is integral antenna and no consideration of replacement. The gain of the antenna is less than 0 dBi.



7.4 Conducted Emissions on Mains Terminals

Frequency Range: 150 KHz to 30 MHz


Limit:

Frequency range MHz	Class B Limits: dB (μV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Note1: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50MHz.

Note2: The lower limit is applicable at the transition frequency.

Test Setup:



Test Procedure:


- 1) The mains terminal disturbance voltage was measured with the EUT in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN, which was bonded to the ground reference plane in the same way as the LISN for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance was between the closest points of the LISN and the EUT. The mains lead of EUT excess 0.8m was folded back and forth parallel to the lead so as to form a horizontal bundle with a length between 0.3m and 0.4m. All other units of the EUT and associated equipment were at least 0.8 m from the LISN.

Remark: Pre-scan was performed with peak detected on all ports, Quasi-peak & average measurements were performed at the frequencies at which maximum peak emission level were detected. Pretest under all modes; choose the worst case mode (GFSK and Hopping enabled mode) record on the report. Please see the attached Quasi-peak and Average test results.

Test Result: Pass

Test Data:


Test Mode: Hopping enabled mode	Test Port: AC Live Line
--	--------------------------------



Item	Freq.	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)	
1	0.175	25.79	0.29	9.86	35.94	54.72	-18.78	Average
2	0.175	34.68	0.29	9.86	44.83	64.72	-19.89	QP
3	0.449	30.94	0.25	9.86	41.05	46.89	-5.84	Average
4	0.449	35.15	0.25	9.86	45.26	56.89	-11.63	QP
5	0.576	18.47	0.24	9.86	28.57	46.00	-17.43	Average
6	0.576	27.04	0.24	9.86	37.14	56.00	-18.86	QP
7	0.830	21.58	0.20	9.86	31.64	46.00	-14.36	Average
8	0.830	28.45	0.20	9.86	38.51	56.00	-17.49	QP
9	1.216	19.03	0.22	9.87	29.12	46.00	-16.88	Average
10	1.216	28.40	0.22	9.87	38.49	56.00	-17.51	QP
11	3.328	21.34	0.38	9.88	31.60	46.00	-14.40	Average
12	3.328	31.35	0.38	9.88	41.61	56.00	-14.39	QP

Test Mode: Hopping enabled mode

Test Port: AC Neutral Line




Item	Freq.	Read Level	LISN Factor	Cable Loss	Level	Limit Line	Over Limit	Detector
(Mark)	(MHz)	(dBμV)	(dB)	(dB)	(dBμV)	(dBμV)	(dB)	
1	0.152	27.68	0.34	9.86	37.88	55.87	-17.99	Average
2	0.152	35.65	0.34	9.86	45.85	65.87	-20.02	QP
3	0.453	26.28	0.30	9.86	36.44	46.82	-10.38	Average
4	0.453	29.20	0.30	9.86	39.36	56.82	-17.46	QP
5	0.608	6.59	0.24	9.86	16.69	46.00	-29.31	Average
6	0.608	14.29	0.24	9.86	24.39	56.00	-31.61	QP
7	0.834	15.75	0.21	9.86	25.82	46.00	-20.18	Average
8	0.834	23.28	0.21	9.86	33.35	56.00	-22.65	QP
9	1.218	5.16	0.45	9.87	15.48	46.00	-30.52	Average
10	1.218	16.29	0.45	9.87	26.61	56.00	-29.39	QP
11	3.344	7.39	0.67	9.88	17.94	46.00	-28.06	Average
12	3.344	16.24	0.67	9.88	26.79	56.00	-29.21	QP

Remark: Level = Read Level + LISN/ISN Factor + Cable Loss.

7.5 20dB Occupied Bandwidth

Test Configuration:



Test Procedure:

- 1) Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
- 2) Set the spectrum analyzer: Span = approximately 2 to 5 times the OBW, centred on the hopping channel;
- 3) Set the spectrum analyzer: RBW $\geq$ 1% to 5% of the OBW (set 30 kHz). VBW $\geq$ RBW. Sweep = Auto; Detector = Peak. Trace = Max Hold.
- 4) Mark the peak frequency and -20dB points.


Test Date:

Test Mode	Test Frequency(MHz)	Bandwidth(MHz)
GFSK	2402	1.044
	2441	1.050
	2480	1.044
$\pi/4$ DQPSK	2402	1.170
	2441	1.116
	2480	1.116
8DPSK	2402	1.182
	2441	1.183
	2480	1.176

Test plot as follows:


Test mode: GFSK

Test channel: 2402




Test mode: GFSK

Test channel: 2441




Test mode: GFSK

Test channel: 2480




Test mode: $\pi/4$ DQPSK

Test channel: 2402




Test mode: $\pi/4$ DQPSK

Test channel: 2441




Test mode: $\pi/4$ DQPSK

Test channel: 2480




Test mode: 8DPSK

Test channel: 2402




Test mode: 8DPSK

Test channel: 2441




Test mode: 8DPSK

Test channel: 2480



7.6 Conducted Peak Output Power

Test Configuration:



Test Procedure:

- 1) Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2) Set the spectrum analyzer: RBW = 3 MHz, VBW = 3 MHz, Sweep = auto; Detector Function = Peak.
- 3) Keep the EUT in transmitting at lowest, middle and highest channel individually. Record the max value.

Test Limit:

Regulation 15.247 (b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts. Refer to the result "Hopping channel number" of this document. The 1 watt (30.0dBm) limit applies.

Test Data:


Test Mode	Test Frequency (MHz)	Reading Power (dBm)	Cable Loss (dB)	Output Power (dBm)	Limit (dBm)	Test Result
GFSK	2402	-0.60	0.5	-0.10	30	Pass
	2441	-0.39		0.11		Pass
	2480	-0.69		-0.19		Pass
π/4DQPSK	2402	-1.30		-0.8		Pass
	2441	0.35		0.85		Pass
	2480	0.28		0.78		Pass
8DPSK	2402	-2.01		-1.51		Pass
	2441	0.83		1.33		Pass
	2480	0.44		0.94		Pass

Remark: Output Power=Reading Power + Cable loss

Test plot as follows:


Test mode: GFSK

Test channel: 2402




Test mode: GFSK

Test channel: 2441




Test mode: GFSK

Test channel: 2480




Test mode: $\pi/4$ DQPSK

Test channel: 2402




Test mode: $\pi/4$ DQPSK

Test channel: 2441




Test mode: $\pi/4$ DQPSK

Test channel: 2480




Test mode: 8DPSK

Test channel: 2402




Test mode: 8DPSK

Test channel: 2441




Test mode: 8DPSK

Test channel: 2480



7.7 Carrier Frequencies Separated

Test Configuration:



Test Procedure:

- 1) Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2) Set the spectrum analyzer: RBW $\geq$ 1% of the span (set 30 kHz). VBW $\geq$ RBW, Span = 3MHz. Sweep = auto; Detector Function = Peak. Trace = Maxhold.
- 3) Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

Limit:

0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)

Test data:


Test Mode	Test Channel	Carrier Frequencies Separated (MHz)	Limit	Test Result
GFSK	Middle Channels (Channel 39 & 40)	1.005	700kHz	Pass
$\pi/4$ DQPSK	Middle Channels (Channel 39 & 40)	1.005	780kHz	Pass
8DPSK	Middle Channels (Channel 39 & 40)	0.999	788kHz	Pass

Remark: 1. According to the section 7.6, the conducted power measured is less than 125mW and 2/3 of 20dB bandwidth is used for limit.
2. 20dB bandwidth reference Section 7.5

Test plot as follows:


Test mode: GFSK

Test channel: Channel 39 & 40



Test mode: $\pi/4$ DQPSK


Test channel: Channel 39 & 40






Test mode: 8DPSK

Test channel: Channel 39 & 40



7.8 Hopping Channel Number

Test Configuration:



Test Procedure:

- 1) Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2) Set the spectrum analyzer: RBW = 100 kHz. VBW = 100 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
- 3) Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
- 4) Set the spectrum analyzer: start frequency = 2400MHz. stop frequency = 2483.5MHz. Submit the test result graph.

Limit:



At least 15 channels

Test Data:



Mode	Hopping channel numbers	Limit	Test Result
GFSK	79	≥15	Pass
π/4DQPSK	79		Pass
8DPSK	79		Pass

Test plot as follows:



Test mode: GFSK



Test mode: $\pi/4$ DQPSK




Test mode: 8DPSK



7.9 Dwell Time

Test Configuration:



Test Procedure:

- 1) Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum. Keep EUT in Hopping transmitting with all kind of modulation.
- 2) Set spectrum analyzer span = 0. centered on a hopping channel;
- 3) Use Emission width * No. of Hopping Channels in 31.6s to determine the dwell time.

Limit:

Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.



Test Data:

Test Mode	Test Frequency	Packet	Emission Width (ms)	Number of Hopping Channel in 31.6s	Average Occupancy Time (s)	Limit(s)	Test Result
GFSK	2441	DH1	0.39	320	0.12	0.4	Pass
		DH3	1.64	160	0.26		Pass
		DH5	2.87	110	0.32		Pass
π/4DQPSK		2DH1	0.39	320	0.12		Pass
		2DH3	1.65	160	0.26		Pass
		2DH5	1.69	160	0.27		Pass
8DPSK		3DH1	0.39	320	0.12		Pass
		3DH3	1.65	160	0.26		Pass
		3DH5	2.88	110	0.32		Pass

Test plot as follows:



Test mode:GFSK-DH1

Test channel:2441





Test mode:GFSK-DH3

Test channel:2441





Test mode:GFSK-DH5

Test channel:2441





Test mode: $\pi/4$ DQPSK -2DH1

Test channel:2441





Test mode: $\pi/4$ DQPSK -2DH3

Test channel:2441





Test mode: $\pi/4$ DQPSK -2DH5

Test channel:2441





Test mode: 8DPSK -3DH1

Test channel:2441





Test mode: 8DPSK -3DH3

Test channel:2441




Test mode: 8DPSK -3DH5

Test channel:2441



7.10 Conducted Spurious Emissions and Band-edge

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100KHz. VBW >= RBW. Sweep = auto; Detector Function = Peak (Max. hold).

Limit:

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Based on either an RF conducted or a radiated measurement. Provided the transmitter demonstrates compliance with the peak conducted power limits.

Test Result:


Pass

7.10.1 Conducted spurious emission


Test plot as follows:

Test mode: GFSK	Test channel: 2402
-----------------	--------------------

30MHz-3GHz:




3GHz-25GHz:




Test mode: GFSK

Test channel: 2441

30MHz-3GHz:




3GHz-25GHz:




Test mode: GFSK	Test channel: 2480
-----------------	--------------------

30MHz-3GHz:




3GHz-25GHz:




Test mode: $\pi/4$ DQPSK	Test channel: 2402
--------------------------	--------------------

30MHz-3GHz:




3GHz-25GHz:




Test mode: $\pi/4$ DQPSK

Test channel: 2441

30MHz-3GHz:




3GHz-25GHz:




Test mode: $\pi/4$ DQPSK

Test channel: 2480

30MHz-3GHz:




3GHz-25GHz:




Test mode: 8DPSK

Test channel: 2402

30MHz-3GHz:




3GHz-25GHz:




Test mode: 8DPSK

Test channel: 2441

30MHz-3GHz:




3GHz-25GHz:




Test mode: 8DPSK

Test channel: 2480

30MHz-3GHz:





3GHz-25GHz:



7.10.2 Conducted Band-edge



Test plot as follows:

Test mode: GFSK	Hopping enabled
-----------------	-----------------





Test mode: $\pi/4$ DQPSK

Hopping enabled




Test mode: 8DPSK


Hopping enabled




Test mode: GFSK	Test channel: Hopping disabled- 2402
-----------------	--------------------------------------




Test mode: GFSK	Test channel: Hopping disabled- 2480
-----------------	--------------------------------------



Test mode: $\pi/4$ DQPSK	Test channel: Hopping disabled- 2402
--------------------------	--------------------------------------




Test mode: $\pi/4$ DQPSK	Test channel: Hopping disabled- 2480
--------------------------	--------------------------------------




Test mode: 8DPSK

Test channel: Hopping disabled- 2402



Test mode: 8DPSK

Test channel: Hopping disabled- 2480



7.11 Radiated Spurious Emissions and Band-edge

Frequency Range: 9KHz to 25GHz

Test site/setup: Measurement Distance: 3m (Semi-Anechoic Chamber)

Test instrumentation set-up:

Frequency Range	Detector	RBW	VBW
0.009MHz-0.090MHz	Peak	10kHz	30kHz
0.009MHz-0.090MHz	Average	10kHz	30kHz
0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz
0.110MHz-0.490MHz	Peak	10kHz	30kHz
0.110MHz-0.490MHz	Average	10kHz	30kHz
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz
30MHz-1GHz	Quasi-peak	100kHz	300kHz
Above 1GHz	Peak	RBW=1MHz	VBW≥RBW
	Average		VBW=10Hz

Sweep=Auto

15.209 Limit:

Frequency	Limit (dBuV/m)
0.009MHz-0.490MHz	128.5 ~ 93.8
0.490MHz-1.705MHz	73.8 ~63.0
1.705MHz-30MHz	69.5
30MHz-88MHz	40.0
88MHz-216MHz	43.5
216MHz-960MHz	46.0
960MHz-1GHz	54.0
Above 1GHz	54.0

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

Test Configuration: Receive antenna scan height 1 m - 4 m. polarization Vertical / Horizontal




Figure1. Below 30MHz radiated emissions test configuration




Figure2. 30MHz to 1GHz radiated emissions test configuration




Figure3. Above 1GHz radiated emissions test configuration

Test Procedure:

The procedure used was ANSI Standard C63.10. The receiver was scanned from 9KHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

Low noise amplifier was used below 1GHz, High pass Filter was used above 3GHz.

Between 1G and 3GHz, we did not use any amplifier or filter.

Pre-test was performed on all modes, Compliance test was performed on worse case (GFSK mode).

Test were performed for their spatial orthogonal(X, Y, Z), the worst test data (X orthogonal) was submitted.

- 1) For this intentional radiator operates below 25 GHz. the spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 5rd harmonic.
- 2) As shown in Section, for frequencies above 1000MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.

Test Result:

Pass

7.11.1 Radiated Spurious Emissions

30MHz-1GHz:

lowest Channel

Item	Freq.	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector	Polarization
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
1	49.19	33.56	13.84	24.60	0.69	23.49	40.00	-16.51	QP	Horizontal
2	137.41	33.14	12.20	24.53	1.31	22.12	43.50	-21.38	QP	Horizontal
3	624.94	26.48	20.15	24.10	3.13	25.66	46.00	-20.34	QP	Horizontal
4	767.47	25.96	22.82	24.02	3.55	28.31	46.00	-17.69	QP	Horizontal
5	819.96	23.54	23.70	23.99	3.68	26.93	46.00	-19.07	QP	Horizontal
6	913.42	22.45	23.22	23.93	3.90	25.64	46.00	-20.36	QP	Horizontal
1	32.52	42.00	12.60	24.60	0.55	30.55	40.00	-9.45	QP	Vertical
2	40.42	47.11	13.58	24.60	0.60	36.69	40.00	-3.31	QP	Vertical
3	42.30	46.04	13.81	24.60	0.63	35.88	40.00	-4.12	QP	Vertical
4	45.22	45.66	13.24	24.60	0.65	34.95	40.00	-5.05	QP	Vertical
5	50.06	43.50	13.79	24.60	0.70	33.39	40.00	-6.61	QP	Vertical
6	122.83	43.13	11.83	24.58	1.23	31.61	43.50	-11.89	QP	Vertical

Middle Channel


Item	Freq.	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector	Polarization
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
1	98.142	45.29	9.01	23.66	0.90	31.54	43.50	-11.96	QP	Horizontal
2	135.032	43.28	11.40	23.64	1.10	32.14	43.50	-11.36	QP	Horizontal
3	144.842	43.10	12.00	23.64	1.16	32.62	43.50	-10.88	QP	Horizontal
4	209.313	42.30	9.10	23.63	1.43	29.20	43.50	-14.30	QP	Horizontal
5	726.805	34.06	20.85	23.89	3.04	34.06	46.00	-11.94	QP	Horizontal
6	948.761	33.56	23.61	23.94	3.56	36.79	46.00	-9.21	QP	Horizontal
1	135.032	42.13	11.40	23.64	1.10	30.99	43.50	-12.51	QP	Vertical
2	144.842	42.67	12.00	23.64	1.16	32.19	43.50	-11.31	QP	Vertical
3	208.580	43.47	9.12	23.62	1.43	30.40	43.50	-13.10	QP	Vertical
4	282.985	43.16	11.28	23.66	1.78	32.56	46.00	-13.44	QP	Vertical
5	454.310	41.50	16.12	23.72	2.33	36.23	46.00	-9.77	QP	Vertical
6	480.528	41.55	16.20	23.73	2.38	36.40	46.00	-9.60	QP	Polarization

Highest Channel


Item	Freq.	Read Level	Antenna Factor	Preamp Factor	Cable Loss	Result Level	Limit Line	Over Limit	Detector	Polarization
(Mark)	(MHz)	(dBμV)	(dB/m)	(dB)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		
1	49.707	39.25	12.73	23.69	0.41	28.70	40.00	-11.30	QP	Horizontal
2	61.995	39.05	11.85	23.68	0.54	27.76	40.00	-12.24	QP	Horizontal
3	98.487	44.25	9.05	23.66	0.90	30.54	43.50	-12.96	QP	Horizontal
4	150.011	43.82	12.30	23.64	1.17	33.65	43.50	-9.85	QP	Horizontal
5	184.490	43.23	11.78	23.62	1.35	32.74	43.50	-10.76	QP	Horizontal
6	332.519	44.03	13.13	23.68	1.92	35.40	46.00	-10.60	QP	Horizontal
1	123.698	40.67	11.16	23.65	1.05	29.23	43.50	-14.27	QP	Vertical
2	150.011	38.43	12.30	23.64	1.17	28.26	43.50	-15.24	QP	Vertical
3	233.349	47.26	9.54	23.64	1.51	34.67	46.00	-11.33	QP	Vertical
4	282.985	47.03	11.28	23.66	1.78	36.43	46.00	-9.57	QP	Vertical
5	332.519	45.45	13.13	23.68	1.92	36.82	46.00	-9.18	QP	Vertical
6	492.469	41.26	16.20	23.73	2.42	36.15	46.00	-9.85	QP	Vertical

Result Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Below is the plot of worst case on lowest channel:
Vertical:



Horizontal:



Above 1GHz:

Lowest Channel(2402MHz)

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4804	41.34	6.18	47.52	54	-6.48	peak	Horizontal
2	7206	39.37	10.63	50.00	54	-4.00	peak	Horizontal
3	9608	36.51	14.38	50.89	54	-3.11	peak	Horizontal
4	4804	40.20	6.18	46.38	54	-7.62	peak	Vertical
5	7206	39.23	10.63	49.86	54	-4.14	peak	Vertical
6	9608	33.96	14.38	48.34	54	-5.66	peak	Vertical

Middle Channel(2441MHz)

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4882	39.11	7.00	46.11	54	-7.89	peak	Horizontal
2	7323	39.70	11.13	50.83	54	-3.17	peak	Horizontal
3	9764	38.18	14.36	52.54	54	-1.46	peak	Horizontal
4	4882	38.46	7.00	45.46	54	-8.54	peak	Vertical
5	7323	38.92	11.13	50.05	54	-3.95	peak	Vertical
6	9764	33.72	14.36	48.08	54	-5.92	peak	Vertical

Highest Channel(2480MHz)

Mark	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	4960	41.14	7.49	48.63	54	-5.37	peak	Horizontal
2	7440	40.53	11.65	52.18	54	-1.82	peak	Horizontal
3	9920	38.35	14.40	52.75	54	-1.25	peak	Horizontal
4	4960	41.21	7.49	48.70	54	-5.30	peak	Vertical
5	7440	39.86	11.65	51.51	54	-2.49	peak	Vertical
6	9920	33.26	14.4	47.66	54	-6.34	peak	Vertical

Remark: 1) Emission = Receiver Reading + Factor

2) Factor = Antenna Factor + Cable Loss + Pre-amplifier Factor.

3) If the Peak value below the AV Limit, the AV test doesn't perform for this submission.


7.11.2 Radiated Band edge

Lowest Channel(2402MHz)


Modulation: GFSK

MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2390	43.49	-3.89	39.60	54	-14.40	Peak	Vertical
2	2402.2	90.85	-3.92	86.93	54	32.93	Peak	Vertical
1	2390	43.78	-3.89	39.89	54	-14.11	Peak	Horizontal
2	2402.2	90.46	-3.92	86.54	54	32.54	Peak	Horizontal

Vertical:



Horizontal:




Highest Channel(2480MHz)


Modulation: GFSK

MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2480.025	89.15	-4.00	85.15	54	31.15	Peak	Vertical
2	2483.5	51.00	-4.01	46.99	54	-7.01	Peak	Vertical
3	2500	43.24	-4.03	39.21	54	-14.79	Peak	Vertical
1	2479.725	90.35	-4.01	86.34	54	32.34	Peak	Horizontal
2	2483.5	50.57	-4.01	46.56	54	-7.44	Peak	Horizontal
3	2500	43.51	-4.03	39.48	54	-14.52	Peak	Horizontal

Vertical:



Horizontal:




Lowest Channel(2402MHz)


Modulation: $\pi/4$ DQPSK

MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2390	43.73	-3.89	39.84	54	-14.16	Peak	Vertical
2	2402.2	86.99	-3.92	83.07	54	29.07	Peak	Vertical
1	2390	43.78	-3.89	39.89	54	-14.11	Peak	Horizontal
2	2402.2	90.46	-3.92	86.54	54	32.54	Peak	Horizontal

Vertical:



Horizontal:




Highest Channel(2480MHz)


Modulation: $\pi/4$ DQPSK

MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2479.95	90.46	-4.00	86.46	54	32.46	Peak	Vertical
2	2483.5	52.02	-4.01	48.01	54	-5.99	Peak	Vertical
3	2500	43.65	-4.03	39.62	54	-14.38	Peak	Vertical
1	2479.8	87.46	-4.00	83.46	54	29.46	Peak	Horizontal
2	2483.5	51.82	-4.01	47.81	54	-6.19	Peak	Horizontal
3	2500	43.65	-4.03	39.62	54	-14.38	Peak	Horizontal

Vertical:



Horizontal:




Lowest Channel(2402MHz)


Modulation: 8DPSK

MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2390	43.47	-3.89	39.58	54	-14.42	Peak	Vertical
2	2401.9	87.82	-3.91	83.91	54	29.91	Peak	Vertical
1	2390	44.30	-3.89	40.41	54	-13.59	Peak	Horizontal
2	2402.1	86.54	-3.92	82.62	54	28.62	Peak	Horizontal

Vertical:



Horizontal:




Highest Channel(2480MHz)


Modulation: 8DPSK

MK.	Frequency (MHz)	Reading (dBuV/m)	Corrected factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	2480.025	89.40	-4.00	85.40	54	31.40	Peak	Vertical
2	2483.5	52.38	-4.01	48.37	54	-5.63	Peak	Vertical
3	2500	42.89	-4.03	38.86	54	-15.14	Peak	Vertical
1	2479.725	88.94	-4.01	84.93	54	30.93	Peak	Horizontal
2	2483.5	51.42	-4.01	47.41	54	-6.59	Peak	Horizontal
3	2500	42.98	-4.03	38.95	54	-15.05	Peak	Horizontal

Vertical:



Horizontal:



Remark: 1). Test Level = Receiver Reading + Antenna Factor + Cable Loss- Preamplifier Factor

2). If the Peak value below the AV Limit, the AV test doesn't perform for this submission.

All frequencies within the "Restricted bands" have been evaluated to compliance. Except as shown in paragraph of this section, only spurious emissions are permitted in any of the frequency bands listed below:

a. FCC Part 15, Subpart C Section 15.205 Restricted bands of operation.

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.5 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	
13.36 - 13.41			



8 Test Setup Photographs

Refer to the < RVM1000(043438)_Test Setup photos-FCC>.

9 EUT Constructional Details

Refer to the < RVM1000(043438)_External Photos > & < RVM1000(043438)_Internal Photos >.

--End of the Report--